WINDOW TYPE	W-A	W-C	W-D	W-E	W-J	W-K	W-L	W-M	W-U	W-DA	W-KA	W-RA
LOCATION	LQ - KITCHEN/ STAIRCASE	ABLUTIONS / BATHROOM	OFFICE	OFFICE / LQ - PATIO	CELLS	STAFF ABLUTION	CELL GUARD	SERVICE LEVEL	STATEMENTS PASSAGE	BATHROOMS	REGISTRY	REGISTRY
ELEVATION & PLAN												
DIMENSIONS	600x1200mm	600x1200mm	1200x1500mm	1500x1500mm	850x950mm	1500x300mm	1200x1200mm View Panel	1800x900mm	2400x300mm	1200x1500mm	1200x300mm	400x1500mm
DESCRIPTION	Aluminum sections.	Aluminum sections.	Aluminum sections.	Aluminum sections.	Fixed GMS Window as per SAP 5 Star Specification.	Aluminum sections.	Fixed GMS Window as per SAP 5 Star Specification.	Aluminum sections.	Aluminum sections.	Aluminum sections.	Aluminum sections.	Aluminum sections.
FRAME	Steel frame with powder coating - Interpon Class 2 D2525T Colour: Matte Charcoal QL258P, to Architect's approval	Steel frame with powder coating - Interpon Class 2 D2525T Colour: Matte Charcoal QL258P, to Architect's approval	Steel frame with powder coating - Interpon Class 2 D2525T Colour: Matte Charcoal QL258P, to Architect's approval	Steel frame with powder coating - Interpon Class 2 D2525T Colour: Matte Charcoal QL258P, to Architect's approval	Steel frame with powder coating - Interpon Class 2 D2525T Colour: Matte Charcoal QL258P, to Architect's approval	Steel frame with powder coating - Interpon Class 2 D2525T Colour: Matte Charcoal QL258P, to Architect's approval	Steel frame with powder coating - Interpon Class 2 D2525T Colour: Matte Charcoal QL258P, to Architect's approval	aluminium frame with powder coating - Interpon Class 2 D2525T Colour: Matte Charcoal QL258P, to Architect's approval	Steel frame with powder coating - Interpon Class 2 D2525T Colour: Matte Charcoal QL258P, to Architect's approval	Steel frame with powder coating - Interpon Class 2 D2525T Colour: Matte Charcoal QL258P, to Architect's approval	Steel frame with powder coating - Interpon Class 2 D2525T Colour: Matte Charcoal QL258P, to Architect's approval	Steel frame with powder coating - Interpon Class 2 D2525T Colour: Matte Charcoal QL258P, to Architect's approval
MISCELLANEOUS	Stainless steel easy clean friction stay hinges to suit opening sections and window size. Black nylon handles to suit window, to Architect's approval	Stainless steel easy clean friction stay hinges to suit opening sections and window size. Black nylon handles to suit window, to Architect's approval	Stainless steel easy clean friction stay hinges to suit opening sections and window size Black nylon handles to suit window, to Architect's approval	Stainless steel easy clean friction stay hinges to suit opening sections and window size Black nylon handles to suit window, to Architect's approval	Purpose made handles from standard PF7 type steel profiles 75mm long welded to opening section.	Stainless steel easy clean friction stay hinges to suit opening sections and window size Black nylon handles to suit window, to Architect's approval	Purpose made handles from standard PF7 type steel profiles 75mm long welded to opening section.	Vermin proof mesh to be fixed to internal face of panel. Panel to be positive fixed with anti-theft screws at corners and evenly spaced as required, into concrete or brickwork to suit.	Stainless steel easy clean friction stay hinges to suit opening sections and window size. Black nylon handles to suit window, to Architect's approval	Stainless steel easy clean friction stay hinges to suit opening sections and window size Black nylon handles to suit window, to Architect's approval	Stainless steel easy clean friction stay hinges to suit opening sections and window size Black nylon handles to suit window, to Architect's approval	Stainless steel easy clean friction stay hinges to suit opening sections and window size. Black nylon handles to suit window, to Architect's approval
GLAZING	Single 6.38mm laminated safety glazing Colour: Neutral	Single 6.38mm laminated safety glazing Colour: Frosted	Single 6.38mm laminated safety glazing Colour: Neutral	Single 6.38mm laminated safety glazing Colour: Neutral	Single 6.5mm laminated safety glazing Colour: Neutral	Single 6.5mm laminated safety glazing Colour: Frosted	Single 6.5mm laminated safety glazing Colour: Neutral	n/a	Single 6.38mm laminated safety glazing Colour: Neutral	Single 6.38mm laminated safety glazing Colour: Frosted.	Single 6.5mm laminated safety glazing Colour: Neutral	Single 6.38mm laminated safety glazing Colour: Frosted Glass

WINDOW TYPE	W-N	W-P	W-Q	W-R	W-S	W-T	W-V	W-W	W-Y	W-YA	W-X	W-SA
LOCATION	SERVICE LEVEL	VFA - PASSAGE	CELLS	VISIBLE POLICING - OFFICE	BOARDROOM/ CSC COMMANDER EXT	VISIBLE POLICING	SECRETARY LEV 5 OFFICE	FINANCE MEMBER LEV 7	BOARDROOM	BOARDROOM STORE	KITCHEN (CELL AREA)/ CELL TOILETS	CSC COMMANDER'S OFFICE
ELEVATION & PLAN												
DIMENSIONS	1500x900mm	3440x900mm	850x950mm	600x1500mm	1500x1500mm	1500x1800mm	1500x2400mm	600x1500mm	1500x1500mm	600x1500mm	850x950mm	1500x1500mm
DESCRIPTION	Aluminum fixed louvre panel with Y profile fins	Aluminum sections.	Fixed GMS Window as per SAP 5 Star Specification.	Aluminum sections.	Aluminum sections.	Aluminum sections.	Aluminum sections.	Aluminum sections.	Aluminum sections.	Aluminum sections.	Fixed GMS Window as per SAP 5 Star Specification.	Fixed Aluminum sections.
FRAME	Aluminum frame with powder coating - Interpon Class 2 D2525T Colour: Matte Charcoal QL258P, to Architect's approval	Aluminum frame with powder coating - Interpon Class 2 D2525T Colour: Matte Charcoal QL258P, to Architect's approval	Steel frame with powder coating - Interpon Class 2 D2525T Colour: Matte Charcoal QL258P, to Architect's approval	Steel frame with powder coating - Interpon Class 2 D2525T Colour: Matte Charcoal QL258P, to Architect's approval	Steel frame with powder coating - Interpon Class 2 D2525T Colour: Matte Charcoal QL258P, to Architect's approval	Steel frame with powder coating - Interpon Class 2 D2525T Colour: Matte Charcoal QL258P, to Architect's approval	Steel frame with powder coating - Interpon Class 2 D2525T Colour: Matte Charcoal QL258P, to Architect's approval	Steel frame with powder coating - Interpon Class 2 D2525T Colour: Matte Charcoal QL258P, to Architect's approval	Steel frame with powder coating - Interpon Class 2 D2525T Colour: Matte Charcoal QL258P, to Architect's approval	Steel frame with powder coating - Interpon Class 2 D2525T Colour: Matte Charcoal QL258P, to Architect's approval	Steel frame with powder coating - Interpon Class 2 D2525T Colour: Matte Charcoal QL258P, to Architect's approval	Steel frame with powder coating - Interpon Class 2 D2525T Colour: Matte Charcoal QL258P, to Architect's approval
MISCELLANEOUS	Vermin proof mesh to be fixed to internal face of panel. Panel to be positive fixed with anti-theft screws at corners and evenly spaced as required, into concrete or brickwork to suit. Window to have steel bars of 10mm diameter at 100mm centre to centre frame border 50mm x 50mm x 5mm hollow frame. Colour to match window.	Stainless steel easy clean friction stay hinges to suit opening sections and window size Black nylon handles to suit window, to Architect's approval	Purpose made handles from standard PF7 type steel profiles 75mm long welded to opening section.	Stainless steel easy clean friction stay hinges to suit opening sections and window size Black nylon handles to suit window, to Architect's approval	Stainless steel easy clean friction stay hinges to suit opening sections and window size. Black nylon handles to suit window, to Architect's approval	Stainless steel easy clean friction stay hinges to suit opening sections and window size Black nylon handles to suit window, to Architect's approval	Stainless steel easy clean friction stay hinges to suit opening sections and window size. Black nylon handles to suit window, to Architect's approval	Stainless steel easy clean friction stay hinges to suit opening sections and window size. Black nylon handles to suit window, to Architect's approval Stainless steel pay under hatch to specialist detail.	Stainless steel easy clean friction stay hinges to suit opening sections and window size. Black nylon handles to suit window, to Architect's approval	Stainless steel easy clean friction stay hinges to suit opening sections and window size. Black nylon handles to suit window, to Architect's approval	Purpose made handles from standard PF7 type steel profiles 75mm long welded to opening section.	No opening sections.
GLAZING	n/a	n/a	Single 6.5mm laminated safety glazing Colour: Neutral	Single 6.38mm laminated safety glazing Colour: Neutral	Single 6.38mm laminated safety glazing Colour: Neutral	Single 6.38mm laminated safety glazing Colour: Neutral	Single 6.38mm laminated safety glazing Colour: Neutral	Single 6.38mm laminated safety glazing Colour: Neutral	Single 6.38mm laminated safety glazing Colour: **Specialised glass**	Single 6.38mm laminated safety glazing Colour: **Specialised glass**		Single 6.5mm laminated safety glazing Colour: Neutral

WINDOW TYPE	W-AB	W-DB
LOCATION	STAIRCASE	OFFICE KITCHENETTE
ELEVATION & PLAN		
DIMENSIONS	600x1500mm	1200x1200mm
DESCRIPTION	Aluminum sections.	Aluminum sections.
FRAME	Steel frame with powder coating - Interpon Class 2 D2525T Colour: Matte Charcoal QL258P, to Architect's approval	Steel frame with powder coating - Interpon Class 2 D2525T Colour: Matte Charcoal QL258P, to Architect's approval
MISCELLANEOUS	Stainless steel easy clean friction stay hinges to suit opening sections and window size. Black nylon handles to suit window, to Architect's approval	Stainless steel easy clean friction stay hinges to suit opening sections and window size Black nylon handles to suit window, to Architect's approval
GLAZING	Single 6.38mm laminated safety glazing Colour: Neutral	Single 6.38mm laminated safety glazing Colour: Neutral

Note:
All Windows to have a solid brick sill on each end.

Note:
6x6mm solid aluminium burglar guards horizontally at 100mm centres to all glazed window sections (opening & fixed)

SPECIALIZED WINDOWS

WINDOW TYPE	BRW-A	BRW-B	BRW-C	BRW-D (STATEMENTS ROOM)
ELEVATION & PLAN				
ELEVATION				
DIMENSIONS	4250x1200mm	1200x1650mm	1500x1630mm	1500x1500mm
DESCRIPTION	Certified Level G3 Bullet Resistant window system (frame and glazing) or equal approved. Finish to Architects spec.	Certified Level G3 Bullet Resistant window system (frame and glazing) or equal approved. Finish to Architects spec.	Certified Level G3 Bullet Resistant window system (frame and glazing) or equal approved. Finish to Architects spec.	Aluminum sections.
FRAME	High-tech steel frame with powder coating - Interpon Class 2 D2525T Colour: Matte Charcoal QL258P, to Architect's approval All vertical posts to be speech posts.	High-tech steel frame with powder coating - Interpon Class 2 D2525T Colour: Matte Charcoal QL258P, to Architect's approval All vertical posts to be speech posts.	High-tech steel frame with powder coating - Interpon Class 2 D2525T Colour: Matte Charcoal QL258P, to Architect's approval All vertical posts to be speech posts.	Galvanised mild steel with powder coating - Interpon Class 2 D2525T Colour: Matte Charcoal QL258P, to Architect's approval
MISCELLANEOUS	200mm deep purpose made Certified Level G3 Bullet Resistant pass-under drawer	150mm deep purpose made Certified Level G3 Bullet Resistant pass-under paper slot.	350x1500mm deep purpose made Certified Level G3 Bullet Resistant pass-under Interlocking Safe.	Galvanised mild steel easy clean friction stay hinges to suit opening sections and window size. Black nylon handles to suit window, to Architect's approval
GLAZING	53mm Certified Level G3 Bullet Resistant Colour: Neutral	53mm Certified Level G3 Bullet Resistant Colour: Neutral	53mm Certified Level G3 Bullet Resistant Colour: Neutral	Bullet Resistant Single 6.38mm laminated safety glazing Colour: Frosted

GENERAL DRAWING NOTES

- THE DESIGN ON THIS DRAWING IS COPYRIGHT AND REMAINS THE PROPERTY OF THE ARCHITECTS.
- ALL WORK TO BE CARRIED OUT STRICTLY IN ACCORDANCE WITH MUNICIPAL REGULATIONS.
- DRAWINGS NOT TO BE SCALED, ONLY ANNOTATED DIMENSIONS TO BE USED.
- ALL RELEVANT DATUM, LEVELS, DIMENSIONS TO BE CHECKED ON SITE BEFORE COMMENCEMENT OF WORK.
- ALL DRAWINGS ARE TO BE CHECKED BY THE MAIN CONTRACTOR AND ANY DISCREPANCIES ON THE DRAWINGS OR BETWEEN THE DRAWINGS ARE TO BE REFERRED TO THE ARCHITECT.
- CONTRACTOR TO CHECK ALL QUANTITIES PRIOR TO ORDERING AND MANUFACTURE.
- CONTRACTOR TO PROVIDE SHOP DRAWINGS FOR APPROVAL BY ARCHITECT PRIOR TO MANUFACTURE.

Revision:

No.	Description	Date

Client

Signature: Date:

SAKHISIZWE ARCHITECTS
33 ADELAIDE TAMBO DR , DURBAN NORTH
TEL: 031 563 3424 FAX: 031 563 3518
www.sakhisizwearchitects.com

Professional Architects signature
Mr K.P Mawesana (Pr. Arch) sacap (7902) saia (7893)

Project Title:
Proposed New Msinsini Police Station for the South African Police Service on Portion 4 of the farm Clifton Park No.9219

First Issue Date: **09/05/24**	Page Size: A0
Drawn: **KLN, JN, CM**	Scale: **1 : 50**
Checked: **BS**	

Drawing Description:
Window Schedule

Job no.:	Drawing no.:	Rev. no.:
s571	**S4-500C**	

Signature:

ISSUED FOR APPROVAL	
ISSUED FOR INFORMATION	
ISSUED FOR SUBMISSION	
ISSUED FOR TENDER	
ISSUED FOR CONSTRUCTION	