

SCOPE OF WORK

MATERIAL NO.	DESCRIPTION	QTY
0665730	SHIELD, TUBE: DIMENSIONS: DIA 54.3MM X LG 2.45M; STYLE: STRAIGHT; MATERIAL: SS GR310; DRAWING NO: 71.RH1.SD48.08.11 REV 0; PROTECTION SHIELD: ID 48.3MM X WALL THICKNESS 3MM; RH OFFSET; VENDOR TO CONFIRM LATEST REVISION DRAWING BEFRE COMMENCING WITH MANUFACTURING; PROTECTING SHIELD TO COVER 180DEG AND THE BANGLE 180DEG RADIUS TO FIT TIGHT AROUND THE APPLICABLE BOILER TUBE; BANGLES AND THE PROTECTION SHIELDS TO BE INCLUDED IN THE DELIVERY; AND BE CHARGED; BUT SUPPLIED AS SEPARATE ITEMS; QCP FOR PRESSING TO BE APPROVED BY ESKOM BEFORE COMMENCING WITH ANY MANIPULATION; PROCURING OF HP PIPEWORK SHOULD BE IN LINE WITH ESKOM STANDARD: 204-87733094; MATERIAL: SS 310; DIMENSIONS: OD 52 X WT 3MM; EACH BANGLE AND SHIELD SHOULD BE HARD STAMPED; HEAT NUMBER WITH LOW STRESS STAMPS; MATERIAL CERTIFICATE 3.1 I.A.W REQUIRED ON EVERY DELIVERY; STANDARD EN1024 3.1; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE)	650
0665726	SHIELD, TUBE: DIMENSIONS: DIA 50.5MM X LG 2.45M; STYLE: BEND; MATERIAL: SS GR310; DRAWING NO: TUT-PP-GEN-122 REV 0; 0.61-02133 REV 2 REV 0; PROTECTION LHS SHIELD: ID 44.5MM X WALL THICKNESS 3MM; VENDOR TO CONFIRM LATEST REVISION DRAWING BEFRE COMMENCING WITH MANUFACTURING; PROTECTING SHIELD TO COVER 180DEG AND THE BANGLE 180DEG RADIUS TO FIT TIGHT AROUND THE APPLICABLE BOILER TUBE; BANGLES AND THE PROTECTION SHIELDS TO BE INCLUDED IN THE DELIVERY; AND BE CHARGED; BUT SUPPLIED AS SEPARATE ITEMS; QCP FOR PRESSING TO BE APPROVED BY ESKOM BEFORE COMMENCING WITH ANY MANIPULATION; PROCURING OF HP PIPEWORK SHOULD BE IN LINE WITH ESKOM STANDARD: 204-87733094; MATERIAL: SS 310; DIMENSIONS: OD 50.5 X WT 3MM; EACH BANGLE AND SHIELD SHOULD BE HARD STAMPED; HEAT NUMBER WITH LOW STRESS STAMPS; MATERIAL CERTIFICATE 3.1 I.A.W REQUIRED ON EVERY DELIVERY; STANDARD EN1024 3.1; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE) .	650

0665728	SHIELD, TUBE: DIMENSIONS: DIA 50.5MM X LG 2.45M; STYLE: BIFURCATION; MATERIAL: SS GR310; DRAWING NO: TUT-PP-GEN-118 REV 0; 60.ST.SDBIF3PB.10.11 REV 0; TUT-PP-GEN-119 REV 0; 60.ST.SDBIF3PB.08.11 REV 0; PROTECTION SHIELD: ID 44.5MM X WALL THICKNESS 3MM; RH OFFSET; VENDOR TO CONFIRM LATEST REVISION DRAWING BEFORE COMMENCING WITH MANUFACTURING; PROTECTING SHIELD TO COVER 180DEG AND THE BANGLE 180DEG RADIUS TO FIT TIGHT AROUND THE APPLICABLE BOILER TUBE; BANGLES AND THE PROTECTION SHIELDS TO BE INCLUDED IN THE DELIVERY; AND BE CHARGED; BUT SUPPLIED AS SEPARATE ITEMS; QCP FOR PRESSING TO BE APPROVED BY ESKOM BEFORE COMMENCING WITH ANY MANIPULATION; PROCURING OF HP PIPEWORK SHOULD BE IN LINE WITH ESKOM STANDARD: 204-87733094; MATERIAL: SS 310; DIMENSIONS: OD 50.5 X WT 3MM; EACH BANGLE AND SHIELD SHOULD BE HARD STAMPED; HEAT NUMBER WITH LOW STRESS STAMPS; MATERIAL CERTIFICATE 3.1 I.A.W REQUIRED ON EVERY DELIVERY; STANDARD EN1024 3.1; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT	650
0665729	SHIELD, TUBE: DIMENSIONS: DIA 57MM X LG 2.45M; STYLE: STRAIGHT; MATERIAL: SS GR310; DRAWING NO: 67.RH2.SD.08.11 REV 0; PROTECTION SHIELD: ID 51MM X WALL THICKNESS 3MM; RH OFFSET; VENDOR TO CONFIRM LATEST REVISION DRAWING BEFRE COMMENCING WITH MANUFACTURING; PROTECTING SHIELD TO COVER 180DEG AND THE BANGLE 180DEG RADIUS TO FIT TIGHT AROUND THE APPLICABLE BOILER TUBE; BANGLES AND THE PROTECTION SHIELDS TO BE INCLUDED IN THE DELIVERY; AND BE CHARGED; BUT SUPPLIED AS SEPARATE ITEMS; QCP FOR PRESSING TO BE APPROVED BY ESKOM BEFORE COMMENCING WITH ANY MANIPULATION; PROCURING OF HP PIPEWORK SHOULD BE IN LINE WITH ESKOM STANDARD: 204-87733094; MATERIAL: SS 310; DIMENSIONS: OD 57 X WT 3MM; EACH BANGLE AND SHIELD SHOULD BE HARD STAMPED; HEAT NUMBER WITH LOW STRESS STAMPS; MATERIAL CERTIFICATE 3.1 I.A.W REQUIRED ON EVERY DELIVERY; STANDARD EN1024 3.1; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE) .	650