


A  
B  
C  
D  
E  
F



2 HOLES 12mm DIA

BOLT SCHEDULE			
MK	TYPE	No. OFF	WASHER PER BOLT
1	M16x35	1	1 FLAT
2	M10x25 SET SCREWS	2	1 FLAT 1 SPRING LOCK

- NOTES :
- 1. ALL WELDING AND WELDING SYMBOLS SHALL CONFORM TO SABS044 PART 1 TO 5.
  - 2. ALL STRUCTURAL USE OF STEEL TO CONFORM TO SABS 0162.  
GRADE OF STEEL TO BE TO SABS 1431 GRADE 300WA.
  - 3. ALL WELDS TO BE SEALED WELDED.
  - 4. STEELWORK TO BE HOT DIP GALVANIZED TO SABS 1461.
  - 5. ALL STEELWORK TO BE FABRICATED, ERECTED & LEVELED TO A TOLERANCE OF + - 1.5mm.
  - 6. ALL BOLTS & NUTS TO CONFORM TO SABS 135, STRENGTH GRADE 4,8.
  - 7. ALL MARKS TO BE STAMPED ONTO STEELWORK AND SHALL BE CLEARLY LEGIBLE AFTER GALVANIZING.
  - 8. ALL HOLES TO BE 18mm DIA UNLESS OTHERWISE STATED.


1	BOLTS REQUIRED CHANGED AND TITLE CHANGED	WWK	MC	NMW	16/05/2003	
0	FIRST ISSUE				/ /	
REV	REVISION DESCRIPTION	BY	CHKD	AUTH	DATE	PROJECT NO.



AUTH: N. WEBBER  
DATE: 26/02/2002  
CHKD: C. Lotteri  
DATE: 25/02/2002  
DRAWN: T. Guzana  
DATE: 25/02/2002

# PHASING DISC LABELS

## MOUNTING BRACKET DETAILS

SCALE 1:20

THIS DRAWING IS THE PROPERTY OF ESKOM

D-EC-1938

SET	SHEET	REVISION
	1	1

SCALE 1:20  
THIS DRAWING IS THE  
PROPERTY OF ESKOM