

Part of Overall Jacket	Detail	Notes
General Garments Specification	<ul style="list-style-type: none"> <li>All garments must comply with: SANS 434; SANS 10101; SANS 1822; SANS 50471; SANS 1387, SANS 1362</li> <li>Eskom Personal Protective Equipment Specification 24044175132.</li> <li>All garments must bear the SABS mark of approval accompanied by a compliance test certificate from an approve laboratory.</li> </ul>	
Fabric/garment	<ul style="list-style-type: none"> <li>Yarn Liner Densities - Material D59 (Warp 42 and Weft 65)</li> <li>Fabric Class C Capable of withstanding wash treatments at temperatures of up to 60 °C</li> <li>Flammability Cart 1 The fabric does not ignite within a given time period (&gt;20 sec).</li> <li>All garments manufactured as per SANS 434 must bear the SABS mark of approval. A compliance test certificate by an approved laboratory shall be submitted during the delivery of each consignment.</li> <li>The type of works suite shall be as per SANS 434 Figure 4.</li> </ul>	
Colour	<ul style="list-style-type: none"> <li>The colour shall be navy blue. Pantone 19_3920</li> <li>Certificate confirming Pantone 19_3920 colour</li> </ul>	
Sizes of Jackets	Size shall comply with SANS 434, section 4.4.1 table 1 to 7	

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom RoteK Industries SOC Ltd.

Part of Overall Jacket	Detail	Notes
Pockets	<ul style="list-style-type: none"> <li>The jacket shall have three front pockets.</li> <li>The top pocket shall be double needle stitched to the top/chest left side of the jacket.</li> <li>The two lower front pockets shall be double needle stitched on the jacket. The lower pockets shall have neatly stitched rounded corners.</li> <li>All pockets' requirements including finished width and depth shall comply with SANS 434 section 4.7.7</li> </ul>	
Collar	The jacket shall have a step type collar that conforms to SANS 434	
Zip/Slide Fasteners	<ul style="list-style-type: none"> <li>The Zip Fastener shall Comply to SANS 1822 section 4.3.1, YKK open end non-conductive zip/slide fastener hidden by a flap</li> <li>The colour of the stringers of the slide fastener shall be of an acceptable match to that of the fabric with which the zip/slide faster is used.</li> <li>The stringers of the slide fastener shall be double stitched as per SANS 10101</li> <li>The performance class of the zip shall be medium (Class C for Denims - Chain width 5.6- 6.0 mm)</li> </ul>	
Safety reflectors	<ul style="list-style-type: none"> <li>A 48 MM silver fire retardant reflective tape shall be double stitched around the two arms by the elbow height.</li> <li>A 30 CM length of cross silver fire retardant reflective tape shall be double stitched at the upper back of the jacket. The stitching shall comply with SANS 10101.</li> <li>The reflective tape shall comply with the performance requirements of SANS 50471 as well as the minimum areas for the disposition of the</li> </ul>	

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom RoteK Industries SOC Ltd.

Part of Overall Jacket	Detail	Notes
	materials in protective clothing.	
Stitching	<ul style="list-style-type: none"> <li>Triple stitching shall be applied to side seam, sleeve seam and shoulder seam in compliance with SANS 10101.</li> <li>The lower hem of the jacket shall be single stitched.</li> </ul>	
Thread	<ul style="list-style-type: none"> <li>The thread used shall comply with SANS 1362 and must be appropriate to maintain the strength of the garment.</li> <li>The garments shall be neatly sewn together with no excess threads.</li> </ul>	
Branding	<ul style="list-style-type: none"> <li>The Eskom RoteK Industries Logo shall appear on the left-hand top pocket in white and shall be in accordance with Eskom RoteK Industries Corporate Identity. The stitching shall comply with SANS 10101.</li> <li>The Zero Harm identification shall appear on the right-side sleeve of the top.</li> <li>The "Zero" shall be white while the harm shall be Pantone 1385C (orange).</li> </ul>	The branding be in accordance with Eskom RoteK Industries Corporate Identity.

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom RoteK Industries SOC Ltd.

Part of Overall Trousers/Pants	Detail	Notes
General Garments Specification	<ul style="list-style-type: none"> <li>All garments must comply with SANS 434; SANS 10101; SANS 1822; SANS 50471; SANS 1387; SANS 1362</li> <li>Eskom Personal protective Equipment Specification 24044175132.</li> <li>All garments must bear the SABS mark of approval accompanied by a compliance test certificate from an approve laboratory.</li> </ul>	
Fabric/Garments	<ul style="list-style-type: none"> <li>Yarn Liner Densities - Material D59 (Warp 42 and Weft 65) Fabric Class C Capable of withstanding wash treatments at temperatures of up to 60 °C</li> <li>Flammability Cart 1 The fabric does not ignite within a given time period (&gt;20 sec).</li> <li>All garments manufactured as per SANS 434 must bear the SABS mark of approval. A compliance test certificate by an approved laboratory shall be submitted during the delivery of each consignment.</li> <li>The type of works suite shall be as per SANS 434 Figure 4. The pants/trouser must be elasticised centrally over each side seam</li> </ul>	
Colour	<ul style="list-style-type: none"> <li>The colour shall be navy blue. Pantone 19_3920 Certificate confirming Pantone 19_3920 colour</li> </ul>	
Sizes	<ul style="list-style-type: none"> <li>Size shall comply with SANS 434, section 4.4.1</li> </ul>	

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom RoteK Industries SOC Ltd.

Part of Overall Trousers/Pants	Detail	Notes
	table 1 to 7	
Pockets	<ul style="list-style-type: none"> <li>The trouser/pants shall have a total of five pockets.</li> <li>Two pockets side pockets.</li> <li>Two pockets double needle stitched at the back of the trouser/pants. The pockets shall have neatly stitched rounded corners</li> <li>One double stitched ruler pocket</li> </ul> <p>All Pockets shall comply with SANS 434 section 4.7.7</p>	
Slide Fasteners	<ul style="list-style-type: none"> <li>The Zip Fastener shall Comply to SANS 1822 section 4.3.1, YKK one-way closed end, non-conductive zip/slide fastener hidden by a flap</li> <li>The interlocking elements shall be of synthetic/non-conductive material nature complying with 4.3.1 of SANS 1822</li> <li>The colour of the stringers of the zip/slide fastener shall be of an acceptable match to that of the fabric with which the Zip/slide fastener is used.</li> <li>The stringers of the zip/slide fastener shall be double stitched as per SANS 10101</li> <li>The Zip/slide shall be concealed with a flap. The performance class of the zip shall be medium (Class C for Denims - Chain width 5.6-6.0 mm)</li> </ul>	
Safety reflectors	<ul style="list-style-type: none"> <li>A 48 MM silver fire retardant reflective tape shall be double stitched around the two legs immediately below the knee.</li> </ul> <p>The fire-retardant reflective tape shall comply with the performance requirements of SANS 50471 as well as the minimum areas for the</p>	

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.


No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

Part of Overall Trousers/Pants	Detail	Notes
	disposition of the materials in protective clothing.	
Thread	<ul style="list-style-type: none"> <li>The thread used shall comply with SANS 1362 and must be appropriate to maintain the strength of the garment.</li> <li>The garments shall be neatly sewn together with no excess threads.</li> </ul>	
Stitching	<ul style="list-style-type: none"> <li>The stitching of side seams, inner leg seam and back rise shall be tripled stitched.</li> <li>The front rise shall be double top stitched</li> </ul>	
Branding	<ul style="list-style-type: none"> <li>The Eskom Rotek Industries Logo shall appear on the right back pocket in a white colour</li> <li>The Zero Harm will appear on the left back pocket. The "Zero" shall be white and the Harm shall be pantone 1385 C (orange). The stitching shall comply with SANS 10101.</li> </ul>	The branding shall be in accordance with Eskom Rotek Industries Corporate Identity.

**Note:**

- A sample of the manufactured garment must be presented before the award of the order. This shall form part of the returnable.
- The addendum must be read in line with the Eskom Personal Protective Equipment 240-44175132 Revision 1.

**Authorised by**



**Bhutana Mhlana**

**Risk and Resilience: SHEQ**

Date: 01/12/2022

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.