

## **DECLARATION CERTIFICATE FOR LOCAL PRODUCTION AND CONTENT FOR DESIGNATED SECTORS**

This Standard Bidding Document (SBD) must form part of all bids invited. It contains general information and serves as a declaration form for local content (local production and local content are used interchangeably).

Before completing this declaration, bidders must study the General Conditions, Definitions, Directives applicable in respect of Local Content as prescribed in the Preferential Procurement Regulations, 2017, the South African Bureau of Standards (SABS) approved technical specification number SATS 1286:2011 (Edition 1) and the Guidance on the Calculation of Local Content together with the Local Content Declaration Templates [Annex C (Local Content Declaration: Summary Schedule), D (Imported Content Declaration: Supporting Schedule to Annex C) and E (Local Content Declaration: Supporting Schedule to Annex C)].

### **1. General Conditions**

- 1.1. Preferential Procurement Regulations, 2017 (Regulation 8) make provision for the promotion of local production and content.
- 1.2. Regulation 8.(2) prescribes that in the case of designated sectors, organs of state must advertise such tenders with the specific bidding condition that only locally produced or manufactured goods, with a stipulated minimum threshold for local production and content will be considered.
- 1.3. Where necessary, for tenders referred to in paragraph 1.2 above, a twostage bidding process may be followed, where the first stage involves a minimum threshold for local production and content and the second stage price and B-BBEE.
- 1.4. A person awarded a contract in relation to a designated sector, may not sub-contract in such a manner that the local production and content of the overall value of the contract is reduced to below the stipulated minimum threshold.
- 1.5. The local content (LC) expressed as a percentage of the bid price must be calculated in accordance with the SABS approved technical specification number SATS 1286: 2011 as follows:

$$LC = [1 - x / y] * 100$$

Where

x is the imported content in Rand

y is the bid price in Rand excluding value added tax (VAT)

Prices referred to in the determination of x must be converted to Rand (ZAR) by using the exchange rate published by South African Reserve Bank (SARB) at 12:00 on the date of advertisement of the bid as indicated in paragraph 4.1 below.

**The SABS approved technical specification number SATS 1286:2011 is accessible on [http://www.thedti.gov.za/industrial development/ip.jsp](http://www.thedti.gov.za/industrial%20development/ip.jsp) at no cost.**

1.6. A bid may be disqualified if this Declaration Certificate and the Annex C (Local Content Declaration: Summary Schedule) are not submitted as part of the bid documentation;

**2. The stipulated minimum threshold(s) for local production and content (refer to Annex A of SATS 1286:2011) for this bid is/are as follows:**

IKWEZI STATION					
BILL	PAGE NO.	ITEM NO.	DESCRIPTION	LOCAL CONTENT THRESHOLD	
Building	26	1	Hoarding 3000mm high extreme formed of 0,6mm thick Z275 spelter galvanised steel	100%	Steel
	28	28	Half brick walls	100%	Cement
	29	34	One brick walls	100%	Cement
	30	36	Make good: On edges of concrete stairs	100%	Cement
	31	38	Breaking out for and forming openings through brick walls for new windows, doors and frames including necessary precast concrete lintels and making good plaster on both sides : Opening for door with steel frame 813 x 2032mm high	100%	Cement
		39	Breaking out for and forming openings through brick walls for new windows, doors and frames including necessary precast concrete lintels and making good plaster on both sides : Opening for window size 600mm x 600mm high	100%	Cement
	37	45	Half brick walls	100%	Cement
		46	One brick walls	100%	Cement
		47	75mm Wide reinforcement	100%	Steel
		48	150mm Wide reinforcement	100%	Steel
		49	110 x 75mm Lintels in lengths not exceeding	100%	Steel
	48	65	100% Stainproof (Polypropylene) structured needlepunch SABS Class 3 fire rating heavy commercial carpet tiles, size 500 x 500 x 8,5mm thick: On floors	100%	Textile
	49	67	WC indicator bolt	100%	Steel
		68	Disabled indicator bolt, fixed to surface with matching stainless steel screws.	100%	Steel
		69	88 x 100mm High overall bush bearing butt hinge	100%	Steel
	50	70	Euro profile Mortice sash lock with reversible latch and deadbolt	100%	Steel
		71	813 x 200mm Kick plate	100%	Steel
		72	Round D pull handle on a long backplate	100%	Steel
		73	Approved delayed action door closer	100%	Steel
		74	Stainless steel: 152 x 152 x 2mm Thick engraved with female pictogram	100%	Steel
		75	Stainless steel: 152 x 152 x 2mm Thick engraved with male pictogram	100%	Steel
		76	152 x 152 x 2mm Thick engraved with paraplegic pictogram	100%	Steel

		77	152 x 152 x 2mm Thick engraved with Unisex pictogram	100%	Steel
		78	152 x 152 x 2mm Thick engraved with kitchen and breakroom pictogram	100%	Steel
		79	152 x 152 x 2mm Thick engraved with cleaning store pictogram	100%	Steel
	51	80	Stainless steel door stop	100%	Steel
		81	Hat and coat hook	100%	Steel
		82	Satin stainless steel recessed toilet roll holders for single or two rolls	100%	Steel
		83	Satin stainless steel waste disposal bins with capacity of plus minus 20 litres	100%	Steel
		84	Satin stainless steel towel rings	100%	Steel
		85	Satin stainless steel soap dispensers with a replaceable and refillable 1 litre container,	100%	Steel
		86	Satin stainless steel paper towel dispenser with min 600 folded paper towels	100%	Steel
	142	87	Satin stainless steel full automatic industrial hand dryer with 2 vandal proof lock screws and key wrench	100%	Steel
		88	Paraplegic Rails dog leg grab rail with 3 supports or equal approved with brushed grade 304 stainless steel finish, overall size 750 x 750mm,	100%	Steel
		89	Paraplegic Rails flush valve grab rail or equal approved with brushed grade 304 stainless steel finish, overall size 842mm long	100%	Steel
	54	90	Sliding manual weatherproofed gate 5.70 x 2.6m high with galvanised wheels	100%	Steel
		91	Sliding manual weatherproofed gate 8.60 x 2.6m high with galvanised wheels	100%	Steel
		92	Pedestrian gate overall size 900 x 2100mm high and lockable sliding bolt	100%	Steel
		93	Frame for door size 813 x 2100mm high	100%	Steel
		94	Window overall size 600 x 600mm high	100%	Steel
	55	95	Transformer: Double door size 1524 x 2134mm high,	100%	Steel
		97	Recycling bin formed of GRC and stainless steel	100%	Steel
	59	98	Cement plaster: On walls	100%	Cement
		99	Cement plaster: On narrow widths	100%	Cement
	68	108	Double end bowl inset sink, overall size 1160 x 460mm wide with two 340 x 370 x 150mm deep bowl	100%	Steel
	69	115	Floor drain square brass including trap	100%	Steel
		117	40mm Deep seal "P" or "S" trap	100%	PVC
		118	Chromium plated bottle trap	100%	Steel
		119	40mm rough brass shower P trap	100%	Steel
		120	15mm ball type angle valve.	70%	Valves

		121	15mm Chrome plated single lever basin mixer	70%	Taps, Cocks
		122	Medical elbow action pillar tap with high waist	70%	Taps, Cocks
	70	123	25mm diameter chrome flush valve for WC	70%	Taps, Cocks
		124	15mm chrome plated deck mounted sink mixer	70%	Taps, Cocks
		125	15mm chrome plated wall mounted underwall shower mixer	70%	Taps, Cocks
	79	150	Allow the amount of R1 200 000.00 (One Million Two Hundred Thousand Rand) for roof installation by a roof specialist,	100%	Steel
Street Furniture	86	14	Perforated galvanised steel seat 1800mm long	100%	Steel
		15	Perforated galvanised steel litter bin 497mm Diameter x 815mm high	100%	Steel
Electrical	1	1	Main Site DB - PC	90%	Electrical Cables
		2	DB - G Refurb - PC	90%	Electrical Cables
		3	DB - F Refurb - PC	90%	Electrical Cables
		4	Platform Distribution Boards - PC	90%	Electrical Cables
		5	50mm <sup>2</sup> x 4 core ecc cable	90%	Electrical Cables
	2	10	2,5mm <sup>2</sup> x 3 (Red, Black & Green) - Housewire	90%	Electrical Cables
		11	25mm diameter PVC conduit	100%	PVC
	3	4	4mm <sup>2</sup> x 3 (Red, Black & Green) - Housewire	90%	Electrical Cables
		5	25mm diameter PVC conduit	100%	PVC
		6	2 compartment PVC Power Skirting	100%	PVC
Mechanical	2	2.3	Galvanised mild steel pipe treated with galvafruid paint and two coats of firemen red signal paint	100%	Steel
	4		<u>PIPING - COPPER</u>		
		1.1	Ø28mm pipe	100%	Steel
		1.2	Ø22mm pipe	100%	Steel
		1.3	Ø15mm pipe	100%	Steel
		2.1	Ø28mm Equal T-piece	100%	Steel
		2.2	Ø22mm Equal T-piece	100%	Steel
		2.3	Ø28mm Elbow: 90°	100%	Steel
		2.4	Ø22mm Elbow: 90°	100%	Steel
		2.5	Ø15mm Elbow: 90°	100%	Steel
		2.6	Reducer: Ø28mm x Ø22mm	100%	Steel
		2.8	Reducer: Ø28mm x Ø15mm	100%	Steel
		2.9	Reducer: Ø22mm x Ø15mm		

		2.10	Pipe clamps and hangers		
	5	3.1	Ø25mm isolating ball valve with lever on cold and hot water main pipes	70%	Valves
		3.2	Ø20mm isolating ball valve with lever on cold and hot water main pipes	70%	Valves
		3.3	Flexible connector to sanitay fittings	70%	Valves
		3.4	15mm diameter stopcock/angle valve on cold and hot water pipe	70%	Valves
		4.1	Supply and install a vertical electric water geyser	70%	Geysers
	6	1.1	Ø50mm uPVC pipe	100%	PVC
		1.2	Ø110mm uPVC pipe	100%	PVC
		2.1	Ø50mm fitting; 90°elbow	100%	PVC
		2.2	Ø110mm fitting; 45°elbow	100%	PVC
		2.3	Ø110mm x Ø110mm x Ø110mm fitting; 87.5° swept entry, lateral branch junction	100%	PVC
		2.4	Ø50mm vent one way valve	100%	PVC
		2.5	Ø110mm x Ø50mm fitting; concentric reducer		
		3.1	40mm flexi rubber "P" trap complete with coupling clamps.	100%	PVC
Electronics	1	9	Cables PH30	90%	Electrical Cables
		10	Cables PH120	90%	Electrical Cables
Access Control	2	4	Cable - CAT 6E U/UTP BC 500m	90%	Electrical Cables
		5	Cable CAT6E UTP 0.57mm Solid Copper	90%	Electrical Cables
	3	11	Full height, bi directional single turnstile - Single turnstile	100%	Steel
	4	15	Security gate 970mm wide x 2 125mm high	100%	Steel
<b>NALEDI STATION</b>					
<b>BILL</b>	<b>PAGE NO.</b>	<b>ITEM NO.</b>	<b>DESCRIPTION</b>	<b>LOCAL CONTENT THRESHOLD</b>	
Building	28	44	One brick walls	100%	Cement
		45	One brick walls		
	30	50	Half brick walls	100%	Cement
		51	One brick walls	100%	Cement
	31	53	Making good defects in concrete with an approved cementious compound: On edges of concrete stairs	100%	Cement
	32	56	Breaking out for and forming openings through brickwalls for new doors and frames including necessary precast concrete lintels and making good plaster on both sides : Opening for door with steel frame 813 x 2032mm high	100%	Cement

		57	Breaking out for and forming openings through brickwalls for new doors and frames including necessary precast concrete lintels and making good plaster on both sides : Opening for window size 1180 x 1360mm high overall through one brick wall	100%	Cement
	42	79	25MPa/19mm concrete: Strip footings	100%	Cement
		80	25MPa/19mm concrete: Surface beds	100%	Cement
		81	25MPa/19mm concrete: Slabs including upstand beams	100%	Cement
		82	Making and testing 150 x 150 x 150mm concrete strength test cubes	100%	Cement
	43	88	Type 193 fabric reinforcement in concrete surface beds	100%	Steel
		89	All diameter bars	100%	Steel
	46	90	Half brick walls	100%	Cement
		91	One brick walls	100%	Cement
		92	Half brick walls	100%	Cement
		93	Half brick walls in beam filling	100%	Cement
		94	One brick walls	100%	Cement
		95	75mm Wide reinforcement	100%	Steel
		96	150mm Wide reinforcement	100%	Steel
		97	110 x 75mm Lintels in lengths not exceeding	100%	Steel
		98	30 x 1,2mm Wall tie 500mm long	100%	Steel
		99	Extra over brickwork for face brickwork	100%	Cement
	100	100	Extra over brickwork for face brickwork in foundations	100%	Cement
		102	Nutec-Cement/Fibre-Cement: 15 x 175mm Wide sills	100%	Cement

	52	111	0.58mm spelter galvanised ribbed sheet steel with Chromadek finish: Roof covering with pitch not exceeding 25 degrees	100%	Steel
		112	Ridge covering 462mm girth	100%	Steel
		113	Apex flashing 462mm girth	100%	Steel
	53	114	Roof covering with pitch not exceeding 25 degrees	100%	Steel
	56	118	Medium density plain fibre-cement : 12 x 300mm Fascias and barge boards	100%	Cement
	63	135	100% Stainproof (Polypropylene) structured needlepunch SABS Class 3 fire rating heavy commercial carpet tiles, size 500 x 500 x 8,5mm thick: On floors	100%	Textile
	64	137	WC indicator bolt	100%	Steel
		138	Disabled indicator bolt, fixed to surface with matching stainless steel screws.	100%	Steel
		139	88 x 100mm High overall bush bearing butt hinge	100%	Steel
	65	140	Euro profile Mortice sash lock with reversible latch and deadbolt	100%	Steel
		141	Security Deadlock with a Deadcase plate in the door frame	100%	Steel
		142	813 x 200mm Kick plate	100%	Steel
		143	900 x 200mm Kick plate	100%	Steel
		144	Round D pull handle on 19 x 200 mm backplate	100%	Steel
		145	Round D pull handle on 19 x 300 mm backplate	100%	Steel
		146	Approved delayed action door closer	100%	Steel
		147	Stainless steel: 152 x 152 x 2mm Thick engraved with female pictogram	100%	Steel
		148	Stainless steel: 152 x 152 x 2mm Thick engraved with male pictogram	100%	Steel
		149	152 x 152 x 2mm Thick engraved with paraplegic pictogram	100%	Steel
		150	152 x 152 x 2mm Thick engraved with Unisex pictogram	100%	Steel
	66	151	152 x 152 x 2mm Thick engraved with kitchen and breakroom pictogram	100%	Steel
		152	152 x 152 x 2mm Thick engraved with cleaning store pictogram	100%	Steel
		153	Stainless steel door stop	100%	Steel
		154	Hat and coat hook	100%	Steel
		155	Satin stainless steel recessed toilet roll holders for single or two rolls	100%	Steel
		156	Satin stainless steel waste disposal bins with capacity of plus minus 10 litres	100%	Steel
		157	Satin stainless steel waste disposal bins with capacity of plus minus 40 litres	100%	Steel
		158	Satin stainless steel waste disposal bins with capacity of plus minus 20 litres	100%	Steel

		159	Satin stainless steel towel rings	100%	Steel
		160	Satin stainless steel soap dispensers with a replaceable and refillable 1 litre container,	100%	Steel
		161	Satin stainless steel paper towel dispenser with min 600 folded paper towels	100%	Steel
	67	162	Satin stainless steel full automatic industrial hand dryer with 2 vandal proof lock screws and key wrench	100%	Steel
		163	Paraplegic Rails dog leg grab rail with 3 supports or equal approved with brushed grade 304 stainless steel finish, overall size 750 x 750mm,	100%	Steel
		164	Paraplegic Rails flush valve grab rail or equal approved with brushed grade 304 stainless steel finish, overall size 842mm long	100%	Steel
	70	166	Double gate 900 x 2100mm high with and including two 16mm expansion bolts	100%	Steel
		167	Double gate 1830 x 2100mm high with and including two 16mm expansion bolts	100%	Steel
		168	Frame for door size 813 x 2100mm high	100%	Steel
		169	Frame for door size 960 x 2400mm high	100%	Steel
		170	Frame for door size 813 x 2100mm high	100%	Steel
		171	Frame for door size 915 x 2100mm high	100%	Steel
	71	172	Door 813 x 2032mm high for one brick wall and with 3 lever mortice lock	100%	Steel
		173	Window, overall size 1350 x 1200mm high	100%	Steel
		174	Window, overall size 1100 x 800mm high	100%	Steel
		175	Window, overall size 450 x 600mm high	100%	Steel
		176	Anti Bandit bullet resistant door and frame 920 x 2100mm high	100%	Steel
	72	177	Bullet resistant glass transaction window 750 x 1100mm high	100%	Steel
		178	Recycling bin formed of GRC and stainless steel	100%	Steel
	75	179	30mm Thick on floors and landings	100%	Cement
		180	Average 50mm thick on floors with upper surface to falls	100%	Cement
		181	Cement plaster: On walls	100%	Cement
		182	Cement plaster:On narrow widths	100%	Cement
		183	Cement plaster:On ceilings	100%	Cement
		184	Cement plaster: On walls	100%	Cement
		185	Cement plaster:On narrow widths	100%	Cement
	83	191	100 x 150mm Eaves gutters	100%	Steel
		192	Extra over 100 x 150mm eaves gutter for stopped end	100%	Steel
		193	Extra for outlet for 100mm pipe	100%	Steel
		194	100 x 75mm Rainwater pipes	100%	Steel

		195	Extra over 100 x 75mm pipe for angle	100%	Steel
		196	Extra over 100 x 75mm pipe for bend	100%	Steel
	80	197	Extra over 100 x 75mm pipe for shoe	100%	Steel
		198	Extra 100 x 75mm pipe for eaves or plinth offset	100%	Steel
	84	201	Stainless steel single end bowl inset sink overall size 800 x 460mm wide with one 340 x 370 x 150mm deep bowl,	100%	Steel
		212	40mm Deep seal "P" or "S" trap	100%	PVC
		213	Chromium plated bottle trap	100%	Steel
		214	15mm ball type angle valve	70%	Valves
		215	15mm Chrome plated single lever basin mixer	70%	Valves
		216	Chrome plated self-closing push button metering spout	70%	Taps, Cocks
		217	Medical elbow action pillar tap	70%	Taps, Cocks
		218	15mm Chrome plated deck mounted sink mixer	70%	Taps, Cocks
		219	15mm Ø BSP built-in sleeve, brass urinal flush valve	70%	Taps, Cocks
	95	262	Allow the amount of R30 000.00 (Thirty Thousand Rand) for extending the staircase handrails and balustrades	100%	Steel
Street Furniture	102	17	Perforated galvanised steel seat 1800mm long	100%	Steel
		18	Perforated galvanised steel litter bin 497mm Diameter x 815mm high	100%	Steel
Boundary Wall	108	44	25 MPa/20mm: Strip footings	100%	Cement
		45	Making and testing 150 x 150 x 150mm concrete strength test cube	100%	Cement
		46	One brick walls	100%	Cement
		47	230mm walls	100%	Cement
	109	48	150mm Wide reinforcement	100%	Steel
		49	Extra over brickwork for face brickwork	100%	Cement
		50	Extra over brickwork for face brickwork in foundations	100%	Cement
		51	Vehicle gate 6,0 x 1,8m high made with galvanised square tubing elements	100%	Steel
Fencing	111	53	Fence 1200m high with and including galvanised posts	100%	Steel
		54	Extra over for 150mm diameter taper post 2.4m long	100%	Steel
		55	Sliding gate 5.5 x 2.4m high made with galvanised square tubing elements	100%	Steel
Electrical	1	1	Main Security DB - PC	90%	Electrical Cables
		2	Ticket Office - 18 Way	90%	Electrical Cables
		3	Security Office DB 18 Way	90%	Electrical Cables
		4	160A MDB Refurb - PC	90%	Electrical Cables

		5	Stall Distribution Boards refurb	90%	Electrical Cables
		6	Toilet Distribution Boards	90%	Electrical Cables
		7	Platform Distribution Boards	90%	Electrical Cables
		8	50mm <sup>2</sup> x 4 core ecc cable	90%	Electrical Cables
		9	35mm <sup>2</sup> x 4 core ecc cable	90%	Electrical Cables
		10	25mm <sup>2</sup> x 4 core ecc cable	90%	Electrical Cables
		11	16mm <sup>2</sup> x 4 core ecc cable	90%	Electrical Cables
	3	10	2,5mm <sup>2</sup> x 3 (Red, Black & Green) - Housewire	90%	Electrical Cables
		11	25mm diameter PVC conduit	100%	PVC
	4	4	4mm <sup>2</sup> x 3 (Red, Black & Green) - Housewire	90%	Electrical Cables
		5	25mm diameter PVC conduit	100%	PVC
		6	2 compartment PVC Power Skirting	100%	PVC
Mechanical	2	2.1	65mm hydrant valve with handwheel opening mechanism & fittings	70%	Hydrants
		2.3	Galvanised mild steel pipe treated with galvafruid paint and two coats of firemen red signal paint	100%	Steel
		2.3.1	25mm	100%	Steel
		2.3.2	50mm	100%	Steel
		2.3.4	100mm	100%	Steel
	4		<u>PIPING - COPPER</u>		
		1.1	Ø28mm pipe	100%	Steel
		1.2	Ø22mm pipe	100%	Steel
		1.3	Ø15mm pipe	100%	Steel
		2.1	Ø28mm Equal T-piece	100%	Steel
		2.2	Ø22mm Equal T-piece	100%	Steel
		2.3	Ø28mm Elbow: 90°	100%	Steel
		2.4	Ø22mm Elbow: 90°	100%	Steel
		2.5	Ø15mm Elbow: 90°	100%	Steel
		2.6	Reducer: Ø28mm x Ø22mm	100%	Steel
		2.8	Reducer: Ø28mm x Ø15mm	100%	Steel
		2.9	Reducer: Ø22mm x Ø15mm	100%	Steel
	5	2.10	Pipe clamps and hangers	100%	Steel
		3.1	Ø25mm isolating ball valve with lever on cold and hot water main pipes	70%	Valves
		3.2	Ø20mm isolating ball valve with lever on cold and hot water main pipes	70%	Valves
		3.3	Flexible connector to sanitay fittings	70%	Valves

		3.4	15mm diameter stopcock/angle valve on cold and hot water pipe	70%	Valves
		4.1	Supply and install a vertical electric water geyser	70%	Geysers
		6.1	Supply and install a 1 000 litres vertical Jojo pvc tank	70%	Storage Tanks
	6	1.1	Ø50mm uPVC pipe	100%	PVC
		1.2	Ø110mm uPVC pipe	100%	PVC
		2.1	Ø50mm fitting; 90°elbow	100%	PVC
		2.2	Ø110mm fitting; 45°elbow	100%	PVC
		2.3	Ø110mm x Ø110mm x Ø110mm fitting; 87.5° swept entry, lateral branch junction	100%	PVC
		2.4	Ø50mm vent one way valve	100%	PVC
		2.5	Ø110mm x Ø50mm fitting; concentric reducer	100%	PVC
		3.1	40mm flexi rubber "P" trap complete with coupling clamps.	100%	PVC
Electronics	1	9	Fire Cables - PH30/30 minutes rated	90%	Electrical Cables
		10	Fire Cables - PH120/120 minutes rated	90%	Electrical Cables
Access Control	2	4	Cable - CAT 6E U/UTP BC 500m	90%	Electrical Cables
		5	Cable CAT6E UTP 0.57mm Solid Copper	90%	Electrical Cables
	3	11	Full height, bi directional single turnstile - Single turnstile	100%	Steel
	4	15	Security gate 970mm wide x 2 125mm high	100%	Steel

**3.** Does any portion of the goods or services offered have any imported content?

(Tick applicable box)

YES	<input type="checkbox"/>	NO	<input type="checkbox"/>
-----	--------------------------	----	--------------------------

**3.1** If yes, the rate(s) of exchange to be used in this bid to calculate the local content as prescribed in paragraph 1.5 of the general conditions must be the rate(s) published by SARB for the specific currency at 12:00 on the date of advertisement of the bid.

The relevant rates of exchange information is accessible on [www.reservebank.co.za](http://www.reservebank.co.za)

Indicate the rate(s) of exchange against the appropriate currency in the table below (refer to Annex A of SATS 1286:2011):

Currency	Rates of exchange
US Dollar	

Pound Sterling	
Euro	
Yen	
Other	

NB: Bidders must submit proof of the SARB rate (s) of exchange used.

4. Where, after the award of a bid, challenges are experienced in meeting the stipulated minimum threshold for local content the dti must be informed accordingly in order for the dti to verify and in consultation with the AO/AA provide directives in this regard.

**LOCAL CONTENT DECLARATION**  
**(REFER TO ANNEX B OF SATS 1286:2011)**

**LOCAL CONTENT DECLARATION BY CHIEF FINANCIAL OFFICER OR OTHER LEGALLY RESPONSIBLE PERSON NOMINATED IN WRITING BY THE CHIEF EXECUTIVE OR SENIOR MEMBER/PERSON WITH MANAGEMENT RESPONSIBILITY (CLOSE CORPORATION, PARTNERSHIP OR INDIVIDUAL)**

**IN RESPECT OF BID NO.....**

**ISSUED BY:** (Procurement Authority / Name of Institution):  
.....NB

- 1 The obligation to complete, duly sign and submit this declaration cannot be transferred to an external authorized representative, auditor or any other third party acting on behalf of the bidder.
- 2 Guidance on the Calculation of Local Content together with Local Content Declaration Templates (Annex C, D and E) is accessible on <http://www.thdti.gov.za/industrialdevelopment/ip.jsp>. Bidders should first complete Declaration D. After completing Declaration D, bidders should complete Declaration E and then consolidate the information on Declaration C. **Declaration C should be submitted with the bid documentation at the closing date and time of the bid in order to substantiate the declaration made in paragraph (c) below.** Declarations D and E should be kept by the bidders for verification purposes for a period of at least 5 years. The successful bidder is required to continuously update Declarations C, D and E with the actual values for the duration of the contract.

I, the undersigned,..... (full names),  
do hereby declare, in my capacity as .....  
of .....(name of bidder  
entity), the following:

- (a) The facts contained herein are within my own personal knowledge.
- (b) I have satisfied myself that:
  - (i) the goods/services/works to be delivered in terms of the above-specified bid comply with the minimum local content requirements as specified in the bid, and as measured in terms of SATS 1286:2011; and
- (c) The local content percentage (%) indicated below has been calculated using the formula given in clause 3 of SATS 1286:2011, the rates of exchange indicated in paragraph 4.1 above and the information contained in Declaration D and E which has been consolidated in Declaration C:

Bid price, excluding VAT (y)	R
Imported content (x), as calculated in terms of SATS 1286:2011	R
Stipulated minimum threshold for local content (paragraph 3 above)	
Local content %, as calculated in terms of SATS 1286:2011	

**If the bid is for more than one product, the local content percentages for each product contained in Declaration C shall be used instead of the table above.**

**The local content percentages for each product has been calculated using the formula given in clause 3 of SATS 1286:2011, the rates of exchange indicated in paragraph 4.1 above and the information contained in Declaration D and E.**

- (d) I accept that the Procurement Authority / Institution has the right to request that the local content be verified in terms of the requirements of SATS 1286:2011.
- (e) I understand that the awarding of the bid is dependent on the accuracy of the information furnished in this application. I also understand that the submission of incorrect data, or data that are not verifiable as described in SATS 1286:2011, may result in the Procurement Authority / Institution imposing any or all of the remedies as provided for in Regulation 14 of the Preferential Procurement Regulations, 2017 promulgated under the Preferential Policy Framework Act (PPPFA), 2000 (Act No. 5 of 2000).

**SIGNATURE:** \_\_\_\_\_

**DATE:** \_\_\_\_\_

**WITNESS No. 1** \_\_\_\_\_

**DATE:** \_\_\_\_\_

**WITNESS No. 2** \_\_\_\_\_

**DATE:** \_\_\_\_\_