

**TECHNICAL EVALUATION CRITERIA: ESTABLISHMENT OF A 5 YEAR SUPPLY CONTRACT CIVIL CONSUMABLES AT LETHABO POWER STATION ON AN AS AND WHEN REQUIRED BASIS.**

Functionality Criteria	Maximum number of points percentages	Tenderers will be expected to score at least the minimum threshold per functional area to proceed to the next step
Technical	100%	The minimum threshold is 80%.

Reference to Technical Specification / Tender Returnable	Criteria Weighting (%)	Criteria Sub Weighting (%)	Score Qualification
<p><b>Data sheets for 88</b> items marked with a <b>"YES"</b> on the below table.</p> <p>Data sheets to be item specific and no score will be allocated if not all data sheets are submitted.</p> <p>Only original or certified copies that reflect the manufacture's name where required will be accepted.</p>	<b>50 %</b>		<p>Provided all 88 items = (50%)</p> <p>Not provided = (0%)</p>
The supplier has <b>guaranteed letter from manufacturer</b> that they are able to provide the quantities of products required	<b>15 %</b>		<p>(Certified)</p> <p>3 Signed agreements =15%</p> <p>0 No letter provided = (0%)</p>
The supplier has provided <b>verifiable references</b> for other customers that they supply with the similar products	<b>15%</b>		<p>List of references (certified) with contact details or copy Previous Purchase order/Contract.</p> <p>More than 2 refs =15%</p> <p>1 verifiable = 5%</p> <p>0 No letter provided = (0%)</p>

**TECHNICAL EVALUATION CRITERIA: ESTABLISHMENT OF A 5 YEAR SUPPLY CONTRACT CIVIL CONSUMABLES AT LETHABO POWER STATION ON AN AS AND WHEN REQUIRED BASIS.**

Functionality Criteria	Maximum number of points percentages	Tenderers will be expected to score at least the minimum threshold per functional area to proceed to the next step
Technical	100%	The minimum threshold is 80%.

Supplier to provide a <b>signed letter</b> with commitments on their <b>lead-time</b>	<b>20 %</b>		Delivery within 14 days after an order = (20%) Delivery within 21 days after an order = (10%) Delivery after 30 days or more after an order = (0%)
<b>TOTAL: 100</b>			

The threshold on the technical evaluation criteria is 80%. Suppliers/Distributors would be deemed technically unacceptable if they score less and will thus be disqualified.

All certified documents should not be older than three months.

TECHNICAL EVALUATION OF TENDERS No.	Name of Supplier	Technically	Reason
Acceptable		Unacceptable	
1.			

Material	Text	Base Unit of Measure	DATA SHEET REQUIRED
0010142	TAPE, ELECTRICAL: WIDTH: 18 MM; LENGTH: 20 M; MATERIAL: VINYL; COLOR: BLACK; PVC; TO SABS 122; 0.18MM THK; ADHESIVE	EA	YES
0010143	TAPE, ELECTRICAL: WIDTH: 18 MM; LENGTH: 20 M; MATERIAL: VINYL; COLOR: BLUE; PVC; TO SABS 122; 0.18MM THK; ADHESIVE	EA	YES
0010144	TAPE, ELECTRICAL: WIDTH: 18 MM; LENGTH: 20 M; MATERIAL: VINYL; COLOR: RED; PVC; TO SABS 122; 0.18MM THK; ADHESIVE	EA	YES

**TECHNICAL EVALUATION CRITERIA: ESTABLISHMENT OF A 5 YEAR SUPPLY CONTRACT CIVIL CONSUMABLES AT LETHABO POWER STATION ON AN AS AND WHEN REQUIRED BASIS.**

Functionality Criteria	Maximum number of points percentages	Tenderers will be expected to score at least the minimum threshold per functional area to proceed to the next step
Technical	100%	The minimum threshold is 80%.

0010145	TAPE, ELECTRICAL: WIDTH: 18 MM; LENGTH: 20 M; MATERIAL: VINYL; COLOR: WHITE; PVC, TO SABS 122; 0.18MM THK; ADHESIVE	EA	YES
0010161	TAPE, ELECTRICAL: WIDTH: 19 MM; LENGTH: 9.15 M; MATERIAL: RUBBER; COLOR: BLACK; SPECIFICATION: C.O.C; Q4:NSF:NC:0; REFERENCE NO: 23, UNK; SUPPL P/N: SCOTCH23; 0.76MM THK; SCOTCH22; SCOTCH23	EA	YES
0011500	TIE, CABLE: TYPE: SELF LOCKING; DIAMETER RANGE: 30 MM; WIDTH: 3.5 MM; LENGTH: 150 MM; MATERIAL: NYLON; STRENGTH: 15 KG; COLOR: BLACK; REFERENCE NO: T30R, UNK	EA	YES
0011501	TIE, CABLE: TYPE: SELF LOCKING; DIAMETER RANGE: 109 MM; WIDTH: 4.7 MM; LENGTH: 395 MM; MATERIAL: NYLON; STRENGTH: 32 KG; COLOR: BLACK; SUPPL P/N: T50L; BRAND INSULOK, PLASTIC, 100 PER PACKET	EA	YES
0016493	TAPE, ADHESIVE: TYPE: MASKING; DIMENSIONS: WD 18 MM X LG 40 M; MATERIAL: PAPER; COLOR: BUFF; CORE SIZE: 75 MM	EA	YES
0016829	PAINT, OIL: TYPE: ENAMEL; COLOR: GREEN; CONTAINER: CAN 5 L; FINISH: GLOSS; SPECIFIC USE: STOEP; REFERENCE NO: SP2, UNK; SHOULD COMPLY WITH THE CHEMICAL HAZARDOUS SUBSTANCES REGULATION OF OCCUPATIONAL HEALTH AND SAFETY ACT; CHEMICAL DATA SHEET MUST BE SUPPLIED WITH EVERY DELIVERY	L	YES
0016830	PAINT, OIL: TYPE: ENAMEL; COLOR: RED; CONTAINER: CAN 5 L; FINISH: GLOSS; SPECIFIC USE: STOEP; REFERENCE NO: SP3, UNK; SPREADING RATE 6 M2/LITRE; DRYING TIME: TOUCH DRY 4HRS/23 DEG C; RE-COATING 16HRS/23 DEG C; DRY TO HANDLE 16HRS/23 DEG C; VISCOSITY 65 KREBS UNITS; SHOULD COMPLY WITH CHEMICAL HAZARDOUS REGULATION OF HEALTH AND SAFETY ACT; CHEMICAL DATA SHEET MUST BE SUPPLIED WITH EVERY DELIVERY	L	YES

**TECHNICAL EVALUATION CRITERIA: ESTABLISHMENT OF A 5 YEAR SUPPLY CONTRACT CIVIL CONSUMABLES AT LETHABO POWER STATION ON AN AS AND WHEN REQUIRED BASIS.**

Functionality Criteria	Maximum number of points percentages	Tenderers will be expected to score at least the minimum threshold per functional area to proceed to the next step
Technical	100%	The minimum threshold is 80%.

0016831	PAINT, OIL: TYPE: ENAMEL; COLOR: BLACK; CONTAINER: CAN 5 L; FINISH: HIGH GLOSS; SPECIFIC USE: EXTERIOR/INTERIOR; SPECIFICATION: SABS 630-1972 TYPE 1; CONTROLLING COLOURS 770, REQUIRED THE NEW STANDARD FOR RELIABILITY POINT 1 TO 16 MATERIAL SAFETY DATA SHEETS THAT COMPLIES WITH THE OCCUPATIONAL HEALTH AND SAFETY ACT'S REGULATIONS TO BE SUPPLIED, NO SUBSTANCES AND/OR INGREDIENTS THAT FALL UNDER TABLE 1 CATEGORY WILL BE USED, ANY CHEMICAL FALLING UNDER TABLE 3 OF THE SAME REGULATIONS SHALL NOT BE USED, SHALL BE BIODEGRADABLE AND OZONE FRIENDLY, COPY OF MSDS TO BE SENT TO MEDICAL CENTRE AND SAFETY RISK	L	YES
0016836	PAINT, OIL: TYPE: ENAMEL; COLOR: YELLOW GOLDEN; CONTAINER: CAN 5 L; FINISH: HIGH GLOSS; SPECIFIC USE: EXTERIOR/INTERIOR; SPECIFICATION: CKS 279-1971; SABS 630-1972; REFERENCE NO: B49, UNK; USE, MATERIAL SAFETY DATA SHEETS THAT COMPLIES WITH THE OCCUPATIONAL HEALTH AND SAFETY ACT'S REGULATIONS TO BE SUPPLIED, NO SUBSTANCES AND/OR INGREDIENTS THAT FALL UNDER TABLE 1 CATEGORY WILL BE USED, ANY CHEMICAL FALLING UNDER TABLE 3 OF THE SAME REGULATIONS SHALL NOT BE USED, SHALL BE BIODEGRADABLE AND OZONE FRIENDLY, COPY OF MSDS TO BE SENT TO MEDICAL CENTRE AND SAFETY RISK	L	YES
0016837	PAINT, OIL: TYPE: OIL BASE; COLOR: ALUM; CONTAINER: CAN 5 L; FINISH: SEMI GLOSS; SPECIFIC USE: EXTERIOR/INTERIOR; SABS 682 1972 GRADE 1, WITH 500ML PASTE (2 TINS = 1 ), ON PRIMED SURFACES, MATERIAL SAFETY DATA SHEETS THAT COMPLIES WITH THE OCCUPATIONAL HEALTH AND SAFETY ACT'S REGULATIONS TO BE SUPPLIED, NO SUBSTANCES AND/OR INGREDIENTS THAT FALL UNDER TABLE 1 CATEGORY WILL BE USED, ANY CHEMICAL FALLING UNDER TABLE 3 OF THE SAME REGULATIONS SHALL NOT BE USED, SHALL BE BIODEGRADABLE AND OZONE FRIENDLY, COPY OF MSDS TO BE SENT TO MEDICAL CENTRE AND SAFETY RISK	L	YES

**TECHNICAL EVALUATION CRITERIA: ESTABLISHMENT OF A 5 YEAR SUPPLY CONTRACT CIVIL CONSUMABLES AT LETHABO POWER STATION ON AN AS AND WHEN REQUIRED BASIS.**

Functionality Criteria	Maximum number of points percentages	Tenderers will be expected to score at least the minimum threshold per functional area to proceed to the next step
Technical	100%	The minimum threshold is 80%.

0016841	PAINT STRIPPER: CONTAINER TYPE: TIN; CONTAINER CAPACITY: 5 L; SUPPL P/N: PR17; GENERAL USE; DOUBLE STRENGTH, TYPE 1 CLASS A, SABS 1323; MATERIAL SAFETY DATA SHEETS THAT COMPLIES WITH THE OCCUPATIONAL HEALTH AND SAFETY ACT'S REGULATIONS TO BE SUPPLIED; NO SUBSTANCES AND/OR INGREDIENTS THAT FALL UNDER TABLE 1 CATAGORY WILL BE USED; ANY CHEMICAL FALLING UNDER TABLE 3 OF THE SAME REGULATIONS SHALL NOT BE USED; SHALL BE BIODEGRADABLE AND OZONE FRIENDLY; COPY OF MSDS TO BE SENT TO MEDICAL CENTRE AND SAFETY RISK	L	YES
0016853	TAPE, THREAD: TYPE: SEALING; WIDTH: 10 MM; MATERIAL: PTFE; COLOR: WHITE; REFERENCE NO: PTFE, UNK; WITHOUT DISPENSER; THK 0.075 MM	EA	YES
0017792	KIT: TYPE: ADHESIVE; COMPRISING: HARDNER PUTTY STICK 125 G; WHITE AND BROWN, GENERAL HEAVY DUTY USE, SHOULD COMPLY WITH THE CHEMICAL HAZARDOUS SUBSTANCES REGULATION OF OCCUPATIONAL HEALTH AND SAFETY ACT, CHEMEALS TO BE SUPPLIED WITH MSDS AND SECTION 12 (ECOLOGICAL INFORMATION OF THE MSDS TO BE COMPLETED IN DETAIL) WITH EVERY DELIVERY	EA	YES
0018801	CLAMP: TYPE: C; MATERIAL: STL; REFERENCE NO: 33-5L, UNK; SCREW; FOR TURBINE	EA	Not required
0020689	COMPOUND: TYPE: LUBRICATION; CONTAINER: CAN AEROSOL; PHYSICAL FORM: SPRAY; SUPPL P/N: DG22; GLACIER GLEIT, USED ON THE BARRING GEAR, CHEMICALS TO BE SUPPLIED WITH MSDS AND SECTION 12 (ECOLOGICAL INFORMATION OF THE MSDS TO BE COMPLETED IN DETAIL)	EA	YES
0020865	COMPOUND, SEALING: TYPE: FERMIT; COLOR: BLK; CONTAINER: CAN 650 G; OEM P/N: 9710-159, OEM: GE STEAM POWER SERVICE; 9710-160, OEM: GE STEAM POWER SERVICE; CHEMICALS TO BE SUPPLIED WITH MSDS AND SECTION 12 (ECOLOGICAL INFORMATION OF THE MSDS TO BE COMPLETED IN DETAIL); THE FOLLOWING IS REQUIRED WITH EVERY DELIVERY; SHELF LIFE; DATE OF MANUFACTURE AND METHOD OF STORAGE	KG	YES
0039607	CLAMP, WIRE ROPE: TYPE: U-BOLT; ROPE SIZE: 20 MM; CLAMP MATERIAL: STL GALV; CROSBY, DROPPED FORGED, SABS813:1973; SINGLE GRIP, SINGLE SADDLES	EA	Not required

**TECHNICAL EVALUATION CRITERIA: ESTABLISHMENT OF A 5 YEAR SUPPLY CONTRACT CIVIL CONSUMABLES AT LETHABO POWER STATION ON AN AS AND WHEN REQUIRED BASIS.**

Functionality Criteria	Maximum number of points percentages	Tenderers will be expected to score at least the minimum threshold per functional area to proceed to the next step
Technical	100%	The minimum threshold is 80%.

0039608	CLAMP, WIRE ROPE: TYPE: SINGLE GRIP, SINGLE SADDLE; ROPE SIZE: 16 MM; CLAMP MATERIAL: STL GALV; SUPPL P/N: 858082002; CROSBY TO SABS 763, TO THE LATEST EDITION OF SABS 813 AND BEARING THE SABS MARK OF APPROVAL; U-BOLT	EA	Not required
0039609	CLAMP, WIRE ROPE: TYPE: U-BOLT; ROPE SIZE: ID 10 MM; CLAMP MATERIAL: STL GALV; CROSBY TO THE LATEST EDITION OF SABS 813 AND BEARING THE SABS MARK OF APPROVAL; SINGLE GRIP, SINGLE SADDLES	EA	YES
0050506	PAINT, OIL: COLOR: BLUE; CONTAINER: CAN 80 ML; FINISH: GLOSS; SPECIFIC USE: TOUCH UP; REFERENCE NO: 518859-82, UNK; FOR TYPE MAB103B-24 OIL SEPARATOR	EA	YES
0053051	CLAMP, HOSE: INSIDE DIAMETER: 140 MM; MATERIAL: STL; FASTENING DEVICE TYPE: SCREW; DRAWING NO: P00234S8 REV 1; REFERENCE NO: ITEM 53, UNK; FOR FILTER MOUNTING BAND, FOR USED ON PRECIPITATORS	EA	Not required
0053057	CLAMP: TYPE: ANVIL ARM; DIMENSIONS: WD 45 X LG 90 MM; MATERIAL: STL; DRAWING NO: E4/912XB,E4 913XB REV 1; PAIRS, USED ON THE PRECIPITATORS	EA	Not required
0057513	CLAMP, HOSE: INSIDE DIAMETER: 17-6 MM; MATERIAL: STL; FASTENING DEVICE TYPE: WORM; SUPPL P/N: GM4; THE ITEM MUST BE ORIGINAL PROTECTIVE PACKED	EA	Not required
0059204	CLAMP, HOSE: INSIDE DIAMETER: 22-10 MM; MATERIAL: SS; FASTENING DEVICE TYPE: WORM; REFERENCE NO: SS0600N, UNK	EA	Not required
0059205	CLAMP, HOSE: INSIDE DIAMETER: 38-17 MM; MATERIAL: SS; FASTENING DEVICE TYPE: WORM; REFERENCE NO: SS1600N, UNK; RANGE 22-38MM	EA	Not required
0059206	CLAMP, HOSE: TYPE: HEAVY DUTY; INSIDE DIAMETER: 82-57 MM; MATERIAL: SS; FASTENING DEVICE TYPE: WORM; REFERENCE NO: SS4400N, UNK; ONLY PARKER WILL BE ACCEPTED	EA	Not required
0059207	CLAMP, HOSE: TYPE: HEAVY DUTY; INSIDE DIAMETER: 127-102 MM; MATERIAL: SS; FASTENING DEVICE TYPE: WORM; REFERENCE NO: SS7200N, UNK; ONLY PARKER WILL BE ACCEPTED; RANGE 83-127MM	EA	Not required
0066735	CLOSURE: MATERIAL: NYLON; DIMENSIONS: DIA 25 X THK 9 MM; TYPE: LUBE OIL PUMP; SUPPL P/N: 400-20028-1; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	EA	YES

**TECHNICAL EVALUATION CRITERIA: ESTABLISHMENT OF A 5 YEAR SUPPLY CONTRACT CIVIL CONSUMABLES AT LETHABO POWER STATION ON AN AS AND WHEN REQUIRED BASIS.**

Functionality Criteria	Maximum number of points percentages	Tenderers will be expected to score at least the minimum threshold per functional area to proceed to the next step
Technical	100%	The minimum threshold is 80%.

0079152	CHISEL, COLD HAND: LENGTH: 210 MM; BLADE WIDTH: 25 MM; MATERIAL: STL FORGED; SHANK: 25 MM HEX; TYPE: FLAT	EA	Not required
0079153	CHISEL: TYPE: COLD DIAMOND POINT; BLADE WIDTH: 7 MM; LENGTH: 160 MM; SHANK: HEX 18 MM; MATERIAL: STL FORGED; SUBMIT TEST TEST CERTIFICATE ON DELIVERY	EA	Not required
0079198	SCRAPER: TYPE: PAINT; DIMENSIONS: WD 75 X LG 230 MM; MATERIAL: STL/WOOD; SEMI FLEXIBLE BLADE	EA	Not required
0079226	CHISEL, COLD HAND: LENGTH: 150 MM; BLADE WIDTH: 10 MM; MATERIAL: FST HARDENED; SHANK: 10 MM HEX; TYPE: FLAT	EA	Not required
0079356	BRUSH: TYPE: CONDENSOR TUBE CLEANING; DIMENSIONS: DIA 22 X LG 218 MM; MATERIAL: NYLON; 133 MM LG; NO HANDLE; FOR CONDENSOR TUBE CLEANING	EA	Not required
0079433	BRUSH: TYPE: TUBE; DIMENSIONS: DIA 22 X LG 75 MM; MATERIAL: NYLON; NO HANDLE; BULLET; COMPLETE WITH ONE RUBBER WASHER PLUS THREE LEATHER WASHERS AND CRIMPED LUGS AT BOTH ENDS	EA	Not required
0079434	BRUSH, WIRE: TYPE: TUBE; TRIM LENGTH: 9 MM; DIMENSIONS: DIA 23 X LG 70 MM; MATERIAL: BRN; NO HANDLE; BULLET; WITH NYLON BRISTLE; COMPLETE WITH ONE RUBBER WASHER PLUS THREE LEATHER WASHERS AND CRIMPED LUGS AT BOTH ENDS	EA	Not required
0079555	BRUSH, ROTARY: TYPE: SCRATCH; DIAMETER: DIA 76 MM; MATERIAL: SS; REFERENCE NO: MSS408, UNK; THK 12MM; NO HANDLE; SOLID SHANK 6MM MOUNTED; TRIM LENGTH: 22 MM	EA	Not required
0079556	BRUSH, WIRE: TYPE: SCRATCH; TRIM LENGTH: 42 MM; DIMENSIONS: ID 22.2 X OD 220 X WD 25 MM; MATERIAL: CS; REFERENCE NO: W500, UNK; FLAT; FOR BENCH GRINDER	EA	Not required
0079557	BRUSH, WIRE: TYPE: SCRATCH; TRIM LENGTH: 40 MM; DIMENSIONS: DIA 140 MM; MATERIAL: CS; REFERENCE NO: C652142, UNK; NO HANDLE; FITTING 14X2MM METRIC	EA	Not required
0097910	TAPE, THREAD: TYPE: SEALING; WIDTH: 20 MM; MATERIAL: GRAPHITE; COLOR: BLACK; 15.2M LG, ONLY STAG OR POPYEX TAPE ACCEPTABLE	EA	YES
0097911	TAPE, THREAD: TYPE: SEALING; WIDTH: 25 MM; MATERIAL: GRAPHITE; COLOR: BLK; SUPPL P/N: 0903; TYPE STAG OR POPYEX ACCEPTABLE; LG 15.2M; 25MMX15M	EA	YES

**TECHNICAL EVALUATION CRITERIA: ESTABLISHMENT OF A 5 YEAR SUPPLY CONTRACT CIVIL CONSUMABLES AT LETHABO POWER STATION ON AN AS AND WHEN REQUIRED BASIS.**

Functionality Criteria	Maximum number of points percentages	Tenderers will be expected to score at least the minimum threshold per functional area to proceed to the next step
Technical	100%	The minimum threshold is 80%.

0098350	SEAL: MATERIAL: SILICON; APPLICATION: ROLLER; USED ON THE ASH FLOW CONTROL GATE SIZE 300MM ON THE ASH CONDITIONERS; ONLY BRELKO WILL BE ACCEPTED; MOULD TO BE KEPT IN LETHABO STORES	EA	YES
0101121	SEALANT: MATERIAL: SILICON; REFERENCE NO: PES1039VJ, UNK; VIKING JOHNSON COUPLING SEAL; EXTRUSION IN 25M LG	M	YES
0101745	COMPOUND, SEALING: CONTAINER: TUBE 50 ML; MATERIAL: RUBBER; ROBEX	EA	YES
0109469	CLOTH, ABRASIVE: TYPE: SANDING; FLINT/EMERY GRADE DESIGNATOR: 100; OVERALL WIDTH: 50 MM; LENGTH: 50 M; ABRASIVE MATERIAL: AL OXIDE; BACKING MATERIAL: RESIN	M	Not required
0109474	CLOTH, ABRASIVE: TYPE: SANDING; FLINT/EMERY GRADE DESIGNATOR: 100; OVERALL WIDTH: 300 MM; LENGTH: 50 M; ABRASIVE MATERIAL: SILICON; BACKING MATERIAL: RESIN; FLOOR BOND/BACKING, EMERY	M	Not required
0109477	CLOTH, ABRASIVE: TYPE: SANDING; FLINT/EMERY GRADE DESIGNATOR: 60; OVERALL WIDTH: 50 MM; LENGTH: 50 M; ABRASIVE MATERIAL: AL OXIDE; BACKING MATERIAL: RESIN; BOND	M	Not required
0109478	CLOTH, ABRASIVE: TYPE: SANDING; FLINT/EMERY GRADE DESIGNATOR: 150; OVERALL WIDTH: 50 MM; LENGTH: 50 M; ABRASIVE MATERIAL: AL OXIDE; BACKING MATERIAL: PAPER; ECONOMY ROLLS; BOND	M	Not required
0109506	COMPOUND, ABRASIVE: TYPE: GRINDING; GRIT: FINE; CONTAINER: CAN 500 G; FORM: PASTE; ABRASIVE MATERIAL: SILICON CARBIDE OIL GREASE BASE; USAGE DESIGN: VALVE; TYPE SUPERLAP, CHEMICALS TO BE SUPPLIED WITH MSDS AND SECTION 12 (ECOLOGICAL INFORMATION OF THE MSDS TO BE COMPLETED IN DETAIL)	EA	YES
0109507	COMPOUND, ABRASIVE: TYPE: GRINDING; GRIT: M; CONTAINER: CAN 500 G; FORM: PASTE; ABRASIVE MATERIAL: SILICON CARBIDE OIL GREASE BASE; USAGE DESIGN: VALVE; TYPE LAPPING SUPERLAP; CHEMICALS TO BE SUPPLIED WITH MSDS AND SECTION 12 (ECOLOGICAL INFORMATION OF THE MSDS TO BE COMPLETED IN DETAIL); THE FOLLOWING IS REQUIRED WITH EVERY DELIVERY; SHELF LIFE; DATE OF MANUFACTURE AND METHOD OF STORAGE	EA	YES



**TECHNICAL EVALUATION CRITERIA: ESTABLISHMENT OF A 5 YEAR SUPPLY CONTRACT CIVIL CONSUMABLES AT LETHABO POWER STATION ON AN AS AND WHEN REQUIRED BASIS.**

Functionality Criteria	Maximum number of points percentages	Tenderers will be expected to score at least the minimum threshold per functional area to proceed to the next step
Technical	100%	The minimum threshold is 80%.

0109508	COMPOUND, ABRASIVE: TYPE: LAPPING; GRIT: COARSE; CONTAINER: CAN 500 G; FORM: PASTE; ABRASIVE MATERIAL: SILICON CARBIDE OIL GREASE BASE; USAGE DESIGN: VALVE; GRINDING; TYPE SUPERLAP; CHEMICALS TO BE SUPPLIED WITH MSDS AND SECTION 12 (ECOLOGICAL INFORMATION OF THE MSDS TO BE COMPLETED IN DETAIL); THE FOLLOWING IS REQUIRED WITH EVERY DELIVERY; SHELF LIFE; DATE OF MANUFACTURE AND METHOD OF STORAGE	EA	YES
0109512	COMPOUND, ABRASIVE: TYPE: GRINDING; GRIT: 100; COARSE; CONTAINER: TUBE 50 G; FORM: PASTE; ABRASIVE MATERIAL: SILICON CARBIDE OIL GREASE BASE; USAGE DESIGN: VALVE; TYPE SUPERLAP, FOR HARD MATERIAL HMC, CHEMICALS TO BE SUPPLIED WITH MSDS AND SECTION 12 (ECOLOGICAL INFORMATION OF THE MSDS TO BE COMPLETED IN DETAIL)	EA	YES
0109513	COMPOUND, ABRASIVE: TYPE: GRINDING; GRIT: 220; FINE; F; CONTAINER: TUBE 50 G; FORM: PASTE; ABRASIVE MATERIAL: SILICON CARBIDE OIL GREASE BASE; USAGE DESIGN: VALVE; TYPE SUPERLAP, FOR HARD MATERIAL HMC, CHEMICALS TO BE SUPPLIED WITH MSDS AND SECTION 12 (ECOLOGICAL INFORMATION OF THE MSDS TO BE COMPLETED IN DETAIL)	EA	YES
0109514	COMPOUND, ABRASIVE: TYPE: GRINDING; GRIT: 320; VERY FINE; F; CONTAINER: TUBE 50 G; FORM: PASTE; ABRASIVE MATERIAL: SILICON CARBIDE OIL GREASE BASE; USAGE DESIGN: VALVE; TYPE SUPERLAP, FOR HARD MATERIAL HMC CHEMICALS TO BE SUPPLIED WITH MSDS AND SECTION 12 (ECOLOGICAL INFORMATION OF THE MSDS TO BE COMPLETED IN DETAIL)	EA	YES
0109515	COMPOUND, ABRASIVE: TYPE: GRINDING; GRIT: 400; F; CONTAINER: TUBE 50 G; FORM: PASTE; ABRASIVE MATERIAL: SILICON CARBIDE OIL GREASE BASE; USAGE DESIGN: VALVE; TYPE SUPERLAP, HARD MATERIAL HMC, CHEMICALS TO BE SUPPLIED WITH MSDS AND SECTION 12 (ECOLOGICAL INFORMATION OF THE MSDS TO BE COMPLETED IN DETAIL)	EA	YES
0109540	CLOTH, ABRASIVE: TYPE: SANDING; FLINT/EMERY GRADE DESIGNATOR: FINE; OVERALL WIDTH: 230 MM; LENGTH: 280 MM; BACKING MATERIAL: EMERY; SHEET	EA	Not required
0109542	CLOTH, ABRASIVE: TYPE: SANDING; FLINT/EMERY GRADE DESIGNATOR: COARSE; OVERALL WIDTH: 230 MM; LENGTH: 280 MM; BACKING MATERIAL: EMERY; SHEET	EA	Not required

**TECHNICAL EVALUATION CRITERIA: ESTABLISHMENT OF A 5 YEAR SUPPLY CONTRACT CIVIL CONSUMABLES AT LETHABO POWER STATION ON AN AS AND WHEN REQUIRED BASIS.**

Functionality Criteria	Maximum number of points percentages	Tenderers will be expected to score at least the minimum threshold per functional area to proceed to the next step
Technical	100%	The minimum threshold is 80%.

0110354	CLAMP: TYPE: MOTOR DRIVE; DIMENSIONS: WD 11 X LG 19 MM; MATERIAL: STL; USED ON MT81 MOTOR DRIVES ON THE SWITCHGEAR LINKAGE BOXES IN THE HIGH VOLTAGE YARD	EA	Not required
0110426	CLAMP: TYPE: LIGHT FITTING; DIMENSIONS: 5 MM; MATERIAL: STL; SPRING TOGGELS	EA	Not required
0114760	BRICK, REFRACTORY: DIMENSIONS: WD 100 X LG 150 X THK 25 MM; SHAPE: TILE; MATERIAL: ALUMINA 94 PCT; WELD ON, COMPLETE WITH STEEL INSERTS AND CERAMIC PLUGS	EA	Not required
0114767	BRICK, REFRACTORY: TYPE: ALUMINA HIGH CONTENT CERAMIC; DIMENSIONS: WD 50 X LG 150 X THK 25 MM; SHAPE: TILE; MATERIAL: ALUMINA 94 PCT; SUPPL P/N: CERAMIC; W07; WELD ON CERAMIC; COMPLETE WITH MILD STEEL RETAINERS AND CERAMIC CAPS	EA	Not required
0114789	TAPE, DUCT: NOMINAL WIDTH: 50 MM; NOMINAL LENGTH: 30 M; MATERIAL: GLASS FIBER BRAIDED; COLOR: WHITE; REFERENCE NO: T6-136X6, UNK; THK 2MM; SEALING	M	YES
0115662	TAPE, MEASURING: TYPE: SILO PILOT; DIMENSIONS: WD 12 MM X LG 50 M; MATERIAL: SS; SUPPL P/N: FMM 760; TO MEASURE THE DEPTH OF ASH SILO COMPARTMENTS	EA	YES
0136034	TAPE: TYPE: NON DRIP INSULATING; DIMENSIONS: WD 50 MM X LG 10 M X THK 3 MM; MATERIAL: PUTTY; COLOR: WHITE; SELF ADHESIVE; CHEMEALS TO BE SUPPLIED WITH MSDS AND SECTION 12 (ECOLOGICAL INFORMATION OF THE MSDS TO BE COMPLETED IN DETAIL) WITH EVERY DELIVERY; THE FOLLOWING IS REQUIRED WITH EVERY DELIVERY; SHELF LIFE; DATE OF MANUFACTURE AND METHOD OF STORAGE	EA	YES
0136280	TIE, CABLE: TYPE: SELF LOCKING; WIDTH: 4.7 MM; LENGTH: 205 MM; MATERIAL: NYLON; COLOR: BLACK; SUPPL P/N: T50R; SIZE: 200MM LONG X 4,6MM WIDE	EA	YES
0136601	CLAMP: TYPE: COAL CONVEYOR SKIRTING RUBBER; DIMENSIONS: WD 180 MM; MATERIAL: STL; SUPPL P/N: NRUE 130250; USED ON THE ASH HANDLING AND COAL CONVEYOR, WELD ON	EA	Not required
0136886	TIE, CABLE: TYPE: SELF LOCKING; WIDTH: 2.5 MM; LENGTH: 105 MM; MATERIAL: NYLON; COLOR: BLACK; SUPPL P/N: T18R	EA	YES
0138053	RECTIFIER: TYPE: SILICON; INDUSTRY STANDARD: SKN100/16; REFERENCE NO: SKN 100/16, UNK; SKN100/16, UNK; ON ORDER 7LT10914 ITEM 280	EA	Not required

**TECHNICAL EVALUATION CRITERIA: ESTABLISHMENT OF A 5 YEAR SUPPLY CONTRACT CIVIL CONSUMABLES AT LETHABO POWER STATION ON AN AS AND WHEN REQUIRED BASIS.**

Functionality Criteria	Maximum number of points percentages	Tenderers will be expected to score at least the minimum threshold per functional area to proceed to the next step
Technical	100%	The minimum threshold is 80%.

0142342	CLAMP: TYPE: STRAP; DIMENSIONS: WD 17 X LG 25 MM; MATERIAL: PLASTIC; REFERENCE NO: 04172, UNK; FOR 3.3KV AND 11KV BREAKER PANELS, ON STATION DAM PUMP-HOUSE BOARDS 1 AND 2	EA	Not required
0158555	CHALK: TYPE: REFILL LINE; COLOR: RED	EA	YES
0158582	CHALK: TYPE: BOILERMAKERS; COLOR: WHITE; FORM: SOAPSTONE; SIZES: 125MM LENGTH X 12MM WIDTH X 5MM THICK	KG	YES
0158663	TAPE, ADHESIVE: TYPE: SELLO; DIMENSIONS: WD 50 MM X LG 66 M; MATERIAL: PLASTIC; COLOR: CLEAR; CORE SIZE: 76 MM	EA	YES
0158735	TAPE, ADHESIVE: TYPE: MAGIC; DIMENSIONS: WD 12 MM X LG 50 M; MATERIAL: ABS PLASTIC	EA	YES
0159642	BRUSH: TYPE: BANNISTER; DIMENSIONS: WD 220 X LG 350 X HT 65 MM; MATERIAL: CEYLON FIBER BLACK; REFERENCE NO: 3407, UNK; UNPAINTED	EA	Not required
0159704	BRUSH, WIRE: TYPE: SCRATCH; TRIM LENGTH: 25 MM; DIMENSIONS: 290 MM; MATERIAL: STL; HANDLE: WOOD, SHOE; REFERENCE NO: HB50STD, UNK; SIZE 45 MM WD X 130 MM	EA	Not required
0159874	THINNER, PAINT: TYPE: TURPENTINE; CONTAINER: CAN 5 L; SABS716; MATERIAL SAFETY DATA SHEETS WITH ENVIRONMENTAL INFORMATION IN THE 16 POINT FORMAT TO BE PROVIDED WITH EVERY DELIVERY AS REQUIRED BY THE OCCUPATIONAL HEALTH AND SAFETY ACT	L	YES
0159880	PAINT, TRAFFIC: COLOR: YELLOW GOLDEN; CONTAINER: CAN 5 L; SPECIFIC USE: ROAD MARKING; REFERENCE NO: TP41, UNK; NON-REFLECTIVE FINISH, SPECIFICATION: SABS731-1966; DELIVERY WILL NOT BE ACCEPTED IF HAZARDOUS CHEMICAL DATA SHEET IS NOT SUPPLIED WITH EVERY DELIVERY	L	YES

**TECHNICAL EVALUATION CRITERIA: ESTABLISHMENT OF A 5 YEAR SUPPLY CONTRACT CIVIL CONSUMABLES AT LETHABO POWER STATION ON AN AS AND WHEN REQUIRED BASIS.**

Functionality Criteria	Maximum number of points percentages	Tenderers will be expected to score at least the minimum threshold per functional area to proceed to the next step
Technical	100%	The minimum threshold is 80%.

0159884	PAINT, OIL: TYPE: ENAMEL; COLOR: BLACK; CONTAINER: CAN 5 L; FINISH: GLOSS; SPECIFIC USE: STOEP; SUPPL P/N: SP1; SPREADING RATE 6 M2/LITRE, DRYING TIME: TOUCH DRY 4HRS/23 DEG C, RE-COATING 16HRS/23 DEG C, DRY TO HANDLE 16HRS/23 DEG C, VISCOSITY 65 KREBS UNITS, MATERIAL SAFETY DATA SHEETS THAT COMPLIES WITH THE OCCUPATIONAL HEALTH AND SAFETY ACT'S REGULATIONS TO BE SUPPLIED, NO SUBSTANCES AND/OR INGREDIENTS THAT FALL UNDER TABLE 1 CATAGORY WILL BE USED,ANY CHEMICAL FALLING UNDER TABLE 3 OF THE SAME REGULATIONS SHALL NOT BE USED,SHALL BE BIODEGRADABLE AND OZONE FRIENDLY,COPY OF MSDS TO BE SENT TO MEDICAL CENTRE AND SAFETY RISK	L	YES
0159885	PAINT, TRAFFIC: COLOR: WHITE; CONTAINER: 5 L; SPECIFIC USE: ROAD MARKING; REFERENCE NO: TP24, UNK; NON-REFLECTIVE FINISH, CONTROLLING DESIGNATOR: CSK279, SABS731; MATERIAL SAFETY DATA SHEETS WITH ENVIRONMENTAL INFORMATION IN THE 16 POINT FORMAT TO BE PROVIDED WITH EVERY DELIVERY AS REQUIRED BY THE OCCUPATIONAL HEALTH AND SAFETY ACT	L	YES
0159898	PAINT, OIL: TYPE: ENAMEL; COLOR: RED SIGNAL; CONTAINER: CAN 5 L; FINISH: HIGH GLOSS; SPECIFICATION: SABS 630-1972; REFERENCE NO: CKS279 1971, UNK; D29, UNK; MATERIAL SAFETY DATA SHEETS THAT COMPLIES WITH THE OCCUPATIONAL HEALTH AND SAFETY ACT'S REGULATIONS TO BE SUPPLIED,NO SUBSTANCES AND/OR INGREDIENTS THAT FALL UNDER TABLE 1 CATAGORY WILL BE UDED, ANY CHEMICAL FALLING UNDER TABLE 3 OF THE SAME REGULATIONS SHALL NOT BE USED,SHALL BE BIODEGRADABLE AND OZONE FRIENDLY,COPY OF MSDS TO BE SENT TO MEDICAL CENTRE AND SAFETY RISK	L	YES
0159903	PAINT, PRIMER: TYPE: ZN CHROMATE; CONTAINER: CAN 5 L; COLOR: GREEN OXIDE; SUPPL P/N: UC501; ZINC OXIDE, 6 HOUR DRYING TIME FOR RECOATING, SHOULD COMPLY WITH THE CHEMICAL HAZARDOUS SUBSTANCES REGULATION OF OCCUPATIONAL HEALTH AND SAFETY ACT, SABS 679-1972	L	YES

**TECHNICAL EVALUATION CRITERIA: ESTABLISHMENT OF A 5 YEAR SUPPLY CONTRACT CIVIL CONSUMABLES AT LETHABO POWER STATION ON AN AS AND WHEN REQUIRED BASIS.**

Functionality Criteria	Maximum number of points percentages	Tenderers will be expected to score at least the minimum threshold per functional area to proceed to the next step
Technical	100%	The minimum threshold is 80%.

0159907	PAINT, OIL: TYPE: ENAMEL; COLOR: WHITE; CONTAINER: CAN 5 L; FINISH: HIGH GLOSS; SPECIFICATION: SABS 630-1972 TYPE 1; PSB CODE 1000, INTERIOR AND EXTERIOR USE, RECOMMENDED DRY FILM THICKNESS 25 MICRONS, SPREADING RATE 10 M2/LITRE, DRYING TIME: TOUCH DRY 4HRS/23 DEG C, RE-COATING 16HRS/23 DEG C, DRY TO HANDLE 16HRS/23 DEG C, VISCOSITY 70 KREBS UNITS, INENT PAINT MATERIAL SAFETY DATA SHEETS THAT COMPLIES WITH THE OCCUPATIONAL HEALTH AND SAFETY ACT'S REGULATIONS TO BE SUPPLIED, NO SUBSTANCES AND/OR INGREDIENTS THAT FALL UNDER TABLE 1 CATAGORY WILL BE USED, ANY CHEMICAL FALLING UNDER TABLE 3 OF THE SAME REGULATIONS SHALL NOT BE USED, SHALL BE BIODEGRADABLE AND OZONE FRIENDLY, COPY OF MSDS TO BE SENT TO MEDICAL CENTRE AND SAFETY RISK	L	YES
0159917	PAINT, OIL: TYPE: CHLORINATED RUBBER; COLOR: BLACK; CONTAINER: CAN 5 L; FINISH: NON SLIP; DRYING SPEED: FAST; REFERENCE NO: CHC3000, UNK; HIGH BUILD VINYL PAINT, NON-THIXOTROPIC VINYL COPOLYMER ENAMEL, VOLUME SOLIDS: 27-31PERCENT, RECOMMENDED DFT: MIN = 25UM MAX = 35UM, VISCOSITY AT 25 DEGEES CELCIUS: 60 - 65KU, HIGH CHEMICAL RESISTANCE, TO BE SUPPLIED WITH HAZARDOUS CHEMICAL DATA SHEET	L	YES
0159926	PAINT, OIL: TYPE: ENAMEL; COLOR: GRAY DARK; CONTAINER: CAN 5 L; FINISH: HIGH GLOSS; SPECIFICATION: SABS 630-1972 CLAUSE 1; REFERENCE NO: D36, UNK; TO CKS279: 1971, PLEASE ENSURE THAT SHELF LIFE HISTORY AND EXPIRY DATES ARE DISPLAYED	L	YES
0159946	PAINT, OIL: TYPE: ENAMEL; COLOR: BLUE ARCTIC; CONTAINER: CAN 5 L; FINISH: HIGH GLOSS; SABS SPEC F28, FOR WATER TREATMENT PLANT	L	YES

**TECHNICAL EVALUATION CRITERIA: ESTABLISHMENT OF A 5 YEAR SUPPLY CONTRACT CIVIL CONSUMABLES AT LETHABO POWER STATION ON AN AS AND WHEN REQUIRED BASIS.**

Functionality Criteria	Maximum number of points percentages	Tenderers will be expected to score at least the minimum threshold per functional area to proceed to the next step
Technical	100%	The minimum threshold is 80%.

0159952	PAINT, WATER: COLOR: WHITE; CONTAINER: CAN 5 L; SPECIFIC USE: EXTERIOR/INTERIOR; REFERENCE NO: HB1, UNK; TYPE ACRYLIC PVA, LOW SHEEN TO MATT FINISH, EMULSION TYPE CODE RECOMMENDED DRY FILM 20 MICRONS(INTERIOR) 30 MICRONS(EXTERIOR), SPREADING RATE 10 M2/LITRE(INTERIOR) NOT MORE THAN 5 M2/LITRE(EXTERIOR), DRYING TIME: TOUCH DRY 30 MIN/23 DEG C, RE-COATING: 2HRS/23 DEG C(INTERIOR), 1HR/23 DEG C(EXTERIOR), DRY TO HANDLE: 2HRS/23 DEG C(INTERIOR), 1HR/23 DEG C(EXTERIOR), VISCOSITY: 90 KREBS UNITS(INTERIOR), 115 KREBS UNITS(EXTERIOR), MATERIAL SAFETY DATA SHEETS THAT COMPLIES WITH THE OCCUPATIONAL HEALTH AND SAFETY ACT'S REGULATIONS TO BE SUPPLIED, NO SUSBTANCES AND/OR INGREDIENTS THAT FALL UNDER TABLE 1 CATAGORY WILL BE USED, ANY CHEMICAL FALLING UNDER TABLE 3 OF THE SAME REGULATIONS SHALL NOT BE USED, SHALLBE BIODEGRADABLE AND OZONE FRIENDLY, COPY OF MSDS TO BE SENT TO MEDICAL CENTRE AND SAFETY RISK	L	YES
0159964	PAINT, OIL: TYPE: SIGMACOLOR CM COATING; COLOR: CREAM; CONTAINER: CAN 4 L; FINISH: GLOSS; DRAFT GROUP TO BE SUPPLIED WITH DATA SHEET, SIGMACOLOUR CM COATING	L	YES
0159965	PAINT, OIL: TYPE: SIGMACOVER CM COATING; COLOR: GRAY; CONTAINER: CAN 5 L; FINISH: GLOSS; SPECIFIC USE: MILL FEEDERS; SUPPL P/N: S910-5654; TO BE SUPPLIED WITH WITH DATA SHEETS	L	YES
0159967	PAINT, OIL: TYPE: ENAMEL; COLOR: BROWN; CONTAINER: CAN 5 L; FINISH: GLOSS; REFERENCE NO: 0411, UNK; D232-X2X2, UNK; WITH DATA SHEET	L	YES
0159980	PAINT, OIL: TYPE: ENAMEL; COLOR: ORANGE SAFETY; CONTAINER: CAN 5 L; FINISH: GLOSS; REFERENCE NO: B26, UNK; SUPPL P/N: HG928	L	YES
0159983	THINNER, PAINT: TYPE: LAQUER GR A; CONTAINER: CAN 5 L; SATIC TYPE; THE FOLLOWING IS REQUIRED WITH EVERY DELIVERY; SHELF LIFE; DATE OF MANUFACTURE AND METHOD OF STORAGE	L	YES
0159988	PAINT, OIL: TYPE: ENAMEL; COLOR: GRAY PALE; CONTAINER: CAN 5 L; FINISH: HIGH GLOSS; PASTEL	L	YES
0160050	BRUSH, PAINT: TYPE: SETTER; WIDTH: 25 MM; MATERIAL: BRISTLE CHINESE PURE; SHAPE: FLAT; HANDLE: PLASTIC;	EA	Not required

**TECHNICAL EVALUATION CRITERIA: ESTABLISHMENT OF A 5 YEAR SUPPLY CONTRACT CIVIL CONSUMABLES AT LETHABO POWER STATION ON AN AS AND WHEN REQUIRED BASIS.**

Functionality Criteria	Maximum number of points percentages	Tenderers will be expected to score at least the minimum threshold per functional area to proceed to the next step
Technical	100%	The minimum threshold is 80%.

	SIZE: 48MM LG X 16MM THK; THE ITEM MUST BE PROTECTIVE PACKED		
0160051	BRUSH, PAINT: TYPE: SETTER; WIDTH: 50 MM; MATERIAL: BRISTLE CHINESE PURE; SHAPE: FLAT; HANDLE: PLASTIC	EA	Not required
0160052	BRUSH, PAINT: TYPE: SETTER; WIDTH: 75 MM; MATERIAL: BRISTLE CHINESE PURE; SHAPE: FLAT; HANDLE: PLASTIC; SIZE: 65MM LG X 22MM THK; THE ITEM MUST BE PROTECTIVE PACKED	EA	Not required
0160053	BRUSH, PAINT: TYPE: SETTER; WIDTH: 100 MM; MATERIAL: BRISTLE CHINESE PURE; SHAPE: FLAT; HANDLE: PLASTIC; LG 79 MM X THK 22 MM	EA	Not required
0160056	BRUSH, PAINT: TYPE: SETTER; WIDTH: 12 MM; MATERIAL: BRISTLE CHINESE PURE; SHAPE: FLAT; HANDLE: PLASTIC; SIZE: 48MM LG X 10MM THK; THE ITEM MUST BE PROTECTIVE PACKED	EA	Not required
0160060	BRUSH, PAINT: TYPE: SETTER; WIDTH: 38 MM; MATERIAL: BRISTLE CHINESE PURE; SHAPE: FLAT; HANDLE: PLASTIC; SIZE: 55MM LG X 16MM THK	EA	Not required
0160062	ROLLER: TYPE: PAINT; DIMENSIONS: LG 225 MM; MATERIAL: WOOL LAMB; REFILL	EA	Not required
0160064	ROLLER: TYPE: PAINT; DIMENSIONS: WD 228 X LG 230 MM; MATERIAL: WOOL LAMB; HANDLE COVERED	EA	Not required
0160080	COMPOUND: TYPE: PLASTIC STL; CONTAINER: CAN PLASTIC 500 G; PHYSICAL FORM: EPOXY PUTTY; REFERENCE NO: 10112, UNK; FOR REPAIRING CASTING, REBUILDING BROKEN MACHINERY AND FIXTURES, REF 10111 REQUIRED THE NEW STANDARD FOR RELIABILITY POINT 1 TO 16, CHEMEALS TO BE SUPPLIED WITH MSDS AND SECTION 12 (ECOLOGICAL INFORMATION OF THE MSDS TO BE COMPLETED IN DETAIL) WITH EVERY DELIVERY	KG	YES
0160117	COMPOUND, SEALING: TYPE: GENERAL PURPOSE; REFERENCE NO: T20-75, UNK; ONLY TITE SEAL LIGHT WEIGHT ACCEPTABLE, CHEMICALS TO BE SUPPLIED WITH MSDS AND SECTION 12 (ECOLOGICAL INFORMATION OF THE MSDS TO BE COMPLETED IN DETAIL)	EA	YES
0160215	ADHESIVE: TYPE: INSTANT; CONTAINER: BOTTLE PLASTIC 20 G; SUPPL P/N: RT300B; MATERIAL SAFETY DATA SHEETS WITH ENVIRONMENTAL INFORMATION IN THE 16 POINT FORMAT TO BE PROVIDED WITH EVERY DELIVERY AS REQUIRED BY THE OCCUPATIONAL HEALTH AND SAFETY ACT	EA	YES

**TECHNICAL EVALUATION CRITERIA: ESTABLISHMENT OF A 5 YEAR SUPPLY CONTRACT CIVIL CONSUMABLES AT LETHABO POWER STATION ON AN AS AND WHEN REQUIRED BASIS.**

Functionality Criteria	Maximum number of points percentages	Tenderers will be expected to score at least the minimum threshold per functional area to proceed to the next step
Technical	100%	The minimum threshold is 80%.

0160216	ADHESIVE: TYPE: INSTANT PLASTIC/VINYL; CONTAINER: BOTTLE PLASTIC 3 G; REFERENCE NO: PATTEX, UNK; SUPERBONDER; BLUE CONTAINERS; MATERIAL SAFETY DATA SHEETS WITH ENVIRONMENTAL INFORMATION IN THE 16 POINT FORMAT TO BE PROVIDED WITH EVERY DELIVERY AS REQUIRED BY THE OCCUPATIONAL HEALTH AND SAFETY ACT; THE FOLLOWING IS REQUIRED WITH EVERY DELIVERY; SHELF LIFE; DATE OF MANUFACTURE AND METHOD OF STORAGE	EA	YES
0160217	ADHESIVE: TYPE: SUPERGLUE; CONTAINER: TUBE 3 G; REFERENCE NO: 45, UNK; CLAUSE:1 (PLEASE ENSURE THAT SHELF LIFE HISTORY AND EXPIRY DATES ARE DISPLAYED 2) ITEMS SUBJECTED TO SHELF LIFE WILL NOT BE ACCEPTED TO ESKOM KENDAL P/S IF MORE THAN 20PCT OF THE SHELF LIFE HAS ALREADY EXPIRED PRIOR TO DELIVERY, MATERIAL SAFETY DATA SHEETS WITH ENVIRONMENTAL INFORMATION IN THE 16 POINT FORMAT TO BE PROVIDED WITH EVERY DELIVERY AS REQUIRED BY THE OCCUPATIONAL HEALTH AND SAFETY ACT	EA	YES
0160228	ADHESIVE: TYPE: CONTACT; CONTAINER: CAN 1 L; REFERENCE NO: 508, UNK; SUPPL P/N: 508; MATERIAL SAFETY DATA SHEETS WITH ENVIRONMENTAL INFORMATION IN THE 16 POINT FORMAT TO BE PROVIDED WITH EVERY DELIVERY AS REQUIRED BY THE OCCUPATIONAL HEALTH AND SAFETY ACT	EA	YES
0160232	ADHESIVE: TYPE: GASKET; CONTAINER: TUBE PLASTIC 300 ML; PHYSICAL FORM: LIQUID; SUPPL P/N: 593; SUPPL P/N: LOCTITE 593; REFERENCE NO: RTV; REFERENCE NO: 593; HYPERLOCK, MATERIAL SILICON, COLOR BLK, MATERIAL SAFETY DATA SHEETS WITH ENVIRONMENTAL INFORMATION IN THE 16 POINT FORMAT TO BE PROVIDED WITH EVERY DELIVERY AS REQUIRED BY THE OCCUPATIONAL HEALTH AND SAFETY ACT; LOCKTITE	EA	YES
0160233	COMPOUND, SEALING: TYPE: GASKET; COLOR: WHITE; CONTAINER: TUBE PLASTIC 310 ML; MATERIAL: SILICON; SUPPL P/N: 594; RUBBER ADHESIVE, TO FIT CAULKING GUN, CHEMICALS TO BE SUPPLIED WITH MSDS AND SECTION 12 (ECOLOGICAL INFORMATION OF THE MSDS TO BE COMPLETED IN DETAIL); LOCKTITE	EA	YES



**TECHNICAL EVALUATION CRITERIA: ESTABLISHMENT OF A 5 YEAR SUPPLY CONTRACT CIVIL CONSUMABLES AT LETHABO POWER STATION ON AN AS AND WHEN REQUIRED BASIS.**

<b>Functionality Criteria</b>	<b>Maximum number of points percentages</b>	<b>Tenderers will be expected to score at least the minimum threshold per functional area to proceed to the next step</b>
<b>Technical</b>	<b>100%</b>	<b>The minimum threshold is 80%.</b>

0160235	ADHESIVE: TYPE: SILICON; CONTAINER: TUBE PLASTIC 300 ML; PHYSICAL FORM: LIQUID; LOCTITE; TYPE 59575; CLEAR, TENSILE STRENGTH D/N 53504 S2 MPA -1.0; TEMPERATURE RATING BETWEEN -60 DEG C AND 230 DEG CELCIUS AND ALSO TO TENSILE AND COMPRESSIVE STRESSES; MATERIAL SAFETY DATA SHEETS WITH ENVIRONMENTAL INFORMATION IN THE 16 POINT FORMAT TO BE PROVIDED WITH EVERY DELIVERY AS REQUIRED BY THE OCCUPATIONAL HEALTH AND SAFETY ACT; THE FOLLOWING IS REQUIRED WITH EVERY DELIVERY; SHELF LIFE; DATE OF MANUFACTURE AND METHOD OF STORAGE	EA	YES
0160237	ADHESIVE: TYPE: SCREWLOCK; CONTAINER: BOTTLE PLASTIC 50 G; PHYSICAL FORM: LIQUID; SUPPL P/N: 230T; QUICKLOCK MATERIAL ANAEROBIC SEALANT; MATERIAL SAFETY DATA SHEETS WITH ENVIRONMENTAL INFORMATION IN THE 16 POINT FORMAT TO BE PROVIDED WITH EVERY DELIVERY AS REQUIRED BY THE OCCUPATIONAL HEALTH AND SAFETY ACT; THE FOLLOWING IS REQUIRED WITH EVERY DELIVERY; SHELF LIFE; DATE OF MANUFACTURE AND METHOD OF STORAGE	EA	YES
0160253	ADHESIVE: TYPE: CEMENT; CONTAINER: TUBE 100 ML; TANGIT SPECIAL FOR PVC PIPES; MATERIAL SAFETY DATA SHEETS WITH ENVIRONMENTAL INFORMATION IN THE 16 POINT FORMAT TO BE PROVIDED WITH EVERY DELIVERY AS REQUIRED BY THE OCCUPATIONAL HEALTH AND SAFETY ACT; THE FOLLOWING IS REQUIRED WITH EVERY DELIVERY; SHELF LIFE; DATE OF MANUFACTURE AND METHOD OF STORAGE	EA	YES
0160266	COMPOUND, SEALING: TYPE: GASKET/JOINT; COLOR: BLUE UNIVERSAL; CONTAINER: TUBE 100 G; MATERIAL: POLYESTER URETHANE; SUPPL P/N: PL32M; CLAUSE: 1: PLEASE ENSURE THAT SHELF LIFE HISTORY AND EXPIRY DATES ARE DISPLAYED, 2: ITEMS SUBJECTED TO SHELF LIFE WILL NOT BE ACCEPTED TO ESKOM IF MORE THAN 25 PCT OF THE SHELF LIFE HAS ALREADY EXPIRED PRIOR TO DELIVERY; MATERIAL SAFETY DATA SHEETS WITH ENVIRONMENTAL INFORMATION IN THE 16 POINT FORMAT TO BE PROVIDED WITH EVERY DELIVERY AS REQUIRED BY THE OCCUPATIONAL HEALTH AND SAFETY ACT	EA	YES

**TECHNICAL EVALUATION CRITERIA: ESTABLISHMENT OF A 5 YEAR SUPPLY CONTRACT CIVIL CONSUMABLES AT LETHABO POWER STATION ON AN AS AND WHEN REQUIRED BASIS.**

Functionality Criteria	Maximum number of points percentages	Tenderers will be expected to score at least the minimum threshold per functional area to proceed to the next step
Technical	100%	The minimum threshold is 80%.

0160269	ADHESIVE: TYPE: SUPERGLUE; CONTAINER: BOTTLE PLASTIC 20 G; REFERENCE NO: M5000, UNK; MATERIAL SAFETY DATA SHEETS WITH ENVIRONMENTAL INFORMATION IN THE 16 POINT FORMAT TO BE PROVIDED WITH EVERY DELIVERY AS REQUIRED BY THE OCCUPATIONAL HEALTH AND SAFETY ACT; THE FOLLOWING IS REQUIRED WITH EVERY DELIVERY; SHELF LIFE; DATE OF MANUFACTURE AND METHOD OF STORAGE	EA	YES
0160278	ADHESIVE: TYPE: SUPERGLUE; CONTAINER: BOTTLE 20 G; PHYSICAL FORM: LIQUID; SPECIFICATION: LOCTITE 401; MATERIAL: CYANOACRYLATE; SUPPL P/N: IS495	EA	YES
0160282	ADHESIVE: TYPE: QUICK SET; CONTAINER: PACK CARDED 15 ML; REFERENCE NO: 1-2-3, UNK; ONE TUBE RESIN AND ONE BOTTLE ACTIVATOR, MATERIAL SAFETY DATA SHEETS WITH ENVIRONMENTAL INFORMATION IN THE 16 POINT FORMAT TO BE PROVIDED WITH EVERY DELIVERY AS REQUIRED BY THE OCCUPATIONAL HEALTH AND SAFETY ACT; THE FOLLOWING IS REQUIRED WITH EVERY DELIVERY; SHELF LIFE; DATE OF MANUFACTURE AND METHOD OF STORAGE	EA	YES
0160283	ADHESIVE: TYPE: NUT LOCK; CONTAINER: BOTTLE PLASTIC 50 G; REFERENCE NO: 250 T, UNK; SUPPL P/N: 243; MEDIUM STRENGTH; HPL 051242; COLOUR BLUE; MATERIAL SAFETY DATA SHEETS WITH ENVIRONMENTAL INFORMATION IN THE 16 POINT FORMAT TO BE PROVIDED WITH EVERY DELIVERY AS REQUIRED BY THE OCCUPATIONAL HEALTH AND SAFETY ACT; THE FOLLOWING IS REQUIRED WITH EVERY DELIVERY; SHELF LIFE; DATE OF MANUFACTURE AND METHOD OF STORAGE; LOCKTITE	EA	YES
0160313	ADHESIVE: TYPE: EPOXY; CONTAINER: SET 1 KG; REFERENCE NO: 319TAQ, UNK; SUPPL P/N: IVORY319TAQ; QUICK SET, STRUCTURAL, RATIO BY VOLUME: 2 (EPOXY) TO 1 (ACTIVATOR), MATERIAL SAFETY DATA SHEETS WITH ENVIRONMENTAL INFORMATION IN THE 16 POINT FORMAT TO BE PROVIDED WITH EVERY DELIVERY AS REQUIRED BY THE OCCUPATIONAL HEALTH AND SAFETY ACT	EA	YES
0160354	BAG: TYPE: CARRY; DIMENSIONS: WD 280 X LG 420 MM; MATERIAL: PLASTIC; MICRON: 30 U	EA	Not required
0160355	BAG: TYPE: CARRY; DIMENSIONS: WD 240 X LG 400 MM; MATERIAL: PLASTIC; MICRON: 30 U	EA	Not required
0160356	BAG: TYPE: REFUSE; DIMENSIONS: WD 750 X LG 950 MM; COLOR: GREEN; MATERIAL: PLASTIC; MICRON: 40 U	EA	Not required

**TECHNICAL EVALUATION CRITERIA: ESTABLISHMENT OF A 5 YEAR SUPPLY CONTRACT CIVIL CONSUMABLES AT LETHABO POWER STATION ON AN AS AND WHEN REQUIRED BASIS.**

Functionality Criteria	Maximum number of points percentages	Tenderers will be expected to score at least the minimum threshold per functional area to proceed to the next step
Technical	100%	The minimum threshold is 80%.

0160385	BAG: TYPE: SELF SEALING; DIMENSIONS: WD 150 X LG 180 MM; MATERIAL: PLASTIC; NON-STATIC	EA	Not required
0161193	GREASE, INDUSTRIAL: TYPE: SILICON; CONTAINER: CAN 5 KG; REFERENCE NO: MS4, UNK; CHEMICALS TO BE SUPPLIED WITH MSDS AND SECTION 12 (ECOLOGICAL INFORMATION OF THE MSDS TO BE COMPLETED IN DETAIL)	KG	YES
0162909	TAPE, ADHESIVE: TYPE: CAUTION/WARNING; DIMENSIONS: WD 25 MM X LG 50 M; MATERIAL: PVC; COLOR: YELLOW/RED PRINT; PTW / IN FORCE	EA	YES
0186570	TILE: TYPE: REFRACTORY; DIMENSIONS: WD 100 X LG 150 X THK 6 MM; MATERIAL: CERAMIC ALUMINA HIGH; COLOR: WHITE; MODEL NO: MP92, UNK; SUPPL P/N: P26	EA	Not required
0186581	TILE: TYPE: REFRACTORY; DIMENSIONS: WD 50 X LG 150 X THK 6 MM; MATERIAL: ALUMINA 90 PCT; COLOR: WHITE; SUPPL P/N: P25	EA	Not required
0186582	BRICK, REFRACTORY: TYPE: ALUMINA HIGH; DIMENSIONS: WD 100 X LG 150 X THK 12 MM; SHAPE: TILE; MATERIAL: CERAMIC; REFERENCE NO: W01, UNK; CONTENT CERAMIC 90 PERCENT; GRADE 92 PCT HIGH ALUMINA; EA = ONE (1) BOX OF 30 TILES; WELD ON	EA	Not required
0186583	TILE: TYPE: REFRACTORY; DIMENSIONS: WD 50 X LG 150 X THK 12 MM; MATERIAL: CERAMIC ALUMINA HIGH; COLOR: WHITE; MODEL NO: MP92, UNK; SUPPL P/N: W06	EA	Not required
0186589	COMPOUND: TYPE: HI-TEMP TROWEL MIX; CONTAINER: 12 KG; SUPPL P/N: 9505-9918; CHEMICALS TO BE SUPPLIED WITH MSDS AND SECTION 12 (ECOLOGICAL INFORMATION OF THE MSDS TO BE COMPLETED IN DETAIL) WITH EVERY DELIVERY	EA	YES
0187596	BRICK, REFRACTORY: TYPE: ALUMINA HIGH CONTENT CERAMIC; DIMENSIONS: WD 25 X LG 150 X THK 6 MM; SHAPE: TILE; MATERIAL: ALUMINA CERAMIC 90 PCT PLUS; SUPPL P/N: P22; GRADE STANDARD WHITE; ESKOM'S SPECS ETS-0253	EA	Not required
0198234	BRICK, REFRACTORY: TYPE: ALUMINA HIGH CONTENT CERAMIC; DIMENSIONS: WD 50 X LG 150 X THK 25 MM; SHAPE: TILE; MATERIAL: ALUMINA CERAMIC 90 PCT PLUS; SUPPL P/N: P7; GRADE: KNOOP HARDNESS 10.8GPa	EA	Not required
0212152	BRUSH, WIRE: TYPE: FOUNDRY; TRIM LENGTH: 42 MM; DIMENSIONS: DIA 61 X LG 165 MM; MATERIAL: STL; REFERENCE NO: FO101, UNK; HT 58MM; NO HANDLE; FINE; FIVE ROWS; ACADEMY BRAND	EA	Not required

**TECHNICAL EVALUATION CRITERIA: ESTABLISHMENT OF A 5 YEAR SUPPLY CONTRACT CIVIL CONSUMABLES AT LETHABO POWER STATION ON AN AS AND WHEN REQUIRED BASIS.**

Functionality Criteria	Maximum number of points percentages	Tenderers will be expected to score at least the minimum threshold per functional area to proceed to the next step
Technical	100%	The minimum threshold is 80%.

0223825	COMPOUND, SEALING: TYPE: GASKET ELIMINATOR; CONTAINER: TUBE 45 G; NUMBER 2; FORM A GASKET; CHEMICALS TO BE SUPPLIED WITH MSDS AND SECTION 12 (ECOLOGICAL INFORMATION OF THE MSDS TO BE COMPLETED IN DETAIL); THE FOLLOWING IS REQUIRED WITH EVERY DELIVERY; SHELF LIFE; DATE OF MANUFACTURE AND METHOD OF STORAGE	EA	YES
0225061	TAPE, EMBOSsing: COLOR: BLACK ON YELLOW; NOMINAL WIDTH: 24 MM; NOMINAL OVERALL THICKNESS: 0.5 MM; NOMINAL LENGTH: 8 M; ATTACHMENT METHOD: ADHESIVE BACKING; MATERIAL: VINYL; TYPE: LAMINATED P TOUCH; SUPPL P/N: TZ-651; APPLCICATION: USED ON BROTHER LABEL PRINITNG MACHINE	EA	YES
0256819	PAINT, OIL: TYPE: EPOXY ENAMEL HI-CHEM; COLOR: GRAY LIGHT; CONTAINER: CAN 5 L; SPECIFIC USE: TOP QUALITY SURFACE COATING; REFERENCE NO: M388-0XXX; IT MUST COME WITH MIXTURE CODE C/A 39490, SUPPLY MATERIAL SAFETY DATA SHEET WITH EVERY DELIVERY	L	YES
0570082	BREATHER: TYPE: SILICA GEL, UNIT; MATERIAL: POLYPROPYLENE; DIMENSIONS: DIA 80 X LG 165 MM; CONNECTION: FNPT 1/4 IN; MANUF P/N: 1011388; CAPACITY: 155 CUBIC CM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	EA	YES
0584568	BROOM: TYPE: PLATFORM; DIMENSIONS: WD 95 X LG 450 MM; TRIM LENGTH: 3-1/4 IN; MATERIAL: FIBER SYNTHETIC SOFT	EA	Not required
0650045	ADHESIVE: TYPE: GLUE STICK; CONTAINER: TUBE 40 G	EA	YES
0650391	TAPE, ADHESIVE: TYPE: BUFF, SELLO; DIMENSIONS: WD 48 MM X LG 100 M; MATERIAL: VINYL; COLOR: CLEAR	EA	YES
0658101	CLAMP, HOSE: TYPE: HEAVY DUTY BOLTED; INSIDE DIAMETER: 31 MM; WIDTH: 19 MM; MATERIAL: STL; FASTENING DEVICE TYPE: BOLT; SET SCREW RECESSED INTO A ROUND TRUNNION FOR EASY INSTALLATION; DIAMETER RANGE: 31 TO 34 MM; MATERIAL: 400 SERIES STEEL BAND WITH ZINC PLATED CARBON STEEL SET SCREW AND TRUNNIONS	EA	Not required
0658118	CLAMP, HOSE: TYPE: HEAVY DUTY BOLTED; INSIDE DIAMETER: 37 MM; WIDTH: 19 MM; MATERIAL: SS; FASTENING DEVICE TYPE: BOLT; SET SCREW RECESSED INTO	EA	Not required

**TECHNICAL EVALUATION CRITERIA: ESTABLISHMENT OF A 5 YEAR SUPPLY CONTRACT CIVIL CONSUMABLES AT LETHABO POWER STATION ON AN AS AND WHEN REQUIRED BASIS.**

Functionality Criteria	Maximum number of points percentages	Tenderers will be expected to score at least the minimum threshold per functional area to proceed to the next step
Technical	100%	The minimum threshold is 80%.

	A ROUND TRUNNION FOR EASY INSTALLATION; DIAMETER RANGE: 37 TO 41MM		
0658320	CLAMP, HOSE: TYPE: HEAVY DUTY BOLTED; INSIDE DIAMETER: 238 MM; WIDTH: 32 MM; MATERIAL: STL; FASTENING DEVICE TYPE: BOLT; SET SCREW RECESSED INTO A ROUND TRUNNION FOR EASY INSTALLATION; DIAMETER RANGE: 238 TO 250MM; MODIFIED RANGE REQUIRED WITHOUT THE USE OF SPECIAL TOOLS: 228 TO 240MM; MATERIAL: 400 SERIES STEEL BAND WITH ZINC PLATED CARBON STEEL SET SCREW AND TRUNNIONS	EA	Not required
0658334	CLAMP, HOSE: TYPE: HEAVY DUTY BOLTED; INSIDE DIAMETER: 70 MM; WIDTH: 25 MM; MATERIAL: STL; SET SCREW RECESSED INTO A ROUND TRUNNION FOR EASY INSTALLATION; DIAMETER RANGE: 70 TO 78MM; MATERIAL: 400 SERIES STEEL BAND WITH ZINC PLATED CARBON STEEL SET SCREW AND TRUNNIONS	EA	Not required
0659593	TILE: TYPE: PRE ENGINEERED WELD ON HIGH ALUMINA CONTENT; DIMENSIONS: WD 100 X LG 150 X THK 25 MM; MATERIAL: MP92 ALUMINA OXIDE; COLOR: WHITE; CHAMFERED 45 DEG ON ONE SIDE OF THE 150MM SIDE OF THE TILE; LARGEST TILE AREA SHOULD BE ON THE BOTTOM OF THE TILE AFTER MOUNTING	EA	Not required
0659594	SEALANT: TYPE: HIGH TEMPERATURE; CONTAINER: BOX 24; MATERIAL: SILICON; COLOR: RED; TEMPERATURE RATING: 80 DEG C; APPLICATION: TILE INSTALLATION; PHYSICAL FORM: PASTE; ODOUR: ACETIC ACID; FLASH POINT: GREATER THAN 250 DEGREES CELSIUS; METHOD: CLOSED CUP; STORAGE: KEEP IN COOL DRY VENTILATED STORAGE AND IN CLOSED CONTAINERS	EA	YES
0659595	TILE: TYPE: HIGH ALUMINA CONTENT CERAMIC; DIMENSIONS: WD 50 X LG 100X THK 25 MM; MATERIAL: MP92 ALUMINA OXIDE; COLOR: WHITE; SUPPL P/N: P16; THE POROSITY SHALL BE 0.0 PERCENT; MAXIMUM USAGE TEMPERATURE 1500 DEG CELSIUS; WEAR RESISTANCE OF 0.10 G PER CUBIC CENTIMETER PER HOUR; GAS TIGHT PERMEABILITY AND THERMAL EXPANSION OF 7.29 10 - 16MM PER MM DEG CELSIUS 800 DEG CELSIUS	EA	YES
0668572	PAINT, WATER: COLOR: WHITE; CONTAINER: DRUM 20 L; PHYSICAL FORM: SUPER ACRYLIC; SPECIFIC USE: EXTERIOR/INTERIOR; REFERENCE NO: PLASCON WALL&ALL	EA	YES

**TECHNICAL EVALUATION CRITERIA: ESTABLISHMENT OF A 5 YEAR SUPPLY CONTRACT CIVIL CONSUMABLES AT LETHABO POWER STATION ON AN AS AND WHEN REQUIRED BASIS.**

Functionality Criteria	Maximum number of points percentages	Tenderers will be expected to score at least the minimum threshold per functional area to proceed to the next step
Technical	100%	The minimum threshold is 80%.