

	Addendum 01 to tender E3122GXGPLET LETHABO POWER STATION	Unique Identifier	240-55105891
		Revision	1
		Revision Date	Once off issue
		Group Technology & Commercial	

To: All Tenders

Date: 30 July 2026

From: Keneilwe Makoele

Enquiries:

Keneilwe Makoele
Tel +27 16 457 5294
Email: Makoelkm@eskom.co.za

DESCRIPTION: SUPPLY AND DELIVERY OF GASKETS FOR STOCK REPLENISHMENT FOR FIVE (5) YEARS AT LETHABO POWER STATION

TENDER: E3122GXGPLET

THIS SERVES TO INFORM YOU OF THE FOLLOWING CHANGES TO THE ABOVE-MENTIONED:

Closing date:

Previous

Closing date		31 July 2026 @10:00 AM
--------------	--	-------------------------------

Current

Closing date		18 August 2026 @ 10:00 AM
--------------	--	----------------------------------

Updated material list:

Material	Material Description	Base Unit of Measure	Price	Lead time
0001610	GASKET, PRE CUT: DIMENSIONS: ID 28 X OD 38 X THK 2 MM; TYPE: BURCKHARDT COMPRESSOR; MATERIAL: CU; SHAPE: RD; SUPPL P/N: 4652; REFERENCE NO: C2N2; C4N2F; C4N1R; FOR USE ON BURCHARD COMPRESSOR	EA		
0001629	GASKET, PRE CUT: DIMENSIONS: ID 84 X OD 113 X THK 0.5 MM; THKNESS: 0.5 MM; TYPE: BURCHARDT COMPRESSOR; MATERIAL: MONTANIT; SHAPE: RD; NOMINAL FLANGE SIZE: 1.5 MM; PCD: 10 MM; HOLES: 6; SUPPL P/N: 5468; REFERENCE NO: 5468; FOR BURCHARDT COMPRESSOR C4N2F	EA		

	Addendum 01 to tender E3122GXGPLET LETHABO POWER STATION	Unique Identifier	240-55105891
		Revision	1
		Revision Date	Once off issue
		Group Technology & Commercial	

0067446	GASKET, PRE CUT: DIMENSIONS: ID 22 X OD 35 X THK 0.5 MM; TYPE: VALVE; MATERIAL: ASB COMPRESSED; SHAPE: RD; SUPPL P/N: 2003719; FOR DEWRANCE 80NB VALVE	EA		
0094197	GASKET, PRE CUT: DIMENSIONS: ID 200 X OD 228 X THK 4 MM; TYPE: SWING COVER; MATERIAL: PAPER SS LINED; SHAPE: RD; REFERENCE NO: 152-1D; FOR SWING CHECK VALVE	EA		
0094421	GASKET, PRE CUT: DIMENSIONS: ID 102 X OD 122 MM; THKNESS: 0.5 MM; TYPE: COMPRESSOR; MATERIAL: ASB COMPRESSED; REFERENCE NO: 5467; SEAL RING, 122X122X0.5, USED ON THE SULZER BURCKHART COMPRESSOR TYPE C4N2F, MAIN EQUIPMENT 20KV BREAKER	EA		
0097252	GASKET, PRE CUT: DIMENSIONS: ID 90 X OD 110 X THK 2 MM; TYPE: GAS GENERATOR TANK; MATERIAL: RUBBER; SHAPE: RD; REFERENCE NO: 37Y112CM	EA		
0097305	GASKET, PRE CUT: DIMENSIONS: ID 25 X OD 64 X THK 1.5 MM; MATERIAL: FIBER COMPRESSED; SHAPE: RD; SUPPL P/N: 535743-04; REFERENCE NO: 535743-04; TYPE ALFA-LAVAL, FOR USE WITH OIL PURIFIER WHPX 410 TGD	EA		
0097396	GASKET, PRE CUT: DIMENSIONS: ID 89 X OD 105 X THK 0.55 MM; TYPE: OUTER LANCE TUBE; MATERIAL: STAINLESS STEEL; SHAPE: RD; SUPPL P/N: 305656-0117; REFERENCE NO: 305656-0117	EA		
0097412	GASKET, PRE CUT: DIMENSIONS: ID 21 X OD 26 X THK 1.5 MM; TYPE: COMPRESSOR; MATERIAL: CU; SHAPE: RD; SUPPL P/N: 027871; MODEL NO: SV125-40; REFERENCE NO: 027871; USED ON BECKER AND SOHNE COMPRESSOR	EA		
0097443	GASKET, PRE CUT: DIMENSIONS: ID 33 X OD 39 X THK 2 MM; TYPE: COMPRESSOR; MATERIAL: CU; SHAPE: RD; SUPPL P/N: 027960; REFERENCE NO: 027960; USED ON BECKER AND SOHNE COMPRESSOR TYPE SV40/125.	EA		

	Addendum 01 to tender E3122GXGPLET LETHABO POWER STATION	Unique Identifier	240-55105891
		Revision	1
		Revision Date	Once off issue
		Group Technology & Commercial	

0097498	GASKET, PRE CUT: DIMENSIONS: ID 20 X OD 28 X THK 1.5 MM; TYPE: BFPT OIL PURIFIER; MATERIAL: MONTANIT; SHAPE: RD; REFERENCE NO: 9281; 9281-00; FOR USE ON BFPT OIL PURIFIER MODEL: MAB 104 B	EA		
0097499	GASKET, PRE CUT: DIMENSIONS: ID 32 X OD 38 X THK 0.5 MM; TYPE: OIL PURIFIER; MATERIAL: PAPER; SHAPE: RD; SUPPL P/N: 33852; REFERENCE NO: 33852; USED ON THE OIL PURIFIER TYPE MAB209S	EA		
0097500	GASKET, PRE CUT: DIMENSIONS: ID 8 X OD 12 X THK 1 MM; TYPE: OIL PURIFIER; MATERIAL: FIBER COMPRESSED; SHAPE: RD; REFERENCE NO: 51836201	EA		
0097501	GASKET, PRE CUT: DIMENSIONS: ID 40 X OD 45 X THK 0.75 MM; TYPE: OIL PURIFIER; MATERIAL: FIBER COMPRESSED; SHAPE: RD; REFERENCE NO: 27H4A; USED ON OIL PURIFIER SEPARATOR TYPE MAB209S	EA		
0097502	GASKET, PRE CUT: DIMENSIONS: ID 42 X OD 52 X THK 1.5 MM; MATERIAL: FIBER COMPRESSED; SHAPE: RD; SUPPL P/N: 35607; REFERENCE NO: 35607; FOR USE WITH MAIN OIL PURIFIER MODEL MAB209	EA		
0097504	GASKET, PRE CUT: DIMENSIONS: ID 57 X OD 77 X THK 3 MM; TYPE: LUBE OIL PURIFIER; MATERIAL: CORK; SHAPE: RD; SUPPL P/N: 38967; REFERENCE NO: 38967; USED ON LUB-OIL PURIFIER WHPX 410 TGD	EA		
0097505	GASKET, PRE CUT: DIMENSIONS: WD 25 X LG 89 X THK 1 MM; TYPE: OIL PURIFIER; MATERIAL: RUBBER; SHAPE: RECT; REFERENCE NO: 526509-01	EA		
0097674	GASKET, PRE CUT: DIMENSIONS: ID 51 X OD 65 X THK 3 MM; TYPE: DOSING PUMP; MATERIAL: PTFE; SHAPE: RD; SUPPL P/N: JP81790; REFERENCE NO: JP81790; TYPE WALLACE AND TIERNAN, FOR USE WITH METERING DOSING PUMP TYPE G400V 7" MD SIMPLEX LIQUID END	EA		
0097678	GASKET, PRE CUT: DIMENSIONS: ID 52 X OD 64 X THK 2 MM; TYPE: CAUSTIC DOSING METERING PUMP LIQUID; MATERIAL: RUBBER; SHAPE: RD; SUPPL	EA		

	Addendum 01 to tender E3122GXGPLET LETHABO POWER STATION	Unique Identifier	240-55105891
		Revision	1
		Revision Date	Once off issue
		Group Technology & Commercial	

	P/N: JP81632; REFERENCE NO: JP81632; FOR USE ON CAUSTIC DOSING METERING PUMP LIQUID END TYPE G300V5MD SIMPLEX			
0097701	GASKET, PRE CUT: DIMENSIONS: ID 310 X OD 340 X THK 30 MM; TYPE: BONNET SEAL; MATERIAL: GRAPHITE; SHAPE: RD; SUPPL P/N: 051342000; 45 DEGREES TAPERING INSIDE	EA		
0097709	GASKET, PRE CUT: DIMENSIONS: ID 610 X OD 638 X THK 8 MM; TYPE: OUTER CASE; MATERIAL: RUBBER; SHAPE: RD; FLAT	EA		
0097712	GASKET, PRE CUT: DIMENSIONS: ID 495 X OD 580 X THK 3 MM; TYPE: TUBE BUNDLE; MATERIAL: ASB COMPRESSED; SHAPE: SQ; FOR H2 COOLER TUBE NEST	EA		
0097754	GASKET, SPIRAL WOUND: STYLE: METAFLEX; INNER RING ID: 32 MM; FILLER OD: 40 MM; FILLER ID: 32 MM; OUTER RING OD: 40 MM; PRESSURE RATING: CI 2500; FILLER MATERIAL: ASB; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; THKNESS: 3.5 MM; METAFLEX; SIZE 38MM OD BY 32MM ID BY 2MM WIDTH	EA		
0097755	GASKET, SPIRAL WOUND: INNER RING ID 62 MM; OUTER RING OD 78 MM; FILLER MATERIAL: GRAPHITE; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; METAFLEX; WID 4 MM; SIZE THK 3 MM	EA		
0097781	GASKET, PRE CUT: DIMENSIONS: ID 65 X OD 90 X THK 2 MM; TYPE: VALVE; MATERIAL: ASB COMPRESSED; SHAPE: RD; REFERENCE NO: 7520-038; USED ON DELAS CHECK VALVE	EA		
0097782	GASKET, PRE CUT: DIMENSIONS: ID 160 X OD 220 X THK 0.2 MM; TYPE: OIL CLOTH; MATERIAL: FIBER BRAIDED; SHAPE: RD	EA		
0097797	GASKET, PRE CUT: DIMENSIONS: ID 412 X OD 476 X THK 3 MM; TYPE: GENERATOR STATOR COOLER; MATERIAL: FIBER COMPRESSED; SHAPE: RD; FOR USE ON COOLER ON GENERATOR STATOR	EA		
0097811	GASKET, PRE CUT: DIMENSIONS: ID 685 X OD 750 X THK 4 MM; TYPE: TURBINE; MATERIAL: ASB COMPRESSED; SHAPE:	EA		

	Addendum 01 to tender E3122GXGPLET LETHABO POWER STATION	Unique Identifier	240-55105891
		Revision	1
		Revision Date	Once off issue
		Group Technology & Commercial	

	RD; REFERENCE NO: 8500-001			
0097812	GASKET, PRE CUT: DIMENSIONS: ID 406 X OD 422 X THK 4 MM; TYPE: TURBINE; MATERIAL: ASB COMPRESSED; SHAPE: RD; FLAT	EA		
0097859	GASKET, PRE CUT: DIMENSIONS: ID 39 X OD 81 X THK 15 MM; TYPE: TURBINE; MATERIAL: RUBBER; SHAPE: RD; REFERENCE NO: 38-128092; GENERATOR	EA		
0097862	GASKET, SPIRAL WOUND: STYLE: F; INNER RING ID: 213 MM; OUTER RING OD: 258 MM; FILLER MATERIAL: ASB; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; SIZE THK 4 MM; 231 X 258 X 4.0	EA		
0097863	GASKET, SPIRAL WOUND: INNER RING ID: 595 MM; OUTER RING OD: 640 MM; FILLER MATERIAL: ASB; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; METAFLEX; SIZE: 4MM THK	EA		
0097864	GASKET, SPIRAL WOUND: INNER RING ID: 535 MM; OUTER RING OD: 575 MM; FILLER MATERIAL: GRAPHITE; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; METAFLEX; SIZE: 4MM THK	EA		
0098029	GASKET, PRE CUT: DIMENSIONS: ID 50 X OD 80 X THK 2 MM; TYPE: TURBINE; MATERIAL: GRAPHITE; SHAPE: RD; REFERENCE NO: 282-19	EA		
0098030	GASKET, PRE CUT: DIMENSIONS: ID 110 X OD 140 X THK 2 MM; TYPE: TURBINE; MATERIAL: GRAPHITE; SHAPE: RD; REFERENCE NO: DIN3754JTCEG1	EA		
0098033	GASKET, PRE CUT: DIMENSIONS: ID 22 X OD 57 X THK 2 MM; TYPE: TURBINE; MATERIAL: MONTANIT; SHAPE: RD; REFERENCE NO: 100-63-92	EA		
0098034	GASKET, PRE CUT: DIMENSIONS: ID 77 X OD 138 X THK 2 MM; TYPE: TURBINE; MATERIAL: MONTANIT; SHAPE: RD; REFERENCE NO: M77	EA		
0098035	GASKET, PRE CUT: DIMENSIONS: ID 83 X OD 133 X THK 2 MM; TYPE: TURBINE; MATERIAL: RUBBER; SHAPE: RD; REFERENCE NO: 100-117	EA		

	Addendum 01 to tender E3122GXGPLET LETHABO POWER STATION	Unique Identifier	240-55105891
		Revision	1
		Revision Date	Once off issue
		Group Technology & Commercial	

0098036	GASKET, PRE CUT: DIMENSIONS: ID 29 X OD 68 X THK 2 MM; TYPE: TURBINE; MATERIAL: RUBBER; SHAPE: RD; REFERENCE NO: 100-121	EA		
0098042	GASKET, PRE CUT: DIMENSIONS: ID 65 X OD 105 X THK 0.5 MM; TYPE: PUMP; MATERIAL: MONTANIT; SHAPE: RD; USED ON LUBRI PUMP	EA		
0098258	GASKET, SPIRAL WOUND: STYLE: GF; INNER RING ID: 118 MM; OUTER RING OD: 140 MM; FILLER MATERIAL: GRAPHITE; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; METAFLEX CF 140 X 18 X 90; SS ASBESTOS; SIZE: THK 5 MM	EA		
0098260	GASKET, PRE CUT: DIMENSIONS: ID 86 X OD 104 X THK 3 MM; TYPE: CHAMBER; MATERIAL: SS GR 316 GRAPHITE FILLED 98 PCT PURE; SHAPE: RD; DRAWING NO: 20.58/2011/12 ESK REV 1; ESK 20.58/2011/12 REV 1; REFERENCE NO: SCHEDULE: 5.01.22.12; 1904646816; USED ON PNEUMATIC REGULATOR SERIE 12800	EA		
0098470	GASKET, PRE CUT: DIMENSIONS: ID 20.5 X OD 32 X THK 3 MM; TYPE: OIL PURIFIER; MATERIAL: CORK; SHAPE: RD; SUPPL P/N: 8392-00; MODEL NO: MAB103B; REFERENCE NO: 8392-00; 8392; FOR PORT USE ON OIL PURIFIER	EA		
0098471	GASKET, PRE CUT: DIMENSIONS: ID 20 X OD 30 X THK 2 MM; TYPE: OIL PURIFIER; MATERIAL: FIBER COMPRESSED; SHAPE: RD; SUPPL P/N: 35002-00; REFERENCE NO: 35002-00; FOR PORT ALFA LAVAL PURIFIER MAB 103B	EA		
0098474	GASKET, PRE CUT: DIMENSIONS: ID 138 X OD 175 X THK 1 MM; TYPE: OIL PURIFIER; MATERIAL: PAPER; SHAPE: RD; SUPPL P/N: 62812-00; REFERENCE NO: 62812-00; FOR USE WITH OIL PURIFIER MODEL MAB 103B	EA		
0098476	GASKET, PRE CUT: DIMENSIONS: ID 23 X OD 30 X THK 2 MM; TYPE: BFPT OIL PURIFIER; MATERIAL: VELLUMOID; SHAPE: RD; SUPPL P/N: 546229-35; REFERENCE NO: 546229-35; FOR USE WITH BFPT OIL PURIFIER MODEL MAB 103B	EA		

	Addendum 01 to tender E3122GXGPLET LETHABO POWER STATION	Unique Identifier	240-55105891
		Revision	1
		Revision Date	Once off issue
		Group Technology & Commercial	

0098582	GASKET, PRE CUT: DIMENSIONS: ID 26 X OD 38 X THK 0.75 MM; TYPE: VALVE; MATERIAL: GRAPHITE; SHAPE: RD; DEWR VALVE 65NB	EA		
0099471	GASKET, PRE CUT: DIMENSIONS: ID 38 X OD 50 X THK 3 MM; TYPE: BLIND FLANGE; MATERIAL: STL; SHAPE: RD; REFERENCE NO: 190-450-8816; MAKE: MASONEILAN; FOR LEVEL REGULATOR ON GEN 687 MVA	EA		
0099472	GASKET, PRE CUT: DIMENSIONS: ID 74 X OD 87 X THK 3 MM; TYPE: LEVEL REGULATOR; MATERIAL: STL; REFERENCE NO: 190-471-0816; TOP CONNECTION; ON GEN 687 MVA	EA		
0099489	GASKET, PRE CUT: DIMENSIONS: ID 29.5 X OD 39.5 X THK 1.5 MM; TYPE: LEVEL CONTROLLER; MATERIAL: STL; SHAPE: RD; SUPPL P/N: NAJ206HR; FOR LEVEL CONTROLLERS ON GEN 687 MVA; TYPE MIP	EA		
0099491	GASKET, PRE CUT: DIMENSIONS: ID 102 X OD 113 X THK 1.5 MM; TYPE: LEVEL CONTROLLER; MATERIAL: STAINLESS STEEL; SHAPE: RD; SUPPL P/N: NAJ208HR; USED ON ARMCO TANK FOR LEVEL CONTROLLERS ON GEN 687 MVA, TYPE MIP	EA		
0099492	GASKET, PRE CUT: DIMENSIONS: ID 102 X OD 113 X THK 1.5 MM; TYPE: LEVEL CONTROLLER; MATERIAL: STAINLESS STEEL; SHAPE: RD; SUPPL P/N: NAJ209AL; FOR LEVEL CONTROLLERS ON GEN 687 MV A, TYPE MIP	EA		
0100019	GASKET, PRE CUT: DIMENSIONS: WD 62 MM X LG 3 M X THK 3.5 MM; TYPE: MANHOLE; MATERIAL: RUBBER COTTON BRAIDED; SUPPL P/N: FAB-CB-89101; ON BOILERS; SHAPE STRIP	EA		
0100194	GASKET, PRE CUT: DIMENSIONS: ID 25 X OD 58 X THK 0.2 MM; TYPE: PUMP; MATERIAL: PAPER; SHAPE: RD; SUPPL P/N: JPR82241; REFERENCE NO: JPR82241; USED ON WALLACE AND TIERNAN HYDRAZINE AMMONIA PUMP TWIN G50V24PX15	EA		

	Addendum 01 to tender E3122GXGPLET LETHABO POWER STATION	Unique Identifier	240-55105891
		Revision	1
		Revision Date	Once off issue
		Group Technology & Commercial	

0100371	GASKET, SPIRAL WOUND: INNER RING ID: 116.5 MM; OUTER RING OD: 133 MM; FILLER MATERIAL: GRAPHITE; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; REFERENCE NO: 319588-1127; 304; METAFLEX; ID 98.5 MM X OD 16.5 MM X WD 4.5 MM; SIZE: THK 3.5 MM	EA		
0100911	GASKET SET: TYPE: DELUGE VALVE 100 MM; APPLICATION: FIRE PROTECTION DELUGE VALVES; SETS OF RUBBER FACE CLACK GASKETS; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	EA		
0100912	GASKET SET: TYPE: DELUGE VALVE 150 MM; APPLICATION: FIRE PROTECTION DELUGE VALVES; OF RUBBER FACE AND CLACK; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	EA		
0101082	GASKET, PRE CUT: DIMENSIONS: DIA 185 X THK 2 MM; TYPE: ACTUATOR; MATERIAL: TEFLON; SHAPE: RD; REFERENCE NO: 7360-006; 7160-006; USED ON HP EMERGENCY STOP VALVE	EA		
0101146	GASKET, PRE CUT: DIMENSIONS: DIA 310 X THK 2 MM; TYPE: PUMP COVER; MATERIAL: ASB COMPRESSED; SHAPE: RD; REFERENCE NO: WKL150/1; USED ON THE MAIN OIL PUMP	EA		
0101171	GASKET, PRE CUT: DIMENSIONS: ID 1.25 M X OD 1.305 M X THK 2 MM; TYPE: CROSSOVER PIPE; MATERIAL: IT300; SHAPE: RD; DRAWING NO: MAN MAIN B42.81600-0039 REV 1; MAN SUB F42.81665-0360 REV 1; REFERENCE NO: 8160-087; SEALING; USED ON THE CROSSOVER PIPES IP-LP DN200	EA		
0101281	GASKET, PRE CUT: DIMENSIONS: ID 55 X OD 65 X THK 0.25 MM; TYPE: OIL PURIFIER; MATERIAL: PAPER; SHAPE: RD; SUPPL P/N: 14161-00; USED ON THE OIL PURIFIER SEPARATOR TYPE MAB103B	EA		

	Addendum 01 to tender E3122GXGPLET LETHABO POWER STATION	Unique Identifier	240-55105891
		Revision	1
		Revision Date	Once off issue
		Group Technology & Commercial	

0101282	GASKET, PRE CUT: DIMENSIONS: ID 19.5 X OD 30 X THK 2 MM; TYPE: OIL PURIFIER; MATERIAL: FIBER COMPRESSED; SHAPE: RD; SUPPL P/N: 37402-00; REFERENCE NO: 37402-00; USED ON THE OIL PURIFIER SEPARATOR TYPE MAB 103B; CHEMECALs TO BE SUPPLIED WITH MSDS AND SECTION 12 (ECOLOGICAL INFORMATION OF THE MSDS TO BE COMPLETED IN DETAIL)	EA		
0101283	GASKET, PRE CUT: DIMENSIONS: ID 147.5 X OD 190 X THK 0.8 MM; TYPE: OIL PURIFIER; MATERIAL: FIBER COMPRESSED; SHAPE: RD; SUPPL P/N: 516842-01; REFERENCE NO: 516842-01; HEIGHT ADJUSTING RING USED ON THE OIL PURIFIER SEPERATOR TYPE MAB 209S	EA		
0101314	GASKET, SPIRAL WOUND: INNER RING ID: 15 MM; OUTER RING OD: 30 MM; FILLER MATERIAL: GRAPHITE; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; METAFLEX; SIZE: 4.5 MM THK	EA		
0101343	GASKET, SPIRAL WOUND: INNER RING ID: 36 MM; OUTER RING OD: 70 MM; FILLER MATERIAL: GRAPHITE; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; METAFLEX, SS OUTER RING AND ASBESTOS, ID 36MM BY 52MM OD, STEEL RING 4.5MM THK, USED ON THE SP DRAIN PUMP ON THE TURBINES; SIZE: 4.5MM THK	EA		
0101344	GASKET, SPIRAL WOUND: STYLE: METAFLEX; INNER RING ID: 60 MM; FILLER OD: 102 MM; FILLER ID: 60 MM; OUTER RING OD: 102 MM; PRESSURE RATING: CI 2500; FILLER MATERIAL: EXFOLIATED GRAPHITE; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; THKNESS: 4.5 MM; STAINLESS STEEL OUTER RING AND GRAPHITE; SIZE 60MM ID BY 96MM OD; USED ON THE LP DRAIN PUMP ON THE TURBINE	EA		
0101370	GASKET, PRE CUT: DIMENSIONS: ID 8.5 X OD 51 X THK 8 MM; TYPE: HOSE; MATERIAL: NEOPRENE; SHAPE: RD; SUPPL P/N: HX14N-10; REFERENCE NO: HX14N-10; REPLACEMENT FOR FREON GASSES ON	EA		

	Addendum 01 to tender E3122GXGPLET LETHABO POWER STATION	Unique Identifier	240-55105891
		Revision	1
		Revision Date	Once off issue
		Group Technology & Commercial	

	CHARGING HOSES			
0101440	GASKET, SPIRAL WOUND: STYLE: METAFLEX; INNER RING ID: 74 MM; FILLER OD: 112 MM; FILLER ID: 74 MM; OUTER RING OD: 112 MM; PRESSURE RATING: CI 2500; FILLER MATERIAL: GRAPHITE; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; THKNESS: 4.5 MM; 3MM WIRE ON ID	EA		
0101441	GASKET, SPIRAL WOUND: STYLE: SPIRAL; INNER RING ID: 110.5 MM; FILLER OD: 129 MM; FILLER ID: 110.5 MM; OUTER RING OD: 129 MM; PRESSURE RATING: CI 2500; FILLER MATERIAL: GRAPHITE; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; THKNESS: 3 MM	EA		
0101442	GASKET, SPIRAL WOUND: STYLE: METAFLEX; INNER RING ID: 100 MM; FILLER OD: 127 MM; FILLER ID: 100 MM; OUTER RING OD: 127 MM; PRESSURE RATING: CL 2500; FILLER MATERIAL: GRAPHITE; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; THKNESS: 3 MM; WITH 3MM WIRE ON THE I.D; SIZE: 4.5MM THK	EA		
0101447	GASKET, SPIRAL WOUND: STYLE: METAFLEX; INNER RING ID: 60 MM; FILLER OD: 86 MM; FILLER ID: 60 MM; OUTER RING OD: 86 MM; PRESSURE RATING: CI 2500; FILLER MATERIAL: GRAPHITE; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; THKNESS: 5.3 MM; 3MM WIRE ON ID	EA		
0101448	GASKET, SPIRAL WOUND: STYLE: METAFLEX; INNER RING ID: 47 MM; FILLER OD: 66.5 MM; FILLER ID: 47 MM; OUTER RING OD: 66.5 MM; PRESSURE RATING: CI 2500; FILLER MATERIAL: GRAPHITE; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; THKNESS: 5.3 MM; 3 MM WIRE ON THE ID	EA		
0101449	GASKET, SPIRAL WOUND: STYLE: METAFLEX; INNER RING ID: 222 MM; FILLER OD: 320 MM; FILLER ID: 222 MM; OUTER RING OD: 320 MM; PRESSURE RATING: CI	EA		

	Addendum 01 to tender E3122GXGPLET LETHABO POWER STATION	Unique Identifier	240-55105891
		Revision	1
		Revision Date	Once off issue
		Group Technology & Commercial	

	2500; FILLER MATERIAL: GRAPHITE; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; THKNESS: 4.5 MM; SUPPL P/N: 8X600 AP1601			
0101587	GASKET SET: TYPE: WORKING OIL COOLER; APPLICATION: GEARBOX; QUANTITY: 6; MODEL NO: R18KGS; REFERENCE NO: 104-695-000-225; CONSISTING OF: 2 O-RINGS ID 377 X WD 10MM ARTICAL NO 119-023-061-251; 2 GASKETS ID 166 X OD 218 X THK 3 MM KLING 100 ARTICAL NO 119-023-061-250; 1 GASKET ID 390 X OD 490 X THK 1.5 MM KLING 100 ARTICAL NO 119-023-061-248 AND 1 SPLIT GASKET ID 390 X OD 490 X THK 1.5 MM KLING 100 ARTICAL NO 119- 023-061-397; FOR USE ON VOITH TURBO GEAR; ITEMS TO BE INDIVIDUALLY PACKED IN A BLACK SEALED POLYURETHANE BAG AND KITS AS A SET. FOR SHELF LIFE CONROL, EACH BAG TO BE CLEARLY MARKED WITH CONTENTS, QUANTITY, BATCH NUMBER AND CURE DATE.; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	EA		
0101588	GASKET SET: TYPE: LUBE OIL COOLER; APPLICATION: GEARBOX; QUANTITY: 6; MODEL NO: R18KGS; REFERENCE NO: 104- 695-000-227; CONSISTING OF; 2 OFF O- RING 300 X 10 ARTICLE NUMBER 119-023- 061-252; 2 OFF GASKETS ID 166 X 218 OD X THK 3 MM KLING 100 ARTICLE NUMBER 119-023-061-250; 2 OFF GASKETS 330 ID X 380 OD X 1.5 MM KLING 100 ARTICLE NUMBER 119-023-061-249; FOR USE ON VOITH TURBO COUPLING; ITEMS TO BE INDIVIDUALLY PACKED IN A BLACK SEALED POLYURETHANE BAG AND KITS AS A SET. FOR SHELF LIFE CONROL, EACH BAG TO BE CLEARLY MARKED WITH CONTENTS, QUANTITY, BATCH NUMBER AND CURE DATE.; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE	EA		

	Addendum 01 to tender E3122GXGPLET LETHABO POWER STATION	Unique Identifier	240-55105891
		Revision	1
		Revision Date	Once off issue
		Group Technology & Commercial	

	CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).			
0102172	GASKET, PRE CUT: DIMENSIONS: ID 70 X OD 80 X THK 10 MM; TYPE: VALVE; MATERIAL: GRAPHITE; SHAPE: RD; REFERENCE NO: NW21-24S120/S121; STYLE V901/I7	EA		
0102174	GASKET, PRE CUT: DIMENSIONS: ID 55 X OD 70 X THK 2 MM; TYPE: VALVE CAP; MATERIAL: FIBER CU LINED; SHAPE: RD; CAP F FIG 470 25MM VALVE CAP	EA		
0102175	GASKET, PRE CUT: DIMENSIONS: ID 39 X OD 47 X THK 2 MM; TYPE: CAP; MATERIAL: FIBER CU LINED; SHAPE: RD; REFERENCE NO: 38; FOR 38 MM VALVE	EA		
0102185	GASKET, PRE CUT: DIMENSIONS: WD 16 X LG 52 X THK 1 MM; MATERIAL: RUBBER; REFERENCE NO: 2715; 051675001660; TYPE VALVE, SHAPE STRIP	EA		
0102195	GASKET, PRE CUT: DIMENSIONS: WD 58 X LG 156 X THK 4 MM; TYPE: PLUG CONNECTOR; MATERIAL: RUBBER; SHAPE: RECT; REFERENCE NO: C74106-A114-C649	EA		
0102198	GASKET SET: SUPPL P/N: F74106-E115-D2; KIT; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	EA		
0104131	GASKET SET: APPLICATION: COMPRESSOR; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	EA		
0104488	GASKET, PRE CUT: DIMENSIONS: ID 18 X OD 30 X THK 1 MM; TYPE: PURIFIER; MATERIAL: CORK; SHAPE: RD; REFERENCE NO: 37402; FOR MAB103B-24 OIL SEPARATOR	EA		
0105780	GASKET, PRE CUT: DIMENSIONS: ID 70 X	EA		

	Addendum 01 to tender E3122GXGPLET LETHABO POWER STATION	Unique Identifier	240-55105891
		Revision	1
		Revision Date	Once off issue
		Group Technology & Commercial	

	OD 105 X THK 0.75 MM; TYPE: VALVE ACTUATOR; MATERIAL: CORK; SHAPE: RD; REFERENCE NO: C74106-A116-C807			
0105785	GASKET, PRE CUT: DIMENSIONS: ID 50 X OD 80 X THK 0.5 MM; TYPE: VALVE ACTUATOR MOTOR; MATERIAL: PAPER; SHAPE: RD; REFERENCE NO: C74106-A116-C805	EA		
0105786	GASKET, PRE CUT: DIMENSIONS: ID 60 X OD 90 X THK 0.75 MM; TYPE: VALVE ACTUATOR; MATERIAL: CORK; SHAPE: RD; REFERENCE NO: C74106-A116-C806	EA		
0105798	GASKET, PRE CUT: DIMENSIONS: ID 13 X OD 18 X THK 6 MM; TYPE: PUMP; MATERIAL: RUBBER; SHAPE: RD; REFERENCE NO: MN10716P14	EA		
0105823	GASKET, PRE CUT: DIMENSIONS: ID 87 X OD 105 X THK 12 MM; MATERIAL: RUBBER; SHAPE: RD; REFERENCE NO: 65247; FOR MAIN OIL PURIFIER MODEL MAB 209	EA		
0106368	GASKET, PRE CUT: DIMENSIONS: ID 14 X OD 38 X THK 1.5 MM; MATERIAL: FIBER COMPRESSED; SHAPE: RD; SUPPL P/N: 535743-02; REFERENCE NO: 535743-02; USED ON OIL PURIFIER FEED PUMP TYPE MAB 103B	EA		
0107816	GASKET, SPIRAL WOUND: STYLE: SPIRAL; INNER RING ID: 59 MM; FILLER OD: 320 MM; FILLER ID: 222 MM; OUTER RING OD: 74 MM; PRESSURE RATING: CI 2500; FILLER MATERIAL: ASB; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; THKNESS: 4.5 MM; METAFLEX; SIZE: THK 4 MM	EA		
0107825	GASKET, SPIRAL WOUND: STYLE: R; INNER RING ID: 240 MM; FILLER OD: 255 MM; FILLER ID: 240 MM; OUTER RING OD: 255 MM; PRESSURE RATING: CI 2500; FILLER MATERIAL: ASB; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; THKNESS: 5 MM; METAFLEX; SIZE: 5MM THK	EA		
0151061	GASKET, PRE CUT: DIMENSIONS: ID 50 X OD 104 X THK 0.75 MM; TYPE: END PLATE; MATERIAL: RUBBER; SHAPE: RD; REFERENCE NO: 15588-00; 1720A	EA		

	Addendum 01 to tender E3122GXGPLET LETHABO POWER STATION	Unique Identifier	240-55105891
		Revision	1
		Revision Date	Once off issue
		Group Technology & Commercial	

0154592	GASKET, PRE CUT: DIMENSIONS: ID 10 X OD 16 X THK 2 MM; TYPE: CAM PROFILE; MATERIAL: STL; SHAPE: RD; SUPPL P/N: 7MF90076CA	EA		
0154602	GASKET, PRE CUT: DIMENSIONS: ID 17.8 X OD 23.8 X THK 3 MM; TYPE: VALVE; MATERIAL: PTFE; SHAPE: RD; DIN 19213; FOR SHUT-OFF VALVE SIEMENS TYPE 7MY1590-OFA; SOLID TYPE	EA		
0154624	GASKET, PRE CUT: DIMENSIONS: ID 20 X OD 25 X THK 7 MM; TYPE: TEMPERATURE GAUGE BLOCK; MATERIAL: RUBBER; SHAPE: RD; FOR TPB/T8S TEMPERATURE GAUGE	EA		
0154644	GASKET, PRE CUT: DIMENSIONS: ID 92 X OD 108 X THK 2 MM; TYPE: WINDOW; MATERIAL: RUBBER; SHAPE: RD; REFERENCE NO: FGBX100; F PBB/DBB/DOB	EA		
0154645	GASKET, PRE CUT: DIMENSIONS: ID 145 X OD 165 X THK 2 MM; TYPE: WINDOW; MATERIAL: RUBBER; SHAPE: RD; SUPPL P/N: FGB-150	EA		
0180461	GASKET, SPIRAL WOUND: INNER RING ID: 610 MM; OUTER RING OD: 664 MM; PRESSURE RATING: 10 MPA; FILLER MATERIAL: GRAPHITE; WINDING MATERIAL: SS GR 304; SHAPE: ROUND; SUPPL P/N: 119-023-062-125; REFERENCE NO: 119-023-062-125; MILD STEEL OUTER RING, SIZE SEALING ELEMENT 610MM X 640MM, IZE STEEL OUTER RING 640MM X 664MM, THKNESS SEALING ELEMENT 4.5MM, THKNESS STEEL OUTER RING 3MM, TO BE INDIVIDUALLY PACKED TO PREVENT DAMAGE	EA		
0180462	GASKET, SPIRAL WOUND: INNER RING ID: 717 MM; OUTER RING OD: 773 MM; PRESSURE RATING: 10 MPA; FILLER MATERIAL: GRAPHITE; WINDING MATERIAL: SS GR 304; SHAPE: ROUND; REFERENCE NO: 119-023-062-127; 4.5MM THK, MILD STEEL OUTER RING, SIZE SEALING ELEMENT 717MM X 747MM, SIZE STEEL OUTER RING 747MM X 773MM, THKNESS STEEL OUTER RING 3MM, TO BE INDIVIDUALLY PACKED TO PREVENT	EA		

	Addendum 01 to tender E3122GXGPLET LETHABO POWER STATION	Unique Identifier	240-55105891
		Revision	1
		Revision Date	Once off issue
		Group Technology & Commercial	

	DAMAGE			
0180463	GASKET, SPIRAL WOUND: INNER RING ID: 920 MM; OUTER RING OD: 991 MM; PRESSURE RATING: 10 MPA; FILLER MATERIAL: GRAPHITE; WINDING MATERIAL: SS GR 304; SHAPE: ROUND; SUPPL P/N: 119-023-062-126; REFERENCE NO: 119-023-062-126; 4.5MM THK, MILD STEEL OUTER RING, SIZE SEALING ELEMENT 920MM X 960MM, SIZE STEEL OUTER RING 960MM X 991MM, THKNESS STEEL OUTER RING 3MM, TO BE INDIVIDUALLY PACKED TO PREVENT DAMAGE	EA		
0180464	GASKET, SPIRAL WOUND: INNER RING ID: 920 MM; OUTER RING OD: 1.06 M; PRESSURE RATING: 10 MPA; FILLER MATERIAL: GRAPHITE; WINDING MATERIAL: SS GR 304; SHAPE: ROUND; SUPPL P/N: 119-023-062-128; 4.5MM THK, MILD STEEL OUTER RING, SIZE SEALING ELEMENT 920MM X 970MM, SIZE STEEL OUTER RING 970MM X 1006MM, THKNESS STEEL OUTER RING 3MM, TO BE INDIVIDUALLY PACKED TO PREVENT DAMAGE	EA		
0215033	GASKET SET: TYPE: VOLUTE COVER; APPLICATION: PUMP; SUPPL P/N: P2000-289ZZ; IN 4 DOVE TAILED SEGMENTS, PCD 1600, THKNESS 0.8MM, FOR 1600 CW PUMP; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	EA		
0565418	GASKET, PRE CUT: DIMENSIONS: ID 1.11M X OD 1.234M X THK 3MM; THKNESS: 3 MM; TYPE: GEN HYDROGEN; MATERIAL: NITRILE; SHAPE: ROUND; RUBBER HARDNESS: 65 - 75 SHORE; > 10 MOHMS @ 500V DC; MATERIAL TYPE UNIQUE IDENTIFICATION: HE 370 NON CONDUCTIVE; MOULD IDENTIFIER:	EA		

	Addendum 01 to tender E3122GXGPLET LETHABO POWER STATION	Unique Identifier	240-55105891
		Revision	1
		Revision Date	Once off issue
		Group Technology & Commercial	

	GASKET C.193.8546 3; PACKAGING: SEALED UV RESISTANT BAG; PACKAGING BAG TO HAVE THE DETAILED INFORMATION ON: MANUFACTURING DATE; EXPIRY DATE; LIFE EXPECTANCY; EACH DELIVERY OF THE GASKET TO BE SUPPLIED TO LETHABO WITH ITS MATERIAL CERTIFICATE; STORE UNDER ROOM TEMPERATURE			
0565419	GASKET, PRE CUT: DIMENSIONS: ID 1.039M X OD 1.264M X THK 3MM; THKNESS: 3 MM; TYPE: GEN HYDROGEN; MATERIAL: NITRILE; SHAPE: ROUND; RUBBER HARDNESS; 65 - 75 SHORE; > 10 MOHMS @ 500V DC; MATERIAL TYPE UNIQUE IDENTIFICATION: HE 370 NON CONDUCTIVE; MOULD IDENTIFIER: GASKET C.193.8546 3; PACKAGING: SEALED UV RESISTANT BAG; PACKAGING BAG TO HAVE THE DETAILED INFORMATION ON: MANUFACTURING DATE; EXPIRY DATE; LIFE EXPECTANCY; EACH DELIVERY OF THE GASKET TO BE SUPPLIED TO LETHABO WITH ITS MATERIAL CERTIFICATE; STORE UNDER ROOM TEMPERATURE	EA		
0565420	GASKET, PRE CUT: DIMENSIONS: ID 1.044M X OD 1.164M X THK 3MM; THKNESS: 3 MM; TYPE: GEN HYDROGEN; MATERIAL: NITRILE; SHAPE: ROUND; RUBBER HARDNESS; 65 - 75 SHORE; > 10 MOHMS @ 500V DC; MATERIAL TYPE UNIQUE IDENTIFICATION: HE 370 NON CONDUCTIVE; MOULD IDENTIFIER: GASKET C.193.8546 3; PACKAGING: SEALED UV RESISTANT BAG; PACKAGING BAG TO HAVE THE DETAILED INFORMATION ON: MANUFACTURING DATE; EXPIRY DATE; LIFE EXPECTANCY; EACH DELIVERY OF THE GASKET TO BE SUPPLIED TO LETHABO WITH ITS MATERIAL CERTIFICATE; STORE UNDER ROOM TEMPERATURE	EA		

	Addendum 01 to tender E3122GXGPLET LETHABO POWER STATION	Unique Identifier	240-55105891
		Revision	1
		Revision Date	Once off issue
		Group Technology & Commercial	

0565421	GASKET, PRE CUT: DIMENSIONS: ID 1.04M X OD 1.225M X THK 3MM; TYPE: GEN HYDROGEN; MATERIAL: NITRILE; SHAPE: ROUND; RUBBER HARDNESS; 65 - 75 SHORE; > 10 MOHMS @ 500V DC; MATERIAL TYPE UNIQUE IDENTIFICATION: HE 370 NON CONDUCTIVE; MOULD IDENTIFIER: GASKET C.193.8546 3; PACKAGING: SEALED UV RESISTANT BAG; PACKAGING BAG TO HAVE THE DETAILED INFORMATION ON: MANUFACTURING DATE; EXPIRY DATE; LIFE EXPECTANCY; EACH DELIVERY OF THE GASKET TO BE SUPPLIED TO LETHABO WITH ITS MATERIAL CERTIFICATE; STORE UNDER ROOM TEMPERATURE	EA		
0565422	GASKET, PRE CUT: DIMENSIONS: ID 925 MM X OD 1.094 M X THK 3 MM; THKNESS: 3 MM; TYPE: GEN HYDROGEN; MATERIAL: NITRILE; SHAPE: ROUND; RUBBER HARDNESS; 65 - 75 SHORE; > 10 MOHMS @ 500V DC; MATERIAL TYPE UNIQUE IDENTIFICATION: HE 370 NON CONDUCTIVE; MOULD IDENTIFIER: GASKET C.193.8546 3; PACKAGING: SEALED UV RESISTANT BAG; PACKAGING BAG TO HAVE THE DETAILED INFORMATION ON: MANUFACTURING DATE; EXPIRY DATE; LIFE EXPECTANCY; EACH DELIVERY OF THE GASKET TO BE SUPPLIED TO LETHABO WITH ITS MATERIAL CERTIFICATE; STORE UNDER ROOM TEMPERATURE	EA		
0609967	GASKET: TYPE: RING; DIMENSIONS: ID 35 X OD 70 X THK 3 MM; MATERIAL: TO-PCHEM 2003; SHAPE: ROUND; APPLICATION: PIPE FLANGE; REFERENCE NO: K10415; PN 16; 25 NB	EA		
0609968	GASKET: TYPE: T/C POCKET FLANGE; DIMENSIONS: ID 35 X OD 70 X THK 3 MM; MATERIAL: GRAPHITE SEALING; SS FOIL HIGH INTEGRITY REINFORCED; SHAPE: ROUND; REFERENCE NO: K110815; 25 NB; PN 16	EA		

	Addendum 01 to tender E3122GXGPLET LETHABO POWER STATION	Unique Identifier	240-55105891
		Revision	1
		Revision Date	Once off issue
		Group Technology & Commercial	

0609972	GASKET: TYPE: SIGHT GLASS LARGE FLANGE; DIMENSIONS: ID 275 X OD 405 X THK 3 MM; MATERIAL: GRAPHITE SEALING; SS FOIL HIGH INTEGRITY REINFORCED; HOLES: (12) DIA 10 MM; SHAPE: ROUND; REFERENCE NO: K10415; 355MM PCD	EA		
0682133	GASKET: TYPE: RING; DIMENSIONS: ID 800 X OD 830 X THK 3 MM; MATERIAL: COPPER ANNEALED; APPLICATION: COLD RH NRV TOP COVER	EA		
0682135	GASKET: TYPE: RING; DIMENSIONS: ID 490 X OD 560 X THK 3 MM; MATERIAL: REINFORCED GRAPHITE SIGRAFLEX HOCHDRUCK; APPLICATION: EXT 4B NRV TOP COVER; OT 300.7 DEG CELCIUS	EA		
0682141	GASKET: TYPE: RING; DIMENSIONS: ID 560 X OD 630 X THK 3 MM; MATERIAL: REINFORCED GRAPHITE SIGRAFLEX HOCHDRUCK; APPLICATION: EXT 3 AND 4 NRV TOP COVER; OT 300.7 DEG CELCIUS	EA		
0682142	GASKET: TYPE: RING; DIMENSIONS: ID 400 X OD 460 X THK 3 MM; MATERIAL: REINFORCED GRAPHITE SIGRAFLEX HOCHDRUCK; APPLICATION: EXT 5 NRV TOP COVER; 443.6 DEG CELCIUS	EA		
0703917	GASKET SET: TYPE: HYDROGEN; QUANTITY: 5; COLOR: BLACK; SHAPE: ROUND; MATERIAL: PUR BUNA N; COMPOUND DESCRIPTION: HE 370 (NON CONDUCTIVE); SHORE HARDNESS: 65-75; INSULATION BREAKDOWN (MEGGER): > 10 MO AT 500V AT 25 PCT MATERIAL COMPRESSION; COMPRISING: GASKET ID 925 MM X OD 1.094 M X THK 3 MM; GASKET ID 1.039 M X OD 1.264 M X THK 3 MM; GASKET ID 1.04 M X OD 1.225 M X THK 3 MM; GASKET ID 1.11 M X OD 1.234 M X THK 3 MM; GASKET ID 1.044 M X OD 1.164 M X THK 3 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	EA		

	Addendum 01 to tender E3122GXGPLET LETHABO POWER STATION	Unique Identifier	240-55105891
		Revision	1
		Revision Date	Once off issue
		Group Technology & Commercial	

0703918	GASKET SET: TYPE: SPIRAL WOUND; APPLICATION: FLANGE SEALING; QUANTITY: 130; SIZE RANGE (50) ID 71 X OD 89 X THK 3 MM; (20) ID 52 X OD 65 X THK 3 MM; (20) ID 43 X OD 57 X THK 3 MM; (20) ID 26 X OD 37 X THK 3 MM; (20) ID 63 X OD 79 X THK 3 MM; MATERIAL: STAINLESS STEEL; SHAPE: ROUND; METAFLEX; SPECIFICATION ASME B16.5, BS 1560, ASME B16.47 SERIES A (MSS-SP44), ASME B16.47 SERIES B (API 605), BS EN 1092 (BS 4504); PLUS DIN, JIS, NF; CONCENTRIC; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	EA		
0703920	GASKET SET: TYPE: SHEET; APPLICATION: BLANKING STATOR COOLANT PIPES; QUANTITY: 2; COMPRISING: GASKET SQ 1 M X THK 1 MM, GASKET SQ 1 M X THK 2 MM; MATERIAL: PTFE; SHAPE: SQUARE; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	EA		
0052144	GASKET, PRE CUT: DIMENSIONS: ID 90 X OD 105 X THK 1.5 MM; TYPE: DISTANCE; MATERIAL: SS GR 316; SHAPE: RD; SUPPL P/N: 304634-0117; FOR USE WITH DIAMOND IK110 AIR HEATER SOOT BLOWER	EA		
0094197	GASKET, PRE CUT: DIMENSIONS: ID 200 X OD 228 X THK 4 MM; TYPE: SWING COVER; MATERIAL: PAPER SS LINED; SHAPE: RD; REFERENCE NO: 152-1D; FOR SWING CHECK VALVE	EA		
0094421	GASKET, PRE CUT: DIMENSIONS: ID 102 X OD 122 MM; THICKNESS: 0.5 MM; TYPE: COMPRESSOR; MATERIAL: ASB COMPRESSED; REFERENCE NO: 5467; SEAL RING, 122X122X0.5, USED ON THE SULZER BURCKHART COMPRESSOR TYPE C4N2F, MAIN EQUIPMENT 20KV BREAKER	EA		
0097252	GASKET, PRE CUT: DIMENSIONS: ID 90 X OD 110 X THK 2 MM; TYPE: GAS GENERATOR TANK; MATERIAL: RUBBER; SHAPE: RD; REFERENCE NO: 37Y112CM	EA		

	Addendum 01 to tender E3122GXGPLET LETHABO POWER STATION	Unique Identifier	240-55105891
		Revision	1
		Revision Date	Once off issue
		Group Technology & Commercial	

0097396	GASKET, PRE CUT: DIMENSIONS: ID 89 X OD 105 X THK 0.55 MM; TYPE: OUTER LANCE TUBE; MATERIAL: STAINLESS STEEL; SHAPE: RD; SUPPL P/N: 305656-0117; REFERENCE NO: 305656-0117	EA		
0097674	GASKET, PRE CUT: DIMENSIONS: ID 51 X OD 65 X THK 3 MM; TYPE: DOSING PUMP; MATERIAL: PTFE; SHAPE: RD; SUPPL P/N: JP81790; REFERENCE NO: JP81790; TYPE WALLACE AND TIERNAN, FOR USE WITH METERING DOSING PUMP TYPE G400V 7" MD SIMPLEX LIQUID END	EA		
0097712	GASKET, PRE CUT: DIMENSIONS: ID 495 X OD 580 X THK 3 MM; TYPE: TUBE BUNDLE; MATERIAL: ASB COMPRESSED; SHAPE: SQ; FOR H2 COOLER TUBE NEST	EA		
0097748	GASKET, PRE CUT: DIMENSIONS: ID 695 X OD 780 X THK 2 MM; TYPE: RUPTURE DIAPHRAGM; MATERIAL: IT400; SHAPE: RD; PRESSURE RATING: PN6; FOR USE ON TURBINE 700PN6 DIN2699	EA		
0097761	GASKET, PRE CUT: DIMENSIONS: ID 138 X OD 198 X THK 0.85 MM; TYPE: OIL PUMP; MATERIAL: PAPER; SHAPE: RD; ITEM 104/18-29	EA		
0097785	GASKET, PRE CUT: DIMENSIONS: ID 186 X OD 225 X THK 3 MM; TYPE: OIL PUMP; MATERIAL: EUROPIL; SHAPE: RD; FLAT	EA		
0097797	GASKET, PRE CUT: DIMENSIONS: ID 412 X OD 476 X THK 3 MM; TYPE: GENERATOR STATOR COOLER; MATERIAL: FIBER COMPRESSED; SHAPE: RD; FOR USE ON COOLER ON GENERATOR STATOR	EA		
0097811	GASKET, PRE CUT: DIMENSIONS: ID 685 X OD 750 X THK 4 MM; TYPE: TURBINE; MATERIAL: ASB COMPRESSED; SHAPE: RD; REFERENCE NO: 8500-001	EA		
0097812	GASKET, PRE CUT: DIMENSIONS: ID 406 X OD 422 X THK 4 MM; TYPE: TURBINE; MATERIAL: ASB COMPRESSED; SHAPE: RD; FLAT	EA		
0097859	GASKET, PRE CUT: DIMENSIONS: ID 39 X OD 81 X THK 15 MM; TYPE: TURBINE; MATERIAL: RUBBER; SHAPE: RD; REFERENCE NO: 38-128092; GENERATOR	EA		

	Addendum 01 to tender E3122GXGPLET LETHABO POWER STATION	Unique Identifier	240-55105891
		Revision	1
		Revision Date	Once off issue
		Group Technology & Commercial	

0097863	GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 595 MM; OUTER RING OUTSIDE DIAMETER: 640 MM; FILLER MATERIAL: ASB; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; METAFLEX; SIZE: 4MM THK	EA		
0097864	GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 535 MM; OUTER RING OUTSIDE DIAMETER: 575 MM; FILLER MATERIAL: GRAPHITE; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; METAFLEX; SIZE: 4MM THK	EA		
0098029	GASKET, PRE CUT: DIMENSIONS: ID 50 X OD 80 X THK 2 MM; TYPE: TURBINE; MATERIAL: GRAPHITE; SHAPE: RD; REFERENCE NO: 282-19	EA		
0098030	GASKET, PRE CUT: DIMENSIONS: ID 110 X OD 140 X THK 2 MM; TYPE: TURBINE; MATERIAL: GRAPHITE; SHAPE: RD; REFERENCE NO: DIN3754JTCEG1	EA		
0098033	GASKET, PRE CUT: DIMENSIONS: ID 22 X OD 57 X THK 2 MM; TYPE: TURBINE; MATERIAL: MONTANIT; SHAPE: RD; REFERENCE NO: 100-63-92	EA		
0098035	GASKET, PRE CUT: DIMENSIONS: ID 83 X OD 133 X THK 2 MM; TYPE: TURBINE; MATERIAL: RUBBER; SHAPE: RD; REFERENCE NO: 100-117	EA		
0098036	GASKET, PRE CUT: DIMENSIONS: ID 29 X OD 68 X THK 2 MM; TYPE: TURBINE; MATERIAL: RUBBER; SHAPE: RD; REFERENCE NO: 100-121	EA		
0098042	GASKET, PRE CUT: DIMENSIONS: ID 65 X OD 105 X THK 0.5 MM; TYPE: PUMP; MATERIAL: MONTANIT; SHAPE: RD; USED ON LUBRI PUMP	EA		
0098260	GASKET, PRE CUT: DIMENSIONS: ID 86 X OD 104 X THK 3 MM; TYPE: CHAMBER; MATERIAL: SS GR 316 GRAPHITE FILLED 98 PCT PURE; SHAPE: RD; DRAWING NO: 20.58/2011/12 ESK REV 1; ESK 20.58/2011/12 REV 1; REFERENCE NO: SCHEDULE: 5.01.22.12; 1904646816; USED ON PNEUMATIC REGULATOR SERIE 12800	EA		

	Addendum 01 to tender E3122GXGPLET LETHABO POWER STATION	Unique Identifier	240-55105891
		Revision	1
		Revision Date	Once off issue
		Group Technology & Commercial	

0098294	GASKET SET: TYPE: SUPPORT INSULATOR; REFERENCE NO: LSI1-1-6D; LS1/1-6D; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	EA		
0099471	GASKET, PRE CUT: DIMENSIONS: ID 38 X OD 50 X THK 3 MM; TYPE: BLIND FLANGE; MATERIAL: STL; SHAPE: RD; REFERENCE NO: 190-450-8816; MAKE: MASONEILAN; FOR LEVEL REGULATOR ON GEN 687 MVA	EA		
0099489	GASKET, PRE CUT: DIMENSIONS: ID 29.5 X OD 39.5 X THK 1.5 MM; TYPE: LEVEL CONTROLLER; MATERIAL: STL; SHAPE: RD; SUPPL P/N: NAJ206HR; FOR LEVEL CONTROLLERS ON GEN 687 MVA; TYPE MIP	EA		
0099491	GASKET, PRE CUT: DIMENSIONS: ID 102 X OD 113 X THK 1.5 MM; TYPE: LEVEL CONTROLLER; MATERIAL: STAINLESS STEEL; SHAPE: RD; SUPPL P/N: NAJ208HR; USED ON ARMCO TANK FOR LEVEL CONTROLLERS ON GEN 687 MVA, TYPE MIP	EA		
0099492	GASKET, PRE CUT: DIMENSIONS: ID 102 X OD 113 X THK 1.5 MM; TYPE: LEVEL CONTROLLER; MATERIAL: STAINLESS STEEL; SHAPE: RD; SUPPL P/N: NAJ209AL; FOR LEVEL CONTROLLERS ON GEN 687 MV A, TYPE MIP	EA		
0100019	GASKET, PRE CUT: DIMENSIONS: WD 62 MM X LG 3 M X THK 3.5 MM; TYPE: MANHOLE; MATERIAL: RUBBER COTTON BRAIDED; SUPPL P/N: FAB-CB-89101; ON BOILERS; SHAPE STRIP	EA		
0100194	GASKET, PRE CUT: DIMENSIONS: ID 25 X OD 58 X THK 0.2 MM; TYPE: PUMP; MATERIAL: PAPER; SHAPE: RD; SUPPL P/N: JPR82241; REFERENCE NO: JPR82241; USED ON WALLACE AND TIERNAN HYDRAZINE AMMONIA PUMP TWIN G50V24PX15	EA		
0100311	GASKET SET: TYPE: HEAT EXCHANGER; APPLICATION: FEEDHEATING PLANT; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING	EA		

	Addendum 01 to tender E3122GXGPLET LETHABO POWER STATION	Unique Identifier	240-55105891
		Revision	1
		Revision Date	Once off issue
		Group Technology & Commercial	

	AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).			
0100371	GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 116.5 MM; OUTER RING OUTSIDE DIAMETER: 133 MM; FILLER MATERIAL: GRAPHITE; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; REFERENCE NO: 319588-1127; 304; METAFLEX; ID 98.5 MM X OD 16.5 MM X WD 4.5 MM; SIZE: THK 3.5 MM	EA		
0100725	GASKET SET: TYPE: VALVE ACTUATOR BLOCK; APPLICATION: STOP HYDRAULIC NUMBER; REFERENCE NO: 269646; 9(A-B-C-D); 12-16; 269646 TAG 2A-7A-8A; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	EA		
0100911	GASKET SET: TYPE: DELUGE VALVE 100 MM; APPLICATION: FIRE PROTECTION DELUGE VALVES; SETS OF RUBBER FACE CLACK GASKETS; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	EA		
0100912	GASKET SET: TYPE: DELUGE VALVE 150 MM; APPLICATION: FIRE PROTECTION DELUGE VALVES; OF RUBBER FACE AND CLACK; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	EA		
0101082	GASKET, PRE CUT: DIMENSIONS: DIA 185 X THK 2 MM; TYPE: ACTUATOR; MATERIAL: TEFLON; SHAPE: RD; REFERENCE NO: 7360-006; 7160-006; USED ON HP EMERGENCY STOP VALVE	EA		
0101146	GASKET, PRE CUT: DIMENSIONS: DIA 310 X THK 2 MM; TYPE: PUMP COVER; MATERIAL: ASB COMPRESSED; SHAPE: RD; REFERENCE NO: WKL150/1; USED ON THE MAIN OIL PUMP	EA		

	Addendum 01 to tender E3122GXGPLET LETHABO POWER STATION	Unique Identifier	240-55105891
		Revision	1
		Revision Date	Once off issue
		Group Technology & Commercial	

0101171	GASKET, PRE CUT: DIMENSIONS: ID 1.25 M X OD 1.305 M X THK 2 MM; TYPE: CROSSOVER PIPE; MATERIAL: IT300; SHAPE: RD; DRAWING NO: MAN MAIN B42.81600-0039 REV 1; MAN SUB F42.81665-0360 REV 1; REFERENCE NO: 8160-087; SEALING; USED ON THE CROSSOVER PIPES IP-LP DN200	EA		
0101314	GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 15 MM; OUTER RING OUTSIDE DIAMETER: 30 MM; FILLER MATERIAL: GRAPHITE; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; METAFLEX; SIZE: 4.5 MM THK	EA		
0101321	SHEET: MATERIAL: RUBBER NATURAL HESSIAN REINFORCED; DIMENSIONS: WD 1.2 M X LG 10 M X THK 6 MM; TYPE: INSERTION	M		
0101343	GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 36 MM; OUTER RING OUTSIDE DIAMETER: 70 MM; FILLER MATERIAL: GRAPHITE; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; METAFLEX, SS OUTER RING AND ASBESTOS, ID 36MM BY 52MM OD, STEEL RING 4.5MM THK, USED ON THE SP DRAIN PUMP ON THE TURBINES; SIZE: 4.5MM THK	EA		
0101344	GASKET, SPIRAL WOUND: STYLE: METAFLEX; INNER RING INSIDE DIAMETER: 60 MM; FILLER OUTSIDE DIAMETER: 102 MM; FILLER INSIDE DIAMETER: 60 MM; OUTER RING OUTSIDE DIAMETER: 102 MM; PRESSURE RATING: CI 2500; FILLER MATERIAL: EXFOLIATED GRAPHITE; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; THICKNESS: 4.5 MM; STAINLESS STEEL OUTER RING AND GRAPHITE; SIZE 60MM ID BY 96MM OD; USED ON THE LP DRAIN PUMP ON THE TURBINE	EA		
0101442	GASKET, SPIRAL WOUND: STYLE: METAFLEX; INNER RING INSIDE DIAMETER: 100 MM; FILLER OUTSIDE DIAMETER: 127 MM; FILLER INSIDE DIAMETER: 100 MM; OUTER RING OUTSIDE DIAMETER: 127 MM; PRESSURE RATING: CL 2500; FILLER	EA		

	Addendum 01 to tender E3122GXGPLET LETHABO POWER STATION	Unique Identifier	240-55105891
		Revision	1
		Revision Date	Once off issue
		Group Technology & Commercial	

	MATERIAL: GRAPHITE; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; THICKNESS: 3 MM; WITH 3MM WIRE ON THE I.D; SIZE: 4.5MM THK			
0101533	GASKET, PRE CUT: DIMENSIONS: ID 1.08 X OD 1.13 X THK 2 MM; TYPE: GASKET OIL COOLER; MATERIAL: CENTELLEN; SHAPE: RD; OEM P/N: 3582-001, OEM: GE STEAM POWER SERVICE	EA		
0101534	GASKET, PRE CUT: DIMENSIONS: ID 1.08 M X OD 1.13 M X THK 3 MM; TYPE: GASKET OIL COOLER; MATERIAL: CENTELLEN; SHAPE: RD; OEM P/N: 3582-002, OEM: GE STEAM POWER SERVICE	EA		
0102198	GASKET SET: SUPPL P/N: F74106-E115-D2; KIT; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	EA		
0102210	GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 35 MM; OUTER RING OUTSIDE DIAMETER: 70 MM; PRESSURE RATING: PN40; FILLER MATERIAL: ASB; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; REFERENCE NO: FJ2; FLEXAJOINT; DN25; SIZE: THK 3.5 MM	EA		
0154602	GASKET, PRE CUT: DIMENSIONS: ID 17.8 X OD 23.8 X THK 3 MM; TYPE: VALVE; MATERIAL: PTFE; SHAPE: RD; DIN 19213; FOR SHUT-OFF VALVE SIEMENS TYPE 7MY1590-OFA; SOLID TYPE	EA		
0180467	GASKET, PRE CUT: TYPE: SEAT RING; SUPPL P/N: 19A-2542X-012.3X2; FOR EHS FISHER VALVE	EA		
0180470	GASKET, PRE CUT: TYPE: CAGE; SUPPL P/N: 26A-5318X-012.3X2; USED FOR EHS FISHER VALVE	EA		
0211974	SHEET, GASKET: THICKNESS: 3 MM; LENGTH: 2 M; WIDTH: 1.5 M; MATERIAL: GRAPHITE FLEXIBLE; SUPPL P/N: 2000; KLINGER; COLOUR BLACK; MAX TEMPERATURE 500 DEG C; WORKING TEMP 300 DEG C; MAX PRESSURE 100 BAR TO 10 MPA; WORKING PRESSURE 40 BAR TO 4 MPA; APPLICATIONS: STEAM FRF	EA		

	Addendum 01 to tender E3122GXGPLET LETHABO POWER STATION	Unique Identifier	240-55105891
		Revision	1
		Revision Date	Once off issue
		Group Technology & Commercial	

0211975	SHEET, GASKET: THICKNESS: 3 MM; LENGTH: 2 M; WIDTH: 1.5 M; MATERIAL: GLASS FIBER/NBR; REFERENCE NO: C4430; KLINGERSIL; COLOUR ONE SIDE GREEN ONE SIDE WHITE; MAX TEMPERATURE 250 DEG C; MAX PRESSURE: 45 BAR; CLASSIFICATION ACC. TO BS 7531:2006: GRADE AX; ASME GASKET FACTORS: M≤1.6, Y≤20 MPA; TENDER RETURNABLES: GASKET SPECIFICATION SHEET	EA		
0211976	SHEET, GASKET: THICKNESS: 2 MM; LENGTH: 2 M; WIDTH: 1.5 M; MATERIAL: GLASS FIBER/NBR; REFERENCE NO: C4430; COLOUR ONE SIDE GREEN ONE SIDE WHITE; MAX TEMPERATURE 250 DEG C; MAX PRESSURE 45 BAR; CLASSIFICATION ACC. TO BS 7531:2006: GRADE AX; ASME GASKET FACTORS: M≤1.6, Y≤20 MPA; TENDER RETURNABLES: GASKET SPECIFICATION SHEET	EA		
0211978	SHEET, GASKET: THICKNESS: 3 MM; LENGTH: 2 M; WIDTH: 1.5 M; MATERIAL: GRAPHITE W/WIRE MESH; SUPPL P/N: 2000W; KLINGER; COLOUR BLACK; MAX TEMPERATURE 500 DEG C; MAX TEMP WITH STEAM 300 DEG C; WORKING TEMP 300 DEG C; MAX PRESSURE 100 BAR TO 10 MPA; WORKING PRESSURE 40 BAR TO 4 MPA; APPLICATIONS STEAM FRF	EA		
0211979	SHEET, GASKET: THICKNESS: 2 MM; LENGTH: 2 M; WIDTH: 1.5 M; MATERIAL: ARAMID FIBER/NBR; SUPPL P/N: C4400; COLOUR GREEN; MAX TEMP 300 DEG C; WORKING TEMP -20 TO 150 DEG C; MAX PRESSURE 50 BAR TO 5 MPA; WORKING PRESSURE 40 BAR TO 4 MPA; APPLICATIONS WATER, GASES, OILS, NO FRF/FUELS	EA		
0212001	SHEET, GASKET: THICKNESS: 2 MM; LENGTH: 2 M; WIDTH: 1.5 M; MATERIAL: ARAMID FIBER NBR BONDED; SUPPL P/N: C4324; KLINGERSIL; COLOUR GREEN; MAX TEMPERATURE 300 DEG C; WORKING TEMP 150 DEG C; MAX PRESSURE 50 BAR TO 5 MPA; WORKING PRESSURE 40 BAR	EA		

	Addendum 01 to tender E3122GXGPLET LETHABO POWER STATION	Unique Identifier	240-55105891
		Revision	1
		Revision Date	Once off issue
		Group Technology & Commercial	

	TO 4 MPA; APPLICATIONS STATOR COOLANT; HOT AND COLD POTABLE WATER, FUELS, HYDROCARBONS, LOW PRESSURE STEAM AND WATER AND HYDRAULIC OIL, NO FRF			
0212002	SHEET, GASKET: THICKNESS: 2 MM; LENGTH: 2 M; WIDTH: 1.5 M; MATERIAL: GRAPHITE/FIBER SYNTHETIC; REFERENCE NO: KLINGER TOP GRAPH; KLINGER; COLOUR BLACK; MAX TEMPERATURE 500 DEG C; WORKING TEMP 300 DEG C; MAX PRESSURE 100 BAR TO 10 MPA; WORKING PRESSURE 40 BAR TO 4 MPA; APPLICATIONS STEAM FRF	EA		
0212003	SHEET, GASKET: THICKNESS: 1 MM; LENGTH: 1.6 M; WIDTH: 1.5 M; MATERIAL: ARAMID FIBER NBR BONDED; SUPPL P/N: NA1002; COLOUR GREEN; MAX TEMPERATURE 400 DEG C; WORKING TEMP 200 DEG C; MAX PRESSURE 110 BAR TO 11 MPA; WORKING PRESSURE 80 BAR TO 8 MPA; APPLICATIONS WATER, POTABLE WATER, SATURATED STEAM, DILUTED ACIDS, ALCOHOLS, DILUTED ALKALIS, NO SULPHUR, HYDRAULIC OILS, NO FRF, MINERAL OILS AND GASES	EA		
0215033	GASKET SET: TYPE: VOLUTE COVER; APPLICATION: PUMP; SUPPL P/N: P2000-289ZZ; IN 4 DOVE TAILED SEGMENTS, PCD 1600, THICKNESS 0.8MM, FOR 1600 CW PUMP; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	EA		
0231316	GASKET, PRE CUT: TYPE: COVER PLATE; SUPPL P/N: 323447-2128; SOOTBLOWERS	EA		
0231317	GASKET, PRE CUT: TYPE: COVER PLATE; SUPPL P/N: 339258-2122; SOOTBLOWERS	EA		
0231318	GASKET, PRE CUT: TYPE: BEARING RETAINER; SUPPL P/N: 323449-2126; SOOTBLOWERS	EA		
0231319	GASKET, PRE CUT: TYPE: HOUSING; SUPPL P/N: 323446-2129; SOOTBLOWERS	EA		
0528418	GASKET: TYPE: HOCHDRUCK; DIMENSIONS: SQ 570 X WD 60 THK 3 MM; MATERIAL: V30011Z31; SPECIFICATION:	EA		

	Addendum 01 to tender E3122GXGPLET LETHABO POWER STATION	Unique Identifier	240-55105891
		Revision	1
		Revision Date	Once off issue
		Group Technology & Commercial	

	DIN 28091-GR-11-I-5-CR			
0565418	GASKET, PRE CUT: DIMENSIONS: ID 1.11M X OD 1.234M X THK 3MM; THICKNESS: 3 MM; TYPE: GEN HYDROGEN; MATERIAL: NITRILE; SHAPE: ROUND; RUBBER HARDNESS; 65 - 75 SHORE; > 10 MOHMS @ 500V DC; MATERIAL TYPE UNIQUE IDENTIFICATION: HE 370 NON CONDUCTIVE; MOULD IDENTIFIER: GASKET C.193.8546 3; PACKAGING: SEALED UV RESISTANT BAG; PACKAGING BAG TO HAVE THE DETAILED INFORMATION ON: MANUFACTURING DATE; EXPIRY DATE; LIFE EXPECTANCY; EACH DELIVERY OF THE GASKET TO BE SUPPLIED TO LETHABO WITH ITS MATERIAL CERTIFICATE; STORE UNDER ROOM TEMPERATURE	EA		
0565419	GASKET, PRE CUT: DIMENSIONS: ID 1.039M X OD 1.264M X THK 3MM; THICKNESS: 3 MM; TYPE: GEN HYDROGEN; MATERIAL: NITRILE; SHAPE: ROUND; RUBBER HARDNESS; 65 - 75 SHORE; > 10 MOHMS @ 500V DC; MATERIAL TYPE UNIQUE IDENTIFICATION: HE 370 NON CONDUCTIVE; MOULD IDENTIFIER: GASKET C.193.8546 3; PACKAGING: SEALED UV RESISTANT BAG; PACKAGING BAG TO HAVE THE DETAILED INFORMATION ON: MANUFACTURING DATE; EXPIRY DATE; LIFE EXPECTANCY; EACH DELIVERY OF THE GASKET TO BE SUPPLIED TO LETHABO WITH ITS MATERIAL CERTIFICATE; STORE UNDER ROOM TEMPERATURE	EA		
0565420	GASKET, PRE CUT: DIMENSIONS: ID 1.044M X OD 1.164M X THK 3MM; THICKNESS: 3 MM; TYPE: GEN HYDROGEN; MATERIAL: NITRILE; SHAPE: ROUND; RUBBER HARDNESS; 65 - 75 SHORE; > 10 MOHMS @ 500V DC; MATERIAL TYPE UNIQUE IDENTIFICATION: HE 370 NON CONDUCTIVE; MOULD IDENTIFIER: GASKET C.193.8546 3; PACKAGING: SEALED UV RESISTANT BAG; PACKAGING	EA		

	Addendum 01 to tender E3122GXGPLET LETHABO POWER STATION	Unique Identifier	240-55105891
		Revision	1
		Revision Date	Once off issue
		Group Technology & Commercial	

	BAG TO HAVE THE DETAILED INFORMATION ON: MANUFACTURING DATE; EXPIRY DATE; LIFE EXPECTANCY; EACH DELIVERY OF THE GASKET TO BE SUPPLIED TO LETHABO WITH ITS MATERIAL CERTIFICATE; STORE UNDER ROOM TEMPERATURE			
0565421	GASKET, PRE CUT: DIMENSIONS: ID 1.04M X OD 1.225M X THK 3MM; TYPE: GEN HYDROGEN; MATERIAL: NITRILE; SHAPE: ROUND; RUBBER HARDNESS; 65 - 75 SHORE; > 10 MOHMS @ 500V DC; MATERIAL TYPE UNIQUE IDENTIFICATION: HE 370 NON CONDUCTIVE; MOULD IDENTIFIER: GASKET C.193.8546 3; PACKAGING: SEALED UV RESISTANT BAG; PACKAGING BAG TO HAVE THE DETAILED INFORMATION ON: MANUFACTURING DATE; EXPIRY DATE; LIFE EXPECTANCY; EACH DELIVERY OF THE GASKET TO BE SUPPLIED TO LETHABO WITH ITS MATERIAL CERTIFICATE; STORE UNDER ROOM TEMPERATURE	EA		
0565422	GASKET, PRE CUT: DIMENSIONS: ID 925 MM X OD 1.094 M X THK 3 MM; THICKNESS: 3 MM; TYPE: GEN HYDROGEN; MATERIAL: NITRILE; SHAPE: ROUND; RUBBER HARDNESS; 65 - 75 SHORE; > 10 MOHMS @ 500V DC; MATERIAL TYPE UNIQUE IDENTIFICATION: HE 370 NON CONDUCTIVE; MOULD IDENTIFIER: GASKET C.193.8546 3; PACKAGING: SEALED UV RESISTANT BAG; PACKAGING BAG TO HAVE THE DETAILED INFORMATION ON: MANUFACTURING DATE; EXPIRY DATE; LIFE EXPECTANCY; EACH DELIVERY OF THE GASKET TO BE SUPPLIED TO LETHABO WITH ITS MATERIAL CERTIFICATE; STORE UNDER ROOM TEMPERATURE	EA		
0588940	GASKET: TYPE: CENTRE RING; DIMENSIONS: OD 142 X THK 4.5 MM; MATERIAL: SS 321; SHAPE: ROUND; APPLICATION: SO3 FIGURE OF 8; DIMENSIONS: 80 NB PN 16; FILLER OD 115 X INNER RING OD 95 X INNER RING ID 86	EA		

	Addendum 01 to tender E3122GXGPLET LETHABO POWER STATION	Unique Identifier	240-55105891
		Revision	1
		Revision Date	Once off issue
		Group Technology & Commercial	

	MM			
0588941	GASKET: TYPE: CENTRE RING; DIMENSIONS: OD 92 X THK 4.5 MM; MATERIAL: SS 321; SHAPE: ROUND; APPLICATION: SO3 LANCE SMALL; DIMENSIONS: 40NB PN40; FILLER OD 70 X INNER RING OD 54 X INNER RING ID 48 MM	EA		
0600367	GASKET: TYPE: COMBUSTION AIR PIPE; DIMENSIONS: THK 3 MM; HOLES: 8; STYLE: FULL FACE; SHAPE: ROUND; APPLICATION: MEDIUM FLANGE; HOLES: DIA 22 MM; DIMENSIONS: 150NB PN/6 X THK 3MM; SIGRAFLEX HOCHDRUCK	EA		
0600368	GASKET: TYPE: MIXING CHAMBER LARGE FLANGE; DIMENSIONS: ID 346 X OD 460 X THK 3 MM; MATERIAL: SIGRAFLEX HOCHDRUCK; HOLES: (12) DIA 14 MM; STYLE: FULL FACE; SHAPE: ROUND; APPLICATION: PIPE FLANGE INTERFACE	EA		
0600369	GASKET: TYPE: INLET MIXING CHAMBER MEDIUM; DIMENSIONS: ID 115 X OD 220 X THK 3 MM; MATERIAL: SIGRAFLEX HOCHDRUCK; HOLES: (8) DIA 18 MM; STYLE: FULL FACE; SHAPE: ROUND; 180 MM PCD	EA		
0600370	GASKET: TYPE: BURNER MIXING CHAMBER VALVES; DIMENSIONS: ID 100 X OD 155 X THK 3 MM; MATERIAL: SIGRAFLEX HOCKDRUCK; HOLES: NONE RING; STYLE: RING; SHAPE: ROUND; VALVE FLAGE PIPE INTERFACE	EA		
0600371	GASKET: TYPE: COMBUSTION AIR VALVE, VERTICAL BELLOWS; DIMENSIONS: ID 170 X OD 280 X THK 3 MM; HOLES: (9) DIA 22 MM; STYLE: FULL FACE; SHAPE: ROUND; SEAL AT FLAGE AND PIPE; SIGRAFLEX HOCHDRUCK	EA		
0600372	GASKET: TYPE: BURNER FLANGE LARGE; DIMENSIONS: ID 320 X OD 460 X THK 3 MM; MATERIAL: SIGRAFLEX HOCHDRUCK; HOLES: (8) DIA 14 MM; STYLE: FULL FACE; SHAPE: ROUND; 410MM PCD	EA		
0601896	GASKET: TYPE: MIXING CHAMBER PIPE POST VALVE; DIMENSIONS: ID 115 X OD	EA		

	Addendum 01 to tender E3122GXGPLET LETHABO POWER STATION	Unique Identifier	240-55105891
		Revision	1
		Revision Date	Once off issue
		Group Technology & Commercial	

	162 X THK 3 MM; STYLE: RING; SHAPE: ROUND; REFERENCE NO: KLING 012015			
0601897	GASKET: TYPE: VALVE FLANGE PIPE CONNECTION; DIMENSIONS: ID 115 X OD 220 X THK 3 MM; HOLES: (8) DIA 18 PDC MM; STYLE: FULL FACE; SHAPE: ROUND; APPLICATION: COMBUSTION AIR VALVE; REFERENCE NO: KLING 012015	EA		
1610	GASKET, PRE CUT: DIMENSIONS: ID 28 X OD 38 X THK 2 MM; TYPE: BURCKHARDT COMPRESSOR; MATERIAL: CU; SHAPE: RD; SUPPL P/N: 4652; REFERENCE NO: C2N2; C4N2F; C4N1R; FOR USE ON BURCHARD COMPRESSOR	EA		
1629	GASKET, PRE CUT: DIMENSIONS: ID 84 X OD 113 X THK 0.5 MM; THICKNESS: 0.5 MM; TYPE: BURCHARDT COMPRESSOR; MATERIAL: MONTANIT; SHAPE: RD; NOMINAL FLANGE SIZE: 1.5 MM; PCD: 10 MM; HOLES: 6; SUPPL P/N: 5468; REFERENCE NO: 5468; FOR BURGHARDT COMPRESSOR C4N2F	EA		
94156	SHEET, GASKET: THICKNESS: 3 MM; LENGTH: 1 M; WIDTH: 1 M; MATERIAL: NEOPRENE; COLOUR RED	EA		
94190	PACKING, BULK: WIDTH: 15 MM; THICKNESS: 15 MM; MATERIAL: GRAPHITE; SHAPE: SQ; SUPPL P/N: 3001	KG		
94191	PACKING, BULK: WIDTH: 12.5 MM; THICKNESS: 12.5 MM; MATERIAL: GRAPHITE; TYPE: VALVE; SHAPE: SQ; SUPPL P/N: 3001; 2KG PER BOX	KG		
94192	PACKING, BULK: WIDTH: 8 MM; THICKNESS: 8 MM; MATERIAL: ASB GRAPHITE IMPREGNATED; TYPE: VALVE; SHAPE: SQ; STYLE: 3001/8MM; 2KG PER PACK; SIZE 8MM DIA; ROUND	KG		
94239	SHEET, GASKET: THICKNESS: 6 MM; LENGTH: 11 M; WIDTH: 1.82 M; MATERIAL: FELT; ROLL, ENGINEERS, WHITE, 2.975 KG/M	KG		
94240	SHEET: MATERIAL: FELT ENGINEERS; DIMENSIONS: WD 900 MM X LG 6 M X THK 12.5 MM; TYPE: SEAL; COLOR: WHITE; ROLL; MOTH REPELLENT	KG		

	Addendum 01 to tender E3122GXGPLET LETHABO POWER STATION	Unique Identifier	240-55105891
		Revision	1
		Revision Date	Once off issue
		Group Technology & Commercial	

94256	SHEET: MATERIAL: RUBBER NATURAL; DIMENSIONS: WD 1.2 M X THK 1.6 MM; TYPE: INSERTION; COLOR: BLACK; SIZE 1.5MM THK; THE FOLLOWING REQUIRED WITH DELIVERY, SHELF LIFE, DATE OF MANUFACTURE AND METHOD OF STORAGE	KG		
94257	SHEET, GASKET: THICKNESS: 3 MM; WIDTH: 1.2 M; MATERIAL: RUBBER HESSIAN REINFORCED; BLACK COLOUR	KG		
94320	SHEET, GASKET: THICKNESS: 3 MM; LENGTH: 1 M; WIDTH: 1 M; MATERIAL: CORK/NEOPRENE; REFERENCE NO: GR53; IMPREGNATED; NEOLONGITE GRADE 53 COMPOSITION	EA		
94322	SHEET, GASKET: THICKNESS: 6.5 MM; LENGTH: 1.27 M; WIDTH: 660 MM; MATERIAL: CORK NEOPRENE IMPREGNATED; GRADE: 53	EA		
94350	SHEET, GASKET: THICKNESS: 1.5 MM; LENGTH: 1 M; WIDTH: 1 M; MATERIAL: VELLUMOID; SUPPLIER NOTE: THE ITEM MUST BE PROTECTIVE PACKED	KG		
94353	SHEET, GASKET: THICKNESS: 6.3 MM; LENGTH: 2.44 M; WIDTH: 1.22 M; MATERIAL: RUBBER; COLOUR RED; THE FOLLOWING IS REQUIRED WITH EVERY DELIVERY; SHELF LIFE; DATE OF MANUFACTURE AND METHOD OF STORAGE	KG		
94389	SHEET, GASKET: THICKNESS: 4.5 MM; LENGTH: 1 M; WIDTH: 1 M; MATERIAL: CORK NEOPRENE IMPREGNATED; SUPPL P/N: GRADE GR53; REQUIRED WITH DELIVERY, DATE OF MANUFACTURE, SHELF LIFE AND STORAGE METHOD	EA		
94390	SHEET, GASKET: THICKNESS: 1.5 MM; LENGTH: 1 M; WIDTH: 1 M; MATERIAL: NEOLANGITE GR 510; CORK PACKING	EA		
97393	PACKING, PREFORMED: INSIDE DIAMETER: 63 MM; OUTSIDE DIAMETER: 82 MM; THICKNESS: 10 MM; TYPE: SQ RING; MATERIAL: GRAPHITE; REFERENCE NO: 5400; GPP 5400; NON POROUS CHESTERTON, FOR USE WITH DIAMOND POWER RETRACTABLE SOOTBLOWER TYPE IK545 FEED TUBE; VENDORS ARE	EA		

	Addendum 01 to tender E3122GXGPLET LETHABO POWER STATION	Unique Identifier	240-55105891
		Revision	1
		Revision Date	Once off issue
		Group Technology & Commercial	

	RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).			
97394	PACKING, PREFORMED: INSIDE DIAMETER: 13 MM; OUTSIDE DIAMETER: 22 MM; THICKNESS: 5 MM; TYPE: SPLIT RING; MATERIAL: GRAPHITE; SUPPL P/N: 302034-0117; MODEL NO: 102D83-0192; IK-525; VALVE STEM, FOR USE ON DIAMOND SOOTBLOWERS; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	EA		
97540	PACKING, BULK: WIDTH: 7.9 MM; THICKNESS: 7.9 MM; MATERIAL: PTFE GRAPHITE IMPREGNATED; TYPE: BRAIDED; SHAPE: SQ; SUPPL P/N: 222G; STAG, TEMPERATURE 280DEG C/-200DEG C	KG		
97541	PACKING, BULK: WIDTH: 6 MM; THICKNESS: 6 MM; MATERIAL: PTFE GRAPHITE IMPREGNATED; TEMPERATURE RANGE: 200-280 DEG C; TYPE: CROSS BRAID; SHAPE: SQ; SUPPL P/N: 222G	KG		
97781	GASKET, PRE CUT: DIMENSIONS: ID 65 X OD 90 X THK 2 MM; TYPE: VALVE; MATERIAL: ASB COMPRESSED; SHAPE: RD; REFERENCE NO: 7520-038; USED ON DELAS CHECK VALVE	EA		
97845	SHEET: MATERIAL: TUFNOL; DIMENSIONS: WD 600 MM X LG 1.7 M X THK 1.5 MM	EA		
98276	PACKING, PREFORMED: INSIDE DIAMETER: 130 MM; OUTSIDE DIAMETER: 140 MM; THICKNESS: 10 MM; MATERIAL: GRAPHITE; SHAPE SQUARE RING, PRE PRESSED RINGS, SOLID, INNER BEVEL, 11MM HIGH, STYLE 0901/I7 SOLID, 1RING PER SET, USED ON LEAK OFF VALVE; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	EA		

	Addendum 01 to tender E3122GXGPLET LETHABO POWER STATION	Unique Identifier	240-55105891
		Revision	1
		Revision Date	Once off issue
		Group Technology & Commercial	

99674	PACKING, BULK: WIDTH: 1 IN; THICKNESS: 1 IN; LENGTH: 8 M; MATERIAL: GRAPHITE/PTFE; APPLICATION: CIRCULATING WATER PUMP; SHAPE: SQ; SUPPL P/N: 1065; REFERENCE NO: IT1002-1065	EA		
100142	SHEET, GASKET: THICKNESS: 5 MM; WIDTH: 8 MM; MATERIAL: RUBBER NATURAL; ROLL; SQ 5 MM X 8 MM; LENGTH AS REQUIRED	M		
100288	KIT: TYPE: SEAL; COMPRISING: (2) GASKETS; (2) O-RINGS; SUPPL P/N: 1170T10; USED WITH FALK STEELFLEX COUPLING TYPE 170T	EA		
100530	KIT: TYPE: SEAL; APPLICATION: FALK COUPLING; COMPRISING: GASKETS; O-RINGS; USED ON FALK COUPLING TYPE 1210T	EA		
101106	PACKING, BULK: WIDTH: 19 MM; THICKNESS: 19 MM; MATERIAL: COTTON GRAPHITE IMPREGNATED; TYPE: BRAIDED; SHAPE: SQ; SUPPL P/N: 894	KG		
101183	PACKING, BULK: WIDTH: 16 MM; THICKNESS: 16 MM; MATERIAL: ASB YARN INCONEL WIRE REINFORCED; SHAPE: SQ; SUPPL P/N: 555; STYLE MAXMECH	KG		
101968	SHEET, GASKET: THICKNESS: 15 MM; WIDTH: 1.8 M; MATERIAL: FELT ENGINEERS/WOOL	KG		
101969	SHEET, GASKET: THICKNESS: 20 MM; WIDTH: 1.8 M; MATERIAL: FELT ENGINEERS/WOOL; NON WOVEN CONSTRUCTION, COLOUR WHITE	KG		
102172	GASKET, PRE CUT: DIMENSIONS: ID 70 X OD 80 X THK 10 MM; TYPE: VALVE; MATERIAL: GRAPHITE; SHAPE: RD; REFERENCE NO: NW21-24S120/S121; STYLE V901/I7	EA		
104131	GASKET SET: APPLICATION: COMPRESSOR; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	EA		
160153	STRIP: TYPE: SEALING; REFERENCE NO: SP105; PRESTIC 105, SIZE 8 MM DIA X 50 M	EA		

	Addendum 01 to tender E3122GXGPLET LETHABO POWER STATION	Unique Identifier	240-55105891
		Revision	1
		Revision Date	Once off issue
		Group Technology & Commercial	

	ROLL, CHEMEICALS TO BE SUPPLIED WITH MSDS AND SECTION 12 (ECOLOGICAL INFORMATION OF THE MSDS TO BE COMPLETED IN DETAIL) WITH EVERY DELIVERY			
160232	ADHESIVE: TYPE: GASKET; CONTAINER: TUBE PLASTIC 300 ML; PHYSICAL FORM: LIQUID; SUPPL P/N: 593; LOCTITE 593; REFERENCE NO: 593; RTV; HYPERLOCK, MATERIAL SILICON, COLOR BLK, MATERIAL SAFETY DATA SHEETS WITH ENVIRONMENTAL INFORMATION IN THE 16 POINT FORMAT TO BE PROVIDED WITH EVERY DELIVERY AS REQUIRED BY THE OCCUPATIONAL HEALTH AND SAFETY ACT; LOCKTITE	EA		
160266	COMPOUND, SEALING: TYPE: GASKET/JOINT; COLOR: BLUE UNIVERSAL; CONTAINER: TUBE 100 G; MATERIAL: POLYESTER URETHANE; SUPPL P/N: PL32M; CLAUSE: 1: PLEASE ENSURE THAT SHELF LIFE HISTORY AND EXPIRY DATES ARE DISPLAYED, 2: ITEMS SUBJECTED TO SHELF LIFE WILL NOT BE ACCEPTED TO ESKOM IF MORE THAN 25 PCT OF THE SHELF LIFE HAS ALREADY EXPIRED PRIOR TO DELIVERY; MATERIAL SAFETY DATA SHEETS WITH ENVIRONMENTAL INFORMATION IN THE 16 POINT FORMAT TO BE PROVIDED WITH EVERY DELIVERY AS REQUIRED BY THE OCCUPATIONAL HEALTH AND SAFETY ACT	EA		
210819	SHEET, GASKET: THICKNESS: 0.4 MM; LENGTH: 1 M; WIDTH: 1 M; MATERIAL: VELLUMOID; SUPPL P/N: STATITE; SUPPLIER NOTE: EACH ROLL TO BE SEALED IN A PLASTIC BAG AND CLEARLY MARKED	M		
210820	SHEET, GASKET: THICKNESS: 0.8 MM; LENGTH: 10 M; WIDTH: 1 M; MATERIAL: VELLUMOID; SUPPLIER NOTE: EACH ROLL MUST BE SEALED IN A PLASTIC BAG AND CLEARLY MARKED	M		
217147	SHEET, GASKET: THICKNESS: 2 MM; LENGTH: 1.5 M; WIDTH: 1.5 M; MATERIAL: PTFE; SUPPL P/N: 2003; PACKING, BULK,	EA		


	Addendum 01 to tender E3122GXGPLET LETHABO POWER STATION	Unique Identifier	240-55105891
		Revision	1
		Revision Date	Once off issue
		Group Technology & Commercial	

	SHAPE FLAT; TOPCHEM			
217148	SHEET, GASKET: THICKNESS: 1.5 MM; LENGTH: 1.5 M; WIDTH: 1.5 M; MATERIAL: PTFE 100 PCT; SUPPL P/N: HYGRADE LS; PACKING, BULK, SHAPE FLAT	EA		
217149	SHEET, GASKET: THICKNESS: 3 MM; LENGTH: 1.5 M; WIDTH: 1.5 M; MATERIAL: PTFE 100 PCT; SUPPL P/N: HYGRADE LS; PACKING, BULK, SHAPE FLAT	EA		
217150	SHEET, GASKET: THICKNESS: 3 MM; LENGTH: 1.5 M; WIDTH: 1.5 M; MATERIAL: PTFE; SUPPL P/N: 2003; PACKING, BULK, SHAPE FLAT; TOPCHEM	EA		
222634	PACKING, BULK: WIDTH: 25.4 MM; THICKNESS: 25.4 MM; MATERIAL: ARG TM SYNTHETIC YARN; SHAPE: SQ; SUPPL P/N: 412-W; NOTE - ONLY CHESTERTON BRAND ACCEPTABLE AT CAMDEN POWER STATION	KG		
223825	COMPOUND, SEALING: TYPE: GASKET ELIMINATOR; CONTAINER: TUBE 45 G; NUMBER 2; FORM A GASKET; CHEMICALS TO BE SUPPLIED WITH MSDS AND SECTION 12 (ECOLOGICAL INFORMATION OF THE MSDS TO BE COMPLETED IN DETAIL); THE FOLLOWING IS REQUIRED WITH EVERY DELIVERY; SHELF LIFE; DATE OF MANUFACTURE AND METHOD OF STORAGE	EA		
237314	SHEET, GASKET: THICKNESS: 1.5 MM; LENGTH: 15 M; WIDTH: 15 M; MATERIAL: PTFE; SUPPL P/N: 2003; PACKING, BULK; SHAPE FLAT; TOPCHEM	EA		
527163	SHEET, GASKET: THICKNESS: 3 MM; LENGTH: 1.5 M; WIDTH: 1.5 M; MATERIAL: GRAPHITE; SPECIFICATION: DIN 28091-GR- 11-I-5-CR; MAXIMUM TEMPERATURE OF 600 DEGREE CELSIUS AND MAXIMUM PRESSURE 200 BAR; LAMINATED GRAPHITE WITH STAINLESS STEEL FOIL 0.05 MM	EA		
563905	PACKING, BULK: WIDTH: 25 MM2; THICKNESS: 25 MM2; LENGTH: 8 M; MATERIAL: AERO DRUM MATERIAL ONLY; APPLICATION: ASH; WATER; MAX	EA		

	Addendum 01 to tender E3122GXGPLET LETHABO POWER STATION	Unique Identifier	240-55105891
		Revision	1
		Revision Date	Once off issue
		Group Technology & Commercial	

	PRESSURE: 56 BAR; PH VALUE RANGE: 3-12; TEMPERATURE RANGE: 260 DEG C; TYPE: CARRIER; LUBRICATION MATERIAL: AERO DRUM; SHAPE: SQ; 2.5 KG BOX; STYLE 99.			
609967	GASKET: TYPE: RING; DIMENSIONS: ID 35 X OD 70 X THK 3 MM; MATERIAL: TO-PCHEM 2003; SHAPE: ROUND; APPLICATION: PIPE FLANGE; REFERENCE NO: K10415; PN 16; 25 NB	EA		
639650	PACKING: TYPE: PURE WHITE 412-W; LENGTH: 1.219 M; WIDTH: 12.7 MM; MATERIAL: FIBER SYNTHETIC CHESTERTON; SHAPE: SQ; THICKNESS: 12.7 MM; DIAMETER: 12.7 MM; DESIGNED FOR SHAFTS AND RODS AGAINST WATER; OIL; STEAM; SOLVENTS AND MILD ACIDS AND ALKALIES TO 250 DEG CELCIUS AND SHAFT SPEED TO 10M PER SECOND; PH 4-10; MASS IS 2.25KG PER BOX	KG		

Yours sincerely,



Ndumiso Mncube
Procurement Manager