

Specifications - L - Plumbing			
Key Value		Keynote Text	
L4-d: Accessible wash basin		Wall mounted vandal-proof wash basin, 420x340x185mm deep from Franke or accepted equal. Unit to be manufactured from Grade 304 (18/10) Stainless Steel, 1,2mm gauge. Unit to include a one piece pressed bowl with a 40mm waste outlet, with a 50mm splashback and 100mm radiused apron. Basin to be fixed to the wall with 4 x 6mm anchor bolts. To be fitted with Cobra 505-21B – Elbow action Pillar tap square type with Blue indice or accepted equal.	
L4: Wash basin		Project specific - to be completed if used	
L5-a: Toilet		Floor standing vandal-proof WC pan from Franke or accepted equal for fitting through duct wall, manufactured from grade 1.4301 (304) stainless steel, material thickness 1.5mm for the pan and shroud - satin polish finish. Installation inclusive of a stainless steel P trap and pressed seating area for a seatless installation. Products to be foam filled, for extra strength and reduction of noise. Product to be SABS approved. Geberit Sigma concealed cistern 8cm, 6 litre, with Mambo Actuator plate or accepted equal.	
L5-d: Accessible toilet		Floor standing vandal-proof WC pan for disabled persons from Franke or accepted equal, manufactured from grade 1.4301 (304) stainless steel - satin polish finish, material thickness of 1.5mm for the pan and shroud with a stainless steel P trap 102mm o/d, supplied complete with multikwik connector. A flush bend and 90° plastic bend are provided for the cistern downpipe connection. Rear mounting plate with 4 no. stainless steel bolts supplied, for mounting onto duct wall. The front of the WC to be fixed to the floor using a joggle strip. The WC is supplied with a white plastic seat for disabled persons. WC supplied with hole for downpipe. Geberit Sigma concealed cistern 8cm, 6 litre, with Mambo Actuator plate or accepted equal.	