

DECLARATION CERTIFICATE FOR LOCAL PRODUCTION AND CONTENT FOR DESIGNATED SECTORS

This Standard Bidding Document (SBD) must form part of all bids invited. It contains general information and serves as a declaration form for local content (local production and local content are used interchangeably).

Before completing this declaration, bidders must study the General Conditions, Definitions, Directives applicable in respect of Local Content as prescribed in the Preferential Procurement Regulations, 2017, the South African Bureau of Standards (SABS) approved technical specification number SATS 1286:2011 (Edition 1) and the Guidance on the Calculation of Local Content together with the Local Content Declaration Templates [Annex C (Local Content Declaration: Summary Schedule), D (Imported Content Declaration: Supporting Schedule to Annex C) and E (Local Content Declaration: Supporting Schedule to Annex C)].

1. General Conditions

- 1.1. Preferential Procurement Regulations, 2017 (Regulation 8) make provision for the promotion of local production and content.
- 1.2. Regulation 8.(2) prescribes that in the case of designated sectors, organs of state must advertise such tenders with the specific bidding condition that only locally produced or manufactured goods, with a stipulated minimum threshold for local production and content will be considered.
- 1.3. Where necessary, for tenders referred to in paragraph 1.2 above, a two stage bidding process may be followed, where the first stage involves a minimum threshold for local production and content and the second stage price and B-BBEE.
- 1.4. A person awarded a contract in relation to a designated sector, may not sub-contract in such a manner that the local production and content of the overall value of the contract is reduced to below the stipulated minimum threshold.
- 1.5. The local content (LC) expressed as a percentage of the bid price must be calculated in accordance with the SABS approved technical specification number SATS 1286: 2011 as follows:

$$LC = [1 - x / y] * 100$$

Where

x is the imported content in Rand

y is the bid price in Rand excluding value added tax (VAT)

Prices referred to in the determination of x must be converted to Rand (ZAR) by using the exchange rate published by South African Reserve Bank (SARB) at 12:00 on the date of advertisement of the bid as indicated in paragraph 4.1 below.

The SABS approved technical specification number SATS 1286:2011 is accessible on [http://www.thedti.gov.za/industrial development/ip.jsp](http://www.thedti.gov.za/industrial%20development/ip.jsp) at no cost.

1.6. A bid may be disqualified if this Declaration Certificate and the Annex C (Local Content Declaration: Summary Schedule) are not submitted as part of the bid documentation;

2. The stipulated minimum threshold(s) for local production and content (refer to Annex A of SATS 1286:2011) for this bid is/are as follows:

PROJECT NAME: UPGRADING OF STORMWATER NETWORK AT BRAAMFONTEIN ROLLING STOCK DEPOT		
BOQ item no's	Description	Minimum Threshold for Local Content
	<u>BILL NO 3</u>	
	<u>CONCRETE WORK</u>	
	<u>REINFORCED CONCRETE CAST AGAINST EXCAVATED SURFACES</u>	
	25MPa/20mm Concrete	
1	Strip footing	100%
	Grouting	
2	70m Non shrink grouting suitable for HDPE underground pipe by the use of machinery	100%
	Stabilizing, densifying, and increase bearing capacity of ground below concrete foundations. The injection process is deemed complete once lift of 0.5mm is achieved	
3	Concrete Epoxy resin for filling resin under the buildings foundation where concrete foundation and loose material was eroded by water	100%
	<u>BILL NO 4</u>	
	<u>MASONRY</u>	
	Bricks shall have been obtained from an approved manufacturer and shall be either general purpose (special) burn clay bricks or Engineering bricks that comply with the applicable requirements of SABS 285. The contractor shall submit to the project manager samples of the bricks that he/she intends using in the construction of the works. The sample of the bricks that are approved will be retained by the Project manager. See sub clause 3.1 of SABS 1200A or 1200AA as applicable	
	Bricks in Class II mortar	

1	One brick wall for storm water channel and catch basin	100%
	<u>FOUNDATIONS (PROVISIONAL)</u>	
	15MPa/20mm concrete	
2	50mm blinding layer	100%
	BRICKWORK SUNDRIES	
	Brick reinforcement	
3	230mm wide reinforcement built in horizontal	100%
	<u>BILL NO 5</u>	
	<u>CARPENTRY AND JOINERY</u>	
	<u>DOORS</u>	
	44mm thick interior grade flush solid core timber single door with 3 mm thick commercial ply on both sides with consolidated edges fitted and complying with SABS 545 in pressed steel frame. All painted in accordance with architects colour schedule.	
1	813 x 2032 x 44mm single interior leaf solid core including painting on both sides	100%
	44mm thick exterior grade flush solid core timber single door with 3mm thick commercial ply on both sides with consolidated edges fitted and complying with SABS 545 in pressed steel frame. All painted in accordance with architect's colour schedules	
2	813 x 2032 x 44mm single exterior leaf solid core including painting on both sides	100%
	<u>BILL NO 6</u>	
	<u>IRONMONGERY</u>	
	<u>LOCKS</u>	
1	3 liver union lock with handles	100%
2	Ultra-security heavy duty locks	100%

3	Stainless Steel Toilet Cubicle Indicator bolt & lock set, Grade 304Stainless Steel indicator bolt fixed to surface with matching stainless steel screws.	100%
	<u>BILL NO 7</u>	
	<u>PLUMBING WORK</u>	
	<u>SANITARY FITTINGS</u>	
1	Vaal Sanitary ware Hibiscus vitreous china close coupled suite colour White , comprising 90° outlet open rim pan with matching 9 litre front single flush cistern including lid and fitments and seat.	100%
2	Bemis vandal proof toilet seat	100%
3	Ceramic wash hand basin colour White, size 510 x 405mm with one tap hole including integrated overflow and chain stay hole bolted to wall with two x 10mm bolts and including Classic floor mounted pedestal and sealed with silicone sealant where basin meets wall.	100%
4	Sanitary ware white vitreous china wall mounted urinal with top inlet (code 705426) or back inlet (code 7054Z1). Overall size 600x385x380mm. Supplied with 38mm c.p. domical grating, a spreader(with a 20mm tread) and two hanger brackets	100%
5	Floor mounted ceramic toilet pan suitable for top entry flush valve	100%
6	50mm pipes with all connection and make good	100%
	<u>WASTE UNINON ETC</u>	
7	Bath and Basin waste, plug, chain, stay and backnut	100%
	<u>TRAPS ETC</u>	
8	365/40 CP bottle trap 40 x 40 INC CP/PVC adaptor to 40mm	100%
9	38mm sink “P” trap	100%
	<u>TAPS, VALVES, ETC</u>	
	<u>Supply and install</u>	
10	15mm push button pillar tap for hot and cold water	70%
11	15mm chrome plated deck mounted sink mixer with overarm swivel outlet and adjustable flanges, manufactured in accordance with SANS 226:2004 Type 1.	70%

12	Top entry toilet flush valve completely with flush pipe	70%
13	Exposed type flush valve with ball-o-stop, wall flange, chrome plate finish and non-hold open feature	70%
14	Flexi connector	100%
15	15 Brass Gate Valve	70%
16	Mini Ball Valve	70%
17	22mm Brass Gate Valve including cast iron valve box	70%
18	Single function vandal resistant shower head including shower arm, stainless steel polished body	100%
19	Chrome plated Shower tap mixer	70%
20	600kpa pressure control valve	70%
21	Relieve/safety valve	70%
22	Vacuum breaker	100%
23	Drain cock	100%
	Extra over PVC pipes for fittings	
24	110mm pan connector completely	100%
	WATER SUPPLIERS	
	Class “O” copper pipe	
25	15mm pipes	100%
26	15mm pipes chased into brick walls and make good	100%
27	22mm pipes	100%
28	22mm pipes chased into brick walls	100%
	Extra over class “O” copper pipes for capillary fittings	
29	15mm fitting	100%
30	22mm fitting	100%

31	15mm Tee	100%
32	22mm Tee	100%
	Manhole covers and grid inlets	
33	1000mm wide x 65mm thick heavy duty polymer grid inlet including frame	100%
	STORM WATER DRAINAGE	
	Class 50D concrete storm water pipes laid in class A bedding including excavation, backfilling etc	
34	300mm pipes laid in 2m deep trenches	100%
35	Cast 700mm wide x 300mm deep x 100mm thick half round concrete drainage channel as per manufacture specification	100%
	HORIZONTAL DIRECTIONAL DRILLING UNDER BUILDINGS AND INSTALLATION OF HDPE PIPE	
36	HDD under the buildings and installation of 300mm diameter HDPE but welded on sleeve pipe with Nominal Pressure class 16 and material of PE100 to be used including all fittings completely installed with a 3% slope or more at an angle of 30°	100%
	<u>BILL NO 9</u>	
	<u>GLAZING</u>	
	<u>GLAZING TO STEEL WITH PUTTY</u>	
	4mm clear float glass	
1	Panes exceeding 0.5 m ² and not exceeding 1.0 m ²	100%
	4mm clear obscure glass	
2	Panes exceeding 0.5 m ² and not exceeding 1.0 m ²	100%
	<u>BILL NO.2</u>	
	<u>ELECTRICAL WORK</u>	
	Fluorescent fittings waterproofed fixture white including 2x58w T8 LED Fluorescent tubes and polycarbonate base with clear polycarbonate cover IP65	

1	Waterproof polycarbonate LED 5ft 2 x58w T8 fluorescent fitting including 2 LED tubes	100%
2	1200m (4 foot) 2x36w Open channel cool white LED Fluorescent fittings double tubes for ticket office building	100%
	Bulkhead fittings	
3	7w LED bulk head fittings completely with bulbs	100%
	The luminaire to consist of a die-cast aluminium control gear housing and spun aluminium refactor. The luminaire to bears SANS475 mark and SANS 60598 2-1 safety mark and the degree of protection, the control gear compartment to be manufactured from high pressure die cast aluminium for good dissipation. the reflector system to be manufactured of brightened and anodized aluminium, mounted onto the control gear housing via two keyholes slots and closed IP65 version	
4	250w HPS 27000/31600 Lumen light fittings	100%
5	Bulb and ballast for above 250w light fittings	100%
	PLUGS	
7	4 X 4 single plug	100%
8	4 X 4 Double plug	100%
	<u>SWITCHES</u>	
9	Day light switches	100%
10	Single 200v 40 Amps contactors	100%
11	White 1 lever 2 way switch	100%
12	White 2 lever 1 way switch	100%
	Electrical cables	
13	4mm2 GP wires for stove and geyser	90%
14	2.5mm2 GP wires (Red, white, blue, black and earth) for lights rewiring of shelters, footbridge, ablutions and access points in 3 phase system	90%
15	2.5mm ² suffix cable or GP wire for plugs	90%

16	1.5mm ² suffix cable or GP wire for lights	90%
	Electrical casing	
17	25 x 40mm PVC trunking	100%
18	20mm PVC SABS conduit completely with all the couplings, saddle, spacer bar assembly and heavy duty U clamps	100%
	Circuit breakers	
19	10 A 1P 6KA single circuit breaker	100%
20	20 A 1P 6KA single circuit breaker	100%
21	40 A stove Isolator	100%
22	30A Air conditioner and gyser Isolator	100%
	DB BOARDS	
23	Flush mounted min distribution board completely with circuit breakers	100%
	HVAC Systems	
24	Supply, install and commission new 24000 BTU split unit, inverter technology air conditioner completely with all accessories (drain pipe, amorflex, copper pipe, refrigerant, cable, communication wire, brackets, circuit breaker, isolator, etc)	70%

3. Does any portion of the goods or services offered have any imported content?

(Tick applicable box)

YES	<input checked="" type="checkbox"/>	NO	<input type="checkbox"/>
-----	-------------------------------------	----	--------------------------

- 3..1 If yes, the rate(s) of exchange to be used in this bid to calculate the local content as prescribed in paragraph 1.5 of the general conditions must be the rate(s) published by SARB for the specific currency at 12:00 on the date of advertisement of the bid.

The relevant rates of exchange information is accessible on www.reservebank.co.za

Indicate the rate(s) of exchange against the appropriate currency in the table below (refer to Annex A of SATS 1286:2011):

Currency	Rates of exchange
US Dollar	
Pound Sterling	
Euro	

Yen	
Other	

NB: Bidders must submit proof of the SARB rate (s) of exchange used.

4. Where, after the award of a bid, challenges are experienced in meeting the stipulated minimum threshold for local content the dti must be informed accordingly in order for the dti to verify and in consultation with the AO/AA provide directives in this regard.

LOCAL CONTENT DECLARATION
(REFER TO ANNEX B OF SATS 1286:2011)

LOCAL CONTENT DECLARATION BY CHIEF FINANCIAL OFFICER OR OTHER LEGALLY RESPONSIBLE PERSON NOMINATED IN WRITING BY THE CHIEF EXECUTIVE OR SENIOR MEMBER/PERSON WITH MANAGEMENT RESPONSIBILITY (CLOSE CORPORATION, PARTNERSHIP OR INDIVIDUAL)

IN RESPECT OF BID NO.....

ISSUED BY: (Procurement Authority / Name of Institution):

.....NB

- 1 The obligation to complete, duly sign and submit this declaration cannot be transferred to an external authorized representative, auditor or any other third party acting on behalf of the bidder.
- 2 Guidance on the Calculation of Local Content together with Local Content Declaration Templates (Annex C, D and E) is accessible on http://www.thdti.gov.za/industrial_development/ip.jsp. Bidders should first complete Declaration D. After completing Declaration D, bidders should complete Declaration E and then consolidate the information on Declaration C. **Declaration C should be submitted with the bid documentation at the closing date and time of the bid in order to substantiate the declaration made in paragraph (c) below.** Declarations D and E should be kept by the bidders for verification purposes for a period of at least 5 years. The successful bidder is required to continuously update Declarations C, D and E with the actual values for the duration of the contract.

I, the undersigned, (full names),
do hereby declare, in my capacity as
of(name of bidder
entity), the following:

- (a) The facts contained herein are within my own personal knowledge.
- (b) I have satisfied myself that:
 - (i) the goods/services/works to be delivered in terms of the above-specified bid comply with the minimum local content requirements as specified in the bid, and as measured in terms of SATS 1286:2011; and
- (c) The local content percentage (%) indicated below has been calculated using the formula given in clause 3 of SATS 1286:2011, the rates of exchange indicated in paragraph 4.1 above and the information contained in Declaration D and E which has

been consolidated in Declaration C:

Bid price, excluding VAT (y)	R
Imported content (x), as calculated in terms of SATS 1286:2011	R
Stipulated minimum threshold for local content (paragraph 3 above)	
Local content %, as calculated in terms of SATS 1286:2011	

If the bid is for more than one product, the local content percentages for each product contained in Declaration C shall be used instead of the table above.

The local content percentages for each product has been calculated using the formula given in clause 3 of SATS 1286:2011, the rates of exchange indicated in paragraph 4.1 above and the information contained in Declaration D and E.

- (d) I accept that the Procurement Authority / Institution has the right to request that the local content be verified in terms of the requirements of SATS 1286:2011.
- (e) I understand that the awarding of the bid is dependent on the accuracy of the information furnished in this application. I also understand that the submission of incorrect data, or data that are not verifiable as described in SATS 1286:2011, may result in the Procurement Authority / Institution imposing any or all of the remedies as provided for in Regulation 14 of the Preferential Procurement Regulations, 2017 promulgated under the Preferential Policy Framework Act (PPPFA), 2000 (Act No. 5 of 2000).

SIGNATURE: _____

DATE: _____

WITNESS No. 1 _____

DATE: _____

WITNESS No. 2 _____

DATE: _____