



- NOTES**
1. ALL WRITTEN DIMENSIONS TO TAKE PRECEDENCE OVER SCALED DIMENSIONS.
 2. ALL LEVELS AND DIMENSIONS TO BE CHECKED BEFORE ANY WORK COMMENCES.
 3. ALL STEEL TO BE HOT-DIPPED GALVANIZED WITH MINIMUM ZINC COATING THICKNESS OF 16 (HEAVY DUTY GALVANISING) (SABS 703).
 4. ALL WELDS TO BE FULL CONTINUOUS FILE.
 5. ALL BOLTS, WASHERS AND NUTS TO BE GALVANIZED.
 6. ALL BOLTS TO HAVE A SPECIAL BREAK OFF FOR SECURITY MEASURES.

No	DATE	AMENDMENT

MANAGER'S DESIGN OFFICE
PORT ENGINEER

National Ports Authority of South Africa

PORT ENGINEER D
SUITE 233
OCEAN TERMINAL, T-JE
PORT OF DURBAN
TEL: (031) 361-8730, 8748

PORT OF DURBAN

PORT SECURITY
DOUBLE SWING GATE
TO SUIT TYPES 'A' AND 'B'
PALLISADE SECURITY

DRAWN: A. MOONSAMY	CHECKED: []
SCALE: 1:20	DATE: 20[]

No	DH61 - 1 - 23
CAD REF: 10023-001-01	SHEET []
FILE REF:	AMEND []