



NEC3 Supply Contract (SC3)

Between **ESKOM HOLDINGS SOC Ltd**
(Reg No. 2002/015527/30)

and [Insert at award stage]
(Reg No. _____)

for **Supply and Delivery of PPE Personal Protective
Clothing As and When Required at Arnot Power
Station for a Period of Five (5) years**

Contents:	No of pages
Part C1 Agreements & Contract Data	[•]
Part C2 Pricing Data	[•]
Part C3 Scope of Work	[•]

CONTRACT No. [Insert at award stage]

PART C1: AGREEMENTS & CONTRACT DATA

Contents:	No of pages
C1.1 Form of Offer and Acceptance	[•]
[to be inserted from Returnable Documents at award stage]	
C1.2a Contract Data provided by the <i>Purchaser</i>	[•]
C1.2b Contract Data provided by the <i>Supplier</i>	[•]
[to be inserted from Returnable Documents at award stage]	
C1.3 Proforma Guarantees	[•]

C1.1 Form of Offer & Acceptance

C.1.1.1 Offer

The Purchaser, identified in the Acceptance signature block, has solicited offers to enter into a contract for the procurement of:

Supply and Delivery of PPE Personal Protective Clothing as and when required at Arnot Power Station for a Period of Five (5) Years

The tenderer, identified in the Offer signature block, has

<i>either</i>	examined the documents listed in the Tender Data and addenda thereto as listed in the Returnable Schedules, and by submitting this Offer has accepted the Conditions of Tender.
<i>or</i>	examined the draft contract as listed in the Acceptance section and agreed to provide this Offer.

By the representative of the tenderer, deemed to be duly authorised, signing this part of this Form of Offer and Acceptance the tenderer offers to perform all of the obligations and liabilities of the *Supplier* under the contract including compliance with all its terms and conditions according to their true intent and meaning for an amount to be determined in accordance with the *conditions of contract* identified in the Contract Data.

	The offered total of the Prices exclusive of VAT is	R [●]
	Value Added Tax @ 15% is	R [●]
	The offered total of the amount due inclusive of VAT is ¹	R [●]
(in words) [●]		

This Offer may be accepted by the Purchaser by signing the Acceptance part of this Form of Offer and Acceptance and returning one copy of this document including the Schedule of Deviations (if any) to the tenderer before the end of the period of validity stated in the Tender Data, or other period as agreed, whereupon the tenderer becomes the party named as the *Supplier* in the *conditions of contract* identified in the Contract Data.

Signature(s)

Name(s) _____

Capacity _____

For the tenderer:

(Insert name and address of organisation)

Name & signature of witness

Date

¹ This total is required by the *Purchaser* for budgeting purposes only. Actual amounts due will be assessed in terms of the *conditions of contract*.

Acceptance

By signing this part of this Form of Offer and Acceptance, the Purchaser identified below accepts the tenderer's Offer. In consideration thereof, the Purchaser shall pay the Supplier the amount due in accordance with the *conditions of contract* identified in the Contract Data. Acceptance of the tenderer's Offer shall form an agreement between the Purchaser and the tenderer upon the terms and conditions contained in this agreement and in the contract that is the subject of this agreement.

The terms of the contract, are contained in:

- Part C1 Agreements and Contract Data, (which includes this Form of Offer and Acceptance)
- Part C2 Pricing Data
- Part C3 Scope of Work: Goods Information including Supply Requirements

and drawings and documents (or parts thereof), which may be incorporated by reference into the above listed Parts.

Deviations from and amendments to the documents listed in the Tender Data and any addenda thereto listed in the Returnable Schedules as well as any changes to the terms of the Offer agreed by the tenderer and the Purchaser during this process of offer and acceptance, are contained in the Schedule of Deviations attached to and forming part of this Form of Offer and Acceptance. No amendments to or deviations from said documents are valid unless contained in this Schedule.

The tenderer shall within two weeks of receiving a completed copy of this agreement, including the Schedule of Deviations (if any), contact the Purchaser's agent (whose details are given in the Contract Data) to arrange the delivery of any securities, bonds, guarantees, proof of insurance and any other documentation to be provided in terms of the *conditions of contract* identified in the Contract Data at, or just after, the date this agreement comes into effect. Failure to fulfil any of these obligations in accordance with those terms shall constitute a repudiation of this agreement.

Notwithstanding anything contained herein, this agreement comes into effect on the date when the tenderer receives one fully completed and signed original copy of this document, including the Schedule of Deviations (if any).

Signature(s)

Name(s)

Capacity

**for the
Purchaser**

**Eskom Holdings SOC Ltd, Megawatt Park, Maxwell Drive, Sandton, Johannesburg,
2199**

(Insert name and address of organisation)

Name &
signature of
witness

Date

Note: If a tenderer wishes to submit alternative tenders, use another copy of this Form of Offer and Acceptance.

Schedule of Deviations to be completed by the *Purchaser* prior to contract award

Note:

1. This part of the Offer & Acceptance would not be required if the contract has been developed by negotiation between the Parties and is not the result of a process of competitive tendering.
2. The extent of deviations from the tender documents issued by the Purchaser prior to the tender closing date is limited to those permitted in terms of the Conditions of Tender.
3. A tenderer's covering letter must not be included in the final contract document. Should any matter in such letter, which constitutes a deviation as aforesaid be the subject of agreement reached during the process of Offer and Acceptance, the outcome of such agreement shall be recorded here, and the final draft of the contract documents shall be revised to incorporate the effect of it.

No.	Subject	Details
1		
2		
3		
4		
5		
6		
7		

By the duly authorised representatives signing this Schedule of Deviations below, the Purchaser and the tenderer agree to and accept this Schedule of Deviations as the only deviations from and amendments to the documents listed in the Tender Data and any addenda thereto listed in the Tender Schedules, as well as any confirmation, clarification or changes to the terms of the Offer agreed by the tenderer and the Purchaser during this process of Offer and Acceptance.

It is expressly agreed that no other matter whether in writing, oral communication or implied during the period between the issue of the tender documents and the receipt by the tenderer of a completed signed copy of this Form shall have any meaning or effect in the contract between the parties arising from this Agreement.

For the tenderer:

For the Purchaser

Signature _____

Name _____

Capacity _____

On behalf of _____
(Insert name and address of organisation)

**Eskom Holdings SOC Ltd, Megawatt
 Park, Maxwell Drive, Sandton,
 Johannesburg, 2199**

Name & signature of witness _____

Date _____

C1.2 SC3 Contract Data

Part one - Data provided by the *Purchaser*

Completion of this data in full, according to the Options chosen, is essential to create a complete contract.

Clause	Statement	Data
1	General	
	The <i>conditions of contract</i> are the core clauses and the clauses for Options	
		X1: Price adjustment for inflation
		X2: Changes in the law
		X7: Delay damages
		Z: Additional conditions of contract
	of the NEC3 Supply Contract (April 2013) ¹	
10.1	The <i>Purchaser</i> is (name):	Eskom Holdings SOC Ltd (reg no: 2002/015527/30), a state-owned company incorporated in terms of the company laws of the Republic of South Africa
	Address	Registered office at Megawatt Park, Maxwell Drive, Sandton, Johannesburg
	Tel No.	013 297 9111
	Fax No.	N/A
10.1	The <i>Supply Manager</i> is (name):	
	Address	Eskom Holdings SOC Limited (Reg No: 2002/015527/06) Arnot Power Station Private Bag x2, Rietkuil 1097
	Tel	013 297 9111
	Fax	N/A
	e-mail	
11.2(13)	The <i>goods</i> are	PPE-Personal Protective Clothing
11.2(13)	The <i>services</i> are	Supply and Delivery of PPE Personal Protective Clothing as and when required at Arnot Power Station for the period of Five (5) Years.

¹ Available from Engineering Contract Strategies Tel 011 803 3008 Fax 086 539 1902, www.ecs.co.za.

11.2(14)	The following matters will be included in the Risk Register	<ul style="list-style-type: none"> • Late Deliveries • Supply and Delivery of Goods that failed to meet contractual specifications 				
11.2(15)	The Goods Information is in	Part 3: Scope of Work and all documents and drawings to which it makes reference.				
11.2(15)	The Supply Requirements as part of the Goods Information is in	Annexure A to this Contract Data				
12.2	The <i>law of the contract</i> is the law of	the Republic of South Africa				
13.1	The <i>language of this contract</i> is	English				
13.3	The <i>period for reply</i> is	Five (5) working days				
2	The Supplier's main responsibilities	Data required by this section of the core clauses is provided by the <i>Supplier</i> in Part 2 and terms in italics used in this section are identified elsewhere in this Contract Data.				
3	Time					
30.1	The <i>starting date</i> is.					
30.1	The <i>delivery date</i> of the goods and services is:	<table border="1"> <thead> <tr> <th><i>Goods and Services</i></th> <th><i>Delivery Date</i></th> </tr> </thead> <tbody> <tr> <td>1 PPE Personal Protective Clothing</td> <td>As stated in every Purchase Order issued</td> </tr> </tbody> </table>	<i>Goods and Services</i>	<i>Delivery Date</i>	1 PPE Personal Protective Clothing	As stated in every Purchase Order issued
<i>Goods and Services</i>	<i>Delivery Date</i>					
1 PPE Personal Protective Clothing	As stated in every Purchase Order issued					
31.1	The <i>Supplier</i> is to submit a first programme for acceptance within	Two weeks of Purchase Order				
32.2	The <i>Supplier</i> submits revised programmes at intervals no longer than					
4	Testing and defects					
42	The <i>defects date</i> is	Fifty-Two (52) weeks after delivery of goods and services				
42.2	The <i>defect access period</i> is	One (1) day				
42.3	The <i>defects corrections period</i> is	One (1) week or as agreed by the parties				
5	Payment					
50.1	The <i>assessment interval</i> is	between the 25th day and the last day of each successive month.				
51.1	The <i>currency of this contract</i> is the	ZAR (South African Rand)				
51.2	The period within which payments are made is	<p>Thirty (30) Calendar days after the signed assessment by both Parties and a valid Tax Invoice.</p> <p>ATTENTION: Eskom's standard policy on payment term for all contracts valued above R50 000 000 (Fifty Million Rand), including VAT, is 60 days. Bidders are requested to bear this</p>				

		payment term in mind when submitting bids and concluding contracts.
51.4	The <i>interest rate</i> is	the publicly quoted prime rate of interest (calculated on a 365-day year) charged from time to time by the Standard Bank of South Africa Limited (as certified, in the event of any dispute, by any manager of such bank, whose appointment it shall not be necessary to prove) for amounts due in Rands.
6	Compensation events	There is no reference to Contract Data in this section of the core clauses and terms in italics used in this section are identified elsewhere in this Contract Data.
7	Title	There is no reference to Contract Data in this section of the core clauses and terms in italics used in this section are identified elsewhere in this Contract Data.
8	Risks, liabilities, indemnities and insurance	
80.1	These are additional <i>Employer's</i> risks	Labour unrest (strike action)
84	Insurance cover by <i>Supplier</i>	Refer to Z 13.1 INSURANCE TABLE A of the <i>additional conditions of contract "Z" clauses</i>
87	Insurance cover by <i>Purchaser</i>	Refer to Z 13.2 INSURANCE TABLE B of the <i>additional conditions of contract "Z" clauses</i>
88.1	The <i>Supplier's</i> liability to the <i>Purchaser</i> for indirect or consequential loss, including loss of profit, revenue and goodwill is limited to	R0.0 (zero Rand)
88.5	The <i>end of liability date</i> is	One (1) year after expiry of contract
9	Termination and dispute resolution	
94.1	The <i>Adjudicator</i> is	the person selected from the ICE-SA Division (or its successor body) of the South African Institution of Civil Engineering Panel of Adjudicators by the Party intending to refer a dispute to him. (see www.ice-sa.org.za). If the Parties do not agree on an Adjudicator the Adjudicator will be appointed by the Arbitration Foundation of Southern Africa (AFSA).
94.2(3)	The <i>Adjudicator nominating body</i> is:	the Chairman of ICE-SA, a Division of the South African Institution of Civil Engineering, or its successor body (See www.ice-sa.org.za)
94.4(2)	The <i>tribunal</i> is:	arbitration

94.4(5)	The <i>arbitration procedure</i> is	the latest edition of Rules for the Conduct of Arbitrations published by The Association of Arbitrators (Southern Africa) or its successor body.
94.4(5)	The place where arbitration is to be held is	South Africa
	The person or organisation who will choose an arbitrator	the Chairman for the time being or his nominee of the Association of Arbitrators (Southern Africa) or its successor body.
	- if the Parties cannot agree a choice or - if the arbitration procedure does not state who selects an arbitrator, is	

10 Data for Option clauses

X1	Price adjustment for inflation		
X1.1	The <i>base date</i> for indices is	The base date is the month before the month in which the enquiry closed	
	The proportions used to calculate the Price Adjustment Factor are:	Proportion	linked to index for
		15%	Fixed
		50%	Material
		35%	Transport
		100%	
			Index prepared by
			Fixed Portion
			SEIFSA Table tbc
			SEIFSA Table L2B (Road Freight Costs)
X2	Changes in the law		
X2.1		is a compensation event if it occurs after the Contract Date	
X2.1	A change in the law of	is a compensation event if it occurs after the Contract Date	
X7	Delay damages		
X7.1	Delay damages for Delivery are	Delivery of	amount per day
		Incorrect items or late delivery	1% of purchase order value
X7.2	Delivery Lead Time	Four-Six (4-6) Weeks	
Z	The <i>additional conditions of contract</i> are		
		Z1 to Z15 always apply for Eskom	

Z1 Cession delegation and assignment

Z1.1 The *Supplier* does not cede, delegate or assign any of its rights or obligations to any person without the written consent of the *Purchaser*.

Z1.2 Notwithstanding the above, the *Purchaser* may on written notice to the *Supplier* cede and delegate its rights and obligations under this contract to any of its subsidiaries or any of its present divisions or operations which may be converted into separate legal entities as a result of the restructuring of the Electricity Supply Industry.

Z2 Joint ventures

Z2.1 If the *Supplier* constitutes a joint venture, consortium or other unincorporated grouping of two or more persons or organisations then these persons or organisations are deemed to be jointly and severally liable to the *Purchaser* for the performance of this contract.

Z2.2 Unless already notified to the *Purchaser*, the persons or organisations notify the *Supply Manager* within two weeks of the Contract Date of the key person who has the authority to bind the *Supplier* on their behalf.

Z2.3 The *Supplier* does not alter the composition of the joint venture, consortium or other unincorporated grouping of two or more persons without the consent of the *Purchaser* having been given to the *Supplier* in writing.

Z3 Change of Broad Based Black Economic Empowerment (B-BBEE) status

Z3.1 Where a change in the *Supplier's* legal status, ownership or any other change to his business composition or business dealings results in a change to the *Supplier's* B-BBEE status, the *Supplier* notifies the *Purchaser* within seven days of the change.

Z3.2 The *Supplier* is required to submit an updated verification certificate and necessary supporting documentation confirming the change in his B-BBEE status to the *Supply Manager* within thirty days of the notification or as otherwise instructed by the *Supply Manager*.

Z3.3 Where, as a result, the *Supplier's* B-BBEE status has decreased since the Contract Date the *Purchaser* may either re-negotiate this contract or alternatively, terminate the *Supplier's* obligation to Provide the Goods and Services.

Z3.4 Failure by the *Supplier* to notify the *Purchaser* of a change in its B-BBEE status may constitute a reason for termination. If the *Purchaser* terminates in terms of this clause, the procedures on termination are P1, P2 and P3 as stated in clause 92, and the amount due is A1 and A3 as stated in clause 93.

Z4 Confidentiality

Z4.1 The *Supplier* does not disclose or make any information arising from or in connection with this contract available to Others. This undertaking does not, however, apply to information which at the time of disclosure or thereafter, without default on the part of the *Supplier*, enters the public domain or to information which was already in the possession of the *Supplier* at the time of disclosure (evidenced by written records in existence at that time). Should the *Supplier* disclose information to Others in terms of clause 23.1, the *Supplier* ensures that the provisions of this clause are complied with by the recipient.

Z4.2 If the *Supplier* is uncertain about whether any such information is confidential, it is to be regarded as such until notified otherwise by the *Supply Manager*.

Z4.3 In the event that the *Supplier* is, at any time, required by law to disclose any such information which is required to be kept confidential, the *Supplier*, to the extent permitted by law prior to disclosure, notifies the *Purchaser* so that an appropriate protection order and/or any other action can be taken, if possible, prior to any disclosure. In the event that such protective order is not, or cannot, be obtained, then the *Supplier* may disclose that portion of the information which it is required to be disclosed by law and uses reasonable efforts to obtain assurances that confidential treatment will be afforded to the information so disclosed.

Z4.4 The taking of images (whether photographs, video footage or otherwise) of the *goods* or any portion thereof, in the course of Providing the Goods and Services and after Delivery, requires the prior written consent of the *Supply Manager*. All rights in and to all such images vests exclusively in the *Purchaser*.

Z4.5 The *Supplier* ensures that all his subcontractors abide by the undertakings in this clause.

Z5 Waiver and estoppel: Add to core clause 12.3:

Z5.1 Any extension, concession, waiver or relaxation of any action stated in this contract by the Parties, the *Supply Manager* or the *Adjudicator* does not constitute a waiver of rights and does not give rise to an estoppel unless the Parties agree otherwise and confirm such agreement in writing.

Z6 Health, safety and the environment: Add to core clause 25.4

Z6.1 The *Supplier* undertakes to take all reasonable precautions to maintain the health and safety of persons in and about the provision of the *goods* and execution of the *services*.

Without limitation the *Supplier*:

- warrants that the total of the Prices as at the Contract Date includes a sufficient amount for proper compliance with all applicable health & safety laws and regulations and the health and safety rules, guidelines and procedures provided for in this contract and generally for the proper maintenance of health & safety in and about the execution of supply and
- undertakes, in and about the execution of the supply, to comply with all applicable health & safety laws and regulations and rules, guidelines and procedures otherwise provided for under this contract and ensures that his Subcontractors, employees and others under the *Supplier's* direction and control, likewise observe and comply with the foregoing.

Z6.2 The *Supplier*, in and about the execution of the supply, complies with all applicable environmental laws and regulations and rules, guidelines and procedures otherwise provided for under this contract and ensures that his Subcontractors, employees and others under the *Supplier's* direction and control, likewise observe and comply with the foregoing.

Z7 Provision of a Tax Invoice and interest. Add to core clause 51

Z7.1 Within one week of receiving a payment certificate from the *Supply Manager* in terms of core clause 51.1, the *Supplier* provides the *Purchaser* with a tax invoice in accordance with the *Purchaser's* procedures stated in the Goods Information, showing the amount due for payment equal to that stated in the payment certificate.

Z7.2 If the *Supplier* does not provide a tax invoice in the form and by the time required by this contract, the time by when the *Purchaser* is to make a payment is extended by a period equal in time to the delayed submission of the correct tax invoice. Interest due by the *Purchaser* in terms of core clause 51.2 is then calculated from the delayed date by when payment is to be made.

Z7.3 The *Supplier* (if registered in South Africa in terms of the companies Act) is required to comply with the requirements of the Value Added Tax Act, no 89 of 1991 (as amended) and to include the *Purchaser's* VAT number 4740101508 on each invoice he submits for payment.

Z8 Notifying compensation events

Z8.1 Delete from the last sentence in core clause 61.3 the words, "unless the event arises from the *Supply Manager* giving an instruction, changing an earlier decision or correcting an

assumption”.

Z9 Purchaser's limitation of liability

- Z9.1 The *Purchaser's* liability to the *Supplier* for the *Supplier's* indirect or consequential loss is limited to R0.00 (zero Rand)
- Z9.2 The *Supplier's* entitlement under the indemnity in 83.1 is provided for in 60.1(12) and the *Purchaser's* liability under the indemnity is limited.

Z10 Termination: Add to core clause 91.1, at the second main bullet point, fourth sub-bullet point, after the words "against it":

- Z10.1 or had a business rescue order granted against it.

Z11 Addition to secondary Option X7 Delay damages (if applicable in this contract)

- Z11.1 If the amount due for the *Supplier's* payment of delay damages reaches the limits stated in this Contract Data for Option X7, the *Purchaser* may terminate the *Supplier's* obligation to Provide the Goods and Services using the same procedures and payment on termination as those applied for reasons R1 to R15 or R18 stated in the Termination Table.

Z12 Ethics

For the purposes of this Z-clause, the following definitions apply:

Affected Party means, as the context requires, any party, irrespective of whether it is the *Supplier* or a third party, such party's employees, agents, or Subcontractors or Subcontractor's employees, or any one or more of all these parties' relatives or friends,

Coercive Action means to harm or threaten to harm, directly or indirectly, an Affected Party or the property of an Affected Party, or to otherwise influence or attempt to influence an Affected Party to act unlawfully or illegally,

Collusive Action means where two or more parties co-operate to achieve an unlawful or illegal purpose, including to influence an Affected Party to act unlawfully or illegally,

Committing Party means, as the context requires, the *Supplier*, or any member thereof in the case of a joint venture, or its employees, agents, or Subcontractors or the Subcontractor's employees,

Corrupt Action means the offering, giving, taking, or soliciting, directly or indirectly, of a good or service to unlawfully or illegally influence the actions of an Affected Party,

Fraudulent Action means any unlawfully or illegally intentional act or omission that misleads, or attempts to mislead, an Affected Party, to obtain a financial or other benefit or to avoid an obligation or incurring an obligation,

Obstructive Action means a Committing Party unlawfully or illegally destroying, falsifying, altering or concealing information or making false statements to materially impede an investigation into allegations of Prohibited Action, and

Prohibited Action means any one or more of a Coercive Action, Collusive Action Corrupt Action, Fraudulent Action or Obstructive Action.

- Z12.1 A Committing Party may not take any Prohibited Action during the course of the procurement of this contract or in execution thereof.

Z12.2 The *Purchaser* may terminate the *Supplier's* obligation to Provide the Services if a Committing Party has taken such Prohibited Action and the *Supplier* did not take timely and appropriate action to prevent or remedy the situation, without limiting any other rights or remedies the *Purchaser* has. It is not required that the Committing Party had to have been found guilty, in court or in any other similar process, of such Prohibited Action before the *Purchaser* can terminate the *Supplier's* obligation to Provide the Services for this reason.

Z12.3 If the *Purchaser* terminates the *Supplier's* obligation to Provide the Services for this reason, the amounts due on termination are those intended in core clauses 92.1 and 92.2.

Z12.4 A Committing Party co-operates fully with any investigation pursuant to alleged Prohibited Action. Where the *Purchaser* does not have a contractual bond with the Committing Party, the *Supplier* ensures that the Committing Party co-operates fully with an investigation.

Z13 Insurance

Z 13.1 Replace core clause 84 with the following:

Insurance cover	84	
	84.1	When requested by a Party, the other Party provides certificates from his insurer or broker stating that the insurances required by this contract are in force.
	84.2	The <i>Supplier</i> provides the insurances stated in the Insurance Table A for events which are at the <i>Supplier's</i> risk from the <i>starting date</i> until the last <i>defects date</i> or a termination certificate has been issued.

INSURANCE TABLE A

Insurance against	Minimum amount of cover or minimum limit of indemnity
Loss of or damage to the <i>goods</i> , plant and materials	The replacement cost where not covered by the <i>Purchaser's</i> insurance. The <i>Purchaser's</i> policy deductible as at Contract Date, where covered by the <i>Purchaser's</i> insurance.
Liability for loss of or damage to property (except the <i>goods</i> , plant and materials and equipment) and liability for bodily injury to or death of a person (not an employee of the <i>Supplier</i>) caused by activity in connection with this contract	<u>Loss of or damage to property</u> <u>Purchaser's property</u> The replacement cost where not covered by the <i>Purchaser's</i> insurance. The <i>Purchaser's</i> policy deductible as at Contract Date, where covered by the <i>Purchaser's</i> insurance. <u>Other property</u> The replacement cost <u>Death of or bodily injury</u> The amount required by the applicable law.
Liability for death of or bodily injury to employees of the <i>Supplier</i> arising out of and in the course of their employment in connection with this contract	The amount required by the applicable law

Z 13.2 Replace core clause 87 with the following:

Insurance by the *Purchaser*

87

87.1 The *Purchaser* provides the insurances stated in the Insurance Table B

INSURANCE TABLE B

Insurance against or name of policy	Minimum amount of cover or minimum of indemnity
Assets All Risk	Per the insurance policy document
Contract Works insurance	Per the insurance policy document
Environmental Liability	Per the insurance policy document
General and Public Liability	Per the insurance policy document
Transportation (Marine)	Per the insurance policy document
Motor Fleet and Mobile Plant	Per the insurance policy document
Terrorism	Per the insurance policy document
Cyber Liability	Per the insurance policy document
Nuclear Material Damage and Business Interruption	Per the insurance policy document

Nuclear Material Damage Terrorism	Per the insurance policy document
--------------------------------------	-----------------------------------

Z14 Nuclear Liability

- Z14.1 The *Purchaser* is the operator of the Koeberg Nuclear Power Station (KNPS), a nuclear installation, as designated by the National Nuclear Regulator of the Republic of South Africa and is the holder of a nuclear licence in respect of the KNPS.
- Z14.2 The *Purchaser* is solely responsible for and indemnifies the *Supplier* or any other person against any and all liabilities which the *Supplier* or any person may incur arising out of or resulting from nuclear damage, as defined in Act 47 of 1999, save to the extent that any liabilities are incurred due to the unlawful intent of the *Supplier* or any other person or the presence of the *Supplier* or that person or any property of the *Supplier* or such person at or in the KNPS or on the KNPS site, without the permission of the *Purchaser* or of a person acting on behalf of the *Purchaser*.
- Z14.3 Subject to clause Z14.4 below, the *Purchaser* waives all rights of recourse, arising from the aforesaid, save to the extent that any claims arise or liability is incurred due or attributable to the unlawful intent of the *Supplier* or any other person, or the presence of the *Supplier* or that person or any property of the *Supplier* or such person at or in the KNPS or on the KNPS site, without the permission of the *Purchaser* or of a person acting on behalf of the *Purchaser*.
- Z14.4 The *Purchaser* does not waive its rights provided for in section 30 (7) of Act 47 of 1999, or any replacement section dealing with the same subject matter.
- Z14.5 The protection afforded by the provisions hereof shall be in effect until the KNPS is decommissioned.

Z15 Asbestos

For the purposes of this Z-clause, the following definitions apply:

- AAIA** means approved asbestos inspection authority.
- ACM** means asbestos containing materials.
- AL** means action level, i.e. a level of 50% of the OEL, i.e. 0.1 regulated asbestos fibres per ml of air measured over a 4-hour period. The value at which proactive actions is required in order to control asbestos exposure to prevent exceeding the OEL.
- Ambient Air** means breathable air in area of work with specific reference to breathing zone, which is defined to be a virtual area within a radius of approximately 30cm from the nose inlet.
- Compliance Monitoring** means compliance sampling used to assess whether or not the personal exposure of workers to regulated asbestos fibres is in compliance with the Standard's requirements for safe processing, handling, storing, disposal and phase-out of asbestos and asbestos containing material, equipment and articles.
- OEL** means occupational exposure limit.
- Parallel Measurements** means measurements performed in parallel, yet separately, to existing measurements to verify validity of results.

Safe Levels	means airborne asbestos exposure levels conforming to the Standard's requirements for safe processing, handling, storing, disposal and phase-out of asbestos and asbestos containing material, equipment and articles.
Standard	means the <i>Purchaser's</i> Asbestos Standard 32-303: Requirements for Safe Processing, Handling, Storing, Disposal and Phase-out of Asbestos and Asbestos Containing Material, Equipment and Articles.
SANAS	means the South African National Accreditation System.
TWA	means the average exposure, within a given workplace, to airborne asbestos fibres, normalised to the baseline of a 4-hour continuous period, also applicable to short term exposures, i.e. 10-minute TWA.

- Z15.1 The *Purchaser* ensures that the Ambient Air in the area where the *Supplier* will Provide the Services conforms to the acceptable prescribed South African standard for asbestos, as per the regulations published in GNR 155 of 10 February 2002, under the Occupational Health and Safety Act, 1993 (Act 85 of 1993) ("Asbestos Regulations"). The OEL for asbestos is 0.2 regulated asbestos fibres per millilitre of air as a 4-hour TWA, averaged over any continuous period of four hours, and the short-term exposure limit of 0.6 regulated asbestos fibres per millilitre of air as a 10-minute TWA, averaged over any 10 minutes, measured in accordance with HSG248 and monitored according to HSG173 and OESSM.
- Z15.2 Upon written request by the *Supplier*, the *Purchaser* certifies that these conditions prevail. All measurements and reporting are affected by an independent, competent, and certified occupational hygiene inspection body, i.e. a SANAS accredited, and Department of Employment and Labour approved AAIA. The *Supplier* may perform Parallel Measurements and related control measures at the *Supplier's* expense. For the purposes of compliance, the results generated from Parallel Measurements are evaluated only against South African statutory limits as detailed in clause Z15.1. Control measures conform to the requirements stipulated in the AAIA-approved asbestos work plan.
- Z15.3 The *Purchaser* manages asbestos and ACM according to the Standard.
- Z15.4 In the event that any asbestos is identified while Providing the Services, a risk assessment is conducted and if so required, with reference to possible exposure to an airborne concentration of above the AL for asbestos, immediate control measures are implemented and relevant air monitoring conducted in order to declare the area safe.
- Z15.5 The *Supplier's* personnel are entitled to stop working and leave the contaminated area forthwith until such time that the area of concern is declared safe by either Compliance Monitoring or an AAIA approved control measure intervention, for example, per the emergency asbestos work plan, if applicable.
- Z15.6 The *Supplier* continues to Provide the Services, without additional control measures presented, on presentation of Safe Levels. The contractually agreed dates to Provide the Services, including the Completion Date, are adjusted accordingly. The contractually agreed dates are extended by the notification periods required by regulations 3 and 21 of the Asbestos Regulations.
- Z15.7 Any removal and disposal of asbestos, asbestos containing materials and waste, is done by a registered asbestos contractor, instructed by the *Purchaser* at the *Purchaser's* expense, and conducted in line with South African legislation.

Annexure A: Supply Requirements

[Notes: The example given in the NEC3 Supply Contract Guidance Notes pages 15 to 20 inclusive is based on Incoterms 2000. However, users will probably wish to use Incoterms 2010 which the details below are based on. Users may need to adjust the information to comply with actual requirements. First decide whether Incoterms will be used or not, then delete the arrangement below which does not apply and delete these notes]

The Supply Requirements for this contract are based on the use of INCOTERMS:

The *Supplier* supplies the *goods* in accordance with INCOTERMS 2010² as follows:

[Select the group and then term within the group which applies and state the applicable delivery place. Delete all the other groups and this note]

Group	Category	Term	Delivery Place
E	departure	EXW	
F	main carriage unpaid	FCA, FAS, FOB	
C	main carriage paid	CFR, CIF, CPT, CIP	
D	arrival	DAT, DAP, DDP	

The Parties obligations described in Incoterms for the category and term selected are now incorporated into this contract as part of the Supply Requirements and hence the Goods Information.

The obligations of seller and buyer for the selected Incoterm determine each Party's costs, risks and insurance requirements incidental to the supply and transport of the *goods* from *Supplier* to *Purchaser*.

For each of the thirteen terms, Incoterms set out obligations of the seller (the *Supplier*) in ten paragraphs identified as A1 to A10 and the corresponding obligations of the buyer (the *Purchaser*) in paragraphs B1 to B10. These obligations cover the following subjects:

A	The <i>Supplier's</i> obligations	B	The <i>Purchaser's</i> obligations
A1	Provision of goods in conformity with contract	B1	Payment of the price
A2	Licences, authorisations and formalities	B2	Licences, authorisations and formalities
A3	Contracts of carriage and insurance	B3	Contracts of carriage and insurance
A4	Delivery	B4	Taking delivery
A5	Transfer of risks	B5	Transfer of risks
A6	Division of costs	B6	Division of costs
A7	Notice to the buyer	B7	Notice to the seller
A8	Proof of delivery, transport document or equivalent electronic message	B8	Proof of delivery, transport document or equivalent electronic message
A9	Checking - packing - marking	B9	Inspection of goods
A10	Other obligations	B10	Other obligations

[Should there be a need to amplify any of the published obligations listed above for the chosen INCOTERM, add them here.]

All other information NOT pertinent to the above is given in the balance of the Goods Information

² International Chamber of Commerce, Incoterms 2010, Paris, January 2011

The Supply Requirements for this contract are as follows:

[Use these when INCOTERMS do not apply].

1. The requirements for the supply are	PPE-Accessories and Boots	
2. The requirements for transport are	The <i>Supplier</i> is responsible for transporting the goods to Site. The <i>Supplier</i> takes responsibility of the goods while in transit i.e. insurances etc. Goods are to be off loaded at Arnot Power Station Main Stores Receiving	
3. The delivery place is	Eskom Arnot Power Station	
4. Actions of the Parties during supply	Action	Party which does it
	Giving notice of Delivery	<i>Supplier</i>
	Checking packing and marking before dispatch	<i>Supplier</i>
	Contracting for transport	<i>Supplier</i>
	Pay costs of transport	<i>Supplier</i>
	Arrange access to delivery place	<i>Supplier</i>
	Loading the <i>goods</i>	<i>Supplier</i>
	Unloading the <i>goods</i>	<i>Supplier</i>
For international procurement	Undertake export requirements	<i>Supplier</i>
	Undertake import requirements	<i>Supplier</i>
5. Information to be provided by the <i>Supplier</i>	Title of document	
	Packing lists for cases and their contents	
	Copy of invoice for the <i>goods</i>	
	Delivery Note	
	Test results and maintenance manuals	

All other information NOT pertinent to the above is given in the balance of the Goods Information

C1.2 Contract Data

Part two - Data provided by the *Supplier*

Notes to a tendering supplier:

1. Please read both the NEC3 Supply Contract (SC3)¹ and the relevant parts of its Guidance Notes (SC3-GN)² in order to understand the implications of this Data which the tenderer is required to complete.
2. The number of the clause which requires the data is shown in the left-hand column for each statement however other clauses may also use the same data
3. Where a form field like this [] appears, data is required to be inserted relevant to the option selected. Click on the form field **once** and type in the data. Otherwise, complete by hand and in ink.

Completion of the data in full, according to Options chosen, is essential to create a complete contract.

Clause	Statement	Data
10.1	The <i>Supplier</i> is (Name): Address Tel No. Fax No.	
11.2(8)	The Goods Information for the <i>Supplier's</i> design is in:	Annexure A
11.2(11)	The tendered total of the Prices is	R (in words)
11.2(12)	The <i>price schedule</i> is in:	
11.2(14)	The following matters will be included in the Risk Register	N/A
25.2	The restrictions to access for the <i>Supply Manager</i> and Others to work being done for this contract are	None
30.1	The <i>delivery date</i> of the <i>goods</i> and <i>services</i> is:	Stated in every Purchase Order
63.2	The <i>percentage for overheads and profit</i> added to the Defined Cost is	N/A

¹ Either April 2013 or December 2009 Edition as stated by *Purchaser* in Contract Data part 1.

² Available from Engineering Contract Strategies Tel 011 803 3008, Fax 086 539 1902, or www.ecs.co.za

PART 2: PRICING DATA

NEC3 Supply Contract

Document reference	Title	No of pages
	This cover page	1
C2.1	Pricing Assumptions	2
C2.2	<i>The Price Schedule</i>	91
	Total number of pages	94

C2.1 Pricing assumptions

1. How goods and services are priced and assessed for payment

Clause 11 in NEC3 Supply Contract, (SC3) core clauses states:

Identified and defined terms	11 11.2	(11) The Prices are the amounts stated in the price column of the Price Schedule. Where a quantity is stated for an item in the Price Schedule, the Price is calculated by multiplying the quantity by the rate. (12) The Price Schedule is the <i>price schedule</i> unless later changed in accordance with this contract.
Assessing the amount due	50.2	The amount due is <ul style="list-style-type: none">the Price for each lump sum item in the Price Schedule which the <i>Supplier</i> has completed,where a quantity is stated for an item in the Price Schedule, an amount calculated by multiplying the quantity which the <i>Supplier</i> has completed by the rate,plus other amounts to be paid to the <i>Supplier</i>,less amounts to be paid by or retained from the <i>Supplier</i>. <p>Any tax which the law requires the <i>Purchaser</i> to pay to the <i>Supplier</i> is included in the amount due.</p>

This confirms that the Supply Contract is a priced contract where the Prices are derived from a list of items of *goods* and *services* which can be priced as lump sums or as expected quantities of *goods* and *services* multiplied by a rate, or a mix of both.

2. Function of the Price Schedule

Clause 53.1 states: "Information in the Price Schedule is not Goods Information". This confirms that instructions to do work or how it is to be done are not included in the Price Schedule but in the Goods Information. This is further confirmed by Clause 20.1 which states, "The *Supplier* Provides the Goods and Services in accordance with the Goods Information". Hence the *Supplier* does **not** Provide the Goods and Services in accordance with the Price Schedule. The Price Schedule is only a pricing document.

3. Preparing the *price schedule*

Items in the *price schedule* may have been inserted by the *Purchaser* and the tendering supplier should insert any additional items which he considers necessary. Whichever party provides the items in the *price schedule* the total of the Prices is assumed to be fully inclusive of everything necessary to Provide the Goods and Services as described at the time of entering into this contract.

It will be assumed that the tendering supplier has

- Read Pages 8, 11, 12 and Appendix 5 of the SC3 Guidance Notes before preparing the *price schedule*;
- Included in his Prices and rates for correction of Defects (core clause 43.1) as there is no compensation event for this unless the Defect is due to a *Supplier's* risk;
- Spread the cost of doing work he chooses not to list as separate items in the *price schedule*

across other Prices and rates in order to fulfil the obligation to Provide the Goods and Services for the tendered total of the Prices;

- Understood that there is no adjustment to lump sum prices in the *price schedule* if the amount, or quantity, of work within that lump sum item later turns out to be different to that which the *Supplier* estimated at time of tender. The only basis for a change to the Prices is as a result of a compensation event per clause 60.1;
- Understood that the *Supplier* does not have to allow in his Prices and rates for matters that may arise as a result of a compensation event.

3.1. Format of the *price schedule*

Entries in the first four columns in the *price schedule* in section C2.2 are made either by the *Purchaser* or the tendering supplier.

If the *Supplier* is to be paid an amount for the item which is not adjusted if the quantity of work in the item changes, the tendering supplier enters the amount in the Price column only, the Unit, Quantity and Rate columns being left blank.

If the *Supplier* is to be paid an amount for the item which is the rate for the item multiplied by the quantity completed, the tendering *Supplier* enters the rate which is then multiplied by the Quantity to produce the Price, which is also entered.

If the *Supplier* is to be paid an amount for an item proportional to the length of time for which the *goods* and *services* are provided, a unit of time is stated in the Unit column and the length of time (as a quantity of the stated units of time is stated in the Quantity column

C2.2 the *price schedule*

Item	Description	Unit	Quantity	Rate	Amount
1	<p>COAT, DUST: TYPE: GENERAL PURPOSE; SIZE: 102 CM; MATERIAL: COTTON; COLOR: BLUE NAVY PANTONE 19-3920; SPECIFICATION: 240-44175132; MATERIAL: PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; LENGTH 3/4; POCKET: FRONT BUTTONS; TWO FRONT POCKETS; SLIT AT BACK; BUTTONS ACCEPTABLE FOUR-HOLE; DYED PLASTICS BUTTONS COMPLY WITH SANS 1457 COATS SHALL FASTEN WITH BUTTON AND BUTTONHOLE AND SHALL BE EQUIDISTANTLY SPACED; BUTTONS SECURED TO POSITIONS CORRESPONDING TO BUTTONHOLES; THE PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; THE BACK SHALL HAVE A SEAM DOWN THE CENTRE WITH A VENT IN THE LOWER PART OF THE SEAM; THE VENT SHALL HAVE AN OVERLAP OF 40 MM AND SHALL BE SECURELY TACKED AND BAR-TACKED AT THE TOP; A HANGER LOOP OF OUTER DOUBLE FOLDED MATERIAL OF FINISHED LENGTH AT LEAST 70 MM AND OF FINISHED WIDTH AT LEAST 10 MM; SHALL BE SECURELY SEWN IN WITH THE COLLAR AT THE BACK NECK ON THE INSIDE; THE BOTTOM OF THE COATS AND THE LOWER EDGE OF PLAIN SLEEVE CUFFS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 15 MM; POCKET MOUTHS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 20 MM; EACH GARMENT SHALL HAVE A LABEL SECURELY ATTACHED AT THE CENTRE BACK NECK BELOW THE COLLAR SEAM ON THE INSIDE OF THE GARMENT; THE LABEL SHALL PROVIDE THE FOLLOWING INFORMATION PRINTED IN LEGIBLE AND INDELIBLE BLOCK LETTERS OF HEIGHT AT LEAST 3 MM; MANUFACTURER'S NAME OR TRADEMARK; CHEST SIZE SANS 434:2011 EDITION 5 22; YEAR OF MANUFACTURE; VAT REGISTRATION NUMBER; COUNTRY OF ORIGIN; ITEM TO BEAR SABS MARK OF APPROVAL REFERENCE SANS 434:2011 FIGURE 3 COATS</p>	EA	300		
2	<p>COAT, DUST: TYPE: GENERAL PURPOSE; SIZE: 112 CM; MATERIAL: COTTON; COLOR: BLUE NAVY PANTONE 19-3920; SPECIFICATION: 240-44175132; MATERIAL: PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; LENGTH 3/4; POCKET: FRONT BUTTONS; TWO FRONT POCKETS; SLIT AT BACK; BUTTONS ACCEPTABLE FOUR-HOLE; DYED PLASTICS BUTTONS COMPLY WITH SANS 1457 COATS SHALL FASTEN WITH BUTTON AND BUTTONHOLE AND SHALL BE EQUIDISTANTLY SPACED; BUTTONS SECURED TO POSITIONS CORRESPONDING TO BUTTONHOLES; THE PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST</p>	EA	300		

Item	Description	Unit	Quantity	Rate	Price
	<p>POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; THE BACK SHALL HAVE A SEAM DOWN THE CENTRE WITH A VENT IN THE LOWER PART OF THE SEAM; THE VENT SHALL HAVE AN OVERLAP OF 40 MM AND SHALL BE SECURELY TACKED AND BAR-TACKED AT THE TOP; A HANGER LOOP OF OUTER DOUBLE FOLDED MATERIAL OF FINISHED LENGTH AT LEAST 70 MM AND OF FINISHED WIDTH AT LEAST 10 MM; SHALL BE SECURELY SEWN IN WITH THE COLLAR AT THE BACK NECK ON THE INSIDE; THE BOTTOM OF THE COATS AND THE LOWER EDGE OF PLAIN SLEEVE CUFFS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 15 MM; POCKET MOUTHS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 20 MM; EACH GARMENT SHALL HAVE A LABEL SECURELY ATTACHED AT THE CENTRE BACK NECK BELOW THE COLLAR SEAM ON THE INSIDE OF THE GARMENT; THE LABEL SHALL PROVIDE THE FOLLOWING INFORMATION PRINTED IN LEGIBLE AND INDELIBLE BLOCK LETTERS OF HEIGHT AT LEAST 3 MM; MANUFACTURER'S NAME OR TRADEMARK; CHEST SIZE SANS 434:2011 EDITION 5 22; YEAR OF MANUFACTURE; VAT REGISTRATION NUMBER; COUNTRY OF ORIGIN; ITEM TO BEAR SABS MARK OF APPROVAL REFERENCE SANS 434:2011 FIGURE 3 COATS</p>				
3	<p>COAT, DUST: TYPE: GENERAL PURPOSE; SIZE: 107 CM; MATERIAL: COTTON; COLOR: BLUE NAVY PANTONE 19-3920; SPECIFICATION: 240-44175132; MATERIAL: PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; LENGTH 3/4; POCKET: FRONT BUTTONS; TWO FRONT POCKETS; SLIT AT BACK; BUTTONS ACCEPTABLE FOUR-HOLE; DYED PLASTICS BUTTONS COMPLY WITH SANS 1457 COATS SHALL FASTEN WITH BUTTON AND BUTTONHOLE AND SHALL BE EQUIDISTANTLY SPACED; BUTTONS SECURED TO POSITIONS CORRESPONDING TO BUTTONHOLES; THE PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; THE BACK SHALL HAVE A SEAM DOWN THE CENTRE WITH A VENT IN THE LOWER PART OF THE SEAM; THE VENT SHALL HAVE AN OVERLAP OF 40 MM AND SHALL BE SECURELY TACKED AND BAR-TACKED AT THE TOP; A HANGER LOOP OF OUTER DOUBLE FOLDED MATERIAL OF FINISHED LENGTH AT LEAST 70 MM AND OF FINISHED WIDTH AT LEAST 10 MM; SHALL BE SECURELY SEWN IN WITH THE COLLAR AT THE BACK NECK ON THE INSIDE; THE BOTTOM OF THE COATS AND THE LOWER EDGE OF PLAIN SLEEVE CUFFS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 15 MM; POCKET MOUTHS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 20 MM; EACH GARMENT SHALL HAVE A LABEL SECURELY ATTACHED AT THE CENTRE BACK NECK BELOW THE COLLAR SEAM ON THE INSIDE OF THE GARMENT; THE LABEL SHALL PROVIDE THE FOLLOWING INFORMATION PRINTED IN LEGIBLE AND INDELIBLE BLOCK LETTERS OF HEIGHT AT LEAST 3 MM; MANUFACTURER'S</p>	EA	300		

Item	Description	Unit	Quantity	Rate	Amount
	NAME OR TRADEMARK; CHEST SIZE SANS 434:2011 EDITION 5 22; YEAR OF MANUFACTURE VAT REGISTRATION NUMBER; COUNTRY OF ORIGIN; ITEM TO BEAR SABS MARK OF APPROVAL REFERENCE SANS 434:2011 FIGURE 3 COATS				
4	COAT, DUST: TYPE: GENERAL PURPOSE; SIZE: 97 CM; MATERIAL: COTTON; COLOR: BLUE NAVY PANTONE 19-3920; SPECIFICATION: 240-44175132; MATERIAL: PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; LENGTH 3/4; POCKET: FRONT BUTTONS; TWO FRONT POCKETS; SLIT AT BACK; BUTTONS ACCEPTABLE FOUR-HOLE; DYED PLASTICS BUTTONS COMPLY WITH SANS 1457 COATS SHALL FASTEN WITH BUTTON AND BUTTONHOLE AND SHALL BE EQUIDISTANTLY SPACED; BUTTONS SECURED TO POSITIONS CORRESPONDING TO BUTTONHOLES; THE PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; THE BACK SHALL HAVE A SEAM DOWN THE CENTRE WITH A VENT IN THE LOWER PART OF THE SEAM; THE VENT SHALL HAVE AN OVERLAP OF 40 MM AND SHALL BE SECURELY TACKED AND BAR-TACKED AT THE TOP; A HANGER LOOP OF OUTER DOUBLE FOLDED MATERIAL OF FINISHED LENGTH AT LEAST 70 MM AND OF FINISHED WIDTH AT LEAST 10 MM; SHALL BE SECURELY SEWN IN WITH THE COLLAR AT THE BACK NECK ON THE INSIDE; THE BOTTOM OF THE COATS AND THE LOWER EDGE OF PLAIN SLEEVE CUFFS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 15 MM; POCKET MOUTHS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 20 MM; EACH GARMENT SHALL HAVE A LABEL SECURELY ATTACHED AT THE CENTRE BACK NECK BELOW THE COLLAR SEAM ON THE INSIDE OF THE GARMENT; THE LABEL SHALL PROVIDE THE FOLLOWING INFORMATION PRINTED IN LEGIBLE AND INDELIBLE BLOCK LETTERS OF HEIGHT AT LEAST 3 MM; MANUFACTURER'S NAME OR TRADEMARK; CHEST SIZE SANS 434:2011 EDITION 5 22; YEAR OF MANUFACTURE; VAT REGISTRATION NUMBER; COUNTRY OF ORIGIN; ITEM TO BEAR SABS MARK OF APPROVAL REFERENCE SANS 434:2011 FIGURE 3 COATS	EA	300		
5	COAT, DUST: TYPE: GENERAL PURPOSE; SIZE: 87 CM; MATERIAL: COTTON; COLOR: BLUE NAVY PANTONE 19-3920; SPECIFICATION: 240-44175132; MATERIAL: PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; LENGTH 3/4; POCKET: FRONT BUTTONS; TWO FRONT POCKETS; SLIT AT BACK; BUTTONS ACCEPTABLE FOUR-HOLE; DYED PLASTICS BUTTONS COMPLY WITH SANS 1457 COATS SHALL FASTEN WITH BUTTON AND BUTTONHOLE AND SHALL BE EQUIDISTANTLY SPACED; BUTTONS SECURED TO POSITIONS CORRESPONDING TO BUTTONHOLES; THE PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET AND SHALL	EA	300		

Item	Description	Unit	Quantity	Rate	Price
	<p>BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; THE BACK SHALL HAVE A SEAM DOWN THE CENTRE WITH A VENT IN THE LOWER PART OF THE SEAM; THE VENT SHALL HAVE ANOVERLAP OF 40 MM AND SHALL BE SECURELY TACKED AND BAR-TACKED AT THE TOP; A HANGER LOOP OF OUTER DOUBLE FOLDED MATERIAL OF FINISHED LENGTH AT LEAST 70 MM AND OF FINISHED WIDTH AT LEAST 10 MM; SHALL BE SECURELY SEWN IN WITH THE COLLAR AT THE BACK NECK ON THE INSIDE; THE BOTTOM OF THE COATS AND THE LOWER EDGE OF PLAIN SLEEVE CUFFS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 15 MM; POCKET MOUTHS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 20 MM; EACH GARMENT SHALL HAVE A LABEL SECURELY ATTACHED AT THE CENTRE BACK NECK BELOW THE COLLAR SEAM ON THE INSIDE OF THE GARMENT; THE LABEL SHALL PROVIDE THE FOLLOWING INFORMATION PRINTED IN LEGIBLE AND INDELIBLE BLOCK LETTERS OF HEIGHT AT LEAST 3 MM; MANUFACTURER'S NAME OR TRADEMARK; CHEST SIZE SANS 434:2011 EDITION 5 22; YEAR OF MANUFACTURE; VAT REGISTRATION NUMBER; COUNTRY OF ORIGIN; ITEM TO BEAR SABS MARK OF APPROVAL REFERENCE SANS 434:2011 FIGURE 3 COATS</p>				
6	<p>COAT, DUST: TYPE: GENERAL PURPOSE; SIZE: 117 CM; MATERIAL: COTTON; COLOR: BLUE NAVY PANTONE 19-3920; SPECIFICATION: 240-44175132; MATERIAL: PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; LENGTH 3/4; POCKET: FRONT BUTTONS; TWO FRONT POCKETS; SLIT AT BACK; BUTTONS ACCEPTABLE FOUR-HOLE; DYED PLASTICS BUTTONS COMPLY WITH SANS 1457 COATS SHALL FASTEN WITH BUTTON AND BUTTONHOLE AND SHALL BE EQUIDISTANTLY SPACED; BUTTONS SECURED TO POSITIONS CORRESPONDING TO BUTTONHOLES; THE PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; THE BACK SHALL HAVE A SEAM DOWN THE CENTRE WITH A VENT IN THE LOWER PART OF THE SEAM; THE VENT SHALL HAVE AN OVERLAP OF 40 MM AND SHALL BE SECURELY TACKED AND BAR-TACKED AT THE TOP; A HANGER LOOP OF OUTER DOUBLE FOLDED MATERIAL OF FINISHED LENGTH AT LEAST 70 MM AND OF FINISHED WIDTH AT LEAST 10 MM; SHALL BE SECURELY SEWN IN WITH THE COLLAR AT THE BACK NECK ON THE INSIDE; THE BOTTOM OF THE COATS AND THE LOWER EDGE OF PLAIN SLEEVE CUFFS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 15 MM; POCKET MOUTHS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 20 MM; EACH GARMENT SHALL HAVE A LABEL SECURELY ATTACHED AT THE CENTRE BACK NECK BELOW THE COLLAR SEAM ON THE INSIDE OF THE GARMENT; THE LABEL SHALL PROVIDE THE FOLLOWING INFORMATION PRINTED IN LEGIBLE AND INDELIBLE BLOCK</p>	EA	300		

Item	Description	Unit	Quantity	Rate	Price
	LETTERS OF HEIGHT AT LEAST 3 MM; MANUFACTURER'S NAME OR TRADEMARK; CHEST SIZE SANS 434:2011 EDITION 5 22; YEAR OF MANUFACTURE; VAT REGISTRATION NUMBER; COUNTRY OF ORIGIN; ITEM TO BEAR SABS MARK OF APPROVAL REFERENCE SANS 434:2011 FIGURE 3 COATS				
7	COAT, DUST: TYPE: GENERAL PURPOSE; SIZE: 122 CM; MATERIAL: COTTON; COLOR: BLUE NAVY PANTONE 19-3920; SPECIFICATION: 240-44175132; MATERIAL: PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; LENGTH 3/4; POCKET: FRONT BUTTONS; TWO FRONT POCKETS; SLIT AT BACK; BUTTONS ACCEPTABLE FOUR-HOLE; DYED PLASTICS BUTTONS COMPLY WITH SANS 1457 COATS SHALL FASTEN WITH BUTTON AND BUTTONHOLE AND SHALL BE EQUIDISTANTLY SPACED; BUTTONS SECURED TO POSITIONS CORRESPONDING TO BUTTONHOLES; THE PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; THE BACK SHALL HAVE A SEAM DOWN THE CENTRE WITH A VENT IN THE LOWER PART OF THE SEAM; THE VENT SHALL HAVE AN OVERLAP OF 40 MM AND SHALL BE SECURELY TACKED AND BAR-TACKED AT THE TOP; A HANGER LOOP OF OUTER DOUBLE FOLDED MATERIAL OF FINISHED LENGTH AT LEAST 70 MM AND OF FINISHED WIDTH AT LEAST 10 MM; SHALL BE SECURELY SEWN IN WITH THE COLLAR AT THE BACK NECK ON THE INSIDE; THE BOTTOM OF THE COATS AND THE LOWER EDGE OF PLAIN SLEEVE CUFFS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 15 MM; POCKET MOUTHS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 20 MM; EACH GARMENT SHALL HAVE A LABEL SECURELY ATTACHED AT THE CENTRE BACK NECK BELOW THE COLLAR SEAM ON THE INSIDE OF THE GARMENT; THE LABEL SHALL PROVIDE THE FOLLOWING INFORMATION PRINTED IN LEGIBLE AND INDELIBLE BLOCK LETTERS OF HEIGHT AT LEAST 3 MM; MANUFACTURER'S NAME OR TRADEMARK; CHEST SIZE SANS 434:2011 EDITION 5 22; YEAR OF MANUFACTURE; VAT REGISTRATION NUMBER; COUNTRY OF ORIGIN; ITEM TO BEAR SABS MARK OF APPROVAL REFERENCE SANS 434:2011 FIGURE 3 COATS	EA	300		
8	JACKET, UTILITY: TYPE: OPERATING; SIZE: 147 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT	EA	100		

Item	Description	Unit	Quantity	Rate	Price
	<p>PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER;THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1</p>				
9	<p>JACKET, UTILITY: TYPE: OPERATING; SIZE: 137 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45</p>	EA	100		

Item	Description	Unit	Quantity	Rate	Price
	<p>MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1</p>				
10	<p>JACKET, UTILITY: TYPE: OPERATING; SIZE: 157 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES</p>	EA	100		

Item	Description	Unit	Quantity	Rate	Price
	<p>SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 5</p>				
11	<p>TROUSERS: TYPE: MEN LONG; SIZE: 77 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE</p>	EA	1500		

Item	Description	Unit	Quantity	Rate	Price
	ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION				
12	TROUSERS: TYPE: MEN LONG; SIZE: 82 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION	EA	2000		
13	TROUSERS: TYPE: MEN LONG; SIZE: 87 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION	EA	2000		
14	TROUSERS: TYPE: MEN LONG; SIZE: 92 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION	EA	3000		
15	TROUSERS: TYPE: MEN LONG; SIZE: 97 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434	EA	3000		

Item	Description	Unit	Quantity	Rate	Price
	(DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION				
16	TROUSERS: TYPE: MEN LONG; SIZE: 102 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132	EA	3000		
17	TROUSERS: TYPE: MEN LONG; SIZE: 107 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION	EA	2000		
18	TROUSERS: TYPE: MEN LONG; SIZE: 112 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION	EA	1000		

Item	Description	Unit	Quantity	Rate	Price
19	TROUSERS: TYPE: MEN LONG; SIZE: 117 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION	EA	500		
20	TROUSERS: TYPE: MEN LONG; SIZE: 122 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION	EA	300		
21	TROUSERS: TYPE: MEN LONG; SIZE: 127 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION	EA	200		
22	TROUSERS: TYPE: MEN LONG; SIZE: 132 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE	EA	50		

Item	Description	Unit	Quantity	Rate	Price
	ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION				
23	TROUSERS: TYPE: MEN LONG; SIZE: 137 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION	EA	30		
24	TROUSERS: TYPE: MEN LONG; SIZE: 142 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION	EA	20		
25	TROUSERS: TYPE: MEN LONG; SIZE: 147 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION	EA	20		
26	JACKET, UTILITY: TYPE: OPERATING; SIZE: 87 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING	EA	1500		

Item	Description	Unit	Quantity	Rate	Price
	<p>METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER;THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1</p>				

Item	Description	Unit	Quantity	Rate	Price
27	<p>JACKET, UTILITY: TYPE: OPERATING; SIZE: 97 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1</p>	EA	1500		

Item	Description	Unit	Quantity	Rate	Price
28	<p>JACKET, UTILITY: TYPE: OPERATING; SIZE: 107 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1</p>	EA	2000		

Item	Description	Unit	Quantity	Rate	Price
29	<p>JACKET, UTILITY: TYPE: OPERATING; SIZE: 117 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1</p>	EA	2000		

Item	Description	Unit	Quantity	Rate	Price
30	<p>JACKET, UTILITY: TYPE: OPERATING; SIZE: 122 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1</p>	EA	1000		

Item	Description	Unit	Quantity	Rate	Price
31	<p>JACKET, UTILITY: TYPE: OPERATING; SIZE: 132 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1</p>	EA	300		

Item	Description	Unit	Quantity	Rate	Price
32	<p>JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 87 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM</p>	EA	300		
33	<p>JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 97 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS;</p>	EA	300		

Item	Description	Unit	Quantity	Rate	Price
	<p>POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM</p>				
34	<p>JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 107 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN</p>	EA	400		

Item	Description	Unit	Quantity	Rate	Amount
	<p>CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM</p>				
35	<p>JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 117 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE</p>	EA	300		

Item	Description	Unit	Quantity	Rate	Amount
	POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM				
36	JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 122 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM	EA	200		
37	JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 132 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS;	EA	100		

Item	Description	Unit	Quantity	Rate	Amount
	<p>POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM</p>				
38	<p>JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 137 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE</p>	EA	50		

Item	Description	Unit	Quantity	Rate	Amount
	<p>PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN</p>				
	<p>IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM</p>				
39	<p>JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 147 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH</p>	EA	10		

Item	Description	Unit	Quantity	Rate	Amount
	LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM				
40	JACKET, UTILITY: TYPE: OPERATING; SIZE: 77 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER;THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE	EA	200		

Item	Description	Unit	Quantity	Rate	Amount
	POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1				
41	JACKET, UTILITY: TYPE: OPERATING; SIZE: 82 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER;THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH	EA	250		

Item	Description	Unit	Quantity	Rate	Amount
	LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1				
42	JACKET, UTILITY: TYPE: OPERATING; SIZE: 102 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER;THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT	EA	2000		

Item	Description	Unit	Quantity	Rate	Amount
	LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1				
43	JACKET, UTILITY: TYPE: OPERATING; SIZE: 112 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH	EA	2000		

Item	Description	Unit	Quantity	Rate	Amount
	AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1				
44	JACKET, UTILITY: TYPE: OPERATING; SIZE: 127 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER;THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A	EA	1000		

Item	Description	Unit	Quantity	Rate	Amount
	BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1				
45	JACKET, UTILITY: TYPE: OPERATING; SIZE: 142 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH	EA	200		

Item	Description	Unit	Quantity	Rate	Amount
	<p>OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1</p>				
46	<p>JACKET, UTILITY: TYPE: OPERATING; SIZE: 152 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER;THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A</p>	EA	50		

Item	Description	Unit	Quantity	Rate	Amount
	BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1				
47	JACKET, UTILITY: TYPE: OPERATING; SIZE: 92 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND	EA	1500		

Item	Description	Unit	Quantity	Rate	Amount
	<p>GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1</p>				
48	<p>JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 77 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM</p>	EA	500		

Item	Description	Unit	Quantity	Rate	Amount
49	JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 82 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT	EA	500		
	HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM				
50	JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 92 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND	EA	500		

Item	Description	Unit	Quantity	Rate	Amount
	<p>THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM</p>				
51	<p>JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 102 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED</p>	EA	500		

Item	Description	Unit	Quantity	Rate	Amount
	<p>MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM</p>				
52	<p>JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 127 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM</p>	EA	200		

Item	Description	Unit	Quantity	Rate	Amount
53	<p>JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 142 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM</p>	EA	200		
54	<p>JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 112 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL</p>	EA	200		

Item	Description	Unit	Quantity	Rate	Amount
	<p>SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM</p>				
55	<p>COVERALL: TYPE: ACID/ALKALI; SIZE: 77 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND</p>	EA	1000		

Item	Description	Unit	Quantity	Rate	Amount
	<p>SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>				
56	<p>COVERALL: TYPE: ACID/ALKALI; SIZE: 82 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE</p>	EA	1000		

Item	Description	Unit	Quantity	Rate	Amount
	<p>SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>				
57	<p>COVERALL: TYPE: ACID/ALKALI; SIZE: 87 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM;</p>	EA	1000		

Item	Description	Unit	Quantity	Rate	Amount
	<p>SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>				

Item	Description	Unit	Quantity	Rate	Amount
58	<p>COVERALL: TYPE: ACID/ALKALI; SIZE: 92 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO</p>	EA	1000		
	<p>WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM</p>				

Item	Description	Unit	Quantity	Rate	Amount
	<p>ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>				
59	<p>COVERALL: TYPE: ACID/ALKALI; SIZE: 97 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A</p>	EA	1000		

Item	Description	Unit	Quantity	Rate	Amount
	<p>ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>				
60	<p>COVERALL: TYPE: ACID/ALKALI; SIZE: 102 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE</p>	EA	1000		

Item	Description	Unit	Quantity	Rate	Amount
	<p>PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>				
61	<p>COVERALL: TYPE: ACID/ALKALI; SIZE: 107 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT</p>	EA	500		

Item	Description	Unit	Quantity	Rate	Amount
	<p>LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>				
62	<p>COVERALL: TYPE: ACID/ALKALI; SIZE: 112 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST</p>	EA	200		

Item	Description	Unit	Quantity	Rate	Amount
	<p>35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BARTACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>				
63	<p>COVERALL: TYPE: ACID/ALKALI; SIZE: 117 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE-SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE</p>	EA	100		

Item	Description	Unit	Quantity	Rate	Amount
	<p>BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>				
64	<p>COVERALL: TYPE: ACID/ALKALI; SIZE: 122 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A</p>	EA	50		

Item	Description	Unit	Quantity	Rate	Amount
	<p>COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A</p>				

Item	Description	Unit	Quantity	Rate	Amount
	SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM				
65	COVERALL: TYPE: ACID/ALKALI; SIZE: 127 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWOWAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE	EA	50		

Item	Description	Unit	Quantity	Rate	Amount
	CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM				
66	COVERALL: TYPE: ACID/ALKALI; SIZE: 132 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER	EA	50		

Item	Description	Unit	Quantity	Rate	Amount
	<p>MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET;THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>				
67	<p>COVERALL: TYPE: ACID/ALKALI; SIZE: 137; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED</p>	EA	20		

Item	Description	Unit	Quantity	Rate	Amount
	<p>ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>				
68	<p>COVERALL: TYPE: ACID/ALKALI; SIZE: 142 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP</p>	EA	20		

Item	Description	Unit	Quantity	Rate	Amount
	<p>POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>				
69	<p>COVERALL: TYPE: ACID/ALKALI; SIZE: 147 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE</p>	EA	20		

Item	Description	Unit	Quantity	Rate	Amount
	<p>SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>				
70	<p>COVERALL: TYPE: ACID/ALKALI; SIZE: 152 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80</p>	EA	20		

Item	Description	Unit	Quantity	Rate	Amount
	<p>MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>				

Item	Description	Unit	Quantity	Rate	Amount
71	<p>COVERALL: TYPE: ACID/ALKALI; SIZE: 157 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE</p>	EA	20		

Item	Description	Unit	Quantity	Rate	Amount
	POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM				
72	TROUSERS: TYPE: MEN LONG; SIZE: 152 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION	EA	40		
73	TROUSERS: TYPE: MEN LONG; SIZE: 157 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION	EA	20		
74	TROUSERS: TYPE: ACID/ALKALI; SIZE: 77; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; LEG LENGTH: LONG; FIT: REGULAR; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132	EA	250		

Item	Description	Unit	Quantity	Rate	Amount
75	TROUSERS: TYPE: ACID/ALKALI; SIZE: 82 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132	EA	280		
76	TROUSERS: TYPE: ACID/ALKALI; SIZE: 87 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID-RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132	EA	300		
77	TROUSERS: TYPE: ACID/ALKALI; SIZE: 97 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132	EA	250		
78	TROUSERS: TYPE: ACID/ALKALI; SIZE: 102 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE	EA	200		

Item	Description	Unit	Quantity	Rate	Amount
	PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132				
79	TROUSERS: TYPE: ACID/ALKALI; SIZE: 107 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132	EA	200		
80	TROUSERS: TYPE: ACID/ALKALI; SIZE: 112 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132	EA	40		
81	TROUSERS: TYPE: ACID/ALKALI; SIZE: 117 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132	EA	40		
82	TROUSERS: TYPE: ACID/ALKALI; SIZE: 122 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT;	EA	20		

Item	Description	Unit	Quantity	Rate	Amount
	SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132				
83	TROUSERS: TYPE: ACID/ALKALI; SIZE: 127 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID-RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132	EA	20		
84	TROUSERS: TYPE: ACID/ALKALI; SIZE: 132 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132	EA	20		
85	TROUSERS: TYPE: ACID/ALKALI; SIZE: 137 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK	EA	20		

Item	Description	Unit	Quantity	Rate	Amount
	PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132				
86	TROUSERS: TYPE: ACID/ALKALI; SIZE: 142 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132	EA	20		
87	TROUSERS: TYPE: ACID/ALKALI; SIZE: 92 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132	EA	500		
88	JACKET, UTILITY: TYPE: THERMAL; SIZE: SMALL; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; SPECIFICATION: 240-44175132 REV 2; INSULATED WITH PRE-SHRUNK HOLLOW FIBRE OR A NON-FLAMMABLE MATERIAL; WITH THE OUTER COVERING MADE OF PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4 CLASS C CATEGORY 1; MATERIAL TYPE D59 AND FLAME RETARDANT; JACKET LENGTH: TO REACH BELOW THE BUTTOCKS; POCKETS: ONE CHEST POCKET SHALL BE BELLOWS TYPE - 15CM DEEP AND 14CM WIDE; 4 SIDE POCKETS; POCKETS TO HAVE FLAPS WITH CUT-OFF EDGES THAT CAN BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; THE SIDE POCKET SHALL BE THE BELLOWS TYPE WITH A SIDE ENTRY INTO ANOTHER SEPARATE POCKET AND SHALL BE 22CM DEEP AND 21CM WIDE; JACKETS SHALL HAVE NON-CONDUCTIVE PRESS STUDS DOWN THE FRONT ON A DOUBLE PANEL STRIP; AS WELL AS A NON-CONDUCTIVE ZIP; THE SLEEVE CUFFS SHALL HAVE TWO NON-CONDUCTIVE PRESS STUDS AT THE END OF THE SLEEVE SO THAT THE SIZE CAN BE ADJUSTED;	EA	300		

Item	Description	Unit	Quantity	Rate	Amount
	IDENTIFICATION: INDELIBLE MNFRS TRADEMARK; REF NO. AND CLEANING INSTRUCTIONS INSIDE COLLAR ON JACKETS AND SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS				
89	JACKET, UTILITY: TYPE: THERMAL; SIZE: MEDIUM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; SPECIFICATION: 240-44175132 REV 2; INSULATED WITH PRE-SHRUNK HOLLOW FIBRE OR A NON-FLAMMABLE MATERIAL; WITH THE OUTER COVERING MADE OF PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4 CLASS C CATEGORY 1; MATERIAL TYPE D59 AND FLAME RETARDANT; JACKET LENGTH: TO REACH BELOW THE BUTTOCKS; POCKETS: ONE CHEST POCKET SHALL BE BELLOWS TYPE - 15CM DEEP AND 14CM WIDE; 4 SIDE POCKETS; POCKETS TO HAVE FLAPS WITH CUT-OFF EDGES THAT CAN BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; THE SIDE POCKET SHALL BE THE BELLOWS TYPE WITH A SIDE ENTRY INTO ANOTHER SEPARATE POCKET AND SHALL BE 22CM DEEP AND 21CM WIDE; JACKETS SHALL HAVE NON-CONDUCTIVE PRESS STUDS DOWN THE FRONT ON A DOUBLE PANEL STRIP; AS WELL AS A NON-CONDUCTIVE ZIP; THE SLEEVE CUFFS SHALL HAVE TWO NON-CONDUCTIVE PRESS STUDS AT THE END OF THE SLEEVE SO THAT THE SIZE CAN BE ADJUSTED; IDENTIFICATION: INDELIBLE MNFRS TRADEMARK; REF NO. AND CLEANING INSTRUCTIONS INSIDE COLLAR ON JACKETS AND SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS	EA	500		
90	JACKET, UTILITY: TYPE: THERMAL; SIZE: LARGE; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; SPECIFICATION: 240-44175132 REV 2; INSULATED WITH PRE-SHRUNK HOLLOW FIBRE OR A NON-FLAMMABLE MATERIAL; WITH THE OUTER COVERING MADE OF PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4 CLASS C CATEGORY 1; MATERIAL TYPE D59 AND FLAME RETARDANT; JACKET LENGTH: TO REACH BELOW THE BUTTOCKS; POCKETS: ONE CHEST POCKET SHALL BE BELLOWS TYPE - 15CM DEEP AND 14CM WIDE; 4 SIDE POCKETS; POCKETS TO HAVE FLAPS WITH CUT-OFF EDGES THAT CAN BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; THE SIDE POCKET SHALL BE THE BELLOWS TYPE WITH A SIDE ENTRY INTO ANOTHER SEPARATE POCKET AND SHALL BE 22CM DEEP AND 21CM WIDE; JACKETS SHALL HAVE NON-CONDUCTIVE PRESS STUDS DOWN THE FRONT ON A DOUBLE PANEL STRIP; AS WELL AS A NON-CONDUCTIVE ZIP; THE SLEEVE CUFFS SHALL HAVE TWO NON-CONDUCTIVE PRESS STUDS AT THE END OF THE SLEEVE SO THAT THE SIZE CAN BE ADJUSTED; IDENTIFICATION: INDELIBLE MNFRS TRADEMARK; REF NO. AND CLEANING INSTRUCTIONS INSIDE COLLAR ON JACKETS AND SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS	EA	300		
91	JACKET, UTILITY: TYPE: THERMAL; SIZE: XLARGE; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE	EA	30		

Item	Description	Unit	Quantity	Rate	Amount
	19_3920; SPECIFICATION: 240-44175132 REV 2; INSULATED WITH PRE-SHRUNK HOLLOW FIBRE OR A NON-FLAMMABLE MATERIAL; WITH THE OUTER COVERING MADE OF PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4 CLASS C CATEGORY 1; MATERIAL TYPE D59 AND FLAME RETARDANT; JACKET LENGTH: TO REACH BELOW THE BUTTOCKS; POCKETS: ONE CHEST POCKET SHALL BE BELLOWS TYPE - 15CM DEEP AND 14CM WIDE; 4 SIDE POCKETS; POCKETS TO HAVE FLAPS WITH CUT-OFF EDGES THAT CAN BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; THE SIDE POCKET SHALL BE THE BELLOWS TYPE WITH A SIDE ENTRY INTO ANOTHER SEPARATE POCKET AND SHALL BE 22CM DEEP AND 21CM WIDE; JACKETS SHALL HAVE NON-CONDUCTIVE PRESS STUDS DOWN THE FRONT ON A DOUBLE PANEL STRIP; AS WELL AS A NON-CONDUCTIVE ZIP; THE SLEEVE CUFFS SHALL HAVE TWO NON-CONDUCTIVE PRESS STUDS AT THE END OF THE SLEEVE SO THAT THE SIZE CAN BE ADJUSTED; IDENTIFICATION: INDELIBLE MNFRS TRADEMARK; REF NO. AND CLEANING INSTRUCTIONS INSIDE COLLAR ON JACKETS AND SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS				
92	JACKET, UTILITY: TYPE: THERMAL; SIZE: 2XLARGE; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; SPECIFICATION: 240-44175132 REV 2; INSULATED WITH PRE-SHRUNK HOLLOW FIBRE OR A NON-FLAMMABLE MATERIAL; WITH THE OUTER COVERING MADE OF PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4 CLASS C CATEGORY 1; MATERIAL TYPE D59 AND FLAME RETARDANT; JACKET LENGTH: TO REACH BELOW THE BUTTOCKS; POCKETS: ONE CHEST POCKET SHALL BE BELLOWS TYPE - 15CM DEEP AND 14CM WIDE; 4 SIDE POCKETS; POCKETS TO HAVE FLAPS WITH CUT-OFF EDGES THAT CAN BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; THE SIDE POCKET SHALL BE THE BELLOWS TYPE WITH A SIDE ENTRY INTO ANOTHER SEPARATE POCKET AND SHALL BE 22CM DEEP AND 21CM WIDE; JACKETS SHALL HAVE NON-CONDUCTIVE PRESS STUDS DOWN THE FRONT ON A DOUBLE PANEL STRIP; AS WELL AS A NON-CONDUCTIVE ZIP; THE SLEEVE CUFFS SHALL HAVE TWO NON-CONDUCTIVE PRESS STUDS AT THE END OF THE SLEEVE SO THAT THE SIZE CAN BE ADJUSTED; IDENTIFICATION: INDELIBLE MNFRS TRADEMARK; REF NO. AND CLEANING INSTRUCTIONS INSIDE COLLAR ON JACKETS AND SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS	EA	300		
93	JACKET, UTILITY: TYPE: THERMAL; SIZE: 3XLARGE; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; SPECIFICATION: 240-44175132 REV 2; INSULATED WITH PRE-SHRUNK HOLLOW FIBRE OR A NON-FLAMMABLE MATERIAL; WITH THE OUTER COVERING MADE OF PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4 CLASS C CATEGORY 1; MATERIAL TYPE D59 AND FLAME RETARDANT; JACKET LENGTH: TO REACH BELOW THE BUTTOCKS; POCKETS: ONE CHEST POCKET SHALL BE BELLOWS TYPE - 15CM	EA	40		

Item	Description	Unit	Quantity	Rate	Amount
	DEEP AND 14CM WIDE; 4 SIDE POCKETS; POCKETS TO HAVE FLAPS WITH CUT-OFF EDGES THAT CAN BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; THE SIDE POCKET SHALL BE THE BELLOWS TYPE WITH A SIDE ENTRY INTO ANOTHER SEPARATE POCKET AND SHALL BE 22CM DEEP AND 21CM WIDE; JACKETS SHALL HAVE NON-CONDUCTIVE PRESS STUDS DOWN THE FRONT ON A DOUBLE PANEL STRIP; AS WELL AS A NON-CONDUCTIVE ZIP; THE SLEEVE CUFFS SHALL HAVE TWO NON-CONDUCTIVE PRESS STUDS AT THE END OF THE SLEEVE SO THAT THE SIZE CAN BE ADJUSTED; IDENTIFICATION: INDELIBLE MNFRS TRADEMARK; REF NO. AND CLEANING INSTRUCTIONS INSIDE COLLAR ON JACKETS AND SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS				
94	COVERALL: TYPE: DISPOSABLE; SIZE: XXXL; MATERIAL: WATERPROOF; STYLE: ONE PIECE; COLOR: WHITE; COMPLY WITH THE FOLLOWING PARTICULATE PROTECTION EN ISO 13982-1 2004 (TYPE 5) CHEMICAL SPLASH PROTECTION EN 13034 2005 +A1 09 (TYPE 6); RADIOACTIVE PROTECTION EN 1073-2 2002; BIOLOGICAL RISK PROTECTION EN 14126 2003\AC 2004; ANTI-STATIC DISCHARGE EN 1149-1 EN 1149-5 2008; NO EQUIVALENT ALLOWED	EA	5000		
95	COVERALL: TYPE: DISPOSABLE; SIZE: XXL; 122; 48; MATERIAL: WATERPROOF; STYLE: ONE PIECE; COLOR: WHITE; COMPLY WITH THE FOLLOWING PARTICULATE PROTECTION EN ISO 13982-1 2004 (TYPE 5) CHEMICAL SPLASH PROTECTION EN 13034 2005 +A1 09 (TYPE 6); RADIOACTIVE PROTECTION EN 1073-2 2002; BIOLOGICAL RISK PROTECTION EN 14126 2003\AC 2004; ANTI-STATIC DISCHARGE EN 1149-1 EN 1149-5 2008; NO EQUIVALENT ALLOWED	EA	5000		
96	COVERALL: TYPE: DISPOSABLE; SIZE: LARGE; MATERIAL: WATERPROOF; STYLE: ONE PIECE; COLOR: WHITE; COMPLY WITH THE FOLLOWING PARTICULATE PROTECTION EN ISO 13982-1 2004 (TYPE 5) CHEMICAL SPLASH PROTECTION EN 13034 2005 +A1 09 (TYPE 6); RADIOACTIVE PROTECTION EN 1073-2 2002; BIOLOGICAL RISK PROTECTION EN 14126 2003\AC 2004; ANTI-STATIC DISCHARGE EN 1149-1 EN 1149-5 2008; NO EQUIVALENT ALLOWED	EA	5000		
97	COVERALL: TYPE: DISPOSABLE; SIZE: XL; 44/46; 112/117; MATERIAL: WATERPROOF; STYLE: ONE PIECE; COLOR:WHITE; COMPLY WITH THE FOLLOWING PARTICULATE PROTECTION EN ISO 13982-1 2004 (TYPE 5) CHEMICAL SPLASH PROTECTION EN 13034 2005 +A1 09 (TYPE 6); RADIOACTIVE PROTECTION EN 1073-2 2002; BIOLOGICAL RISK PROTECTION EN 14126 2003\AC 2004; ANTI-STATIC DISCHARGE EN 1149-1 EN 1149-5 2008; NO EQUIVALENT ALLOWED	EA	5000		
98	RAINWEAR: TYPE: 2 PIECE SUIT; SIZE: S; MATERIAL: POLYESTER 100 PCT PLAIN WEAVE, 180 GM/2 MIN; COLOR: BLUE NAVY; MATERIAL: MINIMUM 180 GRAMS PER M/3 FACE SIDE 100% POLYESTER; PLAIN WEAVE WITH 170 THREADS PER M/3 INCH WITH WATER RESISTANT COATING; UNDER SIDE LAMINATED WITH PVC COATING; SEAMS STRENGTH 50KPA; CONVERTS TO 50KNM/2; LINING 80% POLYESTER 20% COTTON; SIZE TO SANS 434 SIZE CHART ANNEX E FOR	EA	300		

Item	Description	Unit	Quantity	Rate	Amount
	RAIN WEAR; JACKET SHALL HAVE A NYLON SPIRAL ZIP WITH CLOSED FLY FRONT SECURED BY NON-CONDUCTIVE PRESS-STUDS; COMPLY WITH SANS 1822 TYPE 5; HOOD ATTACHED TO THE JACKET; JACKET TO COVER THE BUTTOCKS; FALSE ELASTIC SLEEVE AT THE END MADE OF SOFTER MATERIAL; PANTS SHALL HAVE SIDE SLITS AND ELASTIC WAIST; REFLECTIVE STRIPS TO BE FITTED ON BOTH SLEEVES ON THE UPPER ARM, AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SIDE OF THE SLEEVE AND THE ESKOM LOGO SHALL BE SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON THE FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; UNIQUE IDENTIFIER 240-44175132				
99	RAINWEAR: TYPE: 2 PIECE SUIT; SIZE: L; MATERIAL: POLYESTER 100 PCT PLAIN WEAVE, 180 GM/2 MIN; COLOR: BLUE NAVY; MATERIAL: MINIMUM 180 GRAMS PER M/3 FACE SIDE 100% POLYESTER; PLAIN WEAVE WITH 170 THREADS PER M/3 INCH WITH WATER RESISTANT COATING; UNDER SIDE LAMINATED WITH PVC COATING; SEAMS STRENGTH 50KPA; CONVERTS TO 50KNM/2; LINING 80% POLYESTER 20% COTTON; SIZE TO SANS 434 SIZE CHART ANNEX E FOR RAIN WEAR; JACKET SHALL HAVE A NYLON SPIRAL ZIP WITH CLOSED FLY FRONT SECURED BY NON-CONDUCTIVE PRESS-STUDS; COMPLY WITH SANS 1822 TYPE 5; HOOD ATTACHED TO THE JACKET; JACKET TO COVER THE BUTTOCKS; FALSE ELASTIC SLEEVE AT THE END MADE OF SOFTER MATERIAL; PANTS SHALL HAVE SIDE SLITS AND ELASTIC WAIST; REFLECTIVE STRIPS TO BE FITTED ON BOTH SLEEVES ON THE UPPER ARM, AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SIDE OF THE SLEEVE AND THE ESKOM LOGO SHALL BE SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON THE FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; UNIQUE IDENTIFIER 240-44175132	EA	500		
100	RAINWEAR: TYPE: 2 PIECE SUIT; SIZE: XL; MATERIAL: POLYESTER 100 PCT PLAIN WEAVE, 180 GM/2 MIN; COLOR: BLUE NAVY; MATERIAL: MINIMUM 180 GRAMS PER M/3 FACE SIDE 100% POLYESTER; PLAIN WEAVE WITH 170 THREADS PER M/3 INCH WITH WATER RESISTANT COATING; UNDER SIDE LAMINATED WITH PVC COATING; SEAMS STRENGTH 50KPA; CONVERTS TO 50KNM/2; LINING 80% POLYESTER 20% COTTON; SIZE TO SANS 434 SIZE CHART ANNEX E FOR RAIN WEAR; JACKET SHALL HAVE A NYLON SPIRAL ZIP WITH CLOSED FLY FRONT SECURED BY NON-CONDUCTIVE PRESS-STUDS; COMPLY WITH SANS 1822 TYPE 5; HOOD ATTACHED TO THE JACKET; JACKET TO COVER THE BUTTOCKS; FALSE ELASTIC SLEEVE AT THE END MADE OF SOFTER MATERIAL; PANTS SHALL HAVE SIDE SLITS AND ELASTIC WAIST; REFLECTIVE STRIPS TO BE FITTED ON BOTH SLEEVES ON THE UPPER ARM, AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SIDE OF THE SLEEVE AND THE ESKOM LOGO SHALL BE SILK-SCREENED IN ACCORDANCE WITH ESKOM'S	EA	500		

Item	Description	Unit	Quantity	Rate	Amount
	CORPORATE IDENTITY ON THE FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; UNIQUE IDENTIFIER 240-44175132				
101	RAINWEAR: TYPE: 2 PIECE SUIT; SIZE: 2XL; MATERIAL: POLYESTER 100 PCT PLAIN WEAVE, 180 GM/2 MIN; COLOR: BLUE NAVY; MATERIAL: MINIMUM 180 GRAMS PER M/3 FACE SIDE 100% POLYESTER; PLAIN WEAVE WITH 170 THREADS PER M/3 INCH WITH WATER RESISTANT COATING; UNDER SIDE LAMINATED WITH PVC COATING; SEAMS STRENGTH 50KPA; CONVERTS TO 50KNM/2; LINING 80% POLYESTER 20% COTTON; SIZE TO SANS 434 SIZE CHART ANNEX E FOR RAIN WEAR; JACKET SHALL HAVE A NYLON SPIRAL ZIP WITH CLOSED FLY FRONT SECURED BY NON-CONDUCTIVE PRESS-STUDS; COMPLY WITH SANS 1822 TYPE 5; HOOD ATTACHED TO THE JACKET; JACKET TO COVER THE BUTTOCKS; FALSE ELASTIC SLEEVE AT THE END MADE OF SOFTER MATERIAL; PANTS SHALL HAVE SIDE SLITS AND ELASTIC WAIST; REFLECTIVE STRIPS TO BE FITTED ON BOTH SLEEVES ON THE UPPER ARM, AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SIDE OF THE SLEEVE AND THE ESKOM LOGO SHALL BE SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON THE FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; UNIQUE IDENTIFIER 240-44175132	EA	200		
102	RAINWEAR: TYPE: 2 PIECE SUIT; SIZE: 3XL; MATERIAL: POLYESTER 100 PCT PLAIN WEAVE, 180 GM/2 MIN; COLOR: BLUE NAVY; MATERIAL: MINIMUM 180 GRAMS PER M/3 FACE SIDE 100% POLYESTER; PLAIN WEAVE WITH 170 THREADS PER M/3 INCH WITH WATER RESISTANT COATING; UNDER SIDE LAMINATED WITH PVC COATING; SEAMS STRENGTH 50KPA; CONVERTS TO 50KNM/2; LINING 80% POLYESTER 20% COTTON; SIZE TO SANS 434 SIZE CHART ANNEX E FOR RAIN WEAR; JACKET SHALL HAVE A NYLON SPIRAL ZIP WITH CLOSED FLY FRONT SECURED BY NON-CONDUCTIVE PRESS-STUDS; COMPLY WITH SANS 1822 TYPE 5; HOOD ATTACHED TO THE JACKET; JACKET TO COVER THE BUTTOCKS; FALSE ELASTIC SLEEVE AT THE END MADE OF SOFTER MATERIAL; PANTS SHALL HAVE SIDE SLITS AND ELASTIC WAIST; REFLECTIVE STRIPS TO BE FITTED ON BOTH SLEEVES ON THE UPPER ARM, AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SIDE OF THE SLEEVE AND THE ESKOM LOGO SHALL BE SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON THE FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; UNIQUE IDENTIFIER 240-44175132	EA	200		
103	COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 77 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE	EA	1000		

Item	Description	Unit	Quantity	Rate	Amount
	<p>COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>				

Item	Description	Unit	Quantity	Rate	Amount
104	<p>COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 82 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET</p>	EA	1000		

Item	Description	Unit	Quantity	Rate	Amount
	<p>AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>				
105	<p>COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 87 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A</p>	EA	1000		

Item	Description	Unit	Quantity	Rate	Amount
	ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM				
106	COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 92 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE	EA	1000		

Item	Description	Unit	Quantity	Rate	Amount
	<p>PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>				
107	<p>COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 97 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT</p>	EA	1000		

Item	Description	Unit	Quantity	Rate	Amount
	<p>LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>				
108	<p>COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 102 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE</p>	EA	1000		

Item	Description	Unit	Quantity	Rate	Amount
	<p>POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>				
109	<p>COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 117 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE</p>	EA	500		

Item	Description	Unit	Quantity	Rate	Amount
	<p>TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>				
110	<p>COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 137; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE;</p>	EA	300		

Item	Description	Unit	Quantity	Rate	Amount
	<p>THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>				

Item	Description	Unit	Quantity	Rate	Amount
111	<p>COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 107 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM</p>	EA	1000		

Item	Description	Unit	Quantity	Rate	Amount
	<p>ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>				
112	<p>COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 132 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST</p>	EA			

Item	Description	Unit	Quantity	Rate	Amount
	<p>POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>				
113	<p>COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 127 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE</p>	EA	500		

Item	Description	Unit	Quantity	Rate	Amount
	<p>PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>				
114	<p>COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 142 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT</p>	EA	100		

Item	Description	Unit	Quantity	Rate	Amount
	<p>LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKETFLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>				
115	<p>COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 147 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE</p>	EA	100		

Item	Description	Unit	Quantity	Rate	Amount
	<p>POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>				
116	<p>COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 112 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE</p>	EA	500		

Item	Description	Unit	Quantity	Rate	Amount
	<p>TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>				
117	<p>COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 122 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE;</p>	EA	500		

Item	Description	Unit	Quantity	Rate	Amount
	<p>THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>				

Item	Description	Unit	Quantity	Rate	Amount
118	TROUSERS: TYPE: ACID RESIST; SIZE: 147; COLOR: GREEN BOTTLE; MATERIAL: POLYCOTTON; TO COMPLY WITH ESKOM SPECIFICATION 240-44175132; MATERIAL TO BE POLY COTTON FABRIC (65/35)	EA	100		
119	TROUSERS: TYPE: ACID RESIST; SIZE: 142; COLOR: GREEN BOTTLE; MATERIAL: POLYCOTTON; TO COMPLY WITH ESKOM SPECIFICATION 240-44175132; MATERIAL TO BE POLY COTTON FABRIC (65/35)	EA	100		
120	TROUSERS: TYPE: ACID/ALKALI; SIZE: 102 CM; COLOR: BOTTLE GREEN; MATERIAL: POLYESTER/VISCOSE; 65/35 PCT; SPECIFICATION: 240-44175132-REV 2; INTERNATIONAL ACID-RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS	EA	250		
121	TROUSERS: TYPE: ACID/ALKALI; SIZE: 92 CM; COLOR: BOTTLE GREEN; MATERIAL: POLYESTER/VISCOSE; 65/35 PCT; SPECIFICATION: 240-44175132-REV 2; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS	EA	250		
122	TROUSERS: TYPE: ACID/ALKALI; SIZE: 97 CM; COLOR: BOTTLE GREEN; MATERIAL: POLYESTER/VISCOSE; 65/35 PCT; SPECIFICATION: 240-44175132-REV 2; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS	EA	250		
123	TROUSERS: TYPE: ACID/ALKALI; SIZE: 77 CM; COLOR: BOTTLE GREEN; MATERIAL: POLYESTER/VISCOSE 65/35 PCT; SPECIFICATION: 240-44175132-REV 2; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR	EA	250		

Item	Description	Unit	Quantity	Rate	Amount
	TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS				
124	TROUSERS: TYPE: ACID/ALKALI; SIZE: 87 CM; COLOR: BOTTLE GREEN; MATERIAL: POLYESTER/VISCOSE; 65/35 PCT; SPECIFICATION: 240-44175132-REV 2; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS	EA	250		
125	JACKET, OVERALL: TYPE: ACID RESIST; SIZE: 77; MATERIAL: POLYCOTTON; COLOR: GREEN BOTTLE; COMPLY WITH ESKOM PPE SPECIFICATION; MATERIAL TO BE POLY COTTON FABRIC (65/35)	EA	250		
126	JACKET, OVERALL: TYPE: ACID RESIST; SIZE: 147; MATERIAL: POLYCOTTON; COLOR: GREEN BOTTLE; COMPLY WITH ESKOM PPE SPECIFICATION; MATERIAL TO BE POLY COTTON FABRIC (65/35)	EA	100		
127	JACKET, OVERALL: TYPE: ACID RESIST; SIZE: 142; MATERIAL: POLYCOTTON; COLOR: GREEN BOTTLE; COMPLY WITH ESKOM PPE SPECIFICATION; MATERIAL TO BE POLY COTTON FABRIC (65/35)	EA	100		
128	JACKET, OVERALL: TYPE: ACID/ALKALI; SIZE: 112 CM; MATERIAL: POLYESTER/VISCOSE; 65/35 PCT; COLOR: BOTTLE GREEN; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES	EA	250		
	SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND				
Item	Description	Unit	Quantity	Rate	Amount

	<p>SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM</p>				
129	<p>JACKET, OVERALL: TYPE: ACID/ALKALI; SIZE: 102 CM; MATERIAL: POLYESTER/VISCOSE; 65/35 PCT; COLOR: BOTTLE GREEN; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM</p>	EA	250		

Item	Description	Unit	Quantity	Rate	Amount
	HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM				
130	JACKET, OVERALL: TYPE: ACID/ALKALI; SIZE: 97 CM; MATERIAL: POLYESTER/VISCOSE; 65/35 PCT; COLOR: BOTTLE GREEN; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM	EA	250		
131	JACKET, OVERALL: TYPE: ACID/ALKALI; SIZE: 92 CM; MATERIAL: POLYESTER/VISCOSE; 65/35 PCT; COLOR: BOTTLE GREEN; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE	EA	250		

Item	Description	Unit	Quantity	Rate	Amount
	<p>FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST ANDSIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM</p>				
132	<p>JACKET, OVERALL: TYPE: ACID/ALKALI; SIZE: 87 CM; MATERIAL: POLYESTER/VISCOSE; 65/35 PCT; COLOR: BOTTLE GREEN; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS: A FLAP SHALL BE OF SUCH</p>	EA	250		

Item	Description	Unit	Quantity	Rate	Amount
	LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM				
133	TROUSERS: TYPE: ACID/ALKALI; SIZE: 112 CM; COLOR: BOTTLE GREEN; MATERIAL: POLYESTER/VISCOSE 65/35 PCT; SPECIFICATION: 240-44175132-REV 2; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS	EA	250		
134	WADER: TYPE: FISHERMANS; SIZE: 11; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132	EA	50		
135	WADER: TYPE: FISHERMANS; SIZE: 10; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132	EA	50		
136	WADER: TYPE: FISHERMANS; SIZE: 12; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132	EA	50		
137	WADER: TYPE: FISHERMANS; SIZE: 7; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132	EA	50		
138	WADER: TYPE: FISHERMANS; SIZE: 8; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132	EA	50		
139	WADER: TYPE: FISHERMANS; SIZE: 9; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132	EA	50		
140	WADER: TYPE: FISHERMANS; SIZE: 6; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132	EA	50		
141	WADER: TYPE: FISHERMANS; SIZE: 13; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132	EA	50		
142	SAFETY FILE (FIXED)	SUM	1		
143	SAFETY FILE (TIME RELATED)	ANN UAL	4		



PART 3: SCOPE OF WORK

Document reference	Title	No of pages
	This cover page	1
C3.1	<i>Purchaser's</i> Goods Information	88
C3.2	<i>Supplier's</i> Goods Information	1
	Total number of pages	90

C3.1: *PURCHASER'S* GOODS INFORMATION

1 Overview and purpose of the *goods* and *services*

Supply and delivery of Personal Protective Clothing on as and when required at Arnot Power Station for the period of Five (5) years

The goods must be delivered as per the Purchase Order.

Eskom Holdings SOC Limited - Arnot Power Station will only accept deliveries as stipulated in the purchase order during office hours not later than 16:00 from Monday to Thursday and not later than 12:00 on Fridays. No wrong deliveries will be accepted and must be collected by the supplier. Quality and quantity will be assessed on each delivery. The supplier will deliver the agreed quantity i.e., nothing less or more.

Non-deliveries will be a breach of contract conditions and will result in issuing Non-Conformance Report and terminating contract with immediate effect.

2 Specification and description of the goods

ITEM	MATERIAL	LONG DESCRIPTION	UMC	QTY
1	0016885	COAT, DUST: TYPE: GENERAL PURPOSE; SIZE: 102 CM; MATERIAL: COTTON; COLOR: BLUE NAVY PANTONE 19-3920; SPECIFICATION: 240-44175132; MATERIAL: PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; LENGTH 3/4; POCKET: FRONT BUTTONS; TWO FRONT POCKETS; SLIT AT BACK; BUTTONS ACCEPTABLE FOUR-HOLE; DYED PLASTICS BUTTONS COMPLY WITH SANS 1457 COATS SHALL FASTEN WITH BUTTON AND BUTTONHOLE AND SHALL BE EQUIDISTANTLY SPACED; BUTTONS SECURED TO POSITIONS CORRESPONDING TO BUTTONHOLES; THE PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; THE BACK SHALL HAVE A SEAM DOWN THE CENTRE WITH A VENT IN THE LOWER PART OF THE SEAM; THE VENT SHALL HAVE AN OVERLAP OF 40 MM AND SHALL BE SECURELY TACKED AND BAR-TACKED AT THE TOP; A HANGER LOOP OF OUTER DOUBLE FOLDED MATERIAL OF FINISHED LENGTH AT LEAST 70 MM AND OF FINISHED WIDTH AT LEAST 10 MM; SHALL BE SECURELY SEWN IN WITH THE COLLAR AT THE BACK NECK ON THE INSIDE; THE BOTTOM OF THE COATS AND THE LOWER EDGE OF PLAIN SLEEVE CUFFS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 15 MM; POCKET MOUTHS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 20 MM; EACH GARMENT SHALL HAVE A LABEL SECURELY ATTACHED AT THE CENTRE BACK NECK BELOW THE COLLAR SEAM ON THE INSIDE OF THE GARMENT; THE LABEL SHALL PROVIDE THE FOLLOWING INFORMATION PRINTED IN LEGIBLE AND INDELIBLE BLOCK LETTERS OF HEIGHT AT LEAST 3 MM; MANUFACTURER'S NAME OR TRADEMARK; CHEST SIZE SANS 434:2011 EDITION 5 22; YEAR OF MANUFACTURE; VAT REGISTRATION NUMBER; COUNTRY OF ORIGIN; ITEM TO BEAR SABS MARK OF APPROVAL REFERENCE SANS 434:2011 FIGURE 3 COATS	EA	300
2	0160658	COAT, DUST: TYPE: GENERAL PURPOSE; SIZE: 112 CM; MATERIAL: COTTON; COLOR: BLUE NAVY PANTONE 19-3920; SPECIFICATION: 240-44175132; MATERIAL: PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; LENGTH 3/4; POCKET: FRONT BUTTONS; TWO FRONT POCKETS; SLIT AT BACK; BUTTONS ACCEPTABLE FOUR-HOLE; DYED PLASTICS BUTTONS COMPLY WITH SANS 1457 COATS SHALL FASTEN WITH BUTTON AND BUTTONHOLE AND SHALL BE EQUIDISTANTLY SPACED; BUTTONS SECURED TO POSITIONS CORRESPONDING TO BUTTONHOLES; THE PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET	EA	300

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

ITEM	MATERIAL	LONG DESCRIPTION	UMC	QTY
		<p>AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; THE BACK SHALL HAVE A SEAM DOWN THE CENTRE WITH A VENT IN THE LOWER PART OF THE SEAM; THE VENT SHALL HAVE AN OVERLAP OF 40 MM AND SHALL BE SECURELY TACKED AND BAR-TACKED AT THE TOP; A HANGER LOOP OF OUTER DOUBLE FOLDED MATERIAL OF FINISHED LENGTH AT LEAST 70 MM AND OF FINISHED WIDTH AT LEAST 10 MM; SHALL BE SECURELY SEWN IN WITH THE COLLAR AT THE BACK NECK ON THE INSIDE; THE BOTTOM OF THE COATS AND THE LOWER EDGE OF PLAIN SLEEVE CUFFS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 15 MM; POCKET MOUTHS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 20 MM; EACH GARMENT SHALL HAVE A LABEL SECURELY ATTACHED AT THE CENTRE BACK NECK BELOW THE COLLAR SEAM ON THE INSIDE OF THE GARMENT; THE LABEL SHALL PROVIDE THE FOLLOWING INFORMATION PRINTED IN LEGIBLE AND INDELIBLE BLOCK LETTERS OF HEIGHT AT LEAST 3 MM; MANUFACTURER'S NAME OR TRADEMARK; CHEST SIZE SANS 434:2011 EDITION 5 22; YEAR OF MANUFACTURE; VAT REGISTRATION NUMBER; COUNTRY OF ORIGIN; ITEM TO BEAR SABS MARK OF APPROVAL REFERENCE SANS 434:2011 FIGURE 3 COATS</p>		
3	0160659	<p>COAT, DUST: TYPE: GENERAL PURPOSE; SIZE: 107 CM; MATERIAL: COTTON; COLOR: BLUE NAVY PANTONE 19-3920; SPECIFICATION: 240-44175132; MATERIAL: PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; LENGTH 3/4; POCKET: FRONT BUTTONS; TWO FRONT POCKETS; SLIT AT BACK; BUTTONS ACCEPTABLE FOUR-HOLE; DYED PLASTICS BUTTONS COMPLY WITH SANS 1457 COATS SHALL FASTEN WITH BUTTON AND BUTTONHOLE AND SHALL BE EQUIDISTANTLY SPACED; BUTTONS SECURED TO POSITIONS CORRESPONDING TO BUTTONHOLES; THE PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; THE BACK SHALL HAVE A SEAM DOWN THE CENTRE WITH A VENT IN THE LOWER PART OF THE SEAM; THE VENT SHALL HAVE AN OVERLAP OF 40 MM AND SHALL BE SECURELY TACKED AND BAR-TACKED AT THE TOP; A HANGER LOOP OF OUTER DOUBLE FOLDED MATERIAL OF FINISHED LENGTH AT LEAST 70 MM AND OF FINISHED WIDTH AT LEAST 10 MM; SHALL BE SECURELY SEWN IN WITH THE COLLAR AT THE BACK NECK ON THE INSIDE; THE BOTTOM OF THE COATS AND THE LOWER EDGE OF PLAIN SLEEVE CUFFS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 15 MM; POCKET MOUTHS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 20 MM; EACH GARMENT SHALL HAVE A LABEL SECURELY ATTACHED AT THE CENTRE BACK NECK BELOW THE COLLAR SEAM ON THE INSIDE OF THE GARMENT; THE LABEL SHALL PROVIDE THE FOLLOWING INFORMATION PRINTED IN LEGIBLE AND INDELIBLE BLOCK LETTERS OF HEIGHT AT LEAST 3 MM; MANUFACTURER'S NAME OR TRADEMARK; CHEST SIZE SANS 434:2011 EDITION 5 22; YEAR OF MANUFACTURE VAT</p>	EA	300

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

ITEM	MATERIAL	LONG DESCRIPTION	UMC	QTY
		REGISTRATION NUMBER; COUNTRY OF ORIGIN; ITEM TO BEAR SABS MARK OF APPROVAL REFERENCE SANS 434:2011 FIGURE 3 COATS		
4	0160660	COAT, DUST: TYPE: GENERAL PURPOSE; SIZE: 97 CM; MATERIAL: COTTON; COLOR: BLUE NAVY PANTONE 19-3920; SPECIFICATION: 240-44175132; MATERIAL: PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; LENGTH 3/4; POCKET: FRONT BUTTONS; TWO FRONT POCKETS; SLIT AT BACK; BUTTONS ACCEPTABLE FOUR-HOLE; DYED PLASTICS BUTTONS COMPLY WITH SANS 1457 COATS SHALL FASTEN WITH BUTTON AND BUTTONHOLE AND SHALL BE EQUIDISTANTLY SPACED; BUTTONS SECURED TO POSITIONS CORRESPONDING TO BUTTONHOLES; THE PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; THE BACK SHALL HAVE A SEAM DOWN THE CENTRE WITH A VENT IN THE LOWER PART OF THE SEAM; THE VENT SHALL HAVE AN OVERLAP OF 40 MM AND SHALL BE SECURELY TACKED AND BAR-TACKED AT THE TOP; A HANGER LOOP OF OUTER DOUBLE FOLDED MATERIAL OF FINISHED LENGTH AT LEAST 70 MM AND OF FINISHED WIDTH AT LEAST 10 MM; SHALL BE SECURELY SEWN IN WITH THE COLLAR AT THE BACK NECK ON THE INSIDE; THE BOTTOM OF THE COATS AND THE LOWER EDGE OF PLAIN SLEEVE CUFFS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 15 MM; POCKET MOUTHS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 20 MM; EACH GARMENT SHALL HAVE A LABEL SECURELY ATTACHED AT THE CENTRE BACK NECK BELOW THE COLLAR SEAM ON THE INSIDE OF THE GARMENT; THE LABEL SHALL PROVIDE THE FOLLOWING INFORMATION PRINTED IN LEGIBLE AND INDELIBLE BLOCK LETTERS OF HEIGHT AT LEAST 3 MM; MANUFACTURER'S NAME OR TRADEMARK; CHEST SIZE SANS 434:2011 EDITION 5 22; YEAR OF MANUFACTURE; VAT REGISTRATION NUMBER; COUNTRY OF ORIGIN; ITEM TO BEAR SABS MARK OF APPROVAL REFERENCE SANS 434:2011 FIGURE 3 COATS	EA	300
5	0160661	COAT, DUST: TYPE: GENERAL PURPOSE; SIZE: 87 CM; MATERIAL: COTTON; COLOR: BLUE NAVY PANTONE 19-3920; SPECIFICATION: 240-44175132; MATERIAL: PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; LENGTH 3/4; POCKET: FRONT BUTTONS; TWO FRONT POCKETS; SLIT AT BACK; BUTTONS ACCEPTABLE FOUR-HOLE; DYED PLASTICS BUTTONS COMPLY WITH SANS 1457 COATS SHALL FASTEN WITH BUTTON AND BUTTONHOLE AND SHALL BE EQUIDISTANTLY SPACED; BUTTONS SECURED TO POSITIONS CORRESPONDING TO BUTTONHOLES; THE PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; THE BACK SHALL HAVE A SEAM DOWN THE CENTRE WITH A VENT IN THE LOWER PART OF THE SEAM; THE VENT SHALL HAVE AN	EA	300

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

ITEM	MATERIAL	LONG DESCRIPTION	UMC	QTY
		OVERLAP OF 40 MM AND SHALL BE SECURELY TACKED AND BAR-TACKED AT THE TOP; A HANGER LOOP OF OUTER DOUBLE FOLDED MATERIAL OF FINISHED LENGTH AT LEAST 70 MM AND OF FINISHED WIDTH AT LEAST 10 MM; SHALL BE SECURELY SEWN IN WITH THE COLLAR AT THE BACK NECK ON THE INSIDE; THE BOTTOM OF THE COATS AND THE LOWER EDGE OF PLAIN SLEEVE CUFFS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 15 MM; POCKET MOUTHS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 20 MM; EACH GARMENT SHALL HAVE A LABEL SECURELY ATTACHED AT THE CENTRE BACK NECK BELOW THE COLLAR SEAM ON THE INSIDE OF THE GARMENT; THE LABEL SHALL PROVIDE THE FOLLOWING INFORMATION PRINTED IN LEGIBLE AND INDELIBLE BLOCK LETTERS OF HEIGHT AT LEAST 3 MM; MANUFACTURER'S NAME OR TRADEMARK; CHEST SIZE SANS 434:2011 EDITION 5 22; YEAR OF MANUFACTURE; VAT REGISTRATION NUMBER; COUNTRY OF ORIGIN; ITEM TO BEAR SABS MARK OF APPROVAL REFERENCE SANS 434:2011 FIGURE 3 COATS		
6	0160663	COAT, DUST: TYPE: GENERAL PURPOSE; SIZE: 117 CM; MATERIAL: COTTON; COLOR: BLUE NAVY PANTONE 19-3920; SPECIFICATION: 240-44175132; MATERIAL: PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; LENGTH 3/4; POCKET: FRONT BUTTONS; TWO FRONT POCKETS; SLIT AT BACK; BUTTONS ACCEPTABLE FOUR-HOLE; DYED PLASTICS BUTTONS COMPLY WITH SANS 1457 COATS SHALL FASTEN WITH BUTTON AND BUTTONHOLE AND SHALL BE EQUIDISTANTLY SPACED; BUTTONS SECURED TO POSITIONS CORRESPONDING TO BUTTONHOLES; THE PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; THE BACK SHALL HAVE A SEAM DOWN THE CENTRE WITH A VENT IN THE LOWER PART OF THE SEAM; THE VENT SHALL HAVE AN OVERLAP OF 40 MM AND SHALL BE SECURELY TACKED AND BAR-TACKED AT THE TOP; A HANGER LOOP OF OUTER DOUBLE FOLDED MATERIAL OF FINISHED LENGTH AT LEAST 70 MM AND OF FINISHED WIDTH AT LEAST 10 MM; SHALL BE SECURELY SEWN IN WITH THE COLLAR AT THE BACK NECK ON THE INSIDE; THE BOTTOM OF THE COATS AND THE LOWER EDGE OF PLAIN SLEEVE CUFFS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 15 MM; POCKET MOUTHS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 20 MM; EACH GARMENT SHALL HAVE A LABEL SECURELY ATTACHED AT THE CENTRE BACK NECK BELOW THE COLLAR SEAM ON THE INSIDE OF THE GARMENT; THE LABEL SHALL PROVIDE THE FOLLOWING INFORMATION PRINTED IN LEGIBLE AND INDELIBLE BLOCK LETTERS OF HEIGHT AT LEAST 3 MM; MANUFACTURER'S NAME OR TRADEMARK; CHEST SIZE SANS 434:2011 EDITION 5 22; YEAR OF MANUFACTURE; VAT REGISTRATION NUMBER; COUNTRY OF ORIGIN; ITEM TO BEAR SABS MARK OF APPROVAL REFERENCE SANS 434:2011 FIGURE 3 COATS	EA	300

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

ITEM	MATERIAL	LONG DESCRIPTION	UMC	QTY
7	0160664	COAT, DUST: TYPE: GENERAL PURPOSE; SIZE: 122 CM; MATERIAL: COTTON; COLOR: BLUE NAVY PANTONE 19-3920; SPECIFICATION: 240-44175132; MATERIAL: PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; LENGTH 3/4; POCKET: FRONT BUTTONS; TWO FRONT POCKETS; SLIT AT BACK; BUTTONS ACCEPTABLE FOUR-HOLE; DYED PLASTICS BUTTONS COMPLY WITH SANS 1457 COATS SHALL FASTEN WITH BUTTON AND BUTTONHOLE AND SHALL BE EQUIDISTANTLY SPACED; BUTTONS SECURED TO POSITIONS CORRESPONDING TO BUTTONHOLES; THE PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; THE BACK SHALL HAVE A SEAM DOWN THE CENTRE WITH A VENT IN THE LOWER PART OF THE SEAM; THE VENT SHALL HAVE AN OVERLAP OF 40 MM AND SHALL BE SECURELY TACKED AND BAR-TACKED AT THE TOP; A HANGER LOOP OF OUTER DOUBLE FOLDED MATERIAL OF FINISHED LENGTH AT LEAST 70 MM AND OF FINISHED WIDTH AT LEAST 10 MM; SHALL BE SECURELY SEWN IN WITH THE COLLAR AT THE BACK NECK ON THE INSIDE; THE BOTTOM OF THE COATS AND THE LOWER EDGE OF PLAIN SLEEVE CUFFS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 15 MM; POCKET MOUTHS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 20 MM; EACH GARMENT SHALL HAVE A LABEL SECURELY ATTACHED AT THE CENTRE BACK NECK BELOW THE COLLAR SEAM ON THE INSIDE OF THE GARMENT; THE LABEL SHALL PROVIDE THE FOLLOWING INFORMATION PRINTED IN LEGIBLE AND INDELIBLE BLOCK LETTERS OF HEIGHT AT LEAST 3 MM; MANUFACTURER'S NAME OR TRADEMARK; CHEST SIZE SANS 434:2011 EDITION 5 22; YEAR OF MANUFACTURE; VAT REGISTRATION NUMBER; COUNTRY OF ORIGIN; ITEM TO BEAR SABS MARK OF APPROVAL REFERENCE SANS 434:2011 FIGURE 3 COATS	EA	300
8	0172192	JACKET, UTILITY: TYPE: OPERATING; SIZE: 147 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE	EA	100

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

ITEM	MATERIAL	LONG DESCRIPTION	UMC	QTY
		JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1		
9	0172193	JACKET, UTILITY: TYPE: OPERATING; SIZE: 137 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND	EA	100

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

ITEM	MATERIAL	LONG DESCRIPTION	UMC	QTY
		WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1		
10	0179714	JACKET, UTILITY: TYPE: OPERATING; SIZE: 157 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE	EA	100

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

ITEM	MATERIAL	LONG DESCRIPTION	UMC	QTY
		<p>GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 5</p>		
11	0222467	<p>TROUSERS: TYPE: MEN LONG; SIZE: 77 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION</p>	EA	1500
12	0222468	<p>TROUSERS: TYPE: MEN LONG; SIZE: 82 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER</p>	EA	2000

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

ITEM	MATERIAL	LONG DESCRIPTION	UMC	QTY
		SPECIFICATION		
13	0222469	TROUSERS: TYPE: MEN LONG; SIZE: 87 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION	EA	2000
14	0222470	TROUSERS: TYPE: MEN LONG; SIZE: 92 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION	EA	3000
15	0222471	TROUSERS: TYPE: MEN LONG; SIZE: 97 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION	EA	3000
16	0222472	TROUSERS: TYPE: MEN LONG; SIZE: 102 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132	EA	3000

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

17	0222473	TROUSERS: TYPE: MEN LONG; SIZE: 107 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION	EA	2000
18	0222474	TROUSERS: TYPE: MEN LONG; SIZE: 112 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION	EA	1000
19	0222476	TROUSERS: TYPE: MEN LONG; SIZE: 117 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION		500
20	0222477	TROUSERS: TYPE: MEN LONG; SIZE: 122 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION	EA	300
21	0222478	TROUSERS: TYPE: MEN LONG; SIZE: 127 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS	EA	200

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION		
22	0222479	TROUSERS: TYPE: MEN LONG; SIZE: 132 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION	EA	50
23	0222480	TROUSERS: TYPE: MEN LONG; SIZE: 137 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION	EA	30
24	0222481	TROUSERS: TYPE: MEN LONG; SIZE: 142 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION	EA	20
25	0222482	TROUSERS: TYPE: MEN LONG; SIZE: 147 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER	EA	20

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION		
26	0222535	JACKET, UTILITY: TYPE: OPERATING; SIZE: 87 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE	EA	1500

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1		
27	0222536	JACKET, UTILITY: TYPE: OPERATING; SIZE: 97 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1	EA	1500

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

28	0222537	<p>JACKET, UTILITY: TYPE: OPERATING; SIZE: 107 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1</p>	EA	2000
29	0222538	<p>JACKET, UTILITY: TYPE: OPERATING; SIZE: 117 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET</p>	EA	2000

		<p>TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1</p>		
30	0222539	<p>JACKET, UTILITY: TYPE: OPERATING; SIZE: 122 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN</p>	EA	1000

		<p>HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1</p>		
31	0222540	<p>JACKET, UTILITY: TYPE: OPERATING; SIZE: 132 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH</p>	EA	300

		<p>AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1</p>		
32	0566452	<p>JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 87 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE</p>	EA	300

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM		
33	0566453	JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 97 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT	EA	300

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM		
34	0566454	JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 107 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM	EA	400
35	0566455	JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 117 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE	EA	300

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM		
36	0566456	JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 122 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE	EA	200

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM		
37	0566457	JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 132 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM	EA	100
38	0566458	JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 137 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE	EA	50

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		<p>IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM</p>		
39	0566459	<p>JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 147 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER</p>	EA	10

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM		
40	0566481	JACKET, UTILITY: TYPE: OPERATING; SIZE: 77 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER;THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE	EA	200

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1		
41	0566482	JACKET, UTILITY: TYPE: OPERATING; SIZE: 82 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND	EA	250

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1		
42	0566494	JACKET, UTILITY: TYPE: OPERATING; SIZE: 102 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM	EA	2000

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1		
43	0566503	JACKET, UTILITY: TYPE: OPERATING; SIZE: 112 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT	EA	2000

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1		
44	0566511	JACKET, UTILITY: TYPE: OPERATING; SIZE: 127 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1	EA	1000
45	0566512	JACKET, UTILITY: TYPE: OPERATING; SIZE: 142 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN	EA	200

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		<p>COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1</p>		
46	0566513	<p>JACKET, UTILITY: TYPE: OPERATING; SIZE: 152 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE</p>	EA	50

		<p>WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1</p>		
47	0566544	<p>JACKET, UTILITY: TYPE: OPERATING; SIZE: 92 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN;</p>	EA	1500

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		<p>FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1</p>		
48	0566545	<p>JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 77 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER</p>	EA	500

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		<p>FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM</p>		
<p>49</p>	<p>0566546</p>	<p>JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 82 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND</p>	<p>EA</p>	<p>500</p>

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM		
50	0566547	JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 92 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM	EA	500
51	0566548	JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 102 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND	EA	500

		<p>WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM</p>		
52	0566549	<p>JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 127 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE-SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE</p>	EA	200

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM		
53	0566550	JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 142 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM	EA	200
54	0566552	JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 112 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT	EA	200

		<p>CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM</p>		
55	0566600	<p>COVERALL: TYPE: ACID/ALKALI; SIZE: 77 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE</p>	EA	1000

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE		
ITEM	MATERIAL	LONG DESCRIPTION	UMC	QTY
		POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM		
56	0566601	COVERALL: TYPE: ACID/ALKALI; SIZE: 82 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822	EA	1000

		<p>FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>		
57	0566602	<p>COVERALL: TYPE: ACID/ALKALI; SIZE: 87 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF</p>	EA	1000

		<p>THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET;</p>		
		<p>THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>		
58	0566603	<p>COVERALL: TYPE: ACID/ALKALI; SIZE: 92 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST</p>	EA	1000

		<p>35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER</p>		
		<p>MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>		
59	0566604	<p>COVERALL: TYPE: ACID/ALKALI; SIZE: 97 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE</p>	EA	1000

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		<p>WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>		
60	0566605	COVERALL: TYPE: ACID/ALKALI; SIZE: 102 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION:	EA	1000

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		<p>UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST</p>		
		<p>POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS</p>		

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM		
61	0566606	COVERALL: TYPE: ACID/ALKALI; SIZE: 107 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED	EA	500
		DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS		

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM		
62	0566607	COVERALL: TYPE: ACID/ALKALI; SIZE: 112 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH	EA	200

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM		
63	0566608	COVERALL: TYPE: ACID/ALKALI; SIZE: 117 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE-SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE	EA	100
		MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER		

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM		
64	0566609	COVERALL: TYPE: ACID/ALKALI; SIZE: 122 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE	EA	50

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		<p>POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>		
65	0566610	<p>LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>	EA	50
66	0566611	<p>COVERALL: TYPE: ACID/ALKALI; SIZE: 132 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED</p>	EA	50

		<p>DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>		
67	0566612	<p>COVERALL: TYPE: ACID/ALKALI; SIZE: 137; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE</p>	EA	20

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE		
		MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM		
68	0566613	COVERALL: TYPE: ACID/ALKALI; SIZE: 142 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE	EA	20

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH		
		AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM		
69	0566614	COVERALL: TYPE: ACID/ALKALI; SIZE: 147 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH	EA	20

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		<p>STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH</p>		
		<p>AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>		
70	0566615	<p>COVERALL: TYPE: ACID/ALKALI; SIZE: 152 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW</p>	EA	20

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		<p>EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF</p>		
		<p>VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>		
71	0566616	<p>COVERALL: TYPE: ACID/ALKALI; SIZE: 157 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE</p>	EA	20

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		<p>CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE</p>		
		<p>BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>		
72	0566736	<p>TROUSERS: TYPE: MEN LONG; SIZE: 152 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362;</p>	EA	40

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION		
73	0566737	TROUSERS: TYPE: MEN LONG; SIZE: 157 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION	EA	20
74	0576286	TROUSERS: TYPE: ACID/ALKALI; SIZE: 77; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; LEG LENGTH: LONG; FIT: REGULAR; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132	EA	250
75	0576287	TROUSERS: TYPE: ACID/ALKALI; SIZE: 82 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132	EA	280
76	0576288	TROUSERS: TYPE: ACID/ALKALI; SIZE: 87 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID-RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP	EA	300

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132		
77	0576289	TROUSERS: TYPE: ACID/ALKALI; SIZE: 97 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132	EA	250
78	0576290	TROUSERS: TYPE: ACID/ALKALI; SIZE: 102 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132	EA	200
79	0576291	TROUSERS: TYPE: ACID/ALKALI; SIZE: 107 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132	EA	200
80	0576292	TROUSERS: TYPE: ACID/ALKALI; SIZE: 112 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO	EA	40

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132		
81	0576293	TROUSERS: TYPE: ACID/ALKALI; SIZE: 117 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132	EA	40
82	0576294	TROUSERS: TYPE: ACID/ALKALI; SIZE: 122 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132	EA	20
83	0576295	TROUSERS: TYPE: ACID/ALKALI; SIZE: 127 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132	EA	20
84	0576296	TROUSERS: TYPE: ACID/ALKALI; SIZE: 132 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER	EA	20

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132		
85	0576297	TROUSERS: TYPE: ACID/ALKALI; SIZE: 137 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132	EA	20
86	0576298	TROUSERS: TYPE: ACID/ALKALI; SIZE: 142 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132	EA	20
87	0576301	TROUSERS: TYPE: ACID/ALKALI; SIZE: 92 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID-RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132	EA	500
88	222553	JACKET, UTILITY: TYPE: THERMAL; SIZE: SMALL; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; SPECIFICATION: 240-44175132 REV 2; INSULATED WITH PRE-	EA	300

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		SHRUNK HOLLOW FIBRE OR A NON-FLAMMABLE MATERIAL; WITH THE OUTER COVERING MADE OF PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4 CLASS C CATEGORY 1; MATERIAL TYPE D59 AND FLAME RETARDANT; JACKET LENGTH: TO REACH BELOW THE BUTTOCKS; POCKETS: ONE CHEST POCKET SHALL BE BELLOWS TYPE - 15CM DEEP AND 14CM WIDE; 4 SIDE POCKETS; POCKETS TO HAVE FLAPS WITH CUT-OFF EDGES THAT CAN BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; THE SIDE POCKET SHALL BE THE BELLOWS TYPE WITH A SIDE ENTRY INTO ANOTHER SEPARATE POCKET AND SHALL BE 22CM DEEP AND 21CM WIDE; JACKETS SHALL HAVE NON-CONDUCTIVE PRESS STUDS DOWN THE FRONT ON A DOUBLE PANEL STRIP; AS WELL AS A NON-CONDUCTIVE ZIP; THE SLEEVE CUFFS SHALL HAVE TWO NON-CONDUCTIVE PRESS STUDS AT THE END OF THE SLEEVE SO THAT THE SIZE CAN BE ADJUSTED; IDENTIFICATION: INDELIBLE MNFRS TRADEMARK; REF NO. AND CLEANING INSTRUCTIONS INSIDE COLLAR ON JACKETS AND SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS		
89	222554	JACKET, UTILITY: TYPE: THERMAL; SIZE: MEDIUM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; SPECIFICATION: 240-44175132 REV 2; INSULATED WITH PRE-SHRUNK HOLLOW FIBRE OR A NON-FLAMMABLE MATERIAL; WITH THE OUTER COVERING MADE OF PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4 CLASS C CATEGORY 1; MATERIAL TYPE D59 AND FLAME RETARDANT; JACKET LENGTH: TO REACH BELOW THE BUTTOCKS; POCKETS: ONE CHEST POCKET SHALL BE BELLOWS TYPE - 15CM DEEP AND 14CM WIDE; 4 SIDE POCKETS; POCKETS TO HAVE FLAPS WITH CUT-OFF EDGES THAT CAN BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; THE SIDE POCKET SHALL BE THE BELLOWS TYPE WITH A SIDE ENTRY INTO ANOTHER SEPARATE POCKET AND SHALL BE 22CM DEEP AND 21CM WIDE; JACKETS SHALL HAVE NON-CONDUCTIVE PRESS STUDS DOWN THE FRONT ON A DOUBLE PANEL STRIP; AS WELL AS A NON-CONDUCTIVE ZIP; THE SLEEVE CUFFS SHALL HAVE TWO NON-CONDUCTIVE PRESS STUDS AT THE END OF THE SLEEVE SO THAT THE SIZE CAN BE ADJUSTED; IDENTIFICATION: INDELIBLE MNFRS TRADEMARK; REF NO. AND CLEANING INSTRUCTIONS INSIDE COLLAR ON JACKETS AND SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS	EA	500
90	222555	JACKET, UTILITY: TYPE: THERMAL; SIZE: LARGE; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; SPECIFICATION: 240-44175132 REV 2; INSULATED WITH PRE-SHRUNK HOLLOW FIBRE OR A NON-FLAMMABLE MATERIAL; WITH THE OUTER COVERING MADE OF PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4 CLASS C CATEGORY 1; MATERIAL TYPE D59 AND FLAME RETARDANT; JACKET LENGTH: TO REACH BELOW THE BUTTOCKS; POCKETS: ONE CHEST POCKET SHALL BE BELLOWS TYPE - 15CM DEEP AND 14CM WIDE; 4 SIDE POCKETS; POCKETS TO HAVE FLAPS WITH CUT-OFF EDGES THAT CAN BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; THE SIDE POCKET SHALL BE THE BELLOWS TYPE WITH A SIDE ENTRY INTO ANOTHER SEPARATE POCKET AND	EA	300

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		SHALL BE 22CM DEEP AND 21CM WIDE; JACKETS SHALL HAVE NON-CONDUCTIVE PRESS STUDS DOWN THE FRONT ON A DOUBLE PANEL STRIP; AS WELL AS A NON-CONDUCTIVE ZIP; THE SLEEVE CUFFS SHALL HAVE TWO NON-CONDUCTIVE PRESS STUDS AT THE END OF THE SLEEVE SO THAT THE SIZE CAN BE ADJUSTED; IDENTIFICATION: INDELIBLE MNFRS TRADEMARK; REF NO. AND CLEANING INSTRUCTIONS INSIDE COLLAR ON JACKETS AND SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS		
91	222556	JACKET, UTILITY: TYPE: THERMAL; SIZE: XLARGE; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; SPECIFICATION: 240-44175132 REV 2; INSULATED WITH PRE-SHRUNK HOLLOW FIBRE OR A NON-FLAMMABLE MATERIAL; WITH THE OUTER COVERING MADE OF PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4 CLASS C CATEGORY 1; MATERIAL TYPE D59 AND FLAME RETARDANT; JACKET LENGTH: TO REACH BELOW THE BUTTOCKS; POCKETS: ONE CHEST POCKET SHALL BE BELLOWS TYPE - 15CM DEEP AND 14CM WIDE; 4 SIDE POCKETS; POCKETS TO HAVE FLAPS WITH CUT-OFF EDGES THAT CAN BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; THE SIDE POCKET SHALL BE THE BELLOWS TYPE WITH A SIDE ENTRY INTO ANOTHER SEPARATE POCKET AND SHALL BE 22CM DEEP AND 21CM WIDE; JACKETS SHALL HAVE NON-CONDUCTIVE PRESS STUDS DOWN THE FRONT ON A DOUBLE PANEL STRIP; AS WELL AS A NON-CONDUCTIVE ZIP; THE SLEEVE CUFFS SHALL HAVE TWO NON-CONDUCTIVE PRESS STUDS AT THE END OF THE SLEEVE SO THAT THE SIZE CAN BE ADJUSTED; IDENTIFICATION: INDELIBLE MNFRS TRADEMARK; REF NO. AND CLEANING INSTRUCTIONS INSIDE COLLAR ON JACKETS AND SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS	EA	30
92	222558	JACKET, UTILITY: TYPE: THERMAL; SIZE: 2XLARGE; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; SPECIFICATION: 240-44175132 REV 2; INSULATED WITH PRE-SHRUNK HOLLOW FIBRE OR A NON-FLAMMABLE MATERIAL; WITH THE OUTER COVERING MADE OF PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4 CLASS C CATEGORY 1; MATERIAL TYPE D59 AND FLAME RETARDANT; JACKET LENGTH: TO REACH BELOW THE BUTTOCKS; POCKETS: ONE CHEST POCKET SHALL BE BELLOWS TYPE - 15CM DEEP AND 14CM WIDE; 4 SIDE POCKETS; POCKETS TO HAVE FLAPS WITH CUT-OFF EDGES THAT CAN BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; THE SIDE POCKET SHALL BE THE BELLOWS TYPE WITH A SIDE ENTRY INTO ANOTHER SEPARATE POCKET AND SHALL BE 22CM DEEP AND 21CM WIDE; JACKETS SHALL HAVE NON-CONDUCTIVE PRESS STUDS DOWN THE FRONT ON A DOUBLE PANEL STRIP; AS WELL AS A NON-CONDUCTIVE ZIP; THE SLEEVE CUFFS SHALL HAVE TWO NON-CONDUCTIVE PRESS STUDS AT THE END OF THE SLEEVE SO THAT THE SIZE CAN BE ADJUSTED; IDENTIFICATION: INDELIBLE MNFRS TRADEMARK; REF NO. AND CLEANING INSTRUCTIONS INSIDE COLLAR ON JACKETS AND SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS	EA	300
93	222559	JACKET, UTILITY: TYPE: THERMAL; SIZE: 3XLARGE; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN	EA	40

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		COTTON; COLOR: NAVY BLUE PANTONE 19_3920; SPECIFICATION: 240-44175132 REV 2; INSULATED WITH PRE-SHRUNK HOLLOW FIBRE OR A NON-FLAMMABLE MATERIAL; WITH THE OUTER COVERING MADE OF PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4 CLASS C CATEGORY 1; MATERIAL TYPE D59 AND FLAME RETARDANT; JACKET LENGTH: TO REACH BELOW THE BUTTOCKS; POCKETS: ONE CHEST POCKET SHALL BE BELLOWS TYPE - 15CM DEEP AND 14CM WIDE; 4 SIDE POCKETS; POCKETS TO HAVE FLAPS WITH CUT-OFF EDGES THAT CAN BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; THE SIDE POCKET SHALL BE THE BELLOWS TYPE WITH A SIDE ENTRY INTO ANOTHER SEPARATE POCKET AND SHALL BE 22CM DEEP AND 21CM WIDE; JACKETS SHALL HAVE NON-CONDUCTIVE PRESS STUDS DOWN THE FRONT ON A DOUBLE PANEL STRIP; AS WELL AS A NON-CONDUCTIVE ZIP; THE SLEEVE CUFFS SHALL HAVE TWO NON-CONDUCTIVE PRESS STUDS AT THE END OF THE SLEEVE SO THAT THE SIZE CAN BE ADJUSTED; IDENTIFICATION: INDELIBLE MNFRS TRADEMARK; REF NO. AND CLEANING INSTRUCTIONS INSIDE COLLAR ON JACKETS AND SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS		
94	732122	COVERALL: TYPE: DISPOSABLE; SIZE: XXXL; MATERIAL: WATERPROOF; STYLE: ONE PIECE; COLOR: WHITE; COMPLY WITH THE FOLLOWING PARTICULATE PROTECTION EN ISO 13982-1 2004 (TYPE 5) CHEMICAL SPLASH PROTECTION EN 13034 2005 +A1 09 (TYPE 6); RADIOACTIVE PROTECTION EN 1073-2 2002; BIOLOGICAL RISK PROTECTION EN 14126 2003\AC 2004; ANTI-STATIC DISCHARGE EN 1149-1 EN 1149-5 2008; NO EQUIVALENT ALLOWED	EA	5000
95	732123	COVERALL: TYPE: DISPOSABLE; SIZE: XXL; 122; 48; MATERIAL: WATERPROOF; STYLE: ONE PIECE; COLOR: WHITE; COMPLY WITH THE FOLLOWING PARTICULATE PROTECTION EN ISO 13982-1 2004 (TYPE 5) CHEMICAL SPLASH PROTECTION EN 13034 2005 +A1 09 (TYPE 6); RADIOACTIVE PROTECTION EN 1073-2 2002; BIOLOGICAL RISK PROTECTION EN 14126 2003\AC 2004; ANTI-STATIC DISCHARGE EN 1149-1 EN 1149-5 2008; NO EQUIVALENT ALLOWED	EA	5000
96	732124	COVERALL: TYPE: DISPOSABLE; SIZE: LARGE; MATERIAL: WATERPROOF; STYLE: ONE PIECE; COLOR: WHITE; COMPLY WITH THE FOLLOWING PARTICULATE PROTECTION EN ISO 13982-1 2004 (TYPE 5) CHEMICAL SPLASH PROTECTION EN 13034 2005 +A1 09 (TYPE 6); RADIOACTIVE PROTECTION EN 1073-2 2002; BIOLOGICAL RISK PROTECTION EN 14126 2003\AC 2004; ANTI-STATIC DISCHARGE EN 1149-1 EN 1149-5 2008; NO EQUIVALENT ALLOWED	EA	5000
97	732127	COVERALL: TYPE: DISPOSABLE; SIZE: XL; 44/46; 112/117; MATERIAL: WATERPROOF; STYLE: ONE PIECE; COLOR: WHITE; COMPLY WITH THE FOLLOWING PARTICULATE PROTECTION EN ISO 13982-1 2004 (TYPE 5) CHEMICAL SPLASH PROTECTION EN 13034 2005 +A1 09 (TYPE 6); RADIOACTIVE PROTECTION EN 1073-2 2002; BIOLOGICAL RISK PROTECTION EN 14126 2003\AC 2004; ANTI-STATIC DISCHARGE EN 1149-1 EN 1149-5 2008; NO EQUIVALENT ALLOWED	EA	5000
98	222561	RAINWEAR: TYPE: 2 PIECE SUIT; SIZE: S; MATERIAL: POLYESTER 100 PCT PLAIN WEAVE, 180 GM/2 MIN; COLOR: BLUE NAVY; MATERIAL: MINIMUM 180 GRAMS PER M/3 FACE SIDE 100% POLYESTER; PLAIN WEAVE WITH 170 THREADS PER M/3 INCH WITH WATER RESISTANT COATING; UNDER SIDE	EA	300

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		LAMINATED WITH PVC COATING; SEAMS STRENGTH 50KPA; CONVERTS TO 50KNM/2; LINING 80% POLYESTER 20% COTTON; SIZE TO SANS 434 SIZE CHART ANNEX E FOR RAIN WEAR; JACKET SHALL HAVE A NYLON SPIRAL ZIP WITH CLOSED FLY FRONT SECURED BY NON-CONDUCTIVE PRESS-STUDS; COMPLY WITH SANS 1822 TYPE 5; HOOD ATTACHED TO THE JACKET; JACKET TO COVER THE BUTTOCKS; FALSE ELASTIC SLEEVE AT THE END MADE OF SOFTER MATERIAL; PANTS SHALL HAVE SIDE SLITS AND ELASTIC WAIST; REFLECTIVE STRIPS TO BE FITTED ON BOTH SLEEVES ON THE UPPER ARM, AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SIDE OF THE SLEEVE AND THE ESKOM LOGO SHALL BE SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON THE FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; UNIQUE IDENTIFIER 240-44175132		
99	222566	RAINWEAR: TYPE: 2 PIECE SUIT; SIZE: L; MATERIAL: POLYESTER 100 PCT PLAIN WEAVE, 180 GM/2 MIN; COLOR: BLUE NAVY; MATERIAL: MINIMUM 180 GRAMS PER M/3 FACE SIDE 100% POLYESTER; PLAIN WEAVE WITH 170 THREADS PER M/3 INCH WITH WATER RESISTANT COATING; UNDER SIDE LAMINATED WITH PVC COATING; SEAMS STRENGTH 50KPA; CONVERTS TO 50KNM/2; LINING 80% POLYESTER 20% COTTON; SIZE TO SANS 434 SIZE CHART ANNEX E FOR RAIN WEAR; JACKET SHALL HAVE A NYLON SPIRAL ZIP WITH CLOSED FLY FRONT SECURED BY NON-CONDUCTIVE PRESS-STUDS; COMPLY WITH SANS 1822 TYPE 5; HOOD ATTACHED TO THE JACKET; JACKET TO COVER THE BUTTOCKS; FALSE ELASTIC SLEEVE AT THE END MADE OF SOFTER MATERIAL; PANTS SHALL HAVE SIDE SLITS AND ELASTIC WAIST; REFLECTIVE STRIPS TO BE FITTED ON BOTH SLEEVES ON THE UPPER ARM, AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SIDE OF THE SLEEVE AND THE ESKOM LOGO SHALL BE SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON THE FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; UNIQUE IDENTIFIER 240-44175132	EA	500
100	222567	RAINWEAR: TYPE: 2 PIECE SUIT; SIZE: XL; MATERIAL: POLYESTER 100 PCT PLAIN WEAVE, 180 GM/2 MIN; COLOR: BLUE NAVY; MATERIAL: MINIMUM 180 GRAMS PER M/3 FACE SIDE 100% POLYESTER; PLAIN WEAVE WITH 170 THREADS PER M/3 INCH WITH WATER RESISTANT COATING; UNDER SIDE LAMINATED WITH PVC COATING; SEAMS STRENGTH 50KPA; CONVERTS TO 50KNM/2; LINING 80% POLYESTER 20% COTTON; SIZE TO SANS 434 SIZE CHART ANNEX E FOR RAIN WEAR; JACKET SHALL HAVE A NYLON SPIRAL ZIP WITH CLOSED FLY FRONT SECURED BY NON-CONDUCTIVE PRESS-STUDS; COMPLY WITH SANS 1822 TYPE 5; HOOD ATTACHED TO THE JACKET; JACKET TO COVER THE BUTTOCKS; FALSE ELASTIC SLEEVE AT THE END MADE OF SOFTER MATERIAL; PANTS SHALL HAVE SIDE SLITS AND ELASTIC WAIST; REFLECTIVE STRIPS TO BE FITTED ON BOTH SLEEVES ON THE UPPER ARM, AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SIDE OF THE SLEEVE AND THE ESKOM LOGO SHALL BE SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON THE FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING	EA	500

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; UNIQUE IDENTIFIER 240-44175132		
101	222568	RAINWEAR: TYPE: 2 PIECE SUIT; SIZE: 2XL; MATERIAL: POLYESTER 100 PCT PLAIN WEAVE, 180 GM/2 MIN; COLOR: BLUE NAVY; MATERIAL: MINIMUM 180 GRAMS PER M/3 FACE SIDE 100% POLYESTER; PLAIN WEAVE WITH 170 THREADS PER M/3 INCH WITH WATER RESISTANT COATING; UNDER SIDE LAMINATED WITH PVC COATING; SEAMS STRENGTH 50KPA; CONVERTS TO 50KNM/2; LINING 80% POLYESTER 20% COTTON; SIZE TO SANS 434 SIZE CHART ANNEX E FOR RAIN WEAR; JACKET SHALL HAVE A NYLON SPIRAL ZIP WITH CLOSED FLY FRONT SECURED BY NON-CONDUCTIVE PRESS-STUDS; COMPLY WITH SANS 1822 TYPE 5; HOOD ATTACHED TO THE JACKET; JACKET TO COVER THE BUTTOCKS; FALSE ELASTIC SLEEVE AT THE END MADE OF SOFTER MATERIAL; PANTS SHALL HAVE SIDE SLITS AND ELASTIC WAIST; REFLECTIVE STRIPS TO BE FITTED ON BOTH SLEEVES ON THE UPPER ARM, AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SIDE OF THE SLEEVE AND THE ESKOM LOGO SHALL BE SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON THE FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; UNIQUE IDENTIFIER 240-44175132	EA	200
102	222569	RAINWEAR: TYPE: 2 PIECE SUIT; SIZE: 3XL; MATERIAL: POLYESTER 100 PCT PLAIN WEAVE, 180 GM/2 MIN; COLOR: BLUE NAVY; MATERIAL: MINIMUM 180 GRAMS PER M/3 FACE SIDE 100% POLYESTER; PLAIN WEAVE WITH 170 THREADS PER M/3 INCH WITH WATER RESISTANT COATING; UNDER SIDE LAMINATED WITH PVC COATING; SEAMS STRENGTH 50KPA; CONVERTS TO 50KNM/2; LINING 80% POLYESTER 20% COTTON; SIZE TO SANS 434 SIZE CHART ANNEX E FOR RAIN WEAR; JACKET SHALL HAVE A NYLON SPIRAL ZIP WITH CLOSED FLY FRONT SECURED BY NON-CONDUCTIVE PRESS-STUDS; COMPLY WITH SANS 1822 TYPE 5; HOOD ATTACHED TO THE JACKET; JACKET TO COVER THE BUTTOCKS; FALSE ELASTIC SLEEVE AT THE END MADE OF SOFTER MATERIAL; PANTS SHALL HAVE SIDE SLITS AND ELASTIC WAIST; REFLECTIVE STRIPS TO BE FITTED ON BOTH SLEEVES ON THE UPPER ARM, AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SIDE OF THE SLEEVE AND THE ESKOM LOGO SHALL BE SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON THE FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; UNIQUE IDENTIFIER 240-44175132	EA	200
103	222529	COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 77 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED	EA	1000

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		<p>TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND</p>		
		<p>SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>		
104	222530	<p>COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 82 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE</p>	EA	1000

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		<p>BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>		
105	222531	<p>COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 87 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE</p>	EA	1000

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		<p>JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE</p>		
		<p>POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>		
106	222533	COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 92 CM;	EA	1000

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		<p>MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF</p>		
		<p>THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A</p>		

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM		
107	222534	COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 97 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES	EA	1000

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM		
108	566588	COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 102 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO	EA	1000

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		<p>AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>		
<p>109</p>	<p>566589</p>	<p>COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 117 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE;</p>	<p>EA</p>	<p>500</p>

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		<p>POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>		
110	566590	<p>COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 137; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE</p>	EA	300

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		<p>FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>		
<p>111</p>	<p>566591</p>	<p>COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 107 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS</p>	<p>EA</p>	<p>1000</p>

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM		
112	566592	COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 132 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE	EA	300

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		<p>PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>		
<p>113</p>	<p>566593</p>	<p>COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 127 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE</p>	<p>EA</p>	<p>500</p>

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		<p>MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>		
114	566595	<p>COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 142 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS;</p>	EA	100

		<p>WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A</p>		
		<p>PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>		
115	566597	<p>COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 147 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET</p>	EA	100

		<p>MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES</p>		
		<p>SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>		
116	566598	<p>COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 112 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES</p>	EA	500

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		<p>SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO</p>		
		<p>AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>		
117	566599	<p>COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 122 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND</p>	EA	500

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		<p>STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>		
118	643029	<p>TROUSERS: TYPE: ACID RESIST; SIZE: 147; COLOR: GREEN BOTTLE; MATERIAL: POLYCOTTON; TO COMPLY WITH ESKOM SPECIFICATION 240-44175132; MATERIAL TO BE POLY COTTON FABRIC (65/35)</p>	EA	100
119	643028	<p>TROUSERS: TYPE: ACID RESIST; SIZE: 142; COLOR: GREEN BOTTLE; MATERIAL: POLYCOTTON; TO COMPLY WITH ESKOM SPECIFICATION 240-44175132; MATERIAL TO BE POLY COTTON FABRIC (65/35)</p>	EA	100
120	643020	<p>TROUSERS: TYPE: ACID/ALKALI; SIZE: 102 CM; COLOR: BOTTLE GREEN; MATERIAL: POLYESTER/VISCOSE; 65/35 PCT; SPECIFICATION: 240-44175132-REV 2; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC:</p>	EA	250

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS		
121	643018	TROUSERS: TYPE: ACID/ALKALI; SIZE: 92 CM; COLOR: BOTTLE GREEN; MATERIAL: POLYESTER/VISCOSE; 65/35 PCT; SPECIFICATION: 240-44175132-REV 2; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS	EA	250
122	643019	TROUSERS: TYPE: ACID/ALKALI; SIZE: 97 CM; COLOR: BOTTLE GREEN; MATERIAL: POLYESTER/VISCOSE; 65/35 PCT; SPECIFICATION: 240-44175132-REV 2; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS	EA	250
123	643015	TROUSERS: TYPE: ACID/ALKALI; SIZE: 77 CM; COLOR: BOTTLE GREEN; MATERIAL: POLYESTER/VISCOSE 65/35 PCT; SPECIFICATION: 240-44175132-REV 2; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS	EA	250
124	643017	TROUSERS: TYPE: ACID/ALKALI; SIZE: 87 CM; COLOR: BOTTLE GREEN; MATERIAL: POLYESTER/VISCOSE; 65/35 PCT; SPECIFICATION: 240-44175132-REV 2; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP	EA	250

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS		
125	642998	JACKET, OVERALL: TYPE: ACID RESIST; SIZE: 77; MATERIAL: POLYCOTTON; COLOR: GREEN BOTTLE; COMPLY WITH ESKOM PPE SPECIFICATION; MATERIAL TO BE POLY COTTON FABRIC (65/35)	EA	250
126	643012	JACKET, OVERALL: TYPE: ACID RESIST; SIZE: 147; MATERIAL: POLYCOTTON; COLOR: GREEN BOTTLE; COMPLY WITH ESKOM PPE SPECIFICATION; MATERIAL TO BE POLY COTTON FABRIC (65/35)	EA	100
127	643011	JACKET, OVERALL: TYPE: ACID RESIST; SIZE: 142; MATERIAL: POLYCOTTON; COLOR: GREEN BOTTLE; COMPLY WITH ESKOM PPE SPECIFICATION; MATERIAL TO BE POLY COTTON FABRIC (65/35)	EA	100
128	643005	JACKET, OVERALL: TYPE: ACID/ALKALI; SIZE: 112 CM; MATERIAL: POLYESTER/VISCOSE; 65/35 PCT; COLOR: BOTTLE GREEN; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE	EA	250
		BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM		
129	643003	JACKET, OVERALL: TYPE: ACID/ALKALI; SIZE: 102 CM; MATERIAL: POLYESTER/VISCOSE; 65/35 PCT; COLOR: BOTTLE	EA	250

		<p>GREEN; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY</p>		
		<p>TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM</p>		
130	643002	<p>JACKET, OVERALL: TYPE: ACID/ALKALI; SIZE: 97 CM; MATERIAL: POLYESTER/VISCOSE; 65/35 PCT; COLOR: BOTTLE GREEN; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE</p>	EA	250

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM		
131	643001	JACKET, OVERALL: TYPE: ACID/ALKALI; SIZE: 92 CM; MATERIAL: POLYESTER/VISCOSE; 65/35 PCT; COLOR: BOTTLE GREEN; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM	EA	250
132	643000	JACKET, OVERALL: TYPE: ACID/ALKALI; SIZE: 87 CM; MATERIAL: POLYESTER/VISCOSE; 65/35 PCT; COLOR: BOTTLE GREEN; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF	EA	250

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS: A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM		
133	643022	TROUSERS: TYPE: ACID/ALKALI; SIZE: 112 CM; COLOR: BOTTLE GREEN; MATERIAL: POLYESTER/VISCOSE 65/35 PCT; SPECIFICATION: 240-44175132-REV 2; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS	EA	250
134	160597	WADER: TYPE: FISHERMANS; SIZE: 11; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132	50	
135	160596	WADER: TYPE: FISHERMANS; SIZE: 10; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132	50	
136	566391	WADER: TYPE: FISHERMANS; SIZE: 12; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132	50	
137	160593	WADER: TYPE: FISHERMANS; SIZE: 7; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132	50	
138	160594	WADER: TYPE: FISHERMANS; SIZE: 8; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132	50	
139	160595	WADER: TYPE: FISHERMANS; SIZE: 9; MATERIAL: PVC; COLOR:	50	

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

		GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132		
140	566383	WADER: TYPE: FISHERMANS; SIZE: 6; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132	50	
141	566392	WADER: TYPE: FISHERMANS; SIZE: 13; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132	50	

2.1 Purchaser’s design

2.2 Procedure for submission and acceptance of Supplier’s design

The Supplier must supply as per the item description and as and when required to do so.

2.3 Other requirements of the Supplier’s design

2.4 Use of Supplier’s design

2.5 Manufacture & fabrication

All materials to comply to Eskom standards

2.6 Factory acceptance testing (FAT)

The Purchaser may request FAT and material inspection

2.7 Other tests and inspections and commissioning in place of use

Quality control checks documentation is in place at Arnot Power Station at the Main Store (Receiving)

2.8 Operating manuals and maintenance schedules

3 Supply Requirements

The Supply Requirements for this contract are in an Annexure to the Contract Data provided by the Purchaser.

4 Specification of the services to be provided

All materials to comply with Eskom standards.

5 Constraints on how the Supplier Provides the Goods

5.1 Programming constraints

5.2 Work to be done by the Delivery Date

All goods are to be delivered as per the quantity required and quality check to be done after every delivery

5.3 Marking the goods

5.4 Constraints at the delivery place and place of use

The **PPE Accessories** must be delivered at Arnot Power Station Stores between Monday and Thursday at 09:00 to 15:00. On Friday, between 9:00 and 12:00

5.5 Cooperating with Others

The Supplier must fully co-operate with the Purchaser’s team during off-loading at the project site

5.6 Services & other things to be provided by the Purchaser or Supplier

5.7 Management meetings

Regular meetings of a general nature may be convened and chaired by the *Supply Manager* as follows:

Title and purpose	Approximate time & interval	Location	Attendance by:
Risk register and compensation events	On request by Purchaser	Arnot Power Station/ MS Teams	Purchaser and Supplier representative
Overall contract progress and feedback	On request by Purchaser or Supplier	Arnot Power Station/ MS Teams	Purchaser and Supplier representative

Meetings of a specialist nature may be convened as specified elsewhere in this Goods Information or if not so specified by persons and at times and locations to suit the Parties, the nature and the progress of the manufacture of the goods. Records of these meetings shall be submitted to the Supply Manager by the person convening the meeting within five days of the meeting.

All meetings shall be recorded using minutes or a register prepared and circulated by the person who convened the meeting. Such minutes or register shall not be used for the purpose of confirming actions or instructions under the contract as these shall be done separately by the person identified in the conditions of contract to carry out such actions or instructions.

5.8 Documentation control

All documentation from the Supplier must be provided in hard copy and must also be emailed to the Supply Manager, as per the communication process agreed after contract award.

5.9 Health and safety risk management

The Supplier shall comply with the health and safety requirements:

- Control of noise is through wearing hearing protection
- Dust, dust suppression or as the last resort issue dust mask
- Waste, put waste in the correct waste bin
- Water to be conserve, use as little as possible
- Adhere to all Eskom lifesaving rules

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

A. Road Safety

- a. Speed limit: 40km/h
- b. By passing Speed humps not allowed
- c. Transporting People at the back of the bakkie is not allowed
- d. Buckle up always
- e. Park only at demarcated areas

B. Sanitation

- a. Toilets for both genders are available at the plant

C. Emergency

- a. The emergency number for Arnot is 013 297 9184 Pax:5184
- b. Emergency alarms are tested every Wednesday 10H00

D. Access

- a. Before access can be granted the following must be met:
- b. SHE Induction attended.

COMPLIANCE TO 5 IDENTIFIED CARDINAL RULES:

Rule1: Open, Isolate, Test, Earth, Bond, and/or insulate before touch
(That is, any plant operating above 1 000 V)

No person may work on any electrical network unless:

- He/she is trained and authorised as competent for the task to be done.
- A pre-task risk assessment to identify all risks and hazards has been conducted prior to any work commencing.
- An equipotential zone is created for each worker on the job site by earthing, bonding, and/or insulating according to approved procedures.
- All conducting material is connected, all staff on site wear electrical safety shoes, and insulating techniques are applied according to standards; and
- The authorised person (team leader) has certified and shown all team members that the apparatus is safe to work on.

Rule 2: Hook up on heights

Working at height is defined as any work performed above a stable work surface or where a person puts himself/herself in a position where he/she exposes himself/herself to a fall from or into.

No person may work at height where there is a risk of falling unless:

- A pre-task risk assessment to identify all risks and hazards has been conducted prior to commencing any work at height.
- He/she is appropriately trained.
- He/she is appropriately secured during ascending and descending and
- He/she is using an approved fall arrest system where applicable.

Rule 3: Buckle up

No person may drive any vehicle on Eskom business and/or on Eskom premises unless the driver and all passengers are wearing seat belts.

Rule 4: Be Sober

- 1 No person is allowed to work under the influence of drugs and alcohol.
- 2 "Under the influence" means the use of alcohol, drugs, and/or a controlled substance to the extent that
 - 1 He individual's faculties are in any way impaired by the consumption or use of the substances; or

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

- 2 The individual is unable to perform in a safe, productive manner; or
- 3 The individual has a level of any such substance in his/her body that corresponds to or exceeds accepted medical/legal standards; or
- 4 The individual has a level of alcohol in his/her body that is greater than 0.02% blood alcohol concentration.

This includes any level of an illegal substance in the body, irrespective of when the substance was used.

Rule 5: Ensure that you have a permit to work

Where an authorisation limitation exists, no person shall work without the required Permit to Work (PTW), which is governed by the Plant Safety Regulations, Operating Regulations for High Voltage Systems (ORHVS) etc.

No plant is to be returned to service without the cancellation of all permits on that plant in accordance with procedure.

NB: In the case of live work, a "live work declaration form" is to be completed by the authorised person who is the person responsible for the safe execution of work according to relevant standards and procedures.

Please ensure that these rules are understood and communicated with the urgency that they deserve. If any of these rules are unclear or the consequences not understood, please do not hesitate to discuss it with Eskom.

We would like to continue our current partnership and therefore urge your support in the implementation and upholding of these rules.

5.10 Environmental constraints and management

The Supplier shall comply with the health and safety requirements contained the Purchaser's SHE Specification

5.11 Quality

Quality check sheet should be in place.

The Supplier will be expected to comply with Supplier Quality Management Specification 240-105658000 (previously called QM58) and ISO: 9001 requirements and other Eskom Holdings SOC Limited's Standards and specifications.

5.12 Invoicing and payment

Within one week of receiving a payment certificate from the *Supply Manager* in terms of core clause 51.1, the *Supplier* provides the *Purchaser* with a tax invoice showing the amount due for payment equal to that stated in the *Supply Manager's* certificate.

The *Supplier* shall address the tax invoice to *Purchaser* and include on each invoice the following information:

- Name and address of the *Supplier* and the *Supply Manager*;
- The contract number and title;
- *Supplier's* VAT registration number;
- The *Purchaser's* VAT registration number.
- Description of *goods* and *services* provided for each item invoiced based on the Price Schedule;
- Total amount invoiced excluding VAT, the VAT and the invoiced amount including VAT;

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

- (add other as required)

Detailed tax invoice, clearly showing: Eskom Holdings SOC LTD
Electronic copy to Finance Shared Services
Megawatt Park

5.13 Insurance provided by the *Purchaser*

Refer to Annexure B – Insurance to be provided by the Purchaser

5.14 Contract change management

Clause 6 Compensation events of the NEC3 Supply Contract will apply to all changes in this contract.

5.15 Provision of bonds and guarantees

Not Applicable

5.16 Records of Defined Cost, payments & assessments of compensation events to be kept by the *Supplier*

All records and quality documentation must be provided in hard copy and must be electronically emailed to the Supply manager

6 Procurement

6.1 Subcontracting

6.1.1 Preferred subcontractors

SC does not make use of nominated subcontracting, but the *Purchaser* may list which subcontractors or sub-suppliers the *Supplier* is required to enter into subcontracts with (if any). This is usually only required where plant and materials need to be obtained from a particular supplier or group of suppliers in order to comply with operational standards for the *goods*.

6.1.2 Limitations on subcontracting

6.1.3 Spares and consumables

6.1.4 Other requirements related to procurement

6.1.5 Cataloguing requirements by the *Supplier*

7 List of drawings

7.1 Drawings issued by the *Purchase*

CONTRACT TITLE: SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE CLOTHING ON AS AND WHEN REQUIRED AT ARNOT POWER STATION FOR THE PERIOD OF FIVE (5) YEARS

C3.2 SUPPLIERS GOODS INFORMATION

THIS SECTION OF THE GOODS INFORMATION WILL ALWAYS BE CONTRACT SPECIFIC DEPENDING ON THE NATURE OF THE GOODS AND SERVICES. IT IS MOST LIKELY TO BE REQUIRED FOR SUPPLY CONTRACTS WHERE THE TENDERING SUPPLIER WILL HAVE PROPOSED SPECIFICATIONS AND SCHEDULES FOR THE GOODS AND SERVICES, WHICH ONCE ACCEPTED BY THE PURCHASER PRIOR TO AWARD OF CONTRACT NOW BECOME OBLIGATIONS OF THE SUPPLIER PER CORE CLAUSE 20.1.

THIS SECTION COULD ALSO BE COMPILED AS A SEPARATE FILE.