


DAMPER CAT. NO.	ATTACHMENT ROD CAT. NO.	CONDUCTOR NAME	CONDUCTOR RANGE (mm)	ATTACHMENT RODS			MASS (kg)
				COLOUR CODE	SHOP LENGTH (mm)	WIRE DIAMETER (mm)	
VSD-128	VSDRD 390/413	HAZEL, RABBIT, FLY	9.91-10.49	YELLOW	560	4.47 ^{+0.00} _{-0.08}	1.5
	VSDRD 414/436	PINE, BLUEBOTTLE, MINK	10.52-11.07	RED	560	4.47 ^{+0.00} _{-0.08}	1.5
	VSDRD 437/463	EARWIG	11.10-11.76	BLUE	560	4.47 ^{+0.00} _{-0.08}	1.5
	VSDRD 464/490	WILLOW, RACoon	11.79-12.45	GREEN	590	4.47 ^{+0.00} _{-0.08}	1.5
	VSDRD 491/521	SKUNK	12.47-13.23	ORANGE	600	5.18 ^{+0.00} _{-0.08}	1.5
	VSDRD 522/558	OAK, DOG, HARE, 19/2.7, 19/2.65	13.26-14.17	BROWN	600	5.18 ^{+0.00} _{-0.08}	1.5
	VSDRD 559/585	-	14.20-14.86	WHITE	740	6.35 ^{+0.00} _{-0.08}	1.5
	VSDRD 586/606	-	14.88-15.39	BLUE	800	6.35 ^{+0.00} _{-0.08}	1.6
	VSDRD 607/630	MULBERRY	15.42-16.00	ORANGE	800	6.35 ^{+0.00} _{-0.08}	1.6
	VSDRD 631/655	HORNET, TIGER	16.03-16.64	RED	800	6.35 ^{+0.00} _{-0.08}	1.6
	VSDRD 656/679	-	16.66-17.25	BLACK	845	6.35 ^{+0.00} _{-0.08}	1.6
	VSDRD 680/703	ASH	17.27-17.86	YELLOW	865	6.35 ^{+0.00} _{-0.08}	1.6
	VSDRD 704/739	WOLF	17.88-18.77	WHITE	890	6.35 ^{+0.00} _{-0.08}	1.6
	VSDRD 740/782	ELM, CHICADEE	18.80-19.86	RED	960	6.35 ^{+0.00} _{-0.08}	1.6
VSD-177	VSDRD 783/814	LARK, IBIS	19.89-20.68	GREEN	990	6.35 ^{+0.00} _{-0.08}	2
	VSDRD 815/845	PELICAN, LEMON	20.7-21.46	BROWN	960	6.35 ^{+0.00} _{-0.08}	2
	VSDRD 846/907	FLICKER, HAWK, SYCAMORE	21.49-23.04	YELLOW	820	6.35 ^{+0.00} _{-0.08}	2
VSD-271	VSDRD 908/942	BEAR, KINGBIRD	23.06-23.93	ORANGE	900	6.35 ^{+0.00} _{-0.08}	2
	VSDRD 943/983	UPAS	23.95-24.99	GREEN	918	7.62 ^{+0.00} _{-0.08}	2



CONTRACTOR NAME	
PROJECT NAME:	
CONDUCTOR SIZE:	
PART NO.:	

E	2023/11/02	S.C	JE		UPDATED ATTACHMENT ROD INFORMATION IN TABLE
D	3/14/2023	P.B	JE		ADDED CONDUCTOR INFO
C	16/02/2023	R.B	JE		UPDATED CONDUCTOR INFORMATION IN TABLE
B	2021/11/07	KC	JE		UPDATED TABLE WITH VSD RODS
A	13/07/2018	T.E	JE		UPDATED TABLE FOR VSD-271
REV.	REV DATE	DRWN	APVD	APVD	DESCRIPTION

CUSTOMER DRAWING TITLE

VORTX™ VIBRATION DAMPER

TOLERANCES
UNLESS NOTED

0. ± 1
0.0 ± 0.25
0.00 ± 0.1
ANGLES ± 1°

UNITS

mm

DO NOT SCALE

THIRD ANGLE PROJECTION



NOTES:

- ESKOM DDT-7005
 - CORROSION SPEC - SANS121/ISO 1461
 - CONTACT PLP FOR PLACEMENT GUIDANCE & ADDITIONAL SIZES.
 - DAMPER ASSEMBLY AND ATTACHMENT RODS ORDERED SEPARATE.
- FOR EXAMPLE TO ORDER A DAMPER FOR AN 18MM CONDUCTOR, A VSD-128 DAMPER AND MRSDRD 704-739 ATTACHMENT RODS MUST BE ORDERED.



PREFORMED LINE PRODUCTS

The connection you can count on.

(PLP SOUTH AFRICA)

CONFIDENTIAL

THIS DRAWING IS THE EXCLUSIVE PROPERTY OF PREFORMED LINE PRODUCTS COMPANY AND IS TO BE USED ONLY WITH THE PRIOR EXPRESSED PERMISSION OF PLP.

DRWN: M.H	DATE: 2018/02/20	PLP CATALOGUE NUMBER: VSD	PLP PART NUMBER: SEE CAT. NO.
APVD: JE	DATE: 06/11/2023	CUSTOMER I.D. NUMBER	PLP DRAWING NUMBER: VSD SALES
APVD:	DATE:	SCALE: 1:1	SHEET No.: 1 OF 1
		PLP ORIGIN NUMBER: PLP-SA	REV: E

INTERNAL USE ONLY: FILENAME: VSD SALES