

02.02.2026

Material Details (ZMMM138P)

1

Material No : 50051704 COMPRESSOR LPG 2-CYL GAS SERVICE
BOCK

UOM : EA
Prod Insp Memo:

Mat Type : ERSA
Doc No & Vers :

Mat Group : 40151600
Mat Division : W2

Purchase Order Text:

ITEM	- COMPRESSOR LPG
TYPE	- TWO-CYLINDER, GAS COMPRESSOR
SERVICE	- LPG
VOLTAGE RATING	- N/A
WATTAGE	- N/A
PHASE	- N/A
SUCTION PRESSURE	- 1000 KPA
DISCHARGE PRESSURE	- 1500 KPA
DISCHARGE FLOW	- 50 M3/HR
CONNECTION	- 2" 300LB FLANGED
MODEL NUMBER	- UNKNOWN
PART NUMBER	- UNKNOWN
MANUFACTURER	- N/A

Classification:

SEMI-HERMETIC
380 - 420VAC
N/A
BOCK
3 PHASE
HGX44E/665-4 S

ANCILLARY EQUIPMENT:

- | | |
|---------------------------|----------------------------------------|
| 1) 4-WAY VALVES | - FOR LPG TRANSFER AND VAPOUR RECOVERY |
| 2) FLOAT SWITCHES | - ALARM/TRIP ON HIGH AND LOW LIQUID LE |
| 3) PRESSURE SWITCHES | - SUCTION LOW/LOW-LOW TRIP AND DISCHAR |
| HIGH ALARM | |
| 4) TEMPERATURE SWITCHES | - DISCHARGE GAS AND OIL TEMP ALARM/TRI |
| 5) LIQUID TRAPS | - INSTALLED IN SUCTION LINE |
| 6) LIQUID TRAPS (ASME) | - ASME CODED SUCTION LINE TRAP |
| 7) STRAINER | - 30-MESH STAINLESS STEEL SCREEN |
| 8) BELT GUARDS | - STEEL CONSTRUCTION |
| 9) PRESSURE GAUGES | - SUCTION, DISCHARGE AND OIL LOCATIONS |
| 10) THERMOWELLS | - INSTALLED ON DISCHARGE LINE |
| 11) RELIEF VALVES | - DISCHARGE PSV TO SUCTION OR STORAGE |
| 12) SHUT-OFF VALVES | - MANUAL OR ACTUATED |
| 13) MOTOR / ENGINE DRIVER | - SUITABLE FOR AREA CLASS AND FUEL TY |

NOTE:

COMPRESSOR SUITABLE FOR LPG TRANSFER AND VAPOUR RECOVERY SERVICE.
ALL SAFETY AND CONTROL DEVICES TO COMPLY WITH APPLICABLE CODES
AND SITE REQUIREMENTS.