

TECHNICAL SPECIFICATION FOR TELEHANDLERS

10ton TELEHANDLER

- Maximum lifting capacity: 10,000kg
- Maximum lifting height: 9.52m
- Maximum Reach: 5.05m
- Capacity at Max. Reach: 2600kg
- Deutz TCD 3.6 L4 - stage IV
- Transmission: Hydraulic circuit (350 bar)
- Travel speed: 40 km/h
- Steering radius: 4.725 m
- Drawbar pull: 88kN
- Digital load moment sensing and load management
- Automatic attachment identification
- Pressurized cab, air conditioning
- Fork carriage 10T (with fork positioner)
- Floating fork carriage with capacity up to 10000kg, with hydraulic movement of the individual forks positioner
- Capacity: 10.000 kg (center of gravity 471 mm)
- Fork dimensions: 200 x 60 x 1.500 mm
- Maximum opening: 1.740 mm
- Minimum opening: 820 mm
- Automatic attachments identification tag

5.5 Ton Telehandler

- Maximum lifting capacity: 5,500kg
- Maximum lifting height: 18.80m
- Maximum Reach: 14.1m
- Capacity at Max. Reach: 1000 kg (On Stabilizers)
- Deutz TCD 3,6 L4 EDG Stage IIIA
- Transmission: Hydrostatic (470 bar)
- Travel speed: 35 km/h
- Steering radius: 5.610m
- Drawbar pull: 72kN
- Automatic attachments identification tag
- FOPS/ROPS

ssible.