



Request for Quote

Printed: 30.03.2023

Page:
Number:
Date:

1 of 3
6000369266
30.03.2023

VAT REG NO: 4740101508

ESKOM HOLDINGS GENERATION
eskom holdings generation Ltd
P O Box 2634
johannesburg
2157

RFQ Collective number
MPMAJ10626GX
Contact person
ETHEL PINDIWE SIGONYA

Your person responsible/Your reference

Please deliver to: Majuba
Power Station. Volksrust -
Amersfoort Road. Volksrust.
2470

Your vendor number with us
11070302
Quotation deadl.: 20.04.2023

Delivery date: Day 28.07.2023

SUPPLY AND DELIVER OF VARIOUS SPARES AT MAJUBA POWER STATION

Tender number: MPMAJ0626GX
Issue date: 30 March 2023
Closing date and time: 20 April 2023 at 1 0:00am South African Standard Time
Tender validity period: Fifty two (52) weeks from the closing date and time
Clarification meeting: NIA

Tenders are to be delivered to the following address on the stipulated closing date and time: Eskom Holdings SOC Ltd

Tender Centre No.10 Smuts Avenue
Witbank / Emalahleni
Mpumalanga
1035



Request for Quote

Printed: 30.03.2023

Page: 2 of 3
Number: 6000369266
Date: 30.03.2023

VAT REG NO: 4740101508

ESKOM RESERVES THE RIGHT TO SPLIT ORDERS

Item	Material	Description	Deliv. date
RFQ quantity	Unit		
00010	0717517 12	VLV ASSY:BUTTERFLY;200 MM;1.6 MPA;200 MM each VALVE ASSEMBLY: TYPE: BUTTERFLY; SIZE: 200 MM; BODY MATERIAL: BS 1504 161GD 430; PRESSURE RATING: 1.6 MPA; CONNECTION SIZE: 200 MM; CONNECTION TYPE: LUGGED SINGLE FLANGE (WAFER) TO BS4504 PN16; OPERATED: PNEUMATIC ACTUATOR; VALVE QUANTITY: 1; FACE TO FACE LENGTH: 61 MM; FLOW RATE: 4132.7 KG/HR; TRIM: SHAFT 17/4 PH STAINLESS STEEL ; DISK & SEAL 316L STAINLESS STEEL; SOFTGOODS: GRAPHITE PACKING; MEDIUM: STEAM; APPLICATION: CONTROL VALVE; SPECIFICATION: EN 558 ; EN 12516-1; DRAWING NO: FISHER 2825X100; STYLE : HPBV ; DESIGN TEMPERATURE : 325 DEG C ; DESIGN PRESSURE : 1 MPA, GRADE 430 ; INCLUDING ACTUATOR : 200MM 2052-8580 SIZE 3	
00020	0718348 12	VLV ASSY:BUTTERFLY;100 MM;CARBON STEEL;1 each VALVE ASSEMBLY: TYPE: BUTTERFLY; SIZE: 100 MM; BODY MATERIAL: CARBON STEEL; PRESSURE RATING: 1.6 MPA; CONNECTION SIZE: 100 MM; CONNECTION TYPE: LUGGED SINGLE FLANGE (WAFER) TO BS4504 PN16; OPERATED: PNEUMATIC ACTUATOR; VALVE QUANTITY: 1; FACE TO FACE LENGTH: 53 MM; FLOW RATE: 32.4 L/S; TRIM: SHAFT 17/4 PH STAINLESS STEEL ; DISK & SEAL 316L STAINLESS STEEL; SOFTGOODS: PTFE PACKING AND SEAL; MEDIUM: WATER; APPLICATION: CONTROL VALVE; SPECIFICATION: EN 558 ; EN 12516-1; STANDARD: GRADE ASTM A216 WCC; DRAWING NO: FISHER IQ32476; DESIGN PRESSURE: 1.0 MPA; DESIGN TEMPERATURE: 60 DEGC; TEMPERATURE RATING: 232DEGC; TRIM MATERIAL: SOFT SEAL; STEM DESIGN: 3/4"; SHAFT VISIBLE; ACTUATOR SIZE: 1, 100MM 2052-8580, SERIAL NUMBER 15725281	
00030	0718969 12	VLV ASSY:BUTTERFLY;250 MM;CARBON STEEL;1 each VALVE ASSEMBLY: TYPE: BUTTERFLY; SIZE: 250 MM; BODY MATERIAL: CARBON STEEL; PRESSURE RATING: 1.6 MPA; CONNECTION SIZE: 250 MM; CONNECTION TYPE: FLANGED BS4504 PN16; OPERATED: PNEUMATIC ACTUATOR; VALVE QUANTITY: 1; FACE TO FACE LENGTH: 69 MM; FLOW RATE: 140 L/S; TRIM: SHAFT 17/4 PH STAINLESS STEEL; DISK 316L STAINLESS STEEL; SOFTGOODS: PTFE PACKING AND SEAL; MEDIUM: WATER; APPLICATION: CONTROL VALVE; SPECIFICATION: EN 558 ; EN 12516-1; STANDARD: GRADE ASTM A216 WCC; DRAWING NO: FISHER IQ32476; DESIGN PRESSURE: 1.0 MPA; DESIGN TEMPERATURE: 60 DEGC; TEMPERATURE RATING: 232DEGC; TRIM MATERIAL: SOFT SEAL; STEM DESIGN: 3/4" SHAFT VISIBLE; ACTUATOR SIZE: 3, 100MM 2052-8580 SERIAL NUMBER 15725280	



Request for Quote

Printed: 30.03.2023

Page:
Number:
Date:

3 of 3
6000369266
30.03.2023

00040

10

each

VALVE BTRFLY:WAFER TYPE;200 MM;DOUBLE D

Your material number STM-151360

VALVE, BUTTERFLY: TYPE: WAFER TYPE; VALVE SIZE: 200 MM; DESIGN RATING:
DOUBLE D; TEMPERATURE RATING: 0 TO 20 DEG C; CONNECTION: DOUBLE FLANGE (16)
DIA 22 MM, PCD 460 MM; BODY MATERIAL: C1; FACE TO FACE LENGTH: 100 MM;
OPERATED: 1; DOUBLE D, BUTTERFLY VALVES, WAFER TYPE