
GEAR DATA
SEE DETAIL
2 OFF DRAIN HOLES
EQUI-SPACED ON PCD
1 ON SIDE ONLY
SECTION
DETAIL HEIGHT
SCALE 1 : 1
NOTES
1. CASE HARDENING TO 10-64 HRC TO A DEPTH OF 1.0 TO 1.3 mm
2. MACHINING TO BE DONE AFTER HEAT TREATMENT
3.
4. REFLECT LOADED FLANKS OF DETAIL DRAWING
5. CHAMFERING AND LENGTH TO BE 3 TO 10
6. MATERIAL 655 N/mm² ALTERNATIVE MATERIAL 832 N/mm² TO B.S. 970
DATA FOR SPUR AND HELICAL GEARS
GEAR QUALITY - ERRORS
PROFILE DIAGRAM
TRANSVERSE SECTION
STUDS LEFT FOR DRAWING No.3
PROTUBERANCE DATA TO BE STAMPED BY CUTTER MANUFACTURER
1.
2.
TOOTH PROFILE - TRANSVERSE SECTION
LEGEND
SEE CASTING DRAWING
SEE DETAIL DRAWING
DRILL 2 HOLES 10 mm
DRILL TO 21
DRILL TO 2 DEPTHS mm. 5
DRILL TO 2 DEPTHS mm. 5
APPROXIMATE WEIGHTS CONDITION
TO BE STAMPED LEGIBLY ON
HUB & TAKE SHIELDS
MATIMBA POWER STATION
GENERAL ARRANGEMENT
OUTPUT SHAFT DETAIL
Eskom
28.50/54879