

SECTION 4200: ASPHALT BASE AND SURFACING			
ITEM	DESCRIPTION	UNIT	RATE
42.00	ASPHALT BASE AND SURFACING (continued)		
42.04	Tack coat of 30% stable grade emulsion (anionic/cationic)	litre	
42.05	Binder variations:		
	(1) 50/70 penetration grade bitumen	ton	
	(2) 70/100 penetration grade bitumen	ton	
	Binder modifier variations:		
	(4) A-E2 (Styrene-butadiene-styrene (SBS)) modified bitumen	ton	
	(5) A-P1 (Ethyl Vinyl Acetate (EVA)) modified bitumen	ton	
	(6) A-R1 (Rubber) modified bitumen	ton	
	(7) A-R2 (Rubber) modified bitumen	ton	
42.06	Variations in active filler content		
	(a) cement	ton	
	(b) lime	ton	
B42.07	Extra over items B42.01 and B42.02 for construction of trial sections		
	(a) Asphalt base		
	(i) 50mm minimum thickness	ton	
	(ii) 75mm minimum thickness	ton	
	(iii) 100mm minimum thickness	ton	
	(iv) 150mm minimum thickness	ton	
	(b) Asphalt surfacing		
	(i) 30mm minimum thickness	ton	
	(ii) 40mm minimum thickness	ton	
	(iii) 50mm minimum thickness	ton	
	(iv) 60mm minimum thickness	ton	
B42.08	Cores in asphalt paving		
	(a) 100mm diameter	No	
42.09	Asphalt surfacing on bridge decks		
	(a) Continuously graded (medium)	ton	
42.11	Asphalt layer constructed for rehabilitation purposes in accordance with the provisions of subclauses 4213(i)(ii) or 4213(j)(ii)		
	(b) Surfacing or overlay constructed with new asphalt ('scratchcoat' thickness, 50/70 bitumen)		
	(i) Continuously graded - COLTO Type	ton	
	(ii) Continuously graded - CCC Type	ton	
	(iii) Residential Mix Type	ton	
B42.15	Application of Waterblok or equivalent bitumen rubber emulsion to edges of a layer	litre	