ITEM NO.	

FOR UNTOLERANCED DIMENSIONS SEE ISO 2768-1: DESIGNATION M
FOR GENERAL TOLERANCE ON WELDED CONSTRUCTIONS SEE ISO 13920: CLASS A E

2D STATUS	IN WORK



PROTOTYPE ONLY



NOTE:

1. MATERIAL - ARAMID FIBRE WITH NBR BINDER, NITRILE RUBBER ACRYLONITRILE BUTADIENE

2. MAXIMUM OPERATING TEMPERATURE: 300 DEGREES CELSIUS.
3. MIN OPERATING TEMPERATURE: -100 DEGREES CELSIUS.

-/A
MATERIAL ALTERED
PD_PEL_KLP_05A
2020/09/18
N.T.N.

AMENDMENTS	
MASS	0.02 Kg

COPYRIGHT
THIS DRAWING TOGETHER WITH THE COPYRIGHT IS THE PROPERTY OF
TRANSNET
THIS DRAWING OR ANY PART THEREOF IS NOT TO BE COPIED OR OTHERWISE REPRODUCED OR USED FOR MANUFACTURE OR ANY OTHER PURPOSE WITHOUT THE WRITTEN PERMISSION FROM
CHIEF EXECUTIVE,
TRANSNET ENGINEERING

ASSEMBLY DRG No. - -		DRAWN	N.T.N.
-	-	CHECKED	N.C.L
CLASS -		APPROVED	B.E.D.
TYPE -		DATE	20-02-2020
-		SCALE	2:1

A-3 PROJECTION

DOCUMENT REFERENCE No. PD_PEL_KLP_DRW_05A

KILNER PARK ROTATING MACHINES

GASKET

VV230-180 COMPRESSOR

-

SHEET 1 OF 1

MATERIAL

SEE NOTE
-
SHEET 1
67X67

TRANSNET ENGINEERING

No. PEL05A0392 REV. A