

Business Management System

Supply Chain Management

Warehouse

Plumbing BOQ One

Material	Short Text	Purchase Order Text	Requested Quantity	UMC
0659287	TAP WTR: BASIN MIXER; SS; CHROME; 15 MM	TAP, WATER: TYPE: BASIN MIXER; MATERIAL: SS; CHROME; INLET CONNECTION: 15 MM; MANUF P/N: 33925T; SINGLE HOLE	2396	EA
0659286	TAP WTR: BATH DIVERTED MIXER; SS; CHROME	TAP, WATER: TYPE: BATH DIVERTED MIXER; MATERIAL: SS; CHROME; INLET CONNECTION: 15 MM; OUTLET CONNECTION: CONCEALED; MANUF P/N: 3351ST-15-HQ; WALL TYPE	5631	EA
0594832	TAP WTR: BATH MIXER; INTERNALS BRS CR PLTD	TAP, WATER: TYPE: BATH MIXER; MATERIAL: INTERNALS BRS CR PLTD; INLET CONNECTION: 1/2 IN; OUTLET CONNECTION: PLAIN; SUPPLIED COMPLETE WITH SHOWER KIT AND INSTALLATION INSTRUCTION	5267	EA
0667463	TAP WTR: BATH PILLAR TRIUPH; SS; SCREW IN	TAP, WATER: TYPE: BATH PILLAR TRIUPH; MATERIAL: STAINLESS STEEL; INLET CONNECTION: SCREW IN; OUTLET CONNECTION: 15 MM	4792	EA

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

0667455	TAP WTR:COBRA;BRASS;15MM MALE	TAP, WATER: TYPE: COBRA; MATERIAL: BRASS; INLET CONNECTION: 15MM MALE	4792	EA
0667456	TAP WTR:COBRA;BRASS;22MM MALE	TAP, WATER: TYPE: COBRA; MATERIAL: BRASS; INLET CONNECTION: 22MM MALE	4792	EA
0667457	TAP WTR:CORAL RANGE; ZINK WALL, TRUIMPH	TAP, WATER: TYPE: BIP; MATERIAL: CR PLTD; INLET CONNECTION: 15 MM; MANUF P/N: 106CA-15	4792	EA
0667462	TAP WTR:CXC CACHET UNDERTILE STOP;SS	TAP, WATER: TYPE: CORAL RANGE; ZINK WALL, TRUIMPH; MATERIAL: STAINLESS STEEL; INLET CONNECTION: 15MM MALE	4792	EA
0548155	TAP WTR:EXTENDED BIP;CR PLTD;15 MM	TAP, WATER: TYPE: CXC CACHET UNDERTILE STOP; MATERIAL: STAINLESS STEEL; INLET CONNECTION: 15MM MALE	2396	EA
0548076	TAP WTR:GARDEN;BRS;3/4 IN;THD	TAP, WATER: TYPE: EXTENDED BIP; MATERIAL: CR PLTD; INLET CONNECTION: 15 MM; MANUF P/N: 3306SB/EXT-15	4033	EA

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

0595544	TAP WTR:KITCHEN MIXER;CR PLTD;PLAIN	TAP, WATER: TYPE: GARDEN; MATERIAL: BRASS; INLET CONNECTION: 3/4 IN; OUTLET CONNECTION: THREADED	2396	EA
0659288	TAP WTR:MIXER SWIREL OPERATED;SS; CHROME	TAP, WATER: TYPE: KITCHEN MIXER; MATERIAL: CR PLTD; INLET CONNECTION: MALE 1/2 IN; OUTLET CONNECTION: PLAIN	4198	EA
0548222	TAP WTR:PILLAR;CR PLTD;15 MM	TAP, WATER: TYPE: MIXER SWIREL OPERATED; MATERIAL: SS; CHROME; INLET CONNECTION: 15 MM; MANUF P/N: 296CA; SINGLE HOLE	5643	EA
0659285	TAP WTR:SINK DIVERTED MIXER;SS; CHROME	TAP, WATER: TYPE: PILLER; INLET CONNECTION: 1/2 IN; BATH	5664	EA
0667461	TAP WTR:TRI BATH WALL ISCA;SS;15MM MALE	TAP, WATER: TYPE: SINK DIVERTED MIXER; MATERIAL: SS; CHROME; INLET CONNECTION: 15 MM; OUTLET CONNECTION: CONCEALED; MANUF P/N: 3366/041/10ST; WALL TYPE	6388	EA
0547148	TAP,WATER:106CA-15;BIP;CHROME PLATED	TAP, WATER: TYPE: TRI BATH WALL ISCA; MATERIAL: STAINLESS STEEL; INLET CONNECTION: 15MM MALE	3195	EA

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

0667536	VALVE BALL:15 MM;4 BAR;COLD WATER;BRASS	VALVE, BALL: VALVE SIZE: 15 MM; DESIGN RATING: 4 BAR; TEMPERATURE RATING: COLD WATER; CONNECTION: 15MM MALE; BODY MATERIAL: BRASS; FACE TO FACE LENGTH: 250 MM; OPERATED: WATER FLOW	3195	EA
0667538	VALVE BALL:15 MM;4 BAR;COLD WATER;BRASS	VALVE, BALL: VALVE SIZE: 15 MM; DESIGN RATING: 4 BAR; TEMPERATURE RATING: COLD WATER; CONNECTION: 15MM MALE; BODY MATERIAL: BRASS; FACE TO FACE LENGTH: 250 MM; OPERATED: WATER FLOW; APPLICATION: FP3 SIDE INLET	3195	EA
0667535	VALVE BALL:15 MM;4 BAR;COLD WATER;SS	VALVE, BALL: VALVE SIZE: 15 MM; DESIGN RATING: 4 BAR; TEMPERATURE RATING: COLD WATER; CONNECTION: 15MM FEMALE; BODY MATERIAL: STAINLESS STEEL; FACE TO FACE LENGTH: 100 MM; OPERATED: HAND; APPLICATION: BALLO STOP MXF	3195	EA
0667530	VALVE RELF:22 MM;4 BAR;40 DEG C;MALE	VALVE, RELIEF: VALVE SIZE: 22 MM; SET PRESSURE: 4 BAR; TEMPERATURE RATING: 40 DEG C; CONNECTION: MALE; BODY MATERIAL: BRASS; TRIM: CR 13 FOR 13%; FACE TO FACE LENGTH: 100 MM; OPERATED: PRESSURE; APPLICATION: GEYSER LATCO; DESIGN RATING: 400 KPA	3195	EA

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

0667525	VALVE:STOP;15 MM;4 BAR;COLD WATER;SS	VALVE: TYPE: STOP; VALVE SIZE: 15 MM; DESIGN RATING: 4 BAR; TEMPERATURE RATING: COLD WATER; CONNECTION: 15MM FEMALE TO FEMALE; OPERATED: HANDLE; BODY MATERIAL: STAINLESS STEEL	3195	EA
0667410	VLV FLOAT:BETA; PLUMBING;15 MM;4 BAR	VALVE, FLOAT: TYPE: BOTTOM INLET MK2-FP61; SIZE: 25 MM; PRESSURE RATING: 4 BAR; CONNECTION TYPE: MALE	3195	EA
0667413	VLV FLOAT:BOTTOM INLET MK2-FP61;25 MM	VALVE, FLOAT: TYPE: C/W INLET VALVE; PLUMBING; SIZE: 15 MM; PRESSURE RATING: 4 BAR; CONNECTION TYPE: BOTTOM CONNECT	3195	EA
0667411	VLV FLOAT:C/W INLET VALVE; PLUMBING	VALVE, FLOAT: TYPE: SIDE INLET, BRASS; PLUMBING; SIZE: 30 MM; PRESSURE RATING: 4 BAR; CONNECTION TYPE: MALE SCREW ON	3195	EA
0667412	VLV FLOAT:SIDE INLET, BRASS; PLUMBING	VALVE, FLUSH: TYPE: EXPOSED; SIZE: JUNIOR; STYLE: BALL O STOP; PRESSURE RATING: 600 KPA; FLOW RATE: 65 L+RS/MIN; CONNECTION SIZE: 3/4; CONNECTION TYPE: FLANGE; OPERATED: MANUAL; BODY MATERIAL: BRUHED CROME; TRIM: INTEGRAL VACUUM BREAKER, DIAPHRAGM; APPLICATION: TOILET; SPECIFICATION: SANS1240; MANUF P/N: FJ2000	3195	EA

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

0655131	VLV FLUSH:EXPOSED;JUNIOR;BALL O STOP;600	VALVE, FLUSH: TYPE: EXPOSED; SIZE: JUNIOR; STYLE: BALL O STOP; PRESSURE RATING: 600 KPA; FLOW RATE: 65 L+RS/MIN; CONNECTION SIZE: 3/4; CONNECTION TYPE: FLANGE; OPERATED: MANUAL; BODY MATERIAL: BRUSHED CROME; APPLICATION: URINAL; SPECIFICATION: SABS1240; MANUF P/N: FJ6.001	4276	EA
0667437	VALVE GATE:15 MM;TAP;4 BAR;15 MM;100 MM	VALVE, GATE: VALVE SIZE: 15 MM; TYPE: TAP; DESIGN PRESSURE: 4 BAR; DESIGN TEMPERATURE: -10 TO 40 DEG C; CONNECTION: 15 MM; FACE TO FACE LENGTH: 100 MM; BODY MATERIAL: BRASS; TRIM: CR 13 FOR 13%; OPERATED: MANUAL	3195	EA
0667371	VALVE GATE:15 MM;TAP;4 BAR;22 MM;117 MM	VALVE, GATE: VALVE SIZE: 15 MM; TYPE: TAP; DESIGN PRESSURE: 4 BAR; DESIGN TEMPERATURE: -10 TO 40 DEG C; CONNECTION: 22 MM; FACE TO FACE LENGTH: 117 MM; BODY MATERIAL: BRASS; TRIM: CR13 FOR 13 PCT; OPERATED: MANUAL	3195	EA
0754864	VALVE SLND:24 VDC;114 PSI;180 DEG;IP64	VALVE, SOLENOID: PIPE SIZE: G3/4 IN INLET THREAD OUTLET BARB 12MM; STYLE: (2) PIPE CONNECTIONS; (1) SOLENOID; POTENTIAL: 24 VDC; DESIGN RATING: 114 PSI; CONNECTION: 180 DEG; BODY MATERIAL: PLASTIC AND METAL; OPERATED: ELECTRICAL; ENCLOSURE RATING: IP64; MEDIUM: WATER; APPLICATION: HYDROBOILER; MANUF P/N:	575	EA

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

		FPD-180H1-DC24V		
0667523	VALVE:JOLLY FILLER;15 MM;4 BAR;PVC	VALVE: TYPE: JOLLY FILLER; VALVE SIZE: 15 MM; DESIGN RATING: 4 BAR; TEMPERATURE RATING: COLD WATER; CONNECTION: 15MM FEMALE; OPERATED: PRESSURE; BODY MATERIAL: PVC	3195	EA
0667524	VALVE:NON RETURN;15 MM;4 BAR;COLD WATER	VALVE: TYPE: NON RETURN; VALVE SIZE: 15 MM; DESIGN RATING: 4 BAR; TEMPERATURE RATING: COLD WATER; CONNECTION: 15MM FEMALE TO FEMALE; OPERATED: PRESSURE; BODY MATERIAL: BRASS	3195	EA
0655134	VLV FLUSH:EXPOSED;JUNIOR;BALL O STOP;600	VALVE, FLUSH: TYPE: EXPOSED; SIZE: JUNIOR; STYLE: BALL O STOP; PRESSURE RATING: 600 KPA; FLOW RATE: 65 L+RS/MIN; CONNECTION SIZE: 3/4; CONNECTION TYPE: FLANGE; OPERATED: MANUAL; BODY MATERIAL: BRUSHED CROME; APPLICATION: URINAL; SPECIFICATION: SABS1240; MANUF P/N: FJ6.001	4849	EA

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.



Business Management System

Supply Chain Management

Plumbing BOQ One

Compiled By: Cynthia Tsotetsi

Approved By: Boitshoko Mokolobate

Signature.....*C. Tsotetsi*.....

Signature.....*[Signature]*.....

Date... 18/02/2026.....

Date..... 18/02/2025.....

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.