

## Business Management System

Supply Chain Management

Warehouse

Warehouse Scope of Work for PPE General Bodywear

Material	Short Text	Long Text Description	Qty. Requested	Unit of Measure
0016885	COAT DUST:GP;102 CM;COTTON;240-44175132	COAT, DUST: TYPE: GENERAL PURPOSE; SIZE: 102 CM; MATERIAL: COTTON; COLOR: BLUE NAVY PANTONE 19-3920; SPECIFICATION: 240-44175132; MATERIAL: PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; LENGTH 3/4; POCKET: FRONT BUTTONS; TWO FRONT POCKETS; SLIT AT BACK; BUTTONS ACCEPTABLE FOUR-HOLE; DYED PLASTICS BUTTONS COMPLY WITH SANS 1457 COATS SHALL FASTEN WITH BUTTON AND BUTTONHOLE AND SHALL BE EQUIDISTANTLY SPACED; BUTTONS SECURED TO POSITIONS CORRESPONDING TO BUTTONHOLES; THE PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; THE BACK SHALL HAVE A SEAM DOWN THE CENTRE WITH A VENT IN THE LOWER PART OF THE SEAM; THE VENT SHALL HAVE AN OVERLAP OF 40 MM AND SHALL BE SECURELY	1 150	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

		<p>TACKED AND BAR-TACKED AT THE TOP; A HANGER LOOP OF OUTER DOUBLE FOLDED MATERIAL OF FINISHED LENGTH AT LEAST 70 MM AND OF FINISHED WIDTH AT LEAST 10 MM; SHALL BE SECURELY SEWN IN WITH THE COLLAR AT THE BACK NECK ON THE INSIDE; THE BOTTOM OF THE COATS AND THE LOWER EDGE OF PLAIN SLEEVE CUFFS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 15 MM; POCKET MOUTHS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 20 MM; EACH GARMENT SHALL HAVE A LABEL SECURELY ATTACHED AT THE CENTRE BACK NECK BELOW THE COLLAR SEAM ON THE INSIDE OF THE GARMENT; THE LABEL SHALL PROVIDE THE FOLLOWING INFORMATION PRINTED IN LEGIBLE AND INDELIBLE BLOCK LETTERS OF HEIGHT AT LEAST 3 MM; MANUFACTURER'S NAME OR TRADEMARK; CHEST SIZE SANS 434:2011 EDITION 5 22; YEAR OF MANUFACTURE; VAT REGISTRATION NUMBER; COUNTRY OF ORIGIN; ITEM TO BEAR SABS MARK OF APPROVAL REFERENCE SANS 434:2011 FIGURE 3 COATS</p>		
0160659	COAT DUST:GP;107 CM;COTTON;240-44175132	<p>COAT, DUST: TYPE: GENERAL PURPOSE; SIZE: 107 CM; MATERIAL: COTTON; COLOR: BLUE NAVY PANTONE 19-3920; SPECIFICATION: 240-44175132; MATERIAL: PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; LENGTH 3/4; POCKET: FRONT BUTTONS; TWO FRONT</p>	1 150	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

POCKETS; SLIT AT BACK; BUTTONS ACCEPTABLE FOUR-HOLE; DYED PLASTICS BUTTONS COMPLY WITH SANS 1457 COATS SHALL FASTEN WITH BUTTON AND BUTTONHOLE AND SHALL BE EQUIDISTANTLY SPACED; BUTTONS SECURED TO POSITIONS CORRESPONDING TO BUTTONHOLES; THE PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; THE BACK SHALL HAVE A SEAM DOWN THE CENTRE WITH A VENT IN THE LOWER PART OF THE SEAM; THE VENT SHALL HAVE AN OVERLAP OF 40 MM AND SHALL BE SECURELY TACKED AND BAR-TACKED AT THE TOP; A HANGER LOOP OF OUTER DOUBLE FOLDED MATERIAL OF FINISHED LENGTH AT LEAST 70 MM AND OF FINISHED WIDTH AT LEAST 10 MM; SHALL BE SECURELY SEWN IN WITH THE COLLAR AT THE BACK NECK ON THE INSIDE; THE BOTTOM OF THE COATS AND THE LOWER EDGE OF PLAIN SLEEVE CUFFS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 15 MM; POCKET MOUTHS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 20 MM; EACH GARMENT SHALL HAVE A LABEL SECURELY ATTACHED AT THE CENTRE BACK NECK BELOW THE COLLAR SEAM ON THE INSIDE OF THE GARMENT; THE LABEL SHALL PROVIDE THE FOLLOWING

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

		INFORMATION PRINTED IN LEGIBLE AND INDELIBLE BLOCK LETTERS OF HEIGHT AT LEAST 3 MM; MANUFACTURER'S NAME OR TRADEMARK; CHEST SIZE SANS 434:2011 EDITION 5 22; YEAR OF MANUFACTURE; VAT REGISTRATION NUMBER; COUNTRY OF ORIGIN; ITEM TO BEAR SABS MARK OF APPROVAL REFERENCE SANS 434:2011 FIGURE 3 COATS		
0160658	COAT DUST:GP;112 CM;COTTON;240-44175132	COAT, DUST: TYPE: GENERAL PURPOSE; SIZE: 112 CM; MATERIAL: COTTON; COLOR: BLUE NAVY PANTONE 19-3920; SPECIFICATION: 240-44175132; MATERIAL: PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; LENGTH 3/4; POCKET: FRONT BUTTONS; TWO FRONT POCKETS; SLIT AT BACK; BUTTONS ACCEPTABLE FOUR-HOLE; DYED PLASTICS BUTTONS COMPLY WITH SANS 1457 COATS SHALL FASTEN WITH BUTTON AND BUTTONHOLE AND SHALL BE EQUIDISTANTLY SPACED; BUTTONS SECURED TO POSITIONS CORRESPONDING TO BUTTONHOLES; THE PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; THE BACK SHALL HAVE A SEAM DOWN THE CENTRE WITH A VENT IN THE LOWER	1 150	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

		<p>PART OF THE SEAM; THE VENT SHALL HAVE AN OVERLAP OF 40 MM AND SHALL BE SECURELY TACKED AND BAR-TACKED AT THE TOP; A HANGER LOOP OF OUTER DOUBLE FOLDED MATERIAL OF FINISHED LENGTH AT LEAST 70 MM AND OF FINISHED WIDTH AT LEAST 10 MM; SHALL BE SECURELY SEWN IN WITH THE COLLAR AT THE BACK NECK ON THE INSIDE; THE BOTTOM OF THE COATS AND THE LOWER EDGE OF PLAIN SLEEVE CUFFS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 15 MM; POCKET MOUTHS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 20 MM; EACH GARMENT SHALL HAVE A LABEL SECURELY ATTACHED AT THE CENTRE BACK NECK BELOW THE COLLAR SEAM ON THE INSIDE OF THE GARMENT; THE LABEL SHALL PROVIDE THE FOLLOWING INFORMATION PRINTED IN LEGIBLE AND INDELIBLE BLOCK LETTERS OF HEIGHT AT LEAST 3 MM; MANUFACTURER'S NAME OR TRADEMARK; CHEST SIZE SANS 434:2011 EDITION 5 22; YEAR OF MANUFACTURE; VAT REGISTRATION NUMBER; COUNTRY OF ORIGIN; ITEM TO BEAR SABS MARK OF APPROVAL REFERENCE SANS 434:2011 FIGURE 3 COATS</p>		
0160663	COAT DUST:GP;117 CM;COTTON;240-44175132	COAT, DUST: TYPE: GENERAL PURPOSE; SIZE: 117 CM; MATERIAL: COTTON; COLOR: BLUE NAVY PANTONE 19-3920; SPECIFICATION: 240-44175132; MATERIAL: PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4;	1 150	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

MATERIAL TYPE D59 AND FLAME RETARDANT; LENGTH 3/4; POCKET: FRONT BUTTONS; TWO FRONT POCKETS; SLIT AT BACK; BUTTONS ACCEPTABLE FOUR-HOLE; DYED PLASTICS BUTTONS COMPLY WITH SANS 1457 COATS SHALL FASTEN WITH BUTTON AND BUTTONHOLE AND SHALL BE EQUIDISTANTLY SPACED; BUTTONS SECURED TO POSITIONS CORRESPONDING TO BUTTONHOLES; THE PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; THE BACK SHALL HAVE A SEAM DOWN THE CENTRE WITH A VENT IN THE LOWER PART OF THE SEAM; THE VENT SHALL HAVE AN OVERLAP OF 40 MM AND SHALL BE SECURELY TACKED AND BAR-TACKED AT THE TOP; A HANGER LOOP OF OUTER DOUBLE FOLDED MATERIAL OF FINISHED LENGTH AT LEAST 70 MM AND OF FINISHED WIDTH AT LEAST 10 MM; SHALL BE SECURELY SEWN IN WITH THE COLLAR AT THE BACK NECK ON THE INSIDE; THE BOTTOM OF THE COATS AND THE LOWER EDGE OF PLAIN SLEEVE CUFFS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 15 MM; POCKET MOUTHS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 20 MM; EACH GARMENT SHALL HAVE A LABEL SECURELY ATTACHED AT THE CENTRE BACK NECK BELOW THE

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

		COLLAR SEAM ON THE INSIDE OF THE GARMENT; THE LABEL SHALL PROVIDE THE FOLLOWING INFORMATION PRINTED IN LEGIBLE AND INDELIBLE BLOCK LETTERS OF HEIGHT AT LEAST 3 MM; MANUFACTURER'S NAME OR TRADEMARK; CHEST SIZE SANS 434:2011 EDITION 5 22; YEAR OF MANUFACTURE; VAT REGISTRATION NUMBER; COUNTRY OF ORIGIN; ITEM TO BEAR SABS MARK OF APPROVAL REFERENCE SANS 434:2011 FIGURE 3 COATS		
0160664	COAT DUST:GP;122 CM;COTTON;240-44175132	COAT, DUST: TYPE: GENERAL PURPOSE; SIZE: 122 CM; MATERIAL: COTTON; COLOR: BLUE NAVY PANTONE 19-3920; SPECIFICATION: 240-44175132; MATERIAL: PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; LENGTH 3/4; POCKET: FRONT BUTTONS; TWO FRONT POCKETS; SLIT AT BACK; BUTTONS ACCEPTABLE FOUR-HOLE; DYED PLASTICS BUTTONS COMPLY WITH SANS 1457 COATS SHALL FASTEN WITH BUTTON AND BUTTONHOLE AND SHALL BE EQUIDISTANTLY SPACED; BUTTONS SECURED TO POSITIONS CORRESPONDING TO BUTTONHOLES; THE PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM	1 150	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

		<p>THE FRONT EDGE; THE BACK SHALL HAVE A SEAM DOWN THE CENTRE WITH A VENT IN THE LOWER PART OF THE SEAM; THE VENT SHALL HAVE AN OVERLAP OF 40 MM AND SHALL BE SECURELY TACKED AND BAR-TACKED AT THE TOP; A HANGER LOOP OF OUTER DOUBLE FOLDED MATERIAL OF FINISHED LENGTH AT LEAST 70 MM AND OF FINISHED WIDTH AT LEAST 10 MM; SHALL BE SECURELY SEWN IN WITH THE COLLAR AT THE BACK NECK ON THE INSIDE; THE BOTTOM OF THE COATS AND THE LOWER EDGE OF PLAIN SLEEVE CUFFS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 15 MM; POCKET MOUTHS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 20 MM; EACH GARMENT SHALL HAVE A LABEL SECURELY ATTACHED AT THE CENTRE BACK NECK BELOW THE COLLAR SEAM ON THE INSIDE OF THE GARMENT; THE LABEL SHALL PROVIDE THE FOLLOWING INFORMATION PRINTED IN LEGIBLE AND INDELIBLE BLOCK LETTERS OF HEIGHT AT LEAST 3 MM; MANUFACTURER'S NAME OR TRADEMARK; CHEST SIZE SANS 434:2011 EDITION 5 22; YEAR OF MANUFACTURE; VAT REGISTRATION NUMBER; COUNTRY OF ORIGIN; ITEM TO BEAR SABS MARK OF APPROVAL REFERENCE SANS 434:2011 FIGURE 3 COATS</p>		
0566442	COAT DUST:GP;127 CM;COTTON;240-44175132	COAT, DUST: TYPE: GENERAL PURPOSE; SIZE: 127 CM; MATERIAL: COTTON; COLOR: BLUE NAVY PANTONE 19-3920; SPECIFICATION: 240-44175132;	1 150	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

MATERIAL: PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; LENGTH 3/4; POCKET: FRONT BUTTONS; TWO FRONT POCKETS; SLIT AT BACK; BUTTONS ACCEPTABLE FOUR-HOLE; DYED PLASTICS BUTTONS COMPLY WITH SANS 1457 COATS SHALL FASTEN WITH BUTTON AND BUTTONHOLE AND SHALL BE EQUIDISTANTLY SPACED; BUTTONS SECURED TO POSITIONS CORRESPONDING TO BUTTONHOLES; THE PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; THE BACK SHALL HAVE A SEAM DOWN THE CENTRE WITH A VENT IN THE LOWER PART OF THE SEAM; THE VENT SHALL HAVE AN OVERLAP OF 40 MM AND SHALL BE SECURELY TACKED AND BAR-TACKED AT THE TOP; A HANGER LOOP OF OUTER DOUBLE FOLDED MATERIAL OF FINISHED LENGTH AT LEAST 70 MM AND OF FINISHED WIDTH AT LEAST 10 MM; SHALL BE SECURELY SEWN IN WITH THE COLLAR AT THE BACK NECK ON THE INSIDE; THE BOTTOM OF THE COATS AND THE LOWER EDGE OF PLAIN SLEEVE CUFFS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 15 MM; POCKET MOUTHS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 20 MM; EACH

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

		GARMENT SHALL HAVE A LABEL SECURELY ATTACHED AT THE CENTRE BACK NECK BELOW THE COLLAR SEAM ON THE INSIDE OF THE GARMENT; THE LABEL SHALL PROVIDE THE FOLLOWING INFORMATION PRINTED IN LEGIBLE AND INDELIBLE BLOCK LETTERS OF HEIGHT AT LEAST 3 MM; MANUFACTURER'S NAME OR TRADEMARK; CHEST SIZE SANS 434:2011 EDITION 5 22; YEAR OF MANUFACTURE; VAT REGISTRATION NUMBER; COUNTRY OF ORIGIN; ITEM TO BEAR SABS MARK OF APPROVAL REFERENCE SANS 434:2011 FIGURE 3 COATS		
0160926	COAT DUST:GP;82 CM;COTTON;240-44175132	COAT, DUST: TYPE: GENERAL PURPOSE; SIZE: 82 CM; MATERIAL: COTTON; COLOR: BLUE NAVY PANTONE 19-3920; SPECIFICATION: 240-44175132; MATERIAL: PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; LENGTH 3/4; POCKET: FRONT BUTTONS; TWO FRONT POCKETS; SLIT AT BACK; BUTTONS ACCEPTABLE FOUR-HOLE; DYED PLASTICS BUTTONS COMPLY WITH SANS 1457 COATS SHALL FASTEN WITH BUTTON AND BUTTONHOLE AND SHALL BE EQUIDISTANTLY SPACED; BUTTONS SECURED TO POSITIONS CORRESPONDING TO BUTTONHOLES; THE PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET AND SHALL BE POSITIONED AT THE CENTRE FRONT END	1 150	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

		<p>OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; THE BACK SHALL HAVE A SEAM DOWN THE CENTRE WITH A VENT IN THE LOWER PART OF THE SEAM; THE VENT SHALL HAVE AN OVERLAP OF 40 MM AND SHALL BE SECURELY TACKED AND BAR-TACKED AT THE TOP; A HANGER LOOP OF OUTER DOUBLE FOLDED MATERIAL OF FINISHED LENGTH AT LEAST 70 MM AND OF FINISHED WIDTH AT LEAST 10 MM; SHALL BE SECURELY SEWN IN WITH THE COLLAR AT THE BACK NECK ON THE INSIDE; THE BOTTOM OF THE COATS AND THE LOWER EDGE OF PLAIN SLEEVE CUFFS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 15 MM; POCKET MOUTHS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 20 MM; EACH GARMENT SHALL HAVE A LABEL SECURELY ATTACHED AT THE CENTRE BACK NECK BELOW THE COLLAR SEAM ON THE INSIDE OF THE GARMENT; THE LABEL SHALL PROVIDE THE FOLLOWING INFORMATION PRINTED IN LEGIBLE AND INDELIBLE BLOCK LETTERS OF HEIGHT AT LEAST 3 MM; MANUFACTURER'S NAME OR TRADEMARK; CHEST SIZE SANS 434:2011 EDITION 5 22; YEAR OF MANUFACTURE; VAT REGISTRATION NUMBER; COUNTRY OF ORIGIN; ITEM TO BEAR SABS MARK OF APPROVAL REFERENCE SANS 434:2011 FIGURE 3 COATS</p>		
0160661	COAT DUST:GP;87 CM;COTTON;240-44175132	COAT, DUST: TYPE: GENERAL PURPOSE; SIZE: 87	1 150	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

CM; MATERIAL: COTTON; COLOR: BLUE NAVY PANTONE 19-3920; SPECIFICATION: 240-44175132; MATERIAL: PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; LENGTH 3/4; POCKET: FRONT BUTTONS; TWO FRONT POCKETS; SLIT AT BACK; BUTTONS ACCEPTABLE FOUR-HOLE; DYED PLASTICS BUTTONS COMPLY WITH SANS 1457 COATS SHALL FASTEN WITH BUTTON AND BUTTONHOLE AND SHALL BE EQUIDISTANTLY SPACED; BUTTONS SECURED TO POSITIONS CORRESPONDING TO BUTTONHOLES; THE PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; THE BACK SHALL HAVE A SEAM DOWN THE CENTRE WITH A VENT IN THE LOWER PART OF THE SEAM; THE VENT SHALL HAVE AN OVERLAP OF 40 MM AND SHALL BE SECURELY TACKED AND BAR-TACKED AT THE TOP; A HANGER LOOP OF OUTER DOUBLE FOLDED MATERIAL OF FINISHED LENGTH AT LEAST 70 MM AND OF FINISHED WIDTH AT LEAST 10 MM; SHALL BE SECURELY SEWN IN WITH THE COLLAR AT THE BACK NECK ON THE INSIDE; THE BOTTOM OF THE COATS AND THE LOWER EDGE OF PLAIN SLEEVE CUFFS SHALL HAVE HEMS OF FINISHED WIDTH AT

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

		<p>LEAST 15 MM; POCKET MOUTHS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 20 MM; EACH GARMENT SHALL HAVE A LABEL SECURELY ATTACHED AT THE CENTRE BACK NECK BELOW THE COLLAR SEAM ON THE INSIDE OF THE GARMENT; THE LABEL SHALL PROVIDE THE FOLLOWING INFORMATION PRINTED IN LEGIBLE AND INDELIBLE BLOCK LETTERS OF HEIGHT AT LEAST 3 MM; MANUFACTURER'S NAME OR TRADEMARK; CHEST SIZE SANS 434:2011 EDITION 5 22; YEAR OF MANUFACTURE; VAT REGISTRATION NUMBER; COUNTRY OF ORIGIN; ITEM TO BEAR SABS MARK OF APPROVAL REFERENCE SANS 434:2011 FIGURE 3 COATS</p>		
0566444	COAT DUST:GP;92 CM;COTTON;240-44175132	<p>COAT, DUST: TYPE: GENERAL PURPOSE; SIZE: 92 CM; MATERIAL: COTTON; COLOR: BLUE NAVY PANTONE 19-3920; SPECIFICATION: 240-44175132; MATERIAL: PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; LENGTH 3/4; POCKET: FRONT BUTTONS; TWO FRONT POCKETS; SLIT AT BACK; BUTTONS ACCEPTABLE FOUR-HOLE; DYED PLASTICS BUTTONS COMPLY WITH SANS 1457 COATS SHALL FASTEN WITH BUTTON AND BUTTONHOLE AND SHALL BE EQUIDISTANTLY SPACED; BUTTONS SECURED TO POSITIONS CORRESPONDING TO BUTTONHOLES; THE PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM</p>	1 150	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

AND THE FULL DEPTH OF THE BREAST POCKET AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; THE BACK SHALL HAVE A SEAM DOWN THE CENTRE WITH A VENT IN THE LOWER PART OF THE SEAM; THE VENT SHALL HAVE AN OVERLAP OF 40 MM AND SHALL BE SECURELY TACKED AND BAR-TACKED AT THE TOP; A HANGER LOOP OF OUTER DOUBLE FOLDED MATERIAL OF FINISHED LENGTH AT LEAST 70 MM AND OF FINISHED WIDTH AT LEAST 10 MM; SHALL BE SECURELY SEWN IN WITH THE COLLAR AT THE BACK NECK ON THE INSIDE; THE BOTTOM OF THE COATS AND THE LOWER EDGE OF PLAIN SLEEVE CUFFS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 15 MM; POCKET MOUTHS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 20 MM; EACH GARMENT SHALL HAVE A LABEL SECURELY ATTACHED AT THE CENTRE BACK NECK BELOW THE COLLAR SEAM ON THE INSIDE OF THE GARMENT; THE LABEL SHALL PROVIDE THE FOLLOWING INFORMATION PRINTED IN LEGIBLE AND INDELIBLE BLOCK LETTERS OF HEIGHT AT LEAST 3 MM; MANUFACTURER'S NAME OR TRADEMARK; CHEST SIZE SANS 434:2011 EDITION 5 22; YEAR OF MANUFACTURE; VAT REGISTRATION NUMBER; COUNTRY OF ORIGIN; ITEM TO BEAR SABS MARK OF APPROVAL REFERENCE SANS 434:2011 FIGURE 3

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

		COATS		
0160660	COAT DUST:GP;97 CM;COTTON;240-44175132	COAT, DUST: TYPE: GENERAL PURPOSE; SIZE: 97 CM; MATERIAL: COTTON; COLOR: BLUE NAVY PANTONE 19-3920; SPECIFICATION: 240-44175132; MATERIAL: PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; LENGTH 3/4; POCKET: FRONT BUTTONS; TWO FRONT POCKETS; SLIT AT BACK; BUTTONS ACCEPTABLE FOUR-HOLE; DYED PLASTICS BUTTONS COMPLY WITH SANS 1457 COATS SHALL FASTEN WITH BUTTON AND BUTTONHOLE AND SHALL BE EQUIDISTANTLY SPACED; BUTTONS SECURED TO POSITIONS CORRESPONDING TO BUTTONHOLES; THE PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; THE BACK SHALL HAVE A SEAM DOWN THE CENTRE WITH A VENT IN THE LOWER PART OF THE SEAM; THE VENT SHALL HAVE AN OVERLAP OF 40 MM AND SHALL BE SECURELY TACKED AND BAR-TACKED AT THE TOP; A HANGER LOOP OF OUTER DOUBLE FOLDED MATERIAL OF FINISHED LENGTH AT LEAST 70 MM AND OF FINISHED WIDTH AT LEAST 10 MM; SHALL BE SECURELY SEWN IN WITH THE COLLAR AT THE	1 150	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

## Business Management System

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

		<p>BACK NECK ON THE INSIDE; THE BOTTOM OF THE COATS AND THE LOWER EDGE OF PLAIN SLEEVE CUFFS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 15 MM; POCKET MOUTHS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 20 MM; EACH GARMENT SHALL HAVE A LABEL SECURELY ATTACHED AT THE CENTRE BACK NECK BELOW THE COLLAR SEAM ON THE INSIDE OF THE GARMENT; THE LABEL SHALL PROVIDE THE FOLLOWING INFORMATION PRINTED IN LEGIBLE AND INDELIBLE BLOCK LETTERS OF HEIGHT AT LEAST 3 MM; MANUFACTURER'S NAME OR TRADEMARK; CHEST SIZE SANS 434:2011 EDITION 5 22; YEAR OF MANUFACTURE; VAT REGISTRATION NUMBER; COUNTRY OF ORIGIN; ITEM TO BEAR SABS MARK OF APPROVAL REFERENCE SANS 434:2011 FIGURE 3 COATS</p>		
0566494	JACKET UTIL:OPERATING;102 CM	<p>JACKET, UTILITY: TYPE: OPERATING; SIZE: 102 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG</p>	64 124	EA

### Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

		<p>SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1</p>		
0222537	JACKET UTIL:OPERATING;107 CM	<p>JACKET, UTILITY: TYPE: OPERATING; SIZE: 107 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822;</p>	59 375	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER;THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

		COMPLY TO: SANS 1387 CLASS C CATEGORY 1		
0566503	JACKET UTIL:OPERATING;112 CM	JACKET, UTILITY: TYPE: OPERATING; SIZE: 112 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER;THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM	41 308	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

		SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1		
0222538	JACKET UTIL:OPERATING;117 CM	JACKET, UTILITY: TYPE: OPERATING; SIZE: 117 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE	32 695	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

		<p>PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1</p>		
0222539	JACKET UTIL:OPERATING;122 CM	<p>JACKET, UTILITY: TYPE: OPERATING; SIZE: 122 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE</p>	20 907	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

		<p>OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1</p>		
0566511	JACKET UTIL:OPERATING;127 CM	<p>JACKET, UTILITY: TYPE: OPERATING; SIZE: 127 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN</p>	12 765	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

0222540	JACKET UTIL:OPERATING;132 CM	<p>JACKET, UTILITY: TYPE: OPERATING; SIZE: 132 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER;THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG</p>	6 463	EA
---------	------------------------------	--	-------	----

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH;

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

		SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1		
0172193	JACKET UTIL:OPERATING;137 CM	JACKET, UTILITY: TYPE: OPERATING; SIZE: 137 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF	6 486	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

STITCHING ALONG EACH STRINGER; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

		<p>PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1</p>		
0566512	JACKET UTIL:OPERATING;142 CM	<p>JACKET, UTILITY: TYPE: OPERATING; SIZE: 142 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT</p>	3 519	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

		<p>BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1</p>		
0172192	JACKET UTIL:OPERATING;147 CM	<p>JACKET, UTILITY: TYPE: OPERATING; SIZE: 147 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET</p>	7 728	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

		<p>SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1</p>		
0566513	JACKET UTIL:OPERATING;152 CM	JACKET, UTILITY: TYPE: OPERATING; SIZE: 152 CM;	7 901	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19\_3920; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

		AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1		
0179714	JACKET UTIL:OPERATING;157 CM	JACKET, UTILITY: TYPE: OPERATING; SIZE: 157 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER;THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN	6 693	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

		AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 5		
0566481	JACKET UTIL:OPERATING;77 CM	JACKET, UTILITY: TYPE: OPERATING; SIZE: 77 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE	20 815	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

## Business Management System

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

		<p>4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1</p>		
0566482	JACKET UTIL:OPERATING;82 CM	<p>JACKET, UTILITY: TYPE: OPERATING; SIZE: 82 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE</p>	33 189	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

		<p>SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1</p>		
0222535	JACKET UTIL:OPERATING;87 CM	JACKET, UTILITY: TYPE: OPERATING; SIZE: 87 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE	48 645	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

PANTONE 19\_3920; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER;THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

		JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1		
0566544	JACKET UTIL:OPERATING;92 CM	JACKET, UTILITY: TYPE: OPERATING; SIZE: 92 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER;THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE	54 384	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

		<p>LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1</p>		
0222536	JACKET UTIL:OPERATING;97 CM	<p>JACKET, UTILITY: TYPE: OPERATING; SIZE: 97 CM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: 240-44175132 REV 2; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE</p>	58 248	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

		<p>BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; MATERIAL TO COMPLY TO: SANS 1387 CLASS C CATEGORY 1</p>		
0222558	JACKET UTIL:THERMAL;2XLARGE	<p>JACKET, UTILITY: TYPE: THERMAL; SIZE: 2XLARGE; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; SPECIFICATION: 240-44175132 REV 2; INSULATED WITH PRE-SHRUNK HOLLOW FIBRE OR A NON-FLAMMABLE MATERIAL; WITH THE OUTER COVERING MADE OF PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4 CLASS C CATEGORY 1; MATERIAL TYPE D59 AND FLAME RETARDANT; JACKET LENGTH: TO REACH BELOW THE BUTTOCKS; POCKETS: ONE CHEST POCKET SHALL BE BELLOWS TYPE - 15CM</p>	10 488	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

		DEEP AND 14CM WIDE; 4 SIDE POCKETS; POCKETS TO HAVE FLAPS WITH CUT-OFF EDGES THAT CAN BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; THE SIDE POCKET SHALL BE THE BELLOWS TYPE WITH A SIDE ENTRY INTO ANOTHER SEPARATE POCKET AND SHALL BE 22CM DEEP AND 21CM WIDE; JACKETS SHALL HAVE NON-CONDUCTIVE PRESS STUDS DOWN THE FRONT ON A DOUBLE PANEL STRIP; AS WELL AS A NON-CONDUCTIVE ZIP; THE SLEEVE CUFFS SHALL HAVE TWO NON-CONDUCTIVE PRESS STUDS AT THE END OF THE SLEEVE SO THAT THE SIZE CAN BE ADJUSTED; IDENTIFICATION: INDELIBLE MNFRS TRADEMARK; REF NO. AND CLEANING INSTRUCTIONS INSIDE COLLAR ON JACKETS AND SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS		
0222559	JACKET UTIL:THERMAL;3XLARGE	JACKET, UTILITY: TYPE: THERMAL; SIZE: 3XLARGE; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; SPECIFICATION: 240-44175132 REV 2; INSULATED WITH PRE-SHRUNK HOLLOW FIBRE OR A NON-FLAMMABLE MATERIAL; WITH THE OUTER COVERING MADE OF PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4 CLASS C CATEGORY 1; MATERIAL TYPE D59 AND FLAME RETARDANT; JACKET LENGTH: TO REACH BELOW THE BUTTOCKS; POCKETS: ONE CHEST POCKET SHALL BE BELLOWS TYPE - 15CM DEEP AND 14CM WIDE; 4 SIDE POCKETS; POCKETS	3 680	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

		<p>TO HAVE FLAPS WITH CUT-OFF EDGES THAT CAN BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; THE SIDE POCKET SHALL BE THE BELLOWS TYPE WITH A SIDE ENTRY INTO ANOTHER SEPARATE POCKET AND SHALL BE 22CM DEEP AND 21CM WIDE; JACKETS SHALL HAVE NON-CONDUCTIVE PRESS STUDS DOWN THE FRONT ON A DOUBLE PANEL STRIP; AS WELL AS A NON-CONDUCTIVE ZIP; THE SLEEVE CUFFS SHALL HAVE TWO NON-CONDUCTIVE PRESS STUDS AT THE END OF THE SLEEVE SO THAT THE SIZE CAN BE ADJUSTED; IDENTIFICATION: INDELIBLE MNFRS TRADEMARK; REF NO. AND CLEANING INSTRUCTIONS INSIDE COLLAR ON JACKETS AND SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS</p>		
0187793	JACKET UTIL:THERMAL;4XLARGE	<p>JACKET, UTILITY: TYPE: THERMAL; SIZE: 4XLARGE; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; SPECIFICATION: 240-44175132 REV 2; INSULATED WITH PRE-SHRUNK HOLLOW FIBRE OR A NON-FLAMMABLE MATERIAL; WITH THE OUTER COVERING MADE OF PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4 CLASS C CATEGORY 1; MATERIAL TYPE D59 AND FLAME RETARDANT; JACKET LENGTH: TO REACH BELOW THE BUTTOCKS; POCKETS: ONE CHEST POCKET SHALL BE BELLOWS TYPE - 15CM DEEP AND 14CM WIDE; 4 SIDE POCKETS; POCKETS TO HAVE FLAPS WITH CUT-OFF EDGES THAT CAN BE</p>	3 450	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

		FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; THE SIDE POCKET SHALL BE THE BELLOWS TYPE WITH A SIDE ENTRY INTO ANOTHER SEPARATE POCKET AND SHALL BE 22CM DEEP AND 21CM WIDE; JACKETS SHALL HAVE NON-CONDUCTIVE PRESS STUDS DOWN THE FRONT ON A DOUBLE PANEL STRIP; AS WELL AS A NON-CONDUCTIVE ZIP; THE SLEEVE CUFFS SHALL HAVE TWO NON-CONDUCTIVE PRESS STUDS AT THE END OF THE SLEEVE SO THAT THE SIZE CAN BE ADJUSTED; IDENTIFICATION: INDELIBLE MNFRS TRADEMARK; REF NO. AND CLEANING INSTRUCTIONS INSIDE COLLAR ON JACKETS AND SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS		
0186009	JACKET UTIL:THERMAL;5XLARGE	JACKET, UTILITY: TYPE: THERMAL; SIZE: 5XLARGE; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; SPECIFICATION: 240-44175132 REV 2; INSULATED WITH PRE-SHRUNK HOLLOW FIBRE OR A NON-FLAMMABLE MATERIAL; WITH THE OUTER COVERING MADE OF PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4 CLASS C CATEGORY 1; MATERIAL TYPE D59 AND FLAME RETARDANT; JACKET LENGTH: TO REACH BELOW THE BUTTOCKS; POCKETS: ONE CHEST POCKET SHALL BE BELLOWS TYPE - 15CM DEEP AND 14CM WIDE; 4 SIDE POCKETS; POCKETS TO HAVE FLAPS WITH CUT-OFF EDGES THAT CAN BE FASTENED BY MEANS OF NON-CONDUCTIVE	1 150	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

		BUTTONS; THE SIDE POCKET SHALL BE THE BELLOWS TYPE WITH A SIDE ENTRY INTO ANOTHER SEPARATE POCKET AND SHALL BE 22CM DEEP AND 21CM WIDE; JACKETS SHALL HAVE NON-CONDUCTIVE PRESS STUDS DOWN THE FRONT ON A DOUBLE PANEL STRIP; AS WELL AS A NON-CONDUCTIVE ZIP; THE SLEEVE CUFFS SHALL HAVE TWO NON-CONDUCTIVE PRESS STUDS AT THE END OF THE SLEEVE SO THAT THE SIZE CAN BE ADJUSTED; IDENTIFICATION: INDELIBLE MNFRS TRADEMARK; REF NO. AND CLEANING INSTRUCTIONS INSIDE COLLAR ON JACKETS AND SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS		
0197919	JACKET UTIL:THERMAL;6XLARGE	JACKET, UTILITY: TYPE: THERMAL; SIZE: 6XLARGE; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; SPECIFICATION: 240-44175132 REV 2; INSULATED WITH PRE-SHRUNK HOLLOW FIBRE OR A NON-FLAMMABLE MATERIAL; WITH THE OUTER COVERING MADE OF PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4 CLASS C CATEGORY 1; MATERIAL TYPE D59 AND FLAME RETARDANT; JACKET LENGTH: TO REACH BELOW THE BUTTOCKS; POCKETS: ONE CHEST POCKET SHALL BE BELLOWS TYPE - 15CM DEEP AND 14CM WIDE; 4 SIDE POCKETS; POCKETS TO HAVE FLAPS WITH CUT-OFF EDGES THAT CAN BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; THE SIDE POCKET SHALL BE THE	1 150	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

		BELLOWS TYPE WITH A SIDE ENTRY INTO ANOTHER SEPARATE POCKET AND SHALL BE 22CM DEEP AND 21CM WIDE; JACKETS SHALL HAVE NON-CONDUCTIVE PRESS STUDS DOWN THE FRONT ON A DOUBLE PANEL STRIP; AS WELL AS A NON-CONDUCTIVE ZIP; THE SLEEVE CUFFS SHALL HAVE TWO NON-CONDUCTIVE PRESS STUDS AT THE END OF THE SLEEVE SO THAT THE SIZE CAN BE ADJUSTED; IDENTIFICATION: INDELIBLE MNFRS TRADEMARK; REF NO. AND CLEANING INSTRUCTIONS INSIDE COLLAR ON JACKETS AND SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS		
0222555	JACKET UTIL:THERMAL;LARGE	JACKET, UTILITY: TYPE: THERMAL; SIZE: LARGE; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; SPECIFICATION: 240-44175132 REV 2; INSULATED WITH PRE-SHRUNK HOLLOW FIBRE OR A NON-FLAMMABLE MATERIAL; WITH THE OUTER COVERING MADE OF PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4 CLASS C CATEGORY 1; MATERIAL TYPE D59 AND FLAME RETARDANT; JACKET LENGTH: TO REACH BELOW THE BUTTOCKS; POCKETS: ONE CHEST POCKET SHALL BE BELLOWS TYPE - 15CM DEEP AND 14CM WIDE; 4 SIDE POCKETS; POCKETS TO HAVE FLAPS WITH CUT-OFF EDGES THAT CAN BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; THE SIDE POCKET SHALL BE THE BELLOWS TYPE WITH A SIDE ENTRY INTO ANOTHER	27 853	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

		SEPARATE POCKET AND SHALL BE 22CM DEEP AND 21CM WIDE; JACKETS SHALL HAVE NON-CONDUCTIVE PRESS STUDS DOWN THE FRONT ON A DOUBLE PANEL STRIP; AS WELL AS A NON-CONDUCTIVE ZIP; THE SLEEVE CUFFS SHALL HAVE TWO NON-CONDUCTIVE PRESS STUDS AT THE END OF THE SLEEVE SO THAT THE SIZE CAN BE ADJUSTED; IDENTIFICATION: INDELIBLE MNFRS TRADEMARK; REF NO. AND CLEANING INSTRUCTIONS INSIDE COLLAR ON JACKETS AND SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS		
0222554	JACKET UTIL:THERMAL;MEDIUM	JACKET, UTILITY: TYPE: THERMAL; SIZE: MEDIUM; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; SPECIFICATION: 240-44175132 REV 2; INSULATED WITH PRE-SHRUNK HOLLOW FIBRE OR A NON-FLAMMABLE MATERIAL; WITH THE OUTER COVERING MADE OF PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4 CLASS C CATEGORY 1; MATERIAL TYPE D59 AND FLAME RETARDANT; JACKET LENGTH: TO REACH BELOW THE BUTTOCKS; POCKETS: ONE CHEST POCKET SHALL BE BELLOWS TYPE - 15CM DEEP AND 14CM WIDE; 4 SIDE POCKETS; POCKETS TO HAVE FLAPS WITH CUT-OFF EDGES THAT CAN BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; THE SIDE POCKET SHALL BE THE BELLOWS TYPE WITH A SIDE ENTRY INTO ANOTHER SEPARATE POCKET AND SHALL BE 22CM DEEP AND	27 980	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

		21CM WIDE; JACKETS SHALL HAVE NON-CONDUCTIVE PRESS STUDS DOWN THE FRONT ON A DOUBLE PANEL STRIP; AS WELL AS A NON-CONDUCTIVE ZIP; THE SLEEVE CUFFS SHALL HAVE TWO NON-CONDUCTIVE PRESS STUDS AT THE END OF THE SLEEVE SO THAT THE SIZE CAN BE ADJUSTED; IDENTIFICATION: INDELIBLE MNFRS TRADEMARK; REF NO. AND CLEANING INSTRUCTIONS INSIDE COLLAR ON JACKETS AND SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS		
0222553	JACKET UTIL:THERMAL;SMALL	JACKET, UTILITY: TYPE: THERMAL; SIZE: SMALL; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; SPECIFICATION: 240-44175132 REV 2; INSULATED WITH PRE-SHRUNK HOLLOW FIBRE OR A NON-FLAMMABLE MATERIAL; WITH THE OUTER COVERING MADE OF PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4 CLASS C CATEGORY 1; MATERIAL TYPE D59 AND FLAME RETARDANT; JACKET LENGTH: TO REACH BELOW THE BUTTOCKS; POCKETS: ONE CHEST POCKET SHALL BE BELLOWS TYPE - 15CM DEEP AND 14CM WIDE; 4 SIDE POCKETS; POCKETS TO HAVE FLAPS WITH CUT-OFF EDGES THAT CAN BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; THE SIDE POCKET SHALL BE THE BELLOWS TYPE WITH A SIDE ENTRY INTO ANOTHER SEPARATE POCKET AND SHALL BE 22CM DEEP AND 21CM WIDE; JACKETS SHALL HAVE NON-	24 806	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

		CONDUCTIVE PRESS STUDS DOWN THE FRONT ON A DOUBLE PANEL STRIP; AS WELL AS A NON-CONDUCTIVE ZIP; THE SLEEVE CUFFS SHALL HAVE TWO NON-CONDUCTIVE PRESS STUDS AT THE END OF THE SLEEVE SO THAT THE SIZE CAN BE ADJUSTED; IDENTIFICATION: INDELIBLE MNFRS TRADEMARK; REF NO. AND CLEANING INSTRUCTIONS INSIDE COLLAR ON JACKETS AND SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS		
0222556	JACKET UTIL:THERMAL;XLARGE	JACKET, UTILITY: TYPE: THERMAL; SIZE: XLARGE; MATERIAL: D59; FLAME RETARDANT; PRE-SHRUNK 100 PCT SOFT WOVEN COTTON; COLOR: NAVY BLUE PANTONE 19_3920; SPECIFICATION: 240-44175132 REV 2; INSULATED WITH PRE-SHRUNK HOLLOW FIBRE OR A NON-FLAMMABLE MATERIAL; WITH THE OUTER COVERING MADE OF PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4 CLASS C CATEGORY 1; MATERIAL TYPE D59 AND FLAME RETARDANT; JACKET LENGTH: TO REACH BELOW THE BUTTOCKS; POCKETS: ONE CHEST POCKET SHALL BE BELLOWS TYPE - 15CM DEEP AND 14CM WIDE; 4 SIDE POCKETS; POCKETS TO HAVE FLAPS WITH CUT-OFF EDGES THAT CAN BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; THE SIDE POCKET SHALL BE THE BELLOWS TYPE WITH A SIDE ENTRY INTO ANOTHER SEPARATE POCKET AND SHALL BE 22CM DEEP AND 21CM WIDE; JACKETS SHALL HAVE NON-CONDUCTIVE PRESS STUDS DOWN THE FRONT ON	18 021	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

		A DOUBLE PANEL STRIP; AS WELL AS A NON-CONDUCTIVE ZIP; THE SLEEVE CUFFS SHALL HAVE TWO NON-CONDUCTIVE PRESS STUDS AT THE END OF THE SLEEVE SO THAT THE SIZE CAN BE ADJUSTED; IDENTIFICATION: INDELIBLE MNFRS TRADEMARK; REF NO. AND CLEANING INSTRUCTIONS INSIDE COLLAR ON JACKETS AND SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS		
0222568	RAINWEAR:2 PIECE SUIT;2XL;BLUE NAVY	RAINWEAR: TYPE: 2 PIECE SUIT; SIZE: 2XL; MATERIAL: POLYESTER 100 PCT PLAIN WEAVE, 180 GM/2 MIN; COLOR: BLUE NAVY; MATERIAL: MINIMUM 180 GRAMS PER M/3 FACE SIDE 100% POLYESTER; PLAIN WEAVE WITH 170 THREADS PER M/3 INCH WITH WATER RESISTANT COATING; UNDER SIDE LAMINATED WITH PVC COATING; SEAMS STRENGTH 50KPA; CONVERTS TO 50KNM/2; LINING 80% POLYESTER 20% COTTON; SIZE TO SANS 434 SIZE CHART ANNEX E FOR RAIN WEAR; JACKET SHALL HAVE A NYLON SPIRAL ZIP WITH CLOSED FLY FRONT SECURED BY NON-CONDUCTIVE PRESS-STUDS; COMPLY WITH SANS 1822 TYPE 5; HOOD ATTACHED TO THE JACKET; JACKET TO COVER THE BUTTOCKS; FALSE ELASTIC SLEEVE AT THE END MADE OF SOFTER MATERIAL; PANTS SHALL HAVE SIDE SLITS AND ELASTIC WAIST; REFLECTIVE STRIPS TO BE FITTED ON BOTH SLEEVES ON THE UPPER ARM, AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SIDE OF THE SLEEVE AND THE ESKOM LOGO SHALL BE SILK-	27 888	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

## Business Management System

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

		SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON THE FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; UNIQUE IDENTIFIER 240-44175132		
0222569	RAINWEAR:2 PIECE SUIT;3XL;BLUE NAVY	RAINWEAR: TYPE: 2 PIECE SUIT; SIZE: 3XL; MATERIAL: POLYESTER 100 PCT PLAIN WEAVE, 180 GM/2 MIN; COLOR: BLUE NAVY; MATERIAL: MINIMUM 180 GRAMS PER M/3 FACE SIDE 100% POLYESTER; PLAIN WEAVE WITH 170 THREADS PER M/3 INCH WITH WATER RESISTANT COATING; UNDER SIDE LAMINATED WITH PVC COATING; SEAMS STRENGTH 50KPA; CONVERTS TO 50KNM/2; LINING 80% POLYESTER 20% COTTON; SIZE TO SANS 434 SIZE CHART ANNEX E FOR RAIN WEAR; JACKET SHALL HAVE A NYLON SPIRAL ZIP WITH CLOSED FLY FRONT SECURED BY NON-CONDUCTIVE PRESS-STUDS; COMPLY WITH SANS 1822 TYPE 5; HOOD ATTACHED TO THE JACKET; JACKET TO COVER THE BUTTOCKS; FALSE ELASTIC SLEEVE AT THE END MADE OF SOFTER MATERIAL; PANTS SHALL HAVE SIDE SLITS AND ELASTIC WAIST; REFLECTIVE STRIPS TO BE FITTED ON BOTH SLEEVES ON THE UPPER ARM, AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SIDE OF THE SLEEVE AND THE ESKOM LOGO SHALL BE SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON THE FRONT AND BACK;	10 419	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

		INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; UNIQUE IDENTIFIER 240-44175132		
0565711	RAINWEAR:2 PIECE SUIT;4XL;BLUE NAVY	RAINWEAR: TYPE: 2 PIECE SUIT; SIZE: 4XL; MATERIAL: POLYESTER 100 PCT PLAIN WEAVE, 180 GM/2 MIN; COLOR: BLUE NAVY; MATERIAL: MINIMUM 180 GRAMS PER M/3 FACE SIDE 100% POLYESTER; PLAIN WEAVE WITH 170 THREADS PER M/3 INCH WITH WATER RESISTANT COATING; UNDER SIDE LAMINATED WITH PVC COATING; SEAMS STRENGTH 50KPA; CONVERTS TO 50KNM/2; LINING 80% POLYESTER 20% COTTON; SIZE TO SANS 434 SIZE CHART ANNEX E FOR RAIN WEAR; JACKET SHALL HAVE A NYLON SPIRAL ZIP WITH CLOSED FLY FRONT SECURED BY NON-CONDUCTIVE PRESS-STUDS; COMPLY WITH SANS 1822 TYPE 5; HOOD ATTACHED TO THE JACKET; JACKET TO COVER THE BUTTOCKS; FALSE ELASTIC SLEEVE AT THE END MADE OF SOFTER MATERIAL; PANTS SHALL HAVE SIDE SLITS AND ELASTIC WAIST; REFLECTIVE STRIPS TO BE FITTED ON BOTH SLEEVES ON THE UPPER ARM, AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SIDE OF THE SLEEVE AND THE ESKOM LOGO SHALL BE SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON THE FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH	4 566	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

		SABS MARK OF APPROVAL; UNIQUE IDENTIFIER 240-44175132		
0222566	RAINWEAR:2 PIECE SUIT;L;BLUE NAVY	RAINWEAR: TYPE: 2 PIECE SUIT; SIZE: L; MATERIAL: POLYESTER 100 PCT PLAIN WEAVE, 180 GM/2 MIN; COLOR: BLUE NAVY; MATERIAL: MINIMUM 180 GRAMS PER M/3 FACE SIDE 100% POLYESTER; PLAIN WEAVE WITH 170 THREADS PER M/3 INCH WITH WATER RESISTANT COATING; UNDER SIDE LAMINATED WITH PVC COATING; SEAMS STRENGTH 50KPA; CONVERTS TO 50KNM/2; LINING 80% POLYESTER 20% COTTON; SIZE TO SANS 434 SIZE CHART ANNEX E FOR RAIN WEAR; JACKET SHALL HAVE A NYLON SPIRAL ZIP WITH CLOSED FLY FRONT SECURED BY NON-CONDUCTIVE PRESS-STUDS; COMPLY WITH SANS 1822 TYPE 5; HOOD ATTACHED TO THE JACKET; JACKET TO COVER THE BUTTOCKS; FALSE ELASTIC SLEEVE AT THE END MADE OF SOFTER MATERIAL; PANTS SHALL HAVE SIDE SLITS AND ELASTIC WAIST; REFLECTIVE STRIPS TO BE FITTED ON BOTH SLEEVES ON THE UPPER ARM, AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SIDE OF THE SLEEVE AND THE ESKOM LOGO SHALL BE SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON THE FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; UNIQUE IDENTIFIER 240-44175132	39 802	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

0225676	RAINWEAR:2 PIECE SUIT;M;BLUE NAVY	RAINWEAR: TYPE: 2 PIECE SUIT; SIZE: M; MATERIAL: POLYESTER 100 PCT PLAIN WEAVE, 180 GM/2 MIN; COLOR: BLUE NAVY; MATERIAL: MINIMUM 180 GRAMS PER M/3 FACE SIDE 100% POLYESTER; PLAIN WEAVE WITH 170 THREADS PER M/3 INCH WITH WATER RESISTANT COATING; UNDER SIDE LAMINATED WITH PVC COATING; SEAMS STRENGTH 50KPA; CONVERTS TO 50KNM/2; LINING 80% POLYESTER 20% COTTON; SIZE TO SANS 434 SIZE CHART ANNEX E FOR RAIN WEAR; JACKET SHALL HAVE A NYLON SPIRAL ZIP WITH CLOSED FLY FRONT SECURED BY NON-CONDUCTIVE PRESS-STUDS; COMPLY WITH SANS 1822 TYPE 5; HOOD ATTACHED TO THE JACKET; JACKET TO COVER THE BUTTOCKS; FALSE ELASTIC SLEEVE AT THE END MADE OF SOFTER MATERIAL; PANTS SHALL HAVE SIDE SLITS AND ELASTIC WAIST; REFLECTIVE STRIPS TO BE FITTED ON BOTH SLEEVES ON THE UPPER ARM, AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SIDE OF THE SLEEVE AND THE ESKOM LOGO SHALL BE SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON THE FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; UNIQUE IDENTIFIER 240-44175132	37 341	EA
0222561	RAINWEAR:2 PIECE SUIT;S;BLUE NAVY	RAINWEAR: TYPE: 2 PIECE SUIT; SIZE: S; MATERIAL: POLYESTER 100 PCT PLAIN WEAVE, 180 GM/2 MIN;	14 732	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

## Business Management System

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

		<p>COLOR: BLUE NAVY; MATERIAL: MINIMUM 180 GRAMS PER M/3 FACE SIDE 100% POLYESTER; PLAIN WEAVE WITH 170 THREADS PER M/3 INCH WITH WATER RESISTANT COATING; UNDER SIDE LAMINATED WITH PVC COATING; SEAMS STRENGTH 50KPA; CONVERTS TO 50KNM/2; LINING 80% POLYESTER 20% COTTON; SIZE TO SANS 434 SIZE CHART ANNEX E FOR RAIN WEAR; JACKET SHALL HAVE A NYLON SPIRAL ZIP WITH CLOSED FLY FRONT SECURED BY NON-CONDUCTIVE PRESS-STUDS; COMPLY WITH SANS 1822 TYPE 5; HOOD ATTACHED TO THE JACKET; JACKET TO COVER THE BUTTOCKS; FALSE ELASTIC SLEEVE AT THE END MADE OF SOFTER MATERIAL; PANTS SHALL HAVE SIDE SLITS AND ELASTIC WAIST; REFLECTIVE STRIPS TO BE FITTED ON BOTH SLEEVES ON THE UPPER ARM, AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SIDE OF THE SLEEVE AND THE ESKOM LOGO SHALL BE SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON THE FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; UNIQUE IDENTIFIER 240-44175132</p>		
0222567	RAINWEAR:2 PIECE SUIT;XL;BLUE NAVY	<p>RAINWEAR: TYPE: 2 PIECE SUIT; SIZE: XL; MATERIAL: POLYESTER 100 PCT PLAIN WEAVE, 180 GM/2 MIN; COLOR: BLUE NAVY; MATERIAL: MINIMUM 180 GRAMS PER M/3 FACE SIDE 100% POLYESTER; PLAIN</p>	35 581	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

		<p>WEAVE WITH 170 THREADS PER M/3 INCH WITH WATER RESISTANT COATING; UNDER SIDE LAMINATED WITH PVC COATING; SEAMS STRENGTH 50KPA; CONVERTS TO 50KNM/2; LINING 80% POLYESTER 20% COTTON; SIZE TO SANS 434 SIZE CHART ANNEX E FOR RAIN WEAR; JACKET SHALL HAVE A NYLON SPIRAL ZIP WITH CLOSED FLY FRONT SECURED BY NON-CONDUCTIVE PRESS-STUDS; COMPLY WITH SANS 1822 TYPE 5; HOOD ATTACHED TO THE JACKET; JACKET TO COVER THE BUTTOCKS; FALSE ELASTIC SLEEVE AT THE END MADE OF SOFTER MATERIAL; PANTS SHALL HAVE SIDE SLITS AND ELASTIC WAIST; REFLECTIVE STRIPS TO BE FITTED ON BOTH SLEEVES ON THE UPPER ARM, AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SIDE OF THE SLEEVE AND THE ESKOM LOGO SHALL BE SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON THE FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; UNIQUE IDENTIFIER 240-44175132</p>		
0222499	TROUSERS:LADIES LONG;26; 67;BLUE NAVY	<p>TROUSERS: TYPE: LADIES LONG; SIZE: 26; 67; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL</p>	2 254	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

		<p>COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY</p>		
0222500	TROUSERS:LADIES LONG;28; 72;BLUE NAVY	<p>TROUSERS: TYPE: LADIES LONG; SIZE: 28; 72; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND</p>	2 254	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

		SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY		
0222501	TROUSERS:LADIES LONG;30; 77;BLUE NAVY	TROUSERS: TYPE: LADIES LONG; SIZE: 30; 77; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE	32 982	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

		FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY		
0222502	TROUSERS:LADIES LONG;32; 82;BLUE NAVY	TROUSERS: TYPE: LADIES LONG; SIZE: 32; 82; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY	39 031	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

0222503	TROUSERS:LADIES LONG;34; 87;BLUE NAVY	TROUSERS: TYPE: LADIES LONG; SIZE: 34; 87; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY	46 529	EA
0222504	TROUSERS:LADIES LONG;36; 92;BLUE NAVY	TROUSERS: TYPE: LADIES LONG; SIZE: 36; 92; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL	50 451	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

		<p>COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY</p>		
0222505	TROUSERS:LADIES LONG;38; 97;BLUE NAVY	<p>TROUSERS: TYPE: LADIES LONG; SIZE: 38; 97; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND</p>	47 369	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

		SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY		
0222506	TROUSERS:LADIES LONG;40; 102;BLUE NAVY	TROUSERS: TYPE: LADIES LONG; SIZE: 40; 102; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE	39 445	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

		FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY		
0222507	TROUSERS:LADIES LONG;42; 107;BLUE NAVY	TROUSERS: TYPE: LADIES LONG; SIZE: 42; 107; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY	33 247	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

0222508	TROUSERS:LADIES LONG;44; 112;BLUE NAVY	TROUSERS: TYPE: LADIES LONG; SIZE: 44; 112; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY	31 349	EA
0222509	TROUSERS:LADIES LONG;46; 117;BLUE NAVY	TROUSERS: TYPE: LADIES LONG; SIZE: 46; 117; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL	23 920	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

		<p>COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY</p>		
0222510	TROUSERS:LADIES LONG;48; 122;BLUE NAVY	<p>TROUSERS: TYPE: LADIES LONG; SIZE: 48; 122; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND</p>	6 072	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

		SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY		
0222511	TROUSERS:LADIES LONG;50; 127;BLUE NAVY	TROUSERS: TYPE: LADIES LONG; SIZE: 50; 127; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE	2 588	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

		FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY		
0222512	TROUSERS:LADIES LONG;52; 132;BLUE NAVY	TROUSERS: TYPE: LADIES LONG; SIZE: 52; 132; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY	3 048	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

0222513	TROUSERS:LADIES LONG;54; 137;BLUE NAVY	TROUSERS: TYPE: LADIES LONG; SIZE: 54; 137; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY	2 312	EA
0222472	TROUSERS:MEN LONG;102 CM;BLUE NAVY	TROUSERS: TYPE: MEN LONG; SIZE: 102 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME	78 879	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

		RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132		
0222473	TROUSERS: MEN LONG; 107 CM; BLUE NAVY	TROUSERS: TYPE: MEN LONG; SIZE: 107 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION	66 493	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

0222474	TROUSERS: MEN LONG; 112 CM; BLUE NAVY	TROUSERS: TYPE: MEN LONG; SIZE: 112 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION	62 698	EA
0222476	TROUSERS: MEN LONG; 117 CM; BLUE NAVY	TROUSERS: TYPE: MEN LONG; SIZE: 117 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON	47 829	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

		RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION		
0222477	TROUSERS: MEN LONG; 122 CM; BLUE NAVY	TROUSERS: TYPE: MEN LONG; SIZE: 122 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION	12 144	EA
0222478	TROUSERS: MEN LONG; 127 CM; BLUE NAVY	TROUSERS: TYPE: MEN LONG; SIZE: 127 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING	12 903	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

		SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION		
0222479	TROUSERS: MEN LONG; 132 CM; BLUE NAVY	TROUSERS: TYPE: MEN LONG; SIZE: 132 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION	6 095	EA
0222480	TROUSERS: MEN LONG; 137 CM; BLUE NAVY	TROUSERS: TYPE: MEN LONG; SIZE: 137 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59;	4 623	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

		<p>SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION</p>		
0222481	TROUSERS: MEN LONG; 142 CM; BLUE NAVY	<p>TROUSERS: TYPE: MEN LONG; SIZE: 142 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK;</p>	3 864	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

		SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION		
0222482	TROUSERS: MEN LONG; 147 CM; BLUE NAVY	TROUSERS: TYPE: MEN LONG; SIZE: 147 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION	3 243	EA
0566736	TROUSERS: MEN LONG; 152 CM; BLUE NAVY	TROUSERS: TYPE: MEN LONG; SIZE: 152 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362;	3 508	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

		POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION		
0566737	TROUSERS: MEN LONG; 157 CM; BLUE NAVY	TROUSERS: TYPE: MEN LONG; SIZE: 157 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION	2 875	EA
0626864	TROUSERS: MEN LONG; 72 CM; BLUE NAVY	TROUSERS: TYPE: MEN LONG; SIZE: 72 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR	4 497	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

		TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132		
0222467	TROUSERS:MEN LONG;77 CM;BLUE NAVY	TROUSERS: TYPE: MEN LONG; SIZE: 77 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS	65 953	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

### Business Management System

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

		PER SPECIFICATION		
0222468	TROUSERS: MEN LONG; 82 CM; BLUE NAVY	TROUSERS: TYPE: MEN LONG; SIZE: 82 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION	78 051	EA
0222469	TROUSERS: MEN LONG; 87 CM; BLUE NAVY	TROUSERS: TYPE: MEN LONG; SIZE: 87 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON	93 047	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

		THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION		
0222470	TROUSERS: MEN LONG; 92 CM; BLUE NAVY	TROUSERS: TYPE: MEN LONG; SIZE: 92 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION	100 901	EA
0222471	TROUSERS: MEN LONG; 97 CM; BLUE NAVY	TROUSERS: TYPE: MEN LONG; SIZE: 97 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME	94 726	EA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.



**Business Management System**

Supply Chain Management

Warehouse Scope of Work PPE General Bodywear

RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER SPECIFICATION

Compiled By: Linda de Necker

Checked By: Cynthia Tsotetsi

Approved By: Boitshoko Mokolobate

Signature... *L de Necker* .....

Signature... *C Tsotetsi* .....

Signature... *B Mokolobate* .....

Date...02/10/2025.....

Date...02/10/2025.....

Date...02/10/2025.....

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.