



<u>LEGEND:</u>	
SYMBOL	DESCRIPTION

# OTES

GENERAL

- ALL SETTING OUT TO BE UNDERTAKEN BY A REGISTERED PROFESSIONAL LAND SURVEYOR.
- PROVE ALL SERVICES PRIOR TO CONSTRUCTION.
- ALL WORK AREAS TO BE REINSTATED (PREMIX, CONCRETE, ETC.)
- ALL LEVELS AND DIMENSIONS TO BE VERIFIED ON SITE.
- ALL WORK IS TO BE EXECUTED IN ACCORDANCE WITH SANS 1200.

## INCE AND POST DE SKAGE & FREDRIK

## CKAGE 3: ERECTION OF NEW BOUNDARY FENCE) MAIN STRAINING BOXES

REFER TO DETAIL  
SPECIFIC

SPECIFICATION ON COW WORK PACKAGE 3.

ERECTION OF NEW BOUNDARY FENCE.

INSTALLED AT:

- 1.1. EVERY CORNER, CHANGE OF DIRECTION OR BEND EXCEEDING 5° CHANGE OF DIRECTION IN THE FENCE LINE;
- 1.2. AT INTERVALS OF AT LEAST 1 000M ALONG STRAIGHT SECTIONS OF THE FENCE LINE;
- 1.3. AT BOTH SIDES OF EACH GATE;
- 1.4. AT SIGNIFICANTLY UNEVEN TERRAIN SUCH AS AT RIVER - AND DONGA CROSSINGS AND OVER RIDGES, AS WILL BE IDENTIFIED DURING CONSTRUCTION BY AND AT THE

## INTERMEDIATE STRAINING BOXES

INTERMEDIATE STRAINING BOXES

2.1. REFER TO DETAIL ON DWG L2000-0000-005 AND FULL SPECIFICATION ON SoW WORK PACKAGE 3: ERECTION OF NEW BOUNDARY FENCE.

INSTALLED AT:

2.2. INTERVALS OF AT LEAST EVERY 500M, HALFWAY BETWEEN MAIN STRAINING BOXES, WHERE EVER THE MAIN STRAINING BOXES ARE MORE THAT 500M APART.

## STRAINING POSTS (SINGLE POSTS)

- 3.1. REFER TO DETAIL ON DWG L2000-0000-005 AND FULL SPECIFICATION ON SoW WORK PACKAGE 3: ERECTION OF NEW BOUNDARY FENCE.  
INSTALLED AT:
  - 3.2. STRAINING POSTS CONFORMING TO THE DIAGRAM GIVEN IN FIGURE 4 MUST BE ERECTED AT INTERVALS OF AT LEAST EVERY 50M.

VEHICULAR GATES TO BE  
WHERE THE NEW FENCE L

## DRIVEWAYS.

PEDESTRIAN GATE  
INDICATED MARK.

## PART SITE PLAN

