



NEC3 Supply

Short Contract (SSC3)

A contract between Eskom Holdings SOC Ltd (Reg No. 2002/015527/30)

and [•]

for Supply and delivery of production equipment for
transmission various grids

Contents:	Compiled in accordance with CIDB Standard for Uniformity in Construction Procurement (May 2010) amendments)	Page No.
Part C1	Agreements & Contract Data	
	C1.1 Form of Offer and Acceptance	[•]
	C1.2 Contract Data provided by the <i>Purchaser</i>	[•]
	C1.2 Contract Data provided by the <i>Supplier</i>	[•]
Part C2	Pricing Data	
	C2.1 Pricing assumptions	[•]
	C2.2 Price Schedule	[•]
Part C3	Scope of Work	
	C3.1 Goods Information	[•]
	Pro Forma Batch Order	

Documentation prepared by:

C1 Agreements & Contract Data

C1.1 Form of Offer and Acceptance

Offer

The Purchaser, identified in the Acceptance page signature block on the next page, has solicited offers to enter into a contract for the procurement of:

Supply and delivery of production equipment for transmission various grids

The tenderer, identified in the signature block below, has

<i>either</i>	examined the documents listed in the Tender Data and addenda thereto as listed in the Returnable Schedules, and by submitting this Offer has accepted the Conditions of Tender.
<i>or</i>	examined the draft contract as listed in the Acceptance section and agreed to provide this Offer.

By the representative of the tenderer, deemed to be duly authorised, signing this part of this Form of Offer and Acceptance the tenderer offers to perform all of the obligations and liabilities of the Supplier under the Contract including compliance with all its terms and conditions according to their true intent and meaning for an amount to be determined in accordance with the conditions of contract identified in the Contract Data.

The offered total of the Prices exclusive of VAT is	R[●]
Value Added Tax @ 15% is	R[●]
The offered total of the Prices inclusive of VAT is	R[●]
(in words)	

This Offer may be accepted by the Purchaser by signing the form of Acceptance overleaf and returning one copy of this document including the Schedule of Deviations (if any) to the tenderer before the end of the period of validity stated in the Tender Data, or other period as agreed, whereupon the tenderer becomes the party named as the Supplier in the conditions of contract identified in the Contract Data.

Signature(s)

Name(s)

Capacity

**For the
tenderer:**

(Insert name and address of organisation)

Name &
signature of
witness

Date

Acceptance

By signing this part of this Form of Offer and Acceptance, the Purchaser identified below accepts the tenderer's Offer. In consideration thereof, the Purchaser shall pay the Supplier the amount due in accordance with the conditions of contract identified in the Contract Data. Acceptance of the tenderer's Offer shall form an Agreement between the Purchaser and the tenderer upon the terms and conditions contained in this Agreement and in the Contract that is the subject of this Agreement.

The terms of the Contract, are contained in:

Part 1 Agreements and Contract Data, (which includes this Form of Offer and Acceptance)

Part 2 Pricing Data

Part 3 Scope of Work: Goods Information

and drawings and documents (or parts thereof), which may be incorporated by reference into the above listed Parts.

Deviations from and amendments to the documents listed in the Tender Data and any addenda thereto listed in the Tender Schedules as well as any changes to the terms of the Offer agreed by the tenderer and the Purchaser during this process of Offer and Acceptance, are contained in the Schedule of Deviations attached to and forming part of this Form of Offer and Acceptance. No amendments to or deviations from said documents are valid unless contained in this Schedule, which must be signed by the duly authorised representative(s) for both parties.

The tenderer shall within one week of receiving a completed copy of this Agreement, including the Schedule of Deviations (if any), contact the Purchaser's agent (whose details are given in the Contract Data) to arrange the delivery of any securities, bonds, guarantees, proof of insurance and any other documentation to be provided in terms of the conditions of contract identified in the Contract Data at, or just after, the date this Agreement comes into effect. Failure to fulfil any of these obligations in accordance with those terms shall constitute a repudiation of this Agreement.

Notwithstanding anything contained herein, this Agreement comes into effect on the date when the tenderer receives one fully completed copy of this document, including the Schedule of Deviations (if any) together with all the terms of the contract as listed above.

Unless the tenderer (now *Supplier*) within five working days of the date of such receipt notifies the Purchaser in writing of any reason why he cannot accept the contents of this agreement, this agreement shall constitute a binding contract between the Parties.

Signature(s)

Name(s)

Capacity

**for the
Purchaser**

(Insert name and address of organisation)

Name &
signature of
witness

Date

Note: If a tenderer wishes to submit alternative tender offers, further copies of this document may be used for that purpose, duly endorsed, 'Alternative Tender No. _____'.

Schedule of Deviations

Note:

1. To be completed by the Purchaser prior to award of contract. This part of the Offer & Acceptance would not be required if the contract has been developed by negotiation between the Parties and is not the result of a process of competitive tendering.
2. The extent of deviations from the tender documents issued by the Purchaser prior to the tender closing date is limited to those permitted in terms of the Conditions of Tender.
3. A tenderer's covering letter must not be included in the final contract document. Should any matter in such letter, which constitutes a deviation as aforesaid be the subject of agreement reached during the process of Offer and Acceptance, the outcome of such agreement shall be recorded here and the final draft of the contract documents shall be revised to incorporate the effect of it.

No.	Subject	Details
1		
2		
3		
4		
5		
6		
7		

By the duly authorised representatives signing this Schedule of Deviations below, the Purchaser and the tenderer agree to and accept this Schedule of Deviations as the only deviations from and amendments to the documents listed in the Tender Data and any addenda thereto listed in the Tender Schedules, as well as any confirmation, clarification or changes to the terms of the Offer agreed by the tenderer and the Purchaser during this process of Offer and Acceptance.

It is expressly agreed that no other matter whether in writing, oral communication or implied during the period between the issue of the tender documents and the receipt by the tenderer of a completed signed copy of this Form shall have any meaning or effect in the contract between the parties arising from this Agreement.

For the tenderer:

For the Purchaser

Signature

Name

Capacity

On behalf
of

(Insert name and address of organisation)

(Insert name and address of organisation)

Name &
signature
of witness

Date

C1.2 Contract Data

Data provided by the *Purchaser*

Completion of the data in full is essential to create a complete contract.

Clause	Statement	Data
General		
10.1	The <i>Purchaser</i> is (Name):	Eskom Holdings SOC Limited (reg no: 2002/015527/30), a state owned company incorporated in terms of the company laws of the Republic of South Africa
	Address	Registered office at Megawatt Park, Maxwell Drive, Sandton, Johannesburg
	Tel No.	To be advised
	Fax No.	To be advised
	E-mail address	To be advised
11.2(4)	The <i>delivery date</i> is	30 March 2022
11.2(5)	The Goods Information is in	the document called 'Goods Information' in Part 3 of this contract.
11.2(8)	The <i>goods</i> are	Production equipment for various grids
12.2	The <i>law of the contract</i> is	the Republic of South Africa
13.2	The <i>period for reply</i> is	1 week
15.1	The <i>premises</i> are	Transmission various Grids
23.1	The <i>Purchaser</i> requires the <i>Supplier</i> to Provide the Goods when instructed by Batch Order.	No
23.1		
30.1	The <i>starting date</i> is.	As soon as the contract is signed by both parties
41.1	The <i>defects date</i> is	On installation date.
42.2	The period for the correction of Defects after Delivery is	2 working days
50.1	The <i>assessment day</i> is the	After each delivery subject to approval of QC and visual inspection
50.5	The <i>delay damages</i> are [	[•] per day.
51.2	The interest rate on late payment is	[•]% per complete week of delay. [Insert a rate only if a rate less than 0.5% per week of delay has been agreed]

86.1	The <i>Supplier's</i> liability to the <i>Purchaser</i> for indirect or consequential loss, including loss of profit, revenue and goodwill is limited to	Zero
86.2	The <i>Supplier</i> is not liable to the <i>Purchaser</i> for loss of or damage to the <i>Purchaser's</i> property in excess of	[•] for any one event.
93.1	The <i>Adjudicator</i> is	the person selected from the ICE-SA Division (or its successor body) of the South African Institution of Civil Engineering Panel of Adjudicators by the Party intending to refer a dispute to him (see www.ice-sa.org.za). If the Parties do not agree on an Adjudicator the Adjudicator will be appointed by the Arbitration Foundation of Southern Africa (AFSA).
93.2(2)	The <i>Adjudicator nominating body</i> is:	the Chairman of ICE-SA a joint Division of the South African Institution of Civil Engineering and the Institution of Civil Engineers (UK) or its successor body (See www.ice-sa.org.za).
93.4	The <i>tribunal</i> is: If the <i>tribunal</i> is arbitration, the arbitration procedure is	arbitration. the latest edition of Rules for the Conduct of Arbitrations published by The Association of Arbitrators (Southern Africa) or its successor body.
11.1	The conditions of contract are the NEC3 Supply Short Contract (April 2013) ^{1 2} and the following additional conditions. [Only enter details here if additional conditions are required, otherwise state 'none']	

¹ Can be obtained from Engineering Contract Strategies on www.ecs.co.za, Tel 011 803 3008, Fax 086 539 1902

² If the December 2009 edition is being used, replace April 2013 with December 2009

Z1 Cession delegation and assignment

- Z1.1 The *Supplier* does not cede, delegate or assign any of its rights or obligations to any person without the written consent of the *Purchaser*.
- Z1.2 Notwithstanding the above, the *Purchaser* may on written notice to the *Supplier* cede and delegate its rights and obligations under this contract to any of its subsidiaries or any of its present divisions or operations which may be converted into separate legal entities as a result of the restructuring of the Electricity Supply Industry and the Electricity Distribution Industry.

Z2 Change of Broad Based Black Economic Empowerment (B-BBEE) status

- Z2.1 Where a change in the *Supplier's* legal status, ownership or any other change to his business composition or business dealings results in a change to the *Supplier's* B-BBEE status, the *Supplier* notifies the *Purchaser* within seven days of the change.
- Z2.2 The *Supplier* is required to submit an updated verification certificate and necessary supporting documentation confirming the change in his B-BBEE status to the *Purchaser* within thirty days of the notification or as otherwise instructed by the *Purchaser*.
- Z2.3 Where, as a result, the *Supplier's* B-BBEE status has decreased since the Contract Date the *Purchaser* may either re-negotiate this contract or alternatively, terminate the *Supplier's* obligation to Provide the Goods.
- Z2.4 Failure by the *Supplier* to notify the *Purchaser* of a change in its B-BBEE status may constitute a reason for termination. If the *Purchaser* terminates in terms of this clause, the procedures on termination are the same as for Reason 3 identified in clause 90.3.

Z3 Waiver and estoppel: Add to clause 12.3:

- Z3.1 Any extension, concession, waiver or relaxation of any action stated in this contract by the Parties, or the *Adjudicator* does not constitute a waiver of rights, and does not give rise to an estoppel unless the Parties agree otherwise and confirm such agreement in writing.

Z4 Provision of a Tax Invoice and interest. Add to clause 51

- Z4.1 The *Supplier* provides the *Purchaser* with a tax invoice in accordance with the *Purchaser's* procedures stated in the Goods Information, showing the correctly assessed amount due.
- Z4.2 If the *Supplier* does not provide a tax invoice by the time required in this contract for his assessment of each amount due, the time by when the *Purchaser* is to make a payment is extended by a period equal in time to the delayed submission of the correct tax invoice. Interest due by the *Purchaser* in terms of core clause 51.2 is then calculated from the delayed date by when payment is to be made.
- Z4.3 The *Supplier* (if registered in South Africa in terms of the companies Act) is required to comply with the requirements of the Value Added Tax Act, no 89 of 1991 (as amended) and to include the *Purchaser's* VAT number 4740101508 on each invoice he submits for payment.

Z5 Purchaser's limitation of liability

- Z5.1 The *Purchaser's* liability to the *Supplier* for the *Supplier's* indirect or consequential loss is limited to R0.00 (zero Rand)

Z5.2 The *Supplier's* entitlement under the indemnity in 83.1 is provided for in 60.1(8) and the *Purchaser's* liability under the indemnity is limited.

Z6 Termination: Add to clause 90.2 before (Reason 1)

Z6.1 or had a judicial management order granted against it.

Z7 Addition to clause 50.5

Z7.1 If the amount due for the *Supplier's* payment of *delay damages* reaches the limits stated in this Contract Data (if any), the *Purchaser* may terminate the *Supplier's* obligation to Provide the Goods using the same procedures and payment on termination as those applied for Reason 3. Identified in clause 90.3.

Z8 Ethics

For the purposes of this Z-clause, the following definitions apply:

Affected Party	means, as the context requires, any party, irrespective of whether it is the <i>Supplier</i> or a third party, such party's employees, agents, or Subcontractors or Subcontractor's employees, or any one or more of all of these parties' relatives or friends,
Coercive Action	means to harm or threaten to harm, directly or indirectly, an Affected Party or the property of an Affected Party, or to otherwise influence or attempt to influence an Affected Party to act unlawfully or illegally,
Collusive Action	means where two or more parties co-operate to achieve an unlawful or illegal purpose, including to influence an Affected Party to act unlawfully or illegally,
Committing Party	means, as the context requires, the <i>Supplier</i> , or any member thereof in the case of a joint venture, or its employees, agents, or Subcontractors or the Subcontractor's employees,
Corrupt Action	means the offering, giving, taking, or soliciting, directly or indirectly, of a good or service to unlawfully or illegally influence the actions of an Affected Party,
Fraudulent Action	means any unlawfully or illegally intentional act or omission that misleads, or attempts to mislead, an Affected Party, in order to obtain a financial or other benefit or to avoid an obligation or incurring an obligation,
Obstructive Action	means a Committing Party unlawfully or illegally destroying, falsifying, altering or concealing information or making false statements to materially impede an investigation into allegations of Prohibited Action, and
Prohibited Action	means any one or more of a Coercive Action, Collusive Action Corrupt Action, Fraudulent Action or Obstructive Action.

Z8.1 A Committing Party may not take any Prohibited Action during the course of the procurement of this contract or in execution thereof.

Z8.2 The *Purchaser* may terminate the *Supplier's* obligation to Provide the Services if a Committing Party has taken such Prohibited Action and the *Supplier* did not take timely and appropriate action to prevent or remedy the situation, without limiting any other rights or remedies the *Purchaser* has. It is not required that the Committing Party had to have been found guilty, in court or in any other similar process, of such Prohibited Action before the *Purchaser* can terminate the *Supplier's* obligation to Provide the Services for this reason.

Z8.3 If the *Purchaser* terminates the *Supplier's* obligation to Provide the Services for this reason, the amounts due on termination are those intended in core clauses 92.1 and

92.2.

- Z8.4 A Committing Party co-operates fully with any investigation pursuant to alleged Prohibited Action. Where the *Purchaser* does not have a contractual bond with the Committing Party, the *Supplier* ensures that the Committing Party co-operates fully with an investigation.

Z9 Insurance

Replace condition of contract 84 with the following:

Insurance cover 84

- 84.1** When requested by a Party, the other Party provides certificates from his insurer or broker stating that the insurances required by this contract are in force.
- 84.2** The *Supplier* provides the insurances in this Insurance Table A from the *starting date* until Delivery and against any risks he carries under this contract between Delivery and the *defects date*.

INSURANCE TABLE A

Insurance against	Minimum amount of cover or minimum limit of indemnity
Loss of or damage to the <i>goods</i> , plant and materials	The replacement cost where not covered by the <i>Purchaser's</i> insurance. The <i>Purchaser's</i> policy deductible as at contract date where covered by the <i>Purchaser's</i> insurance.
Liability for loss of or damage to property (except the <i>goods</i> , plant and materials and equipment) and liability for bodily injury to or death of a person (not an employee of the <i>Supplier</i>) caused by activity in connection with this contract	<u>Loss of or damage to property</u> <u><i>Purchaser's</i> property</u> The replacement cost where not covered by the <i>Purchaser's</i> insurance. The <i>Purchaser's</i> policy deductible as at contract date, where covered by the <i>Purchaser's</i> insurance. <u>Other property</u>

	The replacement cost
	Death of or bodily injury
	The amount required by the applicable law.
Liability for death of or bodily injury to employees of the <i>Supplier</i> arising out of and in the course of their employment in connection with this contract	The amount required by the applicable law

84.2 The Purchaser provides the insurances in this Insurance Table B

INSURANCE TABLE B

Insurance against or name of policy	Minimum amount of cover or minimum limit of indemnity
Assets All Risk	Per the insurance policy document
Contract Works insurance	Per the insurance policy document
Environmental Liability	Per the insurance policy document
General and Public Liability	Per the insurance policy document
Transportation (Marine)	Per the insurance policy document
Motor Fleet and Mobile Plant	Per the insurance policy document
Terrorism	Per the insurance policy document
Cyber Liability	Per the insurance policy document
Nuclear Material Damage and Business Interruption	Per the insurance policy document
Nuclear Material Damage Terrorism	Per the insurance policy document

Z10 Nuclear Liability

- Z10.1 The *Purchaser* is the operator of the Koeberg Nuclear Power Station (KNPS), a nuclear installation, as designated by the National Nuclear Regulator of the Republic of South Africa, and is the holder of a nuclear licence in respect of the KNPS.
- Z10.2 The *Purchaser* is solely responsible for and indemnifies the *Supplier* or any other person against any and all liabilities which the *Supplier* or any person may incur arising out of or resulting from nuclear

damage, as defined in Act 47 of 1999, save to the extent that any liabilities are incurred due to the unlawful intent of the *Supplier* or any other person or the presence of the *Supplier* or that person or any property of the *Supplier* or such person at or in the KNPS or on the KNPS site, without the permission of the *Purchaser* or of a person acting on behalf of the *Purchaser*.

Z10.3 Subject to clause Z10.4 below, the *Purchaser* waives all rights of recourse, arising from the aforesaid, save to the extent that any claims arise or liability is incurred due or attributable to the unlawful intent of the *Supplier* or any other person, or the presence of the *Supplier* or that person or any property of the *Supplier* or such person at or in the KNPS or on the KNPS site, without the permission of the *Purchaser* or of a person acting on behalf of the *Purchaser*.

Z10.4 The *Purchaser* does not waive its rights provided for in section 30 (7) of Act 47 of 1999, or any replacement section dealing with the same subject matter.

Z10.5 The protection afforded by the provisions hereof shall be in effect until the KNPS is decommissioned.

Z11 Asbestos

For the purposes of this Z-clause, the following definitions apply:

AAIA	means approved asbestos inspection authority.
ACM	means asbestos containing materials.
AL	means action level, i.e. a level of 50% of the OEL, i.e. 0.1 regulated asbestos fibres per ml of air measured over a 4 hour period. The value at which proactive actions is required in order to control asbestos exposure to prevent exceeding the OEL.
Ambient Air	means breathable air in area of work with specific reference to breathing zone, which is defined to be a virtual area within a radius of approximately 30cm from the nose inlet.
Compliance Monitoring	means compliance sampling used to assess whether or not the personal exposure of workers to regulated asbestos fibres is in compliance with the Standard's requirements for safe processing, handling, storing, disposal and phase-out of asbestos and asbestos containing material, equipment and articles.
OEL	means occupational exposure limit.
Parallel Measurements	means measurements performed in parallel, yet separately, to existing measurements to verify validity of results.
Safe Levels	means airborne asbestos exposure levels conforming to the Standard's requirements for safe processing, handling, storing, disposal and phase-out of asbestos and asbestos containing material, equipment and articles.
Standard	means the <i>Purchaser's</i> Asbestos Standard 32-303: Requirements for Safe Processing, Handling, Storing, Disposal and Phase-out of Asbestos and Asbestos

Containing Material, Equipment and Articles.

SANAS means the South African National Accreditation System.

TWA means the average exposure, within a given workplace, to airborne asbestos fibres, normalised to the baseline of a 4 hour continuous period, also applicable to short term exposures, i.e. 10-minute TWA.

Z11.1 The *Purchaser* ensures that the Ambient Air in the area where the *Supplier* will Provide the Services conforms to the acceptable prescribed South African standard for asbestos, as per the regulations published in GNR 155 of 10 February 2002, under the Occupational Health and Safety Act, 1993 (Act 85 of 1993) ("Asbestos Regulations"). The OEL for asbestos is 0.2 regulated asbestos fibres per millilitre of air as a 4-hour TWA, averaged over any continuous period of four hours, and the short term exposure limit of 0.6 regulated asbestos fibres per millilitre of air as a 10-minute TWA, averaged over any 10 minutes, measured in accordance with HSG248 and monitored according to HSG173 and OESSM.

Z11.2 Upon written request by the *Supplier*, the *Purchaser* certifies that these conditions prevail. All measurements and reporting are effected by an independent, competent, and certified occupational hygiene inspection body, i.e. a SANAS accredited and Department of Employment and Labour approved AAIA. The *Supplier* may perform Parallel Measurements and related control measures at the *Supplier's* expense. For the purposes of compliance the results generated from Parallel Measurements are evaluated only against South African statutory limits as detailed in clause Z11.1. Control measures conform to the requirements stipulated in the AAIA-approved asbestos work plan.

Z11.3 The *Purchaser* manages asbestos and ACM according to the Standard.

Z11.4 In the event that any asbestos is identified while Providing the Services, a risk assessment is conducted and if so required, with reference to possible exposure to an airborne concentration of above the AL for asbestos, immediate control measures are implemented and relevant air monitoring conducted in order to declare the area safe.

Z11.5 The *Supplier's* personnel are entitled to stop working and leave the contaminated area forthwith until such time that the area of concern is declared safe by either Compliance Monitoring or an AAIA approved control measure intervention, for example, per the emergency asbestos work plan, if applicable.

Z11.6 The *Supplier* continues to Provide the Services, without additional control measures presented, on presentation of Safe Levels. The contractually agreed dates to Provide the Services, including the Completion Date, are adjusted accordingly. The contractually agreed dates are extended by the notification periods required by regulations 3 and 21 of the Asbestos Regulations.

Z11.7 Any removal and disposal of asbestos, asbestos containing materials and waste, is done by a registered asbestos contractor, instructed by the *Purchaser* at the *Purchaser's* expense, and conducted in line with South African legislation.

Data provided by the *Supplier* (the *Supplier's Offer*)

The tendering Supplier is advised to read both the NEC3 Supply Short Contract (April 2013) and the relevant parts of its Guidance Notes (SSC3-GN)³ in order to understand the implications of this Data which the tenderer is required to complete. An example of the completed Data is provided on page 28 of the SSC3 Guidance Notes and Flow Charts.

Completion of the data in full is essential to create a complete contract.

10.1	The <i>Supplier</i> is (Name):	[•]
	Address	[•]
	Tel No.	[•]
	Fax No.	[•]
	E-mail address	[•]
11.2(7)	The Price Schedule is in	the document called 'Price Schedule' in Part 2 of this contract.
11.2(7)	The offered total of the Prices	See C1.1 Form of Offer and Acceptance
63.2	The percentage for overheads and profit added to the Defined Cost is	[•]%

³ Available from Engineering Contract Strategies on www.ecs.co.za Tel 011 803 3008, Fax 086 539 1902.

C2 Pricing Data

C2.1 Pricing assumptions

Note: No price to be submitted at the tender closing date.

- Tenders with prices will be disqualified
- Bidders will be given the chance to bid with their prices on the e-auction platform after the enquiry closing date

C2.2 Price Schedule

Note: No price to be submitted at the tender closing date.

- Tenders with prices will be disqualified
- Bidders will be given the chance to bid with their prices on the e-auction platform after the enquiry closing date.

C3: Scope of Work

C3.1 Goods Information

1. Description of the *goods*

North West Region

Class	DESCRIPTION	SAP Short Text	Technical Specification
Tester	Test handle	Handle: type: test handle	Handle: type: test handle; test handle pk2 4 way set - modified; vendors are responsible for ensuring that they are performing against the correct drawing revision number (if applicable)
Tester	Portable capacitive meter	Tester: type: portable capacitive meter	Tester: type: portable capacitive meter; potential: 1.1-1.4 pk-pk, 40-160hz; frequency: more than 8 hours; accuracy: -+ 1.0%; dimensions: 2.4kg; range: 0-1000 microfarads; specification: cb-2000; power: 2000microfarads; portable capacitive meter Measuring range 0-1000 microfarads Measurement accuracy -+ 1.0% maximum load 2000microfarads test volatge 1.1-1.4 pk-pk, 40-160hz Weights(cb-2000) 2.4kg Operating time = more than 8 hours Components: 1. To be delivered with clip on transformer 2. Voltage cl ips

			3. Rechargeable battery pack (nimh) 4. Extra battery holder 5. Usable stick with software and user manual Vendors are responsible for ensuring that they are performing against the correct drawing revision number (if applicable).
Tester	Batt impedance	Tester: type: batt impedance; potential: 120/220 vac	Tester: type: batt impedance; potential: 120/220 vac; frequency: 50/60 hz; accuracy: 5 pct; dimensions: wd 470 x ht 190 x dp 370 mm; range: 1-2.500 vdc; display type: lcd, 2 x 16 characters; power: 14 va; tester 120 v; tester for lead-acid and nickel-cadmium cells up to 7000 ah; vendors are responsible for ensuring that they are performing against the correct drawing revision number (if applicable).
Ducter tester	Meter, electrical test	Meter, electrical test: type: digital microhmmeter	Meter, electrical test: type: digital microhmmeter (ducter tester); readout: digital; range: dlro 200; megger dlro 200 digital microhmmeter with new duplex connect test leads, specifications temperature range - 10 to +50 deg c (-14 to +122°f), storage temperature-25 to +65°c (-13 to 149°f); vendors are responsible for ensuring that they are performing against the correct drawing revision number (if applicable).
Battery charger	Charger	Charger, battery: type: 160a; power source: 230v ac (- 10% + 15%);	Charger, battery: type: 160a; power source: 230v ac (- 10% + 15%); output: 12v - 270v 160a; connection: 1% for full range of dc input voltage; portable and lightweight enough to be carried by one person. E n v i r o n m e n t a l operation temp 0°c-40°c ambient temperature p r o t e c t i o n load current limit current limit adjustable thermal automatic shutdown on thermal overload with

			automatic reset protection load dc fuse. Auxiliary ac power supply 230v ac (– 10% + 15%) dc input voltage range 12v – 270v load current ability variable 12v - 270v 160a Current regulation <1% for full range of dc input voltage Alarms o dc reverse polarity. O battery low voltage. O load over current. O battery over voltage. O fan fail. View test parameters/results in real time using win 10 software Save results to pc for analysis, report generation and storage; vendors are responsible for ensuring that they are performing against the correct drawing revision number (if applicable).
Kit Control	Kit Control	Kit: control earth 6m;10-20 ka	Kit: type: control earth 6m; application: 10-20 ka; comprising: 1 x cable lg 12 m with snap-on line end clamp on one end, earth end clamp on other end, 2 x cables max lg 2 m with snap-on line end clamps on each end; 1 x earth spike; specification: eskom 240-65216546; control earths substation kits (10 - 20ka) e-ces, each bag contains: 3 x 6m earths phase to earths jumpers of 95 mm flexible copper w red translucent pvs sheathing with a screw on clamp on one end and earth clamp on the other end, cable size: 95 mm, cable colour: red translucent pvc; jumper lengths: 6m, jumpers in a kit 3, phase clamps: screw on type earth clamps: brass earths clamp to fit earthball, bag: red with eskom logo, heavy duty carry bag
Tester	Tester Ductor	Tester: type: ductor; potential: 10-200 a;	Tester: type: ductor; potential: 10-200 a; frequency: na; accuracy: aprox 2 a; range: 250 - 1000; specification: micro oh meter; display type: digital; power: 1000v; dlro200 dlro 200 - 200a micro-ohmmeter

			Product documents Data sheet - dlro200 Data sheet - test lead options User guide - dlro200 Overview technical Test currents from 10 a to 200 a dc Filtered direct current output eliminates magnetic transients Up to 0.1 o resolution On board memory for up to 300 test results and notes Rs232 port to download stored results via a pc or laptop powerdb compatible for test result storage and management Small and weighs less than 32 lbs (15 kg) supplied with 16 ft (5m) test leads dlro200 measures resistances between 0.1 o and 1 o, at high currents. This versatile instrument can provide test currents from 10 amps up to 200 amps subject to the load resistance and supply voltage. A large lcd displays all test parameters and measurement results. Specifications for digital micro-ohmmeter Continuous test time More than 60 seconds at 200 a @ 20°C ambient Required leads 2 x 5 m 25 mm² leads and 2 x current leads 8 m 2 x 15 m 95 mm² leads and 2 x current leads 6 m
--	--	--	---

			Measurement: Range: 0.1 to 999.9 m (subject to supply voltage and leads used) Accuracy: Voltage $\pm 0.5\% \pm 0.1$ mv Current $\pm 0.5\% \pm 0.1$ a Resistance: better than 1% from 300 to 100 m Better than $\pm 2\%$ from 100 to 300 power supply for full output (unsmoothed d.c.) 100 to 265 v 50/60 hz with a load Less than 19 m (supply >207 v rms), or 11 m (115 v rms) including current leads test modes: manual, auto, continuous. Test time: 10 seconds normal /auto mode. Refreshed every 2 seconds in continuous mode display: large, high resolution backlit liquid crystal display warnings current flowing: - led. Other warnings are shown on the lcd display data transfer real time or batch download via rs232 using download manager. Storage capacity: 300 result sets and memo, battery backed for 10 years. Memo field: 160 characters max. Test current range: 10 a to 200 a d.c. * Accuracy: $\pm 2\% \pm 2$ a Voltmeter input impedance: >200 k Hum rejection: 5 v rms 50 hz/60 hz Temperature operation: -10 to +50°C (-14 to
--	--	--	---

			+122°F) storage: -25 to +65°C (-13 to 149°F) calibration: 20°C co-efficient: <0.05% per °C Digital micro-ohm meter max. Humidity: 95% rh non-condensing maxi altitude: 2000 m safety: iec61010-1 emc: iec61326-1 Dimensions: 410 x 250 x 270 mm (16.4 x 9.84 x 10.63 ins) weight: 14.5 kg (excluding test leads) (31.97 lbs Vendors are responsible for ensuring that they are performing against the correct drawing revision number (if applicable).
--	--	--	--

Western Region

Safety Harness	Harness safety	Harness sfty indstrl: lanyard;2.5 m	Harness, safety industrial: type: lanyard; harness material: polyester with nylon thread; harness webbing size: 2.5 m; buckle material: aluminium; buckling system: single; lifeline: none; attachment method: clip on; adjustment method: retractable; load rating: 4.79 knm; specification: en360:2002
Safety Harness	Harness safety	Harness sfty indstrl: work position belt	Harness, safety industrial: type: work position belt; harness material: polyester with nylon thread; harness webbing size: 2 m; buckle material: aluminium hardware; buckling system: aluminium hardware; lifeline: none; attachment method: 2m attachment hooks; adjustment method: clip on; load rating: 1.75 knm; specification: sans50358; sans50361

Safety Harness	Harness safety	Harness sfty indstrl: lanyard; l/xl 40	Harness, safety industrial: type: lanyard; harness material: polyester with nylon thread; harness webbing size: l/xl 40; load rating: 4.79 knm; specification: sans50361/50358/50813; safety harness double lanyard with hooks xl
Bag duffel	Bag	Bag: type: duffel; dimensions: 500 x	Bag: type: duffel; dimensions: 500 x 400 x 300 mm; color: red; material: pvc; unit package quantity: 1; fall arrest system carry bag complete with handles and heavy-duty zipper
Tester	Portable capacitance meter	Tester: cb2000 portable capacitance meter	Tester: type: cb2000 portable capacitance meter; potential: 1.1-1.4 vac peak to peak; frequency: 40-160 hz; accuracy: +/- 1 pct; dimensions: 270 x 190 x 60 mm; range: 0- 1000 uf; display type: lcd; rechargeable battery pack 12 v, must include clip on transformer, voltage clips, 4 pin extension cable for voltage clips, 3 pin extension cable for clip on transformer, rechargeable nimh battery pack, power adapter, extra battery holder, usb stick and cable with software, casing and manual
Stabilizer	Stabilizer image Rubber and glass	Stabilizer image Rubber and glass	Stabilizer: type: image; size: wd 152 x lg 193 x ht 81 mm; material: rubber and glass; water resistant; weather proof; built-in image stabilizer (is) provides shake free performance; high magnification ratio: 18 x 50 is threaded to accept 58 mm filters and lens hoods; image stabilizer counteracts hand tremors for +/- 0.7 degree movement in all directions; field flattening lens improves edge- to-edge sharpness; ud ultra-low dispersion glass element; remarkable close focus distance of (6 m) for a 18 x power binocular; eye relief of 15 mm is sufficient for most users; standard threaded tripod socket upon bottom of housing

Camera	Camera dgtl: coolpix	Camera dgtl: coolpix p900;32 gb	Camera, digital: type: coolpix p900; storage capacity: 32 gb; resolution: 16.1-megapixel; zoom: 83x optical zoom (24-2000mm equivalent in 35mm format) and 166x dynamic fine zoom*1; recording medium: memory card; compatibility: windows 10; power source: battery; camera including camera bag and battery and lense
Hydrometer	Hydrometer	Hydrometer:0-3 g;0.001 g/cm3	Hydrometer: type: battery specific gravity analyzer; range: 0-3 g; graduations: 0.001 g/cm3; technical specifications, patents granted smart connection of measuring cell: patent at516421 (b1), ep3015847 (b1), other special functions viscosity correction for reliable measurements, also on highly viscous samples, gesture control for easy one-handed measurements, identification of results outside your specified limits, measuring range density: 0 g/cm3 to 3 g/cm3, temperature: 0-40 deg c (32-104 deg f), accuracy density: 0.001 g/cm3, temperature: 0.2 deg c (0.4 deg f), repeatability, s.d. Density: 0.0005 g/cm3, temperature: 0.1 deg c (0.2 deg f), reproducibility, s.d. Density: 0.0007 g/cm3, digital resolution density: 0.0001 g/cm3, temperature: 0.1 deg c (0.1 deg f), ambient temperature, standard version, ampere version: -10 deg c to +50 deg c (14-122 deg f), ex and ex petrol version: -10 deg c to +40 deg c (14 deg f to 104 deg f), supported measuring units, specific gravity, alcohol tables, sugar/extract tables, api functions, h 2so 4 tables, ten programmable custom-specific measuring units, sample volume 2 ml, dimensions (l x w x h) 245 mm x 103 mm x 126 mm, data memory 1024 measured results, 30 measuring methods, 250 sample ids, power supply three 1.5 v lr06 aa alkaline batteries, weight 660 g, interfaces bluetooth, rfid (both included by default) including software / computer interface cable, protection class ip54, (first digit: 5 – protection against dust

Hydraulic Crimper	Hydraulic Crimper	Crimper: type: hydraulic; crimping range: da7-da13, ds7-ds13;	Crimper: type: hydraulic; crimping range: da7-da13, ds7-ds13; jaw type: hex; design type: manual hydraulic bending/punching tool; furnished items: power pack; 4m diesel hydraulic power pack for dies sizes da7-da13 and ds7-ds13. "hpe-4m-diesel hydraulic power pack complete hpe4 1; specifications: set steel dies- ds7 -ds13 1, set aluminium dies da7-la13 1, 15 x 2 hydraulic hoses with couplings -ptn 3/4 inch 1, 100 ton hydraulic crimping head 1; Oil delivery:7.5 liter / min at low pressure, 1.2liter / min at high pressure; engine: air cooled 4 cycle gasoline engine, 2.2kw (3.0ps) / 3,600 rpm, lead free gasoline; reservoir capacity: 10 liter Size: wd 405 x lg 670 x ht 475mm; weight: 60kg (50kg dry); accessories: hydraulic hoses, crimping head with hex dies fox-bull, spark plug wrench; features: Manual controlled engine driven hydraulic pump suitable for single and double acting 60-, 100- and 200-ton presses for transmission line use. Manual control valve permits the user to advance, hold and retract the ram at will. It's simple design and positive manual control valve is ideal for high voltage construction site where electric magnetic field becomes a concern. Valve mode and operation up: the ram advances and pressure goes up to 68.5mpa. Then the relief vale functions. Neutral: the rams stop and holds it position. Down: the ram retracts to its lowest point (single and double acting presses). Then the pump builds up pressure to 13.7mpaand the relief valve functions (double acting press) ; vendors are responsible for ensuring that they are performing against the correct drawing revision number (if applicable).
----------------------	----------------------	---	--

		:	
Blade saw	Blade saw band	Blade, saw: saw type: band; tooth design: standard; teeth per inch:	Blade, saw: saw type: band; tooth design: standard; teeth per inch: 6; blade material: cobalt hss; cut material: hss hard/hss bi metal; width: 27 mm; length: 3300 mm; thickness: 0.9 mm; tooth set: vari-raker, 2 hp 380v 3-phase motor, 250 mm round cutting capacity at 90 deg, 190 mm round cutting capacity at 90 deg, semi-auto operation, variable blade speed 25-75 m/min, weight limited to 450 kg, 45 deg machine swivel angle for mitre cutting, 4 x spare bi-metal replacement blades, cutting coolant fluid

Kit tap	Kit tap changer	Kit: type: tap changer; application: uzern 250/300; 21 x single fixed	Kit: type: tap changer; application: uzern 250/300; 21 x single fixed contacts (2657 957-af); 3 x transition contact assemblies (5474 013-k); 3 x main and switching contact assemblies (5474 025-y); 3 x current collectors (2656 940-g), serial number 2285 032
---------	-----------------	---	---

Central Region

Fall Arrestors	"Fall arrest system	Fall arrest system, powerlines xlrqd12700	"fall arrest system powerlines extra-large manufactured, tested and marked in accordance to sans specifications supplied in a package containing : 1 x full body harness with work positioning belt to sans 50358 and sans 50361 1 x fixed or adjustable double safety lanyard to sans 50354 fitted with 2 x pylon hooks with minimum gate opening of 60mm to sans 50362, 1 x karabiner double or triple action locked with a captive eye (no screw gate) 25kn to sans 50362 and 1 x energy absorber not longer than 1.75m to sans 50355 1 x adjustable work positioning lanyard not longer than 2m to sans 50358 2 x twist-lock karabiners double or triple action to sans 50362 2 x attachment straps (1.5 m) to sans 50795 1 x protector bag * Eskom drawing d-dt-12700 rev 1 * test/cert., identification , specification and other related requirements : material specification : sans 50354, 50355, 50358, 50360, 50361, 50362 corrosion specification : sans 50354, 50355, 50358, 50360, 50361, 50362 standard specification : sans 50354, 50355, 50358, 50360, 50361, 50362, 50795, Eskom specification : scsscaba5 Test & certification requirements: certificates: type test certificates (at evaluation stage). Declaration of conformity certificate (per product supplied) Instruction for use and marking requirements: document of the general requirements for instruction for use and for marking to sans 50365 and a document on the information supplied by the manufacturer to sans 50354, 50355, 50358, 50360, 50361, 50362, 50795 identification:
----------------	---------------------	---	---

			indelible manufacturers trademark, model number and serial number on all items
Safety Harness	Safety Harness	Harness, safety industrial: type: fall arrest system, powerlines; harness material	Harness, safety industrial: type: fall arrest system, powerlines; harness material: sans 50354/50355/50358/50360/50361/50362; harness webbing size: l/xl 40; buckle material: nylon; buckling system: interlocking 2 part; d ring material: zinc plated forseeel steel; d ring quantity: 5; lifeline: 2 m adjustabe work positioning lanyard; energy absorber 1.75 m; fixed or adjustable double safety lanyard; attachment method: 2 attachment straps, 1.5 m; adjustment method: buckle; load rating: 25 knm; specification: corrosion sans 50354/50355/50358/50360/50361/50362 Eskom scsscaba5; std sans 50354/50355/50358/50360/50361/50362 marking to sans 50365/50354/50355/50358/50360/50361/50362/50795 Eskom powerlines fall arrest kit
Portable Earth	Kit: portable earth	Kit: portable earth 8 m; hv	Kit: type: portable earth 8 m; application: hv; comprising: 3 x 8 m phase to earth jumpers of 95 mm2 flexible copper w red transucent pvc sheathing with a screw on clamp on one end and an earth clamp on the other end plus 1 x heavy duty carry bag; specification: e-cs/20.8

Southern Region

Tester	Tester: for testing	Tester: for testing earth mat;10a	Tester: for testing earth mat;10a Dlro 10 digital micro-ohmmeter
Joint compress	Joint compression	Joint: type: compression; dimensions: dia 23.47 x	Joint: type: compression; dimensions: dia 23.47 x lg 800 mm; material: al; application: conductor bear; manuf p/n.; manufacturer: midspan; drawing no: d7001 rev 1; reference no: 852217
Kit control	Kit control Kit control	kit:control earth 10m;10-20 ka	kit: type: control earth 10m; application: 10-20 ka; comprising: 1 x cable lg 12 m with snap-on line end clamp on one end, earth end clamp on other end, 2 x cables max lg 2 m with snap-on line end clamps on each end; 1 x earth spike; specification: eskom 240-65216546; control earths substation kits (10 - 20ka) e-cs, each bag contains: 3 x 10m earths phase to earths jumpers of 95 mm flexible copper w red translucent pvs sheathing with a screw on clamp on one end and earth clamp on the other end, cable size: 95 mm, cable colour: red translucent pvc; jumper lengths: 10m, jumpers in a kit 3, phase clamps: screw on type earth clamps: brass earths clamp to fit earthball, bag: red with Eskom logo, heavy duty carry bag
Kit control	Kit control	kit:control earth 6m;10-20 ka	kit: type: control earth 6m; application: 10-20 ka; comprising: 1 x cable lg 12 m with snap-on line end clamp on one end, earth end clamp on other end, 2 x cables max lg 2 m with snap-on line end clamps on each end; 1 x earth spike; specification: eskom 240-65216546; control earths substation kits (10 - 20ka) e-cs, each bag contains: 3 x 6m earths

			phase to earths jumpers of 95 mm flexible copper w red translucent pvs sheathing with a screw on clamp on one end and earth clamp on the other end, cable size: 95 mm, cable colour: red translucent pvc; jumper lengths: 6m, jumpers in a kit 3, phase clamps: screw on type earth clamps: brass earths clamp to fit earthball, bag: red with eskom logo, heavy duty carry bag
Oil insulating	Oil insulating	oil insltg:viscous liquid;drum 200 l	oil, insulating: type: viscous liquid; container: drum 200 l; trade name: nytro libra sax; viscosity rating: 9.5 cst at 40 deg c; flash point: 144 deg c; density: 882 kg/m3; color: yellow light; odourless light petrolium; initial boiling point: 250deg c; solubility in water: non soluble; solubility in organic solvents: soluble; decomposition temp: 280deg c; vapour pressuer: 0.01kpa at 20deg c; dmso extractable compounds according to ip346 +/-3pct
Clip and straps	Clip and straps	guard:birds guards and ss straps	guard: type: birds guards and ss straps; dimensions: lg 1 m x ht 575 mm; material: plastic; application: birds guards devices; specification: 240-126259196; refer to plastic bird diverter specification and installation guideline 240-126259196, the bird guards should be made of a plastic material that complies with the rapid aging, material composition, pull and drop tests, they must be 575mm tall and 1m long and have intermediate uprights spaced 80mm apart, they must alternate between tall uprights (500mm) and short uprights of 280mm, on a base of 75mm, the plastic wall thickness should be 2.5mm minimum, they should also not have sharp points that can cause harm to birds or other wildlife, the fasteners must be made of stainless steel strap with a quick release mechanism, the dimensions of

			the stainless straps are 12mm x 0.75mm
--	--	--	--

Northern Region

Oil tank	Oil tank	Tank: type: iso; capacity: 22500 l; dimensions: lg 2591 mm	Tank: type: iso; capacity: 22500 l; dimensions: lg 2591 mm; material: ss 304; furnished items: float valve; media for which designed: oil storage; color: green; tanks mounted vertically and supported in a standard 20 iso container frame; vendors are responsible for ensuring that they are performing against the correct drawing revision number (if applicable)
----------	----------	--	---

Eastern Region

Earth kit	Kit	Kit: type: working earths (yellow in colour)	Kit: type: working earths (yellow in colour) for line up to 400kv x 6 sets current rating 30ka. Jumper 40y x 4m w' all angle g422810sj & earth x18 Clamp Bag yellow - wer x6
-----------	-----	--	--

Dynamo Meter	Dynamo Meter	Dynamometer: type: ocsy st digital dynamometer 50	Dynamometer: type: ocsy st digital dynamometer 50 ton with calibration certificate
Bird guard	Bird guards 1m	Bird guards 1m	Bird guards 1m Plastic bird perch diverter and stainless- steel strap
Release clips	Quick release clips	Quick release clips	X3 quick release clips Plastic bird perch diverter and stainless- steel strap
virgin oil.	virgin oil.	Uninhibited virgin oil	spec: 210l drum 1. Uninhibited virgin oil. 2. kV >70kV 3. moisture < 5 ppm 4. certificate of oil analysis showing the above must be provided upon delivery

Northern Cape Region

links	Link: type: insulated rigid splice;	Link: type: insulated rigid splice; dimensions: dia 38 x lg 3000 mm	Link: type: insulated rigid splice; dimensions: dia 38 x lg 3000 mm; material: fibre solid foam filled; vendors are responsible for ensuring that they are performing against the correct drawing revision number (if applicable).
links	link ext:insulated pentagonal	Link ext:insulated pentagonal telescopic	Link, extension: type: insulated pentagonal telescopic; length: 9.1 m; material: fibre; rating: 400 kv; vendors are responsible for ensuring that they are performing against the correct drawing revision number (if applicable)
Links	Linksticks	Link Sticks	Link, extension: type: linkstick telescopic lg; length: 30 ft (9m); material: fibreglass; rating: 5-7 sec & 5 -7 lid; vendors are responsible for ensuring that they are performing against the correct drawing revision number (if applicable).

North Eastern Region

Kit control	Kit control	Kit: type: control earth 6m; application: 10-20 ka	Kit: type: control earth 6m; application: 10-20 ka; comprising: 1 x cable lg 12 m with snap-on line end clamp on one end, earth end clamp on other end, 2 x cables max lg 2 m with snap-on line end clamps on each end; 1 x earth spike; specification: Eskom 240-65216546; control earths substation kits (10 - 20ka) e-ces, each bag contains: 3 x 6m earths phase to earths jumpers of 95 mm flexible copper w red translucent pvs sheathing with a screw on clamp on one end and earth clamp on the other end, cable size: 95 mm, cable colour: red translucent pvc; jumper lengths: 6m, jumpers in a kit 3, phase clamps: screw on type earth clamps: brass earths clamp to fit earthball, bag: red with Eskom logo, heavy duty carry bag
-------------	-------------	--	--

Kit control	Kit control	Kit: type: control earth 8m; application: 10-20 ka	Kit: type: control earth 8m; application: 10-20 ka; comprising: 1 x cable lg 12 m with snap-on line end clamp on one end, earth end clamp on other end, 2 x cables max lg 2 m with snap-on line end clamps on each end; 1 x earth spike; specification: Eskom 240-65216546; control earths substation kits (10 - 20ka) e-ces, each bag contains: 3 x 8m earths phase to earths jumpers of 95 mm flexible copper w red translucent pvs sheathing with a screw on clamp on one end and earth clamp on the other end, cable size: 95 mm, cable colour: red translucent pvc; jumper lengths: 8m, jumpers in a kit 3, phase clamps: screw on type earth clamps: brass earths clamp to fit earthball, bag: red with Eskom logo, heavy duty carry bag
Kit control	Kit control	Kit: type: control earth 10m; application: 10-20 ka	Kit: type: control earth 10m; application: 10-20 ka; comprising: 1 x cable lg 12 m with snap-on line end clamp on one end, earth end clamp on other end, 2 x cables max lg 2 m with snap-on line end clamps on each end; 1 x earth spike; specification: Eskom 240-65216546; control earths substation kits (10 - 20ka) e-ces, each bag contains: 3 x 10m earths phase to earths jumpers of 95 mm flexible copper w red translucent pvs sheathing with a screw on clamp on one end and earth clamp on the other end, cable size: 95 mm, cable colour: red translucent pvc; jumper lengths: 10m, jumpers in a kit 3, phase clamps: screw on type earth clamps: brass earths clamp to fit earthball, bag: red with Eskom logo, heavy duty carry bag
Kit control	Kit control	Kit: type: control earth 4m; application: 10-20 ka	Kit: type: control earth 4m; application: 10-20 ka; comprising: 1 x cable lg 12 m with snap-on line end clamp on one end, earth end clamp on other end, 2 x cables max lg 2 m with snap-on line end clamps on each end; 1 x earth spike; specification: Eskom 240-65216546; control earths substation kits (10 - 20ka) e-ces, each bag contains: 3 x 4m earths phase to earths jumpers of 95 mm flexible copper w red translucent pvs sheathing with a screw on clamp on one end and earth clamp on the other end, cable size: 95 mm, cable colour: red translucent pvc; jumper lengths: 4m, jumpers in a kit 3, phase clamps: screw on type earth

			clamps: brass earths clamp to fit earthball, bag: red with Eskom logo, heavy duty carry bag
--	--	--	--

2. Specifications

N/A

3. Constraints on how the *Supplier* Provides the Goods

State any constraints on how the *Supplier* is to provide the *goods* such as any limits on subcontracting. Also include any management related constraints, invoicing and payment procedures some of which have been inserted below as a minimum guide.

3.1 Subcontracting

N/A

3.2 Use of standard forms

- Early warning forms
- Non-conformance register form

3.3 Invoicing and payment

List information which is to be shown on an invoice. The following text is provided as a guide; revise to suit actual requirements.

In terms of core clause 50 the *Supplier* assesses the amount due and applies to the *Purchaser* for payment. The *Supplier* applies for payment with a tax invoice addressed to the *Purchaser* as follows:

The *Supplier* includes the following information on each tax invoice:

- Name and address of the *Supplier*
- The contract number and title;
- *Supplier's* VAT registration number;
- The *Purchaser's* VAT registration number which is _____;
- The total of
 - The Price for each lump sum item in the Price Schedule or Batch Order which the *Supplier* has completed;
 - Where a quantity is stated for an item in the Price Schedule or Batch Order, an amount calculated by multiplying the quantity which the *Supplier* has completed by the rate,
- Other amounts to be paid to the *Supplier*;
- Less amounts to be paid by or retained from the *Supplier*;
- The invoiced amount - excluding VAT, the VAT and including VAT;
- (add other as required)

Add procedures for invoice submission and payment (e. g. electronic payment instructions)

3.4 Records of Defined Cost

In order to substantiate the Defined Cost of compensation events, the *Purchaser* may require the *Supplier* to keep records of amounts paid by him for people employed by the *Supplier*, plant and materials, work subcontracted by the *Supplier* and equipment. [See clause 11.2(2) and 63.2]. State in what form these records are to be kept and how accessed by the *Purchaser*.

3.5 BBBEE and preferencing scheme

Specify constraints which *Supplier* must comply with after contract award in regard to any Broad Based Black Economic Empowerment (B-BBEE) or preferencing scheme measures.

3.6 Cataloguing requirements by the *Supplier* N/A

4. Requirements for the programme

This information is required by clause 32.1. State whether a programme is required and, if it is, state what form it is to be in, what information is to be shown on it, when it is to be submitted and when it is to be updated.

5. Services and other things provided by the *Purchaser*

Describe what the *Purchaser* will provide, in connection with the supply of the *goods*, such as transport, loading or unloading of the *goods*.

Item	Date by which it will be provided

6. Supply requirements

State the information which describes the *Purchaser's* requirements (other than services he is to provide) in connection with the supply of the *goods* including the requirements for transport, the mode of transport and the loading and unloading of the *goods*.

State the delivery place, the hours of access to the delivery place and other information to be provided by the *Supplier* at the time of Delivery such as the delivery note, which notifies the actual delivery date. The information necessary for a purchase that involves international, cross border, transactions should be stated here, such as export and import requirements of the Customs authorities.

Batch Order

Batch Order form for use when the Contract Data states that, in terms of clause 23, the *Purchaser* requires the *Supplier* to supply the *goods* in batches.

Contract number [•]

Batch Order No. [•]

Date

To: [•].....
..... (*Supplier*)

I instruct you to supply the following *goods* selected from the Price Schedule:

Item no.	Description	Unit	Quantity	Rate	Price

Total of the Prices for the Batch Order

The start date is [•]

The *delivery date* is [•]

Signed:

Name (in print)

(for *Purchaser*)