

TRANSNET



**TRANSNET ENGINEERING
TECHNICAL SPECIFICATION**

For

Fuel Pump Inverter for Class 44D Diesel Locomotive

Date of release

12 February 2024

Doc. No. SIAS_NAT_SPEC_2005

Revision 0

Summary of Revision

First Issue: December 2023

Document No.: SIAS_NAT_SPEC_2005

The following changes have been made in these revisions:

Rev	Description	Author	Date
0	Initial Release	Wing Lau	Feb 2024

Document Name: Fuel Pump Inverter for Class 44D Diesel Locomotive	Doc. No.: SIAS_NAT_SPEC_2005
Classification: Technical Specification Document	Revision: 0
Date: February 2024	Page 2 of 14

Symbols and Abbreviations

TE	Transnet Engineering
TFR	Transnet Freight Rail
GPM	Gallons per Minute
COTS	Commercial Off the Shelf

Document Name: Fuel Pump Inverter for Class 44D Diesel Locomotive	Doc. No.: SIAS_NAT_SPEC_2005
Classification: Technical Specification Document	Revision: 0
Date: February 2024	Page 3 of 14

TABLE OF CONTENTS

1. Background and Introduction	5
2. Document Scope	5
3. Response to Technical Specification	5
3.1. General	5
3.2. Bidder’s Technical Response.....	5
3.3. Alternatives Offered.....	6
3.4. Quotation Requirements	6
4. Scope of Goods and Services	7
4.1. General	7
5. Technical Specification	8
5.1. General	8
5.2. Environment Requirement.....	8
5.3. Operating Requirement.....	9
6. Constraints	10
7. Clarification	10
8. Type Test (FAI – First article Inspection)	10
9. Static and Dynamic Testing	10
10. In-service Evaluation	11
11. Data Pack and training	11
12. Maintenance Support	11
13. Project Timelines	11
14. Quality Assurance	12
15. Warranty	12
16. Standards Adherence	13

Document Name: Fuel Pump Inverter for Class 44D Diesel Locomotive	Doc. No.: SIAS_NAT_SPEC_2005
Classification: Technical Specification Document	Revision: 0
Date: February 2024	Page 4 of 14

1. BACKGROUND AND INTRODUCTION

The fuel pump on the class 44D delivers fuel from the fuel tank to the engine on the locomotive. The fuel pumps deliver fuel at a rate of 12 gallons per minute (GPM) for the class 44D locomotive at a pressure of 120 psi. The existing fuel pump uses a three-phase motor supplied with a three-phase inverter.

The purpose of this document is to provide the scope of work to the successful bidder which will provide an end-to-end solution of an alternative inverter for the fuel pump for the class 44D locomotive.

Due to time pressure a COTS solution that allows for the waiver, or shortening, of type testing and/or in-service tests (see section 10) is likely to be scored higher due to shorter project completion times.

2. DOCUMENT SCOPE

- 2.1. This Technical Specification is for the supply of an inverter for the fuel pumps of the class 44D locomotive.
- 2.2. The specification states the minimum requirements relating to the required service of supplying an inverter for the fuel pump(s) for the class 44D locomotive, and in no way absolves the supplier from additional duties of ensuring the inverter is suitable for the fuel pump.
- 2.3. For clarity, when used in the context of this document the entities listed below shall have the following meanings:
 - 2.3.1. Fuel Pump – Refers to the fuel pump for the class 44D locomotive.
 - 2.3.2. Inverter – Refers to the inverter for the fuel pump for the class 44D locomotive.
 - 2.3.3. Respondent – the person/organisation tendering along with others for the supply of the Goods/Services required under this tender or procurement process.
 - 2.3.4. Successful Bidder – the person/organisation who after submitting the tender response, has successfully passed evaluation and has been awarded the business, thereafter, referred to as the Supplier.

3. RESPONSE TO TECHNICAL SPECIFICATION

3.1. General

The Respondent must adhere to all the requirements included in this document. Failure to adhere to these requirements may, subject to the decision of the adjudication panel, result in the disqualification of the Respondent's submission.

Transnet reserves the right to disqualify any Respondent should its submission not adhere to all the requirements specified in this document.

3.2. Bidder's Technical Response

- 3.2.1. Respondents shall provide a clause-by-clause response to this Technical Specification. Failure to comply with this requirement may result in the disqualification of a Respondent.
- 3.2.2. The responses should therefore contain a clause-by-clause response for each clause in this document, containing at least one of the following answers:
 - FULLY COMPLIANT: When the bidder complies completely with the clause.
 - PARTIAL COMPLIANT: In case of partial compliance of the clause by the bidder.

Document Name: Fuel Pump Inverter for Class 44D Diesel Locomotive	Doc. No.: SIAS_NAT_SPEC_2005
Classification: Technical Specification Document	Revision: 0
Date: February 2024	Page 5 of 14

- NOT COMPLIANT: To state that the clause is not met currently and not an option at all.
- 3.2.3. The Respondents must supply an outline proposal of the design, and/or datasheets along with corresponding test results if an existing unit is quoted. This includes comprehensive information on performance and efficiency.
- 3.2.4. Respondents shall provide drawings, diagrams, and additional literature to clearly describe the operation of the proposed system and highlight any noteworthy features.
- 3.2.5. Commercial Off-The-Shelf (COTS) unit that is already in use for railway locomotive system application shall be preferred. In all instances the following information shall be furnished:
- Type test report
 - All relevant technical information (datasheet, previous application used, etc.)
 - Provide sample(s) for viewing, static testing, and test fitting.
- 3.2.6. The respondent shall attend a compulsory tender briefing, prior to tender submission, to outline the scope of work, solution, and product that the successful bidder will provide. This tender briefing will provide a platform for bidders to request or ask any questions with regards to this specification.

Table 1: Technical Documentation Checklist

Information Description	Content	Bidder Checklist
Cover letter	Contains information on: - Warranty	
Detailed Technical Offering	Evidence for the responses given in Section 4 - 15 . (Please be very detailed in the information provided)	
List of Documents Supplied for tender	List of technical documents, data sheets and other documents supplied as part of the offering.	
Previous Experience information	- Contact information of relevant reference where a similar type product was supplied, - List of relevant projects and detail, - Company brochure, - OEM authorization letters.	
Technical Documentation	Filled in, signed and stamped Technical Specification Document.	

3.3. Alternatives Offered

- 3.3.1. In addition to offers which, in the first instance, comply with the requirements set forth in this Specification, Respondents may also offer, as alternatives, variations of detail that they consider might be advantageous and acceptable to TE.
- 3.3.2. The respondent may also offer additions to the scope, either being requested or of their own accord. The final decision on the additions rests with TE.

3.4. Quotation Requirements

- 3.4.1. TE requires that the price breakdown be made available in at least the following detail:

Document Name: Fuel Pump Inverter for Class 44D Diesel Locomotive	Doc. No.: SIAS_NAT_SPEC_2005
Classification: Technical Specification Document	Revision: 0
Date: February 2024	Page 6 of 14

- COTS inverter for fuel pump (if applicable).
- Prototyping or development cost (if applicable).
- Prototype inverter for fuel pump (if applicable).
- Pre-production inverter for fuel pump (if applicable).

3.4.2. The quantities for the prototype and pre-production unit are as follow:

	Capacitor Type	Qty
Prototype	Class 44D inverter for fuel pump	1
Pre-production	Class 44D inverter for fuel pump	3

4. SCOPE OF GOODS AND SERVICES

4.1. General

- 4.1.1. The successful bidder shall supply the fuel pump inverter for the class 44D locomotive.
- 4.1.2. This Technical Specification is for the development, or supply of a COTS solutions, of a fuel pump inverter, as per section 5, for the existing diesel fuel pump for the class 44D locomotive.
- 4.1.3. The successful bidder will be given an opportunity to develop, or supply, initial fuel pump inverters (prototype units) for the class 44D locomotive. The supplied initial inverters will undergo comprehensive testing. After testing, the Supplier will be given the opportunity to rectify any identified deficiencies in the supplied inverter. Additional inverters, with the identified deficiencies corrected (pre-production units), will then be used for further in-service evaluation. Failure to meet the expectation of this technical specification, as well as fit for purpose use, will result in discontinuation of business with the successful bidder regarding the supply of such goods and services.
- 4.1.4. The prototype units will undergo a dummy test fit, and type testing (as per section 8)
- 4.1.5. Only upon acceptance of the prototype units shall further approval be given to continue to the development, or supply, of pre-production units.
- 4.1.6. The fuel pump inverters will undergo an in-service evaluation, as per section 9, for each phase of development – prototyping, and pre-production unit.
- 4.1.7. The successful bidder shall provide the type test, or service proven, report(s) for the supplied fuel pump inverters as per section 8. Only once the type test report(s) or service proven report(s) are satisfactory shall the prototype fuel pump inverter units be approved to be fitted in the locomotive for in-service evaluation.
- 4.1.8. The successful bidder shall collaborate with Transnet for the development, installation, integration, and in-service evaluation on the locomotive.
- 4.1.9. The fuel pump inverters supplied by the successful bidder shall undergo in-service evaluation (as per section 10) before further approval will be made for further purchasing.
- 4.1.10. The respondent shall respond to the following table in the right hand most column, with **FULLY COMPLIANT**, **PARTIALLY COMPLIANT**, or **NOT COMPLIANT**, with respect to compliance with the requirement.

Document Name: Fuel Pump Inverter for Class 44D Diesel Locomotive	Doc. No.: SIAS_NAT_SPEC_2005
Classification: Technical Specification Document	Revision: 0
Date: February 2024	Page 7 of 14

Note: Scope of Goods and Service is mandatory. A respondent will be disqualified if the answer “Not Compliant” (i.e. response No/blank) to any point in the table below.

#	Scope of Goods and Service Required		Response (FULLY COMPLIANT/ PARTIALLY COMPLIANT/ NOT COMPLIANT)
D.1	Supply	Prototype and provide fuel pump inverter solution for class 44D locomotive as per section 5.	
D.2	Delivery	Delivery of fuel pump inverters as mentioned to site (including all freight forwarding and custom cost): - Koedoespoort Depot, - Cnr. Lynette Street and Koedoespoort Rd, - Koedoespoort, - Pretoria - Gauteng - 0186	
D.3	Documentation of Supplied Equipment	Technical Data Sheet	
D.4		Type Test report or service proven report	
D.5		Maintenance Manuals, and Installation Manuals	
D.6	Training	Training to be provided for installation and maintenance and service.	
D.7	Installation, Testing and Commissioning	Support during the in-service evaluation, testing, and commission of the fuel pumps inverters for the locomotive.	

5. TECHNICAL SPECIFICATION

The following technical specification shows the technical information to the item mentioned.

5.1. General

- 5.1.1. The respondent shall supply supporting document that can demonstrate the ability to supply according to these requirements.
- 5.1.2. The successful bidder shall be responsible for the installation of the prototype and preproduction units on to the locomotive.

5.2. Environment Requirement

The equipment shall have the following environmental operating requirement:

- 5.2.1. Shock and Vibration resistance: IEC61373:2010
- 5.2.2. Operating Altitude: 2200m
- 5.2.3. Ambient Temperature: -40°C to +85°C
- 5.2.4. Humidity: Yearly average humidity: ≤ 75 %, Relative humidity: ≤ 95 %

Document Name: Fuel Pump Inverter for Class 44D Diesel Locomotive	Doc. No.: SIAS_NAT_SPEC_2005
Classification: Technical Specification Document	Revision: 0
Date: February 2024	Page 8 of 14

- 5.2.5. IP protection: at least IP66
- 5.2.6. Oil and Diesel Fuel Resistance

5.3. Operating Requirement

- 5.3.1 The inverter shall be able to drive and power the class 44D fuel pump.
- 5.3.2 The supplied inverter shall have similar or better performance than the existing fuel pump inverters of the 44D class locomotive.
- 5.3.3 It is the successful bidder’s responsibility to characterise the fuel pumps, for the class 44D, to drive them correctly to obtain the necessary performance from the fuel pumps.
- 5.3.4 Nominal input voltage of 74VDC shall be used to power the inverter.
- 5.3.5 The inverter shall be able to operate with an input voltage range between 40 VDC to 104 VDC. Bidder to provide input capability voltage range for the inverter.
- 5.3.6 The inverter shall be capable of driving the fuel pump of the class 44D locomotive to be able to provide a flow rate of 12 GPM at a pressure of 120 psi.
- 5.3.7 The inverter will have the following V/Hz characteristics curve to control the fuel pump.

Supply Voltage (VDC)	Output Voltage (Pk-Pk)	Output Frequency (Hz)
20	0	0
23	48	19.5
30	62	25.6
40	82	35.1
50	104	43.8
60	124	51.8
70	145.6	59.3
80	168	66.2
90	188	72.6

Note: These values are indicative from tests conducted by Transnet, however, it is the successful bidder’s responsibility to supply an inverter to drive the fuel pump to provide the performance required in 5.3.6.

- 5.3.8 The inverter has an input current of 20A, with circuit breaker tripping at 25A.
- 5.3.9 The inverter shall have the following protection: overtemperature, over current, over voltage and stall protection.
- 5.3.10 The inverter shall have soft starting capability.
- 5.3.11 The inverter shall be able to provide sufficient power, without damaging the fuel pump, to drive the fuel pump with a back pressure of 120 psi.
- 5.3.12 The inverter shall be able to withstand a voltage drop of up to 35 VDC of at least 15s during cranking of the engine at start-up.

Document Name: Fuel Pump Inverter for Class 44D Diesel Locomotive	Doc. No.: SIAS_NAT_SPEC_2005
Classification: Technical Specification Document	Revision: 0
Date: February 2024	Page 9 of 14

5.3.13 The inverter shall have EMI protection and within EMI levels as according to standards mentioned in section 16.

5.3.14 Sine-wave inverters may be given preference.

5.3.15 Inverter with vector control (e.g. Field oriented control) will be preferred.

6. CONSTRAINTS

- 6.1. The fuel pump inverters shall interface with the original fuel pumps on the class 44D.
- 6.2. If the inverters must be relocated, the inverter must be capable of providing sufficient voltage to compensate for the voltage drop.
- 6.3. It is preferred to install the inverter in the same position as the original inverter for the fuel pump, utilizing the original mounting holes and space as the original.
- 6.4. Should reuse of the original mounting holes and placement of the inverter is not possible, the successful bidder will work with Transnet engineers to identify the alternative placement.
- 6.5. Additional mounting brackets and interfaces required for the inverter to drive the fuel pump will be part of the inverter solution for the fuel pump along with any accessories accompanying the inverter.

7. CLARIFICATION

- 7.1. The respondent may contact TE at any time through the relevant procurement personnel should any void exist in this specification or there be any uncertainty as a result any contradictory statement(s) within this specification.
- 7.2. All clarification questions directed to TE shall be made in writing through the official channels as detailed in the supporting documents of this procurement event.

8. TYPE TEST (FAI – FIRST ARTICLE INSPECTION)

- 8.1. The respondent must provide a list of standards and applicable clauses that they adhere to other than those mentioned in this specification.
- 8.2. The successful bidder will make available the type test procedure for review and approval, as well as the witnessing of the type tests.
- 8.3. The successful bidder shall conduct and provide a type test report for the supplied fuel pump inverters for review and approval.
- 8.4. The respondent may provide an existing type test report for the fuel pump inverters if an existing product is available.
- 8.5. Only upon approval of the type test report shall the fuel pump inverters be approved to undergo further testing in the locomotive for static and dynamic tests.

9. STATIC AND DYNAMIC TESTING

- 9.1. Static and dynamic testing shall be conducted to determine the inverters capability of driving the fuel pump to deliver the necessary fuel flow rate and pressure to the engine.

Document Name: Fuel Pump Inverter for Class 44D Diesel Locomotive	Doc. No.: SIAS_NAT_SPEC_2005
Classification: Technical Specification Document	Revision: 0
Date: February 2024	Page 10 of 14

- 9.2. Static and dynamic testing procedure and results shall be discussed, reviewed, and approved with the successful bidder during the prototyping stage.
- 9.3. Only upon approval of the static and dynamic tests shall the fuel pump inverters be approved to undergo further in-service evaluation testing.

10. IN-SERVICE EVALUATION

- 10.1. The successful bidder shall arrange with Transnet engineers for the installation of the mention fuel pump inverters, as per section 3.4.2, for in-service evaluation.
- 10.2. The in-service evaluation testing period, of the installed fuel pump inverters, shall be three (3) to six (6) months for the prototype units, and three (3) months for the pre-production units. TE will monitor its in-service performance and follow-up on any possible failures.
- 10.3. The in-service testing period may be shortened or negated if:
 - 10.3.1 The part supplied by the supplier is the same as the original and is certified to be used on the locomotive.
 - 10.3.2 When Transnet Engineering’s Chief Maintenance Engineer or Fleet Maintenance Owner accepts the product at an earlier stage for operational or other reasons.
- 10.4 The part shall only be granted approval, for fit for use purpose, once the in-service evaluation testing is successful.

11. DATA PACK AND TRAINING

- 11.1. The successful bidder will provide the maintenance pack for the fuel pump inverters. The maintenance pack will include the following: datasheet of the fuel pump inverters, maintenance manuals, replacement parts, installation manuals, and maintenance schedule (if applicable)
- 11.2. The successful bidder will provide training on how to install and maintain the fuel pump inverters.

12. MAINTENANCE SUPPORT

- 12.1. The successful bidder will provide maintenance support and spare parts for at minimum period of 10 years.
- 12.2. In the event of repetitive similar failures, the successful supplier shall investigate and support with an updated solution.

13. PROJECT TIMELINES

- 13.1. The Respondent shall include the dates which the Respondent will be able to deliver (for both prototype and pre-production), together with the activities (and accommodating dates).
- 13.2. The following table shall be responded to in the right hand most column, with a YES or NO, with respect to compliance of the requirement.

Note: Scope of Delivery Period for the prototype is mandatory. A respondent will be disqualified if the table is not completed (i.e., blank), indicating the possible delivery date of the prototype. The respondent with the shortest delivery period will receive a higher evaluation score.

Document Name: Fuel Pump Inverter for Class 44D Diesel Locomotive	Doc. No.: SIAS_NAT_SPEC_2005
Classification: Technical Specification Document	Revision: 0
Date: February 2024	Page 11 of 14

#	Prototype Delivery	Response [YES/NO]
D.1	1 Months	
D.2	<3 Months	
D.3	<6 Months	
D.4	Other: _____ (Supplier to stipulate the delivery period of the prototype, please provide reasons of not meeting <6 months delivery date)	

13.3. The Respondent is made aware that failure to reach the stated delivery date in 13.2 above may result in disqualification of this tender.

14. QUALITY ASSURANCE

The Supplier is to provide certificate of compliance for quality assurance.

15. Warranty

The following table shall be responded to in the right hand most column, with a YES or NO, with respect to compliance with the requirement.

Note: Scope of Warranty Period is mandatory. A respondent will be disqualified if the table is not completed (i.e., blank), indicating the warranty period to be provided. The respondent with a longer warranty period will receive a higher evaluation score.

#	Warranty Period	Response [YES/NO]
W.1	3 Months	
W.2	6 Months	
W.3	12 Months	
W.4	Other: _____ (Supplier to stipulate the warranty period they will provide)	

Document Name: Fuel Pump Inverter for Class 44D Diesel Locomotive	Doc. No.: SIAS_NAT_SPEC_2005
Classification: Technical Specification Document	Revision: 0
Date: February 2024	Page 12 of 14

16. STANDARDS ADHERENCE

The respondent shall adhere to the standards that are identified in this document, should the respondent be the successful bidder. The respondent must also provide a list of standards and applicable clauses that they have adhered to, other than those mentioned in this specification document, which address the requirements of the requested standards. The following tables a comprehensive list of SANS, IEC, EB and Transnet standards that the solution should adhere to. Bidders are to provide additional standards which the solution complies with, other than the list mentioned below.

S1	SANS Standards	COMPLY [YES/NO]
S1.1	SANS 10111 (Latest) Engineering Drawing	
S1.2	SANS 60529:2013 Degrees of protection provided by enclosures (IP Code)	
S2	EN Standards	COMPLY [YES/NO]
S2.1	EN 50121-3-2: Railway Applications - Electromagnetic compatibility, Rolling stock apparatus	
S2.2	EN 61373:2010 Railway applications – Rollingstock equipment – Shock and vibration tests.	
S3	Transnet Standards/Drawings	COMPLY [YES/NO]
S3.1	BBB2274 (Latest): Electromagnetic compatibility requirements for rolling stock operating on TFR railway lines	
S4	IEC Standards	COMPLY [YES/NO]
S4.1	IEC 60068-1:2013 Environmental testing – Part 1: General and guidance	
S4.2	IEC 60068-2-1:2007 Environmental testing – Part 2-1: Tests – Test A: Cold	
S4.3	IEC 60068-2-2:2007 Environmental testing – Part 2-2: Tests – Test B: Dry heat	
S4.4	IEC 61373:2010 Railway applications – Rolling stock equipment – Shock and vibration tests	
S4.5	IEC 50155 Railway applications - Electronic equipment used on rolling stock	
S5	ISO Standards	COMPLY [YES/NO]
S5.1	ISO 9001:2015 Quality management systems — Requirements	

Document Name: Fuel Pump Inverter for Class 44D Diesel Locomotive	Doc. No.: SIAS_NAT_SPEC_2005
Classification: Technical Specification Document	Revision: 0
Date: February 2024	Page 13 of 14

DOCUMENT AUTHORITIES

COMPLIED BY	
Wing Lau	Signed: 
Engineer TE: System Integration, Assurance and Support	Date: 2024/02/12

REVIEWED BY	
Philip Botha	Signed: 
Engineer TE: Research and Development	Date: 2024/02/13

APROVED BY	
Otsile Magae	Signed: 
Chief Engineer TE: System Integration, Assurance and Support	Date: 2024/02/12

Document Name: Fuel Pump Inverter for Class 44D Diesel Locomotive	Doc. No.: SIAS_NAT_SPEC_2005
Classification: Technical Specification Document	Revision: 0
Date: February 2024	Page 14 of 14