

Item 2:

**Mechanical
Grease Reservoir, 9 Kg
capacity fitted with Quick
Flow Non return filler Valve
and Snap Lock Cap.
Colour – Grey.
Depth gauge for quick and
easy visual indication.
Supplied with Anti-Theft
bracket to protect against
vandalism.**

Specifications

**Capacity 9 Kg of grease
Depth Gauge –
50 mm = Full
200 mm = Empty
Equipped with Quick Coupler for
easy refilling.
Snap Lock Cap ensures there is no
ingress of moisture or debris into
the reservoir.
Supplied with Piston Lock Spider to
be used during major maintenance.
Does not attach to the rail so no
additional engineering or drilling is
required.
Can be installed between the
sleepers and rails for added
protection.**

Item 3

**Pair EasiBlade- Steel 60cm, 16
Port rail applicator with
central Rail clamp and Blade
Pivot Bracket (Suits 16 mm
bore hose).**

Specification

**Steel EasiBlade that does not
require additional engineering or
welding during installation.
Does not contain any gaskets or Orings.
Consists only of 2 metal blade
surfaces and metal membrane
ensuring that no leaks are
encountered.
No rail drilling required during
installation**

Item 4

**Dual Pump for
Mechanical Rail
Lubricator, 110 mm Pump
Body Dual Plunger for 16 mm
hose.**

Specification

**Adjustable plunger heights for
correct pressure.
Recessed Allen screws to control
grease output with independent
locking nut.**