



| | | | | | | | |
|---|---|--|------------|--------------------|------------|---------|--------------------|
| SAP MATERIAL No.: | | 0175465 | | | | | |
| SHORT DESCRIPTION: | | PLATFORM,EQUIP H-POLE 2600mm LG. D3020 | | | | | |
| TECH. DESCRIPTION: | | | | | | | |
| H-POLE MOUNTED EQUIPMENT PLATFORM * | | | | | | | |
| MATERIAL GRADE S355JR/350WA STEEL * | | | | | | | |
| HOT DIPPED GALVANISED * | | | | | | | |
| CONSISTING OF : | | | | | | | |
| 120x55x13x2600 LONG CHANNELS (2 OFF), | | | | | | | |
| M20x450 THREADED RODS (D-DT-3015) (4 OFF) AND 12x75 LONG | | | | | | | |
| COACH SCREWS (D-DT-3090) (4 OFF) * ALL OF THE ABOVE PACKAGED | | | | | | | |
| AS A UNIT. ALL PACKAGING IS TO BE SUITABLE FOR STORAGE OUTDOORS * | | | | | | | |
| TOLERANCES ON DIMENSIONS ± 2mm AND ON DRILLING CENTRES ± 1mm * | | | | | | | |
| ESKOM DRAWING No. D-DT-3020 * | | | | | | | |
| | | | | | | | |
| ITEM | | :- PLATFORM,EQUIP H-POLE 2600mm LG. | | | | | |
| MATERIAL SPECIFICATION | | :- EN 10025-2 / SANS 1431 | | | | | |
| CORROSION SPECIFICATION | | :- SANS 121 | | | | | |
| STANDARD SPECIFICATION | | :- | | | | | |
| ESKOM SPECIFICATION | | :- D-DT-3020 | | | | | |
| TEST & CERTIFICATION REQUIREMENTS :- | | | | | | | |
| INSPECTION | | Yes | No | ESKOM RELEASE NOTE | | Yes | No |
| IDENTIFICATION:- INDELIBLE MANUFACTURES TRADEMARK & PART No. ON ALL ITEMS | | | | | | | |
| 10 | OUTER SLOTS INCREASED BY 50mm ON TOP OF CHANNEL | | | P.A.T. | B. HILL | B. HILL | 08.08.2012 |
| 9 | MATERIAL AND SPECS CHANGED | | | P.A.T. | S. MASHABA | B. HILL | 10.03.2010 |
| 8 | OUTER SLOTS IN FRONT VIEW EXTENDED BY 100mm | | | P.A.V. | B. HILL | B. HILL | 03.07.2006 |
| REV | REVISION DESCRIPTION | | | BY | CHKD | AUTH | DATE REF. DRAWINGS |
| AUTH: | P.CROWDY | DATE: | 14.07.1995 | SCALE NTS | | SAP No: | |
| CHKD: | J.SWAN | DATE: | 14.07.1995 | CAD REF: | | 0175465 | |
| | | | | SERIES 3000 | | | |
| DRAWN: | P.A. VERMAAK | DATE: | 13.01.1995 | FILE No: | | SET | |
| | | | | 3020 | | SHEET | |
| | | | | D-DT-3020 | | REV | |
| | | | | | | 1 1 10 | |