

SPECIFICATION FOR SAFETY BOOTS RIGGING TEAM



- MANUFACTURED WITH A DOUBLE LAYER OF LEATHER (2.2MM FULL GRAIN LEATHER, LINED WITH 1.6MM CALF LEATHER)
- DOUBLE LAYER OF LEATHER AIDS IN THE BOOTS WATER RESISTANT PROPERTIES (NOT WATERPROOF)
- ANKLE PADDING FOR EXCELLENT SUPPORT, COMFORT AND PROTECTION
- THERMOPLASTIC TOE PUFF AND A HEEL STIFFENER FOR EXTRA SUPPORT
- A STEEL SHANK BETWEEN THE INSOLE BOARD AND SOLE OFFERS EXTRA SUPPORT AND STABILITY
- INSOLE BOARD IS SECURED TO THE UPPER WITH A DOUBLE STITCHED 2.2MM BRAIDED NYLON CORD
- SOLE IS MADE FROM A GENUINE RUBBER
- CAN BE RESOLED
-

SPECIFICATION FOR BOOTS CONSTRUCTION TEAM

- Full Grain Crazy Horse Leather Upper
- Padded Collar
- Padded Tongue
- Full Moisture-wicking Lining
- New improved moulded, padded, removable sockliner
- Steel Shank
- 200J Impact Resistant Steel Toe Cap
- Dual-density PU Sole
- Slip Resistant
- Acid & Oil Resistant
- Anti-static
- EN ISO 20345:S1



Balaclava for protection against cold and wind

BALACLAVA protects the head, the face and the neck on cold, windy days. The design, specific to each zone, optimizes thermal insulation and regulates humidity. The seamless fitted design and multiple side vents make it comfortable to wear under a helmet, without getting in the way.

Description

- Optimal protection for the head, face and neck, for cold and extreme environments:
 - central section in Windstopper® offers thermal insulation against the cold and wind for the face
 - lower section in fleece protects the neck from the cold
- Designed for wearing under a helmet:
 - upper section is breathable, to limit perspiration inside the helmet
 - seamless, fitted design for optimal comfort with the helmet
- Does not get in user's way during everyday work:
 - lateral slots in front of the ears ensure hearing is not impeded
 - holes around the nose and in front of the mouth ensure good breathing and limit the formation of damp areas
- Machine washable up to 30° C
- Available in two size
- Weight: 60 g
- Material(s): polyester, spandex

References

References	A016CA00	A016CA01
Color(s)	black/yellow	black/yellow
Size	M/L	L/XL
Head circumference	56-59 cm	59-63 cm
Guarantee	3 years	3 years
Inner Pack Count	1	1



DESCRIPTION

The Petzl Vertex helmet is a comfortable safety helmet for work at height.

Features:

- Comfortable 6-point suspension system
- Adjustable chinstrap
- Outer shell protects against electrical hazards, molten metal splash and flames
- Compatible with many accessories including hearing protection, visors, headlamps etc.

Specifications:

Head circumference: 53 – 63 cm

Weight: 490 g

Certification: CE, EN 397, EN 12492 (1), EN 50365, ANSI Z89.1 Type I Class E, EAC, AS/NZS 1801

HARNESS

Comfortable harness for fall arrest, work positioning, and suspension

The AVAO BOD FAST fall-arrest, work positioning and suspension harness is designed for greater comfort in all situations. The wide, semi-rigid waistbelt and leg loops provide excellent support. Its lightweight, breathable construction maximizes air flow. The shoulder straps have a system for stowing the fall-arrest lanyard connectors and keeping them within reach. The

DOUBLEBACK self-locking buckles at the rear of the harness, between the waistbelt and the leg loops, allow for a shorter adjustment when the dorsal attachment point is used. The harness also makes it easier to carry and organize work tools, with multiple gear loops and slots for attaching CARITool tool holders and TOOLBAG tool pouches. The harness is fastened with a SCREW-LOCK manual locking carabiner and is certified to European and Russian standards. The AVAO BOD FAST features leg loops with FAST LT buckles.

Description

- Comfortable throughout the workday:
 - Wide, semi-rigid waistbelt and leg loops for excellent support and lightweight, breathable construction to maximize air flow
 - Padded shoulder straps are widely spaced to reduce neck chafing and help distribute the load over the shoulders when the waistbelt is loaded
- Easy to adjust:
 - Waistbelt and shoulder straps equipped with self-locking DOUBLEBACK buckles for quick and easy adjustment
 - Leg loops equipped with FAST LT buckles for quick and easy fastening and unfastening without loss of adjustment, even while wearing gloves
 - Stowing system for the MGO connectors on fall-arrest lanyards, on each shoulder strap, allows the user to be unhindered by the lanyard and keep the connectors within reach; in the event of a fall, the system releases the MGO connectors and allows the absorber to be deployed
 - Side attachment points can be folded down to prevent accidental snagging when not in use
 - DOUBLEBACK self-locking buckles at the rear of the harness, between the waistbelt and the leg loops, make it possible to adjust for use on the dorsal attachment point; in the event of a fall on this point, a shorter adjustment allows the weight to be taken up on the leg loops so that the user may remain more comfortably suspended while awaiting rescue
- Easy to carry and organize tools:
 - Six pre-shaped equipment loops with protective sheath
 - Two slots for CARITool tool holder
 - Four slots for TOOLBAG tool pouch

Specifications

- Ventral attachment point: Attachment for a descender or a positioning lanyard for use in single mode
- Lateral attachment points: Attachment for a positioning lanyard for use in double mode
- Sternal attachment point: Fall-arrest system attachment
- Dorsal attachment point: Fall-arrest system attachment
- Rear attachment point on the waistbelt: Restraint lanyard attachment
- Certification(s): CE EN 361, CE EN 358, CE EN 813, EAC
- Material(s): Nylon, polyester, aluminum, steel

References

References	C071BA00	C071BA01	C071BA02	C071BA03	C071BA04	C071BA05
Color(s)	Black/Yellow	Black/Yellow	Black/Yellow	Black	Black	Black
Size	0	1	2	0	1	2
Waist belt	65-80 cm	70-93 cm	83-120 cm	65-80 cm	70-93 cm	83-120 cm
Leg loops	44-59 cm	47-62 cm	50-65 cm	44-59 cm	47-62 cm	50-65 cm
Stature	160-180 cm	165-185 cm	175-200 cm	160-180 cm	165-185 cm	175-200 cm
Weight	2000 g	2045 g	2125 g	2000 g	2045 g	2125 g
Guarantee	3 years	3 years	3 years	3 years	3 years	3 years
Inner Pack Count	1	1	1	1	1	