

	The Supply and Delivery Air- conditioning units and Electrical Appliances for Nuclear Operating Unit (NOU) on an “as and when” required basis for a period of five (5) years.	User Requirement Specifications
---	--	--

Title: **The Supply and Delivery Air- conditioning units and Electrical Appliances for Nuclear Operating Unit (NOU) on an “as and when” required basis for a period of five (5) years.**

Area of Applicability: **Koeberg Power Nuclear Station**

Functional Area: **Materials Management**

Revision: **1**

Total Pages: **10**

Compiled by

.....


Name: H Van Jaarsveld

Position: Snr MRP

Date: 30 August 2024

Reviewed by

.....


Name: R Hendricks

Position: Snr Advisor

Date: 30 August 2024

Authorised by

.....


Name: J Booysen

Position: MM Manager

Date: 30 August 2024

CONTENTS

Page

1. SCOPE OF WORK 3

2. DESCRIPTION OF THE SERVICES 3

3. ABBREVIATIONS 10

5. DELIVERY TIMES 10

6. METHOD..... 10

1. SCOPE OF WORK

The Supply and Delivery of various Air-Conditioning Units and Electrical Appliances for the Nuclear Operating Unit.

2. DESCRIPTION OF THE SERVICES

The Supply and Delivery of various Air-Conditioning Units for the Nuclear Operating Unit.

The following is a categorized list of items.

Batch 1: Air-Conditioning Units

<u>Material nr.</u>	<u>Description</u>	<u>Long Description</u>	<u>Estimated 5yr. quantity</u>
220839	UNIT:HIGH WALL SPLIT INVERTER	C.O.C; 0040/88Q; Q4:NSF:NC:NEV; UNIT; MNF: ALLIANCE; TYPE: HIGH WALL SPLIT INVERTER; MODEL NO: QHG009DS; APPLICATION: AIR CONDITIONING; WD 725 X HT 385 X DP 460 MM; POWER SOURCE: 220 -240 V; CAPACITY RATING: 9000 BTU/H; MOUNTING TYPE: HIGH WALL; REFRIGERANT: R410 A; FUNCT.LOC: 6 HFF001-004 AE;0 DWH 111-127AE; 6 DWI 123,124AE, 6 DWE 603,604AU; END DETAIL DESCRIPTION: JNF 2006/04/07; CLC 2012/10/17; ML 2020/01/22; ML 2020/03/06; YA 2023/05/29; ND 2023/07/10; YA 2024/02/08	85
588210	AIRCON:WALL UNIT;6000 W;R-410A	C.O.C; DATA SHEET; 0001/87C; Q4:NSF:NC:NEV; SEE EQUIVALENCE M012/14E; SEE OLD MATERIALNO.0040010; WALL AIR CONDITIONING UNIT; MFR:ALLIANCE; MODEL: FOUWH21/A; TYPE: WALL AIR CONDITIONING UNIT; CAPACITY RATING: 6000 W; REFRIGERANT: R-410A; WIDTH:660MM; HEIGHT:428MM; DEPTH:770MM; PHASE:SINGLE; VOLTAGE:220-240V; HEATING CAPACITY: 5500 W; M/MAN:022 VOL 3; FUNCT.LOC:1/2DVM 001,002AE; ***** END DETAIL DESCRIPTION *****; JNF 2014/06/10; JNF 2014/08/20; JNF 2014/12/17; ML 2018/01/17; ML 2021/03/29; ML 2022/06/20	10
640280	AIRCON:UNDER CEILING FIXED;36000 BTU	C.O.C;004/88; Q4:MSF:NC:NEV; MNF: ALLIANCE; TYPE: UNDERCEILING FIXED; CAPACITY RATING: 36000 BTU; FUNC LOC: 6 SSM 001,002 EV, 6 DWD 003, 005, 006 EV; END DETAIL DESCRIPTION: ML 2017/09/06; YA 2024/02/08	15
669604	AIRCON:INVERTER UNDERCEILING SPLIT UNIT	C.O.C; 0200/87Q; Q4:NSF:NC:NEV; AIR CONDITIONER; MNF: CARRIER-METRACLARK; P/NO: QZL060DT; YPE: INVERTER UNDERCEILING SPLIT UNIT; CAPACITY RATING: 60000 BTU; MOUNTING TYPE: WALL; REFRIGERANT: R410A; CONDENSER COOLING TYPE: AIR; POWER SOURCE: 380 V 3 PH 50 HZ; FUNC LOC: 0 DVB 003, 004 EV; 0DVB003CS; 0DVB004CS	5

The Supply and Delivery Air- conditioning units and Electrical Appliances for Nuclear Operating Unit (NOU) on an “as and when” required basis for a period of five (5) years.

Revision:

0

Page:

4 of 10

STM-107083	AIRCON:36 000 BTU;CEILING;R32;ROTARY	AIR CONDITIONER: TYPE: WALL MOUNTED AIR CONDITIONING UNIT; CAPACITY RATING: 36 000 BTU; MOUNTING TYPE: CEILING; REFRIGERANT: R32; COMPRESSOR UNIT TYPE: ROTARY; CONDENSER COOLING TYPE: AIR; POWER SOURCE: 220-240 V 50 HZ; DAIKIN PART NUMBER:FAA100A SKY AIR<LARGE<H/P<FAA<100 DIMENSIONS - UNIT - DEPTH X HEIGHT X WIDTH 240 X 340 X 1,200 MM SOUND PRESSURE LEVEL - COOLING - MEDIUM 45 DBA SOUND PRESSURE LEVEL - HEATING - MEDIUM 45 DBA POWER SUPPLY - FREQUENCY X PHASE X VOLTAGE 50 X 1~ X 220-240 HZ; SPECIFICATION CLASSIFICATION No.: 0002/93Q. SAFETY CLASS: NSF. QUALITY LEVEL: Q3. SEISMIC CLASS: NC. SAFETY LEVEL OF ORGANISATION: L3. ENVIRONMENTAL: NEV. SPEC No: DSG-312-085. IMPORTANCE: SR. CERTIFICATION REQUIRED: I.A.W. SPEC.	5
STM-169533	AIRCON:36 000 BTU;CEILING;R410A;AIR	ALLIANCE AQUA 36000BTU CEILING CASSETTE INVERTER SPLIT AIR-CON UNIT,R410A REFRIGERANT GAS,POWER SOURCE: 220-240V	5
STM-148202	AIRCON:AIR CONDITIONER MIDWALL SPLIT	AIR CONDITIONER: TYPE: AIR CONDITIONER MIDWALL SPLIT; CAPACITY RATING: 18000 BTU; MOUNTING TYPE: WALL; COMPRESSOR UNIT TYPE: INVERTER; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IFAPPLICABLE). AIR CONDITIONER: Y18l - York 18000Btu Inverter Midwall Split	15
STM-150965	AIRCON:AIR CONDITIONER;36000 BTU;CEILING	SUPPLY 1 X CARRIER WATER CHILLED CEILING MOUNTED CASSETTE UNIT WITH ALL THE ACCESSORIES - PART NO: 42GW300CQGAA; IT MUST INCLUDE: INFRARED RECEIVER WTC-IS - PART No:33WT4000061M REMOTE CONTROL IR - PART No: 33WT500035M-ERCD CASSETTE GRILL INFRARED WITH MANUAL LOUVERS-20X30X40 - PART No: 42GW9041	15
STM-116252	AIRCON:CEILING CASSETTE;22000	CARRIER WATER CHILLED CEILING MOUNTED CASSETTE UNIT WITH ALL THE ACCESSORIES - PART NO: 42GW300CQGAA; IT MUST INCLUDE: INFRARED RECEIVER WTC-IS - PART No:33WT4000061M REMOTE CONTROL IR - PART No: 33WT500035M-ERCD CASSETTE GRILL INFRARED WITH MANUAL LOUVERS-20X30X40 - PART No: 42GW9041	5
STM-117431	AIRCON:INDOOR UNIT;18000;WALL	AIR CONDITIONER: TYPE: INDOOR UNIT; CAPACITY RATING: 18000; MOUNTING TYPE: WALL; 18000 AC YORK UNIT	5
STM-117434	AIRCON:INDOOR UNIT;24000;WALL	AIR CONDITIONER: TYPE: INDOOR UNIT; CAPACITY RATING: 24000; MOUNTING TYPE: WALL; 24000 AC YORK UNIT	5

The Supply and Delivery Air- conditioning units and Electrical Appliances for Nuclear Operating Unit (NOU) on an “as and when” required basis for a period of five (5) years.

Revision:

0

Page:

5 of 10

STM-148165	AIRCON:INVERTER UNDERCEILING SPLIT UNIT	CARRIER 12000BTU INVERTER UNDERCEILING SPLIT UNIT REFRIGERANT:410A GAS;POWER SOURCE:220-240V;MANUF P/N:QHG012DS	5
STM-150818	AIRCON:INVERTER UNDERCEILING SPLIT UNIT	ALLIANCE AQUA 24000BTU MID-WALL INVERTER SPLIT AIR-CON UNIT,R410A REFRIGERANT GAS,POWER SOURCE - 220-240V AIR CONDITIONER: TYPE: MIDWALL SPLIT UNIT; CAPACITY RATING: 24000 BTU; MOUNTING TYPE: MID-WALL SPLIT AIR-CON; REFRIGERANT: 410A GAS; COMPRESSOR UNIT TYPE: INVERTER AIR-CON; CONDENSER COOLING TYPE: TURBO MODE, FOLLOW ME FUNCTION	5
STM-161996	AIRCON:MIDWALL SPLIT UNIT;12000 BTU;WALL	ALLIANCE AQUA 12000BTU MID-WALL INVERTER SPLIT AIR-CON UNIT,R410A REFRIGERANT GAS,POWER SOURCE - 220-240V	10
STM-111312	AIRCON:MIDWALL SPLIT UNIT;12000BTU	AIR CONDITIONER: TYPE: MIDWALL SPLIT UNIT; CAPACITY RATING: 12000BTU; GREE, 12000BTU MIDWALL SPLIT UNIT - HEATING AND COOLING	5
STM-162005	AIRCON:MIDWALL SPLIT UNIT;18000 BTU	ALLIANCE AQUA 18000BTU MID-WALL INVERTER SPLIT AIR-CON UNIT,R410A REFRIGERANT GAS,POWER SOURCE - 220-240V AIR CONDITIONER: TYPE: MIDWALL SPLIT UNIT; CAPACITY RATING: 18000 BTU; MOUNTING TYPE: MID-WALL SPLIT AIR-CON; REFRIGERANT: 410A GAS; COMPRESSOR UNIT TYPE: INVERTER AIR-CON; CONDENSER COOLING TYPE:TURBO MODE, FOLLOW ME FUNCTION	5
STM-162018	AIRCON:MIDWALL SPLIT UNIT;24000 BTU	ALLIANCE AQUA 24000BTU MID-WALL INVERTER SPLIT AIR-CON UNIT,R410A REFRIGERANT GAS,POWER SOURCE - 220-240V AIR CONDITIONER: TYPE: MIDWALL SPLIT UNIT; CAPACITY RATING: 24000 BTU; MOUNTING TYPE: MID-WALL SPLIT AIR-CON; REFRIGERANT: 410A GAS; COMPRESSOR UNIT TYPE: INVERTER AIR-CON; CONDENSER COOLING TYPE:TURBO MODE, FOLLOW ME FUNCTION	5
STM-151112	AIRCON:MIDWALL SPLIT UNIT;36000 BTU;WALL	ALLIANCE AQUA 36000BTU MID-WALL INVERTER SPLIT AIR-CON UNIT,R410A REFRIGERANT GAS,POWER SOURCE - 220-240V. AIR CONDITIONER: TYPE: MIDWALL SPLIT UNIT; CAPACITY RATING: 36000BTU; MOUNTING TYPE: MID-WALL SPLIT AIR-CON; REFRIGERANT: 410A GAS; COMPRESSOR UNIT TYPE: INVERTER AIR-CON; CONDENSER COOLING TYPE:TURBO MODE, FOLLOW ME FUNCTION	5
STM-170450	AIRCON:UNDER CEILING UNIT;12000 BTU	ALLIANCE AQUA 12000BTU UNDERCEILING INVERTER SPLIT AIR-CON UNIT,R410A REFRIGERANT GAS,POWER SOURCE - 220-240V	5
STM-170427	AIRCON:UNDER CEILING SPLIT UNIT;18000	ALLIANCE AQUA 18000BTU UNDERCEILING INVERTER SPLIT AIR-CON UNIT,R410A REFRIGERANT GAS,POWER SOURCE - 220-240V,	5
STM-170389	AIRCON:UNDER CEILING SPLIT UNIT;24000	ALLIANCE AQUA 24000 BTU MID-WALL INVERTER SPLIT AIR-CON UNIT,R410A REFRIGERANT GAS,POWER SOURCE - 220-240V	5
STM-170371	AIRCON:UNDERCEILING SPLIT UNIT;36000 BTU	ALLIANCE AQUA 36000BTU UNDERCEILING INVERTER SPLIT AIR-CON UNIT,R410A REFRIGERANT GAS,POWER SOURCE - 220-240V	15

Batch 2: Electrical Appliances

<u>Material nr.</u>	<u>Description</u>	<u>Long Description</u>	<u>Estimated 5yr. quantity</u>
STM-149721	KETTLE:15 LITRE URN;15 LITRE;240 V;2000	KETTLE: TYPE: 15 LITRE URN; SIZE: 15 LITRE; POTENTIAL: 240 V; MATERIAL: SILVER GERY; POWER: 2000 W; CURRENT: 0.2 A	15
STM-145399	KETTLE:CORDLESS;1.7 L;220 V;2000 W;10 A	KETTLE: TYPE: CORDLESS; SIZE: 1.7 L; POTENTIAL: 220 V; MATERIAL: STAINLESS STEEL; POWER: 2000 W; CURRENT: 10 A; BASE WITH 3-PIN PLUG	100
687732	KETTLE:ZIP HYDROBOIL;7.5 L;220 V;WHITE	KETTLE: TYPE: ZIP HYDROBOIL; SIZE: 7.5 L; POTENTIAL: 220 V; MATERIAL: WHITE; CURRENT: 0.2 A	25
STM-161844	OVEN MCRWAVE:1550 W 40L MICRPOWAVE;220	OVEN, MICROWAVE: HEATING METHOD: SAMSUNG 40 L MICROWAVE; POTENTIAL: 220 V; POWER DISSIPATION RATING: 1550 W; OPERATING CONTROL TYPE: TOUCH CONTROL; MOUNTING TYPE: FREE STANDING; LENGTH: 556 MM; WIDTH: 439 MM; HEIGHT: 313 MM; OEM P/N: 1550 W40L MICRPOWAVE	70
STM-147212	OVEN MCRWAVE:230 V;1000 W;FREESTANDING	OVEN, MICROWAVE: POTENTIAL: 230 V; POWER DISSIPATION RATING: 1000 W; OPERATING CONTROL TYPE: ELETRONIC TOUCH CONTROL; MOUNTING TYPE: FREESTANDING; LENGTH: 385 MM; WIDTH: 517 MM; HEIGHT: 297 MM; MANUF P/N: ME6104ST1; CAPACITY: 28L	30
703367	REFRIGERATOR:1 DOOR UPRIGHT;387 L;220 V	REFRIGERATOR: TYPE: 1 DOOR UPRIGHT; CAPACITY: 387 L; POTENTIAL: 220 V; CURRENT: 2.8 A;	10
705203	REFRIGERATOR:BAR;91 L;120 V;15 A	REFRIGERATOR: TYPE: BAR; CAPACITY: 91 L; POTENTIAL: 120 V; CURRENT: 15 A;	15
542637	REFRIGERATOR:FRIDGE	FRIDGE, LG 446L, MODEL GC-F569NQHM,MATT BLACK, WATER DISPENSER, BOTTOM FREEZER, INVERTER LINEAR COMPRESSOR	10
702073	REFRIGERATOR:FRIDGE/FREEZER;220 L;220 V	REFRIGERATOR: TYPE: FRIDGE/FREEZER; CAPACITY: 220 L; POTENTIAL: 220 V; CURRENT: 1.5 A;	30

The Supply and Delivery Air- conditioning units and Electrical Appliances for Nuclear Operating Unit (NOU) on an “as and when” required basis for a period of five (5) years.

Revision:

0

Page:

7 of 10

727793	TELEVISION:LG 4K SMART UHD AI;43 INCH;5	TELEVISION: TYPE: LG 4K SMART UHD AI; SIZE: 43 INCH; POTENTIAL: 5 V; CURRENT: 20 (10W PER CHANNEL) W; POWER: 100-240 V; REAL 4K UHD RESOLUTION 3840 X 2160; HDMI X2; 4K QUAD CORE PROCESSOR; ACTIVE HDR; CONNECT WITH BLUETOOTH SPEAKERS; USB X1	20
STM-119571	TELEVISION:SAMSUNG TV;50 IN;4K LED;N/A	TELEVISION: TYPE: SIZE: 50 IN; POTENTIAL: 4K LED; CURRENT: N/A; POWER: N/A; TV - SAMSUNG 127 CM (50") SMART UHD 4K LED TV	25
702074	TOASTER SNDWCH MKR:PRESS;4;2000 W	TOASTER: SANDWICH MAKER: TYPE: PRESS; NUMBER OF SLICES: 4; POWER: 2000 W; DIMENSIONS: 36 X 14.7 X 36.8 CM; FEATURES: NON STICK; MULTI GRILL, NON STICK	27
707544	TOASTER:POP UP;4;SILVER;STL;220 V	TOASTER: TYPE: POP UP; NUMBER OF SLICES: 4; COLOR: SILVER; MATERIAL: STL; FEATURES: 5 HEAT SETTINGS; POTENTIAL: 220 V; 1400 WATT	35
STM-143363	TOASTER:STAINLESS STEEL;2;GREY;750	TOASTER: TYPE: STAINLESS STEEL; NUMBER OF SLICES: 2; COLOR: GREY; MATERIAL: FLAT NON STICK COATED PLATES; FEATURES: DRIP TRAY; POTENTIAL: 750 W	15
STM-151302	VACUUM CLEANER:HTC-VAC90 POWA-VAC;90 L	VACUUM CLEANER: TYPE: HTC-VAC90 POWA-VAC; CAPACITY: 90 L; POTENTIAL: 220 V WET & DRY P/N: 441454	22
STM-151304	VACUUM CLEANER:30 L;220 V;NA	VACUUM CLEANER: TYPE: HITACHI HTC-VAC30P POWA-VAC; CAPACITY: 30 L; POTENTIAL: 220 V; WET & DRY SUPPL P/N: 398034	15
STM-136575	VACUUM CLEANER:1 L,1000 W,220-240 V	VACUUM CLEANER: TYPE: 80GMM GENESIS MINIMAX STICK; CAPACITY: 1 L; POWER SOURCE: 1000 W; POTENTIAL: 220-240 V; CURRENT: 4.2-4.5 A; MANUF P/N: 1229650; GENESIS 4-IN-1 MINIMAX STICK UPRIGHT/HANDHELD VACUUM CLEANER	20
STM-146774	WASHING MACHINE:FRONT LOADER;HISENSE;12	WASHING MACHINE: TYPE: FRONT LOADER; TRADE CAPACITY: 12 KG; COLOR: TITANIUM GREY Rev per minute 1400 Energy rating :A+++Water usage: 76L.	5

The Supply and Delivery Air- conditioning units and Electrical Appliances for Nuclear Operating Unit (NOU) on an “as and when” required basis for a period of five (5) years.

Revision:

0

Page:

8 of 10

STM-147146	WASHING MACHINE:TOP LOADER;SPEED QUEEN	Semi-Industrial Washing Machines Front loader Digital Self heating Semi-Industrial Washing Machines, that can wash radiological controlled zone clothing. The size should be 10Kg. The machines should contain a heating element for warming up the washing water. CLASSIFICATION No.: 0040/88Q SAFETY CLASS: NSF SEISMIC CLASS: NC QUALITY LEVEL: Q4 SAFETY LEVEL OF ORGANISATION: L3 ENVIRONMENTAL: NEV SPECIFICATION No.: COC MPORTANCE:: NSA	2
STM-147147	DRYER:10 KG, SPEED QUEEN	Semi-Industrial Dryer Front loader Digital Self heating Semi-Industrial Dryer, that can dry radiological controlled zone clothing. The size should be 10Kg. CLASSIFICATION No.: 0040/88Q SAFETY CLASS: NSF SEISMIC CLASS: NC QUALITY LEVEL: Q4 SAFETY LEVEL OF ORGANISATION: L3 ENVIRONMENTAL: NEV SPECIFICATION No.: COC MPORTANCE:: NSA	4
STM 093679/ 704735	SHREDDER OFFC:PAPER CROSS CUT;9.25 IN;13	SHREDDER, OFFICE: TYPE: PAPER CROSS CUT; FEED WIDTH: 9.25 IN; SHRED CAPACITY: 13 GAL; SHRED SIZE: 4 X 38 MM; SHRED SPEED: 350 (12MANUAL); WASTE VOLUME: 400 BAGS; DIMENSIONS: WD 39 X HT 812 X DP 55.3 MM; WEIGHT: 68 KG; FELLOWS AUTOMAX SHREDDER CROSS CUT 68 LITRE 2/20 350C 4964101	15
STM-135810	PROJECTOR MULTMD:LASER, FULL HD,3800 LM	PROJECTOR, MULTIMEDIA: TYPE: LASER, FULL HD; POTENTIAL: 3800 LM; EPSON LASER, WUXGA ULTRA SHORT THROW. 3800 LUMENS, 2 X VGA, 3 X HDMI, MIRACAST MODEL: EB735Fi	15
STM-136951	SCREEN PRJCTN:MOTORISED PROJECTOR SCREEN	SCREEN, PROJECTION: TYPE: MOTORISED PROJECTOR SCREEN; OPERATION METHOD: MOTORISED; MOUNTING TYPE: WALL MOUNT; HEIGHT: 2656 MM; LENGTH: 1660 MM; MATERIAL: UNKNOWN; COLOR: WHITE; PROJECTION: 16:10 RATIO; MAXIMUM PICTURE SIZE: 120; 120INCH 16:10 RATIO MOTORISED SCREEN, 2656 X 1660MM	5
STM-149213	CAMERA DGTL:CANON POWERSHOT SX70HS;128	CAMERA, DIGITAL: TYPE: CANON POWERSHOT SX70HS; STORAGE CAPACITY: 128 GB; RESOLUTION: 20.3 MPXL; COLORS: BLACK/GREY; ZOOM: 65X ZOOM LENSE; RECORDING MEDIUM: 8 HOURS; COMPATIBILITY: PICTBRIDGE; POWER SOURCE: 220V	20
STM-143201	CAMERA DGTL:SONY CYBERSHOT DSC - WX500	CAMERA, DIGITAL: TYPE: SONY CYBERSHOT DSC - WX500; STORAGE CAPACITY: 64 GB; RESOLUTION: 20 MPXL; COLORS: BLACK; ZOOM: 45; RECORDING MEDIUM: 8 HOURSE; COMPATIBILITY: GOOD; POWER SOURCE: BATTERY	20

The Supply and Delivery Air- conditioning units and Electrical Appliances for Nuclear Operating Unit (NOU) on an “as and when” required basis for a period of five (5) years.

Revision: 0
Page: 9 of 10

STM-152585	LAMINATOR: LAMINATION PROCESS: BONDING; TYPE: DELI 1000L 250MIC; DOCUMENT SIZE: A3; SPEED: 1 MIN	LAMINATOR: LAMINATION PROCESS: BONDING; TYPE: DELI 1000L 250MIC; DOCUMENT SIZE: A3; SPEED: 1 MIN	35
STM-151514	LOUDSPEAKER: TYPE: EPOS EXPAND 80T BT;	LOUDSPEAKER: TYPE: EPOS EXPAND 80T BT; DIMENSIONS: n/a; MATERIAL: PLASTIC	15
STM-095264	PRINTER: TYPE: EPSON-LQ 350; TECHNIQUE: IMPACT DOT MATRIX; TRADE NAME: EPSON LQ-350 SKU	PRINTER: TYPE: EPSON-LQ 350; TECHNIQUE: IMPACT DOT MATRIX; TRADE NAME: EPSON LQ-350 SKU C11CC25001; HIGH RELIABILITY MTBF OF 10,000 OPERATING HOURS POWER-EFFICIENT 1.3W ON STANDBY, 22W POWERED ON ECONOMICAL RIBBON YIELD OF 2.5M CHARACTERS EASY INTEGRATION PARALLEL, SERIAL AND USB INTERFACES COMPACT DESIGN FITS NEATLY ONTO DESKS	10
STM-117865	PRINTER, LABEL: UNIT TYPE: PT-P750W LABEL PRINTER;	PRINTER, LABEL: UNIT TYPE: PT-P750W LABEL PRINTER; PT-P750W LABEL PRINTER - MAXIMUM TAPE WIDTH 24MM - MAXIMUM PRINT RESOLUTION 180 DPI (MAX 180X360 DPI) - POWER SOURCE AC POWER ADAPTER (INCLUDED) RECHARGEABLE, LI-ION BATTERY (OPTIONAL) 6 X AA BATTERIES (OPTIONAL) - INTERFACE USB, WIRELESS (802.11 B/G/N), NFC	5
STM-160238	HEATER SPC:OIL 9 FIN SLIMLINE;2000 W	HEATER TYPE: OIL 9 FIN SLIMLINE; DIMENSIONS: 420X140X650 MM; POWER: 2000 W; POTENTIAL: 2000 W AUTO THERMOSTAT CONTROL : 3 HEAT SETTINGS	30
STM-160236	HEATER SPC:FAN;50.5,23.0,25.0 CM;2000 W	HEATER, TYPE: FAN; DIMENSIONS: 50.0 x 23.0 x 25.0cm POTENTIAL : 2000 WATT	30

3. ABBREVIATIONS

Abbreviation	Meaning given to the abbreviation
KNPS	Koeberg Nuclear Power Station
SSC	Short Supply Contract
PO	Purchase Order
PR	Purchase Requestion
NOU	Nuclear Operating Unit

4. TIMING AND PLANNING

- Period of contract – Five (5) years
- Start Date 01 October 2024
- Completion Date 30 May 2024

5. DELIVERY TIMES

The delivery times will be stipulated on the Purchase Order (PO), and it will be on and as and when required basis.

6. METHOD

This various Air-Conditioning Units contract will be mainly for stock replenishment but will include non-stock request. End users will request stock items via the stock reservation requests system. If the stock is low, the Inventory Planner will do a material run as per their schedule. For non-stock request the end-user will raise a PR based on their requirements. The Supplier will receive a PO to deliver and off load items at the Koeberg Nuclear Power Station Site Stores. Inventory Management will either distribute the items or replenish the bin location of the stock.