

Vehicle Job Description:	ABNORMAL (6X4) Truck Tractor To f
T10	Annexure A3
Vehicle Type Required:	Abnormal Truck Tractor 6x4 > 145 000Kgs GCM
AIR CONDITIONER (Factory Warranty)	To be Standard Factory Fitted
RADIO/CD/BLUETOOTH PRICE FITTED (IF NOT STD)	To be Standard Factory Fitted
SEAT BELTS: SABS APPROVED	To be Standard Factory Fitted
DRIVER AND PASSENGER SEATBELT REMINDER INDICATOR/ALARM	To be Standard Factory Fitted
EBS BRAKES	To be Standard Factory Fitted
POWER STEERING	To be Standard Factory Fitted
DAY TIME RUNNING LIGHTS INSTALLED	To be Standard Factory Fitted
TWO EMMERGENCY TRIANGLES	To be Standard Factory Fitted
IMMOBILISER (Factory Warranty)	To be Standard Factory Fitted
ALARM (Factory Warranty)	To be Standard Factory Fitted
ENGINE PROTECTION DEVICE(Water level, water temperature,oil pressure etc)	To be Standard Factory Fitted
TRAILER BRAKE CONTROL	To be Standard Factory Fitted
AIR CHARGE LINE TO THE FRONT	To be Standard Factory Fitted
REVERSE ALARM/BEEPER	To be Standard Factory Fitted
FITTED TOWING/RECOVERY FACILITY ON FRONT	To be Standard Factory Fitted
VEHICLE CONFIGURATION :	Truck tractor
TRACTION:	6x4
PBS Ready	YES
LED Working lights - 2 fitted facing rear of vehicle	YES
Amber Light (Bar Type)	YES
Brackets To Mount ABNORMAL Sign Board with dual flags, left & right, front of truck tractor	YES
Double sleeper cab	YES
Cooler / fridge	YES
Adjustable double oscillating 5th Wheel To Accommodate a 90mm King Pin	YES
PTO	YES
Walkway on Fuel Tank & rear of cab to access air lines	YES
Diesel Powered (Normally aspirated or Turbo)	YES
Fuel Tank Capacity	600l + 200l
Power Rating - hp	600
Torque Rating - NM	Manufacturer to specify
Permissible Front axle rating " Max."	7700 kg
Permissible Rear axle rating " Max."	18000 kg
OEM Front axle rating	OEM to Specify
OEM Rear axle rating	OEM to Specify
GCM	145000 Kg
Wheel base (Center front axle to center of rear axle unit) (Max)	3890mm
Transmission	Heavy Duty
Double Crawler Gears	YES
Retarder	YES
Roll Back Brake Assist	YES
Diff Lock	YES

Hub Reduction	YES
Vehicle to be able to pull a trailer of 125000 Kgs to 145000 Kgs	YES
Tyre Size Front	385/65 R 22.5
Tyre Size Rear	315/80 R 22.5
Spare wheel should be one of each size (2)	YES
Jost Tow Hitch at rear to accommodate a- frame trailer	YES
All Air Couplings to be fitted with isolating valves	YES
Mud-flaps: Factory fitted	YES
Maintenance Plan (60 Months)	YES, OEM to specify details of plan & submit with tender
Operator training	YES
WARRANTY PERIOD: MONTHS/DISTANCE	OEM to specify
CARBON DIOXIDE (CO ₂) EMISSION: g/km	OEM to specify
Acceptance / Acceptance	
Name of Evaluator 1:	
Name of Evaluator 2:	
Name of Verifier :	

Any proposed deviations from this specification shall be listed below with reasons for the deviation(s). In addition effective than that specified by Eskom.

Tendering supplier to score 90 in order to be Technically Acceptable	
Fully completed questionnaire in Annexure A3 confirming the compliance and non-compliance to the technical specification as well as prove (brochures) for verification of compliance.	50
Original Equipment manufacturer (OEM) or Registered dealer, to provide a confirmation letter from Original Equipment manufacturer (OEM)	20
Proof of 12 (twelve) month warranty certificate from the Original Equipment manufacturer (OEM)	20
Proof of after sales service and repairs (OEM Service Level Agreement)	10

Signatures

Noor Hassim - KZN
Anton Barnard - FS

Sign

	