



PROTOTYPE ONLY

- NOTE:
- 1. MATERIAL - ARAMID FIBRE WITH NBR BINDER, NITRILE RUBBER ACRYLONITRILE BUTADIENE (COMPRESSIBILITY: 7-15%)  
RECOVERY: 50 MIN, TENSILE STRENGTH >= 8.5 MPA)
  - 2. MAXIMUM OPERATING TEMPERATURE: 300 DEGREES CELSIUS.
  - 3. MIN OPERATING TEMPERATURE: -100 DEGREES CELSIUS.

engineering

Transnet Ltd Reg. No. 1990/00900/06

TRANSNET

07 July 2025

Durban

Configuration

-/A MATERIAL ALTERED PD_PEL_KLP_05A 2020/09/18 N.T.N.	
AMENDMENTS	
MASS	0.12 Kg

<div>COPYRIGHT</div> <div>THIS DRAWING TOGETHER WITH THE COPYRIGHT IS THE PROPERTY OF</div> <div>TRANSNET</div> <div>THIS DRAWING OR ANY PART THEREOF IS NOT TO BE COPIED OR OTHERWISE REPRODUCED OR USED FOR MANUFACTURE OR ANY OTHER PURPOSE WITHOUT THE WRITTEN PERMISSION FROM</div> <div>CHIEF EXECUTIVE,</div> <div>TRANSNET ENGINEERING</div>		ASSEMBLY DRG No. - -		DRAWN		N.T.N.		<div>KILNER PARK</div> <div>ROTATING MACHINES</div> <div>GASKET</div> <div>VV230-180 COMPRESSOR</div> <div>-</div> <div>SHEET 1 OF 1</div>				<div>MATERIAL</div> <div>SEE NOTE</div> <div>-</div> <div>SHEET 1</div> <div>389X128</div>					
		-		CHECKED		N.C.L											
		CLASS -		APPROVED		B.E.D.											
		TYPE -		DATE		20-02-2020											
		-		SCALE		1:2											
A-3		PROJECTION		DOCUMENT REFERENCE No.		PD_PEL_KLP_DRW_05A		TRANSNET ENGINEERING				No.		PEL05A0391		REV. A	