

ERP Number	Short Format Description	Purchase Order Description
0593642	THINNER:THINNERS;CAN 1 L	THINNER: TYPE: THINNERS; CONTAINER: CAN 1 L; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0160139	CHEMICAL:RUST CONVERTER;LIQD;5 L;DRUM	CHEMICAL: TYPE: RUST CONVERTER; FORM: LIQUID; CONTAINER CAPACITY: 5 L; CONTAINER: DRUM; SUPPL P/N: ACPRC; MATERIAL SAFETY DATA SHEETS WITH ENVIRONMENTAL INFORMATION PROVIDED WITH EVERY DELIVERY AS REQUIRED BY THE OCCUPATIONAL HEALTH AND SAFETY ACT, MSDS TO BE SUPPLIED AS PART OF THE TENDER, NO SUBSTANCES AND/OR MATERIALS OF CATEGORY OF THE HAZARDOUS SUBSTANCES WILL BE USED, ANY FALLING UNDER TABLE 3 OF THE SAME REGULATIONS SHALL NOT BE USED WITHOUT THE PRIOR PERMISSION OF THE TENDERING OFFICE.
0709708	BREATHER:SILICA GEL, UNIT;POLYCARBONATE	BREATHER: TYPE: SILICA GEL, UNIT; MATERIAL: POLYCARBONATE; WEIGHT: 7.62 KG; DIMENSIONS: DIA 250 X LG 670 MM; CONNECTION: FLANGE; SA200/4; OIL CAP 25200 LITRES; THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0648339	DEGREASER:BIO-D EXTRA;5 L;DRUM PLASTIC	DEGREASER: TYPE: BIO-D EXTRA; CAPACITY: 5 L; CONTAINER: DRUM PLASTIC; SUPPLIER NOTE! MATERIAL SAFETY DATA SHEET REQUIRE WITH DELIVERY
0161653	LUBRICANT:PENETRATING;150 G	LUBRICANT: TYPE: PENETRATING; CONTAINER: 150 G; MODEL NO: Q20 AEROSOL SPRAY; REFERENCE NO: H6329
0404230	GEL:SILICA ORANGE;4 KG	GEL: TYPE: SILICA ORANGE; PACKAGE TYPE: BUCKET PLASTIC, AIRTIGHT; PACKAGE WEIGHT: 4 KG; GRANULAR; ENVIROGEL; MATERIAL SAFETY DATA SHEET (MSDS) SHALL ACCORD TO THE PRODUCTS THAT CONTAIN CHEMICALS. NOTHING WILL BE ACCEPTED IF NOT SUPPLIED; (LOCALLY TERMED AS SILSORB)
0640076	OIL AUTOMTV:ENGINE;SAE 20W50;CF/SF	OIL, AUTOMOTIVE: TYPE: ENGINE; GRADE: SAE 20W50; CLASS: CF/SF; CONTAINER: DRUM 210 L; TRADE NAME: CASTROL GTX; TRUNNION BEARINGS SEAL SOAKING OIL; GRADE: SAE 20W50
0732388	TRFR:OIL FILLED;1520 A;0.28/22 KV;1000	TRANSFORMER: TYPE: OIL FILLED; CURRENT: 1520 A; POTENTIAL: 0.28/22 KV; PHASE: 3 PHASE; APPARENT POWER: 1000 KVA; CONNECTION: DYN11; SPECIFICATION: 240-6897
0646258	SEALANT:SILICON;TUBE 280 ML;CLEAR;K86	SEALANT: TYPE: SILICON; CONTAINER: TUBE 280 ML; MATERIAL: ACETOXY-CURRING; COLOR: CLEAR; TEMPERATURE RATING: -40 TO 120 DEG C; APPLICATION: SEAL BATHROOM SHOWERS, TOILET; REFERENCE NO: K86; MOULD RESISTANT; CURRING TIME APROXIMATELY 24 HOURS PER 2MM; SHELF LIFE 18 MONTHS WHEN SEALED AND STORED BELOW 10 DEG C
0648801	ADHESIVE:THREADLOCKER LOCTITE 243	ADHESIVE: TYPE: THREADLOCKER LOCTITE 243; CONTAINER: BOTTLE PLASTIC 250 ML; PHYSICAL FORM: LIQUID BLUE; SPECIFICATION: ISO 9001
0729609	ADHESIVE:LOCTITE 542;RED LIQUID	ADHESIVE: TYPE: LOCTITE 542; CONTAINER: 50ML PLASTIC BOTTLE; PHYSICAL FORM: RED LIQUID; MATERIAL: ANAEROBIC; OPERATING TEMPERATURE -55C TO 150C
0161520	OIL INDSTRL:DRUM 210 L;218 DEG C;AMBER	OIL, INDUSTRIAL: CONTAINER: DRUM 210 L; FLASH POINT: 218 DEG C; TYPE: HYDRAULIC; TRADE NAME: ENGEN TQH; VISCOSITY RATING: 46 MM2/S AT 40 DEG C; DENSITY: 0.877; GRADE: ISO VG46; SPECIFICATION: ESKOM GGSS 0867; MANUF P/N: TQH 20/46; MATERIAL SAFETY DATA SHEETS WITH ENVIRONMENTAL INFORMATION IN THE 16 POINT FORM
0714900	COMPOUND CLNG:NUEVA MODO C-EL99-10;LIQD	COMPOUND, CLEANING: TYPE: ELECTRICAL COMPONENTS CLEANING; BRAND NAME: NUEVA MODO C-EL99-10; PHYSICAL FORM: LIQUID; COMPOSITION: HIGH BOILING POINT FLUORINATED ETHER; CONTAINER TYPE: BOTTLE; CONTAINER CAPACITY: 20 L; REFERENCE NO: C-EL99-10
0654880	CHEMICAL:HYDREX 4503;LIQD;25 KG;PLASTIC	CHEMICAL: TYPE: HYDREX 4503; FORM: LIQUID; CONTAINER CAPACITY: 25 KG; CONTAINER: PLASTIC; COMPOSITION: ORGANIC ACID SOLUTION; COLOR: CLEAR; MSDS NUMBER: 4503
0550689	LUBRICANT:SPANJAARD 1010;GREASE	LUBRICANT: TYPE: SPANJAARD 1010; FORM: GREASE; CONTAINER: TIN 500 G; BASE MATERIAL: TRANSLUCENT; SPECIFICATION: SABS ISO9001; NOTE: MATERIAL SAFETY DATA SHEET WITH DELIVERY ELECTRICAL CONTACTS, PREVENTS TRACKING & SHORTING OUT, ELIMINATE ARCING, SOFTENS & LOOSENS OXIDE FILMS, NOT HARMFUL TO PLASTICS & RUBBER, PROTECTS METAL SURFACES
0541124	COMPOUND SEALG:HYLOMAR;BLUE;100 G	COMPOUND, SEALING: TYPE: HYLOMAR; COLOR: BLUE; CONTAINER: 100 G; MATERIAL: RUBBER SI; NOTE: MATERIAL SAFETY DATA SHEET REQUIRE WITH DELIVERY
0670841	ADHESIVE:HARDNER HY840;CAN 1 KG;LIQD	ADHESIVE: TYPE: HARDNER HY840; CONTAINER: CAN 1 KG; PHYSICAL FORM: LIQUID; SPECIFICATION: CLAS-A; MATERIAL: ARLADITE
0687571	CLEANER HND:LIQUID SOAP;1 L	CLEANER, HAND: TYPE: LIQUID SOAP; CONTAINER: 1 L; TRADE NAME: TORK MILD FOAM; (IT IS NON-REFILLABLE, AVAILABLE IN 1LITRES), 1 LITRE PLASTIC BOTTLE (92 X 240MM), MANUFACTURED IN ACCORDANCE WITH GOOD MANUFACTURING PRACTICES (GMPs), THE PRODUCT HAS BEEN ASSESSED FOR SAFETY ACCORDING TO ARTICLE 10 OF THE COSMETICS REGULATION, CONSIDERED AS SAFE FOR HUMAN HEALTH WHEN USED UNDER NORMAL OR REASONABLY FORESEEABLE CONDITIONS, NO SIGNIFICANT HAZARD TO HUMAN HEALTH OR THE ENVIRONMENT WITH EU REGULATIONS ON ANIMAL TESTING, THE PRODUCT IS IN CONFORMITY WITH THE REACH REGULATION EC/1907/2006 AND ITS AMENDMENTS.ACCORDING TO THE ART
0727136	CHEMICAL:ACETONE AR;LIQD;2.5 L;PLASTIC	CHEMICAL: TYPE: ACETONE AR; FORM: LIQUID; CONTAINER CAPACITY: 2.5 L; CONTAINER: PLASTIC
0157568	CLEANER:CONTACT;AEROSOL COMPOUND	CLEANER: TYPE: CONTACT; FORM: AEROSOL COMPOUND; CONTAINER: CAN 454 G; REFERENCE NO: LECTRO-KLEEN; DELIVERY WILL NOT BE ACCEPTED IF HAZARDOUS CHEMICALS ARE DETECTED
0545017	SOLVENT:FO128;ELEC CLNR;LIQD;CLEAR;+80	SOLVENT: TYPE: ELECTRICAL CLEANER; CONTAINER: DRUM PLASTIC 20 L; PHYSICAL FORM: LIQUID; COLOR: CLEAR; FLASH POINT: +80 DEG C; TRADE NAME: FINE ORGANICS; C
0221097	INHIBITOR:RUST AND CORROSION	INHIBITOR: TYPE: RUST AND CORROSION; CONTAINER: TRIGGER SPRAY 454 ML; SUPPL P/N: 91002; SUPPLIER NOTE: THE ITEM WILL NOT BE ACCEPTED WITHOUT A MATERIAL SAFETY DATA SHEET
0161194	CUTTING FLUID:SOLUBLE OIL	CUTTING FLUID: LUBRICANT TYPE: SOLUBLE OIL; SUPPL P/N: ULTRACUT 370; REFERENCE NO: 370; CONTAINER 5 L PLASTIC CAN, SEMI SYNTHETIC CUTTING AND GRINDING, IN
0160015	POLISH FURNT:CAN;500 ML	POLISH, FURNITURE: TYPE: WOOD STAIN, MEDIUM OAK VARNISH; CONTAINER: CAN; CAPACITY: 500 ML
0648800	LUBRICANT:PENETRATING Q20;AEROSOL;300 G	LUBRICANT: TYPE: PENETRATING Q20; FORM: AEROSOL; CONTAINER: 300 G; BASE MATERIAL: RUST INHIBITOR; SPECIFICATION: ISO 9001; MANUF P/N: 30022
0760528	LUBRICANT:NICKEL ANTI-SEIZE;453.6 GRAMS	LUBRICANT: TYPE: NICKEL ANTI-SEIZE; FORM: SILVER GREY CONTAINER; CONTAINER: 453.6 GRAMS; SUPPL P/N: 77164
0766237	COMPOUND:NICKEL;TIN, 350ML;AEROSOL SPRAY	COMPOUND: TYPE: NICKEL; CONTAINER: TIN, 350ML; PHYSICAL FORM: AEROSOL SPRAY; SPECIFICATION: ANTISEIZE; CHEMICAL LUBRICANT
0711906	CLEANER HND:PASTE WITH GRIT;TUB 2 L	CLEANER, HAND: TYPE: PASTE WITH GRIT; CONTAINER: TUB 2 L; TRADE NAME: REINOL
0729612	ADHESIVE:LOCTITE 2701;GREEN LIQUID	ADHESIVE: TYPE: LOCTITE 2701; CONTAINER: 50ML PLASTIC BOTTLE; PHYSICAL FORM: GREEN LIQUID; SPECIFICATION: DVGW, NSF, WRAS; MATERIAL: METHACRYLATE; VISCOSITY: 1000 CPS
0765817	CHEMICAL:HYDREX 9509;LIQD;25 L;PLASTIC	CHEMICAL: TYPE: HYDREX 9509; FORM: LIQUID; CONTAINER CAPACITY: 25 L; CONTAINER: PLASTIC; COMPOSITION: SODIUM HYDROXIDE SOLUTION, 8, PG II; SPECIFICATION: F
0599186	ADHESIVE:PVC PENTA WELD;CAN 500 ML	ADHESIVE: TYPE: PVC PENTA WELD; CONTAINER: CAN 500 ML; PHYSICAL FORM: LIQUID WHITE; PVC-U; PRESSURE RATING 0-16 BAR; TEMPERATURE -30 TO 60 DEGREE CEL; S
0242278	CLEANER:DEGREASER, BIODEGRADABLE	CLEANER: TYPE: DEGREASER, BIODEGRADABLE; FORM: LIQUID WATER BASED; CONTAINER: CAN PLASTIC 25 L; REFERENCE NO: 8642; MATERIAL SAFETY DATA TO BE SUPPLIED WITH DELIVERY
0160167	COMPOUND:COPPER;CAN 500 G;PASTE;ISO 9001	COMPOUND: TYPE: COPPER; CONTAINER: CAN 500 G; PHYSICAL FORM: PASTE; CONCENTRATION: GREASE, METAL POWEREDS AND ADDITIVES; SPECIFICATION: ISO 9001; COM
0597292	SEALANT:GASKET MAKER;TUBE;SILICON;RED	SEALANT: TYPE: GASKET MAKER; CONTAINER: TUBE; MATERIAL: SILICON; COLOR: RED; TEMPERATURE RATING: +300 DEG C; ACETOXY 100%
0515827	SOAP:CAR SHAMPOO	SOAP: TYPE: CAR SHAMPOO

0256978	ADDITIVE COOLANT:HD ULTRA ELC 50/50	ADDITIVE, COOLANT: TYPE: ANTI FREEZE, EMERGENCY DIESEL ENGINE; ACTIVE INGREDIENT: MONO-ETHYLENE-GLYCOL, PRE-DILUTED 50/50; REFERENCE NO: HD ULTRA ELC 50/50; AT 101.3 KPA:HIGHER THAN 129 DEG C; DENSITY AT 15 DEG C; FREEZING POINT 1120 DEG C:-37 DEG C; MATERIAL SAFETY DATA SHEET, MSDS AND OR TECHNICAL DATE SHEET REQUIRED WITH EVERY DELIVERY AND MUST INCLUDE MANUFACTURING DATE, EXPIRY DATE AND ALLOWABLE DEVIATION OF PRODUCT; ALL CHEMICALS WITH A SHELF-LIFE, SHALL NOT EXPIRE WITHIN ONE (1) YEAR
0570103	CHEMICAL:SIWASH W;LIQD;200 L;COLORLESS	CHEMICAL: TYPE: SIWASH W; FORM: LIQUID; CONTAINER CAPACITY: 200 L; CONTAINER: DRUM PLASTIC; COMPOSITION: ISOTRIDECYLALCOHOL 15-30 PCT; COLOR: COLORLESS
0654879	CHEMICAL:HYDREX 4502;LIQD;25 KG;PLASTIC	CHEMICAL: TYPE: HYDREX 4502; FORM: LIQUID; CONTAINER CAPACITY: 25 KG; CONTAINER: PLASTIC; COMPOSITION: ORGANIC ACID SOLUTION; COLOR: CLEAR; MSDS NUMBER: 0654879
0756858	SOLVENT:CLEANING;PLASTIC CONTAINER, 1L	SOLVENT: TYPE: CLEANING; CONTAINER: PLASTIC CONTAINER, 1L; PICKLING PASTE FOR THE CLEANING OF PLATED HEAT EXCHANGER PLATES
0665089	COMPOUND SEALG:ADHESIVE;CLEAR;SILICONE	COMPOUND, SEALING: TYPE: ADHESIVE; COLOR: CLEAR; CONTAINER: TUBE 280 ML; MATERIAL: SILICONE; BENEFIT AND FIXTURES: CLEAR GRADE NON YELLOWING; EXCELLENT DURABLE BOND; LOW TEMPERATURE: - 50 DEG C; HIGH TEMPERATURE: 50 DEG C; WATERPROOF; VERSATILE; SUITABLE FOR EXTERNAL APPLICATIONS
0550730	CREAM:PETROLEUM JELLY WHITE;CAN;500 G	CREAM: TYPE: PETROLEUM JELLY WHITE; PACKAGE TYPE: CAN; PACKAGE WEIGHT: 500 G; NOTE: MATERIAL SAFETY DATA SHEET REQUIRE WITH EACH DELIVERY
0547121	SOLVENT:ACETONE;CAN 5 L;COMMERCIAL;-20	SOLVENT: TYPE: ACETONE; CONTAINER: CAN 5 L; GRADE: COMMERCIAL; PHYSICAL FORM: FLAMMABLE LIQUID; COLOR: COLORLESS; DENSITY: 0.79G/CM3; FLASH POINT: -20 DEG C
0224922	SOLVENT:CLEANER ELECTRICAL;5 L	SOLVENT: TYPE: CLEANER ELECTRICAL; CONTAINER: 5 L; SUPPL P/N: ESK F0655; ESKOMF0655; SAFETY: MATERIAL SAFETY DATA SHEET (MSDS) SHALL ACCOMPANY ALL PURCHASES
0753437	OIL INDSTR:20 L;195;AIR COMPRESSOR	OIL, INDUSTRIAL: CONTAINER: 20 L; FLASH POINT: 195; TYPE: AIR COMPRESSOR; TRADE NAME: SHELL CORENA S2 P68; VISCOSITY RATING: 68 MM2/S AT 40 DEG C
0256838	DYE MRKNG BLUE:LAYOUT INK SPRAY	DYE, MARKING BLUE: TYPE: LAYOUT INK SPRAY; SPECIFICATION: DSG-317-094; Q3:NSF:NC:NEV; CRACK APPROVED; MATERIAL SAFETY DATA SHEET, MSDS AND OR TECHNICAL DATE SHEET REQUIRED WITH EVERY DELIVERY AND MUST INCLUDE MANUFACTURING DATE, EXPIRY DATE AND ALLOWABLE DEVIATION OF PRODUCT; ALL CHEMICALS WITH A SHELF-LIFE, SHALL NOT EXPIRE WITHIN ONE (1) YEAR
0160278	ADHESIVE:SUPERGLUE;BOTTLE 20 G;LIQD	ADHESIVE: TYPE: SUPERGLUE; CONTAINER: BOTTLE 20 G; PHYSICAL FORM: LIQUID; SPECIFICATION: LOCTITE 401; MATERIAL: CYANOACRYLATE; SUPPL P/N: IS495; HYPERBONDING; MATERIAL SAFETY DATA SHEETS THAT COMPLIES WITH THE OCCUPATIONAL HEALTH AND SAFETY ACT'S REGULATIONS TO BE SUPPLIED; NO SUBSTANCES AND/OR INGREDIENTS WILL BE USED; ANY CHEMICAL FALLING UNDER TABLE 3 OF THE SAME REGULATIONS SHALL NOT BE USED; SHALL BE BIODEGRADABLE AND OZONE FRIENDLY; CHEMICALS TO BE SUPPLIED WITH MSDS
0666991	HERBICIDE:GRANULAR;WATER 100ML/10L	HERBICIDE: FORM: GRANULAR; COMPOSITION: WATER 100ML/10L; USE: WEED CONTROL; CONTAINER: BAG 25 KG; TRADE NAME: BROMURON 100GR (25KG); KILO WSG 700(1000)G
0732389	TRFR:OIL FILLED;760 A;0.38/13.2 KV;500	TRANSFORMER: TYPE: OIL FILLED; CURRENT: 760 A; POTENTIAL: 0.38/13.2 KV; PHASE: 3 PHASE; APPARENT POWER: 500 KVA; CONNECTION: DYN11; SPECIFICATION: 240-6897
0687430	CLEANER:DEGREASER, BIODEGRADABLE	CLEANER: TYPE: DEGREASER, BIODEGRADABLE; FORM: LIQUID WATER BASED; CONTAINER: CAN PLASTIC 25 L; TRADE NAME: SOLVECRETE; MATERIAL SAFETY DATA TO BE SUPPLIED WITH EVERY DELIVERY
0766094	CHEMICAL:HYDREX 4101;LIQD;25 L;PLASTIC	CHEMICAL: TYPE: HYDREX 4101; FORM: LIQUID; CONTAINER CAPACITY: 25 L; CONTAINER: PLASTIC; SPECIFICATION: REQUIRED A MSDS WITH EVERY DELIVERY; SUPPL P/N: HYDREX 4101
0160266	COMPOUND SEALG:GASKET/JOINT;TUBE 100 G	COMPOUND, SEALING: TYPE: GASKET/JOINT; COLOR: BLUE UNIVERSAL; CONTAINER: TUBE 100 G; MATERIAL: POLYESTER URETHANE; SUPPL P/N: PL32M; CLAUSE: 1: PLEASE ENQUIRE IF ITEMS ARE DISPLAYED, 2: ITEMS SUBJECTED TO SHELF LIFE WILL NOT BE ACCEPTED TO ESKOM IF MORE THAN 25 PCT OF THE SHELF LIFE HAS ALREADY EXPIRED PRIOR TO DELIVERY; MATERIAL SAFETY DATA SHEET REQUIRED WITH EVERY DELIVERY
0737834	SEALANT:SIKAFLEX ELASTIC JOINT;600 ML	SEALANT: TYPE: SIKAFLEX ELASTIC JOINT; CONTAINER: 600 ML; MATERIAL: POLYURETHANE; COLOR: GREY; TEMPERATURE RATING: +5 TO + 25; APPLICATION: SEALING OF EXPANDED POLYSTYRENE
0749187	ADHESIVE:H330 ;1 KG;LIQUID (THICK)	ADHESIVE: TYPE: CONDUCTIVE EPOXY CURING AGENT; CONTAINER: 1 KG; PHYSICAL FORM: LIQUID (THICK); OEM P/N: H330 ; H330 CONDUCTIVE PAINT - EPOXY CURING AGENT
0256859	ADHESIVE:CONTACT;5 L	ADHESIVE: TYPE: CONTACT; CONTAINER: 5 L; MANUF P/N: 847; SPECIFICATION: DSG-317-094; Q3:NSF:NC:NEV; REFERENCE NO: 1236; CRACK APPROVED CATEGORY 1; MATERIAL SAFETY DATA SHEET, TDS REQUIRED WITH EVERY DELIVERY AND MUST INCLUDE MANUFACTURING DATE, EXPIRY DATE AND ALLOWABLE DEVIATION OF PRODUCT; ALL CHEMICALS WITH A SHELF-LIFE, SHALL NOT EXPIRE WITHIN ONE (1) YEAR
0718965	PAINT:PRIMER;OXIDE-RED;BASE;20 L	PAINT: TYPE: PRIMER; COLOR: OXIDE-RED; FINISH: BASE; CONTAINER: 20 L; SPECIFICATION: STEELPRIMER PLASCON 20 LT PAINT
0765467	CHEMICAL:ACETONE;LIQD;20 L;PLASTIC	CHEMICAL: TYPE: ACETONE; FORM: LIQUID; CONTAINER CAPACITY: 20 L; CONTAINER: PLASTIC
0654881	CHEMICAL:HYDREX 4203;LIQD;25 KG;PLASTIC	CHEMICAL: TYPE: HYDREX 4203; FORM: LIQUID; CONTAINER CAPACITY: 25 KG; CONTAINER: PLASTIC; COMPOSITION: ORGANIC ACID SOLUTION; COLOR: CLEAR; MSDS NUMBER: 0654881
0211507	RESIN:AMBERLITE IRN9882 H/OH;GRANULAR	RESIN: TYPE: AMBERLITE IRN9882 H/OH; FORM: GRANULAR; CONTAINER: DRUM BLUE 50 L; INDUSTRIAL NUCLEAR GRADE; MATRIX POLYSTYRENE BULK DENSITY: 665-740 G/L; TECHNICAL DATE SHEET (TDS) REQUIRED WITH EVERY DELIVERY AND MUST INCLUDE MANUFACTURING DATE, EXPIRY DATE AND ALLOWABLE DEVIATION OF PRODUCT; ALL CHEMICALS WITH A SHELF-LIFE, SHALL NOT EXPIRE WITHIN ONE (1) YEAR
0749175	ADHESIVE:VOLTATEX 5131 HARDENER;HARDNER	ADHESIVE: TYPE: HARDNER; CONTAINER: 1 KG; PHYSICAL FORM: LIQUID (THICK); OEM P/N: VOLTATEX 5131 HARDENER; VOLTATEX 5131 HARDENER. SAFETY DATA AND TECHNICAL DATE SHEET REQUIRED WITH EVERY DELIVERY
0729614	ADHESIVE:LOCTITE 243 THREADLOCKER;50 ML	ADHESIVE: TYPE: LOCTITE 243 THREADLOCKER; CONTAINER: 50 ML; PHYSICAL FORM: BLUE LIQUID; SPECIFICATION: DVGW,NSF; MATERIAL: THIXOTROPIC; T, 2150.0 MPA-S CP
0729611	ADHESIVE:LOCTITE 431;20G	ADHESIVE: TYPE: LOCTITE 431; CONTAINER: 20G; PHYSICAL FORM: TRANSPARANT LIQUID; MATERIAL: ETHYL BASED INSTANT ADHESIVE; OPERATING TEMPERATURE -40C TO 80C
0692884	CLEANER:ELECTRICAL CONTACT;AEROSOL	CLEANER: TYPE: ELECTRICAL CONTACT; FORM: AEROSOL; CONTAINER: CAN 400 ML
0749174	ADHESIVE:3100 ;5 KG;LIQUID (THICK)	ADHESIVE: TYPE: POLYURETHANE CASTING RESIN; CONTAINER: 5 KG; PHYSICAL FORM: LIQUID (THICK); SPECIFICATION: CLASS E - B (120 - 130 °C) POLYBROMINATED DIPHENYL ETHER; MATERIAL: POLYURETHANE CASTING RESIN; OEM P/N: 3100 ; VOLTACAST 3100 - PIGMENTED, FILLED AND COLD-CURING TWO-COMPONENT POLYURETHANE CASTING RESIN.
0765816	CHEMICAL:HYDREX 4301;LIQD;25 L;PLASTC	CHEMICAL: TYPE: HYDREX 4301; FORM: LIQUID; CONTAINER CAPACITY: 25 L; CONTAINER: PLASTC; SPECIFICATION: REQUIRED A MSDS WITH EVERY DELIVERY; SUPPL P/N: HYDREX 4301
0040820	GAS:SMOKE DETECTOR;CAN 250 G;8	GAS: TYPE: SMOKE DETECTOR; PURITY: ISOBUTANE 58-66/BUTANE 0-2/PROPANE 34-42 PCT; CONTAINER: CAN 250 G; SUPPL P/N: A5Q00011687; SPECIFICATION: C.O.C; Q4:NSF; DETECTOR, DIMEN:250ML CANNISTER; (MATERIAL SAFETY DATA SHEET (MSDS) AND OR TECHNICAL DATE SHEET (TDS) REQUIRED WITH EVERY DELIVERY AND MUST INCLUDE MANUFACTURING DATE, EXPIRY DATE AND ALLOWABLE DEVIATION OF PRODUCT; ALL CHEMICALS WITH A SHELF-LIFE, SHALL NOT EXPIRE WITHIN ONE (1) YEAR
0759867	GREASE INDSTR:BEARING GREASE;-35 to 140	GREASE, INDUSTRIAL: TYPE: BEARING GREASE; TEMPERATURE RATING: -35 to 140 DEG C; THICKENER: LITHIUM; VISCOSITY RATING: 95MM2S @ 40 °C/104 °F; COLOR: BROWN; 100-2 PD; TRADE NAME: TRIBOL GR 100-2 PD; SPECIFICATION: DIN 51502 KP 2 N-30; MANUF P/N: TRIBOL GR 100-2 PD
0756717	ABSORBENT:CARBON MC110;ACTIVATED CARBON	ABSORBENT: TYPE: CARBON MC110; FORM: ACTIVATED CARBON; CONTAINER CAPACITY: 25 KG; CONTAINER: PLASTIC BAG; COCONUT BASED GAC
0679938	SOLVENT:ELECTRICAL;DRUM 25 L;DEGREASER	SOLVENT: TYPE: ELECTRICAL; CONTAINER: DRUM 25 L; GRADE: DEGREASER; PHYSICAL FORM: LIQUID; COLOR: YELLOW/ORANGE; DENSITY: 0.79 - 080 G/CM3; FLASH POINT: 45 DEG C
0157601	CHEMICAL:RUST REMOVER;20 L;DRUM	CHEMICAL: TYPE: RUST REMOVER; CONTAINER CAPACITY: 20 L; CONTAINER: DRUM; REFERENCE NO: 338; METAL CONDITIONER; NON FLAMMABLE; ACID BASE CLEANER; CHEMICAL SAFETY DATA SHEETS WITH ENVIRONMENTAL INFORMATION IN THE 16 POINT FORMAT TO BE PROVIDED WITH EVERY DELIVERY AS REQUIRED BY THE OCCUPATIONAL HEALTH AND SAFETY ACT
0648338	SOLVENT:F0128;ELEC CLNR;DRUM 5 L;LIQD	SOLVENT: TYPE: ELECTRICAL CLEANER; CONTAINER: DRUM 5 L; PHYSICAL FORM: LIQUID; COLOR: CLEAR; FLASH POINT: +80 DEG C; TRADE NAME: FINE ORGANICS; OEM P/N: F0128

0765976	RESIN:EPOXY;LIQD;1 LITRE BOTTLE	RESIN: TYPE: EPOXY; FORM: LIQUID; CONTAINER: 1 LITRE BOTTLE
0527731	RESIN:AMBERLITE;IRN 150;DRUM BLUE 50 L	RESIN: TYPE: AMBERLITE; FORM: IRN 150; CONTAINER: DRUM BLUE 50 L; (CRACK APPROVED - CATEGORY 1); (MATERIAL SAFETY DATA SHEET (MSDS) AND OR TECHNICAL DATA SHEET (TDS) MUST BE PROVIDED WITH EVERY DELIVERY; ALL CHEMICALS WITH A SHELF-LIFE, SHALL NOT EXPIRE WITHIN ONE (1) YEAR); MUST INCLUDE MANUFACTURING DATE, EXPIRY DATE AND ALLOWABLE DEVIATION OF PRODUCT; ALL CHEMICALS WITH A SHELF-LIFE, SHALL NOT EXPIRE WITHIN ONE (1) YEAR)
0729610	ADHESIVE:LOCTITE 577;YELLOW PASTE	ADHESIVE: TYPE: LOCTITE 577; CONTAINER: 50ML PLASTIC BOTTLE; PHYSICAL FORM: YELLOW PASTE; SPECIFICATION: DVGW, NSF, WRAS; MATERIAL: ANAEROBIC; VISCOSITY: 2500 CPS
0729608	ADHESIVE:LOCTITE 561;19G;WHITE;NSF	ADHESIVE: TYPE: LOCTITE 561; CONTAINER: 19G; PHYSICAL FORM: WHITE; SPECIFICATION: NSF; MATERIAL: METHACRYLATE; OPERATING TEMPERATURE -55C TO 150C, BREAKDOWN TEMPERATURE 200C
0766194	ADHESIVE:O-RING GLUE 406;20 GRAM	ADHESIVE: TYPE: O-RING GLUE 406; CONTAINER: 20 GRAM
0161348	GREASE INDSTR:L.TUBE;ALVANIA R2	GREASE, INDUSTRIAL: CONTAINER: TUBE; TRADE NAME: ALVANIA R2; LENGTH 215MM X 50MM THICK
0638236	COMPOUND:ANTI SEIZURE;CAN 500 G	COMPOUND: TYPE: ANTI SEIZURE; CONTAINER: CAN 500 G; SPECIFICATION: SP NICKEL; SPANJAARD GREASE FOR S/STEEL
0765823	OIL GEAR:MOBILGEAR 600 XP 320;VG320;20 L	OIL, GEAR: TRADE NAME: MOBILGEAR 600 XP 320; GRADE: VG320; CONTAINER: 20 L; VISCOSITY RATING: 320 CST @ 40 °C; FLASH POINT: 240 DEG C; SUPPL P/N: MOBILGEAR 600 XP 320
0727135	CHEMICAL:ACETYLACETONE;LIQD;5 L;PLASTC	CHEMICAL: TYPE: ACETYLACETONE; FORM: LIQUID; CONTAINER CAPACITY: 5 L; CONTAINER: PLASTC; TRADE NAME: ACETONE GENERAL PURPOSE REAGENT; COLOR: CLEAR AND COLORLESS
0161479	COMPOUND:CUTTING;CAN 500 G;PASTE	COMPOUND: TYPE: CUTTING; CONTAINER: CAN 500 G; PHYSICAL FORM: PASTE; REFERENCE NO: 53-510-500; SUITABLE FOR HAND AND MACHINE TOOLS, IDEAL MEDIUM FOR REMOVING BURRS AND CHIPS
0729613	ADHESIVE:LOCTITE 572;OFF WHITE PASTE	ADHESIVE: TYPE: LOCTITE 572; CONTAINER: 250ML PLASTIC BOTTLE; PHYSICAL FORM: OFF WHITE PASTE; SPECIFICATION: DVGW, NSF, WRAS; MATERIAL: METHACRYLATE; VISCOSITY: 2500 CPS
0174268	THINNER:THINNERS;5 L	THINNER: TYPE: THINNERS; CONTAINER: 5 L; SUPPL P/N: 623; REQUIRED A MATERIAL SAFETY DATA SHEET WITH EVERY DELIVERY; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THE THINNER IS SUITABLE FOR THE APPLICATION

PG 3 of 3
R Muller
2026/01/12

