

SPEC SHEET

SAP MATERIAL No.:	0403115							
SHORT DESCRIPTION:	COND,ACSR SQUIRREL 6.33D UNGRS D3136							
TECH. DESCRIPTION:								
ALUMINIUM CONDUCTOR STEEL REINFORCED * 6 ALUMINIUM STRANDS OF 2.11mm DIA * ONE STEEL STRAND OF 2.11mm DIA.* CONDUCTOR 6.33mm DIA. * UNGREASED * CODE NAME SQUIRREL * RATED TENSILE STRENGTH 8.02kN * ESKOM DRAWING No. D-DT-3136 *								
SAP MATERIAL No.:	0403033							
SHORT DESCRIPTION:	COND,ACSR MAGPIE 6.35D UNGRS D3136							
TECH. DESCRIPTION:								
ALUMINIUM CONDUCTOR STEEL REINFORCED * 3 ALUMINIUM STRANDS OF 2.118mm DIA * 4 STEEL STRANDS OF 2.118mm DIA.* CONDUCTOR 6.35mm DIA. * UNGREASED * CODE NAME MAGPIE * RATED TENSILE STRENGTH 18.573kN * ESKOM DRAWING No. D-DT-3136 *								
SAP MATERIAL No.:	0403027							
SHORT DESCRIPTION:	COND,ACSR FOX 8.37D UNGRS D3136							
TECH. DESCRIPTION:								
ALUMINIUM CONDUCTOR STEEL REINFORCED * 6 ALUMINIUM STRANDS OF 2.79mm DIA * ONE STEEL STRAND OF 2.79mm DIA.* CONDUCTOR 8.37mm DIA. * UNGREASED * CODE NAME FOX * RATED TENSILE STRENGTH 13.1kN * ESKOM DRAWING No. D-DT-3136 *								
ITEM	:- CONDUCTOR, STRANDED							
MATERIAL SPECIFICATION	:- IEC 104, IEC 888, IEC 889							
CORROSION SPECIFICATION	:- IEC 61089, IEC 61394, SANS 121, ISO 1461							
STANDARD SPECIFICATION	:- SANS 182-2, 3 & 5, IEC 61089							
ESKOM SPECIFICATION	:- DSP 34-377							
TEST & CERTIFICATION REQUIREMENTS :- TYPE TESTS AS PER IEC 61089, IEC 61394								
INSPECTION	Yes	No	ESKOM RELEASE NOTE			Yes	No	
IDENTIFICATION:- INDELIBLE MANUFACTURES TRADEMARK & PART No. ON ALL ITEMS								
13	SAP 0014606, 0014443, 0014440, 0014442, 0014441 0014445, 0014697, 0014439, 0014657, 0014677, 0014675, 0014781, 0014752, 0171327, 0014678, 0014580, 0014446,0014447, 0014452 CORRECTED		P.A.T.	D. RAMJASS	D. RAMJASS	20.01.2017		
12	RAIL CONDUCTOR GREASED AND UNGREASED ADDED AND ESKOM SPEC CHANGED		P.A.T.	B. HILL	M. RAPAPA	07.12.2009		
11	FOX CONDUCTOR GREASED REINSTATED		P.A.T.	M. RAPAPA	M. RAPAPA	07.07.2009		
REV	REVISION DESCRIPTION		BY	CHKD	AUTH	DATE	REF. DWGS	
AUTH:	P.CROWDY	DATE:	17.07.1995			SAP No:		
CHKD:	J.SWAN	DATE:	17.07.1995			0403115 0403033		0403027
DRAWN:	P.A.VERMAAK	DATE:	11.05.1995			SET		SHEET
				D-DT- 3136		8	1	13

SPEC SHEET

SAP MATERIAL No.:	0403031						
SHORT DESCRIPTION:	COND,ACSR MINK 10.98D UNGRS D3136						
TECH. DESCRIPTION:							
ALUMINIUM CONDUCTOR STEEL REINFORCED * 6 ALUMINIUM STRANDS OF 3.66mm DIA * ONE STEEL STRAND OF 3.66mm DIA. * CONDUCTOR 10.98mm DIA. * UNGREASED * CODE NAME MINK * RATED TENSILE 21.9kN * ESKOM DRAWING No. D-DT-3136 *							
SAP MATERIAL No.:	0403029						
SHORT DESCRIPTION:	COND,ACSR HARE 14.16D UNGRS D3136						
TECH. DESCRIPTION:							
ALUMINIUM CONDUCTOR STEEL REINFORCED * 6 ALUMINIUM STRANDS OF 4.72mm DIA * ONE STEEL STRAND OF 4.72mm DIA.* CONDUCTOR 14.16mm DIA. * UNGREASED * CODE NAME HARE * RATED TENSILE STRENGTH 36kN * ESKOM DRAWING No. D-DT-3136 *							
SAP MATERIAL No.:	0403037						
SHORT DESCRIPTION:	COND,ACSR WOLF 18.13D UNGRS D3136						
TECH. DESCRIPTION:							
ALUMINIUM CONDUCTOR STEEL REINFORCED * 30 ALUMINIUM STRANDS OF 2.59mm DIA * 7 STEEL STRAND OF 2.59mm DIA. * CONDUCTOR 18.13mm DIA. * UNGREASED * CODE NAME WOLF * RATED TENSILE 69.2kN * ESKOM DRAWING No. D-DT-3136 *							
SAP MATERIAL No.:	0403130						
SHORT DESCRIPTION:	COND,ACSR CHICADEE 18.87D UNGRS D3136						
TECH. DESCRIPTION:							
ALUMINIUM CONDUCTOR STEEL REINFORCED * 18 ALUMINIUM STRANDS OF 3.77mm DIA * ONE STEEL STRAND OF 3.77mm DIA.* CONDUCTOR 18.87mm DIA. * UNGREASED * CODE NAME CHICADEE * RATED TENSILE STRENGTH 44.9kN * ESKOM DRAWING No. D-DT-3136 *							
13	SAP 0014606, 0014443, 0014440, 0014442, 0014441 0014445, 0014697, 0014439, 0014657, 0014677, 0014675, 0014781, 0014752, 0171327, 0014678, 0014580, 0014446,0014447, 0014452 CORRECTED		P.A.T.	D. RAMJASS	D. RAMJASS	20.01.2017	
12	RAIL CONDUCTOR GREASED AND UNGREASED ADDED AND ESKOM SPEC CHANGED		P.A.T.	B. HILL	M. RAPAPA	07.12.2009	
11	FOX CONDUCTOR GREASED REINSTATED		P.A.T.	M. RAPAPA	M. RAPAPA	07.07.2009	
REV	REVISION DESCRIPTION		BY	CHKD	AUTH	DATE	
AUTH:	P.CROWDY	DATE:	17.07.1995	 D-DT-3136		SAP No:	
CHKD:	J.SWAN	DATE:	17.07.1995			0403031	0403037
						0403029	0403130
DRAWN:	P.A.VERMAAK	DATE:	11.05.1995			SET	SHEET
				8	2	13	

SPEC SHEET									
SAP MATERIAL No.:		0403025							
SHORT DESCRIPTION:		COND,ACSR BEAR 23.45D UNGRS D3136							
TECH. DESCRIPTION: ALUMINIUM CONDUCTOR STEEL REINFORCED * 30 ALUMINIUM STRANDS OF 3.35mm DIA * 7 STEEL STRAND OF 3.35mm DIA.* CONDUCTOR 23.45mm DIA. * UNGREASED * CODE NAME BEAR * RATED TENSILE STRENGTH 112kN * ESKOM DRAWING No. D-DT-3136 *									
SAP MATERIAL No.:		0400662							
SHORT DESCRIPTION:		COND,ACSR KINGBIRD 23.90D UNGRS D3136							
TECH. DESCRIPTION: ALUMINIUM CONDUCTOR STEEL REINFORCED * 18 ALUMINIUM STRANDS OF 4.78mm DIA * ONE STEEL STRAND OF 4.78mm DIA.* CONDUCTOR 23.90mm DIA. * UNGREASED * CODE NAME KINGBIRD * RATED TENSILE STRENGTH 71.32kN * ESKOM DRAWING No. D-DT-3136 *									
SAP MATERIAL No.:		0400669							
SHORT DESCRIPTION:		COND,ACSR TERN 27.00D UNGRS D3136							
TECH. DESCRIPTION: ALUMINIUM CONDUCTOR STEEL REINFORCED * 45 ALUMINIUM STRANDS OF 3.38mm DIA * 7 STEEL STRAND OF 2.25mm DIA. * CONDUCTOR 27.00mm DIA. * UNGREASED * CODE NAME TERN * RATED TENSILE 98.7kN * ESKOM DRAWING No. D-DT-3136 *									
SAP MATERIAL No.:		0245988							
SHORT DESCRIPTION:		COND,ACSR RAIL 29.59D UNGRS D3136							
TECH. DESCRIPTION: ALUMINIUM CONDUCTOR STEEL REINFORCED * 45 ALUMINIUM STRANDS OF 3.70mm DIA * 7 STEEL STRAND OF 2.47mm DIA. * CONDUCTOR 29.59mm DIA. * UNGREASED * CODE NAME RAIL * RATED TENSILE 117kN * ESKOM DRAWING No. D-DT-3136 *									
SAP MATERIAL No.:		0400667							
SHORT DESCRIPTION:		COND,ACSR BERS-FORT 35.58D UNGRS D3136							
TECH. DESCRIPTION: ALUMINIUM CONDUCTOR STEEL REINFORCED * 48 ALUMINIUM STRANDS OF 4.27mm DIA * 7 STEEL STRAND OF 3.32mm DIA. * CONDUCTOR 35.58mm DIA. * UNGREASED * CODE NAME BERS-FORT * RATED TENSILE 177,65kN * ESKOM DRAWING No. D-DT-3136 *									
13	SAP 0014606, 0014443, 0014440, 0014442, 0014441 0014445, 0014697, 0014439, 0014657, 0014677, 0014675, 0014781, 0014752, 00171327, 0014678, 0014580, 0014446, 0014447, 0014452 CORRECTED	P.A.T.	D. RAMJASS	D. RAMJASS	20.01.2017				
12	RAIL CONDUCTOR GREASED AND UNGREASED ADDED AND ESKOM SPEC CHANGED	P.A.T.	B. HILL	M. RAPAPA	07.12.2009				
11	FOX CONDUCTOR GREASED REINSTATED	P.A.T.	M. RAPAPA	M. RAPAPA	07.07.2009				
REV	REVISION DESCRIPTION	BY	CHKD	AUTH	DATE	REF. DWGS			
AUTH:	P.CROWDY	DATE:	17.07.1995	SCALE	 D-DT- 3136	SAP No:			
				NTS		0403025	0245988 0400662 0400669		
CHKD:	J.SWAN	DATE:	17.07.1995	CAD REF:					
				SERIES 3000			SET	SHEET	REV
DRAWN:	P.A.VERMAAK	DATE:	11.05.1995	FILE No:		8	3	13	
				3136					

SPEC SHEET

SAP MATERIAL No.:		0171330	
SHORT DESCRIPTION:		COND,ACSR FOX 8.37D GRS D3136	
TECH. DESCRIPTION:			
ALUMINIUM CONDUCTOR STEEL REINFORCED *			
6 ALUMINIUM STRANDS OF 2.79mm DIA *			
ONE STEEL STRAND OF 2.79mm DIA.* CONDUCTOR 8.378mm DIA. *			
GREASED * CODE NAME FOX * RATED TENSILE STRENGTH 13.1kN *			
ESKOM DRAWING No. D-DT-3136 *			
SAP MATERIAL No.:		0171331	
SHORT DESCRIPTION:		COND,ACSR MINK 10.98D GRS D3136	
TECH. DESCRIPTION:			
ALUMINIUM CONDUCTOR STEEL REINFORCED *			
6 ALUMINIUM STRANDS OF 3.66mm DIA *			
ONE STEEL STRAND OF 3.66mm DIA.* CONDUCTOR 10.98mm DIA. *			
GREASED * CODE NAME MINK * RATED TENSILE STRENGTH 21.9kN *			
ESKOM DRAWING No. D-DT-3136 *			
SAP MATERIAL No.:		0171332	
SHORT DESCRIPTION:		COND,ACSR HARE 14.16D GRS D3136	
TECH. DESCRIPTION:			
ALUMINIUM CONDUCTOR STEEL REINFORCED *			
6 ALUMINIUM STRANDS OF 4.72mm DIA *			
ONE STEEL STRAND OF 4.72mm DIA.* CONDUCTOR 14.16mm DIA. *			
GREASED * CODE NAME HARE * RATED TENSILE STRENGTH 36kN *			
ESKOM DRAWING No. D-DT-3136 *			
SAP MATERIAL No.:		0403150	
SHORT DESCRIPTION:		COND,ACSR WOLF 18.13D GRS D3136	
TECH. DESCRIPTION:			
ALUMINIUM CONDUCTOR STEEL REINFORCED *			
30 ALUMINIUM STRANDS OF 2.59mm DIA *			
7 STEEL STRAND OF 2.59mm DIA.* CONDUCTOR 18.13mm DIA. *			
GREASED * CODE NAME WOLF * RATED TENSILE STRENGTH 69.2kN *			
ESKOM DRAWING No. D-DT-3136 *			
SAP MATERIAL No.:		0171326	
SHORT DESCRIPTION:		COND,ACSR CHICADEE 18.87D GRS D3136	
TECH. DESCRIPTION:			
ALUMINIUM CONDUCTOR STEEL REINFORCED *			
18 ALUMINIUM STRANDS OF 3.77mm DIA *			
ONE STEEL STRAND OF 3.77mm DIA.* CONDUCTOR 18.87mm DIA. *			
GREASED * CODE NAME CHICADEE * RATED TENSILE STRENGTH 44.9kN *			
ESKOM DRAWING No. D-DT-3136 *			

13	SAP 0014606, 0014443, 0014440, 0014442, 0014441 0014445, 0014697, 0014439, 0014657, 0014677, 0014675, 0014781, 0014752, 0171327, 0014678, 0014580, 0014446, 0014447, 0014452 CORRECTED	P.A.T.	D. RAMJASS	D. RAMJASS	20.01.2017			
12	RAIL CONDUCTOR GREASED AND UNGREASED ADDED AND ESKOM SPEC CHANGED	P.A.T.	B. HILL	M. RAPAPA	07.12.2009			
11	FOX CONDUCTOR GREASED REINSTATED	P.A.T.	M. RAPAPA	M. RAPAPA	07.07.2009			
REV	REVISION DESCRIPTION	BY	CHKD	AUTH	DATE	REF. DWGS		
AUTH:	P.CROWDY	DATE:	17.07.1995	SCALE	 D-DT-3136 SAP No: 0171330 0171331 0171332 0403150 0171326 SET 8 SHEET 4 REV 13			
				NTS				
CHKD:	J.SWAN	DATE:	17.07.1995	CAD REF:				
				SERIES 3000				
DRAWN:	P.A.VERMAAK	DATE:	11.05.1995	FILE No:				
				3136				
							SAP No:	
							0171330	
							0171331	
							0171332	
							0403150	
							0171326	
					SET	SHEET	REV	
					8	4	13	

SPEC SHEET

SAP MATERIAL No.:	0403055							
SHORT DESCRIPTION:	COND,ACSR BEAR 23.45D GRS D3136							
TECH. DESCRIPTION:								
ALUMINIUM CONDUCTOR STEEL REINFORCED * 30 ALUMINIUM STRANDS OF 3.35mm DIA * 7 STEEL STRAND OF 3.35mm DIA * CONDUCTOR 23.45mm DIA. * GREASED * CODE NAME BEAR * RATED TENSILE STRENGTH 112kN * ESKOM DRAWING No. D-DT-3136 *								
SAP MATERIAL No.:	0401188							
SHORT DESCRIPTION:	COND,ACSR KINGBIRD 23.90D GRS D3136							
TECH. DESCRIPTION:								
ALUMINIUM CONDUCTOR STEEL REINFORCED * 18 ALUMINIUM STRANDS OF 4.78mm DIA * ONE STEEL STRAND OF 4.78mm DIA * CONDUCTOR 23.90mm DIA. * GREASED * CODE NAME KINGBIRD * RATED TENSILE STRENGTH 71.32kN * ESKOM DRAWING No. D-DT-3136 *								
SAP MATERIAL No.:	0400671							
SHORT DESCRIPTION:	COND,ACSR TERN 27.00D GRS D3136							
TECH. DESCRIPTION:								
ALUMINIUM CONDUCTOR STEEL REINFORCED * 45 ALUMINIUM STRANDS OF 3.38mm DIA * 7 STEEL STRAND OF 2.25mm DIA * CONDUCTOR 27.00mm DIA. * GREASED * CODE NAME TERN * RATED TENSILE STRENGTH 98.7kN * ESKOM DRAWING No. D-DT-3136 *								
SAP MATERIAL No.:	0245989							
SHORT DESCRIPTION:	COND,ACSR RAIL 29.59D GRS D3136							
TECH. DESCRIPTION:								
ALUMINIUM CONDUCTOR STEEL REINFORCED * 45 ALUMINIUM STRANDS OF 3.70mm DIA * 7 STEEL STRAND OF 2.47mm DIA. * CONDUCTOR 29.59mm DIA. * GREASED * CODE NAME RAIL * RATED TENSILE 117kN * ESKOM DRAWING No. D-DT-3136 *								
13	SAP 0014606, 0014443, 0014440, 0014442, 0014441 0014445, 0014697, 0014439, 0014657, 0014677, 0014675, 0014781, 0014752, 0171327, 0014678, 0014580, 0014446, 0014447, 0014452 CORRECTED		P.A.T.	D. RAMJASS	D. RAMJASS	20.01.2017		
12	RAIL CONDUCTOR GREASED AND UNGREASED ADDED AND ESKOM SPEC CHANGED		P.A.T.	B. HILL	M. RAPAPA	07.12.2009		
11	FOX CONDUCTOR GREASED REINSTATED		P.A.T.	M. RAPAPA	M. RAPAPA	07.07.2009		
REV	REVISION DESCRIPTION		BY	CHKD	AUTH	DATE		
AUTH:	P.CROWDY	DATE:	17.07.1995	 D-DT-3136		SAP No:		
CHKD:	J.SWAN	DATE:	17.07.1995			0403055	0400671	
						0401188	0245989	
						SET	SHEET	REV
DRAWN:	P.A.VERMAAK	DATE:	11.05.1995			8	5	13

Unique Identifier:240-48887441

Revision 1

SPEC SHEET

SAP MATERIAL No.:		0174614	
SHORT DESCRIPTION:		COND,AAAC ACACIA 6.24D GRS D3136	
TECH. DESCRIPTION:			
ALL ALUMINIUM ALLOY CONDUCTOR *			
7 STRANDS OF 2.08mm DIA * CONDUCTOR 6.24mm DIA. *			
GREASED * CODE NAME ACACIA *			
RATED TENSILE STRENGTH 6.69kN *			
ESKOM DRAWING No. D-DT-3136 *			
SAP MATERIAL No.:		0174613	
SHORT DESCRIPTION:		COND,AAAC 35 8.31D GRS D3136	
TECH. DESCRIPTION:			
ALL ALUMINIUM ALLOY CONDUCTOR *			
7 STRANDS OF 2.77mm DIA * CONDUCTOR 8.31mm DIA. *			
GREASED * CODE NAME 35 *			
RATED TENSILE STRENGTH 11.86kN *			
ESKOM DRAWING No. D-DT-3136 *			
SAP MATERIAL No.:		0174612	
SHORT DESCRIPTION:		COND,AAAC PINE 10.83D GRS D3136	
TECH. DESCRIPTION:			
ALL ALUMINIUM ALLOY CONDUCTOR *			
7 STRANDS OF 3.61mm DIA * CONDUCTOR 10.83mm DIA. *			
GREASED * CODE NAME PINE *			
RATED TENSILE STRENGTH 20.2kN *			
ESKOM DRAWING No. D-DT-3136 *			
SAP MATERIAL No.:		0403107	
SHORT DESCRIPTION:		COND,AAAC OAK 13.95D GRS D3136	
TECH. DESCRIPTION:			
ALL ALUMINIUM ALLOY CONDUCTOR *			
7 STRANDS OF 4.65mm DIA * CONDUCTOR 13.95mm DIA. *			
GREASED * CODE NAME OAK *			
RATED TENSILE STRENGTH 33.33kN *			
ESKOM DRAWING No. D-DT-3136 *			

13	SAP 0014606, 0014443, 0014440, 0014442, 0014441 0014445, 0014697, 0014439, 0014657, 0014677, 0014675, 0014781, 0014752, 00171327, 0014678, 0014580, 0014446,0014447, 0014452 CORRECTED	P.A.T.	D. RAMJASS	D. RAMJASS	20.01.2017	
12	RAIL CONDUCTOR GREASED AND UNGREASED ADDED AND ESKOM SPEC CHANGED	P.A.T.	B. HILL	M. RAPAPA	07.12.2009	
11	FOX CONDUCTOR GREASED REINSTATED	P.A.T.	M. RAPAPA	M. RAPAPA	07.07.2009	
REV	REVISION DESCRIPTION	BY	CHKD	AUTH	DATE	REF. DWGS
AUTH:	P.CROWDY	DATE:	17.07.1995	 D-DT- 3136	SAP No:	
CHKD:	J.SWAN	DATE:	17.07.1995		0174614	0174612
					0174613	0403107
DRAWN:	P.A.VERMAAK	DATE:	11.05.1995		SET	SHEET
				8	6	13

SPEC SHEET

SAP MATERIAL No.:		0403039					
SHORT DESCRIPTION:		COND,AAC HORNET 16.25D UNGRS D3136					
TECH. DESCRIPTION:							
ALL ALUMINIUM CONDUCTOR *							
19 ALUMINIUM STRANDS OF 3.25mm DIA *							
CONDUCTOR 16.25mm DIA. *							
UNGREASED * CODE NAME HORNET * RATED TENSILE STRENGTH 26kN *							
ESKOM DRAWING No. D-DT-3136 *							
SAP MATERIAL No.:		0403041					
SHORT DESCRIPTION:		COND,AAC CENTIPEDE 26.46D UNGRS D3136					
TECH. DESCRIPTION:							
ALL ALUMINIUM CONDUCTOR *							
37 ALUMINIUM STRANDS OF 3.78mm DIA *							
CONDUCTOR 26.46mm DIA. * UNGREASED *							
CODE NAME CENTIPEDE * RATED TENSILE STRENGTH 67.2kN *							
ESKOM DRAWING No. D-DT-3136 *							
SAP MATERIAL No.:		0403047					
SHORT DESCRIPTION:		COND,AAC BULL 38.25D UNGRS D3136					
TECH. DESCRIPTION:							
ALL ALUMINIUM CONDUCTOR *							
61 ALUMINIUM STRANDS OF 4.25mm DIA *							
CONDUCTOR 38.25mm DIA. *							
UNGREASED * CODE NAME BULL * RATED TENSILE STRENGTH 139kN *							
ESKOM DRAWING No. D-DT-3136 *							

13	SAP 0014606, 0014443, 0014440, 0014442, 0014441 0014445, 0014697, 0014439, 0014657, 0014677, 0014675, 0014781, 0014752, 0171327, 0014678, 0014580, 0014446,0014447, 0014452 CORRECTED	P.A.T.	D. RAMJASS	D. RAMJASS	20.01.2017			
12	RAIL CONDUCTOR GREASED AND UNGREASED ADDED AND ESKOM SPEC CHANGED	P.A.T.	B. HILL	M. RAPAPA	07.12.2009			
11	FOX CONDUCTOR GREASED REINSTATED	P.A.T.	M. RAPAPA	M. RAPAPA	07.07.2009			
REV	REVISION DESCRIPTION	BY	CHKD	AUTH	DATE	REF. DWGS		
AUTH:	P.CROWDY	DATE:	17.07.1995	 Eskom		SAP No:		
CHKD:	J.SWAN	DATE:	17.07.1995			0403039		0403047
DRAWN:	P.A.VERMAAK	DATE:	11.05.1995			0403041		
				D-DT- 3136		SET	SHEET	REV
						8	7	13

SPEC SHEET

SAP MATERIAL No.:		0403059	
SHORT DESCRIPTION:		COND,AAC HORNET 16.25D INSU UNGRS D3136	
TECH. DESCRIPTION:			
ALL ALUMINIUM CONDUCTOR *			
19 ALUMINIUM STRANDS OF 3.25mm DIA *			
PVC INSULATED 5mm THICK (COVERED) * CONDUCTOR 16.25mm DIA. *			
UNGREASED * CODE NAME HORNET * RATED TENSILE STRENGTH 26kN *			
ESKOM DRAWING No. D-DT-3136 *			
SAP MATERIAL No.:		0403061	
SHORT DESCRIPTION:		COND,AAC CENT 26.46D INSU UNGRS D3136	
TECH. DESCRIPTION:			
ALL ALUMINIUM CONDUCTOR *			
37 ALUMINIUM STRANDS OF 3.78mm DIA *			
PVC INSULATED 5mm THICK (COVERED) * CONDUCTOR 26.46mm DIA. *			
UNGREASED * CODE NAME CENTIPEDE * RATED TENSILE STRENGTH 67.2kN *			
ESKOM DRAWING No. D-DT-3136 *			
SAP MATERIAL No.:		0403063	
SHORT DESCRIPTION:		COND,AAC BULL 38.25D INSU UNGRS D3136	
TECH. DESCRIPTION:			
ALL ALUMINIUM CONDUCTOR *			
61 ALUMINIUM STRANDS OF 4.25mm DIA *			
PVC INSULATED 5mm THICK (COVERED) * CONDUCTOR 38.25mm DIA. *			
UNGREASED * CODE NAME BULL * RATED TENSILE STRENGTH 139kN *			
ESKOM DRAWING No. D-DT-3136 *			

13	SAP 0014606, 0014443, 0014440, 0014442, 0014441 0014445, 0014697, 0014439, 0014657, 0014677, 0014675, 0014781, 0014752, 0171327, 0014678, 0014580, 0014446,0014447, 0014452 CORRECTED	P.A.T.	D. RAMJASS	D. RAMJASS	20.01.2017		
12	RAIL CONDUCTOR GREASED AND UNGREASED ADDED AND ESKOM SPEC CHANGED	P.A.T.	B. HILL	M. RAPAPA	07.12.2009		
11	FOX CONDUCTOR GREASED REINSTATED	P.A.T.	M. RAPAPA	M. RAPAPA	07.07.2009		
REV	REVISION DESCRIPTION	BY	CHKD	AUTH	DATE	REF. DWGS	
AUTH:	P.CROWDY	DATE:	17.07.1995	 D-DT- 3136	SAP No:		
CHKD:	J.SWAN	DATE:	17.07.1995		0014759		0014761
					0014760		
DRAWN:	P.A.VERMAAK	DATE:	11.05.1995		SET	SHEET	REV
				8	8	13	