

Item	Description	Activity category Where will item be used (so you can link to WBS element)	QTY	Unit	Unit/Allowable Cost Price	Total Value Ex. Vat
1	P1000 CHANNEL 6M HDG	U5-6	26	Each		
2	CSN106/EG SPRING NUT LONG M6 EG	U5-6	2400	Each		
3	HEX SET SCREW GR 4.8 M06 X 35MM EG	U5-6	2400	Each		
4	SPRING WASHER DIN7980 M06 EG	U5-6	2400	Each		
5	WM 4PCE JOINER CLAMP SET COMPL HDG	U5-6	2160	Each		
6	WWMD 100MM STR 100 X 50 3M HDG	U5-6	572	Each		
7	WWMD 200MM STR 100 X 50 3M HDG	U5-6	168	Each		
8	WM FLUSH HOLD DOWN SADDLE 8.5MM HDG	U5-6	1440	Each		
9	WM 2PCE JOINER CLAMP SET SG	U5-6	480	Each		
10	AEROCOAT ZINCDEK SHINY GALV SPRAY 400ML	U5-6	72	Each		
11	P1271 BEAM CLAMP ONLY HDG	U5-6	400	Each		
12	CONE POINT SCREW M12 X 45MM EG	U5-6	400	Each		
13	P1272 BEAM CLAMP ONLY HDG	U5-6	400	Each		
14	CONE POINT SCREW M10 X 45MM EG	U5-6	1000	Each		
15	HEX SET SCREW GR 4.8 M10 X 35MM EG	U5-6	1000	Each		
16	CSN110/EG SPRING NUT LONG M10 EG	U5-6	1000	Each		
17	P1063 FLAT FITTING 11MM HDG	U5-6	300	Each		
18	Supply and Delivery of Instrument cabling, type: UVG02 ACM: Low Halogen, Flame Retardant Polyvinyl Chloride (LH PVC)	U5-6	8000	m		
19	BB24MM1.50-21-24 WAY Sequential Controller	U5-6	4	Each		
20	Emission controller Probe Turbo-check 4-20mA with BS400 – Gas temp socket, Inter-Connecting Data Cable for Probe and Controller – 20m	U5-6	4	Each		
21	KUNKLE VALVE PRV 3" PRESSURE RELIEF VALVE	U5-6	14	Each		
22	8mm Dekabon Tubing, Ø D 8mm and Ø d 5.3mm	U5-6	9000	m		
23	12mm Dekabon Tubing, Ø D 12mm and Ø d 8.2mm	U5-6	9000	m		
24	¼ Male to 8mm Tube- Pneumatic Push in Fitting (Composite -Nickel Plated)	U5-6	600	Each		
25	1/2 Male to 12mm Tube- Pneumatic Push in Fitting (Composite -Nickel Plated)	U5-6	160	Each		
26	¾ Male to 12mm Tube- Pneumatic Push in Fitting (Composite Nickel Plated)	U5-6	160	Each		
27	12 to 8mm Reducer -Push in connector	U5-6	160	Each		
28	8mm Tube Tee -Push in Connector	U5-6	160	Each		
29	12mm Tube Tee-Push in connector	U5-6	160	Each		
30	8mm to 6mm -Push in Connector	U5-6	40	Each		
31	8mm Straight -Push in Connector	U5-6	40	Each		
32	12mm Straight-Push in Connector	U5-6	60	Each		
33	1/8 Male to 8mm Tube- Pneumatic Push in Fitting (Composite Nickel Plated)	U5-6	60	Each		


K MOTHATA


T NGWENYA