

Short Text	Long Text	Quantity requested (36 Months)	Unit of Measure
PROTECTOR HEARNG:EARPLUG;92-102 DB	PROTECTOR, HEARING: TYPE: EARPLUG; MATERIAL: POLYMER NON ALLERGENIC; NOISE REDUCTION RATING: 92-102 DB; SPECIFICATION: 240-44175132; EARPLUG RE-USABLE CORDED WOVEN NYLON WITH CARRYING CASE AND CHAIN CONTOURED 4 FLANGE ULTRA-SOFT POLYMER DESIGN; UNIVERSAL SIZE SELF CONTOUR TO FIT ANY EAR CANAL; NON ALLERGENIC POLYMER MATERIAL; 25 NNR ANSI AND 26 SNR CE PROTECTION LEVEL 92-102DB	47 429	EA
PROTECTOR HEARNG:EARMUFF;CUSHIONS	PROTECTOR, HEARING: TYPE: EARMUFF; EARCUP FORM: CUSHIONS; SPECIFICATION: 240-44575132; EARMUFF HIGH PERFORMANCE SMART FOLD OUT DESIGN DI-ELECTRIC CONSTRUCTION; MULTI POSITION USE WITHOUT SUPPORT; SELF-ALIGNING SUSPENSION; SOFT PLIABLE SUPER SEAL EAR CUSHIONS FOR LONG LASTING AND RESISTANT AGAINST BODY OIL AND SWEAT COLOUR BLACK/RED COMPLY TO CE SNR30 NRR28	4 600	EA
PROTECTOR HEARNG:EARPLUG;PU FOAM	PROTECTOR, HEARING: TYPE: EARPLUG; MATERIAL: PU FOAM; NOISE REDUCTION RATING: 96-106 DB; SPECIFICATION: 240-44175132; UNI-FIT DISPOSABLE FOAM EARPLUG; SOFT TAPERED SLOW EXPANDING POLYURETHANE FOAM; TAPERED WITH LONGER THINNER TIP; CORDED PVC CORD COLOUR ORANGE 32 NRR ANSI 37 SNR CE PROTECTION LEVEL 96-106 DB	32 402	EA

#### Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

SPECTACLE SFTY:WRAP AROUND;CLEAR;48 MM	SPECTACLE, SAFETY: TYPE: WRAP AROUND; LENS COLOR: CLEAR; LENS SIZE: 48 MM; TEMPLE SIZE: ADJUSTABLE; SIDE SHIELDS: VENTILATED; WRAP AROUND BALLISTIC PROTECTION HARS INDUSTRIAL ENVIROMENTS; FRAME COLOUR BLACK VENTED; LENS TINT CLEAR; LENS COATING SUPERCOAT TM AF; TEMPLE STYLE DROP WITH ADJUSTABLE LENGTHS; SOFT SELF-FITTING RUBBER NOSE BRIDGE; TEMPLE TO ADJUST TO 4 DIFFERENT LENGTHS; SUPERCOAT PROTECTION WITH ANTI-FOG; ANTI SCRATCH; ANTI-STATIC AND UV PROTECTION 100% ULTRAVIOLET PROTECTION; COMPLY TO ANSI Z87.1; MEET TRAFIC SIGNAL COLOR RECOGNITION REQUIREMENTS OF ANSI Z80.3-1996; EN-166; BALLISTIC RATED TO MIL PRF-31013 REQUIREMENT OF 360 FEET PER SECOND; UNIQUE IDENTIFIER 240-44175132	83 401	PAA
GOGGLES INDSTRL:DUST/MIST;GRAY;PLASTIC	GOGGLES, INDUSTRIAL: TYPE: DUST/MIST; LENS COLOR: GRAY; LENS TYPE: ANTI FOG/SCRATCH; FRAME MATERIAL: PLASTIC; APERTURE ELEMENT TYPE: VENTILATION; IMPACT SPLASH DUST AND MIST RESISTANT; MOLDED LENS AND ANTI-FOG COATING TO ANSI D3 D4; FRAME COLOUR SMOKE; LENS COATING ANTI FOG ANTI SCRATCH; TEMPLE STYLE EXTRA WIDE ADJUSTABLE FABRIC STRAP WITH D SLIDES COMPLY TO ANSI Z87.1 EN 166; UNIQUE IDENTIFIER 240-44175132	936	EA
SPECTACLE SFTY:GAS WELDING;GREEN;STD	SPECTACLE, SAFETY: TYPE: GAS WELDING; LENS COLOR: GREEN; LENS SIZE: STD; TEMPLE SIZE: ADJUSTABLE; SIDE SHIELDS: DROP; FRAME COLOUR BLACK; LENS TINT WELDING SHADE 5.0; LENS COATING HARD COAT; ADJUSTABLE DROP TEMPLE; TEMPLE STYLE DROP WITH ADJUSTABLE LENGTH; UNIVERSAL NOSE BRIDGE; COMPLY TO ANSI Z87; UNIQUE IDENTIFIER 240-44175132	465	EA

### Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

PROTECTOR:SHOE;LG 320 X HT 250 MM	PROTECTOR: TYPE: SHOE; DIMENSIONS: LG 320 X HT 250 MM; MATERIAL: LEATHER COWHIDE; SPECIFICATION: UNIQUE IDENTIFIER 240-44157132; REFERENCE NO: CSP, UNK; WITH SELF GRIP BACK FASTENER, UNDER STRAP	93	PAA
GOGGLES INDSTRL:DUST/MIST;CLEAR;PLASTIC	GOGGLES, INDUSTRIAL: TYPE: DUST/MIST; LENS COLOR: CLEAR; LENS TYPE: ANTI FOG/SCRATCH; FRAME MATERIAL: PLASTIC; IMPACT SPLASH DUST AND MIST RESISTANT; MOLDED LENS AND ANTI-FOG COATING TO ANSI D3 D4; FRAME COLOUR SMOKE; LENS COATING ANTI FOG ANTI SCRATCH; TEMPLE STYLE WIDER ADJUSTABLE FABRIC STRAP WITH D SLIDES COMPLY TO ANSI Z87.1 EN 166; UNIQUE IDENTIFIER 240-44175132	10 916	EA
SHIELD SFTY EQP:FACE PROTECTOR LV;CLEAR	SHIELD, SAFETY EQUIPMENT: TYPE: FACE PROTECTOR LV; DIMENSIONS: WD 205 X LG 310 X THK 1 MM; COLOR: CLEAR; MATERIAL: POLYCARBONATE; FOR LV (LOW VOLTAGE) SWITCHING; PROTECTION AGAINST ELECTRICAL BURNS AND FLASHES; UNIVERSAL FITTING ADJUSTABLE; TEST/CERT; IDENTIFICATION AND SPECIFICATION REQUIREMENTS; ANTIFOG COATING; PROTECTION BAG; COMPLY WITH CATEGORY 1 OF NFPA70E-2000 MIN ATPV PERFORMANCE 5 CAL/CM2; UNIQUE IDENTIFIER 240-44175132	1 027	EA
VEST HIGH VIS:EMPLOYEE AT WORK;S;NYLON	VEST, HIGH VISIBILITY: TYPE: EMPLOYEE AT WORK; SIZE: S; MATERIAL: NYLON; COLOR: ORANGE LIGHT B26 NCS-1673-Y48R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A4 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A4; POCKET TYPE: LEFT TOP; EMPLOYEE AT WORK TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO	3 957	EA

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

	<p>ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A4; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A4 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS</p>		
VEST HIGH VIS:EVACUATION;S;NYLON	<p>VEST, HIGH VISIBILITY: TYPE: EVACUATION; SIZE: S; MATERIAL: NYLON; COLOR: WHITE CLOUD G80 NCS0704G28Y; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; EVACUATION CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND</p>	300	EA

### Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

	SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS		
VEST HIGH VIS:EVACUATION;M;NYLON	VEST, HIGH VISIBILITY: TYPE: EVACUATION; SIZE: M; MATERIAL: NYLON; COLOR: WHITE CLOUD G80 NCS0704G28Y; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; EVACUATION CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS	377	EA
VEST HIGH VIS:EVACUATION;L;NYLON	VEST, HIGH VISIBILITY: TYPE: EVACUATION; SIZE: L; MATERIAL: NYLON; COLOR: WHITE CLOUD G80 NCS0704G28Y; GARMENT CLOSING METHOD: ZIP FASTENER	355	EA

#### Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

	WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; EVACUATION CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS		
VEST HIGH VIS:EVACUATION;XL;NYLON	VEST, HIGH VISIBILITY: TYPE: EVACUATION; SIZE: XL; MATERIAL: NYLON; COLOR: WHITE CLOUD G80 NCS0704G28Y; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; EVACUATION CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY	250	EA

#### Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

	AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS		
VEST HIGH VIS:EVACUATION;2XL;NYLON	VEST, HIGH VISIBILITY: TYPE: EVACUATION; SIZE: 2XL; MATERIAL: NYLON; COLOR: WHITE CLOUD G80 NCS0704G28Y; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; EVACUATION CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE	200	EA

### Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.



## Appendix A

### BOM for PPE Accessories

	IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS		
VEST HIGH VIS:EVACUATION;3XL;NYLON	VEST, HIGH VISIBILITY: TYPE: EVACUATION; SIZE: 3XL; MATERIAL: NYLON; COLOR: WHITE CLOUD G80 NCS0704G28Y; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; EVACUATION CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS	20	EA
HOOD SFTY:ARC FLASH CL2;PROTERA ATPV	HOOD, SAFETY: TYPE: ARC FLASH CL2; DIMENSIONS: WD 485 X LG 500 X THK 2 MM; MATERIAL: PROTERA ATPV; SUPPL P/N: 60091616831798; COLOUR 8 CAL/CM2VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	20	EA

#### Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.



HELMET SFTY:ARC FLASH;WHITE	HELMET, SAFETY: TYPE: ARC FLASH; COLOR: WHITE; SUPPL P/N: 6009161831750; COMPLY WITH ARC PPE SPECIFICATIONS 240-70044736	30	EA
COVERALLS:DISPOSABLE;L;WHITE	COVERALLS, SAFETY, INDUSTRIAL: TYPE: DISPOSABLE; COMMERCIAL SIZE: L; MATERIAL: POLYETHYLENE LAMINATED; COLOR: WHITE; CLOSURE METHOD: ZIP; EXTENDED WASTE TO THE NECK; HEAD PROTECTION WITH CHIN FASTENING; SPECIAL FEATURES: BREATHABLE; SPECIFICATION: 240-160125821; STANDARD: SANS 434; EN ISO 13982:1 2004; SANS 18822; EN 14325; ALL SLEEVES AND ANKLE CUFFS SHALL BE FITTED WITH ELASTIC BANDS; THE HOOD SHALL HAVE AN ELASTIC BAND STITCHED INTO THE EDGES OF THE HOOD; THE COVERALL MUST HAVE A HIGH NECKLINE; DISPOSABLE COVERALL MUST PROTECT AGAINST FIBRES DOWN TO 0.7 MICRONS; FULL BODY CHEMICAL PROTECTIVE CLOTHING AGAINST LIQUIDS AND SOLID PARTIALS; MATERIAL MUST ABLE TO WITHSTAND DUST, OIL, ACID AND CHEMICAL EXPOSURE	49 429	EA
SPECTACLE SFTY:PROTECTIVE;DARK	SPECTACLE, SAFETY: TYPE: PROTECTIVE; LENS COLOR: DARK; LENS SIZE: WD 145 X THK 2.1 MM; TEMPLE SIZE: LG 115 MM; SIDE SHIELDS: WRAP-AROUND; SPECIFICATION: EN166:2001; REFERENCE NO: 1015367	11 710	EA
LENS SFTY EQP:WELDING;CLEAR;GLASS	LENS, SAFETY EQUIPMENT: TYPE: WELDING; SHADE: CLEAR; MATERIAL: GLASS; DIMENSIONS: WD 50 X LG 108 MM	461	EA
COVERALL:DISPOSABLE WHEATHER CAP;2XL	COVERALL: TYPE: DISPOSABLE WHEATHER CAP; SIZE: 2XL	13 500	EA
RETAINER:PRE-FILTER;DIA 92 X THK 34 MM	RETAINER: TYPE: PRE-FILTER; DIMENSIONS: DIA 92 X THK 34 MM; MATERIAL: PLASTIC; SPECIFICATION: EN 141 / EN 143; REFERENCE NO: 1001590	810	EA
MASK RSPTR:HALF DISPOSABLE;ADJUSTABLE	MASK, RESPIRATOR: DESIGN FORM: HALF DISPOSABLE;	296 810	EA

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

	USAGE DESIGN: DUST/MIST/BIO AGENTS; SIZE: ADJUSTABLE; MATERIAL: POLYPROPYLENE NON WOVEN FIBERS; COLOR: GRAY; MANUF P/N: FFP2; REFERENCE NO: 1005600; CHARCOAL COATED; WITH VALVE; THE PRODUCT MUST MEET THE REQUIREMENTS OF EN149:2001; A1:2009 AND SANS 50149:2003; ISO 9001:2015; HOMOLOGATION CERTIFICATE WILL BE REQUIRED WITH QUOTATION		
COVER:OVERSHOE DISPOSABLE;L;PVC;BLUE	COVER: TYPE: OVERSHOE DISPOSABLE; DIMENSIONS: L; MATERIAL: PVC; COLOR: BLUE; APPLICATION: CLEAN ROOM CONDITIONS; SPECIFICATION: ANTI SLIP SOLE; ANTI STATIC	17 218	EA
COVERALLS:DISPOSABLE;M;WHITE	COVERALLS, SAFETY, INDUSTRIAL: TYPE: DISPOSABLE; COMMERCIAL SIZE: M; MATERIAL: POLYETHYLENE LAMINATED; COLOR: WHITE; CLOSURE METHOD: ZIP; EXTENDED WASTE TO THE NECK; HEAD PROTECTION WITH CHIN FASTENING; SPECIAL FEATURES: BREATHABLE; SPECIFICATION: 240-160125821; STANDARD: SANS 434; EN ISO 13982:1 2004; SANS 18822; EN 14325; ALL SLEEVES AND ANKLE CUFFS SHALL BE FITTED WITH ELASTIC BANDS; THE HOOD SHALL HAVE AN ELASTIC BAND STITCHED INTO THE EDGES OF THE HOOD; THE COVERALL MUST HAVE A HIGH NECKLINE; DISPOSABLE COVERALL MUST PROTECT AGAINST FIBRES DOWN TO 0.7 MICRONS; FULL BODY CHEMICAL PROTECTIVE CLOTHING AGAINST LIQUIDS AND SOLID PARTIALS; MATERIAL MUST ABLE TO WITHSTAND DUST, OIL, ACID AND CHEMICAL EXPOSURE	27 722	EA
COVERALLS:DISPOSABLE;XL;WHITE	COVERALLS, SAFETY, INDUSTRIAL: TYPE: DISPOSABLE; COMMERCIAL SIZE: XL; MATERIAL: POLYETHYLENE LAMINATED; COLOR: WHITE; CLOSURE METHOD: ZIP; EXTENDED WASTE TO THE NECK; HEAD PROTECTION WITH CHIN FASTENING; SPECIAL FEATURES: BREATHABLE; SPECIFICATION: 240-160125821; STANDARD: SANS 434; EN	32 154	EA

#### Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

	ISO 13982:1 2004; SANS 18822; EN 14325; ALL SLEEVES AND ANKLE CUFFS SHALL BE FITTED WITH ELASTIC BANDS; THE HOOD SHALL HAVE AN ELASTIC BAND STITCHED INTO THE EDGES OF THE HOOD; THE COVERALL MUST HAVE A HIGH NECKLINE; DISPOSABLE COVERALL MUST PROTECT AGAINST FIBRES DOWN TO 0.7 MICRONS; FULL BODY CHEMICAL PROTECTIVE CLOTHING AGAINST LIQUIDS AND SOLID PARTIALS; MATERIAL MUST ABLE TO WITHSTAND DUST, OIL, ACID AND CHEMICAL EXPOSURE		
GOGGLES INDSTRL:DUST/GRINDING;SMOKE	GOGGLES, INDUSTRIAL: TYPE: DUST/GRINDING; LENS COLOR: SMOKE; LENS TYPE: IMPACT RESISTANCE; FRAME MATERIAL: PLASTIC; SUPPL P/N: GG-25C-AF-AS	700	EA
MASK RSPTR:HALF FACE;DUST/VAPOURS;L	MASK, RESPIRATOR: DESIGN FORM: HALF FACE; USAGE DESIGN: DUST/VAPOURS; SIZE: L; MATERIAL: HIGH-GRADE SILICONE; COLOR: PURPLE; REFERENCE NO: 1001576	1 211	EA
MASK RSPTR:HALF DISPOSABLE;ADJUSTABLE	MASK, RESPIRATOR: DESIGN FORM: HALF DISPOSABLE; USAGE DESIGN: DUST/MIST/BIO AGENTS; SIZE: ADJUSTABLE; MATERIAL: POLYPROPYLENE NON WOVEN FIBERS; COLOR: WHITE; MANUF P/N: FFP2; WITHOUT VALVE; THE PRODUCT MUST MEET THE REQUIREMENTS OF EN149:2001; A1:2009 AND SANS 50149:2003; ISO 9001:2015; HOMOLOGATION CERTIFICATE WILL BE REQUIRED WITH QUOTATION	899 421	EA
HELMET SFTY:HEIGHT THREE POINT;WHITE	HELMET, SAFETY: TYPE: HEIGHT THREE POINT; SIZE: 530-630 MM; MATERIAL: PLASTIC MOLDED; COLOR: WHITE; SPECIFICATION: SANS 1397:2003; SPECIAL FEATURES: SHORT PEAK; ALL HARD HATS MUST BE IN ACCORDANCE WITH SANS 1397:2003 AND ESKOM SPECIFICATION; SUPPLIED WITH A BLACK ADJUSTABLE THREE POINT CHIN STRAP; MINIMUM HARD HAT ELECTRICAL INSULATION: 440 VAC; WITH A SHORTER PEAK AND A LIMITED SIDE BRIM;	17 654	EA

#### Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

	ITEM TO BE MARKED WITH SABS MARK OF APPROVAL; APPROVED ESKOM LOGO AND A ZERO HARM SLOGAN MUST BE POSITIONED ACCORDING TO THE ESKOM SPECIFICATION AND BE INLINE WITH THE CORPORATE IDENTITY PROCEDURE; WHITE REFLECTIVE AND BLUE LETTERS EUROP ASSIST EMERGENCY NO 086 123 7566 MUST BE DISPLAYED ON THE BACK OF THE HELMETS		
VEST HIGH VIS:EMPLOYEE AT WORK;M;NYLON	VEST, HIGH VISIBILITY: TYPE: EMPLOYEE AT WORK; SIZE: M; MATERIAL: NYLON; COLOR: ORANGE LIGHT B26 NCS-1673-Y48R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A4 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A4; POCKET TYPE: LEFT TOP; EMPLOYEE AT WORK TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A4; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A4 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS	5 695	EA
VEST HIGH VIS:EMPLOYEE AT WORK;L;NYLON	VEST, HIGH VISIBILITY: TYPE: EMPLOYEE AT WORK; SIZE: L;	5 460	EA

### Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

	MATERIAL: NYLON; COLOR: ORANGE LIGHT B26 NCS-1673-Y48R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A4 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A4; POCKET TYPE: LEFT TOP; EMPLOYEE AT WORK TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A4; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A4 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS		
VEST HIGH VIS:EMPLOYEE AT WORK;XL;NYLON	VEST, HIGH VISIBILITY: TYPE: EMPLOYEE AT WORK; SIZE: XL; MATERIAL: NYLON; COLOR: ORANGE LIGHT B26 NCS-1673-Y48R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A4 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A4; POCKET TYPE: LEFT TOP; EMPLOYEE AT WORK TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO	3 465	EA

### Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

	SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A4; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A4 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS		
VEST HIGH VIS:EMPLOYEE AT WORK;2XL;NYLON	VEST, HIGH VISIBILITY: TYPE: EMPLOYEE AT WORK; SIZE: 2XL; MATERIAL: NYLON; COLOR: ORANGE LIGHT B26 NCS-1673-Y48R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A4 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A4; POCKET TYPE: LEFT TOP; EMPLOYEE AT WORK TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A4; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS	1 645	EA

### Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom RoteK Industries SOC Ltd.

	50471 AND FIGURE A4 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS		
VEST HIGH VIS:EMPLOYEE AT WORK;3XL;NYLON	VEST, HIGH VISIBILITY: TYPE: EMPLOYEE AT WORK; SIZE: 3XL; MATERIAL: NYLON; COLOR: ORANGE LIGHT B26 NCS-1673-Y48R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A4 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A4; POCKET TYPE: LEFT TOP; EMPLOYEE AT WORK TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A4; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A4 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS	680	EA
VEST HIGH VIS:EMPLOYEE AT WORK;4XL;NYLON	VEST, HIGH VISIBILITY: TYPE: EMPLOYEE AT WORK; SIZE: 4XL; MATERIAL: NYLON; COLOR: ORANGE LIGHT B26 NCS-1673-Y48R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON	241	EA

#### Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

	CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A4 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A4; POCKET TYPE: LEFT TOP; EMPLOYEE AT WORK TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A4; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A4 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS		
VEST HIGH VIS:EMPLOYEE AT WORK;5XL;NYLON	VEST, HIGH VISIBILITY: TYPE: EMPLOYEE AT WORK; SIZE: 5XL; MATERIAL: NYLON; COLOR: ORANGE LIGHT B26 NCS-1673-Y48R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A4 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A4; POCKET TYPE: LEFT TOP; EMPLOYEE AT WORK TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A4; RELECTIVE	92	EA

### Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.



	TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A4 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS		
VEST HIGH VIS:EMPLOYEE AT WORK;6XL;NYLON	VEST, HIGH VISIBILITY: TYPE: EMPLOYEE AT WORK; SIZE: 6XL; MATERIAL: NYLON; COLOR: ORANGE LIGHT B26 NCS-1673-Y48R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A4 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A4; POCKET TYPE: LEFT TOP; EMPLOYEE AT WORK TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A4; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A4 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE	68	EA

#### Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

	MNFRS. TRADEMARK AND SIZE ON ALL ITEMS		
VISOR:SUN BRIM FOR SAFETY HAT	VISOR: TYPE: SUN BRIM FOR SAFETY HAT; DIMENSIONS: ID 740 X OD 430 MM; MATERIAL: D59 WOVEN COTTON; COLOR: BLUE NAVY; SHAPE OF BRIM TO BE OVAL AND SHALL COMPLY TO THE FOLLOWING FRONT BACK AND NECK PROTECTOR ATTACH TO BOTTOM OF BRIM MATERIAL TYPE D59 FLAME RETARDANT PRE-SHRUNK 100 % WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; SUN BRIM SHALL HAVE A REINFORCED STIFFENED BROAD BRIM OF AT LEAST 90 MM BRIM MALGREY CHIP BOARD MATERIAL 600 TO 800GSM; INSIDE DIAMETER 740MM (FRONT TO BACK 240MM AND SIDE TO SIDE 200MM) OUTSIDE FRONT TO BACK 430MM AND FROM SIDE TO SIDE 380MM; STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS WITH SANS 1362; INSERT FOR HARD HAT FRONT PEAK FLAP CENTRE 130MM AND SIDE FITTED TO OTHER BRIM INSERT FOR HARD HAT REAR SECTION CENTRE 130MM AND SIDES FITTED TO OTHER BRIM; NECK PROTECTOR AT BACK CENTRE 230MM LONG AND SIDES FITTED HALF WAY TO OUTER SUN BRIM PROTECTOR; VELCRO 40 X 25MM ATTACH ON LEFT SIDE OF BRIM AND REAR INSERT OF FLAP FOR STABILITY; UNIQUE IDENTIFIER 240-44175132	1 240	EA
HELMET WELDG:POLYCARBONATE;ADJUSTABLE	HELMET, WELDING: MATERIAL: POLYCARBONATE; FACEPIECE TYPE: ELECTRONIC AUTO-DARKENING FILTER LENS; DIMENSIONS: ADJUSTABLE; AUTO DARKENING FULL WELDING HELMET; ROBUST AND LIGHTWEIGHT; CE EN 175S; EN 329 ANSI; COVERS MAG-MIG COVERED ELECTRODES AND TIG FROM 5 AMPS APPLICATIONS; ENLARGED VIEWING AREA: 98 X 51MM; SHADE; DELAY AND SENSITIVITY MANUAL ADJUSTMENTS; SOLAR CELLS WITH RECHARGEABLE AND INTERCHANGEABLE BATTERIES CR2032; 3D HEAD HARNESS;	10	EA

### Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

	LENS WARRANTY 24 MONTHS; UNIQUE IDENTIFIER 240-44175132		
MASK RSPTR:FULL FACE;CHEMICALS;BLACK	MASK, RESPIRATOR: DESIGN FORM: FULL FACE; USAGE DESIGN: CHEMICALS; SIZE: ADJUSTABLE; COLOR: BLACK; FULL FACE MASK REUSABLE AIR-PURIFYING RESPIRATOR; TIGHT FITTING; 5 POINT; EN 136 CL 2; CE 0158; PART NUMBER D2055790; FP 42; OF CLASSES 1, 2, OR 3 (MASK); HIGHEST STANDARD OF FACE SEAL TO PROTECTS THE EYES; THESE RESPIRATORS FOR USE WITH CHEMICAL CARTRIDGES IN EMERGENCIES; UNIQUE IDENTIFIER 240-44175132	22	EA
COVER:OVERSHOE;M;WHITE;CLEAN ROOM	COVER: TYPE: OVERSHOE; DIMENSIONS: M; MATERIAL: COTTON BULL DENIM 100 PCT; COLOR: WHITE; APPLICATION: CLEAN ROOM; SPECIFICATION: SABS/SANS 20345-2008; RE-WASHABLE; 1.5 MM WHITE NON-SLIP RUBBER SOLE, DOUBLE STITCHING EXSTRA STRONG BRADE THREAD; HIGH ENOUGH TO COVER A BOOT TIPE SAFETY SHOE; SHOE LACE TO KEEP SHOE TIGHT AT ALL TIMES; SUPPLIER NOTE ! THE OVERSHOE MUST CONFORM TO SABS SANS 20345:2008 SECTION 5.3.5 (5.3.5.2 MINIMUM SPEC) TESTED IN ACCORDANCE WITH ISO 20344 SECTION 5.11 AND THE COEFFICIENT OF FRICTION DETERMINED IN ACCORDANCE WITH ISO 13287	8	EA
COVER:OVERSHOE;L;WHITE;CLEAN ROOM	COVER: TYPE: OVERSHOE; DIMENSIONS: L; MATERIAL: COTTON BULL DENIM 100 PCT; COLOR: WHITE; APPLICATION: CLEAN ROOM; SPECIFICATION: SABS/SANS 20345-2008; RE-WASHABLE; 1.5 MM WHITE NON-SLIP RUBBER SOLE, DOUBLE STITCHING EXSTRA STRONG BRADE THREAD; HIGH ENOUGH TO COVER A BOOT TIPE SAFETY SHOE; SHOE LACE TO KEEP SHOE TIGHT AT ALL TIMES; SUPPLIER NOTE ! THE OVERSHOE MUST CONFORM TO SABS	1	EA

### Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

	SANS 20345:2008 SECTION 5.3.5 (5.3.5.2 MINIMUM SPEC) TESTED IN ACCORDANCE WITH ISO 20344 SECTION 5.11 AND THE COEFFICIENT OF FRICTION DETERMINED IN ACCORDANCE WITH ISO 13287		
PROTECTOR HEARNG:RUBBER FOAM/PLASTIC	PROTECTOR, HEARING: TYPE: EARMUFF ELECTRICAL COMMUNICATION; MATERIAL: RUBBER FOAM/PLASTIC; SIZE: MULTI-POSITION; NOISE REDUCTION RATING: SNR 37; EARCUP FORM: CUSHION FOAM FILLED; SPECIFICATION: EN 352-3-2002; SPECIAL FEATURES: BUILT IN COMMUNICATION RADIO; REFERENCE NO: XH001680475; BUILD IN TWO WAY RADIO COMMUNICATION; 8 CHANNNELS; 121 SUBCHANNELS; LEVEL DEPENDENT FUCTION FOR AMBLENTLISTENING; RECHARGEABLE LITHIUM-ION BATTERY WITH 20 HOURS OPERATING SYSTEM; VOICE OPERATION TRANSMISSION; AUTO POWER OFF FUNCTION; BATTERY STATUS INDICATOR; VOICE GUIDED MENU SYSTEM	19	EA
COVERALLS:DISPOSABLE;2XL;WHITE	COVERALLS, SAFETY, INDUSTRIAL: TYPE: DISPOSABLE; COMMERCIAL SIZE: 2XL; MATERIAL: POLYETHYLENE LAMINATED; COLOR: WHITE; CLOSURE METHOD: ZIP; EXTENDED WASTE TO THE NECK; HEAD PROTECTION WITH CHIN FASTENING; SPECIAL FEATURES: BREATHABLE; SPECIFICATION: 240-160125821; STANDARD: SANS 434; EN ISO 13982:1 2004; SANS 18822; EN 14325; ALL SLEEVES AND ANKLE CUFFS SHALL BE FITTED WITH ELASTIC BANDS; THE HOOD SHALL HAVE AN ELASTIC BAND STITCHED INTO THE EDGES OF THE HOOD; THE COVERALL MUST HAVE A HIGH NECKLINE; DISPOSABLE COVERALL MUST PROTECT AGAINST FIBRES DOWN TO 0.7 MICRONS; FULL BODY CHEMICAL PROTECTIVE CLOTHING AGAINST LIQUIDS AND SOLID PARTIALS; MATERIAL MUST ABLE TO WITHSTAND DUST, OIL, ACID AND CHEMICAL EXPOSURE	25 002	EA

#### Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

RETAINER:RESPIRATOR FILTER;PLASTIC	RETAINER: TYPE: RESPIRATOR FILTER; DIMENSIONS: WD 11.4 X LG 21.5 X HT 10.2 MM; MATERIAL: PLASTIC; MANUF P/N: 3M501	620	PAA
RESPIRATOR:HALF FACE;S	RESPIRATOR: TYPE: HALF FACE; USE: ACID GAS/ORGANIC VAPOUR; SIZE: S; MANUF P/N: 3M6100	188	EA
RESPIRATOR:HALF FACE;M	RESPIRATOR: TYPE: HALF FACE; USE: ACID GAS/ORGANIC VAPOUR; SIZE: M; MANUF P/N: 3M6200	421	EA
RESPIRATOR:HALF FACE;L	RESPIRATOR: TYPE: HALF FACE; USE: ACID GAS/ORGANIC VAPOUR; SIZE: L; MANUF P/N: 3M6300	439	EA
HAT:BASEBALL BUMP;6.75 - 7.75 IN	HAT: TYPE: BASEBALL BUMP; SIZE: 6.75 - 7.75 IN; COLOR: NAVY BLUE; MATERIAL: HDPE INNER LINER; D59; TERRY CLOTH SWEATBAND; SHELL FITS MOST 6 PANEL SPORTS CAPS; VENTILATION EYELETS PROMOTE AIR CIRCULATION; METAL FREE; HDPE LINER IS REMOVABLE, SO OUTER CAP IS FULLY WASHABLE AND PLASTIC BRIM; EMBROID WITH THE LATEST ERI LOGO; DESIGN FOR SAFEGUARD AGAINST BUMPING OR SCRATCHING IN AREAS WHERE HARDHATS ARE NOT REQUIRED.	100	EA
SPECTACLE SFTY:ANTI-FOG & ANTI SCRATCH	SPECTACLE, SAFETY: TYPE: ANTI-FOG & ANTI SCRATCH; LENS COLOR: CLEAR; LENS SIZE: STD; TEMPLE SIZE: ADJUSTABLE; SIDE SHIELDS: WRAP-AROUND; SPECIFICATION: ANSI Z87.1-201+, CE EC-166; MANUF P/N: SG-56C-AF; PANTOSCOPIC ANGLE ADJUSTMENT; TOPE VENTED RUBBER BROW GUARD FOR ADDED IMPACT PROTECTION, ALLOWS AIR TO VENT AND REDUCE FOGGING; ADJUSTABLE 3-LENGTH DROP TEMPLES WITH RUBBER OVERLAY FOR BETTER FIT AND SLIP RESISTANCE DURING WORK ACTIVITY; BALLISTIC V RATED FOR IMPACT PROTECTION – 7X ANSI Z87+ ENERGY; TESTED TO US MILITARY STANDARD MIL-PRF-	6 250	EA

#### Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

	31013 IMPACT TEST; SUPER COAT ANTI-FOG AND ANTI-SCRATCH LENSES		
LENS SFTY EQP:SPECTACLES;CLEAR AF;STD	LENS, SAFETY EQUIPMENT: TYPE: SPECTACLES; SHADE: CLEAR AF; MATERIAL: POLYCARBONATE; DIMENSIONS: STD; SPECIFICATION: ANSI Z87.1-2010+, CE EN-166; MANUF P/N: SG-56C-AF; SUPERCOAT ANTI-FOG AND ANTI-SCRATCH	252	EA
VISOR:DISPOSABLE	VISOR: TYPE: DISPOSABLE; CONSTRUCTED FROM HIGH-QUALITY OPTICALLY CLEAR, DISTORTION-FREE 7 MIL POLYESTER FILMANTI-FOG COATING, MUST FIT WELL OVER SPECTACLES, FOAM BROW-BAND FITS COMFORTABLY AGAINST THE FOREHEAD, HEADBAND, ARMS TO HOLDS VISOR IN PLACE DISPOSABLE/REUSABLE, RTCOVID19-015	800	EA
HAT:SOFT BUSH;S; 56;BLUE NAVY	HAT: TYPE: SOFT BUSH; SIZE: S; 56; COLOR: BLUE NAVY; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, WOVEN PRE SHRUNK; THE ESKOM LOGO SHALL BE EMBROIDERED ON THE FRONT OF THE HAT AND THE ZERO HARM IDENTIFICATION SHALL BE EMBROIDERED ON THE REAR OF THE HAT AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; SOFT HATS SHALL HAVE A REINFORCED STIFFENED BROAD BRIM OF AT LEAST 80 MM; STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD SHALL COMPLY WITH SANS 1362; ALL GARMENTS MUST BEAR THE S.A.B.S. MARK OF APPROVAL; FULL WASHING INSTRUCTIONS; SIZE AND TRACEABILITY SHALL BE MARKED WITH SANS 432 INDELIBLE MARKING INK FOR TEXTILE FABRICS ON HAT; UNIQUE IDENTIFIER 240-44175132	906	EA
HAT:SOFT BUSH;M; 57;BLUE NAVY	HAT: TYPE: SOFT BUSH; SIZE: M; 57; COLOR: BLUE NAVY; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, WOVEN PRE SHRUNK; THE ESKOM LOGO SHALL BE EMBROIDERED ON THE FRONT OF THE HAT AND THE ZERO HARM	732	EA

### Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

	IDENTIFICATION SHALL BE EMBROIDERED ON THE REAR OF THE HAT AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; SOFT HATS SHALL HAVE A REINFORCED STIFFENED BROAD BRIM OF AT LEAST 80 MM; STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD SHALL COMPLY WITH SANS 1362; ALL GARMENTS MUST BEAR THE S.A.B.S. MARK OF APPROVAL; FULL WASHING INSTRUCTIONS; SIZE AND TRACEABILITY SHALL BE MARKED WITH SANS 432 INDELIBLE MARKING INK FOR TEXTILE FABRICS ON HAT; UNIQUE IDENTIFIER 240-44175132		
HAT:SOFT BUSH;L; 58;BLUE NAVY	HAT: TYPE: SOFT BUSH; SIZE: L; 58; COLOR: BLUE NAVY; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, WOVEN PRE SHRUNK; THE ESKOM LOGO SHALL BE EMBROIDERED ON THE FRONT OF THE HAT AND THE ZERO HARM IDENTIFICATION SHALL BE EMBROIDERED ON THE REAR OF THE HAT AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; SOFT HATS SHALL HAVE A REINFORCED STIFFENED BROAD BRIM OF AT LEAST 80 MM; STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD SHALL COMPLY WITH SANS 1362; ALL GARMENTS MUST BEAR THE S.A.B.S. MARK OF APPROVAL; FULL WASHING INSTRUCTIONS; SIZE AND TRACEABILITY SHALL BE MARKED WITH SANS 432 INDELIBLE MARKING INK FOR TEXTILE FABRICS ON HAT; UNIQUE IDENTIFIER 240-44175132	980	EA
HAT:SOFT BUSH;XL; 59;BLUE NAVY	HAT: TYPE: SOFT BUSH; SIZE: XL; 59; COLOR: BLUE NAVY; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, WOVEN PRE SHRUNK; THE ESKOM LOGO SHALL BE EMBROIDERED ON THE FRONT OF THE HAT AND THE ZERO HARM IDENTIFICATION SHALL BE EMBROIDERED ON THE REAR OF THE HAT AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; SOFT HATS SHALL HAVE A	21	EA

### Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.



## Appendix A

### BOM for PPE Accessories

	REINFORCED STIFFENED BROAD BRIM OF AT LEAST 80 MM; STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD SHALL COMPLY WITH SANS 1362; ALL GARMENTS MUST BEAR THE S.A.B.S. MARK OF APPROVAL; FULL WASHING INSTRUCTIONS; SIZE AND TRACEABILITY SHALL BE MARKED WITH SANS 432 INDELIBLE MARKING INK FOR TEXTILE FABRICS ON HAT; UNIQUE IDENTIFIER 240-44175132		
HAT:SOFT BUSH;XXL; 60;BLUE NAVY	HAT: TYPE: SOFT BUSH; SIZE: XXL; 60; COLOR: BLUE NAVY; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, WOVEN PRE SHRUNK; THE ESKOM LOGO SHALL BE EMBROIDERED ON THE FRONT OF THE HAT AND THE ZERO HARM IDENTIFICATION SHALL BE EMBROIDERED ON THE REAR OF THE HAT AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; SOFT HATS SHALL HAVE A REINFORCED STIFFENED BROAD BRIM OF AT LEAST 80 MM; STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD SHALL COMPLY WITH SANS 1362; ALL GARMENTS MUST BEAR THE S.A.B.S. MARK OF APPROVAL; FULL WASHING INSTRUCTIONS; SIZE AND TRACEABILITY SHALL BE MARKED WITH SANS 432 INDELIBLE MARKING INK FOR TEXTILE FABRICS ON HAT; UNIQUE IDENTIFIER 240-44175132	150	EA

Total Price:

VAT:

Total Inclusive VAT

#### Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.





## Appendix A

BOM for PPE Accessories

### Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.