SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

Perkins ELC(Extended Life Coolant) Premix 50/50 with Embitterment

of the mixture

Registration number

None.

Synonyms Product code

1002881

Issue date

19-August-2016

Version number

02

Revision date

22-October-2018

Supersedes date 1.2. Relevant identified uses of the substance or mixture and uses advised against

19-August-2016

Identified uses

Antifreeze / Coolant.

Uses advised against

None known,

1.3. Details of the supplier of the safety data sheet

ARTECO NV

Supplier

Metropoolstraat 25

B-2900 Schoten (Antwerpen)

Belgium

e-mail

customerservice@arteco-coolants.com

Product information

Technical Information: +32 (0) 9 397 06 00

1.4. Emergency telephone

number

Transportation emergency

Europe: +44 20 35147487 (24hr) Access code: 335087

Health Emergency

Europe: +44 20 35147487 (24hr) Access code: 335087

General in EU

112 (Available 24 hours a day. SDS/Product information may not be available for

the Emergency Service.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards

exposure

Specific target organ toxicity - repeated

Category 2 (kidney)

H373 - May cause damage to organs (kidney) through prolonged

or repeated exposure.

Hazard summary

May cause damage to organs through prolonged or repeated exposure. Occupational exposure to

the substance or mixture may cause adverse health effects.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains:

Ethylene glycol

Hazard pictograms

Signal word

Hazard statements

H373

May cause damage to organs (kidney) through prolonged or repeated exposure.

Perkins ELC(Extended Life Coolant) Premix 50/50 with Embitterment

SDS UK

934343 Version # 02 Revision date: 22-October-2018 Issue date: 19-August-2016

Precautionary statements

Prevention

Keep out of reach of children. P102

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

Response

P101 P301 + P310 If medical advice is needed, have product container or label at hand. IF SWALLOWED: Immediately call a POISON CENTRE/doctor.

Storage

Not assigned.

Disposal

P501

Supplemental label information

Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3. Other hazards Not a PBT or vPvB substance or mixture.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name		%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Ethylene glycol	•	≥ 34 - < 80	107-21-1 203-473-3	01-2119456816-28-XXXX	- i	#
Classification:	Acute Tox.	4;H302, ST	OT RE 2;H373			
Sodium 2-ethylhexanoa	te	0.1 - < 3	19766-89-3 243-283-8	Exempt	7	
Classification:	Repr. 2;H36	51d				E.
Sodium molÿbdate dihý	drate	< 0.2	10102-40-6 231-551-7	01-2119489495-21-XXXX	-	• • • • • • • • • • • • • • • • • • • •
Classification:	-					

List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

Composition comments

The full text for all H-statements is displayed in section 16. All concentrations are in percent by

E Exempted from registration as per Annex V of the Regulation 1907/2006 concerning the

Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

This product contains a bittering agent.

SECTION 4: First aid measures

General information

IF exposed or concerned: Get medical advice/attention, if you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

4.1. Description of first aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact

Rinse with water. Remove contact lenses, if present and easy to do. Continue rinsing, Get medical

attention if irritation develops and persists.

Ingestion

Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Get medical advice/attention if you feel unwell,

4.2. Most important symptoms and effects, both acute and delayed

Convulsions, Dizziness, Nausea, vomiting, Abdominal pain, Oedema, Prolonged exposure may cause chronic effects.

4.3. Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Keep victim warm, Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards

No unusual fire or explosion hazards noted.

5.1. Extinguishing media

Suitable extinguishing

Alcohol resistant foam. Powder. Carbon dioxide (CO2),

media

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

Perkins ELC(Extended Life Coolant) Premix 50/50 with Embitterment.

SDS UK

5.2. Special hazards arising from the substance or mixture Thermal decomposition may produce smoke, oxides of carbon and lower molecular weight organic compounds whose composition have not been characterised.

5.3. Advice for firefighters

Special protective equipment for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting procedures

Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials,

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapour, Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained

For emergency responders

Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up Avoid discharge into drains, water courses or onto the ground. Use water spray to reduce vapours or divert vapour cloud drift.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product

recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to

remove residual contamination.

Never return spills to original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe mist or vapour, Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices,

7.2. Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Store away from incompatible materials (see section 10 of

the SDS).

7.3. Specific end use(s)

Antifreeze / Coolant.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Biol

Occupational exposure limits

HK EHAO Moskologo Evenence Limite (MEL -)

Components	Туре	Value	Form
Ethylene glycol (CAS. 107-21-1)	STEL	104 mg/m3	Vароиř.
		40 ppm	Vapour.
	TWA	52 mg/m3	Vapour.
		10 mg/m3	Particulate.
		20 ppm	Vapour.
Sodium molybdate dihydrate (CAS 10102-40-6)	STEL	10 mg/m3	
	TWA	5 mg/m3	
EU. Indicative Exposure Limit \	Values in Directives 91/322/EEC,	2000/39/EC, 2006/15/EC, 2009	/161/EU
Components	Туре	Value	
Ethylene glycol (CAS 107-21-1)	STEL	104 mg/m3	
		40 ppm	
	TWA	52 mg/m3	
		20 ppm	
ogical limit values N	o biological exposure limits noted t	or the ingredient(s).	
	•	- ·	

procedures

Derived no effect levels (DNELs)

General	Population

Components	Value	Assessment factor	Notes
Ethylene glycol (CAS 107-21-1)			
Long-term, Systemic, Dermal	53 mg/kg bw/day	84	Repeated dose toxicity
Short-term, Systemic, Inhalation	7 mg/m3	10	Skin irritation/corrosion
Sodium mölybdate dihydrate (CAS 10102-	40-6)		
Long-term, Systemic, Inhalation	7.15 mg/m3	· 5	
Long-term, Systemic, Oral	7.3 mg/kg/day	5	
Workers			
Components	Value	Assessment factor	Notes
Ethylene glycol (CAS 107-21-1)			
Long-term, Systemic, Dermal	106 mg/kg bw/day	42	Repeated dose toxicity
Short-term, Systemic, Inhalation	35 mg/m3	2	Skin irritation/corrosion
Sodium molyboate dihydrate (CAS 10102-	40-6)		
Long-term, Systemic, Inhalation	23.97 mg/m3	3	
licted no effect concentrations (PNECs)			
Components	Value	Assessment factor	Notes
Components Ethylene glycol (CAS 107-21-1)	Value	Assessment factor	Notes
	Value 10 mg/l	Assessment factor	Notes
Ethylene glycol (CAS 107-21-1)			Notes
Ethylene glycol (CAS 107-21-1) Freshwater	10 mg/l	10	Notes
Ethylene glycol (CAS 107-21-1) Freshwater Merine water	10 mg/l 1 mg/l	10	Notes
Ethylene glycol (CAS 107-21-1) Freshwater Marine water Sediment (freshwater) Sediment (marine water) Soil	10 mg/l 1 mg/l 37 mg/kg	10	Notes
Ethylene glycol (CAS 107-21-1) Freshwater Marine water Sediment (freshwater) Sediment (marine water)	10 mg/l 1 mg/l 37 mg/kg 3.7 mg/kg	10	Notes
Ethylene glycol (CAS 107-21-1) Freshwater Marine water Sediment (freshwater) Sediment (marine water) Soil	10 mg/l 1 mg/l 37 mg/kg 3.7 mg/kg 1.53 mg/kg 199.5 mg/l	10 100	Notes
Ethylene glycol (CAS 107-21-1) Freshwater Marine water Sediment (freshwater) Sediment (marine water) Soil STP Sodium molybdate dihydrate (CAS 10102-4)	10 mg/l 1 mg/l 37 mg/kg 3.7 mg/kg 1.53 mg/kg 199.5 mg/l	10 100	Notes
Ethylene glycol (CAS 107-21-1) Freshwater Marine water Sediment (freshwater) Sediment (marine water) Soil STP Sodium molybdate dihydrate (CAS 10102-4) Freshwater Marine water	10 mg/l 1 mg/l 37 mg/kg 3.7 mg/kg 1.53 mg/kg 199.5 mg/l	10 100 10	Notes
Ethylene glycol (CAS 107-21-1) Freshwater Marine water Sediment (freshwater) Sediment (marine water) Soil STP Sodium molybdate dihydrate (CAS 10102-4)	10 mg/l 1 mg/l 37 mg/kg 3.7 mg/kg 1.53 mg/kg 199.5 mg/l 40-6) 27.25 mg/l 4,87 mg/l	10 100	Notes
Ethylene glycol (CAS 107-21-1) Freshwater Marine water Sediment (freshwater) Sediment (marine water) Soil STP Sodium molybdate dihydrate (CAS 10102-4) Freshwater Marine water	10 mg/l 1 mg/l 37 mg/kg 3.7 mg/kg 1.53 mg/kg 199.5 mg/l 40-6) 27,25 mg/l 4,87 mg/l 48500 mg/kg	10 100 10 3 3	Notes
Ethylene glycol (CAS 107-21-1) Freshwater Marine water Sediment (freshwater) Sediment (marine water) Soil STP Sodium molybdate dihydrate (CAS 10102-4 Freshwater Marine water Sediment (freshwater)	10 mg/l 1 mg/l 37 mg/kg 3.7 mg/kg 1.53 mg/kg 199.5 mg/l 40-6) 27.25 mg/l 4,87 mg/l	10 100 10 3 3	Notes

Exposure guidelines

UK EH40 WEL: Skin designation

Ethylene glycol (CAS 107-21-1)

Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

General information

Personal protection equipment should be chosen according to the CEN standards and in

discussion with the supplier of the personal protective equipment,

Eye/face protection Skin protection

Chemical respirator with organic vapour cartridge and full facepiece.

- Hand protection

Wear appropriate chemical resistant gloves. Wear suitable gloves tested to EN374. Full contact: Use gloves classified protection index 6 with breakthrough time of 480 minutes. Minimum glove

thickness 0.38 mm. Neoprene, butyl rubber, nitrile or Viton gloves are recommended. Suitable

gloves can be recommended by the glove supplier.

- Other

Wash hands thoroughly after handling. Use of an impervious apron is recommended.

Respiratory protection

Chemical respirator with organic vapour cartridge and full facepiece.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

Hygiene measures

Observe any medical surveillance requirements, Keep away from food and drink, Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove

contaminants.

Environmental exposure

controls

Environmental manager must be informed of all major releases.

Perkins ELC(Extended Life Coolant) Premix 50/50 with Embitterment

SDS UK

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state

Liquid.

Form

Clear liquid.

Colour

Red.

Odour

Mild.

Odour threshold

Not determined.

рΗ

8.25 - 8.60 (20°C)

Melting point/freezing point

Not determined. / -36 °C (-32.8 °F)

Initial boiling point and boiling

range

109 °C (228.2 °F) (Estimated)

Flash point

Not applicable.

Evaporation rate

Not determined.

Flammability (solid, gas)

Not applicable.

Upper/lower flammability or explosive limits Flammability limit - lower

Not determined,

(%)

Flammability limit - upper

Not determined.

(%)

Vapour pressure

Not determined.

Vapour density

Not determined.

Relative density

Not determined.

Solubility(ies)

Miscible.

Partition coefficient

Not determined.

(n-octanol/water)

Not determined.

Auto-ignition temperature Decomposition temperature

Not determined.

Viscosity

Not determined.

Explosive properties

Not explosive. Not exidising.

Oxidising properties 9.2. Other information

Density

1.070 kg/l (20 °C) (Typical)

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Material is stable under normal conditions. No dangerous reaction known under conditions of normal use.

10.3. Possibility of hazardous reactions

Contact with incompatible materials.

10.4. Conditions to avoid 10.5. Incompatible materials

decomposition products

Strong acids, Strong exidising agents, Nitrates, Peroxides, Chlorates,

10.6. Hazardous

At elevated temperatures: Ketones, Aldehydes,

SECTION 11: Toxicological information

General information

Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation

In high concentrations, mists/vapours may irritate throat and respiratory system and cause

coughing.

Skin contact

Prolonged or repeated contact may dry skin and cause irritation.

Eye contact

Direct contact with eyes may cause temporary irritation.

Ingestion

Ingestion of ethylene glycol may result in nausea, vomiting, abdominal cramps, blindness, liver damage, irritation, reproductive effects, nerve damage, convulsions, oedema of the lung,

cardiopulmonary effects (metabolic acidosis), pneumonia and kidney failure which could result in death. The single lethal dose for humans is about 100 ml. Inhalation of high levels of vapour or

mists for prolonged periods of time may also result in toxic effects.

Symptoms

Convulsions, Dizziness, Nausea, vomiting, Abdominal pain, Oedema.

Product Species **Test Results**

Perkins ELC(Extended Life Coolant) Premix 50/50 with Embitterment (CAS -)

Acute Oral

3278 mg/kg ATE Components **Species Test Results**

Ethylene glycol (CAS 107-21-1)

Acute Dermal

LD50

Mouse

> 3500 mg/kg

Inhalation

Aerosol LC50

Rat

> 2.5 mg/l, 6 Hours

Oral LD50

Skin corrosion/irritation

Cat

1600 mg/kg

Serious eye damage/eye

irritation

Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met.

Respiratory sensitisation

Due to partial or complete lack of data the classification is not possible.

Skin sensitisation Germ cell mutagenicity

Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met.

Carcinogenicity

Due to partial or complete lack of data the classification is not possible.

Reproductive toxicity

Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met.

Specific target organ toxicity single exposure

Specific target organ toxicity -

repeated exposure

May cause damage to organs (kidney) through prolonged or repeated exposure.

Aspiration hazard

Due to partial or complete lack of data the classification is not possible.

Mixture versus substance

information

No information available.

Other information

No data available.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met for hazardous to the aquatic environment.

Components

Species Test Results

Ethylene glycol (CAS 107-21-1)

Aquatic

Crustacea

EC50

Daphnia magna

> 100 mg/l, 48 Hours

Fish

LC50

Fathead minnow (Pimephales promelas) 72860 mg/l, 96 hours

12.2. Persistence and

Expected to be readily biodegradable.

degradability

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow)

Ethylene glycol (CAS 107-21-1)

-1.36

Bioconcentration factor (BCF)

Not available.

12.4. Mobility in soil

No data available.

No data available.

12.5. Results of PBT and vPvB

Not a PBT or vPvB substance or mixture.

assessment

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Perkins ELC(Extended Life Coolant) Premix 50/50 with Embitterment 934343 Version #: 02 Revision date: 22-October-2018 Issue date: 19-August-2016 Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

EU waste code

Disposal methods/information

EWC: 16.01-14
Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Special precautions

Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. - 14.6.: Not regulated as dangerous goods.

RID

14.1. - 14.6.: Not regulated as dangerous goods.

ADN

14.1. - 14.6.: Not regulated as dangerous goods.

IATA

14.1. - 14.6.: Not regulated as dangerous goods.

IMDG

14.1. - 14.6.: Not regulated as dangerous goods.

14.7. Transport in bulk

Not established.

according to Annex II of MARPOL 73/78 and the IBC

Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorisation, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006; REACH Annex XVII Substances subject to restriction on marketing and use as amended Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended Not listed.

Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

All components of this product are compliant with the registration requirements of Regulation (EC) 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals, as amended.

All components comply with the following chemical inventory requirements: AICS (Australia), DSL (Canada), EINECS (European Union), ENCS (Japan), IECSC (China), KECI (Korea), PICCS (Philippines), TSCA (United States), TCSI (Taiwan), NZIoC (New Zealand).

National regulations

Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended. Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

TWA: Time weighted average. STEL: Short term exposure limit. DNEL: Derived No-Effect Level.

PNEC: Predicted No-Effect Concentration.

STP: Sewage treatment plant. LD50: Lethal Dose, 50%.

EC50: Effective Concentration, 50%. LC50: Lethal Concentration, 50%.

PBT: Persistent, bioaccumulative and toxic. vPvB: Very Persistent and very Bioaccumulative.

References

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any H-statements not written out in full under

Sections 2 to 15

H302 Harmful if swallowed.

ECHA CHEM

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure by ingestion.

This SDS contains revisions in the following section(s):

Training information

Disclaimer

Follow training instructions when handling this material.

ARTECO NV cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.