

 Eskom	Scope Of Work	Generation
---	---------------	------------

Title: **THE SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE EQUIPMENT (PPE) ACCESSORIES ON AN "AS AND WHEN REQUIRED" BASIS TO ESKOM KRIEL POWER STATION**

Unique Identifier: **EEP1015**

Alternative Reference Number: **N/A**

Area of Applicability: **Engineering/  
Maintenance**




Documentation Type: **Scope of Work**

Revision: **1**

Total Pages:

Next Review Date: **N/A**

Disclosure Classification: **CONTROLLED  
DISCLOSURE**

<b>Compiled by</b>	<b>Functional Responsibility</b>	<b>Authorised by</b>
		
.....	.....	.....
<b>S Biyela</b>	<b>M Mutheiwana</b>	<b>L Gumbi</b>
<b>Senior Advisor</b>	<b>Material Manager</b>	<b>Maintenance Manager</b>
Date: 14 Feb 2022	Date: 15/02/22	Date: 17/02/2022
.....	.....	.....

## CONTENTS

	Page
<b>1. INTRODUCTION .....</b>	<b>3</b>
<b>2. SUPPORTING CLAUSES .....</b>	<b>4</b>
2.1 SCOPE .....	4
2.1.1 Purpose .....	4
2.1.2 Applicability .....	12
2.2 NORMATIVE/INFORMATIVE REFERENCES .....	12
2.2.1 Normative .....	12
2.3 GENERAL ARRANGEMENT AND LOCATION DRAWINGS .....	12
Not applicable .....	12
2.3.1 informative .....	12
2.4 DEFINITIONS .....	12
2.4.1 Disclosure Classification .....	12
2.5 ABBREVIATIONS .....	13
2.6 ROLES AND RESPONSIBILITIES .....	14
2.7 PROCESS FOR MONITORING .....	14
<b>3. THE <i>WORKS</i> .....</b>	<b>15</b>
3.1 BACKGROUND .....	15
3.2 DESCRIPTION OF THE <i>WORKS</i> .....	15
3.2.1 Scope of work .....	15
3.2.2 Design Life .....	106
Documentation Submission And Recording .....	106
3.2.3 Plant Codification .....	106
3.3 STANDARDS, SPECIFICATIONS AND PROCEDURES .....	107
<b>4. AUTHORISATION .....</b>	<b>108</b>
<b>5. REVISIONS .....</b>	<b>108</b>
<b>6. DEVELOPMENT TEAM .....</b>	<b>108</b>
<b>7. ACKNOWLEDGEMENT .....</b>	<b>108</b>
<b>8. APPENDIX A .....</b>	<b>109</b>

### CONTROLLED DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

## **1. INTRODUCTION**

Kriel Power Station is situated approximately 10 kilometres from the town of Kriel in Mpumalanga. Access to the station is by road.

This document therefore specifies the scope of work that will be an input for the open tender contract between Eskom – Kriel power Station and service provider for THE SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE EQUIPMENT (PPE) ACCESSORIES ON AN “AS AND WHEN REQUIRED” BASIS TO ESKOM KRIEL POWER STATION for period of three (3) years.

### **CONTROLLED DISCLOSURE**

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

## 2. SUPPORTING CLAUSES

### 2.1 SCOPE

This document specifies the scope of work that will be an input for the s open tender contract between Eskom – Kriel power Station and service provide for the supply and delivery of personal protective equipment (ppe) accessories on an “as and when required” basis to Eskom kriel power station for period of three (3) years.

The purpose of the document is to provide technical governance in terms of a scope of work for supply and delivery of personal protective equipment (ppe) accessories on an “as and when required” basis to Eskom Kriel power station for period of three (3) years., at Kriel Power Station in the Units 1-6 for Kriel Power Station. This document is intended to be the input to the NEC Part 3:

#### Scope of Work.

Item No	Description
1	COAT,DUST:GP;102 CM;COTTON
2	GUMBOOTS SFTY:STL;7;KNEE HEIGHT;BLACK
3	GUMBOOTS SFTY:STL;8;KNEE HEIGHT;BLACK
4	GUMBOOTS SFTY:STL;9;KNEE HEIGHT;BLACK
5	GUMBOOTS SFTY:STL;10;KNEE HEIGHT;BLACK
6	GUMBOOTS SFTY:STL;11;KNEE HEIGHT;BLACK
7	COAT,DUST:GP;112 CM;COTTON
8	COAT,DUST:GP;107 CM;COTTON
9	COAT,DUST:GP;97 CM;COTTON;240-44175132
10	COAT,DUST:GP;87 CM;COTTON;240-44175132
11	COAT,DUST:GP;117 CM;COTTON
12	COAT,DUST:GP;122 CM;COTTON
13	COAT,DUST:GP;82 CM;COTTON;240-44175132
14	APRON:CHEMICAL;WD 700MM X LG 1.1M
15	GUMBOOTS SFTY:STL;6;KNEE HEIGHT;BLACK
16	GUMBOOTS SFTY:STL;12;KNEE HEIGHT;BLACK
17	GUMBOOTS SFTY:STL;13;KNEE HEIGHT;BLACK
18	BAG,DUFFEL:NAVY BLUE ;PVC CANVAS
19	JACKET,UTILITY:OPERATING;147 CM
20	JACKET,UTILITY:OPERATING;137 CM
21	JACKET,UTILITY:OPERATING;157 CM
22	APRON,WELDER:FULL LENGTH
23	JACKET,UTILITY:THERMAL;5XL
24	JACKET,UTILITY:THERMAL;4XL

#### CONTROLLED DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

25	HAT:SOFT BUSH;S; 56;NAVY BLUE
26	HAT:SOFT BUSH;M; 57;NAVY BLUE
27	HAT:SOFT BUSH;L; 58;NAVY BLUE
28	HAT:SOFT BUSH;XL; 59;NAVY BLUE
29	SHIRT:MEN LONG SLEEVE;36 CM;COTTON
30	SHIRT:MEN LONG SLEEVE;37 CM;COTTON
31	SHIRT:MEN LONG SLEEVE;38 CM;COTTON
32	SHIRT:MEN LONG SLEEVE;39 CM;COTTON
33	SHIRT:MEN LONG SLEEVE;40 CM;COTTON
34	SHIRT:MEN LONG SLEEVE;41 CM;COTTON
35	SHIRT:MEN LONG SLEEVE;42 CM;COTTON
36	SHIRT:MEN LONG SLEEVE;43 CM;COTTON
37	SHIRT:MEN LONG SLEEVE;44 CM;COTTON
38	SHIRT:MEN LONG SLEEVE;45 CM;COTTON
39	SHIRT:MEN LONG SLEEVE;46 CM;COTTON
40	SHIRT:MEN LONG SLEEVE;47 CM;COTTON
41	SHIRT:MEN LONG SLEEVE;48 CM;COTTON
42	SHIRT:MEN LONG SLEEVE;49 CM;COTTON
43	SHIRT:MEN SHORT SLEEVE;36 CM;COTTON
44	SHIRT:MEN SHORT SLEEVE;37 CM;COTTON
45	SHIRT:MEN SHORT SLEEVE;38 CM;COTTON
46	SHIRT:MEN SHORT SLEEVE;39 CM;COTTON
47	SHIRT:MEN SHORT SLEEVE;40 CM;COTTON
48	SHIRT:MEN SHORT SLEEVE;41 CM;COTTON
49	SHIRT:MEN SHORT SLEEVE;42 CM;COTTON
50	SHIRT:MEN SHORT SLEEVE;43 CM;COTTON
51	SHIRT:MEN SHORT SLEEVE;44 CM;COTTON
52	SHIRT:MEN SHORT SLEEVE;45 CM;COTTON
53	SHIRT:MEN SHORT SLEEVE;46 CM;COTTON
54	SHIRT:MEN SHORT SLEEVE;47 CM;COTTON
55	SHIRT:MEN SHORT SLEEVE;48 CM;COTTON
56	SHIRT:MEN SHORT SLEEVE;49 CM;COTTON
57	SHIRT,WOMAN:LONG;77 CM;SAND STONE
58	SHIRT,WOMAN:LONG;82 CM;SAND STONE
59	SHIRT,WOMAN:LONG;87 CM;SAND STONE
60	SHIRT,WOMAN:LONG;92 CM;SAND STONE
61	SHIRT,WOMAN:LONG;102 CM;SAND STONE
62	SHIRT,WOMAN:LONG;107 CM;SAND STONE
63	SHIRT,WOMAN:LONG;112 CM;SAND STONE
64	SHIRT,WOMAN:LONG;117 CM;SAND STONE
65	SHIRT,WOMAN:LONG;122 CM;SAND STONE

**CONTROLLED DISCLOSURE**

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

66	SHIRT,WOMAN:LONG;127 CM;SAND STONE
67	SHIRT,WOMAN:LONG;132 CM;SAND STONE
68	SHIRT,WOMAN:LONG;137 CM;SAND STONE
69	SHIRT,WOMAN:LONG;142 CM;SAND STONE
70	SHIRT,WOMAN:LONG;147 CM;SAND STONE
71	SHIRT,WOMAN:SHORT;77 CM;SAND STONE
72	SHIRT,WOMAN:SHORT;82 CM;SAND STONE
73	SHIRT,WOMAN:SHORT;87 CM;SAND STONE
74	SHIRT,WOMAN:SHORT;92 CM;SAND STONE
75	SHIRT,WOMAN:SHORT;102 CM;SAND STONE
76	SHIRT,WOMAN:SHORT;107 CM;SAND STONE
77	SHIRT,WOMAN:SHORT;112 CM;SAND STONE
78	SHIRT,WOMAN:SHORT;117 CM;SAND STONE
79	SHIRT,WOMAN:SHORT;122 CM;SAND STONE
80	SHIRT,WOMAN:SHORT;127 CM;SAND STONE
81	SHIRT,WOMAN:SHORT;132 CM;SAND STONE
82	SHIRT,WOMAN:SHORT;137 CM;SAND STONE
83	SHIRT,WOMAN:SHORT;142 CM;SAND STONE
84	SHIRT,WOMAN:SHORT;147 CM;SAND STONE
85	TROUSERS:MEN LONG;77 CM;NAVY BLUE
86	TROUSERS:MEN LONG;82 CM;NAVY BLUE
87	TROUSERS:MEN LONG;87 CM;NAVY BLUE
88	TROUSERS:MEN LONG;92 CM;NAVY BLUE
89	TROUSERS:MEN LONG;97 CM;NAVY BLUE
90	TROUSERS:MEN LONG;102 CM;NAVY BLUE
91	TROUSERS:MEN LONG;107 CM;NAVY BLUE
92	TROUSERS:MEN LONG;112 CM;NAVY BLUE
93	TROUSERS:MEN LONG;117 CM;NAVY BLUE
94	TROUSERS:MEN LONG;122 CM;NAVY BLUE
95	TROUSERS:MEN LONG;127 CM;NAVY BLUE
96	TROUSERS:MEN LONG;132 CM;NAVY BLUE
97	TROUSERS:LADIES LONG;26; 67;NAVY BLUE
98	TROUSERS:LADIES LONG;28; 72;NAVY BLUE
99	TROUSERS:LADIES LONG;30; 77;NAVY BLUE
100	TROUSERS:LADIES LONG;32; 82;NAVY BLUE
101	TROUSERS:LADIES LONG;34; 87;NAVY BLUE
102	TROUSERS:LADIES LONG;36; 92;NAVY BLUE
103	TROUSERS:LADIES LONG;38; 97;NAVY BLUE
104	TROUSERS:LADIES LONG;40; 102;NAVY BLUE
105	TROUSERS:LADIES LONG;42; 107;NAVY BLUE
106	TROUSERS:LADIES LONG;44; 112;NAVY BLUE

**CONTROLLED DISCLOSURE**

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

107	TROUSERS:LADIES LONG;46; 117;NAVY BLUE
108	TROUSERS:LADIES LONG;48; 122;NAVY BLUE
109	TROUSERS:LADIES LONG;50; 127;NAVY BLUE
110	TROUSERS:LADIES LONG;52; 132;NAVY BLUE
111	COVERALL:ARTISAN BOILER SUIT ;77 CM
112	COVERALL:ARTISAN BOILER SUIT ;82 CM
113	COVERALL:ARTISAN BOILER SUIT ;87 CM
114	COVERALL:ARTISAN BOILER SUIT ;92 CM
115	COVERALL:ARTISAN BOILER SUIT ;97 CM
116	JACKET,UTILITY:OPERATING;87 CM
117	JACKET,UTILITY:OPERATING;97 CM
118	JACKET,UTILITY:OPERATING;107 CM
119	JACKET,UTILITY:OPERATING;117 CM
120	JACKET,UTILITY:OPERATING;122 CM
121	JACKET,UTILITY:OPERATING;132 CM
122	RAINWEAR:2 PIECE SUIT;S;NAVY BLUE
123	RAINWEAR:2 PIECE SUIT;L;NAVY BLUE
124	RAINWEAR:2 PIECE SUIT;XL;NAVY BLUE
125	RAINWEAR:2 PIECE SUIT;XXL;NAVY BLUE
126	RAINWEAR:2 PIECE SUIT;XXXL;NAVY BLUE
127	BOOTS SFTY:4;STRD; STL OR CARBON FIBER
128	BOOTS SFTY:5;STRD; STL OR CARBON FIBER
129	BOOTS SFTY:6;STRD; STL OR CARBON FIBER
130	BOOTS SFTY:7;STRD; STL OR CARBON FIBER
131	BOOTS SFTY:8;STRD; STL OR CARBON FIBER
132	BOOTS SFTY:9;STRD; STL OR CARBON FIBER
133	BOOTS SFTY:10;STRD; STL OR CARBON FIBER
134	RAINWEAR:2 PIECE SUIT;M;NAVY BLUE
135	SHOES SFTY:4;BLACK/BROWN;34-232;LAC
136	SHOES SFTY:5;BLACK/BROWN;34-232;LACE
137	SHOES SFTY:6;BLACK/BROWN;34-232;LACE
138	SHOES SFTY:7;BLACK/BROWN;34-232;LACE
139	SHOES SFTY:8;BLACK/BROWN;34-232;LACE
140	SHOES SFTY:9;BLACK/BROWN;34-232;LACE
141	SHOES SFTY:10;BLACK/BROWN;34-232;LACE
142	SHOES SFTY:11;BLACK/BROWN;34-232;LACE
143	VEST, H/VISIB:EMPLOYEE AT WORK;S;NYLON
144	SOCKS CALF LENGTH [S-M]
145	SOCKS CALF LENGTH [L-XL]
146	SOCKS CALF LENGTH [2XL-3XL]
147	VEST, H/VISIB:EVACUATION;S;NYLON

**CONTROLLED DISCLOSURE**

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

148	VEST, H/VISIB:EVACUATION;M;NYLON
149	VEST, H/VISIB:EVACUATION;L;NYLON
150	VEST, H/VISIB:EVACUATION;XL;NYLON
151	VEST, H/VISIB:EVACUATION;XXL;NYLON
152	VEST, H/VISIB:EVACUATION;XXXL;NYLON
153	VEST, H/VISIB:EVACUATION;4XL;NYLON
154	VEST, H/VISIB:EVACUATION;5XL;NYLON
155	HELMET SFTY:HEIGHT THREE POINT;WHITE
156	VEST, H/VISIB:TRANSPORT;M;NYLON
157	VEST, H/VISIB:TRANSPORT;XXXL;NYLON
158	VEST, H/VISIB:TRANSPORT;L;NYLON
159	VEST, H/VISIB:TRANSPORT;XL;NYLON
160	VEST, H/VISIB:TRANSPORT;XXL;NYLON
161	VEST, H/VISIB:TRANSPORT;S;NYLON
162	VEST, H/VISIB:MANAGEMENT;S;NYLON
163	VEST, H/VISIB:MANAGEMENT;M;NYLON
164	VEST, H/VISIB:MANAGEMENT;L;NYLON
165	VEST, H/VISIB:MANAGEMENT;XL;NYLON
166	VEST, H/VISIB:MANAGEMENT;XXL;NYLON
167	VEST, H/VISIB:MANAGEMENT;XXXL;NYLON
168	VEST, H/VISIB:EMPLOYEE AT WORK;M;NYLON
169	VEST, H/VISIB:EMPLOYEE AT WORK;L;NYLON
170	VEST, H/VISIB:EMPLOYEE AT WORK;XL;NYLON
171	VEST, H/VISIB:EMPLOYEE AT WORK;XXL;NYLON
172	VEST, H/VISIB:EMPLOYEE AT WORK;XXXL
173	VEST, H/VISIB:EMPLOYEE AT WORK;4XL;NYLON
174	VEST, H/VISIB:EMPLOYEE AT WORK;5XL;NYLON
175	VEST, H/VISIB:FIRE PROTECTION;S;NYLON
176	VEST, H/VISIB:FIRE PROTECTION;M;NYLON
177	VEST, H/VISIB:FIRE PROTECTION;L;NYLON
178	VEST, H/VISIB:FIRE PROTECTION;XL;NYLON
179	VEST, H/VISIB:FIRE PROTECTION;XXL;NYLON
180	VEST, H/VISIB:FIRE PROTECTION;XXXL;NYLON
181	VEST, H/VISIB:FIRE PROTECTION;4XL;NYLON
182	VEST, H/VISIB:FIRE PROTECTION;5XL;NYLON
183	VEST, H/VISIB:FIRE PROTECTION;6XL;NYLON
184	VEST, H/VISIB:FIRST AID;S;NYLON
185	VEST, H/VISIB:FIRST AID;XXXL;NYLON
186	RAINWEAR:2 PIECE SUIT;4XL;NAVY BLUE
187	SUIT CHEM PROT:S;YELLOW;ACID PROOF
188	SUIT CHEM PROT:M;YELLOW;ACID PROOF

**CONTROLLED DISCLOSURE**

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.



189	SUIT CHEM PROT:L;YELLOW;ACID PROOF
190	SUIT CHEM PROT:XL;YELLOW;ACID PROOF
191	SUIT CHEM PROT:XXXL;YELLOW;ACID PROOF
192	SUIT CHEM PROT:XXL;YELLOW;ACID PROOF
193	SUIT CHEM PROT:4XL;YELLOW;ACID PROOF
194	VISOR:SUN BRIM FOR SAFETY HAT
195	SHIRT,WOMAN:LONG;97 CM;SAND STONE
196	SHIRT,WOMAN:SHORT;97 CM;SAND STONE
197	GUMBOOTS SFTY:STL;5;KNEE HEIGHT;BLACK
198	COAT,DUST:GP;127 CM;COTTON
199	COAT,DUST:GP;92 CM;COTTON;240-44175132
200	JACKET,UTILITY:ACID/ALKALI;87 CM
201	JACKET,UTILITY:ACID/ALKALI;97 CM
202	JACKET,UTILITY:ACID/ALKALI;107 CM
203	JACKET,UTILITY:ACID/ALKALI;117 CM
204	JACKET,UTILITY:ACID/ALKALI;122 CM
205	JACKET,UTILITY:ACID/ALKALI;132 CM
206	JACKET,UTILITY:OPERATING;77 CM
207	JACKET,UTILITY:OPERATING;82 CM
208	JACKET,UTILITY:OPERATING;102 CM
209	JACKET,UTILITY:OPERATING;112 CM
210	JACKET,UTILITY:OPERATING;127 CM
211	JACKET,UTILITY:OPERATING;92 CM
212	JACKET,UTILITY:ACID/ALKALI;77 CM
213	JACKET,UTILITY:ACID/ALKALI;82 CM
214	JACKET,UTILITY:ACID/ALKALI;92 CM
215	JACKET,UTILITY:ACID/ALKALI;102 CM
216	JACKET,UTILITY:ACID/ALKALI;127 CM
217	JACKET,UTILITY:ACID/ALKALI;142 CM
218	JACKET,UTILITY:ACID/ALKALI;112 CM
219	BOOTS SFTY:11;STRD; STL OR CARBON FIBER
220	BOOTS SFTY:12;STRD; STL OR CARBON FIBER
221	BOOTS SFTY:3;STRD; STL OR CARBON FIBER
222	BOOTS SFTY:13;STRD; STL OR CARBON FIBER
223	SHOES SFTY:3;BLACK/BROWN;34-232;LACE
224	COVERALL:ARTISAN BOILER SUIT ;102 CM
225	COVERALL:ARTISAN BOILER SUIT ;117 CM
226	COVERALL:ARTISAN BOILER SUIT ;107 CM
227	COVERALL:ARTISAN BOILER SUIT ;132 CM
228	COVERALL:ARTISAN BOILER SUIT ;127 CM
229	COVERALL:ARTISAN BOILER SUIT ;112 CM

**CONTROLLED DISCLOSURE**

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

230	COVERALL:ARTISAN BOILER SUIT ;122 CM
231	COVERALL:ACID/ALKALI ;77 CM
232	COVERALL:ACID/ALKALI ;82 CM
233	COVERALL:ACID/ALKALI ;87 CM
234	COVERALL:ACID/ALKALI ;92 CM
235	COVERALL:ACID/ALKALI ;97 CM
236	COVERALL:ACID/ALKALI ;102 CM
237	COVERALL:ACID/ALKALI ;107 CM
238	COVERALL:ACID/ALKALI ;112 CM
239	COVERALL:ACID/ALKALI ;117 CM
240	COVERALL:ACID/ALKALI ;122 CM
241	COVERALL:ACID/ALKALI ;127 CM
242	COVERALL:ACID/ALKALI ;132 CM
243	JACKET,OVERALL:CLEAN CONDITION;112 CM
244	JACKET,OVERALL:CLEAN CONDITION;117 CM
245	JACKET,OVERALL:CLEAN CONDITION;122 CM
246	JACKET,OVERALL:CLEAN CONDITION;127 CM
247	JACKET,OVERALL:CLEAN CONDITION;132 CM
248	JACKET,OVERALL:CLEAN CONDITION;137 CM
249	JACKET,OVERALL:CLEAN CONDITION;142 CM
250	JACKET,OVERALL:CLEAN CONDITION;147 CM
251	JACKET,OVERALL:CLEAN CONDITION;152 CM
252	JACKET,OVERALL:CLEAN CONDITION;157 CM
253	TROUSERS:CLEAN CONDITION;77 CM;WHITE
254	TROUSERS:CLEAN CONDITION;82 CM;WHITE
255	TROUSERS:CLEAN CONDITION;87 CM;WHITE
256	TROUSERS:CLEAN CONDITION;92 CM;WHITE
257	TROUSERS:CLEAN CONDITION;97 CM;WHITE
258	TROUSERS:CLEAN CONDITION;102 CM;WHITE
259	TROUSERS:CLEAN CONDITION;107 CM;WHITE
260	TROUSERS:CLEAN CONDITION;112 CM;WHITE
261	TROUSERS:CLEAN CONDITION;117 CM;WHITE
262	TROUSERS:CLEAN CONDITION;122 CM;WHITE
263	TROUSERS:CLEAN CONDITION;127 CM;WHITE
264	TROUSERS:ACID/ALKALI ;77 CM
265	TROUSERS:ACID/ALKALI ;82 CM
266	TROUSERS:ACID/ALKALI ;87 CM
267	TROUSERS:ACID/ALKALI ;97 CM
268	TROUSERS:ACID/ALKALI ;102 CM
269	TROUSERS:ACID/ALKALI ;107 CM
270	TROUSERS:ACID/ALKALI ;112 CM

**CONTROLLED DISCLOSURE**

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

271	TROUSERS:ACID/ALKALI ;117 CM
272	TROUSERS:ACID/ALKALI ;122 CM
273	TROUSERS:ACID/ALKALI ;127 CM
274	TROUSERS:ACID/ALKALI ;132 CM
275	TROUSERS:ACID/ALKALI ;92 CM
276	COVERALL:ACID RESIST ;77 ;POLY COTTON
277	COVERALL:ACID RESIST ;82 ;POLY COTTON
278	COVERALL:ACID RESIST ;87 ;POLY COTTON
279	COVERALL:ACID RESIST ;92 ;POLY COTTON
280	COVERALL:ACID RESIST ;97 ;POLY COTTON
281	COVERALL:ACID RESIST ;102 ;POLY COTTON
282	COVERALL:ACID RESIST ;107 ;POLY COTTON
283	COVERALL:ACID RESIST ;112 ;POLY COTTON
284	COVERALL:ACID RESIST ;117 ;POLY COTTON
285	COVERALL:ACID RESIST ;122 ;POLY COTTON
286	COVERALL:ACID RESIST ;127 ;POLY COTTON
287	COVERALL:ACID RESIST ;132 ;POLY COTTON
288	COVERALL:ACID RESIST ;137 ;POLY COTTON
289	COVERALL:ACID RESIST ;142 ;POLY COTTON
290	COVERALL:ACID RESIST ;147 ;POLY COTTON
291	COVERALL:ACID RESIST ;152 ;POLY COTTON
292	COVERALL:ACID RESIST ;157 ;POLY COTTON
293	JACKET,OVERALL:ACID RESIST ;77
294	JACKET,OVERALL:ACID RESIST ;82
295	JACKET,OVERALL:ACID RESIST ;87
296	JACKET,OVERALL:ACID RESIST ;92
297	JACKET,OVERALL:ACID RESIST ;97
298	JACKET,OVERALL:ACID RESIST ;102
299	JACKET,OVERALL:ACID RESIST ;107
300	JACKET,OVERALL:ACID RESIST ;112
301	JACKET,OVERALL:ACID RESIST ;117
302	JACKET,OVERALL:ACID RESIST ;122
303	JACKET,OVERALL:ACID RESIST ;127
304	JACKET,OVERALL:ACID RESIST ;132
305	JACKET,OVERALL:ACID RESIST ;137
306	JACKET,OVERALL:ACID RESIST ;142
307	JACKET,OVERALL:ACID RESIST ;147
308	TROUSERS:ACID RESIST ;77 ;BOTTLE GREEN
309	TROUSERS:ACID RESIST ;82 ;BOTTLE GREEN
310	TROUSERS:ACID RESIST ;87 ;BOTTLE GREEN
311	TROUSERS:ACID RESIST ;92 ;BOTTLE GREEN

**CONTROLLED DISCLOSURE**

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

312	TROUSERS:ACID RESIST ;97 ;BOTTLE GREEN
313	TROUSERS:ACID RESIST ;102 ;BOTTLE GREEN
314	TROUSERS:ACID RESIST ;107 ;BOTTLE GREEN
315	TROUSERS:ACID RESIST ;112 ;BOTTLE GREEN
316	TROUSERS:ACID RESIST ;117 ;BOTTLE GREEN
317	TROUSERS:ACID RESIST ;122 ;BOTTLE GREEN
318	TROUSERS:ACID RESIST ;127 ;BOTTLE GREEN
319	TROUSERS:ACID RESIST ;132 ;BOTTLE GREEN
320	TROUSERS:ACID RESIST ;137 ;BOTTLE GREEN
321	TROUSERS:ACID RESIST ;142 ;BOTTLE GREEN
322	TROUSERS:ACID RESIST ;147 ;BOTTLE GREEN
323	TROUSERS:ACID RESIST ;152 ;BOTTLE GREEN
324	TROUSERS:ACID RESIST ;157 ;BOTTLE GREEN
325	HELMET SFTY:HEIGHT THREE POINT;WHITE

### 2.1.1 APPLICABILITY

This document is applicable to Kriel Power Station and services provide to Supply and deliver of ENGEN GENCIRC 46 IN BULK “as and when required

## NORMATIVE/INFORMATIVE REFERENCES

### 2.1.2 NORMATIVE

- [1] ISO 9000: Quality Management Systems.
- [2] Occupational Health and Safety Act (Osh Act; Act 85 of 93)

## 2.2 General arrangement and location drawings

NOT APPLICABLE

### 2.2.1 INFORMATIVE

Not applicable.

## 2.3 DEFINITIONS

### 2.3.1 DISCLOSURE CLASSIFICATION

**Controlled Disclosure:** Controlled Disclosure to external parties (either enforced by law, or discretionary)

## CONTROLLED DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

## 2.4 ABBREVIATIONS

Abbreviations	Description
AKZ	Anlagen Kenn Zeichnungs
BOQ	Bill of Quantities
C&I	Control and Instrumentation
CAD	Computer Aided Design
ESP	Electro static precipitator
EMD	Electrical Maintenance Department
HAZOP	Hazard and Operability Analysis
NDT	Non-Destructive Testing
OHSA	Occupational Health and Safety Act
PEI	Production Engineering Integration
PPE	Personal Protective Equipment
PTW	Permit To Work
QA	Quality Assurance
QC	Quality Control
QCP	Quality control program/plan/procedure
SO3	Sulphur Tri-Oxide
RO	Reverse Osmosis
SHE	Safety, Health & Environmental
SHEQ	Occupational Safety, Health, Environmental, and Quality
SOW	Scope of Work
Unit	Description

### CONTROLLED DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

AVR	Automatic Voltage Regulator
AC	Alternative Current
Kv	Kilovolts
MV	Medium Voltage

## **2.5 ROLES AND RESPONSIBILITIES**

Roles and responsibilities are as follows:

System Technical Advisor – Compile contract strategy for the contract

Material Management to manage the PPE Contract.

## **2.6 PROCESS FOR MONITORING**

The QCPs on incoming product and services rendered by the supplier will be done and all materials are to be signed off by the system engineer and hold/witness points should be marked to ensure the quality of the supplied goods is according to standard.

### **CONTROLLED DISCLOSURE**

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

### 3. THE *WORKS*

The *works* is the THE SUPPLY AND DELIVERY OF PERSONAL PROTECTIVE EQUIPMENT (PPE) ACCESSORIES ON AN “AS AND WHEN REQUIRED” BASIS TO ESKOM KRIEL POWER STATION. “as and when required at Kriel Power Station in the Units 1-6 and common plant for Kriel Power Station.

#### 3.1 BACKGROUND

#### 3.2 DESCRIPTION OF THE *WORKS*

##### 3.2.1 SCOPE OF WORK

The scope of work highlighted below is applicable to but not limited to the list of critical components in appendix A.

##### 3.2.1 SCOPE OF WORK

1	COAT DUST:GP;102 CM;COTTON COAT, DUST: TYPE: GENERAL PURPOSE; SIZE: 102 CM; MATERIAL: COTTON; COLOR: BLUE NAVY PANTONE 19-3920; SPECIFICATION: 240-44175132; MATERIAL: PRE-SHRUNK 100 % WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; LENGTH 3/4; POCKET: FRONT BUTTONS; TWO FRONT POCKETS; SLIT AT BACK; BUTTONS ACCEPTABLE FOUR-HOLE; DYED PLASTICS BUTTONS COMPLY WITH SANS 1457 COATS SHALL FASTEN WITH BUTTON AND BUTTONHOLE AND SHALL BE EQUIDISTANTLY SPACED; BUTTONS SECURED TO POSITIONS CORRESPONDING TO BUTTONHOLES; THE PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; THE BACK SHALL HAVE A SEAM DOWN THE CENTRE WITH A VENT IN THE LOWER PART OF THE SEAM; THE VENT SHALL HAVE AN OVERLAP OF 40 MM AND SHALL BE SECURELY TACKED AND BAR-TACKED AT THE TOP; A HANGER LOOP OF OUTER DOUBLE FOLDED MATERIAL OF FINISHED LENGTH AT LEAST 70 MM AND OF FINISHED WIDTH AT LEAST 10 MM; SHALL BE SECURELY SEWN IN WITH THE COLLAR AT THE BACK NECK ON THE INSIDE; THE BOTTOM OF THE COATS AND THE LOWER EDGE OF PLAIN SLEEVE CUFFS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 15 MM; POCKET MOUTHS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 20 MM; EACH GARMENT SHALL HAVE A LABEL SECURELY ATTACHED AT THE CENTRE BACK NECK BELOW THE COLLAR SEAM ON THE INSIDE OF THE GARMENT; THE LABEL SHALL PROVIDE THE FOLLOWING INFORMATION PRINTED IN LEGIBLE AND INDELIBLE BLOCK LETTERS OF HEIGHT AT LEAST 3 MM; MANUFACTURER'S NAME OR TRADEMARK; CHEST SIZE SANS 434:2011 EDITION 5 22; YEAR OF MANUFACTURE; VAT REGISTRATION NUMBER; COUNTRY OF ORIGIN; ITEM TO BEAR SABS MARK OF APPROVAL REFERENCE SANS 434:2011 FIGURE 3 COATS
2	GUMBOOTS SFTY:STL;7;KNEE HEIGHT;BLACK GUMBOOTS, SAFETY: TOE CAP: STL; SIZE: 7; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; SIZE 255; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT; NON SLIP SOLE; WATERPROOF CONSTRUCTION; BEARING SABS MARK OF APPROVAL
3	GUMBOOTS SFTY:STL;8;KNEE HEIGHT;BLACK GUMBOOTS, SAFETY: TOE CAP: STL; SIZE: 8; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; SIZE 262; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT; NON SLIP SOLE; WATERPROOF CONSTRUCTION; TO SABS 20345

#### CONTROLLED DISCLOSURE



4	GUMBOOTS SFTY:STL;9;KNEE HEIGHT;BLACK GUMBOOTS, SAFETY: TOE CAP: STL; SIZE: 9; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; SIZE 270; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT; NON SLIP SOLE; WATERPROOF CONSTRUCTION; TO SABS 20345
5	GUMBOOTS SFTY:STL;10;KNEE HEIGHT;BLACK GUMBOOTS, SAFETY: TOE CAP: STL; SIZE: 10; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; SIZE 280; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT; NON SLIP SOLE; WATERPROOF CONSTRUCTION; TO SABS 20345
6	GUMBOOTS SFTY:STL;11;KNEE HEIGHT;BLACK GUMBOOTS, SAFETY: TOE CAP: STL; SIZE: 11; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; SIZE: 290; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT; NON SLIP SOLE; WATERPROOF CONSTRUCTION; TO SABS 20345
7	COAT DUST:GP;112 CM;COTTON COAT, DUST: TYPE: GENERAL PURPOSE; SIZE: 112 CM; MATERIAL: COTTON; COLOR: BLUE NAVY PANTONE 19-3920; SPECIFICATION: 240-44175132; MATERIAL: PRE-SHRUNK 100 % WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; LENGTH 3/4; POCKET: FRONT BUTTONS; TWO FRONT POCKETS; SLIT AT BACK; BUTTONS ACCEPTABLE FOUR-HOLE; DYED PLASTICS BUTTONS COMPLY WITH SANS 1457 COATS SHALL FASTEN WITH BUTTON AND BUTTONHOLE AND SHALL BE EQUIDISTANTLY SPACED; BUTTONS SECURED TO POSITIONS CORRESPONDING TO BUTTONHOLES; THE PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; THE BACK SHALL HAVE A SEAM DOWN THE CENTRE WITH A VENT IN THE LOWER PART OF THE SEAM; THE VENT SHALL HAVE AN OVERLAP OF 40 MM AND SHALL BE SECURELY TACKED AND BAR-TACKED AT THE TOP; A HANGER LOOP OF OUTER DOUBLE FOLDED MATERIAL OF FINISHED LENGTH AT LEAST 70 MM AND OF FINISHED WIDTH AT LEAST 10 MM; SHALL BE SECURELY SEWN IN WITH THE COLLAR AT THE BACK NECK ON THE INSIDE; THE BOTTOM OF THE COATS AND THE LOWER EDGE OF PLAIN SLEEVE CUFFS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 15 MM; POCKET MOUTHS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 20 MM; EACH GARMENT SHALL HAVE A LABEL SECURELY ATTACHED AT THE CENTRE BACK NECK BELOW THE COLLAR SEAM ON THE INSIDE OF THE GARMENT; THE LABEL SHALL PROVIDE THE FOLLOWING INFORMATION PRINTED IN LEGIBLE AND INDELIBLE BLOCK LETTERS OF HEIGHT AT LEAST 3 MM; MANUFACTURER'S NAME OR TRADEMARK; CHEST SIZE SANS 434:2011 EDITION 5 22; YEAR OF MANUFACTURE; VAT REGISTRATION NUMBER; COUNTRY OF ORIGIN; ITEM TO BEAR SABS MARK OF APPROVAL REFERENCE SANS 434:2011 FIGURE 3 COATS
8	COAT DUST:GP;107 CM;COTTON COAT, DUST: TYPE: GENERAL PURPOSE; SIZE: 107 CM; MATERIAL: COTTON; COLOR: BLUE NAVY PANTONE 19-3920; SPECIFICATION: 240-44175132; MATERIAL: PRE-SHRUNK 100 % WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; LENGTH 3/4; POCKET: FRONT BUTTONS; TWO FRONT POCKETS; SLIT AT BACK; BUTTONS ACCEPTABLE FOUR-HOLE; DYED PLASTICS BUTTONS COMPLY WITH SANS 1457 COATS SHALL FASTEN WITH BUTTON AND BUTTONHOLE AND SHALL BE EQUIDISTANTLY SPACED; BUTTONS SECURED TO POSITIONS CORRESPONDING TO BUTTONHOLES; THE PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; THE BACK SHALL HAVE A SEAM DOWN THE CENTRE WITH A VENT IN THE LOWER PART OF THE SEAM; THE VENT SHALL HAVE AN OVERLAP OF 40 MM AND SHALL BE SECURELY TACKED AND BAR-TACKED AT THE TOP; A HANGER LOOP OF OUTER DOUBLE FOLDED MATERIAL OF FINISHED LENGTH AT LEAST 70 MM AND OF FINISHED WIDTH AT LEAST 10 MM; SHALL BE SECURELY SEWN IN WITH THE COLLAR AT THE BACK NECK ON THE INSIDE; THE BOTTOM OF THE COATS AND THE LOWER EDGE OF

**CONTROLLED DISCLOSURE**



	PLAIN SLEEVE CUFFS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 15 MM; POCKET MOUTHS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 20 MM; EACH GARMENT SHALL HAVE A LABEL SECURELY ATTACHED AT THE CENTRE BACK NECK BELOW THE COLLAR SEAM ON THE INSIDE OF THE GARMENT; THE LABEL SHALL PROVIDE THE FOLLOWING INFORMATION PRINTED IN LEGIBLE AND INDELIBLE BLOCK LETTERS OF HEIGHT AT LEAST 3 MM; MANUFACTURER'S NAME OR TRADEMARK; CHEST SIZE SANS 434:2011 EDITION 5 22; YEAR OF MANUFACTURE; VAT REGISTRATION NUMBER; COUNTRY OF ORIGIN; ITEM TO BEAR SABS MARK OF APPROVAL REFERENCE SANS 434:2011 FIGURE 3 COATS
9	COAT DUST:GP;97 CM;COTTON COAT, DUST: TYPE: GENERAL PURPOSE; SIZE: 97 CM; MATERIAL: COTTON; COLOR: BLUE NAVY PANTONE 19-3920; SPECIFICATION: 240-44175132; MATERIAL: PRE-SHRUNK 100 % WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; LENGTH 3/4; POCKET: FRONT BUTTONS; TWO FRONT POCKETS; SLIT AT BACK; BUTTONS ACCEPTABLE FOUR-HOLE; DYED PLASTICS BUTTONS COMPLY WITH SANS 1457 COATS SHALL FASTEN WITH BUTTON AND BUTTONHOLE AND SHALL BE EQUIDISTANTLY SPACED; BUTTONS SECURED TO POSITIONS CORRESPONDING TO BUTTONHOLES; THE PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; THE BACK SHALL HAVE A SEAM DOWN THE CENTRE WITH A VENT IN THE LOWER PART OF THE SEAM; THE VENT SHALL HAVE AN OVERLAP OF 40 MM AND SHALL BE SECURELY TACKED AND BAR-TACKED AT THE TOP; A HANGER LOOP OF OUTER DOUBLE FOLDED MATERIAL OF FINISHED LENGTH AT LEAST 70 MM AND OF FINISHED WIDTH AT LEAST 10 MM; SHALL BE SECURELY SEWN IN WITH THE COLLAR AT THE BACK NECK ON THE INSIDE; THE BOTTOM OF THE COATS AND THE LOWER EDGE OF PLAIN SLEEVE CUFFS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 15 MM; POCKET MOUTHS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 20 MM; EACH GARMENT SHALL HAVE A LABEL SECURELY ATTACHED AT THE CENTRE BACK NECK BELOW THE COLLAR SEAM ON THE INSIDE OF THE GARMENT; THE LABEL SHALL PROVIDE THE FOLLOWING INFORMATION PRINTED IN LEGIBLE AND INDELIBLE BLOCK LETTERS OF HEIGHT AT LEAST 3 MM; MANUFACTURER'S NAME OR TRADEMARK; CHEST SIZE SANS 434:2011 EDITION 5 22; YEAR OF MANUFACTURE; VAT REGISTRATION NUMBER; COUNTRY OF ORIGIN; ITEM TO BEAR SABS MARK OF APPROVAL REFERENCE SANS 434:2011 FIGURE 3 COATS
10	COAT DUST:GP;87 CM;COTTON COAT, DUST: TYPE: GENERAL PURPOSE; SIZE: 87 CM; MATERIAL: COTTON; COLOR: BLUE NAVY PANTONE 19-3920; SPECIFICATION: 240-44175132; MATERIAL: PRE-SHRUNK 100 % WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; LENGTH 3/4; POCKET: FRONT BUTTONS; TWO FRONT POCKETS; SLIT AT BACK; BUTTONS ACCEPTABLE FOUR-HOLE; DYED PLASTICS BUTTONS COMPLY WITH SANS 1457 COATS SHALL FASTEN WITH BUTTON AND BUTTONHOLE AND SHALL BE EQUIDISTANTLY SPACED; BUTTONS SECURED TO POSITIONS CORRESPONDING TO BUTTONHOLES; THE PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; THE BACK SHALL HAVE A SEAM DOWN THE CENTRE WITH A VENT IN THE LOWER PART OF THE SEAM; THE VENT SHALL HAVE AN OVERLAP OF 40 MM AND SHALL BE SECURELY TACKED AND BAR-TACKED AT THE TOP; A HANGER LOOP OF OUTER DOUBLE FOLDED MATERIAL OF FINISHED LENGTH AT LEAST 70 MM AND OF FINISHED WIDTH AT LEAST 10 MM; SHALL BE SECURELY SEWN IN WITH THE COLLAR AT THE BACK NECK ON THE INSIDE; THE BOTTOM OF THE COATS AND THE LOWER EDGE OF PLAIN SLEEVE CUFFS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 15 MM; POCKET MOUTHS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 20 MM; EACH GARMENT SHALL HAVE A LABEL SECURELY ATTACHED AT THE CENTRE BACK NECK BELOW THE COLLAR SEAM ON THE INSIDE OF THE GARMENT; THE LABEL SHALL PROVIDE THE FOLLOWING INFORMATION PRINTED IN LEGIBLE AND INDELIBLE BLOCK LETTERS OF HEIGHT AT LEAST 3 MM; MANUFACTURER'S NAME OR TRADEMARK; CHEST SIZE SANS 434:2011 EDITION 5 22;

**CONTROLLED DISCLOSURE**

	YEAR OF MANUFACTURE; VAT REGISTRATION NUMBER; COUNTRY OF ORIGIN; ITEM TO BEAR SABS MARK OF APPROVAL REFERENCE SANS 434:2011 FIGURE 3 COATS
11	COAT DUST:GP;117 CM;COTTON COAT, DUST: TYPE: GENERAL PURPOSE; SIZE: 117 CM; MATERIAL: COTTON; COLOR: BLUE NAVY PANTONE 19-3920; SPECIFICATION: 240-44175132; MATERIAL: PRE-SHRUNK 100 % WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; LENGTH 3/4; POCKET: FRONT BUTTONS; TWO FRONT POCKETS; SLIT AT BACK; BUTTONS ACCEPTABLE FOUR-HOLE; DYED PLASTICS BUTTONS COMPLY WITH SANS 1457 COATS SHALL FASTEN WITH BUTTON AND BUTTONHOLE AND SHALL BE EQUIDISTANTLY SPACED; BUTTONS SECURED TO POSITIONS CORRESPONDING TO BUTTONHOLES; THE PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; THE BACK SHALL HAVE A SEAM DOWN THE CENTRE WITH A VENT IN THE LOWER PART OF THE SEAM; THE VENT SHALL HAVE AN OVERLAP OF 40 MM AND SHALL BE SECURELY TACKED AND BAR-TACKED AT THE TOP; A HANGER LOOP OF OUTER DOUBLE FOLDED MATERIAL OF FINISHED LENGTH AT LEAST 70 MM AND OF FINISHED WIDTH AT LEAST 10 MM; SHALL BE SECURELY SEWN IN WITH THE COLLAR AT THE BACK NECK ON THE INSIDE; THE BOTTOM OF THE COATS AND THE LOWER EDGE OF PLAIN SLEEVE CUFFS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 15 MM; POCKET MOUTHS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 20 MM; EACH GARMENT SHALL HAVE A LABEL SECURELY ATTACHED AT THE CENTRE BACK NECK BELOW THE COLLAR SEAM ON THE INSIDE OF THE GARMENT; THE LABEL SHALL PROVIDE THE FOLLOWING INFORMATION PRINTED IN LEGIBLE AND INDELIBLE BLOCK LETTERS OF HEIGHT AT LEAST 3 MM; MANUFACTURER'S NAME OR TRADEMARK; CHEST SIZE SANS 434:2011 EDITION 5 22; YEAR OF MANUFACTURE; VAT REGISTRATION NUMBER; COUNTRY OF ORIGIN; ITEM TO BEAR SABS MARK OF APPROVAL REFERENCE SANS 434:2011 FIGURE 3 COATS
12	COAT DUST:GP;122 CM;COTTON COAT, DUST: TYPE: GENERAL PURPOSE; SIZE: 122 CM; MATERIAL: COTTON; COLOR: BLUE NAVY PANTONE 19-3920; SPECIFICATION: 240-44175132; MATERIAL: PRE-SHRUNK 100 % WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; LENGTH 3/4; POCKET: FRONT BUTTONS; TWO FRONT POCKETS; SLIT AT BACK; BUTTONS ACCEPTABLE FOUR-HOLE; DYED PLASTICS BUTTONS COMPLY WITH SANS 1457 COATS SHALL FASTEN WITH BUTTON AND BUTTONHOLE AND SHALL BE EQUIDISTANTLY SPACED; BUTTONS SECURED TO POSITIONS CORRESPONDING TO BUTTONHOLES; THE PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; THE BACK SHALL HAVE A SEAM DOWN THE CENTRE WITH A VENT IN THE LOWER PART OF THE SEAM; THE VENT SHALL HAVE AN OVERLAP OF 40 MM AND SHALL BE SECURELY TACKED AND BAR-TACKED AT THE TOP; A HANGER LOOP OF OUTER DOUBLE FOLDED MATERIAL OF FINISHED LENGTH AT LEAST 70 MM AND OF FINISHED WIDTH AT LEAST 10 MM; SHALL BE SECURELY SEWN IN WITH THE COLLAR AT THE BACK NECK ON THE INSIDE; THE BOTTOM OF THE COATS AND THE LOWER EDGE OF PLAIN SLEEVE CUFFS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 15 MM; POCKET MOUTHS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 20 MM; EACH GARMENT SHALL HAVE A LABEL SECURELY ATTACHED AT THE CENTRE BACK NECK BELOW THE COLLAR SEAM ON THE INSIDE OF THE GARMENT; THE LABEL SHALL PROVIDE THE FOLLOWING INFORMATION PRINTED IN LEGIBLE AND INDELIBLE BLOCK LETTERS OF HEIGHT AT LEAST 3 MM; MANUFACTURER'S NAME OR TRADEMARK; CHEST SIZE SANS 434:2011 EDITION 5 22; YEAR OF MANUFACTURE; VAT REGISTRATION NUMBER; COUNTRY OF ORIGIN; ITEM TO BEAR SABS MARK OF APPROVAL REFERENCE SANS 434:2011 FIGURE 3 COATS
13	COAT DUST:GP;82 CM;COTTON COAT, DUST: TYPE: GENERAL PURPOSE; SIZE: 82 CM; MATERIAL: COTTON; COLOR: BLUE NAVY PANTONE 19-3920; SPECIFICATION: 240-44175132; MATERIAL: PRE-SHRUNK 100 % WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; LENGTH 3/4; POCKET: FRONT BUTTONS; TWO FRONT POCKETS; SLIT AT BACK; BUTTONS ACCEPTABLE FOUR-HOLE;

**CONTROLLED DISCLOSURE**

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

	DYED PLASTICS BUTTONS COMPLY WITH SANS 1457 COATS SHALL FASTEN WITH BUTTON AND BUTTONHOLE AND SHALL BE EQUIDISTANTLY SPACED; BUTTONS SECURED TO POSITIONS CORRESPONDING TO BUTTONHOLES; THE PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; THE BACK SHALL HAVE A SEAM DOWN THE CENTRE WITH A VENT IN THE LOWER PART OF THE SEAM; THE VENT SHALL HAVE AN OVERLAP OF 40 MM AND SHALL BE SECURELY TACKED AND BAR-TACKED AT THE TOP; A HANGER LOOP OF OUTER DOUBLE FOLDED MATERIAL OF FINISHED LENGTH AT LEAST 70 MM AND OF FINISHED WIDTH AT LEAST 10 MM; SHALL BE SECURELY SEWN IN WITH THE COLLAR AT THE BACK NECK ON THE INSIDE; THE BOTTOM OF THE COATS AND THE LOWER EDGE OF PLAIN SLEEVE CUFFS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 15 MM; POCKET MOUTHS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 20 MM; EACH GARMENT SHALL HAVE A LABEL SECURELY ATTACHED AT THE CENTRE BACK NECK BELOW THE COLLAR SEAM ON THE INSIDE OF THE GARMENT; THE LABEL SHALL PROVIDE THE FOLLOWING INFORMATION PRINTED IN LEGIBLE AND INDELIBLE BLOCK LETTERS OF HEIGHT AT LEAST 3 MM; MANUFACTURER'S NAME OR TRADEMARK; CHEST SIZE SANS 434:2011 EDITION 5 22; YEAR OF MANUFACTURE; VAT REGISTRATION NUMBER; COUNTRY OF ORIGIN; ITEM TO BEAR SABS MARK OF APPROVAL REFERENCE SANS 434:2011 FIGURE 3 COATS
14	APRON:CHEMICAL;WD 700 MM X LG 1.1 M APRON: TYPE: CHEMICAL; SIZE: WD 700 MM X LG 1.1 M; MATERIAL: PVC HEAVY DUTY; STYLE: FULL LENGTH; 400 GRAMS P/M3; PVC COATED POLYESTER; COLOUR HIGH VISIBILITY YELLOW; TEAR STRENGTH WELF 40N WARP 30N; BURST STRENGTH WELF 655N/50MM WARP 1232N/50MM; COATING ADHESIVE 15N/50MM; BASE FABRIC 100% POLYESTER WEIGHT 80 GRAMS PER M/3; YARN/CM 16 X 14.5; HOOK AND LOOP TAPE 20MM-WHITE; DRAW CORD 3MM POLYESTER; SEAMS HIGH FREQUENCY WELDED; WITH ADJUSTABLE NECK STRAP; ONE SIZE'S FITS ALL; UNIQUE IDENTIFIER 240-44175132
15	GUMBOOTS SFTY:STL;6;KNEE HEIGHT;BLACK GUMBOOTS, SAFETY: TOE CAP: STL; SIZE: 6; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; SIZE 247; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT; NON SLIP SOLE; WATERPROOF CONSTRUCTION; TO SABS 20345
16	GUMBOOTS SFTY:STL;12;KNEE HEIGHT;BLACK GUMBOOTS, SAFETY: TOE CAP: STL; SIZE: 12; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; SIZE 292, STYLE F881-982, TO SABS REF 492-1982 PART II
17	GUMBOOTS SFTY:STL;13;KNEE HEIGHT;BLACK GUMBOOTS, SAFETY: TOE CAP: STL; SIZE: 13; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; SIZE 300; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT; NON SLIP SOLE; WATERPROOF CONSTRUCTION; TO SABS 20345
18	BAG DFFL:BLUE NAVY;PVC CANVAS BAG, DUFFEL: COLOR: BLUE NAVY; MATERIAL: PVC CANVAS; DIMENSIONS: DIA 300 X LG 600 MM; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; KIT MATERIAL: HARD WEARING WITH DRAW STRING CLOSURE A LABLE HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON ONE SIDE OF TOG BAG ESKOM LOGO SHALL APPEAR IN WHITE SILKSCREEN PRINTING AND THE ZERO HARM IDENTIFICATION SHALL BE SILKSCREEN PRINTED ON THE BAG AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY TEST/CERT IDENTIFICATION AND SPECIFICATION REQUIREMENTS: IDENTIFICATION: INDELIBLE MNFRS TRADEMARK AND PART/REF NO ON ITEMS; UNIQUE IDENTIFIER: 240-44175132 VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER.
19	JACKET UTIL:OPERATING;147 CM JACKET, UTILITY: TYPE: OPERATING; SIZE: 147 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS;

**CONTROLLED DISCLOSURE**

	POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM
20	JACKET UTIL:OPERATING;137 CM JACKET, UTILITY: TYPE: OPERATING; SIZE: 137 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM
21	JACKET UTIL:OPERATING;157 CM JACKET, UTILITY: TYPE: OPERATING; SIZE: 157 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM

**CONTROLLED DISCLOSURE**



	POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM
22	APRON WLDR:FULL LENGTH;WD 24 X LG 42 IN APRON, WELDER: GARMENT STYLE: FULL LENGTH; GARMENT SIZE: WD 24 X LG 42 IN; MATERIAL: LEATHER COWHIDE; SUPPL P/N: BSA-2442; WITH ADJUSTABLE NECK STRAP; MUST PROVIDE COMPLETE FRONT BODY PROTECTION; NOTE! EACH APRON MUST BE PROTECTIVE PACKED AND SEALED IN A PLASTIC BAG; UNIQUE IDENTIFIER 240-44175132
23	JACKET UTIL:THERMAL;5XL JACKET, UTILITY: TYPE: THERMAL; SIZE: 5XL; MATERIAL: COTTON, D59, FLAME RETARDANT; COLOR: BLUE PANTO 19-3920; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INSULATED WITH PRE-SHRUNK HOLLOW FIBRE OR A NON-FLAMMABLE MATERIAL; WITH THE OUTER COVERING MADE OF PRE-SHRUNK 100 % WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; JACKET LENGTH TO REACH BELOW THE BUTTOCKS; POCKETS ONE CHEST POCKET SHALL BE BELLOWS TYPE - 15CM DEEP AND 14CM WIDE; 4 SIDE POCKETS; POCKETS TO HAVE FLAPS WITH CUT-OFF EDGES THAT CAN BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; THE SIDE POCKET SHALL BE THE BELLOWS TYPE WITH A SIDE ENTRY INTO ANOTHER SEPARATE POCKET AND SHALL BE 22CM DEEP AND 21CM WIDE; JACKETS SHALL HAVE NON-CONDUCTIVE PRESS STUDS DOWN THE FRONT ON A DOUBLE PANEL STRIP AS WELL AS A NON-CONDUCTIVE ZIP; THE SLEEVE CUFFS SHALL HAVE TWO NON-CONDUCTIVE PRESS STUDS AT THE END OF THE SLEEVE SO THAT THE SIZE CAN BE ADJUSTED; IDENTIFICATION: INDELIBLE MNFRS TRADEMARK REF NO. AND CLEANING INSTRUCTIONS INSIDE COLLAR ON JACKETS AND SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS; REFER TO UNIQUE IDENTIFIER 240-44175132
24	JACKET UTIL:THERMAL;4XL JACKET, UTILITY: TYPE: THERMAL; SIZE: 4XL; MATERIAL: COTTON, D59, FLAME RETARDANT; COLOR: BLUE PANTO 19-3920; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INSULATED WITH PRE-SHRUNK HOLLOW FIBRE OR A NON-FLAMMABLE MATERIAL; WITH THE OUTER COVERING MADE OF PRE-SHRUNK 100 % WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; JACKET LENGTH TO REACH BELOW THE BUTTOCKS; POCKETS ONE CHEST POCKET SHALL BE BELLOWS TYPE - 15CM DEEP AND 14CM WIDE; 4 SIDE POCKETS; POCKETS TO HAVE FLAPS WITH CUT-OFF EDGES THAT CAN BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; THE SIDE POCKET SHALL BE THE BELLOWS TYPE WITH A SIDE ENTRY INTO ANOTHER SEPARATE POCKET AND SHALL BE 22CM DEEP AND 21CM WIDE; JACKETS SHALL HAVE NON-CONDUCTIVE PRESS STUDS DOWN THE FRONT ON A DOUBLE PANEL STRIP AS WELL AS A NON-CONDUCTIVE ZIP; THE SLEEVE CUFFS SHALL HAVE TWO NON-CONDUCTIVE PRESS STUDS AT THE END OF THE SLEEVE SO THAT THE SIZE CAN BE ADJUSTED; IDENTIFICATION: INDELIBLE MNFRS TRADEMARK REF NO.

**CONTROLLED DISCLOSURE**

	AND CLEANING INSTRUCTIONS INSIDE COLLAR ON JACKETS AND SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS; REFER TO UNIQUE IDENTIFIER 240-44175132
25	HAT:SOFT BUSH;S; 56;BLUE NAVY HAT: TYPE: SOFT BUSH; SIZE: S; 56; COLOR: BLUE NAVY; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, WOVEN PRE SHRUNK; THE ESKOM LOGO SHALL BE EMBROIDERED ON THE FRONT OF THE HAT AND THE ZERO HARM IDENTIFICATION SHALL BE EMBROIDERED ON THE REAR OF THE HAT AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; SOFT HATS SHALL HAVE A REINFORCED STIFFENED BROAD BRIM OF AT LEAST 80 MM; STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD SHALL COMPLY WITH SANS 1362; ALL GARMENTS MUST BEAR THE S.A.B.S. MARK OF APPROVAL; FULL WASHING INSTRUCTIONS; SIZE AND TRACEABILITY SHALL BE MARKED WITH SANS 432 INDELIBLE MARKING INK FOR TEXTILE FABRICS ON HAT; UNIQUE IDENTIFIER 240-44175132
26	HAT:SOFT BUSH;M; 57;BLUE NAVY HAT: TYPE: SOFT BUSH; SIZE: M; 57; COLOR: BLUE NAVY; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, WOVEN PRE SHRUNK; THE ESKOM LOGO SHALL BE EMBROIDERED ON THE FRONT OF THE HAT AND THE ZERO HARM IDENTIFICATION SHALL BE EMBROIDERED ON THE REAR OF THE HAT AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; SOFT HATS SHALL HAVE A REINFORCED STIFFENED BROAD BRIM OF AT LEAST 80 MM; STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD SHALL COMPLY WITH SANS 1362; ALL GARMENTS MUST BEAR THE S.A.B.S. MARK OF APPROVAL; FULL WASHING INSTRUCTIONS; SIZE AND TRACEABILITY SHALL BE MARKED WITH SANS 432 INDELIBLE MARKING INK FOR TEXTILE FABRICS ON HAT; UNIQUE IDENTIFIER 240-44175132
27	HAT:SOFT BUSH;L; 58;BLUE NAVY HAT: TYPE: SOFT BUSH; SIZE: L; 58; COLOR: BLUE NAVY; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, WOVEN PRE SHRUNK; THE ESKOM LOGO SHALL BE EMBROIDERED ON THE FRONT OF THE HAT AND THE ZERO HARM IDENTIFICATION SHALL BE EMBROIDERED ON THE REAR OF THE HAT AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; SOFT HATS SHALL HAVE A REINFORCED STIFFENED BROAD BRIM OF AT LEAST 80 MM; STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD SHALL COMPLY WITH SANS 1362; ALL GARMENTS MUST BEAR THE S.A.B.S. MARK OF APPROVAL; FULL WASHING INSTRUCTIONS; SIZE AND TRACEABILITY SHALL BE MARKED WITH SANS 432 INDELIBLE MARKING INK FOR TEXTILE FABRICS ON HAT; UNIQUE IDENTIFIER 240-44175132
28	HAT:SOFT BUSH;XL; 59;BLUE NAVY HAT: TYPE: SOFT BUSH; SIZE: XL; 59; COLOR: BLUE NAVY; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, WOVEN PRE SHRUNK; THE ESKOM LOGO SHALL BE EMBROIDERED ON THE FRONT OF THE HAT AND THE ZERO HARM IDENTIFICATION SHALL BE EMBROIDERED ON THE REAR OF THE HAT AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; SOFT HATS SHALL HAVE A REINFORCED STIFFENED BROAD BRIM OF AT LEAST 80 MM; STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD SHALL COMPLY WITH SANS 1362; ALL GARMENTS MUST BEAR THE S.A.B.S. MARK OF APPROVAL; FULL WASHING INSTRUCTIONS; SIZE AND TRACEABILITY SHALL BE MARKED WITH SANS 432 INDELIBLE MARKING INK FOR TEXTILE FABRICS ON HAT; UNIQUE IDENTIFIER 240-44175132
29	SHIRT:MEN L/SLEEVE;36 CM;COTTON;GRAY SHIRT: TYPE: MEN L/SLEEVE; SIZE: 36 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF- 65 MM WIDE SET IN LONG SLEEVE WITH TWO KNIFE PLEATS SEPARATE THE CUFF WITH BUTTON CLOSURE OF NON-CONDUCTIVE BUTTONS; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER; SLEEVE AND BACK YOKE

**CONTROLLED DISCLOSURE**

	POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132
30	SHIRT:MEN L/SLEEVE;37 CM;COTTON;GRAY SHIRT: TYPE: MEN L/SLEEVE; SIZE: 37 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF- 65 MM WIDE SET IN LONG SLEEVE WITH TWO KNIFE PLEATS SEPARATE THE CUFF WITH BUTTON CLOSURE OF NON-CONDUCTIVE BUTTONS; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER; SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132
31	SHIRT:MEN L/SLEEVE;38 CM;COTTON;GRAY SHIRT: TYPE: MEN L/SLEEVE; SIZE: 38 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF- 65 MM WIDE SET IN LONG SLEEVE WITH TWO KNIFE PLEATS SEPARATE THE CUFF WITH BUTTON CLOSURE OF NON-CONDUCTIVE BUTTONS; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER; SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132
32	SHIRT:MEN L/SLEEVE;39 CM;COTTON;GRAY SHIRT: TYPE: MEN L/SLEEVE; SIZE: 39 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF- 65 MM WIDE SET IN LONG SLEEVE WITH TWO KNIFE PLEATS SEPARATE THE CUFF WITH BUTTON CLOSURE OF NON-CONDUCTIVE BUTTONS; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER; SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132

**CONTROLLED DISCLOSURE**

33	SHIRT:MEN L/SLEEVE;40 CM;COTTON;GRAY SHIRT: TYPE: MEN L/SLEEVE; SIZE: 40 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF- 65 MM WIDE SET IN LONG SLEEVE WITH TWO KNIFE PLEATS SEPARATE THE CUFF WITH BUTTON CLOSURE OF NON-CONDUCTIVE BUTTONS; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER; SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-4417532
34	SHIRT:MEN L/SLEEVE;41 CM;COTTON;GRAY SHIRT: TYPE: MEN L/SLEEVE; SIZE: 41 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF- 65 MM WIDE SET IN LONG SLEEVE WITH TWO KNIFE PLEATS SEPARATE THE CUFF WITH BUTTON CLOSURE OF NON-CONDUCTIVE BUTTONS; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER; SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132
35	SHIRT:MEN L/SLEEVE;42 CM;COTTON;GRAY SHIRT: TYPE: MEN L/SLEEVE; SIZE: 42 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF- 65 MM WIDE SET IN LONG SLEEVE WITH TWO KNIFE PLEATS SEPARATE THE CUFF WITH BUTTON CLOSURE OF NON-CONDUCTIVE BUTTONS; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER; SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132
36	SHIRT:MEN L/SLEEVE;43 CM;COTTON;GRAY SHIRT: TYPE: MEN L/SLEEVE; SIZE: 43 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1;

**CONTROLLED DISCLOSURE**



	SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF- 65 MM WIDE SET IN LONG SLEEVE WITH TWO KNIFE PLEATS SEPARATE THE CUFF WITH BUTTON CLOSURE OF NON-CONDUCTIVE BUTTONS; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER; SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132
37	SHIRT:MEN L/SLEEVE;44 CM;COTTON;GRAY SHIRT: TYPE: MEN L/SLEEVE; SIZE: 44 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF- 65 MM WIDE SET IN LONG SLEEVE WITH TWO KNIFE PLEATS SEPARATE THE CUFF WITH BUTTON CLOSURE OF NON-CONDUCTIVE BUTTONS; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER; SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132
38	SHIRT:MEN L/SLEEVE;45 CM;COTTON;GRAY SHIRT: TYPE: MEN L/SLEEVE; SIZE: 45 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF- 65 MM WIDE SET IN LONG SLEEVE WITH TWO KNIFE PLEATS SEPARATE THE CUFF WITH BUTTON CLOSURE OF NON-CONDUCTIVE BUTTONS; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER; SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132
39	SHIRT:MEN L/SLEEVE;46 CM;COTTON;GRAY SHIRT: TYPE: MEN L/SLEEVE; SIZE: 46 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT

**CONTROLLED DISCLOSURE**

	EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF- 65 MM WIDE SET IN LONG SLEEVE WITH TWO KNIFE PLEATS SEPARATE THE CUFF WITH BUTTON CLOSURE OF NON-CONDUCTIVE BUTTONS; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER; SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132
40	SHIRT:MEN L/SLEEVE;47 CM;COTTON;GRAY SHIRT: TYPE: MEN L/SLEEVE; SIZE: 47 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF- 65 MM WIDE SET IN LONG SLEEVE WITH TWO KNIFE PLEATS SEPARATE THE CUFF WITH BUTTON CLOSURE OF NON-CONDUCTIVE BUTTONS; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER; SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132
41	SHIRT:MEN L/SLEEVE;48 CM;COTTON;GRAY SHIRT: TYPE: MEN L/SLEEVE; SIZE: 48 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF- 65 MM WIDE SET IN LONG SLEEVE WITH TWO KNIFE PLEATS SEPARATE THE CUFF WITH BUTTON CLOSURE OF NON-CONDUCTIVE BUTTONS; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER; SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132
42	SHIRT:MEN L/SLEEVE;49 CM;COTTON;GRAY SHIRT: TYPE: MEN L/SLEEVE; SIZE: 49 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; LONG-SLEEVED SHIRTS

**CONTROLLED DISCLOSURE**

	SHALL HAVE A CUFF- 65 MM WIDE SET IN LONG SLEEVE WITH TWO KNIFE PLEATS SEPARATE THE CUFF WITH BUTTON CLOSURE OF NON-CONDUCTIVE BUTTONS; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER; SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132
43	SHIRT:MEN S/SLEEVE;36 CM;COTTON;GRAY SHIRT: TYPE: MEN S/SLEEVE; SIZE: 36 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE, ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER, SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132
44	SHIRT:MEN S/SLEEVE;37 CM;COTTON;GRAY SHIRT: TYPE: MEN S/SLEEVE; SIZE: 37 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE, ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER, SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132
45	SHIRT:MEN S/SLEEVE;38 CM;COTTON;GRAY SHIRT: TYPE: MEN S/SLEEVE; SIZE: 38 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE, ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER, SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132
46	SHIRT:MEN S/SLEEVE;39 CM;COTTON;GRAY SHIRT: TYPE: MEN S/SLEEVE; SIZE: 39 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1;

**CONTROLLED DISCLOSURE**

	SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE, ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER, SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132
47	SHIRT:MEN S/SLEEVE;40 CM;COTTON;GRAY SHIRT: TYPE: MEN S/SLEEVE; SIZE: 40 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE, ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER, SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132
48	SHIRT:MEN S/SLEEVE;41 CM;COTTON;GRAY SHIRT: TYPE: MEN S/SLEEVE; SIZE: 41 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE, ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER, SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132
49	SHIRT:MEN S/SLEEVE;42 CM;COTTON;GRAY SHIRT: TYPE: MEN S/SLEEVE; SIZE: 42 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE, ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER, SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132

**CONTROLLED DISCLOSURE**



50	SHIRT:MEN S/SLEEVE;43 CM;COTTON;GRAY SHIRT: TYPE: MEN S/SLEEVE; SIZE: 43 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE, ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER, SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132
51	SHIRT:MEN S/SLEEVE;44 CM;COTTON;GRAY SHIRT: TYPE: MEN S/SLEEVE; SIZE: 44 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE, ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER, SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132
52	SHIRT:MEN S/SLEEVE;45 CM;COTTON;GRAY SHIRT: TYPE: MEN S/SLEEVE; SIZE: 45 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE, ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER, SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132
53	SHIRT:MEN S/SLEEVE;46 CM;COTTON;GRAY SHIRT: TYPE: MEN S/SLEEVE; SIZE: 46 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE, ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND

**CONTROLLED DISCLOSURE**

	SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER, SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132
54	SHIRT:MEN S/SLEEVE;47 CM;COTTON;GRAY SHIRT: TYPE: MEN S/SLEEVE; SIZE: 47 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE, ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER, SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132
55	SHIRT:MEN S/SLEEVE;48 CM;COTTON;GRAY SHIRT: TYPE: MEN S/SLEEVE; SIZE: 48 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE, ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER, SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132
56	SHIRT:MEN S/SLEEVE;49 CM;COTTON;GRAY SHIRT: TYPE: MEN S/SLEEVE; SIZE: 49 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE, ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER, SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132
57	SHIRT WMAN:LONG;77 CM;GRAY;COTTON SHIRT, WOMAN: SLEEVE TYPE: LONG; SIZE: 77 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE LONG SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET

**CONTROLLED DISCLOSURE**

	SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF 65 MM WIDE; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132
58	SHIRT WMAN:LONG;82 CM;GRAY;COTTON SHIRT, WOMAN: SLEEVE TYPE: LONG; SIZE: 82 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE LONG SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF 65 MM WIDE; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132
59	SHIRT WMAN:LONG;87 CM;GRAY;COTTON SHIRT, WOMAN: SLEEVE TYPE: LONG; SIZE: 87 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE LONG SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF 65 MM WIDE; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132
60	SHIRT WMAN:LONG;92 CM;GRAY;COTTON SHIRT, WOMAN: SLEEVE TYPE: LONG; SIZE: 92 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE LONG SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF 65 MM WIDE; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-

**CONTROLLED DISCLOSURE**

	CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132
61	SHIRT WMAN:LONG;102 CM;GRAY;COTTON SHIRT, WOMAN: SLEEVE TYPE: LONG; SIZE: 102 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE LONG SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF 65 MM WIDE; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132
62	SHIRT WMAN:LONG;107 CM;GRAY;COTTON SHIRT, WOMAN: SLEEVE TYPE: LONG; SIZE: 107 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE LONG SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF 65 MM WIDE; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132
63	SHIRT WMAN:LONG;112 CM;GRAY;COTTON SHIRT, WOMAN: SLEEVE TYPE: LONG; SIZE: 112 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE LONG SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF 65 MM WIDE; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132
64	SHIRT WMAN:LONG;117 CM;GRAY;COTTON SHIRT, WOMAN: SLEEVE TYPE: LONG; SIZE: 117 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE

**CONTROLLED DISCLOSURE**



	MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE LONG SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF 65 MM WIDE; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132
65	SHIRT WMAN:LONG;122 CM;GRAY;COTTON SHIRT, WOMAN: SLEEVE TYPE: LONG; SIZE: 122 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE LONG SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF 65 MM WIDE; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132
66	SHIRT WMAN:LONG;127 CM;GRAY;COTTON SHIRT, WOMAN: SLEEVE TYPE: LONG; SIZE: 127 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE LONG SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF 65 MM WIDE; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132
67	SHIRT WMAN:LONG;132 CM;GRAY;COTTON SHIRT, WOMAN: SLEEVE TYPE: LONG; SIZE: 132 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE LONG SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM

**CONTROLLED DISCLOSURE**

	IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF 65 MM WIDE; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132
68	SHIRT WMAN:LONG;137 CM;GRAY;COTTON SHIRT, WOMAN: SLEEVE TYPE: LONG; SIZE: 137 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE LONG SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF 65 MM WIDE; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132
69	SHIRT WMAN:LONG;142 CM;GRAY;COTTON SHIRT, WOMAN: SLEEVE TYPE: LONG; SIZE: 142 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE LONG SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF 65 MM WIDE; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132
70	SHIRT WMAN:LONG;147 CM;GRAY;COTTON SHIRT, WOMAN: SLEEVE TYPE: LONG; SIZE: 147 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE LONG SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF 65 MM WIDE; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE

**CONTROLLED DISCLOSURE**

	HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132
71	SHIRT WMAN:SHORT;77 CM;GRAY;COTTON SHIRT, WOMAN: SLEEVE TYPE: SHORT; SIZE: 77 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE SHORT SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132
72	SHIRT WMAN:SHORT;82 CM;GRAY;COTTON SHIRT, WOMAN: SLEEVE TYPE: SHORT; SIZE: 82 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE SHORT SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132
73	SHIRT WMAN:SHORT;87 CM;GRAY;COTTON SHIRT, WOMAN: SLEEVE TYPE: SHORT; SIZE: 87 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE SHORT SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132
74	SHIRT WMAN:SHORT;92 CM;GRAY;COTTON SHIRT, WOMAN: SLEEVE TYPE: SHORT; SIZE: 92 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE SHORT SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE

**CONTROLLED DISCLOSURE**

	14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132
75	SHIRT WMAN:SHORT;102 CM;GRAY;COTTON SHIRT, WOMAN: SLEEVE TYPE: SHORT; SIZE: 102 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE SHORT SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132
76	SHIRT WMAN:SHORT;107 CM;GRAY;COTTON SHIRT, WOMAN: SLEEVE TYPE: SHORT; SIZE: 107 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE SHORT SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132
77	SHIRT WMAN:SHORT;112 CM;GRAY;COTTON SHIRT, WOMAN: SLEEVE TYPE: SHORT; SIZE: 112 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE SHORT SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE

**CONTROLLED DISCLOSURE**



	STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132
78	SHIRT WMAN:SHORT;117 CM;GRAY;COTTON SHIRT, WOMAN: SLEEVE TYPE: SHORT; SIZE: 117 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE SHORT SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132
79	SHIRT WMAN:SHORT;122 CM;GRAY;COTTON SHIRT, WOMAN: SLEEVE TYPE: SHORT; SIZE: 122 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE SHORT SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132
80	SHIRT WMAN:SHORT;127 CM;GRAY;COTTON SHIRT, WOMAN: SLEEVE TYPE: SHORT; SIZE: 127 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE SHORT SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132
81	SHIRT WMAN:SHORT;132 CM;GRAY;COTTON SHIRT, WOMAN: SLEEVE TYPE: SHORT; SIZE: 132 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE SHORT SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE

**CONTROLLED DISCLOSURE**

	POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132
82	SHIRT WMAN:SHORT;137 CM;GRAY;COTTON SHIRT, WOMAN: SLEEVE TYPE: SHORT; SIZE: 137 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE SHORT SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132
83	SHIRT WMAN:SHORT;142 CM;GRAY;COTTON SHIRT, WOMAN: SLEEVE TYPE: SHORT; SIZE: 142 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE SHORT SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132
84	SHIRT WMAN:SHORT;147 CM;GRAY;COTTON SHIRT, WOMAN: SLEEVE TYPE: SHORT; SIZE: 147 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE SHORT SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132

**CONTROLLED DISCLOSURE**

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

85	TROUSERS:MEN LONG;77 CM;BLUE NAVY TROUSERS: TYPE: MEN LONG; SIZE: 77 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132
86	TROUSERS:MEN LONG;82 CM;BLUE NAVY TROUSERS: TYPE: MEN LONG; SIZE: 82 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132
87	TROUSERS:MEN LONG;87 CM;BLUE NAVY TROUSERS: TYPE: MEN LONG; SIZE: 87 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132
88	TROUSERS:MEN LONG;92 CM;BLUE NAVY TROUSERS: TYPE: MEN LONG; SIZE: 92 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132
89	TROUSERS:MEN LONG;97 CM;BLUE NAVY TROUSERS: TYPE: MEN LONG; SIZE: 97 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132
90	TROUSERS:MEN LONG;102 CM;BLUE NAVY TROUSERS: TYPE: MEN LONG; SIZE: 102 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM

**CONTROLLED DISCLOSURE**



	LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132
91	TROUSERS: MEN LONG; 107 CM; BLUE NAVY TROUSERS: TYPE: MEN LONG; SIZE: 107 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132
92	TROUSERS: MEN LONG; 112 CM; BLUE NAVY TROUSERS: TYPE: MEN LONG; SIZE: 112 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132
93	TROUSERS: MEN LONG; 117 CM; BLUE NAVY TROUSERS: TYPE: MEN LONG; SIZE: 117 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132
94	TROUSERS: MEN LONG; 122 CM; BLUE NAVY TROUSERS: TYPE: MEN LONG; SIZE: 122 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132
95	TROUSERS: MEN LONG; 127 CM; BLUE NAVY TROUSERS: TYPE: MEN LONG; SIZE: 127 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132
96	TROUSERS: MEN LONG; 132 CM; BLUE NAVY TROUSERS: TYPE: MEN LONG; SIZE: 132 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT;

**CONTROLLED DISCLOSURE**

	STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132
97	TROUSERS:LADIES LONG;26; 67;BLUE NAVY TROUSERS: TYPE: LADIES LONG; SIZE: 26; 67; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY
98	TROUSERS:LADIES LONG;28; 72;BLUE NAVY TROUSERS: TYPE: LADIES LONG; SIZE: 28; 72; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY
99	TROUSERS:LADIES LONG;30; 77;BLUE NAVY TROUSERS: TYPE: LADIES LONG; SIZE: 30; 77; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY
100	TROUSERS:LADIES LONG;32; 82;BLUE NAVY TROUSERS: TYPE: LADIES LONG; SIZE: 32; 82; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS

**CONTROLLED DISCLOSURE**

	TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY
101	TROUSERS:LADIES LONG;34; 87;BLUE NAVY TROUSERS: TYPE: LADIES LONG; SIZE: 34; 87; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY
102	TROUSERS:LADIES LONG;36; 92;BLUE NAVY TROUSERS: TYPE: LADIES LONG; SIZE: 36; 92; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY
103	TROUSERS:LADIES LONG;38; 97;BLUE NAVY TROUSERS: TYPE: LADIES LONG; SIZE: 38; 97; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY
104	TROUSERS:LADIES LONG;40; 102;BLUE NAVY TROUSERS: TYPE: LADIES LONG; SIZE: 40; 102; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3

**CONTROLLED DISCLOSURE**

	AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY
105	TROUSERS:LADIES LONG;42; 107;BLUE NAVY TROUSERS: TYPE: LADIES LONG; SIZE: 42; 107; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY
106	TROUSERS:LADIES LONG;44; 112;BLUE NAVY TROUSERS: TYPE: LADIES LONG; SIZE: 44; 112; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY
107	TROUSERS:LADIES LONG;46; 117;BLUE NAVY TROUSERS: TYPE: LADIES LONG; SIZE: 46; 117; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY
108	TROUSERS:LADIES LONG;48; 122;BLUE NAVY TROUSERS: TYPE: LADIES LONG; SIZE: 48; 122; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH

**CONTROLLED DISCLOSURE**



	LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY
109	TROUSERS:LADIES LONG;50; 127;BLUE NAVY TROUSERS: TYPE: LADIES LONG; SIZE: 50; 127; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY
110	TROUSERS:LADIES LONG;52; 132;BLUE NAVY TROUSERS: TYPE: LADIES LONG; SIZE: 52; 132; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY
111	COVERALL:ARTISAN BOILER SUIT;77 CM COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 77 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY

**CONTROLLED DISCLOSURE**



	<p>FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>
112	<p>COVERALL:ARTISAN BOILER SUIT;82 CM COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 82 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH</p>

**CONTROLLED DISCLOSURE**

	TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM
113	COVERALL:ARTISAN BOILER SUIT;87 CM COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 87 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM
114	COVERALL:ARTISAN BOILER SUIT;92 CM COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 92 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF

**CONTROLLED DISCLOSURE**

	<p>ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>
115	<p>COVERALL:ARTISAN BOILER SUIT;97 CM COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 97 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND</p>

**CONTROLLED DISCLOSURE**

	<p>STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>
116	<p>JACKET UTIL:OPERATING;87 CM JACKET, UTILITY: TYPE: OPERATING; SIZE: 87 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM</p>
117	<p>JACKET UTIL:OPERATING;97 CM JACKET, UTILITY: TYPE: OPERATING; SIZE: 97 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS;</p>

**CONTROLLED DISCLOSURE**



	POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM
118	JACKET UTIL:OPERATING;107 CM JACKET, UTILITY: TYPE: OPERATING; SIZE: 107 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM
119	JACKET UTIL:OPERATING;117 CM JACKET, UTILITY: TYPE: OPERATING; SIZE: 117 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM

**CONTROLLED DISCLOSURE**



	POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM
120	JACKET UTIL:OPERATING;122 CM JACKET, UTILITY: TYPE: OPERATING; SIZE: 122 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM
121	JACKET UTIL:OPERATING;132 CM JACKET, UTILITY: TYPE: OPERATING; SIZE: 132 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE

**CONTROLLED DISCLOSURE**

	GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM
122	RAINWEAR:2 PIECE SUIT;S;BLUE NAVY RAINWEAR: TYPE: 2 PIECE SUIT; SIZE: S; MATERIAL: POLYESTER 100 PCT PLAIN WEAVE, 180 GM/2 MIN; COLOR: BLUE NAVY; MATERIAL: MINIMUM 180 GRAMS PER M/3 FACE SIDE 100% POLYESTER; PLAIN WEAVE WITH 170 THREADS PER M/3 INCH WITH WATER RESISTANT COATING; UNDER SIDE LAMINATED WITH PVC COATING; SEAMS STRENGTH 50KPA; CONVERTS TO 50KNM/2; LINING 80% POLYESTER 20% COTTON; SIZE TO SANS 434 SIZE CHART ANNEX E FOR RAIN WEAR; JACKET SHALL HAVE A NYLON SPIRAL ZIP WITH CLOSED FLY FRONT SECURED BY NON-CONDUCTIVE PRESS-STUDS; COMPLY WITH SANS 1822 TYPE 5; HOOD ATTACHED TO THE JACKET; JACKET TO COVER THE BUTTOCKS; FALSE ELASTIC SLEEVE AT THE END MADE OF SOFTER MATERIAL; PANTS SHALL HAVE SIDE SLITS AND ELASTIC WAIST; REFLECTIVE STRIPS TO BE FITTED ON BOTH SLEEVES ON THE UPPER ARM, AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SIDE OF THE SLEEVE AND THE ESKOM LOGO SHALL BE SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON THE FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; UNIQUE IDENTIFIER 240-44175132
123	RAINWEAR:2 PIECE SUIT;L;BLUE NAVY RAINWEAR: TYPE: 2 PIECE SUIT; SIZE: L; MATERIAL: POLYESTER 100 PCT PLAIN WEAVE, 180 GM/2 MIN; COLOR: BLUE NAVY; MATERIAL: MINIMUM 180 GRAMS PER M/3 FACE SIDE 100% POLYESTER; PLAIN WEAVE WITH 170 THREADS PER M/3 INCH WITH WATER RESISTANT COATING; UNDER SIDE LAMINATED WITH PVC COATING; SEAMS STRENGTH 50KPA; CONVERTS TO 50KNM/2; LINING 80% POLYESTER 20% COTTON; SIZE TO SANS 434 SIZE CHART ANNEX E FOR RAIN WEAR; JACKET SHALL HAVE A NYLON SPIRAL ZIP WITH CLOSED FLY FRONT SECURED BY NON-CONDUCTIVE PRESS-STUDS; COMPLY WITH SANS 1822 TYPE 5; HOOD ATTACHED TO THE JACKET; JACKET TO COVER THE BUTTOCKS; FALSE ELASTIC SLEEVE AT THE END MADE OF SOFTER MATERIAL; PANTS SHALL HAVE SIDE SLITS AND ELASTIC WAIST; REFLECTIVE STRIPS TO BE FITTED ON BOTH SLEEVES ON THE UPPER ARM, AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SIDE OF THE SLEEVE AND THE ESKOM LOGO SHALL BE SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON THE FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; UNIQUE IDENTIFIER 240-44175132
124	RAINWEAR:2 PIECE SUIT;XL;BLUE NAVY RAINWEAR: TYPE: 2 PIECE SUIT; SIZE: XL; MATERIAL: POLYESTER 100 PCT PLAIN WEAVE, 180 GM/2 MIN; COLOR: BLUE NAVY; MATERIAL: MINIMUM 180 GRAMS PER M/3 FACE SIDE 100% POLYESTER; PLAIN WEAVE WITH 170 THREADS PER M/3 INCH WITH WATER RESISTANT COATING; UNDER SIDE LAMINATED WITH PVC COATING; SEAMS STRENGTH 50KPA; CONVERTS TO 50KNM/2;

**CONTROLLED DISCLOSURE**

	LINING 80% POLYESTER 20% COTTON; SIZE TO SANS 434 SIZE CHART ANNEX E FOR RAIN WEAR; JACKET SHALL HAVE A NYLON SPIRAL ZIP WITH CLOSED FLY FRONT SECURED BY NON-CONDUCTIVE PRESS-STUDS; COMPLY WITH SANS 1822 TYPE 5; HOOD ATTACHED TO THE JACKET; JACKET TO COVER THE BUTTOCKS; FALSE ELASTIC SLEEVE AT THE END MADE OF SOFTER MATERIAL; PANTS SHALL HAVE SIDE SLITS AND ELASTIC WAIST; REFLECTIVE STRIPS TO BE FITTED ON BOTH SLEEVES ON THE UPPER ARM, AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SIDE OF THE SLEEVE AND THE ESKOM LOGO SHALL BE SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON THE FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; UNIQUE IDENTIFIER 240-44175132
125	RAINWEAR:2 PIECE SUIT;2XL;BLUE NAVY RAINWEAR: TYPE: 2 PIECE SUIT; SIZE: 2XL; MATERIAL: POLYESTER 100 PCT PLAIN WEAVE, 180 GM/2 MIN; COLOR: BLUE NAVY; MATERIAL: MINIMUM 180 GRAMS PER M/3 FACE SIDE 100% POLYESTER; PLAIN WEAVE WITH 170 THREADS PER M/3 INCH WITH WATER RESISTANT COATING; UNDER SIDE LAMINATED WITH PVC COATING; SEAMS STRENGTH 50KPA; CONVERTS TO 50KNM/2; LINING 80% POLYESTER 20% COTTON; SIZE TO SANS 434 SIZE CHART ANNEX E FOR RAIN WEAR; JACKET SHALL HAVE A NYLON SPIRAL ZIP WITH CLOSED FLY FRONT SECURED BY NON-CONDUCTIVE PRESS-STUDS; COMPLY WITH SANS 1822 TYPE 5; HOOD ATTACHED TO THE JACKET; JACKET TO COVER THE BUTTOCKS; FALSE ELASTIC SLEEVE AT THE END MADE OF SOFTER MATERIAL; PANTS SHALL HAVE SIDE SLITS AND ELASTIC WAIST; REFLECTIVE STRIPS TO BE FITTED ON BOTH SLEEVES ON THE UPPER ARM, AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SIDE OF THE SLEEVE AND THE ESKOM LOGO SHALL BE SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON THE FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; UNIQUE IDENTIFIER 240-44175132
126	RAINWEAR:2 PIECE SUIT;3XL;BLUE NAVY RAINWEAR: TYPE: 2 PIECE SUIT; SIZE: 3XL; MATERIAL: POLYESTER 100 PCT PLAIN WEAVE, 180 GM/2 MIN; COLOR: BLUE NAVY; MATERIAL: MINIMUM 180 GRAMS PER M/3 FACE SIDE 100% POLYESTER; PLAIN WEAVE WITH 170 THREADS PER M/3 INCH WITH WATER RESISTANT COATING; UNDER SIDE LAMINATED WITH PVC COATING; SEAMS STRENGTH 50KPA; CONVERTS TO 50KNM/2; LINING 80% POLYESTER 20% COTTON; SIZE TO SANS 434 SIZE CHART ANNEX E FOR RAIN WEAR; JACKET SHALL HAVE A NYLON SPIRAL ZIP WITH CLOSED FLY FRONT SECURED BY NON-CONDUCTIVE PRESS-STUDS; COMPLY WITH SANS 1822 TYPE 5; HOOD ATTACHED TO THE JACKET; JACKET TO COVER THE BUTTOCKS; FALSE ELASTIC SLEEVE AT THE END MADE OF SOFTER MATERIAL; PANTS SHALL HAVE SIDE SLITS AND ELASTIC WAIST; REFLECTIVE STRIPS TO BE FITTED ON BOTH SLEEVES ON THE UPPER ARM, AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SIDE OF THE SLEEVE AND THE ESKOM LOGO SHALL BE SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON THE FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; UNIQUE IDENTIFIER 240-44175132
127	BOOTS SFTY:4;STRD; STL OR CARBON FIBER BOOTS, SAFETY: SIZE: 4; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT
128	BOOTS SFTY:5;STRD; STL OR CARBON FIBER BOOTS, SAFETY: SIZE: 5; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER;

**CONTROLLED DISCLOSURE**

	OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT
129	BOOTS SFTY:6;STRD; STL OR CARBON FIBER BOOTS, SAFETY: SIZE: 6; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT
130	BOOTS SFTY:7;STRD; STL OR CARBON FIBER BOOTS, SAFETY: SIZE: 7; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT
131	BOOTS SFTY:8;STRD; STL OR CARBON FIBER BOOTS, SAFETY: SIZE: 8; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT
132	BOOTS SFTY:9;STRD; STL OR CARBON FIBER BOOTS, SAFETY: SIZE: 9; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT
133	BOOTS SFTY:10;STRD; STL OR CARBON FIBER BOOTS, SAFETY: SIZE: 10; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS

**CONTROLLED DISCLOSURE**



	ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT
134	RAINWEAR:2 PIECE SUIT;M;BLUE NAVY RAINWEAR: TYPE: 2 PIECE SUIT; SIZE: M; MATERIAL: POLYESTER 100 PCT PLAIN WEAVE, 180 GM/2 MIN; COLOR: BLUE NAVY; MATERIAL: MINIMUM 180 GRAMS PER M/3 FACE SIDE 100% POLYESTER; PLAIN WEAVE WITH 170 THREADS PER M/3 INCH WITH WATER RESISTANT COATING; UNDER SIDE LAMINATED WITH PVC COATING; SEAMS STRENGTH 50KPA; CONVERTS TO 50KNM/2; LINING 80% POLYESTER 20% COTTON; SIZE TO SANS 434 SIZE CHART ANNEX E FOR RAIN WEAR; JACKET SHALL HAVE A NYLON SPIRAL ZIP WITH CLOSED FLY FRONT SECURED BY NON-CONDUCTIVE PRESS-STUDS; COMPLY WITH SANS 1822 TYPE 5; HOOD ATTACHED TO THE JACKET; JACKET TO COVER THE BUTTOCKS; FALSE ELASTIC SLEEVE AT THE END MADE OF SOFTER MATERIAL; PANTS SHALL HAVE SIDE SLITS AND ELASTIC WAIST; REFLECTIVE STRIPS TO BE FITTED ON BOTH SLEEVES ON THE UPPER ARM, AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SIDE OF THE SLEEVE AND THE ESKOM LOGO SHALL BE SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON THE FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; UNIQUE IDENTIFIER 240-44175132
135	SHOES SFTY:4;BLACK/BROWN;34-232;LACE SHOES, SAFETY: SIZE: 4; TOE CONSTRUCTION TYPE: STL OR CARBON FIBER, WIDE FIT; COLOR: BLACK/BROWN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; MATERIAL: UPPER LEATHER FULL GRAIN; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; WIDE; SHOES TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; THE SHOES TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT SHOE COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT
136	SHOES SFTY:5;BLACK/BROWN;34-232;LACE SHOES, SAFETY: SIZE: 5; TOE CONSTRUCTION TYPE: STL OR CARBON FIBER, WIDE FIT; COLOR: BLACK/BROWN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; MATERIAL: UPPER LEATHER FULL GRAIN; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; WIDE; SHOES TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; THE SHOES TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT SHOE COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT
137	SHOES SFTY:6;BLACK/BROWN;34-232;LACE SHOES, SAFETY: SIZE: 6; TOE CONSTRUCTION TYPE: STL OR CARBON FIBER, WIDE FIT; COLOR: BLACK/BROWN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; MATERIAL: UPPER LEATHER FULL GRAIN; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; WIDE; SHOES TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; THE SHOES TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT SHOE COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT
138	SHOES SFTY:7;BLACK/BROWN;34-232;LACE SHOES, SAFETY: SIZE: 7; TOE CONSTRUCTION TYPE: STL OR CARBON FIBER, WIDE FIT; COLOR: BLACK/BROWN; STYLE: 34-232; TREAD

**CONTROLLED DISCLOSURE**



	SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; MATERIAL: UPPER LEATHER FULL GRAIN; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; WIDE; SHOES TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; THE SHOES TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT SHOE COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT
139	SHOES SFTY:8;BLACK/BROWN;34-232;LACE SHOES, SAFETY: SIZE: 8; TOE CONSTRUCTION TYPE: STL OR CARBON FIBER, WIDE FIT; COLOR: BLACK/BROWN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; MATERIAL: UPPER LEATHER FULL GRAIN; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; WIDE; SHOES TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; THE SHOES TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT SHOE COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT
140	SHOES SFTY:9;BLACK/BROWN;34-232;LACE SHOES, SAFETY: SIZE: 9; TOE CONSTRUCTION TYPE: STL OR CARBON FIBER, WIDE FIT; COLOR: BLACK/BROWN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; MATERIAL: UPPER LEATHER FULL GRAIN; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; WIDE; SHOES TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; THE SHOES TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT SHOE COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT
141	SHOES SFTY:10;BLACK/BROWN;34-232;LACE SHOES, SAFETY: SIZE: 10; TOE CONSTRUCTION TYPE: STL OR CARBON FIBER, WIDE FIT; COLOR: BLACK/BROWN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; MATERIAL: UPPER LEATHER FULL GRAIN; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; WIDE; SHOES TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; THE SHOES TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT SHOE COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT
142	SHOES SFTY:11;BLACK/BROWN;34-232;LACE SHOES, SAFETY: SIZE: 11; TOE CONSTRUCTION TYPE: STL OR CARBON FIBER, WIDE FIT; COLOR: BLACK/BROWN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; MATERIAL: UPPER LEATHER FULL GRAIN; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; WIDE; SHOES TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; THE SHOES TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT SHOE COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT
143	VEST HIGH VIS:EMPLOYEE AT WORK;S;NYLON VEST, HIGH VISIBILITY: TYPE: EMPLOYEE AT WORK; SIZE: S; MATERIAL: NYLON; COLOR: ORANGE LIGHT B26 NCS-1673-Y48R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A4 ANEX A SANS 50471; REFLECTOR

**CONTROLLED DISCLOSURE**

	MARKING: REFER FIG A4; POCKET TYPE: LEFT TOP; EMPLOYEE AT WORK TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A4; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A4 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS
144	SOCKS:CALF LG;S TO M;COTTON;BLUE NAVY SOCKS: TYPE: CALF LG; SIZE: S TO M; MATERIAL: COTTON; COLOR: BLUE NAVY; SPECIFICATION: 240-44175132; NON-CONDUCTIVE; ANTI-STATIC; ANTI-BACTERIAL; MATERIAL SOCKS SHALL BE MADE FROM 72% COTTON, 26% POLY; 2% SILVER FIBRE 1
145	SOCKS:CALF LG;L; XL;COTTON;BLUE NAVY SOCKS: TYPE: CALF LG; SIZE: L; XL; MATERIAL: COTTON; COLOR: BLUE NAVY; SPECIFICATION: 240-44175132; NON-CONDUCTIVE; ANTI-STATIC; ANTI-BACTERIAL; MATERIAL SOCKS SHALL BE MADE FROM 72% COTTON, 26% POLY; 2% SILVER FIBRE 1
146	SOCKS:CALF LG;2XL; 3XL;COTTON;BLUE NAVY SOCKS: TYPE: CALF LG; SIZE: 2XL; 3XL; MATERIAL: COTTON; COLOR: BLUE NAVY; SPECIFICATION: 240-44175132; NON-CONDUCTIVE; ANTI-STATIC; ANTI-BACTERIAL; MATERIAL SOCKS SHALL BE MADE FROM 72% COTTON, 26% POLY; 2% SILVER FIBRE 1
147	VEST HIGH VIS:EVACUATION;S;NYLON VEST, HIGH VISIBILITY: TYPE: EVACUATION; SIZE: S; MATERIAL: NYLON; COLOR: WHITE CLOUD G80 NCS0704G28Y; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; EVACUATION CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS
148	VEST HIGH VIS:EVACUATION;M;NYLON VEST, HIGH VISIBILITY: TYPE: EVACUATION; SIZE: M; MATERIAL: NYLON; COLOR: WHITE CLOUD G80 NCS0704G28Y; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; EVACUATION CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS

**CONTROLLED DISCLOSURE**

149	VEST HIGH VIS:EVACUATION;L;NYLON VEST, HIGH VISIBILITY: TYPE: EVACUATION; SIZE: L; MATERIAL: NYLON; COLOR: WHITE CLOUD G80 NCS0704G28Y; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; EVACUATION CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS
150	VEST HIGH VIS:EVACUATION;XL;NYLON VEST, HIGH VISIBILITY: TYPE: EVACUATION; SIZE: XL; MATERIAL: NYLON; COLOR: WHITE CLOUD G80 NCS0704G28Y; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; EVACUATION CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS
151	VEST HIGH VIS:EVACUATION;2XL;NYLON VEST, HIGH VISIBILITY: TYPE: EVACUATION; SIZE: 2XL; MATERIAL: NYLON; COLOR: WHITE CLOUD G80 NCS0704G28Y; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; EVACUATION CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS
152	VEST HIGH VIS:EVACUATION;3XL;NYLON VEST, HIGH VISIBILITY: TYPE: EVACUATION; SIZE: 3XL; MATERIAL: NYLON; COLOR: WHITE CLOUD G80 NCS0704G28Y; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; EVACUATION CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3;

**CONTROLLED DISCLOSURE**

	RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS
153	VEST HIGH VIS:EVACUATION;4XL;NYLON VEST, HIGH VISIBILITY: TYPE: EVACUATION; SIZE: 4XL; MATERIAL: NYLON; COLOR: WHITE CLOUD G80 NCS0704G28Y; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; EVACUATION CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS
154	VEST HIGH VIS:EVACUATION;5XL;NYLON VEST, HIGH VISIBILITY: TYPE: EVACUATION; SIZE: 5XL; MATERIAL: NYLON; COLOR: WHITE CLOUD G80 NCS0704G28Y; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; EVACUATION CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS
155	HELMET SFTY:HEIGHT THREE POINT;WHITE HELMET, SAFETY: TYPE: HEIGHT THREE POINT; SIZE: 530-630 MM; MATERIAL: PLASTIC MOLDED; COLOR: WHITE; SPECIFICATION: SANS 1397:2003; SPECIAL FEATURES: SHORT PEAK; ALL HARD HATS MUST BE IN ACCORDANCE WITH SANS 1397:2003 AND ESKOM SPECIFICATION; SUPPLIED WITH A BLACK ADJUSTABLE THREE POINT CHIN STRAP; MINIMUM HARD HAT ELECTRICAL INSULATION: 440 VAC; WITH A SHORTER PEAK AND A LIMITED SIDE BRIM; ITEM TO BE MARKED WITH SABS MARK OF APPROVAL; APPROVED ESKOM LOGO AND A ZERO HARM SLOGAN MUST BE POSITIONED ACCORDING TO THE ESKOM SPECIFICATION AND BE INLINE WITH THE CORPORATE IDENTITY PROCEDURE; WHITE REFLECTIVE AND BLUE LETTERS EUROP ASSIST EMERGENCY NO 086 123 7566 MUST BE DISPLAYED ON THE BACK OF THE HELMETS
156	VEST HIGH VIS:TRANSPORT;M;NYLON VEST, HIGH VISIBILITY: TYPE: TRANSPORT; SIZE: M; MATERIAL: NYLON; COLOR: ICE BLUE F76 NCS-0809-B66G; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; TRANSPORT CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR

**CONTROLLED DISCLOSURE**



	HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS
157	VEST HIGH VIS:TRANSPORT;3XL;NYLON VEST, HIGH VISIBILITY: TYPE: TRANSPORT; SIZE: 3XL; MATERIAL: NYLON; COLOR: ICE BLUE F76 NCS-0809-B66G; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; TRANSPORT CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS
158	VEST HIGH VIS:TRANSPORT;L;NYLON VEST, HIGH VISIBILITY: TYPE: TRANSPORT; SIZE: L; MATERIAL: NYLON; COLOR: ICE BLUE F76 NCS-0809-B66G; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; TRANSPORT CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS
159	VEST HIGH VIS:TRANSPORT;XL;NYLON VEST, HIGH VISIBILITY: TYPE: TRANSPORT; SIZE: XL; MATERIAL: NYLON; COLOR: ICE BLUE F76 NCS-0809-B66G; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; TRANSPORT CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS

**CONTROLLED DISCLOSURE**



160	VEST HIGH VIS:TRANSPORT;2XL;NYLON VEST, HIGH VISIBILITY: TYPE: TRANSPORT; SIZE: 2XL; MATERIAL: NYLON; COLOR: ICE BLUE F76 NCS-0809-B66G; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; TRANSPORT CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS
161	VEST HIGH VIS:TRANSPORT;S;NYLON VEST, HIGH VISIBILITY: TYPE: TRANSPORT; SIZE: S; MATERIAL: NYLON; COLOR: ICE BLUE F76 NCS-0809-B66G; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; TRANSPORT CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS
162	VEST HIGH VIS:MANAGEMENT;S;NYLON VEST, HIGH VISIBILITY: TYPE: MANAGEMENT; SIZE: S; MATERIAL: NYLON; COLOR: GOLDEN YELLOW B49 NCS-1178-Y14R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; MANAGEMENT; AUDITORS; OBSERVERS; SECURITY TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS
163	VEST HIGH VIS:MANAGEMENT;M;NYLON VEST, HIGH VISIBILITY: TYPE: MANAGEMENT; SIZE: M; MATERIAL: NYLON; COLOR: GOLDEN YELLOW B49 NCS-1178-Y14R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; MANAGEMENT; AUDITORS; OBSERVERS; SECURITY TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS

**CONTROLLED DISCLOSURE**

	50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS
164	VEST HIGH VIS:MANAGEMENT;L;NYLON VEST, HIGH VISIBILITY: TYPE: MANAGEMENT; SIZE: L; MATERIAL: NYLON; COLOR: GOLDEN YELLOW B49 NCS-1178-Y14R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; MANAGEMENT; AUDITORS; OBSERVERS; SECURITY TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS
165	VEST HIGH VIS:MANAGEMENT;XL;NYLON VEST, HIGH VISIBILITY: TYPE: MANAGEMENT; SIZE: XL; MATERIAL: NYLON; COLOR: GOLDEN YELLOW B49 NCS-1178-Y14R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; MANAGEMENT; AUDITORS; OBSERVERS; SECURITY TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS
166	VEST HIGH VIS:MANAGEMENT;2XL;NYLON VEST, HIGH VISIBILITY: TYPE: MANAGEMENT; SIZE: 2XL; MATERIAL: NYLON; COLOR: GOLDEN YELLOW B49 NCS-1178-Y14R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; MANAGEMENT; AUDITORS; OBSERVERS; SECURITY TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS
167	VEST HIGH VIS:MANAGEMENT;3XL;NYLON VEST, HIGH VISIBILITY: TYPE: MANAGEMENT; SIZE: 3XL; MATERIAL: NYLON; COLOR: GOLDEN YELLOW B49 NCS-1178-Y14R; GARMENT

**CONTROLLED DISCLOSURE**

	CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; MANAGEMENT; AUDITORS; OBSERVERS; SECURITY TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS
168	VEST HIGH VIS:EMPLOYEE AT WORK;M;NYLON VEST, HIGH VISIBILITY: TYPE: EMPLOYEE AT WORK; SIZE: M; MATERIAL: NYLON; COLOR: ORANGE LIGHT B26 NCS-1673-Y48R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A4 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A4; POCKET TYPE: LEFT TOP; EMPLOYEE AT WORK TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A4; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A4 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS
169	VEST HIGH VIS:EMPLOYEE AT WORK;L;NYLON VEST, HIGH VISIBILITY: TYPE: EMPLOYEE AT WORK; SIZE: L; MATERIAL: NYLON; COLOR: ORANGE LIGHT B26 NCS-1673-Y48R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A4 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A4; POCKET TYPE: LEFT TOP; EMPLOYEE AT WORK TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A4; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A4 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS
170	VEST HIGH VIS:EMPLOYEE AT WORK;XL;NYLON VEST, HIGH VISIBILITY: TYPE: EMPLOYEE AT WORK; SIZE: XL; MATERIAL: NYLON; COLOR: ORANGE LIGHT B26 NCS-1673-Y48R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A4 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A4; POCKET TYPE: LEFT TOP; EMPLOYEE AT WORK TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A4; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR

**CONTROLLED DISCLOSURE**

	BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A4 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS
171	VEST HIGH VIS:EMPLOYEE AT WORK;2XL;NYLON VEST, HIGH VISIBILITY: TYPE: EMPLOYEE AT WORK; SIZE: 2XL; MATERIAL: NYLON; COLOR: ORANGE LIGHT B26 NCS-1673-Y48R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A4 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A4; POCKET TYPE: LEFT TOP; EMPLOYEE AT WORK TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A4; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A4 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS
172	VEST HIGH VIS:EMPLOYEE AT WORK;3XL;NYLON VEST, HIGH VISIBILITY: TYPE: EMPLOYEE AT WORK; SIZE: 3XL; MATERIAL: NYLON; COLOR: ORANGE LIGHT B26 NCS-1673-Y48R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A4 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A4; POCKET TYPE: LEFT TOP; EMPLOYEE AT WORK TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A4; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A4 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS
173	VEST HIGH VIS:EMPLOYEE AT WORK;4XL;NYLON VEST, HIGH VISIBILITY: TYPE: EMPLOYEE AT WORK; SIZE: 4XL; MATERIAL: NYLON; COLOR: ORANGE LIGHT B26 NCS-1673-Y48R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A4 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A4; POCKET TYPE: LEFT TOP; EMPLOYEE AT WORK TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A4; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A4 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS
174	VEST HIGH VIS:EMPLOYEE AT WORK;5XL;NYLON VEST, HIGH VISIBILITY: TYPE: EMPLOYEE AT WORK; SIZE: 5XL; MATERIAL: NYLON; COLOR: ORANGE LIGHT B26 NCS-1673-Y48R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A4 ANEX A SANS 50471;

**CONTROLLED DISCLOSURE**



	REFLECTOR MARKING: REFER FIG A4; POCKET TYPE: LEFT TOP; EMPLOYEE AT WORK TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A4; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A4 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS
175	VEST HIGH VIS:FIRE PROTECTION;S;NYLON VEST, HIGH VISIBILITY: TYPE: FIRE PROTECTION; SIZE: S; MATERIAL: NYLON; COLOR: SIGNAL RED A11 NCS-1678-Y86R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; FIRE PROTECTION CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS
176	VEST HIGH VIS:FIRE PROTECTION;M;NYLON VEST, HIGH VISIBILITY: TYPE: FIRE PROTECTION; SIZE: M; MATERIAL: NYLON; COLOR: SIGNAL RED A11 NCS-1678-Y86R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; FIRE PROTECTION CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS
177	VEST HIGH VIS:FIRE PROTECTION;L;NYLON VEST, HIGH VISIBILITY: TYPE: FIRE PROTECTION; SIZE: L; MATERIAL: NYLON; COLOR: SIGNAL RED A11 NCS-1678-Y86R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; FIRE PROTECTION CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL

**CONTROLLED DISCLOSURE**



	SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS
178	VEST HIGH VIS:FIRE PROTECTION;XL;NYLON VEST, HIGH VISIBILITY: TYPE: FIRE PROTECTION; SIZE: XL; MATERIAL: NYLON; COLOR: SIGNAL RED A11 NCS-1678-Y86R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; FIRE PROTECTION CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS
179	VEST HIGH VIS:FIRE PROTECTION;2XL;NYLON VEST, HIGH VISIBILITY: TYPE: FIRE PROTECTION; SIZE: 2XL; MATERIAL: NYLON; COLOR: SIGNAL RED A11 NCS-1678-Y86R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; FIRE PROTECTION CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS
180	VEST HIGH VIS:FIRE PROTECTION;3XL;NYLON VEST, HIGH VISIBILITY: TYPE: FIRE PROTECTION; SIZE: 3XL; MATERIAL: NYLON; COLOR: SIGNAL RED A11 NCS-1678-Y86R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; FIRE PROTECTION CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS
181	VEST HIGH VIS:FIRE PROTECTION;4XL;NYLON VEST, HIGH VISIBILITY: TYPE: FIRE PROTECTION; SIZE: 4XL; MATERIAL: NYLON; COLOR: SIGNAL RED A11 NCS-1678-Y86R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; FIRE PROTECTION CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC

**CONTROLLED DISCLOSURE**

	WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS
182	VEST HIGH VIS:FIRE PROTECTION;5XL;NYLON VEST, HIGH VISIBILITY: TYPE: FIRE PROTECTION; SIZE: 5XL; MATERIAL: NYLON; COLOR: SIGNAL RED A11 NCS-1678-Y86R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; FIRE PROTECTION CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS
183	VEST HIGH VIS:FIRE PROTECTION;6XL;NYLON VEST, HIGH VISIBILITY: TYPE: FIRE PROTECTION; SIZE: 6XL; MATERIAL: NYLON; COLOR: SIGNAL RED A11 NCS-1678-Y86R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; FIRE PROTECTION CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS
184	VEST HIGH VIS:FIRST AID;S;NYLON VEST, HIGH VISIBILITY: TYPE: FIRST AID; SIZE: S; MATERIAL: NYLON; COLOR: EMERALD GREEN E14 NCS-3745-B99G; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; FIRST AID CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR

**CONTROLLED DISCLOSURE**

	REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS
185	VEST HIGH VIS:FIRST AID;3XL;NYLON VEST, HIGH VISIBILITY: TYPE: FIRST AID; SIZE: 3XL; MATERIAL: NYLON; COLOR: EMERALD GREEN E14 NCS-3745-B99G; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; FIRST AID CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS
186	RAINWEAR:2 PIECE SUIT;4XL;BLUE NAVY RAINWEAR: TYPE: 2 PIECE SUIT; SIZE: 4XL; MATERIAL: POLYESTER 100 PCT PLAIN WEAVE, 180 GM/2 MIN; COLOR: BLUE NAVY; MATERIAL: MINIMUM 180 GRAMS PER M/3 FACE SIDE 100% POLYESTER; PLAIN WEAVE WITH 170 THREADS PER M/3 INCH WITH WATER RESISTANT COATING; UNDER SIDE LAMINATED WITH PVC COATING; SEAMS STRENGTH 50KPA; CONVERTS TO 50KNM/2; LINING 80% POLYESTER 20% COTTON; SIZE TO SANS 434 SIZE CHART ANNEX E FOR RAIN WEAR; JACKET SHALL HAVE A NYLON SPIRAL ZIP WITH CLOSED FLY FRONT SECURED BY NON-CONDUCTIVE PRESS-STUDS; COMPLY WITH SANS 1822 TYPE 5; HOOD ATTACHED TO THE JACKET; JACKET TO COVER THE BUTTOCKS; FALSE ELASTIC SLEEVE AT THE END MADE OF SOFTER MATERIAL; PANTS SHALL HAVE SIDE SLITS AND ELASTIC WAIST; REFLECTIVE STRIPS TO BE FITTED ON BOTH SLEEVES ON THE UPPER ARM, AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SIDE OF THE SLEEVE AND THE ESKOM LOGO SHALL BE SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON THE FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; UNIQUE IDENTIFIER 240-44175132
187	SUIT CHEM PRTCTV:S;YELLOW;ACID PROOF SUIT, CHEMICAL PROTECTIVE: GARMENT SIZE: S; COLOR: YELLOW; MATERIAL: PVC COATED POLYESTER 400GRAM P/M3; TYPE: ACID PROOF; TEAR STRENGTH WELF 40N WARP 30N; BURST STRENGTH WELF 655N/50MM WARP 1232N/50MM; COATING ADHESIVE 15N/50MM; BASE FABRIC 100% POLYESTER WEIGHT 80 GRAMS PER M/3; YARN/CM 16 x 14.5; HOOK AND LOOP TAPE 20MM-WHITE; DRAW CORD 3MM POLYESTER; SEAMS HIGH FREQUENCY WELDED; NYLON SPIRAL ZIP CLOSED FLY FRONT WITH ACID RESISTANT PRESS-STUDS; HOOD ATTACHED TO JACKET; JACKET TO COVER BUTTOCKS; FALSE ELASTIC SLEEVE OF SOFT MATERIAL TO PREVENT CHEMICALS ENTERING SLEEVE; PANTS SHALL HAVE ELASTICISED WAIST WITH NO SIDE SLITS AND NO POCKETS; SUIT TO BE YELLOW HIGH VISIBILITY MATERIAL; REFLECTIVE STRIPS ON BOTH SLEEVES UPPER ARM; AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; COMPLY WITH SANS 1822 TYPE 5 CHEMICAL TESTED TO ASTM P903-96; UNIQUE IDENTIFIER 240-44175132
188	SUIT CHEM PRTCTV:M;YELLOW;ACID PROOF SUIT, CHEMICAL PROTECTIVE: GARMENT SIZE: M; COLOR: YELLOW; MATERIAL: PVC COATED POLYESTER 400GRAM P/M3; TYPE: ACID PROOF; TEAR STRENGTH WELF 40N WARP 30N; BURST STRENGTH WELF 655N/50MM WARP 1232N/50MM; COATING ADHESIVE 15N/50MM; BASE FABRIC 100% POLYESTER WEIGHT 80 GRAMS PER M/3; YARN/CM 16 x 14.5; HOOK AND LOOP TAPE 20MM-WHITE; DRAW CORD 3MM POLYESTER; SEAMS HIGH FREQUENCY WELDED; NYLON SPIRAL ZIP CLOSED FLY FRONT WITH ACID RESISTANT PRESS-STUDS; HOOD ATTACHED TO JACKET;

**CONTROLLED DISCLOSURE**

	JACKET TO COVER BUTTOCKS; FALSE ELASTIC SLEEVE OF SOFT MATERIAL TO PREVENT CHEMICALS ENTERING SLEEVE; PANTS SHALL HAVE ELASTICISED WAIST WITH NO SIDE SLITS AND NO POCKETS; SUIT TO BE YELLOW HIGH VISIBILITY MATERIAL; REFLECTIVE STRIPS ON BOTH SLEEVES UPPER ARM; AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; COMPLY WITH SANS 1822 TYPE 5 CHEMICAL TESTED TO ASTM P903-96; UNIQUE IDENTIFIER 240-44175132
189	SUIT CHEM PRTCTV:L;YELLOW;ACID PROOF SUIT, CHEMICAL PROTECTIVE: GARMENT SIZE: L; COLOR: YELLOW; MATERIAL: PVC COATED POLYESTER 400GRAM P/M3; TYPE: ACID PROOF; TEAR STRENGTH WELF 40N WARP 30N; BURST STRENGTH WELF 655N/50MM WARP 1232N/50MM; COATING ADHESIVE 15N/50MM; BASE FABRIC 100% POLYESTER WEIGHT 80 GRAMS PER M/3; YARN/CM 16 x 14.5; HOOK AND LOOP TAPE 20MM-WHITE; DRAW CORD 3MM POLYESTER; SEAMS HIGH FREQUENCY WELDED; NYLON SPIRAL ZIP CLOSED FLY FRONT WITH ACID RESISTANT PRESS-STUDS; HOOD ATTACHED TO JACKET; JACKET TO COVER BUTTOCKS; FALSE ELASTIC SLEEVE OF SOFT MATERIAL TO PREVENT CHEMICALS ENTERING SLEEVE; PANTS SHALL HAVE ELASTICISED WAIST WITH NO SIDE SLITS AND NO POCKETS; SUIT TO BE YELLOW HIGH VISIBILITY MATERIAL; REFLECTIVE STRIPS ON BOTH SLEEVES UPPER ARM; AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; COMPLY WITH SANS 1822 TYPE 5 CHEMICAL TESTED TO ASTM P903-96; UNIQUE IDENTIFIER 240-44175132
190	SUIT CHEM PRTCTV:XL;YELLOW;ACID PROOF SUIT, CHEMICAL PROTECTIVE: GARMENT SIZE: XL; COLOR: YELLOW; MATERIAL: PVC COATED POLYESTER 400GRAM P/M3; TYPE: ACID PROOF; TEAR STRENGTH WELF 40N WARP 30N; BURST STRENGTH WELF 655N/50MM WARP 1232N/50MM; COATING ADHESIVE 15N/50MM; BASE FABRIC 100% POLYESTER WEIGHT 80 GRAMS PER M/3; YARN/CM 16 x 14.5; HOOK AND LOOP TAPE 20MM-WHITE; DRAW CORD 3MM POLYESTER; SEAMS HIGH FREQUENCY WELDED; NYLON SPIRAL ZIP CLOSED FLY FRONT WITH ACID RESISTANT PRESS-STUDS; HOOD ATTACHED TO JACKET; JACKET TO COVER BUTTOCKS; FALSE ELASTIC SLEEVE OF SOFT MATERIAL TO PREVENT CHEMICALS ENTERING SLEEVE; PANTS SHALL HAVE ELASTICISED WAIST WITH NO SIDE SLITS AND NO POCKETS; SUIT TO BE YELLOW HIGH VISIBILITY MATERIAL; REFLECTIVE STRIPS ON BOTH SLEEVES UPPER ARM; AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; COMPLY WITH SANS 1822 TYPE 5 CHEMICAL TESTED TO ASTM P903-96; UNIQUE IDENTIFIER 240-44175132
191	SUIT CHEM PRTCTV:XXXL;YELLOW;ACID PROOF SUIT, CHEMICAL PROTECTIVE: GARMENT SIZE: XXXL; COLOR: YELLOW; MATERIAL: PVC COATED POLYESTER 400GRAM P/M3; TYPE: ACID PROOF; TEAR STRENGTH WELF 40N WARP 30N; BURST STRENGTH WELF 655N/50MM WARP 1232N/50MM; COATING ADHESIVE 15N/50MM; BASE FABRIC 100% POLYESTER WEIGHT 80 GRAMS PER M/3; YARN/CM 16 x 14.5; HOOK AND LOOP TAPE 20MM-WHITE; DRAW CORD 3MM POLYESTER; SEAMS HIGH FREQUENCY WELDED; NYLON SPIRAL ZIP CLOSED FLY FRONT WITH ACID RESISTANT PRESS-STUDS; HOOD ATTACHED TO JACKET; JACKET TO COVER BUTTOCKS; FALSE ELASTIC SLEEVE OF SOFT MATERIAL TO PREVENT CHEMICALS ENTERING SLEEVE; PANTS SHALL HAVE ELASTICISED WAIST WITH NO SIDE SLITS AND NO POCKETS; SUIT TO BE YELLOW HIGH VISIBILITY MATERIAL; REFLECTIVE STRIPS ON BOTH SLEEVES UPPER ARM; AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; COMPLY WITH SANS 1822 TYPE 5 CHEMICAL TESTED TO ASTM P903-96; UNIQUE IDENTIFIER 240-44175132

**CONTROLLED DISCLOSURE**



192	SUIT CHEM PRTCTV:2XL;YELLOW;ACID PROOF SUIT, CHEMICAL PROTECTIVE: GARMENT SIZE: 2XL; COLOR: YELLOW; MATERIAL: PVC COATED POLYESTER 400GRAM P/M3; TYPE: ACID PROOF; TEAR STRENGTH WELF 40N WARP 30N; BURST STRENGTH WELF 655N/50MM WARP 1232N/50MM; COATING ADHESIVE 15N/50MM; BASE FABRIC 100% POLYESTER WEIGHT 80 GRAMS PER M/3; YARN/CM 16 x 14.5; HOOK AND LOOP TAPE 20MM-WHITE; DRAW CORD 3MM POLYESTER; SEAMS HIGH FREQUENCY WELDED; NYLON SPIRAL ZIP CLOSED FLY FRONT WITH ACID RESISTANT PRESS-STUDS; HOOD ATTACHED TO JACKET; JACKET TO COVER BUTTOCKS; FALSE ELASTIC SLEEVE OF SOFT MATERIAL TO PREVENT CHEMICALS ENTERING SLEEVE; PANTS SHALL HAVE ELASTICISED WAIST WITH NO SIDE SLITS AND NO POCKETS; SUIT TO BE YELLOW HIGH VISIBILITY MATERIAL; REFLECTIVE STRIPS ON BOTH SLEEVES UPPER ARM; AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; COMPLY WITH SANS 1822 TYPE 5 CHEMICAL TESTED TO ASTM P903-96; UNIQUE IDENTIFIER 240-44175132
193	SUIT CHEM PRTCTV:4XL;YELLOW;ACID PROOF SUIT, CHEMICAL PROTECTIVE: GARMENT SIZE: 4XL; COLOR: YELLOW; MATERIAL: PVC COATED POLYESTER 400GRAM P/M3; TYPE: ACID PROOF; TEAR STRENGTH WELF 40N WARP 30N; BURST STRENGTH WELF 655N/50MM WARP 1232N/50MM; COATING ADHESIVE 15N/50MM; BASE FABRIC 100% POLYESTER WEIGHT 80 GRAMS PER M/3; YARN/CM 16 x 14.5; HOOK AND LOOP TAPE 20MM-WHITE; DRAW CORD 3MM POLYESTER; SEAMS HIGH FREQUENCY WELDED; NYLON SPIRAL ZIP CLOSED FLY FRONT WITH ACID RESISTANT PRESS-STUDS; HOOD ATTACHED TO JACKET; JACKET TO COVER BUTTOCKS; FALSE ELASTIC SLEEVE OF SOFT MATERIAL TO PREVENT CHEMICALS ENTERING SLEEVE; PANTS SHALL HAVE ELASTICISED WAIST WITH NO SIDE SLITS AND NO POCKETS; SUIT TO BE YELLOW HIGH VISIBILITY MATERIAL; REFLECTIVE STRIPS ON BOTH SLEEVES UPPER ARM; AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; COMPLY WITH SANS 1822 TYPE 5 CHEMICAL TESTED TO ASTM P903-96; UNIQUE IDENTIFIER 240-44175132
194	VISOR:SUN BRIM FOR SAFETY HAT VISOR: TYPE: SUN BRIM FOR SAFETY HAT; DIMENSIONS: ID 740 X OD 430 MM; MATERIAL: D59 WOVEN COTTON; COLOR: BLUE NAVY; SHAPE OF BRIM TO BE OVAL AND SHALL COMPLY TO THE FOLLOWING FRONT BACK AND NECK PROTECTOR ATTACH TO BOTTOM OF BRIM MATERIAL TYPE D59 FLAME RETARDANT PRE-SHRUNK 100 % WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; SUN BRIM SHALL HAVE A REINFORCED STIFFENED BROAD BRIM OF AT LEAST 90 MM BRIM MALGREY CHIP BOARD MATERIAL 600 TO 800GSM; INSIDE DIAMETER 740MM (FRONT TO BACK 240MM AND SIDE TO SIDE 200MM) OUTSIDE FRONT TO BACK 430MM AND FROM SIDE TO SIDE 380MM; STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS WITH SANS 1362; INSERT FOR HARD HAT FRONT PEAK FLAP CENTRE 130MM AND SIDE FITTED TO OTHER BRIM INSERT FOR HARD HAT REAR SECTION CENTRE 130MM AND SIDES FITTED TO OTHER BRIM; NECK PROTECTOR AT BACK CENTRE 230MM LONG AND SIDES FITTED HALF WAY TO OUTER SUN BRIM PROTECTOR; VELCRO 40 X 25MM ATTACH ON LEFT SIDE OF BRIM AND REAR INSERT OF FLAP FOR STABILITY; UNIQUE IDENTIFIER 240-44175132
195	SHIRT WMAN:LONG;97 CM;GRAY;COTTON SHIRT, WOMAN: SLEEVE TYPE: LONG; SIZE: 97 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE LONG SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF 65 MM WIDE; THE

**CONTROLLED DISCLOSURE**



	SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132
196	SHIRT WMAN:SHORT;97 CM;GRAY;COTTON SHIRT, WOMAN: SLEEVE TYPE: SHORT; SIZE: 97 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE SHORT SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132
197	GUMBOOTS SFTY:STL;5;KNEE HEIGHT;BLACK GUMBOOTS, SAFETY: TOE CAP: STL; SIZE: 5; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT; NON SLIP SOLE; WATERPROOF CONSTRUCTION; TO SABS 20345
198	COAT DUST:GP;127 CM;COTTON COAT, DUST: TYPE: GENERAL PURPOSE; SIZE: 127 CM; MATERIAL: COTTON; COLOR: BLUE NAVY PANTONE 19-3920; SPECIFICATION: 240-44175132; MATERIAL: PRE-SHRUNK 100 % WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; LENGTH 3/4; POCKET: FRONT BUTTONS; TWO FRONT POCKETS; SLIT AT BACK; BUTTONS ACCEPTABLE FOUR-HOLE; DYED PLASTICS BUTTONS COMPLY WITH SANS 1457 COATS SHALL FASTEN WITH BUTTON AND BUTTONHOLE AND SHALL BE EQUIDISTANTLY SPACED; BUTTONS SECURED TO POSITIONS CORRESPONDING TO BUTTONHOLES; THE PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; THE BACK SHALL HAVE A SEAM DOWN THE CENTRE WITH A VENT IN THE LOWER PART OF THE SEAM; THE VENT SHALL HAVE AN OVERLAP OF 40 MM AND SHALL BE SECURELY TACKED AND BAR-TACKED AT THE TOP; A HANGER LOOP OF OUTER DOUBLE FOLDED MATERIAL OF FINISHED LENGTH AT LEAST 70 MM AND OF FINISHED WIDTH AT LEAST 10 MM; SHALL BE SECURELY SEWN IN WITH THE COLLAR AT THE BACK NECK ON THE INSIDE; THE BOTTOM OF THE COATS AND THE LOWER EDGE OF PLAIN SLEEVE CUFFS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 15 MM; POCKET MOUTHS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 20 MM; EACH GARMENT SHALL HAVE A LABEL SECURELY ATTACHED AT THE CENTRE BACK NECK BELOW THE COLLAR SEAM ON THE INSIDE OF THE GARMENT; THE LABEL SHALL PROVIDE THE FOLLOWING INFORMATION PRINTED IN LEGIBLE AND INDELIBLE BLOCK LETTERS OF HEIGHT AT LEAST 3 MM; MANUFACTURER'S NAME OR TRADEMARK; CHEST SIZE SANS 434:2011 EDITION 5 22; YEAR OF MANUFACTURE; VAT REGISTRATION NUMBER; COUNTRY OF ORIGIN; ITEM TO BEAR SABS MARK OF APPROVAL REFERENCE SANS 434:2011 FIGURE 3 COATS
199	COAT DUST:GP;92 CM;COTTON COAT, DUST: TYPE: GENERAL PURPOSE; SIZE: 92 CM; MATERIAL: COTTON; COLOR: BLUE NAVY PANTONE 19-3920; SPECIFICATION: 240-44175132; MATERIAL: PRE-SHRUNK 100 % WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; LENGTH 3/4; POCKET: FRONT BUTTONS; TWO FRONT POCKETS; SLIT AT BACK; BUTTONS ACCEPTABLE FOUR-HOLE;

**CONTROLLED DISCLOSURE**

	DYED PLASTICS BUTTONS COMPLY WITH SANS 1457 COATS SHALL FASTEN WITH BUTTON AND BUTTONHOLE AND SHALL BE EQUIDISTANTLY SPACED; BUTTONS SECURED TO POSITIONS CORRESPONDING TO BUTTONHOLES; THE PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; THE BACK SHALL HAVE A SEAM DOWN THE CENTRE WITH A VENT IN THE LOWER PART OF THE SEAM; THE VENT SHALL HAVE AN OVERLAP OF 40 MM AND SHALL BE SECURELY TACKED AND BAR-TACKED AT THE TOP; A HANGER LOOP OF OUTER DOUBLE FOLDED MATERIAL OF FINISHED LENGTH AT LEAST 70 MM AND OF FINISHED WIDTH AT LEAST 10 MM; SHALL BE SECURELY SEWN IN WITH THE COLLAR AT THE BACK NECK ON THE INSIDE; THE BOTTOM OF THE COATS AND THE LOWER EDGE OF PLAIN SLEEVE CUFFS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 15 MM; POCKET MOUTHS SHALL HAVE HEMS OF FINISHED WIDTH AT LEAST 20 MM; EACH GARMENT SHALL HAVE A LABEL SECURELY ATTACHED AT THE CENTRE BACK NECK BELOW THE COLLAR SEAM ON THE INSIDE OF THE GARMENT; THE LABEL SHALL PROVIDE THE FOLLOWING INFORMATION PRINTED IN LEGIBLE AND INDELIBLE BLOCK LETTERS OF HEIGHT AT LEAST 3 MM; MANUFACTURER'S NAME OR TRADEMARK; CHEST SIZE SANS 434:2011 EDITION 5 22; YEAR OF MANUFACTURE; VAT REGISTRATION NUMBER; COUNTRY OF ORIGIN; ITEM TO BEAR SABS MARK OF APPROVAL REFERENCE SANS 434:2011 FIGURE 3 COATS
200	JACKET UTIL:ACID/ALKALI;87 CM JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 87 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM
201	JACKET UTIL:ACID/ALKALI;97 CM JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 97 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY

**CONTROLLED DISCLOSURE**

	FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM
202	JACKET UTIL:ACID/ALKALI;107 CM JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 107 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM
203	JACKET UTIL:ACID/ALKALI;117 CM JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 117 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE

**CONTROLLED DISCLOSURE**

	FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM
204	JACKET UTIL:ACID/ALKALI;122 CM JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 122 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM
205	JACKET UTIL:ACID/ALKALI;132 CM JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 132 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT

**CONTROLLED DISCLOSURE**



	EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM
206	JACKET UTIL:OPERATING;77 CM JACKET, UTILITY: TYPE: OPERATING; SIZE: 77 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
207	JACKET UTIL:OPERATING;82 CM JACKET, UTILITY: TYPE: OPERATING; SIZE: 82 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE

**CONTROLLED DISCLOSURE**



	FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM
208	JACKET UTIL:OPERATING;102 CM JACKET, UTILITY: TYPE: OPERATING; SIZE: 102 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM
209	JACKET UTIL:OPERATING;112 CM JACKET, UTILITY: TYPE: OPERATING; SIZE: 112 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT

**CONTROLLED DISCLOSURE**

	EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM
210	JACKET UTIL:OPERATING;127 CM JACKET, UTILITY: TYPE: OPERATING; SIZE: 127 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM
211	JACKET UTIL:OPERATING;92 CM JACKET, UTILITY: TYPE: OPERATING; SIZE: 92 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED

**CONTROLLED DISCLOSURE**

	AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM
212	JACKET UTIL:ACID/ALKALI;77 CM JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 77 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM
213	JACKET UTIL:ACID/ALKALI;82 CM JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 82 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO

**CONTROLLED DISCLOSURE**

	ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM
214	JACKET UTIL:ACID/ALKALI;92 CM JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 92 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM
215	JACKET UTIL:ACID/ALKALI;102 CM JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 102 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE

**CONTROLLED DISCLOSURE**



	BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM
216	JACKET UTIL:ACID/ALKALI;127 CM JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 127 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM
217	JACKET UTIL:ACID/ALKALI;142 CM JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 142 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A

**CONTROLLED DISCLOSURE**

	PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM
218	JACKET UTIL:ACID/ALKALI;112 CM JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 112 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM
219	BOOTS SFTY:11;STRD; STL OR CARBON FIBER BOOTS, SAFETY: SIZE: 11; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT
220	BOOTS SFTY:12;STRD; STL OR CARBON FIBER BOOTS, SAFETY: SIZE: 12; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS

**CONTROLLED DISCLOSURE**

	ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT
221	BOOTS SFTY:3;STRD; STL OR CARBON FIBER BOOTS, SAFETY: SIZE: 3; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT
222	BOOTS SFTY:13;STRD; STL OR CARBON FIBER BOOTS, SAFETY: SIZE: 13; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT
223	SHOES SFTY:3;BLACK/BROWN;34-232;LACE SHOES, SAFETY: SIZE: 3; TOE CONSTRUCTION TYPE: STL OR CARBON FIBER, WIDE FIT; COLOR: BLACK/BROWN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; MATERIAL: UPPER LEATHER FULL GRAIN; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; WIDE; SHOES TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; THE SHOES TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT SHOE COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT
224	COVERALL:ARTISAN BOILER SUIT;102 CM COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 102 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE

**CONTROLLED DISCLOSURE**

	<p>ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>
225	<p>COVERALL:ARTISAN BOILER SUIT;117 CM COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 117 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST</p>

**CONTROLLED DISCLOSURE**



	POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM
226	COVERALL:ARTISAN BOILER SUIT;107 CM COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 107 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM

**CONTROLLED DISCLOSURE**

227	<p>COVERALL:ARTISAN BOILER SUIT;132 CM COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 132 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>
228	<p>COVERALL:ARTISAN BOILER SUIT;127 CM COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 127 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE</p>

**CONTROLLED DISCLOSURE**

	FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM
229	COVERALL:ARTISAN BOILER SUIT;112 CM COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 112 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY

**CONTROLLED DISCLOSURE**

	FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM
230	COVERALL:ARTISAN BOILER SUIT;122 CM COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 122 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH

**CONTROLLED DISCLOSURE**



	TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM
231	COVERALL:ACID/ALKALI;77 CM COVERALL: TYPE: ACID/ALKALI; SIZE: 77 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM
232	COVERALL:ACID/ALKALI;82 CM COVERALL: TYPE: ACID/ALKALI; SIZE: 82 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED

**CONTROLLED DISCLOSURE**

	<p>TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>
233	<p>COVERALL:ACID/ALKALI;87 CM COVERALL: TYPE: ACID/ALKALI; SIZE: 87 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE</p>

**CONTROLLED DISCLOSURE**

	<p>SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>
234	<p>COVERALL:ACID/ALKALI;92 CM COVERALL: TYPE: ACID/ALKALI; SIZE: 92 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE</p>

**CONTROLLED DISCLOSURE**

	POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM
235	COVERALL:ACID/ALKALI;97 CM COVERALL: TYPE: ACID/ALKALI; SIZE: 97 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM
236	COVERALL:ACID/ALKALI;102 CM COVERALL: TYPE: ACID/ALKALI; SIZE: 102 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND

**CONTROLLED DISCLOSURE**



	<p>BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>
237	<p>COVERALL:ACID/ALKALI;107 CM COVERALL: TYPE: ACID/ALKALI; SIZE: 107 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF</p>

**CONTROLLED DISCLOSURE**

	<p>THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>
238	<p>COVERALL:ACID/ALKALI;112 CM COVERALL: TYPE: ACID/ALKALI; SIZE: 112 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL</p>

**CONTROLLED DISCLOSURE**

	BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM
239	COVERALL:ACID/ALKALI;117 CM COVERALL: TYPE: ACID/ALKALI; SIZE: 117 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM
240	COVERALL:ACID/ALKALI;122 CM COVERALL: TYPE: ACID/ALKALI; SIZE: 122 CM; MATERIAL: COTTON 100 PCT D59 WOVEN PRESHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT

**CONTROLLED DISCLOSURE**

	<p>LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED</p>
241	<p>COVERALL:ACID/ALKALI;127 CM COVERALL: TYPE: ACID/ALKALI; SIZE: 127 CM; MATERIAL: COTTON 100 PCT D59 WOVEN PRESHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED</p>
242	<p>COVERALL:ACID/ALKALI;132 CM COVERALL: TYPE: ACID/ALKALI; SIZE: 132 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND</p>

**CONTROLLED DISCLOSURE**



	<p>BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>
243	<p>JACKET OVRL:CLEAN CONDITION;112 CM JACKET, OVERALL: TYPE: CLEAN CONDITION; SIZE: 112 CM; MATERIAL: COTTON 100% D59 PRE-SHRUNK; COLOR: WHITE; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE A CLOSED ONE PANEL ONLY MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE JACKET SHALL HAVE NO POCKETS; NO BUTTONS METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE LEFT-HAND TOP CHEST IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE RIGHT SIDE SLEEVE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TOPS TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH SLEEVES CIRCUMFERENCE ON THE INNER UPPER ARM; SANS 1822 ZIP; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; UNIQUE IDENTIFIER 240-44175132; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS</p>
244	<p>JACKET OVRL:CLEAN CONDITION;117 CM JACKET, OVERALL: TYPE: CLEAN CONDITION; SIZE: 117 CM; MATERIAL: COTTON 100% D59 PRE-SHRUNK; COLOR: WHITE; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE A CLOSED ONE PANEL ONLY MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE JACKET SHALL HAVE NO POCKETS; NO BUTTONS METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE LEFT-HAND TOP CHEST IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE RIGHT SIDE SLEEVE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE</p>

**CONTROLLED DISCLOSURE**

	CLOTHING TOPS TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH SLEEVES CIRCUMFERENCE ON THE INNER UPPER ARM; SANS 1822 ZIP; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; UNIQUE IDENTIFIER 240-44175132; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS
245	JACKET OVRL:CLEAN CONDITION;122 CM JACKET, OVERALL: TYPE: CLEAN CONDITION; SIZE: 122 CM; MATERIAL: COTTON 100% D59 PRE-SHRUNK; COLOR: WHITE; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE A CLOSED ONE PANEL ONLY MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE JACKET SHALL HAVE NO POCKETS; NO BUTTONS METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE LEFT-HAND TOP CHEST IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE RIGHT SIDE SLEEVE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TOPS TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH SLEEVES CIRCUMFERENCE ON THE INNER UPPER ARM; SANS 1822 ZIP; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; UNIQUE IDENTIFIER 240-44175132; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS
246	JACKET OVRL:CLEAN CONDITION;127 CM JACKET, OVERALL: TYPE: CLEAN CONDITION; SIZE: 127 CM; MATERIAL: COTTON 100% D59 PRE-SHRUNK; COLOR: WHITE; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE A CLOSED ONE PANEL ONLY MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE JACKET SHALL HAVE NO POCKETS; NO BUTTONS METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE LEFT-HAND TOP CHEST IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE RIGHT SIDE SLEEVE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TOPS TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH SLEEVES CIRCUMFERENCE ON THE INNER UPPER ARM; SANS 1822 ZIP; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; UNIQUE IDENTIFIER 240-44175132; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS
247	JACKET OVRL:CLEAN CONDITION;132 CM JACKET, OVERALL: TYPE: CLEAN CONDITION; SIZE: 132 CM; MATERIAL: COTTON 100% D59 PRE-SHRUNK; COLOR: WHITE; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE A CLOSED ONE PANEL ONLY MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE JACKET SHALL HAVE NO POCKETS; NO BUTTONS METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE LEFT-HAND TOP CHEST IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE RIGHT SIDE SLEEVE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TOPS TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH SLEEVES CIRCUMFERENCE ON THE INNER UPPER ARM; SANS 1822 ZIP; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; UNIQUE IDENTIFIER 240-44175132; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS
248	JACKET OVRL:CLEAN CONDITION;137 CM JACKET, OVERALL: TYPE: CLEAN CONDITION; SIZE: 137 CM; MATERIAL: COTTON 100% D59 PRE-SHRUNK; COLOR: WHITE; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE A CLOSED ONE PANEL ONLY MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE JACKET SHALL HAVE NO POCKETS; NO BUTTONS METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE LEFT-HAND TOP CHEST IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE RIGHT SIDE SLEEVE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TOPS TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH SLEEVES CIRCUMFERENCE ON THE INNER UPPER ARM; SANS 1822 ZIP; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; UNIQUE IDENTIFIER 240-44175132; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS

**CONTROLLED DISCLOSURE**

249	JACKET OVRL:CLEAN CONDITION;142 CM JACKET, OVERALL: TYPE: CLEAN CONDITION; SIZE: 142 CM; MATERIAL: COTTON 100% D59 PRE-SHRUNK; COLOR: WHITE; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE A CLOSED ONE PANEL ONLY MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE JACKET SHALL HAVE NO POCKETS; NO BUTTONS METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE LEFT-HAND TOP CHEST IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE RIGHT SIDE SLEEVE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TOPS TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH SLEEVES CIRCUMFERENCE ON THE INNER UPPER ARM; SANS 1822 ZIP; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; UNIQUE IDENTIFIER 240-44175132; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS
250	JACKET OVRL:CLEAN CONDITION;147 CM JACKET, OVERALL: TYPE: CLEAN CONDITION; SIZE: 147 CM; MATERIAL: COTTON 100% D59 PRE-SHRUNK; COLOR: WHITE; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE A CLOSED ONE PANEL ONLY MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE JACKET SHALL HAVE NO POCKETS; NO BUTTONS METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE LEFT-HAND TOP CHEST IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE RIGHT SIDE SLEEVE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TOPS TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH SLEEVES CIRCUMFERENCE ON THE INNER UPPER ARM; SANS 1822 ZIP; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; UNIQUE IDENTIFIER 240-44175132; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS
251	JACKET OVRL:CLEAN CONDITION;152 CM JACKET, OVERALL: TYPE: CLEAN CONDITION; SIZE: 152 CM; MATERIAL: COTTON 100% D59 PRE-SHRUNK; COLOR: WHITE; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE A CLOSED ONE PANEL ONLY MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE JACKET SHALL HAVE NO POCKETS; NO BUTTONS METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE LEFT-HAND TOP CHEST IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE RIGHT SIDE SLEEVE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TOPS TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH SLEEVES CIRCUMFERENCE ON THE INNER UPPER ARM; SANS 1822 ZIP; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; UNIQUE IDENTIFIER 240-44175132; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS
252	JACKET OVRL:CLEAN CONDITION;157 CM JACKET, OVERALL: TYPE: CLEAN CONDITION; SIZE: 157 CM; MATERIAL: COTTON 100% D59 PRE-SHRUNK; COLOR: WHITE; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE A CLOSED ONE PANEL ONLY MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE JACKET SHALL HAVE NO POCKETS; NO BUTTONS METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE LEFT-HAND TOP CHEST IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE RIGHT SIDE SLEEVE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TOPS TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH SLEEVES CIRCUMFERENCE ON THE INNER UPPER ARM; SANS 1822 ZIP; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; UNIQUE IDENTIFIER 240-44175132; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS
253	TROUSERS:CLEAN CONDITION;77 CM;WHITE TROUSERS: TYPE: CLEAN CONDITION; SIZE: 77 CM; COLOR: WHITE; MATERIAL: COTTON 100% D59 PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE SPECIFICATION REQUIREMENTS FOR SIZES UNDER SECTION 2.6 (OVERALL-BOILER SUITS OR 2 PIECE WORK WEAR SUITS) SHALL APPLY; MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN

**CONTROLLED DISCLOSURE**

	<p>ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE TROUSER SHALL HAVE NO POCKETS; NO BUTTONS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH DRAW CORD 10MM COTTON BELT STRING FOR FASTENING AND WITHOUT ZIP ON THE FRONT NO METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE RIGHT BACK IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE LEFT BACK SIDE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH LEGS CIRCUMFERENCE ON THE INNER UPPER LEG; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS ALL RELAVANT ITEMS TO COMPLY AS PER UNIQUE IDENTIFIER 240-44175132</p>
254	<p>TROUSERS:CLEAN CONDITION;82 CM;WHITE TROUSERS: TYPE: CLEAN CONDITION; SIZE: 82 CM; COLOR: WHITE; MATERIAL: COTTON 100% D59 PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE SPECIFICATION REQUIREMENTS FOR SIZES UNDER SECTION 2.6 (OVERALL-BOILER SUITS OR 2 PIECE WORK WEAR SUITS) SHALL APPLY; MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE TROUSER SHALL HAVE NO POCKETS; NO BUTTONS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH DRAW CORD 10MM COTTON BELT STRING FOR FASTENING AND WITHOUT ZIP ON THE FRONT NO METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE RIGHT BACK IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE LEFT BACK SIDE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH LEGS CIRCUMFERENCE ON THE INNER UPPER LEG; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS ALL RELAVANT ITEMS TO COMPLY AS PER UNIQUE IDENTIFIER 240-44175132</p>
255	<p>TROUSERS:CLEAN CONDITION;87 CM;WHITE TROUSERS: TYPE: CLEAN CONDITION; SIZE: 87 CM; COLOR: WHITE; MATERIAL: COTTON 100% D59 PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE SPECIFICATION REQUIREMENTS FOR SIZES UNDER SECTION 2.6 (OVERALL-BOILER SUITS OR 2 PIECE WORK WEAR SUITS) SHALL APPLY; MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE TROUSER SHALL HAVE NO POCKETS; NO BUTTONS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH DRAW CORD 10MM COTTON BELT STRING FOR FASTENING AND WITHOUT ZIP ON THE FRONT NO METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE RIGHT BACK IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE LEFT BACK SIDE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH LEGS CIRCUMFERENCE ON THE INNER UPPER LEG; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS ALL RELAVANT ITEMS TO COMPLY AS PER UNIQUE IDENTIFIER 240-44175132</p>
256	<p>TROUSERS:CLEAN CONDITION;92 CM;WHITE TROUSERS: TYPE: CLEAN CONDITION; SIZE: 92 CM; COLOR: WHITE; MATERIAL: COTTON 100% D59 PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE SPECIFICATION REQUIREMENTS FOR SIZES UNDER SECTION 2.6 (OVERALL-BOILER SUITS OR 2 PIECE WORK WEAR SUITS) SHALL APPLY; MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE TROUSER SHALL HAVE NO POCKETS; NO BUTTONS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH DRAW CORD 10MM COTTON BELT STRING FOR FASTENING AND WITHOUT ZIP ON THE FRONT NO METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE RIGHT BACK IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR</p>

**CONTROLLED DISCLOSURE**



	ON THE LEFT BACK SIDE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH LEGS CIRCUMFERENCE ON THE INNER UPPER LEG; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS ALL RELAVANT ITEMS TO COMPLY AS PER UNIQUE IDENTIFIER 240-44175132
257	TROUSERS:CLEAN CONDITION;97 CM;WHITE TROUSERS: TYPE: CLEAN CONDITION; SIZE: 97 CM; COLOR: WHITE; MATERIAL: COTTON 100% D59 PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE SPECIFICATION REQUIREMENTS FOR SIZES UNDER SECTION 2.6 (OVERALL-BOILER SUITS OR 2 PIECE WORK WEAR SUITS) SHALL APPLY; MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE TROUSER SHALL HAVE NO POCKETS; NO BUTTONS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH DRAW CORD 10MM COTTON BELT STRING FOR FASTENING AND WITHOUT ZIP ON THE FRONT NO METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE RIGHT BACK IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE LEFT BACK SIDE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH LEGS CIRCUMFERENCE ON THE INNER UPPER LEG; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS ALL RELAVANT ITEMS TO COMPLY AS PER UNIQUE IDENTIFIER 240-44175132
258	TROUSERS:CLEAN CONDITION;102 CM;WHITE TROUSERS: TYPE: CLEAN CONDITION; SIZE: 102 CM; COLOR: WHITE; MATERIAL: COTTON 100% D59 PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE SPECIFICATION REQUIREMENTS FOR SIZES UNDER SECTION 2.6 (OVERALL-BOILER SUITS OR 2 PIECE WORK WEAR SUITS) SHALL APPLY; MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE TROUSER SHALL HAVE NO POCKETS; NO BUTTONS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH DRAW CORD 10MM COTTON BELT STRING FOR FASTENING AND WITHOUT ZIP ON THE FRONT NO METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE RIGHT BACK IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE LEFT BACK SIDE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH LEGS CIRCUMFERENCE ON THE INNER UPPER LEG; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS ALL RELAVANT ITEMS TO COMPLY AS PER UNIQUE IDENTIFIER 240-44175132
259	TROUSERS:CLEAN CONDITION;107 CM;WHITE TROUSERS: TYPE: CLEAN CONDITION; SIZE: 107 CM; COLOR: WHITE; MATERIAL: COTTON 100% D59 PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE SPECIFICATION REQUIREMENTS FOR SIZES UNDER SECTION 2.6 (OVERALL-BOILER SUITS OR 2 PIECE WORK WEAR SUITS) SHALL APPLY; MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE TROUSER SHALL HAVE NO POCKETS; NO BUTTONS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH DRAW CORD 10MM COTTON BELT STRING FOR FASTENING AND WITHOUT ZIP ON THE FRONT NO METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE RIGHT BACK IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE LEFT BACK SIDE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH LEGS CIRCUMFERENCE ON THE INNER UPPER LEG; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS ALL RELAVANT ITEMS TO COMPLY AS PER UNIQUE IDENTIFIER 240-44175132

**CONTROLLED DISCLOSURE**

260	TROUSERS:CLEAN CONDITION;112 CM;WHITE TROUSERS: TYPE: CLEAN CONDITION; SIZE: 112 CM; COLOR: WHITE; MATERIAL: COTTON 100% D59 PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE SPECIFICATION REQUIREMENTS FOR SIZES UNDER SECTION 2.6 (OVERALL-BOILER SUITS OR 2 PIECE WORK WEAR SUITS) SHALL APPLY; MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE TROUSER SHALL HAVE NO POCKETS; NO BUTTONS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH DRAW CORD 10MM COTTON BELT STRING FOR FASTENING AND WITHOUT ZIP ON THE FRONT NO METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE RIGHT BACK IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE LEFT BACK SIDE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH LEGS CIRCUMFERENCE ON THE INNER UPPER LEG; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS ALL RELAVANT ITEMS TO COMPLY AS PER UNIQUE IDENTIFIER 240-44175132
261	TROUSERS:CLEAN CONDITION;117 CM;WHITE TROUSERS: TYPE: CLEAN CONDITION; SIZE: 117 CM; COLOR: WHITE; MATERIAL: COTTON 100% D59 PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE SPECIFICATION REQUIREMENTS FOR SIZES UNDER SECTION 2.6 (OVERALL-BOILER SUITS OR 2 PIECE WORK WEAR SUITS) SHALL APPLY; MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE TROUSER SHALL HAVE NO POCKETS; NO BUTTONS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH DRAW CORD 10MM COTTON BELT STRING FOR FASTENING AND WITHOUT ZIP ON THE FRONT NO METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE RIGHT BACK IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE LEFT BACK SIDE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH LEGS CIRCUMFERENCE ON THE INNER UPPER LEG; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS ALL RELAVANT ITEMS TO COMPLY AS PER UNIQUE IDENTIFIER 240-44175132
262	TROUSERS:CLEAN CONDITION;122 CM;WHITE TROUSERS: TYPE: CLEAN CONDITION; SIZE: 122 CM; COLOR: WHITE; MATERIAL: COTTON 100% D59 PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE SPECIFICATION REQUIREMENTS FOR SIZES UNDER SECTION 2.6 (OVERALL-BOILER SUITS OR 2 PIECE WORK WEAR SUITS) SHALL APPLY; MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE TROUSER SHALL HAVE NO POCKETS; NO BUTTONS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH DRAW CORD 10MM COTTON BELT STRING FOR FASTENING AND WITHOUT ZIP ON THE FRONT NO METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE RIGHT BACK IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE LEFT BACK SIDE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH LEGS CIRCUMFERENCE ON THE INNER UPPER LEG; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS ALL RELAVANT ITEMS TO COMPLY AS PER UNIQUE IDENTIFIER 240-44175132
263	TROUSERS:CLEAN CONDITION;127 CM;WHITE TROUSERS: TYPE: CLEAN CONDITION; SIZE: 127 CM; COLOR: WHITE; MATERIAL: COTTON 100% D59 PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE SPECIFICATION REQUIREMENTS FOR SIZES UNDER SECTION 2.6 (OVERALL-BOILER SUITS OR 2 PIECE WORK WEAR SUITS) SHALL APPLY; MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE TROUSER SHALL HAVE NO

**CONTROLLED DISCLOSURE**

	POCKETS; NO BUTTONS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH DRAW CORD 10MM COTTON BELT STRING FOR FASTENING AND WITHOUT ZIP ON THE FRONT NO METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE RIGHT BACK IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE LEFT BACK SIDE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH LEGS CIRCUMFERENCE ON THE INNER UPPER LEG; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS ALL RELAVANT ITEMS TO COMPLY AS PER UNIQUE IDENTIFIER 240-44175132
264	TROUSERS:ACID/ALKALI;77;GREEN BOTTLE TROUSERS: TYPE: ACID/ALKALI; SIZE: 77; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; LEG LENGTH: LONG; FIT: REGULAR; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132
265	TROUSERS:ACID/ALKALI;82 CM;GREEN BOTTLE TROUSERS: TYPE: ACID/ALKALI; SIZE: 82 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132
266	TROUSERS:ACID/ALKALI;87 CM;GREEN BOTTLE TROUSERS: TYPE: ACID/ALKALI; SIZE: 87 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132
267	TROUSERS:ACID/ALKALI;97 CM;GREEN BOTTLE TROUSERS: TYPE: ACID/ALKALI; SIZE: 97 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132
268	TROUSERS:ACID/ALKALI;102 CM;GREEN BOTTLE TROUSERS: TYPE: ACID/ALKALI; SIZE: 102 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE

**CONTROLLED DISCLOSURE**

	IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132
269	TROUSERS:ACID/ALKALI;107 CM;GREEN BOTTLE TROUSERS: TYPE: ACID/ALKALI; SIZE: 107 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132
270	TROUSERS:ACID/ALKALI;112 CM;GREEN BOTTLE TROUSERS: TYPE: ACID/ALKALI; SIZE: 112 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132
271	TROUSERS:ACID/ALKALI;117 CM;GREEN BOTTLE TROUSERS: TYPE: ACID/ALKALI; SIZE: 117 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132
272	TROUSERS:ACID/ALKALI;122 CM;GREEN BOTTLE TROUSERS: TYPE: ACID/ALKALI; SIZE: 122 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132
273	TROUSERS:ACID/ALKALI;127 CM;GREEN BOTTLE TROUSERS: TYPE: ACID/ALKALI; SIZE: 127 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS

**CONTROLLED DISCLOSURE**



	434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132
274	TROUSERS:ACID/ALKALI;132 CM;GREEN BOTTLE TROUSERS: TYPE: ACID/ALKALI; SIZE: 132 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132
275	TROUSERS:ACID/ALKALI;92 CM;GREEN BOTTLE TROUSERS: TYPE: ACID/ALKALI; SIZE: 92 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132
276	COVERALL:ACID RESIST;77;POLYCOTTON COVERALL: TYPE: ACID RESIST; SIZE: 77; MATERIAL: POLYCOTTON; COLOUR: BOTTLE GREEN; TO COMPLY WITH ESKOM PPE SPECIFICATION 240-44175132; MATERIAL TO POLY COTTON 65/35 FABRIC
277	COVERALL:ACID RESIST;82;POLYCOTTON COVERALL: TYPE: ACID RESIST; SIZE: 82; MATERIAL: POLYCOTTON; COLOUR: BOTTLE GREEN; TO COMPLY WITH ESKOM PPE SPECIFICATION 240-44175132; MATERIAL TO POLY COTTON 65/35 FABRIC
278	COVERALL:ACID RESIST;87;POLYCOTTON COVERALL: TYPE: ACID RESIST; SIZE: 87; MATERIAL: POLYCOTTON; COLOUR: BOTTLE GREEN; TO COMPLY WITH ESKOM PPE SPECIFICATION 240-44175132; MATERIAL TO POLY COTTON 65/35 FABRIC
279	COVERALL:ACID RESIST;92;POLYCOTTON COVERALL: TYPE: ACID RESIST; SIZE: 92; MATERIAL: POLYCOTTON; COLOUR: BOTTLE GREEN; TO COMPLY WITH ESKOM PPE SPECIFICATION 240-44175132; MATERIAL TO POLY COTTON 65/35 FABRIC
280	COVERALL:ACID RESIST;97;POLYCOTTON COVERALL: TYPE: ACID RESIST; SIZE: 97; MATERIAL: POLYCOTTON; COLOUR: BOTTLE GREEN; TO COMPLY WITH ESKOM PPE SPECIFICATION 240-44175132; MATERIAL TO POLY COTTON 65/35 FABRIC
281	COVERALL:ACID RESIST;102;POLYCOTTON COVERALL: TYPE: ACID RESIST; SIZE: 102; MATERIAL: POLYCOTTON; COLOUR: BOTTLE GREEN; TO COMPLY WITH ESKOM PPE SPECIFICATION 240-44175132; MATERIAL TO POLY COTTON 65/35 FABRIC
282	COVERALL:ACID RESIST;107;POLYCOTTON COVERALL: TYPE: ACID RESIST; SIZE: 107; MATERIAL: POLYCOTTON; COLOUR: BOTTLE GREEN; TO COMPLY WITH ESKOM PPE SPECIFICATION 240-44175132; MATERIAL TO POLY COTTON 65/35 FABRIC
283	COVERALL:ACID RESIST;112;POLYCOTTON COVERALL: TYPE: ACID RESIST; SIZE: 112; MATERIAL: POLYCOTTON; COLOUR: BOTTLE GREEN; TO COMPLY WITH ESKOM PPE SPECIFICATION 240-44175132; MATERIAL TO POLY COTTON 65/35 FABRIC
284	COVERALL:ACID RESIST;117;POLYCOTTON COVERALL: TYPE: ACID RESIST; SIZE: 117; MATERIAL: POLYCOTTON; COLOUR: BOTTLE GREEN; TO COMPLY WITH ESKOM PPE SPECIFICATION 240-44175132; MATERIAL TO POLY COTTON 65/35 FABRIC

**CONTROLLED DISCLOSURE**

285	COVERALL:ACID RESIST;122;POLYCOTTON COVERALL: TYPE: ACID RESIST; SIZE: 122; MATERIAL: POLYCOTTON; COLOUR: BOTTLE GREEN; TO COMPLY WITH ESKOM PPE SPECIFICATION 240-44175132; MATERIAL TO POLY COTTON 65/35 FABRIC
286	COVERALL:ACID RESIST;127;POLYCOTTON COVERALL: TYPE: ACID RESIST; SIZE: 127; MATERIAL: POLYCOTTON; COLOUR: BOTTLE GREEN; TO COMPLY WITH ESKOM PPE SPECIFICATION 240-44175132; MATERIAL TO POLY COTTON 65/35 FABRIC
287	COVERALL:ACID RESIST;132;POLYCOTTON COVERALL: TYPE: ACID RESIST; SIZE: 132; MATERIAL: POLYCOTTON; COLOUR: BOTTLE GREEN; TO COMPLY WITH ESKOM PPE SPECIFICATION 240-44175132; MATERIAL TO POLY COTTON 65/35 FABRIC
288	COVERALL:ACID RESIST;137;POLYCOTTON COVERALL: TYPE: ACID RESIST; SIZE: 137; MATERIAL: POLYCOTTON; COLOUR: BOTTLE GREEN; TO COMPLY WITH ESKOM PPE SPECIFICATION 240-44175132; MATERIAL TO POLY COTTON 65/35 FABRIC
289	COVERALL:ACID RESIST;142;POLYCOTTON COVERALL: TYPE: ACID RESIST; SIZE: 142; MATERIAL: POLYCOTTON; COLOUR: BOTTLE GREEN; TO COMPLY WITH ESKOM PPE SPECIFICATION 240-44175132; MATERIAL TO POLY COTTON 65/35 FABRIC
290	COVERALL:ACID RESIST;147;POLYCOTTON COVERALL: TYPE: ACID RESIST; SIZE: 147; MATERIAL: POLYCOTTON; COLOUR: BOTTLE GREEN; TO COMPLY WITH ESKOM PPE SPECIFICATION 240-44175132; MATERIAL TO POLY COTTON 65/35 FABRIC
291	COVERALL:ACID RESIST;152;POLYCOTTON COVERALL: TYPE: ACID RESIST; SIZE: 152; MATERIAL: POLYCOTTON; COLOUR: BOTTLE GREEN; TO COMPLY WITH ESKOM PPE SPECIFICATION 240-44175132; MATERIAL TO POLY COTTON 65/35 FABRIC
292	COVERALL:ACID RESIST;157;POLYCOTTON COVERALL: TYPE: ACID RESIST; SIZE: 157; MATERIAL: POLYCOTTON; COLOUR: BOTTLE GREEN; TO COMPLY WITH ESKOM PPE SPECIFICATION 240-44175132; MATERIAL TO POLY COTTON 65/35 FABRIC
293	JACKET OVRL:ACID RESIST;77;POLYCOTTON JACKET, OVERALL: TYPE: ACID RESIST; SIZE: 77; MATERIAL: POLYCOTTON; COLOR: GREEN BOTTLE; COMPLY WITH ESKOM PPE SPECIFICATION; MATERIAL TO BE POLY COTTON FABRIC (65/35)
294	JACKET OVRL:ACID RESIST;82;POLYCOTTON JACKET, OVERALL: TYPE: ACID RESIST; SIZE: 82; MATERIAL: POLYCOTTON; COLOR: GREEN BOTTLE; COMPLY WITH ESKOM PPE SPECIFICATION; MATERIAL TO BE POLY COTTON FABRIC (65/35)
295	JACKET OVRL:ACID RESIST;87;POLYCOTTON JACKET, OVERALL: TYPE: ACID RESIST; SIZE: 87; MATERIAL: POLYCOTTON; COLOR: GREEN BOTTLE; COMPLY WITH ESKOM PPE SPECIFICATION; MATERIAL TO BE POLY COTTON FABRIC (65/35)
296	JACKET OVRL:ACID RESIST;92;POLYCOTTON JACKET, OVERALL: TYPE: ACID RESIST; SIZE: 92; MATERIAL: POLYCOTTON; COLOR: GREEN BOTTLE; COMPLY WITH ESKOM PPE SPECIFICATION; MATERIAL TO BE POLY COTTON FABRIC (65/35)
297	JACKET OVRL:ACID RESIST;97;POLYCOTTON JACKET, OVERALL: TYPE: ACID RESIST; SIZE: 97; MATERIAL: POLYCOTTON; COLOR: GREEN BOTTLE; COMPLY WITH ESKOM PPE SPECIFICATION; MATERIAL TO BE POLY COTTON FABRIC (65/35)
298	JACKET OVRL:ACID RESIST;102;POLYCOTTON JACKET, OVERALL: TYPE: ACID RESIST; SIZE: 102; MATERIAL: POLYCOTTON; COLOR: GREEN BOTTLE; COMPLY WITH ESKOM PPE SPECIFICATION; MATERIAL TO BE POLY COTTON FABRIC (65/35)
299	JACKET OVRL:ACID RESIST;107;POLYCOTTON JACKET, OVERALL: TYPE: ACID RESIST; SIZE: 107; MATERIAL: POLYCOTTON; COLOR: GREEN BOTTLE; COMPLY WITH ESKOM PPE SPECIFICATION; MATERIAL TO BE POLY COTTON FABRIC (65/35)
300	JACKET OVRL:ACID RESIST;112;POLYCOTTON JACKET, OVERALL: TYPE: ACID RESIST; SIZE: 112; MATERIAL: POLYCOTTON; COLOR: GREEN BOTTLE; COMPLY WITH ESKOM PPE SPECIFICATION; MATERIAL TO BE POLY COTTON FABRIC (65/35)
301	JACKET OVRL:ACID RESIST;117;POLYCOTTON JACKET, OVERALL: TYPE: ACID RESIST; SIZE: 117; MATERIAL: POLYCOTTON; COLOR: GREEN BOTTLE; COMPLY WITH ESKOM PPE SPECIFICATION; MATERIAL TO BE POLY COTTON FABRIC (65/35)
302	JACKET OVRL:ACID RESIST;122;POLYCOTTON JACKET, OVERALL: TYPE: ACID RESIST; SIZE: 122; MATERIAL: POLYCOTTON; COLOR: GREEN BOTTLE; COMPLY WITH ESKOM PPE SPECIFICATION; MATERIAL TO BE POLY COTTON FABRIC (65/35)
303	JACKET OVRL:ACID RESIST;127;POLYCOTTON JACKET, OVERALL: TYPE: ACID RESIST; SIZE: 127; MATERIAL: POLYCOTTON; COLOR: GREEN BOTTLE; COMPLY WITH ESKOM PPE SPECIFICATION; MATERIAL TO BE POLY COTTON FABRIC (65/35)

**CONTROLLED DISCLOSURE**

304	JACKET OVRL:ACID RESIST;132;POLYCOTTON JACKET, OVERALL: TYPE: ACID RESIST; SIZE: 132; MATERIAL: POLYCOTTON; COLOR: GREEN BOTTLE; COMPLY WITH ESKOM PPE SPECIFICATION; MATERIAL TO BE POLY COTTON FABRIC (65/35)
305	JACKET OVRL:ACID RESIST;137;POLYCOTTON JACKET, OVERALL: TYPE: ACID RESIST; SIZE: 137; MATERIAL: POLYCOTTON; COLOR: GREEN BOTTLE; COMPLY WITH ESKOM PPE SPECIFICATION; MATERIAL TO BE POLY COTTON FABRIC (65/35)
306	JACKET OVRL:ACID RESIST;142;POLYCOTTON JACKET, OVERALL: TYPE: ACID RESIST; SIZE: 142; MATERIAL: POLYCOTTON; COLOR: GREEN BOTTLE; COMPLY WITH ESKOM PPE SPECIFICATION; MATERIAL TO BE POLY COTTON FABRIC (65/35)
307	JACKET OVRL:ACID RESIST;147;POLYCOTTON JACKET, OVERALL: TYPE: ACID RESIST; SIZE: 147; MATERIAL: POLYCOTTON; COLOR: GREEN BOTTLE; COMPLY WITH ESKOM PPE SPECIFICATION; MATERIAL TO BE POLY COTTON FABRIC (65/35)
308	TROUSERS:ACID RESIST;77;GREEN BOTTLE TROUSERS: TYPE: ACID RESIST; SIZE: 77; COLOR: GREEN BOTTLE; MATERIAL: POLYCOTTON; TO COMPLY WITH ESKOM SPECIFICATION 240-44175132; MATERIAL TO BE POLY COTTON FABRIC (65/35)
309	TROUSERS:ACID RESIST;82;GREEN BOTTLE TROUSERS: TYPE: ACID RESIST; SIZE: 82; COLOR: GREEN BOTTLE; MATERIAL: POLYCOTTON; TO COMPLY WITH ESKOM SPECIFICATION 240-44175132; MATERIAL TO BE POLY COTTON FABRIC (65/35)
310	TROUSERS:ACID RESIST;87;GREEN BOTTLE TROUSERS: TYPE: ACID RESIST; SIZE: 87; COLOR: GREEN BOTTLE; MATERIAL: POLYCOTTON; TO COMPLY WITH ESKOM SPECIFICATION 240-44175132; MATERIAL TO BE POLY COTTON FABRIC (65/35)
311	TROUSERS:ACID RESIST;92;GREEN BOTTLE TROUSERS: TYPE: ACID RESIST; SIZE: 92; COLOR: GREEN BOTTLE; MATERIAL: POLYCOTTON; TO COMPLY WITH ESKOM SPECIFICATION 240-44175132; MATERIAL TO BE POLY COTTON FABRIC (65/35)
312	TROUSERS:ACID RESIST;97;GREEN BOTTLE TROUSERS: TYPE: ACID RESIST; SIZE: 97; COLOR: GREEN BOTTLE; MATERIAL: POLYCOTTON; TO COMPLY WITH ESKOM SPECIFICATION 240-44175132; MATERIAL TO BE POLY COTTON FABRIC (65/35)
313	TROUSERS:ACID RESIST;102;GREEN BOTTLE TROUSERS: TYPE: ACID RESIST; SIZE: 102; COLOR: GREEN BOTTLE; MATERIAL: POLYCOTTON; TO COMPLY WITH ESKOM SPECIFICATION 240-44175132; MATERIAL TO BE POLY COTTON FABRIC (65/35)
314	TROUSERS:ACID RESIST;107;GREEN BOTTLE TROUSERS: TYPE: ACID RESIST; SIZE: 107; COLOR: GREEN BOTTLE; MATERIAL: POLYCOTTON; TO COMPLY WITH ESKOM SPECIFICATION 240-44175132; MATERIAL TO BE POLY COTTON FABRIC (65/35)
315	TROUSERS:ACID RESIST;112;GREEN BOTTLE TROUSERS: TYPE: ACID RESIST; SIZE: 112; COLOR: GREEN BOTTLE; MATERIAL: POLYCOTTON; TO COMPLY WITH ESKOM SPECIFICATION 240-44175132; MATERIAL TO BE POLY COTTON FABRIC (65/35)
316	TROUSERS:ACID RESIST;117;GREEN BOTTLE TROUSERS: TYPE: ACID RESIST; SIZE: 117; COLOR: GREEN BOTTLE; MATERIAL: POLYCOTTON; TO COMPLY WITH ESKOM SPECIFICATION 240-44175132; MATERIAL TO BE POLY COTTON FABRIC (65/35)
317	TROUSERS:ACID RESIST;122;GREEN BOTTLE TROUSERS: TYPE: ACID RESIST; SIZE: 122; COLOR: GREEN BOTTLE; MATERIAL: POLYCOTTON; TO COMPLY WITH ESKOM SPECIFICATION 240-44175132; MATERIAL TO BE POLY COTTON FABRIC (65/35)
318	TROUSERS:ACID RESIST;127;GREEN BOTTLE TROUSERS: TYPE: ACID RESIST; SIZE: 127; COLOR: GREEN BOTTLE; MATERIAL: POLYCOTTON; TO COMPLY WITH ESKOM SPECIFICATION 240-44175132; MATERIAL TO BE POLY COTTON FABRIC (65/35)
319	TROUSERS:ACID RESIST;132;GREEN BOTTLE TROUSERS: TYPE: ACID RESIST; SIZE: 132; COLOR: GREEN BOTTLE; MATERIAL: POLYCOTTON; TO COMPLY WITH ESKOM SPECIFICATION 240-44175132; MATERIAL TO BE POLY COTTON FABRIC (65/35)
320	TROUSERS:ACID RESIST;137;GREEN BOTTLE TROUSERS: TYPE: ACID RESIST; SIZE: 137; COLOR: GREEN BOTTLE; MATERIAL: POLYCOTTON; TO COMPLY WITH ESKOM SPECIFICATION 240-44175132; MATERIAL TO BE POLY COTTON FABRIC (65/35)
321	TROUSERS:ACID RESIST;142;GREEN BOTTLE TROUSERS: TYPE: ACID RESIST; SIZE: 142; COLOR: GREEN BOTTLE; MATERIAL: POLYCOTTON; TO COMPLY WITH ESKOM SPECIFICATION 240-44175132; MATERIAL TO BE POLY COTTON FABRIC (65/35)
322	TROUSERS:ACID RESIST;147;GREEN BOTTLE TROUSERS: TYPE: ACID RESIST; SIZE: 147; COLOR: GREEN BOTTLE; MATERIAL: POLYCOTTON; TO COMPLY WITH ESKOM SPECIFICATION 240-44175132; MATERIAL TO BE POLY COTTON FABRIC (65/35)

**CONTROLLED DISCLOSURE**

323	TROUSERS:ACID RESIST;152;GREEN BOTTLE TROUSERS: TYPE: ACID RESIST; SIZE: 152; COLOR: GREEN BOTTLE; MATERIAL: POLYCOTTON; TO COMPLY WITH ESKOM SPECIFICATION 240-44175132; MATERIAL TO BE POLY COTTON FABRIC (65/35)
324	TROUSERS:ACID RESIST;157;GREEN BOTTLE TROUSERS: TYPE: ACID RESIST; SIZE: 157; COLOR: GREEN BOTTLE; MATERIAL: POLYCOTTON; TO COMPLY WITH ESKOM SPECIFICATION 240-44175132; MATERIAL TO BE POLY COTTON FABRIC (65/35)
325	HELMET SFTY:HEIGHT THREE POINT;WHITE HELMET, SAFETY: TYPE: HEIGHT THREE POINT; SIZE: 530-630 MM; MATERIAL: PLASTIC MOLDED; COLOR: WHITE; SPECIFICATION: SANS 1397:2003; SPECIAL FEATURES: SHORT PEAK; ALL HARD HATS MUST BE IN ACCORDANCE WITH SANS 1397:2003 AND ESKOM SPECIFICATION; SUPPLIED WITH A BLACK ADJUSTABLE THREE POINT CHIN STRAP; MINIMUM HARD HAT ELECTRICAL INSULATION: 440 VAC; WITH A SHORTER PEAK AND A LIMITED SIDE BRIM; ITEM TO BE MARKED WITH SABS MARK OF APPROVAL; APPROVED ESKOM LOGO AND A ZERO HARM SLOGAN MUST BE POSITIONED ACCORDING TO THE ESKOM SPECIFICATION AND BE INLINE WITH THE CORPORATE IDENTITY PROCEDURE; WHITE REFLECTIVE AND BLUE LETTERS EUROP ASSIST EMERGENCY NO 086 123 7566 MUST BE DISPLAYED ON THE BACK OF THE HELMETS

### 3.2.2 DESIGN LIFE

The design life of the plant is till end of Kriel Power Station life 2038.

### DOCUMENTATION SUBMISSION AND RECORDING

The supplier is to provide the following documentation;

- Type test results certificates
- Medical and induction certificates
- Safety file
- Quality Control Process files (for quality assurance)
- Installation and Commissioning Manuals

### 3.2.3 PLANT CODIFICATION

Kriel Power Station uses the AKZ numbering system.

### CONTROLLED DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.



### 3.3 STANDARDS, SPECIFICATIONS AND PROCEDURES

All material and equipment shall be new and of the standard and quality specified. The design and manufacture of equipment and the complete installation shall be carried out and tested in accordance with the latest issue or amendments of the following Standards and Regulations, as applicable:

**Table 1: Relevant Standards and Codes**

Document Number	Title
<b>Eskom Standards</b>	
240-28463367	SHE Organization
240-30008949	Safety, Health and Environmental Specifications for Contractors
240-49230111	Hazard and Operability Analysis (HAZOP) Guideline (Rev 1)
240-55944466	Supplier Contract Quality Requirement's Specification
240-56364545	Structural Design and Engineering Standards
32-421	Cardinal Rules
36-681	Generation Plant Safety Regulations
OPS 0158	AKZ Power Plant Classification System
QM 58	Supplier Contract Quality Requirements
<b>General Standards</b>	
7.1/ST/02	Quality Requirements for Engineering and Construction work
ISO 9001	Quality Management Systems.
OSH Act 85 of 1993	Occupational Health and Safety Act and Regulations Act 85 of 1993.
SANS 10064	The Preparation of Steel Surfaces for Coatings
SANS 10108 (2005)	Classification of Hazardous Location (Electrical Plant)
SANS 10142	The Code of Practice for the Wiring of Premises

#### CONTROLLED DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

#### 4. AUTHORISATION

This document has been seen and accepted by:

Designation	Names
Material Management Manager	Mavis Mutheiwana
Maintenance Manager	Lungile Gumbi
Material Supervisor	Mshojo Mashaba
Senior Advisor	Spha Biyela

#### 5. REVISIONS

Date	Rev.	Compiler	Remarks
Feb 2022	1	S Biyela	First revision

#### 6. DEVELOPMENT TEAM

The following people were involved in the development of this document:

- S Biyela
- M Mashaba

#### 7. ACKNOWLEDGEMENT

#### CONTROLLED DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

---

## 8. APPENDIX A

### CONTROLLED DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.