

**ANNEXURE A**

TENDERER'S NAME																						
ITEM NO	ITEM DESCRIPTION	QUANTITY	ITEM SPECIFICATIONS	COMPLIANCE/NON-COMPLIANCE TO SPECIFICATIONS AND REQUIRED ITEM QUANTITIES	IF MARKED 'NO' IN THE PREVIOUS COLUMN, SPECIFY THE DEVIATION/S OR REASON/S FOR THE NON-COMPLIANCE	MANUFACTURER'S DATA SHEET INCLUDED (YES/NO)																
1	Portable electric compressors	4	<p><b>General Information</b></p> <p>Application: Compressor plant Dimensions (LxWxH) (mm): 5240 x 2210 x 2359 Mass (kg): 8650 Delivery port: 80mm Everlite 3" Male Spud with Gasket Sound Pressure Level (7m)dB(A): 98 Electric Motor Power (kW): 300/400 Voltage (V): 400 Frequency: 50 Startup Amps (A): 1200 Running Amps @ 7-10 bar (A): 500-560 Circuit Breaker (A): 630 Cabling: 2 x 120mm<sup>2</sup> Performance:</p> <table border="1"> <thead> <tr> <th>Performance</th> <th>Capacity (FAD)</th> </tr> <tr> <th>cfm</th> <th>m<sup>3</sup>/min</th> </tr> </thead> <tbody> <tr> <td>Pressure up to 0.6 bar (g)</td> <td>1613</td> <td>45.7</td> <td>762</td> </tr> <tr> <td>Pressure up to 0.9 bar (g)</td> <td>1522</td> <td>43.1</td> <td>718</td> </tr> <tr> <td>Pressure up to 10.3 bar (g)</td> <td>1320</td> <td>37.4</td> <td>632</td> </tr> </tbody> </table> <p><b>Other Features</b></p> <p>Auto Start: Hot Air Outlet Spillage Free Frame: Emergency Stop Switch Forklift Slots &amp; Lifting Eye Class Zero certified : Integrated Aftercooler +Water Separator (oil-free according to ISO8573-1)</p> <p><b>Mobile Dryer</b> Air Compressor Output: 1613 CFM (45,7m<sup>3</sup>/min) Dew point temperature: -20°C</p>	Performance	Capacity (FAD)	cfm	m <sup>3</sup> /min	Pressure up to 0.6 bar (g)	1613	45.7	762	Pressure up to 0.9 bar (g)	1522	43.1	718	Pressure up to 10.3 bar (g)	1320	37.4	632			
Performance	Capacity (FAD)																					
cfm	m <sup>3</sup> /min																					
Pressure up to 0.6 bar (g)	1613	45.7	762																			
Pressure up to 0.9 bar (g)	1522	43.1	718																			
Pressure up to 10.3 bar (g)	1320	37.4	632																			
2	Submersible water pump, 37kW	3	<p>Application: Station sumps and dams Pump type: Centrifugal submersible Discharge Pipe Size: 100mm Stage: 1 Capacity: 169m<sup>3</sup>/hr Total head: 28m NPSHr: 3.5m Speed: 1475 rpm Driver: Electric motor Mount: Vertical Model no.: HS-5150.300MT</p>																			
3	Mobile diesel lights	4	<p><b>Dimensions</b> Length: 2420mm Width: 1360mm Height: 3050mm Loading container: 2600mm height Full extending: 9m Height Gross weight: 850kg Genset power: 6kW (1500/1800rpm-kw)</p> <p><b>Engine Specifications</b> Speed: 1500/1800rpm Number of cylinders: 3 Engine characters: 4 cycles, water cooled, diesel Combustion system: E-TVS Engine aspiration: Naturally aspirated Emission level: Regular</p> <p><b>Alternator</b> Frequency: 50/60Hz Rating voltage: 220/110V (50 Hz), AC Alternator: Class H insulation Alternator: IP23 protection grade</p> <p><b>Mass &amp; Light</b> Type of lights: Regular metal halide Light fixture: Oval Luminous flux: 110 000LM/light Number &amp; power: 4 x 1000W Of lights Number of mast: Electrical (Vertical, 350lb winch) Sections Mast rotation: 359 degrees, manual rotation, self Locking Light tilt: Manually</p> <p><b>Trailer</b> Trailer suspension: Leaf springs axle without brake and axle with brakes Tow bar: A-style frame with supporting jack Stabilizing legs &amp; 4pcs drawbar with manual jacks number: Wheel's rim size: 14"sunraya rim with regular tyres &amp; tyres Tow adapter: 2" ball coupler or 3" pintle ring Di Tail lights: Complex tail lights 1"4HQ: 16 container</p>																			