

## ANNEXURE 1 - CATERING EQUIPMENT TECHNICAL SPECIFICATIONS

Item	Equipment Descriotion	Techical Specifications	Tendered to confirm if the tendered equipment complys not.	Reason For Non compliance	Comments by Eskom Evaluantor
1	Mobile food warmer cabinet with 11 shelves	External temperature display  Recessed handles to aid mobility  Protective rubber bumper strips prevent damage when moving  Double wall insulated construction maintains heat when not connected.  POWER RATING: 230V - 50Hz - 2620W  DIMENSIONS: 691 x 874 x 1797mm  CAPACITY: 22 TRAYS - GN 1/1  COMPLIES WITH SPEC: SABS IEC 60335	tendered equipment complys not.		
2	Hood type dishwasher	Must be capable of washing up to 720 plates per hour  28 litre wash tank  Boiler heating zero pressure 8,6 kW  Theoretical max racks per hour:  40  Plates per rack: 18  Wash pump size: 0.58kW  Wash pump capacity: 380  Ltrs/min  Wash tank heating: 4.05kW  Rinse boiler heating 380- 415A/C/50/3N : 12KW  Three-phase current 380V- 415V3N~; 50 Hz Fuse protection 17 Ampere  Operating voltage – Standard: 380-415AC/50/3N  Required water pressure: 2-4 bar			
		TOTAL VOLUMETRIC CAPACITY: 60 Lt VOLTAGE: 400V – 50Hz – 3 Phase			

1	1	POWER: 2.3kW		
3	60 -litre planetary mixer - NO HUB	DIMENSIONS: 910 x 730 x		
		DIMENSIONS: 910 x 730 x 1460mm		
		PLANETARY SPEED: 114 / 221 /		
		458rpm		
		WEIGHT: B63kg		
		WEIGHT. BOSKS		
		Cut Capacity: 290 x 140mm		
		Cut Thickness: 1-30mm		
		Cut length: 290mm		
		Cut Height: 140mm		
		Power: 1 PH, 0.25kW, 50 Hz		
4	300mm Meat Slicer	Dimensions: 650mm x 540mm x		
		460mm		
		Blade Diameter 300mm		
		Weight: 30 kg		
		Built in blade sharpener		
		·		
		Powered by Incoloy elements		
		that ensure consistent peak		
		performance		
		40mm drain valve		
		Front-mounted controls		
		Thermostatically controlled with		
		automatic safety cut-out to		
	Floor standing electric fover comprising of 2	prevent oil flashing		
5	Floor standing electric fryer comprising of 2 baskets of 20 litres each	Adjustable feet		
	busices of 20 in es cuen	Operating temperature range:		
		50 – 190 Degree Celsius		
		Power: 16.5kW		
		Voltage: 380V – 3 phase		
		Oil volume: 2 x 20L		
		Weight: 45kg		
		Dimensions: 510 x 660 x		
		1000mm		
		Capacity: 1200L		
		Number of doors: 2		
		Shelves per door: 3		
		Temperature range: -10°C To - 22°C		
		Refrigerant: R404a		
		Voltage: 230V – 50Hz		
		Interior dimensions: 1275 x 682 x		
		1395mm		
		Outside dimensions: 1425 x 818		
6	Commercial Kitchen Refreezer – Double Door –	x 1980mm		
1	S/Steel - 1200Lt			

	0,0000. 120020	I		T
		Grade 304 Stainless Steel		
		Construction		
		High Density Insulation		
		GN2/1 Shelf Size		
		GN Pan Or Wire Shelf Uses Same		
		Rails		
		Rounded Internal Corners For		
		Easy Cleaning		
		Self-Closing Doors With Lock		
		Self-Closing Doors With Lock		
		Digital Controller With Constant		
		Digital Display		
		Capacity: 1200L		
		Number of doors: 2		
		Shelves per door: 3		
		Temperature range: 0°C to +10°C		
		Refrigerant: R404a		
	COMMERCIAL KITCHEN REFRIGERATOR - DOUBLE DOOR - S/STEEL 1200Lt			
		Voltage: 230V – 50Hz		
		Interior dimensions: 1275 x 682 x		
		1395mm		
		Outside dimensions: 1425 x 818		
7		x 1980mm		
		Grade 304 Stainless Steel		
		Construction		
		High Density Insulation		
		GN2/1 Shelf Size		
		GN Pan Or Wire Shelf Uses Same		
		Rails		
		Rounded Internal Corners For		
		Easy Cleaning		
		Self-Closing Doors With Lock		
		Digital Controller With Constant		
		Digital Display		
		÷ 11 · 7		 
	<u> </u>	CRATED DIMENSIONS (EXCL	<u> </u>	
		COOLING UNIT): 3.7m L x 1.4m		
		W x 2.02m H		
		COOLING UNIT: AC Direct		
		Cubimax CXL 4000Z - B3		
		TEMPERATURE HOLDING LEVEL: -		
		18 °C		
8				
	o o	1.11m L x 0.61m H		
		20HD EPS Floor, with		
		checkerplate overlay		
		<del></del>		•

		20HD EPS Hinged Freezer Door, mounted into 20HD Wall Panel,		
		including Italian Pressure Relief		
		Port		
		20HD Wall and Ceiling Panels		
		6 Division		
	6 division Bain Marie	Floor standing		
		Dimensions: 2230x730x1400mm		
9		Power: 3.0kw		
		Voltage: 220volts		
		With Glass Sneeze Guard		
		6 X GN1/1 150 insert with lids		
		tray slide.		
		POWER RATING: 36KW		
	20 pan Electro- mechanical combi Steamer with trolley	VOLTAGE:380V - 3 PHASE - 50Hz		
		DIMENSIONS:		
10		1008X928X1970MM		
		CHAMBER DIMENSIONS: 506X642X1490MM		
		CAPACITY:20 TRAYS - GN 1/1		
		WEIGHT: 350KG		
		MUST INCLUDE: 20XGRILL		
		SHELVES		
	Compiled by	Caroline Letswalo	Supported By	Veliswa Mlotshwa
	unique number	4587332	unique number	4622/67
	Signature		Signature	A
			W)	( who thinks)