

www.pelchem.com

1. PRODUCT AND COMPANY IDENTIFACTION

PRODUCT NAME:

Hydrofluoric Acid Dilute <85% Solutions

COMPANY NAME: Pelchem (pty) Ltd

P O Box 582, Pretoria, 0001, South Africa Tel: 27 12 305-4444 / Fax: 27 12 305-4445 E-mail: cheminfo@pelchem.necsa.co.za Emergency tel: +27 12 305-3333/4

CHEMICAL FORMULA:

HFA

2. COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL NAME OF SUBSTANCE:

CONCENTRATION:

Aqueous Hydrofluoric Acid - contains water.

SYNONYMS:

Hydrofluoric Acid, Solution. Aqueous Hydrogen Fluoride.

UN No: 1790

CAS-No: 7664-39-3

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Very toxic by inhalation, in contact with skin and if swallowed. Causes severe burns. Inhalation of vapors in high concentration may cause shortness of breath (lung oedema). Ingestion causes burns of the upper digestive and respiratory tracts. Will penetrate skin and attack underlying tissues and bone.

4. FIRST AID MEASURES

GENERAL ADVICE:

Remove from exposure, lie down. Show this safety data sheet to the doctor in attendance.

SKIN CONTACT:

Wash off immediately with plenty of water. Take all contaminated clothing off immediately. First treatment with calcium gluconate paste. Consult a physician.

INGESTION:

Call a physician immediately. Drink plenty of water. Do not induce vomiting. If possible drink milk afterwards.

INHALATION:

Remove from exposure, lie down. Consult a physician. Oxygen or artificial respiration is needed. Observe patient for 24 hours for possible delayed symptoms.

EYE CONTACT:

Rinse thoroughly with plenty of water for at least 15 minutes keeping eyes wide open. Consult a physician.



5. FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA:

Water or water spray for fires adjacent to non-leaking tanks or containers. Carbon dioxide (CO₂), dry powder.

SPECIFIC METHODS:

Cool containers/tanks with water spray if not leaking.

SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS:

In case of fire, wear a self-contained breathing apparatus and full protective flameproof clothing.

SPECIFIC HAZARDS:

Reacts violently to water and can splash acid onto personnel.

EXTINGUISHING MEDIA WHICH MUST NOT BE USED FOR SAFETY REASONS:

Water or water spray for fires adjacent to leaking tanks or containers.

6. ACCIDENTAL RELEASE MEASURES

ENVIRONMENTAL PRECAUTIONS:

Prevent product from entering drains or environment.

METHODS OF CLEANING UP:

Dam up - dilute with water. Neutralize with soda ash or lime. Soak with inert absorbent material

PERSONAL PRECAUTIONS:

Ensure adequate ventilation. Use personal protective equipment. Evacuate personnel to safe areas.

7. HANDLING AND STORAGE

TECHNICAL MEASURES AND PRECAUTIONS:

Use only in area provided with appropriate exhaust ventilation.

HANDLING AND OPEN STORAGE CONDITIONS:

Keep container tightly closed in a dry, cool and well-ventilated area.

INCOMPATIBLE PRODUCTS:

Reacts violently with water. Strong oxidizing agents - metals.

PACKAGING MATERIAL:

70% HF (Industrial Grade) mild steel pressure vessels. (Bulk deliveries in South Africa only).

< 60% HF 200 liter or 25 liter polyethylene cans.

SAFE HANDLING DEVICE:

Do not breathe vapors or spray mist. Avoid contact with skin and eyes. Wear self-contained breathing apparatus and a protective suit.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

ENGINEERING MEASURES TO REDUCE EXPOSURE:

EYE PROTECTION:

Tightly fitting safety goggles and face-



Ensure adequate ventilation, especially in confined areas.

HAND PROTECTION:

Hydrofluoric acid-resistant and solvent-resistant gloves (gloves made of VITON*).

HYGIENE MEASURES:

Avoid contact with skin, eyes and clothing. When using - do not eat, drink or smoke. Contaminated work clothing should not be allowed out of the workplace.

RESPIRATORY PROTECTION:

Wear a positive-pressure supplied-air respirator with face shield (In case of higher concentration) Wear self-contained breathing apparatus and protective suit.

shield.

SKIN AND BODY PROTECTION:

Complete suit with rubber or plastic boots protecting against Hydrofluoric Acid.

CONTROL PARAMETERS:

OSHA PEL (3ppm). ACGIH TLV (3ppm).

9. PHYSICAL AND CHEMICAL PROPERTIES

FORM:

COLOR:

DENSITY:

Liquid.

Colorless

70% HF 1225 kg/m3 at 20 □ C

70% HF 1260 kg/m3 at 0□C

nH:

ODOR:

VAPOR DENSITY:

Strongly acidic.

Pungent.

2.21 (Air 1).

BOILING POINT: 70% HF: 63□C at sea **MELTING POINT:**

SOLUBILITY:

10/01

70% HF: 75□C.

Water solubility: completely miscible.

level

VAPOR PRESSURE:

70% HF 20 kPa at 20°C.

MOLECULAR WEIGHT (HF): 20.01

OTAD

70% HF 43 kPa at 40°C.

10. STABILITY AND REACTIVITY

STABILITY:

Stable at normal conditions.

CONDITIONS TO AVOID:

Gives off Hydrogen by reaction with

metals.

HAZARDOUS DECOMPOSITION

PRODUCTS:

Hydrogen, by reaction with metals. Silicon
Tetra fluoride by reaction with silicates, e.g.:

glass or sand.

MATERIALS TO AVOID: Glass, metals and bases

11. TOXICOLOGICAL INFORMATION

HUMAN EXPERIENCE:

Will penetrate skin and attack underlying tissues and bone.

CHRONIC TOXICITY:

May cause fluorosis.



LOCAL EFFECTS:

Very toxic by inhalation, in contact with skin and if swallowed. Risk of serious damage to eves, Ingestion causes burns of the upper digestive and respiratory tracts. Causes severe burns.

ACUTE TOXICITY:

LC50/inhalation/4h/rat = 456ppm. LC50/inhalation/1h/mouse = 342 ppm.

12. **ECOLOGICAL INFORMATION:**

ECOTOXICITY:

Acute fish toxicity = 60ppm/*/fish/lethal/fresh water (* = time period not specified.)

13. **DISPOSAL CONSIDERATIONS**

SAFE AND PREFERRED DISPOSAL METHODS:

Contact manufacturer.

CONTAMINATED PACKAGING:

Contact manufacturer.

TRANSPORT INFORMATION 14.

HS NO:

UN NO:

EMERGENCY ACTION CODE:

2811.11

1790

Corrosive

ADR/RID:

ADR/RID-Labels:

Proper shipping name:

Class: 8:6.1 TREM-CARD: Hydrofluoric Acid, Solution/ Fluoric Acid, Solution/Hydrogen Fluoride.

Solution

IMO:

IMDG Page: 8184

Proper shipping name:

Class: 8:6.1 Packaging group: | Hydrofluoric Acid, Solution/ Fluoric Acid, Solution/ Hydrogen Fluoride,

Solution

Solution

MFAG: 750

ICAO:

CLASS: 8:6.1

IMO-Labels:

Corrosive

Proper shipping name:

UN No: 1790

ICAO-Labels: Corrosive Packaging group: | Subrisk: Poison

Hydrofluoric Acid, Solution/Fluoric Acid, Solution/ Hydrogen Fluoride,

15. REGULATORY INFORMATION

APPLICABLE REGULATIONS:

Refer to country of destination.

SAFETY AND RISK PHRASES:

According to (National equivalent of EC-Dir.67/548), as amended, the product is labelled as follows:



According to (National equivalent of EC-Dir.67/548), as amended, the product is labeled

as follows:

T : Very toxic C : Corrosive

R26/27/28: Very toxic by inhalation, in contact with skin and if swallowed.

R35 : Causes severe burns.

S7/9 : Keep container tightly closed in well ventilated area.

S26 : In case of contact with eyes, rinse immediately with plenty of water and

seek medical advice.

S36/37/39: Wear suitable protective clothing, gloves and eye/face protection. In case of an accident or if you feel unwell, seek medical advice

immediately

(show the label where possible).

16. OTHER INFORMATION

RECOMMENDED USE:

- 1. Pickling agent for stainless steel.
- 2. Polishing of cut glass.
- 3. Cleaning of diamonds.
- 4. Chemical cleaning of components.
- 5. Preparation of natural gas wells.
- 6. Preparation of metal surfaces for plating.

REFERENCES:

- 1. (CED) Chemical Exchange Directory S.A., Geneva, Switzerland.
- 2. Hydrogen Fluoride Handling Guidelines, AECI Chloralkali and Plastics Ltd, Sasolburg, South Africa, April 1989.
- 3. Unpublished Reports, AEC of SA Ltd, Pelindaba, South Africa, 1993.
- 4. IMDG SABS 0228, SABS 0229.

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES:

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for his or her particular purpose(s).