



## Business Management System

Supply Chain Management

Warehouse

Warehouse Scope of Work for PPE Footwear

Material	Short Text	Long Text Description	Quantity Requested	Unit of Measure
0758979	BOOTS SFTY:GENERAL;3;BLACK AND BROWN	BOOTS, SAFETY: STYLE: GENERAL; SIZE: 3; COLOR: BLACK AND BROWN; FASTENING METHOD: LACE-UP; TOE CONSTRUCTION TYPE: STEEL OR CARBON FIBER; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; STANDARD: SABS SANS 20345; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2	2 000	PAA
0758960	BOOTS SFTY:GENERAL;4;BLACK/BROWN;LACE	BOOTS, SAFETY: STYLE: GENERAL; SIZE: 4; COLOR: BLACK/BROWN; FASTENING METHOD: LACE; TOE CONSTRUCTION TYPE: STEEL OR CARBON FIBRE; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; SPECIFICATION: SABS SANS 20345 MARK OF APPROVAL; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL	7 000	PAA

### Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

### Business Management System

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

		BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2		
0758961	BOOTS SFTY:GENERAL;5;BLACK AND BROWN	BOOTS, SAFETY: STYLE: GENERAL; SIZE: 5; COLOR: BLACK AND BROWN; FASTENING METHOD: LACE-UP; TOE CONSTRUCTION TYPE: STEEL OR CARBON FIBER; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; STANDARD: SABS SANS 20345; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2	11 640	PAA
0758954	BOOTS SFTY:GENERAL;6;BLACK AND BROWN	BOOTS, SAFETY: STYLE: GENERAL; SIZE: 6; COLOR: BLACK AND BROWN; FASTENING METHOD: LACE-UP; TOE CONSTRUCTION TYPE: STEEL OR CARBON FIBER; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; STANDARD: SABS SANS 20345; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2	13 640	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

### Business Management System

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

0758978	BOOTS SFTY:GENERAL;7;BLACK AND BROWN	BOOTS, SAFETY: STYLE: GENERAL; SIZE: 7; COLOR: BLACK AND BROWN; FASTENING METHOD: LACE-UP; TOE CONSTRUCTION TYPE: STEEL OR CARBON FIBER; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; STANDARD: SABS SANS 20345; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2	15 040	PAA
0758964	BOOTS SFTY:GENERAL;8;BLACK AND BROWN	BOOTS, SAFETY: STYLE: GENERAL; SIZE: 8; COLOR: BLACK AND BROWN; FASTENING METHOD: LACE-UP; TOE CONSTRUCTION TYPE: STEEL OR CARBON FIBER; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; STANDARD: SABS SANS 20345; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2	18 380	PAA
0758975	BOOTS SFTY:GENERAL;9;BLACK AND BROWN	BOOTS, SAFETY: STYLE: GENERAL; SIZE: 9; COLOR: BLACK AND BROWN; FASTENING METHOD: LACE-UP; TOE	15 000	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

## Business Management System

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

		CONSTRUCTION TYPE: STEEL OR CARBON FIBER; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; STANDARD: SABS SANS 20345; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2		
0758972	BOOTS SFTY:GENERAL;10;BLACK AND BROWN	BOOTS, SAFETY: STYLE: GENERAL; SIZE: 10; COLOR: BLACK AND BROWN; FASTENING METHOD: LACE-UP; TOE CONSTRUCTION TYPE: STEEL OR CARBON FIBER; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; STANDARD: SABS SANS 20345; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2	12 830	PAA
0758980	BOOTS SFTY:GENERAL;11;BLACK AND BROWN	BOOTS, SAFETY: STYLE: GENERAL; SIZE: 11; COLOR: BLACK AND BROWN; FASTENING METHOD: LACE-UP; TOE CONSTRUCTION TYPE: STEEL OR CARBON FIBER; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT	6 000	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

		LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; STANDARD: SABS SANS 20345; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2		
0758973	BOOTS SFTY:GENERAL;12;BLACK AND BROWN	BOOTS, SAFETY: STYLE: GENERAL; SIZE: 12; COLOR: BLACK AND BROWN; FASTENING METHOD: LACE-UP; TOE CONSTRUCTION TYPE: STEEL OR CARBON FIBER; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; STANDARD: SABS SANS 20345; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2	2 000	PAA
0758969	BOOTS SFTY:GENERAL;13;BLACK AND BROWN	BOOTS, SAFETY: STYLE: GENERAL; SIZE: 13; COLOR: BLACK AND BROWN; FASTENING METHOD: LACE-UP; TOE CONSTRUCTION TYPE: STEEL OR CARBON FIBER; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; STANDARD: SABS	500	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

## Business Management System

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

		SANS 20345; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2		
0758952	BOOTS SFTY:GENERAL;14;BLACK AND BROWN	BOOTS, SAFETY: STYLE: GENERAL; SIZE: 14; COLOR: BLACK AND BROWN; FASTENING METHOD: LACE-UP; TOE CONSTRUCTION TYPE: STEEL OR CARBON FIBER; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; STANDARD: SABS SANS 20345; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2	50	PAA
0670077	BOOTS SFTY:NEBULA;15;BLACK AND BROWN	BOOTS, SAFETY: STYLE: NEBULA; SIZE: 15; COLOR: BLACK AND BROWN; FASTENING METHOD: LACE-UP; TOE CONSTRUCTION TYPE: STEEL OR CARBON FIBER; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE	30	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

### Business Management System

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

		RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT		
0672082	BOOTS SFTY:NEBULA;16;BLACK AND BROWN	BOOTS, SAFETY: STYLE: NEBULA; SIZE: 16; COLOR: BLACK AND BROWN; FASTENING METHOD: LACE-UP; TOE CONSTRUCTION TYPE: STEEL OR CARBON FIBER; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT	50	PAA
0758974	BOOTS SFTY:ELECTRICAL;3;BLACK AND BROWN	BOOTS, SAFETY: STYLE: ELECTRICAL; SIZE: 3; COLOR: BLACK AND BROWN; FASTENING METHOD: LACE-UP; TOE CONSTRUCTION TYPE: CARBON FIBER; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4;	1 000	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

## Business Management System

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

		ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; STANDARD: SABS SANS 20345; MUST COMPLY TO ELECTRICAL TESTING SPECIFICATION 34-232; TO WITHSTAND ELECTRICAL RESISTANCE OF 20 KILO VOLT FOR 60 SECONDS; LACES MUST MATCH THE RELEVANT COLOUR BOOT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2		
0758956	BOOTS SFTY:ELECTRICAL;4;BLACK AND BROWN	BOOTS, SAFETY: STYLE: ELECTRICAL; SIZE: 4; COLOR: BLACK AND BROWN; FASTENING METHOD: LACE-UP; TOE CONSTRUCTION TYPE: CARBON FIBER; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; STANDARD: SABS SANS 20345; MUST COMPLY TO ELECTRICAL TESTING SPECIFICATION 34-232; TO WITHSTAND ELECTRICAL RESISTANCE OF 20 KILO VOLT FOR 60 SECONDS; LACES MUST MATCH THE RELEVANT COLOUR BOOT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2	1 000	PAA
0758968	BOOTS SFTY:ELECTRICAL;5;BLACK AND BROWN	BOOTS, SAFETY: STYLE: ELECTRICAL; SIZE: 5; COLOR: BLACK AND BROWN; FASTENING METHOD: LACE-UP; TOE CONSTRUCTION TYPE: CARBON FIBER; MATERIAL: FULL	1 000	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

		GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; STANDARD: SABS SANS 20345; MUST COMPLY TO ELECTRICAL TESTING SPECIFICATION 34-232; TO WITHSTAND ELECTRICAL RESISTANCE OF 20 KILO VOLT FOR 60 SECONDS; LACES MUST MATCH THE RELEVANT COLOUR BOOT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2		
0758944	BOOTS SFTY:ELECTRICAL;6;BLACK AND BROWN	BOOTS, SAFETY: STYLE: ELECTRICAL; SIZE: 6; COLOR: BLACK AND BROWN; FASTENING METHOD: LACE-UP; TOE CONSTRUCTION TYPE: CARBON FIBER; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; STANDARD: SABS SANS 20345; MUST COMPLY TO ELECTRICAL TESTING SPECIFICATION 34-232; TO WITHSTAND ELECTRICAL RESISTANCE OF 20 KILO VOLT FOR 60 SECONDS; LACES MUST MATCH THE RELEVANT COLOUR BOOT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2	1 000	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

0758959	BOOTS SFTY:ELECTRICAL;7;BLACK AND BROWN	BOOTS, SAFETY: STYLE: ELECTRICAL; SIZE: 7; COLOR: BLACK AND BROWN; FASTENING METHOD: LACE-UP; TOE CONSTRUCTION TYPE: CARBON FIBER; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; STANDARD: SABS SANS 20345; MUST COMPLY TO ELECTRICAL TESTING SPECIFICATION 34-232; TO WITHSTAND ELECTRICAL RESISTANCE OF 20 KILO VOLT FOR 60 SECONDS; LACES MUST MATCH THE RELEVANT COLOUR BOOT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2	1 000	PAA
0758967	BOOTS SFTY:ELECTRICAL;8;BLACK AND BROWN	BOOTS, SAFETY: STYLE: ELECTRICAL; SIZE: 8; COLOR: BLACK AND BROWN; FASTENING METHOD: LACE-UP; TOE CONSTRUCTION TYPE: CARBON FIBER; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; STANDARD: SABS SANS 20345; MUST COMPLY TO ELECTRICAL TESTING SPECIFICATION 34-232; TO WITHSTAND ELECTRICAL RESISTANCE OF 20 KILO VOLT FOR 60 SECONDS; LACES MUST MATCH THE RELEVANT COLOUR BOOT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR	1 000	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

### Business Management System

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

		FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2		
0758949	BOOTS SFTY:ELECTRICAL;9;BLACK AND BROWN	BOOTS, SAFETY: STYLE: ELECTRICAL; SIZE: 9; COLOR: BLACK AND BROWN; FASTENING METHOD: LACE-UP; TOE CONSTRUCTION TYPE: CARBON FIBER; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; STANDARD: SABS SANS 20345; MUST COMPLY TO ELECTRICAL TESTING SPECIFICATION 34-232; TO WITHSTAND ELECTRICAL RESISTANCE OF 20 KILO VOLT FOR 60 SECONDS; LACES MUST MATCH THE RELEVANT COLOUR BOOT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2	1 000	PAA
0758945	BOOTS SFTY:ELECTRICAL;10;BLACK AND BROWN	BOOTS, SAFETY: STYLE: ELECTRICAL; SIZE: 10; COLOR: BLACK AND BROWN; FASTENING METHOD: LACE-UP; TOE CONSTRUCTION TYPE: CARBON FIBER; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; STANDARD: SABS SANS 20345; MUST COMPLY TO ELECTRICAL TESTING SPECIFICATION 34-232; TO WITHSTAND ELECTRICAL RESISTANCE OF 20 KILO	1 000	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

## Business Management System

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

		VOLT FOR 60 SECONDS; LACES MUST MATCH THE RELEVANT COLOUR BOOT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2		
0758962	BOOTS SFTY:ELECTRICAL;11;BLACK AND BROWN	BOOTS, SAFETY: STYLE: ELECTRICAL; SIZE: 11; COLOR: BLACK AND BROWN; FASTENING METHOD: LACE-UP; TOE CONSTRUCTION TYPE: CARBON FIBER; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; STANDARD: SABS SANS 20345; MUST COMPLY TO ELECTRICAL TESTING SPECIFICATION 34-232; TO WITHSTAND ELECTRICAL RESISTANCE OF 20 KILO VOLT FOR 60 SECONDS; LACES MUST MATCH THE RELEVANT COLOUR BOOT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2	1 000	PAA
0758981	BOOTS SFTY:ELECTRICAL;12;BLACK AND BROWN	BOOTS, SAFETY: STYLE: ELECTRICAL; SIZE: 12; COLOR: BLACK AND BROWN; FASTENING METHOD: LACE-UP; TOE CONSTRUCTION TYPE: CARBON FIBER; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION	500	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

		RESISTANT INSERT; STANDARD: SABS SANS 20345; MUST COMPLY TO ELECTRICAL TESTING SPECIFICATION 34-232; TO WITHSTAND ELECTRICAL RESISTANCE OF 20 KILO VOLT FOR 60 SECONDS; LACES MUST MATCH THE RELEVANT COLOUR BOOT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2		
0758970	BOOTS SFTY:ELECTRICAL;13;BLACK AND BROWN	BOOTS, SAFETY: STYLE: ELECTRICAL; SIZE: 13; COLOR: BLACK AND BROWN; FASTENING METHOD: LACE-UP; TOE CONSTRUCTION TYPE: CARBON FIBER; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; STANDARD: SABS SANS 20345; MUST COMPLY TO ELECTRICAL TESTING SPECIFICATION 34-232; TO WITHSTAND ELECTRICAL RESISTANCE OF 20 KILO VOLT FOR 60 SECONDS; LACES MUST MATCH THE RELEVANT COLOUR BOOT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2	200	PAA
0758976	BOOTS SFTY:ELECTRICAL;14;BLACK AND BROWN	BOOTS, SAFETY: STYLE: ELECTRICAL; SIZE: 14; COLOR: BLACK AND BROWN; FASTENING METHOD: LACE-UP; TOE CONSTRUCTION TYPE: CARBON FIBER; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL	50	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

		RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; STANDARD: SABS SANS 20345; MUST COMPLY TO ELECTRICAL TESTING SPECIFICATION 34-232; TO WITHSTAND ELECTRICAL RESISTANCE OF 20 KILO VOLT FOR 60 SECONDS; LACES MUST MATCH THE RELEVANT COLOUR BOOT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2		
0758950	BOOTS SFTY:ELECTRICAL;15;BLACK AND BROWN	BOOTS, SAFETY: STYLE: ELECTRICAL; SIZE: 15; COLOR: BLACK AND BROWN; FASTENING METHOD: LACE-UP; TOE CONSTRUCTION TYPE: CARBON FIBER; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; STANDARD: SABS SANS 20345; MUST COMPLY TO ELECTRICAL TESTING SPECIFICATION 34-232; TO WITHSTAND ELECTRICAL RESISTANCE OF 20 KILO VOLT FOR 60 SECONDS; LACES MUST MATCH THE RELEVANT COLOUR BOOT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2	50	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

0758948	BOOTS SFTY:ELECTRICAL;16;BLACK AND BROWN	BOOTS, SAFETY: STYLE: ELECTRICAL; SIZE: 16; COLOR: BLACK AND BROWN; FASTENING METHOD: LACE-UP; TOE CONSTRUCTION TYPE: CARBON FIBER; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; STANDARD: SABS SANS 20345; MUST COMPLY TO ELECTRICAL TESTING SPECIFICATION 34-232; TO WITHSTAND ELECTRICAL RESISTANCE OF 20 KILO VOLT FOR 60 SECONDS; LACES MUST MATCH THE RELEVANT COLOUR BOOT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2	50	PAA
0758997	SHOES SFTY:GENERAL;3;BLACK/BROWN;LACE	SHOES, SAFETY: STYLE: GENERAL; SIZE: 3; COLOR: BLACK/BROWN; FASTENING METHOD: LACE; TOE CONSTRUCTION TYPE: STEEL OR CARBON FIBRE; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; SPECIFICATION: SABS SANS 20345 MARK OF APPROVAL; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2	340	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

0758988	SHOES SFTY:GENERAL;4;BLACK/BROWN;LACE	SHOES, SAFETY: STYLE: GENERAL; SIZE: 4; COLOR: BLACK/BROWN; FASTENING METHOD: LACE; TOE CONSTRUCTION TYPE: STEEL OR CARBON FIBRE; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; SPECIFICATION: SABS SANS 20345 MARK OF APPROVAL; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2	750	PAA
0758985	SHOES SFTY:GENERAL;6;BLACK/BROWN;LACE	SHOES, SAFETY: STYLE: GENERAL; SIZE: 6; COLOR: BLACK/BROWN; FASTENING METHOD: LACE; TOE CONSTRUCTION TYPE: STEEL OR CARBON FIBRE; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; SPECIFICATION: SABS SANS 20345 MARK OF APPROVAL; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2	1 800	PAA
0759000	SHOES SFTY:GENERAL;7;BLACK/BROWN;LACE	SHOES, SAFETY: STYLE: GENERAL; SIZE: 7; COLOR: BLACK/BROWN; FASTENING METHOD: LACE; TOE	3 500	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

		CONSTRUCTION TYPE: STEEL OR CARBON FIBRE; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; SPECIFICATION: SABS SANS 20345 MARK OF APPROVAL; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2		
0758986	SHOES SFTY:GENERAL;8;BLACK/BROWN;LACE	SHOES, SAFETY: STYLE: GENERAL; SIZE: 8; COLOR: BLACK/BROWN; FASTENING METHOD: LACE; TOE CONSTRUCTION TYPE: STEEL OR CARBON FIBRE; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; SPECIFICATION: SABS SANS 20345 MARK OF APPROVAL; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2	3 820	PAA
0758998	SHOES SFTY:GENERAL;9;BLACK/BROWN;LACE	SHOES, SAFETY: STYLE: GENERAL; SIZE: 9; COLOR: BLACK/BROWN; FASTENING METHOD: LACE; TOE CONSTRUCTION TYPE: STEEL OR CARBON FIBRE; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT	3 600	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

		LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; SPECIFICATION: SABS SANS 20345 MARK OF APPROVAL; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2		
0758996	SHOES SFTY:GENERAL;10;BLACK/BROWN;LACE	SHOES, SAFETY: STYLE: GENERAL; SIZE: 10; COLOR: BLACK/BROWN; FASTENING METHOD: LACE; TOE CONSTRUCTION TYPE: STEEL OR CARBON FIBRE; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; SPECIFICATION: SABS SANS 20345 MARK OF APPROVAL; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2	1 640	PAA
0758994	SHOES SFTY:GENERAL;11;BLACK/BROWN;LACE	SHOES, SAFETY: STYLE: GENERAL; SIZE: 11; COLOR: BLACK/BROWN; FASTENING METHOD: LACE; TOE CONSTRUCTION TYPE: STEEL OR CARBON FIBRE; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; SPECIFICATION: SABS	900	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

## Business Management System

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

		SANS 20345 MARK OF APPROVAL; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2		
0758982	SHOES SFTY:GENERAL;12;BLACK/BROWN;LACE	SHOES, SAFETY: STYLE: GENERAL; SIZE: 12; COLOR: BLACK/BROWN; FASTENING METHOD: LACE; TOE CONSTRUCTION TYPE: STEEL OR CARBON FIBRE; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; SPECIFICATION: SABS SANS 20345 MARK OF APPROVAL; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2	200	PAA
0759001	SHOES SFTY:GENERAL;13;BLACK/BROWN;LACE	SHOES, SAFETY: STYLE: GENERAL; SIZE: 13; COLOR: BLACK/BROWN; FASTENING METHOD: LACE; TOE CONSTRUCTION TYPE: STEEL OR CARBON FIBRE; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; SPECIFICATION: SABS SANS 20345 MARK OF APPROVAL; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL	100	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

### Business Management System

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

		BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2		
0758984	SHOES SFTY:ELECTRICAL;3;BLACK/BROWN;LACE	SHOES, SAFETY: STYLE: ELECTRICAL; SIZE: 3; COLOR: BLACK/BROWN; FASTENING METHOD: LACE; TOE CONSTRUCTION TYPE: CARBON FIBRE; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; SPECIFICATION: SABS SANS 20345 MARK OF APPROVAL; MUST COMPLY TO ELECTRICAL TESTING SPECIFICATION 34-232; TO WITHSTAND ELECTRICAL RESISTANCE OF 20 KILO VOLT FOR 60 SECONDS; LACES MUST MATCH THE RELEVANT COLOUR BOOT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2	500	PAA
0758990	SHOES SFTY:ELECTRICAL;4;BLACK/BROWN;LACE	SHOES, SAFETY: STYLE: ELECTRICAL; SIZE: 4; COLOR: BLACK/BROWN; FASTENING METHOD: LACE; TOE CONSTRUCTION TYPE: CARBON FIBRE; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; SPECIFICATION: SABS SANS 20345 MARK OF APPROVAL; MUST COMPLY TO ELECTRICAL TESTING SPECIFICATION 34-232; TO WITHSTAND ELECTRICAL RESISTANCE OF 20 KILO VOLT FOR 60	500	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

		SECONDS; LACES MUST MATCH THE RELEVANT COLOUR BOOT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2		
0759003	SHOES SFTY:ELECTRICAL;5;BLACK/BROWN;LACE	SHOES, SAFETY: STYLE: ELECTRICAL; SIZE: 5; COLOR: BLACK/BROWN; FASTENING METHOD: LACE; TOE CONSTRUCTION TYPE: CARBON FIBRE; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; SPECIFICATION: SABS SANS 20345 MARK OF APPROVAL; MUST COMPLY TO ELECTRICAL TESTING SPECIFICATION 34-232; TO WITHSTAND ELECTRICAL RESISTANCE OF 20 KILO VOLT FOR 60 SECONDS; LACES MUST MATCH THE RELEVANT COLOUR BOOT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2	500	PAA
0758991	SHOES SFTY:ELECTRICAL;6;BLACK/BROWN;LACE	SHOES, SAFETY: STYLE: ELECTRICAL; SIZE: 6; COLOR: BLACK/BROWN; FASTENING METHOD: LACE; TOE CONSTRUCTION TYPE: CARBON FIBRE; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; SPECIFICATION: SABS SANS 20345	500	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

### Business Management System

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

		MARK OF APPROVAL; MUST COMPLY TO ELECTRICAL TESTING SPECIFICATION 34-232; TO WITHSTAND ELECTRICAL RESISTANCE OF 20 KILO VOLT FOR 60 SECONDS; LACES MUST MATCH THE RELEVANT COLOUR BOOT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2		
0758992	SHOES SFTY:ELECTRICAL;7;BLACK/BROWN;LACE	SHOES, SAFETY: STYLE: ELECTRICAL; SIZE: 7; COLOR: BLACK/BROWN; FASTENING METHOD: LACE; TOE CONSTRUCTION TYPE: CARBON FIBRE; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; SPECIFICATION: SABS SANS 20345 MARK OF APPROVAL; MUST COMPLY TO ELECTRICAL TESTING SPECIFICATION 34-232; TO WITHSTAND ELECTRICAL RESISTANCE OF 20 KILO VOLT FOR 60 SECONDS; LACES MUST MATCH THE RELEVANT COLOUR BOOT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2	200	PAA
0758995	SHOES SFTY:ELECTRICAL;8;BLACK/BROWN;LACE	SHOES, SAFETY: STYLE: ELECTRICAL; SIZE: 8; COLOR: BLACK/BROWN; FASTENING METHOD: LACE; TOE CONSTRUCTION TYPE: CARBON FIBRE; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER	200	PAA

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

		RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; SPECIFICATION: SABS SANS 20345 MARK OF APPROVAL; MUST COMPLY TO ELECTRICAL TESTING SPECIFICATION 34-232; TO WITHSTAND ELECTRICAL RESISTANCE OF 20 KILO VOLT FOR 60 SECONDS; LACES MUST MATCH THE RELEVANT COLOUR BOOT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2		
0758983	SHOES SFTY:ELECTRICAL;9;BLACK/BROWN;LACE	SHOES, SAFETY: STYLE: ELECTRICAL; SIZE: 9; COLOR: BLACK/BROWN; FASTENING METHOD: LACE; TOE CONSTRUCTION TYPE: CARBON FIBRE; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; SPECIFICATION: SABS SANS 20345 MARK OF APPROVAL; MUST COMPLY TO ELECTRICAL TESTING SPECIFICATION 34-232; TO WITHSTAND ELECTRICAL RESISTANCE OF 20 KILO VOLT FOR 60 SECONDS; LACES MUST MATCH THE RELEVANT COLOUR BOOT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2	200	PAA
0758989	SHOES	SHOES, SAFETY: STYLE: ELECTRICAL; SIZE: 10; COLOR: BLACK/BROWN; FASTENING METHOD: LACE; TOE	500	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

	SFTY:ELECTRICAL;10;BLACK/BROWN	CONSTRUCTION TYPE: CARBON FIBRE; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; SPECIFICATION: SABS SANS 20345 MARK OF APPROVAL; MUST COMPLY TO ELECTRICAL TESTING SPECIFICATION 34-232; TO WITHSTAND ELECTRICAL RESISTANCE OF 20 KILO VOLT FOR 60 SECONDS; LACES MUST MATCH THE RELEVANT COLOUR BOOT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2		
0758999	SHOES SFTY:ELECTRICAL;11;BLACK/BROWN	SHOES, SAFETY: STYLE: ELECTRICAL; SIZE: 11; COLOR: BLACK/BROWN; FASTENING METHOD: LACE; TOE CONSTRUCTION TYPE: CARBON FIBRE; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; SPECIFICATION: SABS SANS 20345 MARK OF APPROVAL; MUST COMPLY TO ELECTRICAL TESTING SPECIFICATION 34-232; TO WITHSTAND ELECTRICAL RESISTANCE OF 20 KILO VOLT FOR 60 SECONDS; LACES MUST MATCH THE RELEVANT COLOUR BOOT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST	500	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

### Business Management System

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

		COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2		
0758987	SHOES SFTY:ELECTRICAL;12;BLACK/BROWN	SHOES, SAFETY: STYLE: ELECTRICAL; SIZE: 12; COLOR: BLACK/BROWN; FASTENING METHOD: LACE; TOE CONSTRUCTION TYPE: CARBON FIBRE; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; SPECIFICATION: SABS SANS 20345 MARK OF APPROVAL; MUST COMPLY TO ELECTRICAL TESTING SPECIFICATION 34-232; TO WITHSTAND ELECTRICAL RESISTANCE OF 20 KILO VOLT FOR 60 SECONDS; LACES MUST MATCH THE RELEVANT COLOUR BOOT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2	500	PAA
0759002	SHOES SFTY:ELECTRICAL;13;BLACK/BROWN	SHOES, SAFETY: STYLE: ELECTRICAL; SIZE: 13; COLOR: BLACK/BROWN; FASTENING METHOD: LACE; TOE CONSTRUCTION TYPE: CARBON FIBRE; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; SPECIFICATION: SABS SANS 20345 MARK OF APPROVAL; MUST COMPLY TO ELECTRICAL TESTING SPECIFICATION 34-232; TO WITHSTAND ELECTRICAL RESISTANCE OF 20 KILO VOLT FOR 60 SECONDS; LACES MUST MATCH THE RELEVANT COLOUR	500	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

		BOOT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2		
0758947	BOOTS SFTY:CLEAN CONDITION;3;WHITE	BOOTS, SAFETY: STYLE: CLEAN CONDITION; SIZE: 3; COLOR: WHITE; FASTENING METHOD: SLIP-ON; TOE CONSTRUCTION TYPE: CARBON FIBER; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; STANDARD: SABS SANS 20345; MUST COMPLY TO ELECTRICAL TESTING SPECIFICATION 34-232; TO WITHSTAND ELECTRICAL RESISTANCE OF 20 KILO VOLT FOR 60 SECONDS; LACES MUST MATCH THE RELEVANT COLOUR BOOT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2	300	PAA
0758951	BOOTS SFTY:CLEAN CONDITION;4;WHITE	BOOTS, SAFETY: STYLE: CLEAN CONDITION; SIZE: 4; COLOR: WHITE; FASTENING METHOD: SLIP-ON; TOE CONSTRUCTION TYPE: CARBON FIBER; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; STANDARD: SABS SANS 20345; MUST COMPLY TO ELECTRICAL TESTING SPECIFICATION 34-232;	600	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

		TO WITHSTAND ELECTRICAL RESISTANCE OF 20 KILO VOLT FOR 60 SECONDS; LACES MUST MATCH THE RELEVANT COLOUR BOOT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2		
0758963	BOOTS SFTY:CLEAN CONDITION;5;WHITE	BOOTS, SAFETY: STYLE: CLEAN CONDITION; SIZE: 5; COLOR: WHITE; FASTENING METHOD: SLIP-ON; TOE CONSTRUCTION TYPE: CARBON FIBER; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; STANDARD: SABS SANS 20345; MUST COMPLY TO ELECTRICAL TESTING SPECIFICATION 34-232; TO WITHSTAND ELECTRICAL RESISTANCE OF 20 KILO VOLT FOR 60 SECONDS; LACES MUST MATCH THE RELEVANT COLOUR BOOT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2	740	PAA
0758953	BOOTS SFTY:CLEAN CONDITION;6;WHITE	BOOTS, SAFETY: STYLE: CLEAN CONDITION; SIZE: 6; COLOR: WHITE; FASTENING METHOD: SLIP-ON; TOE CONSTRUCTION TYPE: CARBON FIBER; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4;	1 220	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

### Business Management System

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

		ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; STANDARD: SABS SANS 20345; MUST COMPLY TO ELECTRICAL TESTING SPECIFICATION 34-232; TO WITHSTAND ELECTRICAL RESISTANCE OF 20 KILO VOLT FOR 60 SECONDS; LACES MUST MATCH THE RELEVANT COLOUR BOOT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2		
0758966	BOOTS SFTY:CLEAN CONDITION;7;WHITE	BOOTS, SAFETY: STYLE: CLEAN CONDITION; SIZE: 7; COLOR: WHITE; FASTENING METHOD: SLIP-ON; TOE CONSTRUCTION TYPE: CARBON FIBER; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; STANDARD: SABS SANS 20345; MUST COMPLY TO ELECTRICAL TESTING SPECIFICATION 34-232; TO WITHSTAND ELECTRICAL RESISTANCE OF 20 KILO VOLT FOR 60 SECONDS; LACES MUST MATCH THE RELEVANT COLOUR BOOT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2	1 900	PAA
0758965	BOOTS SFTY:CLEAN CONDITION;8;WHITE	BOOTS, SAFETY: STYLE: CLEAN CONDITION; SIZE: 8; COLOR: WHITE; FASTENING METHOD: SLIP-ON; TOE CONSTRUCTION TYPE: CARBON FIBER; MATERIAL: FULL	2 100	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

		GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; STANDARD: SABS SANS 20345; MUST COMPLY TO ELECTRICAL TESTING SPECIFICATION 34-232; TO WITHSTAND ELECTRICAL RESISTANCE OF 20 KILO VOLT FOR 60 SECONDS; LACES MUST MATCH THE RELEVANT COLOUR BOOT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2		
0758958	BOOTS SFTY:CLEAN CONDITION;9;WHITE	BOOTS, SAFETY: STYLE: CLEAN CONDITION; SIZE: 9; COLOR: WHITE; FASTENING METHOD: SLIP-ON; TOE CONSTRUCTION TYPE: CARBON FIBER; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; STANDARD: SABS SANS 20345; MUST COMPLY TO ELECTRICAL TESTING SPECIFICATION 34-232; TO WITHSTAND ELECTRICAL RESISTANCE OF 20 KILO VOLT FOR 60 SECONDS; LACES MUST MATCH THE RELEVANT COLOUR BOOT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2	1 700	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

0758957	BOOTS SFTY:CLEAN CONDITION;10;WHITE	BOOTS, SAFETY: STYLE: CLEAN CONDITION; SIZE: 10; COLOR: WHITE; FASTENING METHOD: SLIP-ON; TOE CONSTRUCTION TYPE: CARBON FIBER; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; STANDARD: SABS SANS 20345; MUST COMPLY TO ELECTRICAL TESTING SPECIFICATION 34-232; TO WITHSTAND ELECTRICAL RESISTANCE OF 20 KILO VOLT FOR 60 SECONDS; LACES MUST MATCH THE RELEVANT COLOUR BOOT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2	1 180	PAA
0758971	BOOTS SFTY:CLEAN CONDITION;11;WHITE	BOOTS, SAFETY: STYLE: CLEAN CONDITION; SIZE: 11; COLOR: WHITE; FASTENING METHOD: SLIP-ON; TOE CONSTRUCTION TYPE: CARBON FIBER; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; STANDARD: SABS SANS 20345; MUST COMPLY TO ELECTRICAL TESTING SPECIFICATION 34-232; TO WITHSTAND ELECTRICAL RESISTANCE OF 20 KILO VOLT FOR 60 SECONDS; LACES MUST MATCH THE RELEVANT COLOUR BOOT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR	640	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

		FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2		
0758946	BOOTS SFTY:CLEAN CONDITION;12;WHITE	BOOTS, SAFETY: STYLE: CLEAN CONDITION; SIZE: 12; COLOR: WHITE; FASTENING METHOD: SLIP-ON; TOE CONSTRUCTION TYPE: CARBON FIBER; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; STANDARD: SABS SANS 20345; MUST COMPLY TO ELECTRICAL TESTING SPECIFICATION 34-232; TO WITHSTAND ELECTRICAL RESISTANCE OF 20 KILO VOLT FOR 60 SECONDS; LACES MUST MATCH THE RELEVANT COLOUR BOOT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2	465	PAA
0758977	BOOTS SFTY:CLEAN CONDITION;13;WHITE	BOOTS, SAFETY: STYLE: CLEAN CONDITION; SIZE: 13; COLOR: WHITE; FASTENING METHOD: SLIP-ON; TOE CONSTRUCTION TYPE: CARBON FIBER; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; STANDARD: SABS SANS 20345; MUST COMPLY TO ELECTRICAL TESTING SPECIFICATION 34-232; TO WITHSTAND ELECTRICAL RESISTANCE OF 20 KILO	170	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

		VOLT FOR 60 SECONDS; LACES MUST MATCH THE RELEVANT COLOUR BOOT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2		
0758955	BOOTS SFTY:CLEAN CONDITION;14;WHITE	BOOTS, SAFETY: STYLE: CLEAN CONDITION; SIZE: 14; COLOR: WHITE; FASTENING METHOD: SLIP-ON; TOE CONSTRUCTION TYPE: CARBON FIBER; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; STANDARD: SABS SANS 20345; MUST COMPLY TO ELECTRICAL TESTING SPECIFICATION 34-232; TO WITHSTAND ELECTRICAL RESISTANCE OF 20 KILO VOLT FOR 60 SECONDS; LACES MUST MATCH THE RELEVANT COLOUR BOOT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2	50	PAA
0747169	BOOTS:FIREFIGHTER;10;BLACK AND YELLOW	BOOTS: TYPE: FIREFIGHTER; SIZE: 10; COLOR: BLACK AND YELLOW; MATERIAL: KEVLAR NOMEX LINING; SOLE MATERIAL: STEEL MID SOLE; OIL RESISTANT AND FLAME RETARDANT; STYLE: ART: 9679; CE/CSA CLASS I/ ANSI AND NFPA CONFORMANCE; FLAME RETARDANT HEAVY-DUTY PULL-ON STRAPS; FLAME RETARDANT UPPER COMPUND; SHIN GUARD; FOAM MIDLEG PADDING FOR	50	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

		EXTRA WARMTH AND LONGER DURATION; LEG LINING WITH KEVLAR NOMEX AND INTERLINING MATERIAL FOR HEAT RESISTANT; STEEL TO CAP CSA GRADE 1; ANSIZ41P101; BS EN 12565:1998; 200 JOULES AND COMPRESSION ENGERGY 15000 NEWTONS; ANGLE PADDING; TOP AND IDE HI-VISIBILITY REFLECTOR; BUILT IN CUSHION SPONGE INSOLE; SOLE ELECTRIC SHOCK RESISTANT; RUST PROOF STEEL SHANK		
0747170	BOOTS:FIREFIGHTER;11;BLACK AND YELLOW	BOOTS: TYPE: FIREFIGHTER; SIZE: 11; COLOR: BLACK AND YELLOW; MATERIAL: KEVLAR NOMEX LINING; SOLE MATERIAL: STEEL MID SOLE; OIL RESISTANT AND FLAME RETARDANT; STYLE: ART: 9679; CE/CSA CLASS I/ ANSI AND NFPA CONFORMANCE; FLAME RETARDANT HEAVY-DUTY PULL-ON STRAPS; FLAME RETARDANT UPPER COMPUND; SHIN GUARD; FOAM MIDLEG PADDING FOR EXTRA WARMTH AND LONGER DURATION; LEG LINING WITH KEVLAR NOMEX AND INTERLINING MATERIAL FOR HEAT RESISTANT; STEEL TO CAP CSA GRADE 1; ANSIZ41P101; BS EN 12565:1998; 200 JOULES AND COMPRESSION ENGERGY 15000 NEWTONS; ANGLE PADDING; TOP AND IDE HI-VISIBILITY REFLECTOR; BUILT IN CUSHION SPONGE INSOLE; SOLE ELECTRIC SHOCK RESISTANT; RUST PROOF STEEL SHANK	50	PAA
0747164	BOOTS:FIREFIGHTER;5;BLACK AND YELLOW	BOOTS: TYPE: FIREFIGHTER; SIZE: 5; COLOR: BLACK AND YELLOW; MATERIAL: KEVLAR NOMEX LINING; SOLE MATERIAL: STEEL MID SOLE; OIL RESISTANT AND FLAME RETARDANT; STYLE: ART: 9679; CE/CSA CLASS I/ ANSI AND NFPA CONFORMANCE; FLAME RETARDANT HEAVY-DUTY PULL-ON STRAPS; FLAME RETARDANT UPPER	50	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

		COMPUND; SHIN GUARD; FOAM MIDLEG PADDING FOR EXTRA WARMTH AND LONGER DURATION; LEG LINING WITH KEVLAR NOMEX AND INTERLINING MATERIAL FOR HEAT RESISTANT; STEEL TO CAP CSA GRADE 1; ANSIZ41P101; BS EN 12565:1998; 200 JOULES AND COMPRESSION ENGERGY 15000 NEWTONS; ANGLE PADDING; TOP AND IDE HI-VISIBILITY REFLECTOR; BUILT IN CUSHION SPONGE INSOLE; SOLE ELECTRIC SHOCK RESISTANT; RUST PROOF STEEL SHANK		
0747165	BOOTS:FIREFIGHTER;6;BLACK AND YELLOW	BOOTS: TYPE: FIREFIGHTER; SIZE: 6; COLOR: BLACK AND YELLOW; MATERIAL: KEVLAR NOMEX LINING; SOLE MATERIAL: STEEL MID SOLE; OIL RESISTANT AND FLAME RETARDANT; STYLE: ART: 9679; CE/CSA CLASS I/ ANSI AND NFPA CONFORMANCE; FLAME RETARDANT HEAVY-DUTY PULL-ON STRAPS; FLAME RETARDANT UPPER COMPUND; SHIN GUARD; FOAM MIDLEG PADDING FOR EXTRA WARMTH AND LONGER DURATION; LEG LINING WITH KEVLAR NOMEX AND INTERLINING MATERIAL FOR HEAT RESISTANT; STEEL TO CAP CSA GRADE 1; ANSIZ41P101; BS EN 12565:1998; 200 JOULES AND COMPRESSION ENGERGY 15000 NEWTONS; ANGLE PADDING; TOP AND IDE HI-VISIBILITY REFLECTOR; BUILT IN CUSHION SPONGE INSOLE; SOLE ELECTRIC SHOCK RESISTANT; RUST PROOF STEEL SHANK	50	PAA
0747166	BOOTS:FIREFIGHTER;7;BLACK AND YELLOW	BOOTS: TYPE: FIREFIGHTER; SIZE: 7; COLOR: BLACK AND YELLOW; MATERIAL: KEVLAR NOMEX LINING; SOLE MATERIAL: STEEL MID SOLE; OIL RESISTANT AND FLAME RETARDANT; STYLE: ART: 9679; CE/CSA CLASS I/ ANSI AND NFPA CONFORMANCE; FLAME RETARDANT HEAVY-	1 000	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

		DUTY PULL-ON STRAPS; FLAME RETARDANT UPPER COMPUND; SHIN GUARD; FOAM MIDLEG PADDING FOR EXTRA WARMTH AND LONGER DURATION; LEG LINING WITH KEVLAR NOMEX AND INTERLINING MATERIAL FOR HEAT RESISTANT; STEEL TO CAP CSA GRADE 1; ANSIZ41P101; BS EN 12565:1998; 200 JOULES AND COMPRESSION ENGERGY 15000 NEWTONS; ANGLE PADDING; TOP AND IDE HI-VISIBILITY REFLECTOR; BUILT IN CUSHION SPONGE INSOLE; SOLE ELECTRIC SHOCK RESISTANT; RUST PROOF STEEL SHANK		
0747167	BOOTS:FIREFIGHTER;8;BLACK AND YELLOW	BOOTS: TYPE: FIREFIGHTER; SIZE: 8; COLOR: BLACK AND YELLOW; MATERIAL: KEVLAR NOMEX LINING; SOLE MATERIAL: STEEL MID SOLE; OIL RESISTANT AND FLAME RETARDANT; STYLE: ART: 9679; CE/CSA CLASS I/ ANSI AND NFPA CONFORMANCE; FLAME RETARDANT HEAVY-DUTY PULL-ON STRAPS; FLAME RETARDANT UPPER COMPUND; SHIN GUARD; FOAM MIDLEG PADDING FOR EXTRA WARMTH AND LONGER DURATION; LEG LINING WITH KEVLAR NOMEX AND INTERLINING MATERIAL FOR HEAT RESISTANT; STEEL TO CAP CSA GRADE 1; ANSIZ41P101; BS EN 12565:1998; 200 JOULES AND COMPRESSION ENGERGY 15000 NEWTONS; ANGLE PADDING; TOP AND IDE HI-VISIBILITY REFLECTOR; BUILT IN CUSHION SPONGE INSOLE; SOLE ELECTRIC SHOCK RESISTANT; RUST PROOF STEEL SHANK	100	PAA
0747168	BOOTS:FIREFIGHTER;9;BLACK AND YELLOW	BOOTS: TYPE: FIREFIGHTER; SIZE: 9; COLOR: BLACK AND YELLOW; MATERIAL: KEVLAR NOMEX LINING; SOLE MATERIAL: STEEL MID SOLE; OIL RESISTANT AND FLAME RETARDANT; STYLE: ART: 9679; CE/CSA CLASS I/ ANSI	100	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

		AND NFPA CONFORMANCE; FLAME RETARDANT HEAVY-DUTY PULL-ON STRAPS; FLAME RETARDANT UPPER COMPUND; SHIN GUARD; FOAM MIDLEG PADDING FOR EXTRA WARMTH AND LONGER DURATION; LEG LINING WITH KEVLAR NOMEX AND INTERLINING MATERIAL FOR HEAT RESISTANT; STEEL TO CAP CSA GRADE 1; ANSIZ41P101; BS EN 12565:1998; 200 JOULES AND COMPRESSION ENGERGY 15000 NEWTONS; ANGLE PADDING; TOP AND IDE HI-VISIBILITY REFLECTOR; BUILT IN CUSHION SPONGE INSOLE; SOLE ELECTRIC SHOCK RESISTANT; RUST PROOF STEEL SHANK		
0759203	BOOTS SFTY:WELDERS;7;BLACK;LACE-UP	BOOTS, SAFETY: STYLE: WELDERS; SIZE: 7; COLOR: BLACK; FASTENING METHOD: LACE-UP; TOE CONSTRUCTION TYPE: STEEL CAP; MATERIAL: FULL GRAIN UPPER LEATHER; LEATHER SPAT COVERING TO SHIELD LACES; TREAD SURFACE TYPE: DUAL DENSITY POLYURETHANE; HEAT-RESISTANT UP TO 300 DEG C; STANDARD: SANS/ISO 20345	100	PAA
0759207	BOOTS SFTY:WELDERS;8;BLACK;LACE-UP	BOOTS, SAFETY: STYLE: WELDERS; SIZE: 8; COLOR: BLACK; FASTENING METHOD: LACE-UP; TOE CONSTRUCTION TYPE: STEEL CAP; MATERIAL: FULL GRAIN UPPER LEATHER; LEATHER SPAT COVERING TO SHIELD LACES; TREAD SURFACE TYPE: DUAL DENSITY POLYURETHANE; HEAT-RESISTANT UP TO 300 DEG C; STANDARD: SANS/ISO 20345	100	PAA
0759209	BOOTS SFTY:WELDERS;9;BLACK;LACE-UP	BOOTS, SAFETY: STYLE: WELDERS; SIZE: 9; COLOR: BLACK; FASTENING METHOD: LACE-UP; TOE CONSTRUCTION TYPE: STEEL CAP; MATERIAL: FULL	100	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

## Business Management System

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

		GRAIN UPPER LEATHER; LEATHER SPAT COVERING TO SHIELD LACES; TREAD SURFACE TYPE: DUAL DENSITY POLYURETHANE; HEAT-RESISTANT UP TO 300 DEG C; STANDARD: SANS/ISO 20345		
0759210	BOOTS SFTY:WELDERS;10;BLACK;LACE-UP	BOOTS, SAFETY: STYLE: WELDERS; SIZE: 10; COLOR: BLACK; FASTENING METHOD: LACE-UP; TOE CONSTRUCTION TYPE: STEEL CAP; MATERIAL: FULL GRAIN UPPER LEATHER; LEATHER SPAT COVERING TO SHIELD LACES; TREAD SURFACE TYPE: DUAL DENSITY POLYURETHANE; HEAT-RESISTANT UP TO 300 DEG C; STANDARD: SANS/ISO 20345	100	PAA
0759211	BOOTS SFTY:WELDERS;11;BLACK;LACE-UP	BOOTS, SAFETY: STYLE: WELDERS; SIZE: 11; COLOR: BLACK; FASTENING METHOD: LACE-UP; TOE CONSTRUCTION TYPE: STEEL CAP; MATERIAL: FULL GRAIN UPPER LEATHER; LEATHER SPAT COVERING TO SHIELD LACES; TREAD SURFACE TYPE: DUAL DENSITY POLYURETHANE; HEAT-RESISTANT UP TO 300 DEG C; STANDARD: SANS/ISO 20345	100	PAA
0017014	GUMBOOTS SFTY:STL;7;KNEE HEIGHT;BLACK	GUMBOOTS, SAFETY: TOE CAP: STEEL; SIZE: 7; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; FASTENING METHOD: SLIP ON; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132 REV 2; SIZE 255; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT LEVEL 4; NON SLIP SOLE; WATERPROOF CONSTRUCTION; BEARING SABS MARK OF APPROVAL	1 730	PAA
0017015	GUMBOOTS SFTY:STL;8;KNEE	GUMBOOTS, SAFETY: TOE CAP: STEEL; SIZE: 8; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER;	1 630	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

	HEIGHT;BLACK	TREAD TYPE: RUBBER MOLDED; FASTENING METHOD: SLIP ON; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132 REV 2; SIZE 262; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT LEVEL 4; NON SLIP SOLE; WATERPROOF CONSTRUCTION; TO SABS 20345		
0017016	GUMBOOTS SFTY:STL;9;KNEE HEIGHT;BLACK	GUMBOOTS, SAFETY: TOE CAP: STEEL; SIZE: 9; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; FASTENING METHOD: SLIP ON; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132 REV 2; SIZE 270; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT LEVEL 4; NON SLIP SOLE; WATERPROOF CONSTRUCTION; TO SABS 20345	1 460	PAA
0017017	GUMBOOTS SFTY:STL;10;KNEE HEIGHT;BLACK	GUMBOOTS, SAFETY: TOE CAP: STEEL; SIZE: 10; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; FASTENING METHOD: SLIP ON; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132 REV 2; SIZE 280; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT LEVEL 4; NON SLIP SOLE; WATERPROOF CONSTRUCTION; TO SABS 20345	1 050	PAA
0017018	GUMBOOTS SFTY:STL;11;KNEE HEIGHT;BLACK	GUMBOOTS, SAFETY: TOE CAP: STEEL; SIZE: 11; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; FASTENING METHOD: SLIP ON; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132 REV 2; SIZE: 290; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT	550	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

## Business Management System

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

		LEVEL 4; NON SLIP SOLE; WATERPROOF CONSTRUCTION; TO SABS 20345		
0161000	GUMBOOTS SFTY:STL;12;KNEE HEIGHT;BLACK	GUMBOOTS, SAFETY: TOE CAP: STEEL; SIZE: 12; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; FASTENING METHOD: SLIP ON; SPECIFICATION: UNIQUE IDENTIFIER 240- 44175132 REV 2; SIZE 292; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT LEVEL 4; NON SLIP SOLE; WATERPROOF CONSTRUCTION; TO SABS 20345	1 740	PAA
0161108	GUMBOOTS SFTY:STL;6;KNEE HEIGHT;BLACK	GUMBOOTS, SAFETY: TOE CAP: STEEL; SIZE: 6; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; FASTENING METHOD: SLIP ON; SPECIFICATION: UNIQUE IDENTIFIER 240- 44175132 REV 2; SIZE 247; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT LEVEL 4; NON SLIP SOLE; WATERPROOF CONSTRUCTION; TO SABS 20345	1 000	PAA
0161114	GUMBOOTS SFTY:STL;13;KNEE HEIGHT;BLACK	GUMBOOTS, SAFETY: TOE CAP: STEEL; SIZE: 13; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; FASTENING METHOD: SLIP ON; SPECIFICATION: UNIQUE IDENTIFIER 240- 44175132 REV 2; SIZE 300; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT LEVEL 4; NON SLIP SOLE; WATERPROOF CONSTRUCTION; TO SABS 20345	130	PAA
0566206	GUMBOOTS SFTY:STL;3;KNEE	GUMBOOTS, SAFETY: TOE CAP: STEEL; SIZE: 3; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER;	160	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

	HEIGHT;BLACK	TREAD TYPE: RUBBER MOLDED; FASTENING METHOD: SLIP ON; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132 REV 2; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT LEVEL 4; NON SLIP SOLE; WATERPROOF CONSTRUCTION; TO SABS 20345		
0566207	GUMBOOTS SFTY:STL;4;KNEE HEIGHT;BLACK	GUMBOOTS, SAFETY: TOE CAP: STEEL; SIZE: 4; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; FASTENING METHOD: SLIP ON; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132 REV 2; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT LEVEL 4; NON SLIP SOLE; WATERPROOF CONSTRUCTION; TO SABS 20345	190	PAA
0566208	GUMBOOTS SFTY:STL;5;KNEE HEIGHT;BLACK	GUMBOOTS, SAFETY: TOE CAP: STEEL; SIZE: 5; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; FASTENING METHOD: SLIP ON; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132 REV 2; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT LEVEL 4; NON SLIP SOLE; WATERPROOF CONSTRUCTION; TO SABS 20345	640	PAA
0566391	WADER:FISHERMANS;12;PVC;GREEN OLIVE	WADER: TYPE: FISHERMANS; SIZE: 12; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132	50	PAA
0566392	WADER:FISHERMANS;13;PVC;GREEN	WADER: TYPE: FISHERMANS; SIZE: 13; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF	60	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

## Business Management System

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

	OLIVE	TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132		
0160593	WADER:FISHERMANS;7;PVC;GREEN OLIVE	WADER: TYPE: FISHERMANS; SIZE: 7; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132	170	PAA
0160594	WADER:FISHERMANS;8;PVC;GREEN OLIVE	WADER: TYPE: FISHERMANS; SIZE: 8; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132	150	PAA
0160595	WADER:FISHERMANS;9;PVC;GREEN OLIVE	WADER: TYPE: FISHERMANS; SIZE: 9; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132	260	PAA
0160596	WADER:FISHERMANS;10;PVC;GREEN OLIVE	WADER: TYPE: FISHERMANS; SIZE: 10; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132	150	PAA
0160597	WADER:FISHERMANS;11;PVC;GREEN OLIVE	WADER: TYPE: FISHERMANS; SIZE: 11; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132	280	PAA
0566383	WADER:FISHERMANS;6;PVC;GREEN OLIVE	WADER: TYPE: FISHERMANS; SIZE: 6; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132	100	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

## Business Management System

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

0594002	COVER:OVERSHOE;M;WHITE;CLEAN ROOM	COVER: TYPE: OVERSHOE; DIMENSIONS: M; MATERIAL: COTTON BULL DENIM 100 PCT; COLOR: WHITE; APPLICATION: CLEAN ROOM; SPECIFICATION: SABS/SANS 20345-2008; RE-WASHABLE; 1.5 MM WHITE NON-SLIP RUBBER SOLE, DOUBLE STITCHING EXSTRA STRONG BRADE THREAD; HIGH ENOUGH TO COVER A BOOT TIPE SAFETY SHOE; SHOE LACE TO KEEP SHOE TIGHT AT ALL TIMES; SUPPLIER NOTE ! THE OVERSHOE MUST CONFORM TO SABS SANS 20345:2008 SECTION 5.3.5 (5.3.5.2 MINIMUM SPEC) TESTED IN ACCORDANCE WITH ISO 20344 SECTION 5.11 AND THE COEFFICIENT OF FRICTION DETERMINED IN ACCORDANCE WITH ISO 13287	2 980	EA
0594003	COVER:OVERSHOE;L;WHITE;CLEAN ROOM	COVER: TYPE: OVERSHOE; DIMENSIONS: L; MATERIAL: COTTON BULL DENIM 100 PCT; COLOR: WHITE; APPLICATION: CLEAN ROOM; SPECIFICATION: SABS/SANS 20345-2008; RE-WASHABLE; 1.5 MM WHITE NON-SLIP RUBBER SOLE, DOUBLE STITCHING EXSTRA STRONG BRADE THREAD; HIGH ENOUGH TO COVER A BOOT TIPE SAFETY SHOE; SHOE LACE TO KEEP SHOE TIGHT AT ALL TIMES; SUPPLIER NOTE ! THE OVERSHOE MUST CONFORM TO SABS SANS 20345:2008 SECTION 5.3.5 (5.3.5.2 MINIMUM SPEC) TESTED IN ACCORDANCE WITH ISO 20344 SECTION 5.11 AND THE COEFFICIENT OF FRICTION DETERMINED IN ACCORDANCE WITH ISO 13287	3 900	EA
0672096	BOOTS SFTY:JIM GREEN HIGHLANDER B3;9;TAN	BOOTS, SAFETY: STYLE: JIM GREEN HIGHLANDER B3; SIZE: 9; COLOR: TAN; FASTENING METHOD: BRAIDED LACES; TOE CONSTRUCTION TYPE: STEEL CAP; MATERIAL: 2-2.2 MM – BEST FULL GRAIN GENUINE	15	PAA

### Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

		LEATHER; TREAD SURFACE TYPE: GENUINE RUBBER MAN-MADE NON-TOXIC CLEATED; LINING: SUPER ABSORBENT GENUINE LEATHER LINING WITH EXTRA SOFTNESS AS WELL AS SYNTHETIC LINING; TONGUE PADDING: 32 MM SUPERSOFT SPONGE PADDING ENSURING SOFTNESS ON THE INSTEP; COLLAR PADDING: 32 MM SUPERSOFT SPONGE PADDING AND AN ADDED SOFT 4 MM EVA BACKING LAMINATED TO ACTUAL SPONGE FOR ANGLE SECURE AND PROTECTION; EYELETS AND HOOKS: DOUBLE RIVEITED FOR EXTRA STRENGTH AS WELL AS BEING FIRMLY SECURE AND RUST PROOF; UPPER STITCHING: POLYESTER UV RESISTANT DURABLE HEAVY DUTY THREAD AND INDUSTRIAL THREAD; INNER SOLE; NON-WOOVEN 2.5 MM FLEXIBLE STURDY INSOLE BOARD; OUTER INSOLE: NON-WOOVEN 4MM FLEXIBLE AND STRONG NON-CRUMBLE PROVIDING FOOT SUPPORT; FOOTBED: REMOVABLE MICRO-FIBRE ABSORBENT BREATHABLE AIR-RATED FOOTBED ALLOWING FOR CUSHIONING OF THE FOOT AND COMFORT DURING WALKING AND WEAR; ENVIROMENTALLY FRIENDLY		
0672719	BOOTS SFTY:RE424-BR;8;BROWN;LACE-UP	BOOTS, SAFETY: STYLE: RE424-BR; SIZE: 8; COLOR: BROWN; FASTENING METHOD: LACE-UP; TOE CONSTRUCTION TYPE: STEEL CAP; MATERIAL: NUBUCK LEATHER; EVA MIDSOLE AND RUBBER OUTSOLE; TREAD SURFACE TYPE: SLIP RESISTANT; ANTI-PENETRAION; MODEL NO: REBEL EXPEDITION HI RE424-BR	100	PAA
0672813	SHOES SFTY:TRENDY	SHOES, SAFETY: STYLE: TRENDY SNEAKER; SIZE: 09; COLOR: CHARCOAL; FASTENING METHOD: LACES; TOE	15	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

## Business Management System

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

	SNEAKER;09;CHARCOAL	CONSTRUCTION TYPE: 200J WIDE STEEL TOE CAP; MATERIAL: QUALITY TEAR RESISTANT MICRO-FIBRE; TREAD SURFACE TYPE: DUAL DENSITY POLY-URETHANE; SLIP AND PENETRANT RESISTANT; SPECIFICATION: ISO 20345; GENDER: MALE		
0642356	BOOTS SFTY:NEBULA;3;BROWN;STEEL CAP	BOOTS, SAFETY: STYLE: NEBULA; SIZE: 3; COLOR: BROWN; FASTENING METHOD: 5 PAIR LOOPS; SKI HOOKS CORROSION-RESISTANT GUNMETAL COATING; BRAIDED LACE; TOE CONSTRUCTION TYPE: STEEL CAP; MATERIAL: LEATHER FULL GRAIN OILY PULL-UP; TREAD SURFACE TYPE: POLYURETHANE/VIBRAM RUBBER; SRC SLIP RESISTANCE; SPECIFICATION: UNIQUE IDENTIFIER 240- 44175132; MODEL NO: 43606; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT	40	PAA
0642355	BOOTS SFTY:NEBULA;4;BROWN;STEEL CAP	BOOTS, SAFETY: STYLE: NEBULA; SIZE: 4; COLOR: BROWN; FASTENING METHOD: 5 PAIR LOOPS; SKI HOOKS CORROSION-RESISTANT GUNMETAL COATING; BRAIDED LACE; TOE CONSTRUCTION TYPE: STEEL CAP; MATERIAL: LEATHER FULL GRAIN OILY PULL-UP; TREAD SURFACE TYPE: POLYURETHANE/VIBRAM RUBBER; SRC SLIP RESISTANCE; SPECIFICATION: UNIQUE IDENTIFIER 240- 44175132; MODEL NO: 43606; STANDARD BOOTS TO	60	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

		COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT		
0642357	BOOTS SFTY:NEBULA;5;BROWN;STEEL CAP	BOOTS, SAFETY: STYLE: NEBULA; SIZE: 5; COLOR: BROWN; FASTENING METHOD: 5 PAIR LOOPS; SKI HOOKS CORROSION-RESISTANT GUNMETAL COATING; BRAIDED LACE; TOE CONSTRUCTION TYPE: STEEL CAP; MATERIAL: LEATHER FULL GRAIN OILY PULL-UP; TREAD SURFACE TYPE: POLYURETHANE/VIBRAM RUBBER; SRC SLIP RESISTANCE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; MODEL NO: 43606; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT	40	PAA
0642358	BOOTS SFTY:NEBULA;6;BROWN;STEEL CAP	BOOTS, SAFETY: STYLE: NEBULA; SIZE: 6; COLOR: BROWN; FASTENING METHOD: 5 PAIR LOOPS; SKI HOOKS CORROSION-RESISTANT GUNMETAL COATING; BRAIDED LACE; TOE CONSTRUCTION TYPE: STEEL CAP; MATERIAL: LEATHER FULL GRAIN OILY PULL-UP; TREAD SURFACE	40	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

		TYPE: POLYURETHANE/VIBRAM RUBBER; SRC SLIP RESISTANCE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; MODEL NO: 43606; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT		
0642359	BOOTS SFTY:NEBULA;7;BROWN;STEEL CAP	BOOTS, SAFETY: STYLE: NEBULA; SIZE: 7; COLOR: BROWN; FASTENING METHOD: 5 PAIR LOOPS; SKI HOOKS CORROSION-RESISTANT GUNMETAL COATING; BRAIDED LACE; TOE CONSTRUCTION TYPE: STEEL CAP; MATERIAL: LEATHER FULL GRAIN OILY PULL-UP; TREAD SURFACE TYPE: POLYURETHANE/VIBRAM RUBBER; SRC SLIP RESISTANCE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; MODEL NO: 43606; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT	100	PAA
0642360	BOOTS SFTY:NEBULA;8;BROWN;STEEL	BOOTS, SAFETY: STYLE: NEBULA; SIZE: 8; COLOR: BROWN; FASTENING METHOD: 5 PAIR LOOPS; SKI HOOKS	120	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

**Business Management System**

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

	CAP	CORROSION-RESISTANT GUNMETAL COATING; BRAIDED LACE; TOE CONSTRUCTION TYPE: STEEL CAP; MATERIAL: LEATHER FULL GRAIN OILY PULL-UP; TREAD SURFACE TYPE: POLYURETHANE/VIBRAM RUBBER; SRC SLIP RESISTANCE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; MODEL NO: 43606; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT		
0642361	BOOTS SFTY:NEBULA;9;BROWN;STEEL CAP	BOOTS, SAFETY: STYLE: NEBULA; SIZE: 9; COLOR: BROWN; FASTENING METHOD: 5 PAIR LOOPS; SKI HOOKS CORROSION-RESISTANT GUNMETAL COATING; BRAIDED LACE; TOE CONSTRUCTION TYPE: STEEL CAP; MATERIAL: LEATHER FULL GRAIN OILY PULL-UP; TREAD SURFACE TYPE: POLYURETHANE/VIBRAM RUBBER; SRC SLIP RESISTANCE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; MODEL NO: 43606; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF	100	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

		APPROVAL; WITH PENETRATION-RESISTANT INSERT		
0642362	BOOTS SFTY:NEBULA;10;BROWN;STEEL CAP	BOOTS, SAFETY: STYLE: NEBULA; SIZE: 10; COLOR: BROWN; FASTENING METHOD: 5 PAIR LOOPS; SKI HOOKS CORROSION-RESISTANT GUNMETAL COATING; BRAIDED LACE; TOE CONSTRUCTION TYPE: STEEL CAP; MATERIAL: LEATHER FULL GRAIN OILY PULL-UP; TREAD SURFACE TYPE: POLYURETHANE/VIBRAM RUBBER; SRC SLIP RESISTANCE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; MODEL NO: 43606; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT	100	PAA
0642363	BOOTS SFTY:11;STRD; STL;BROWN;34-232	BOOTS, SAFETY: STYLE: NEBULA; SIZE: 11; COLOR: BROWN; FASTENING METHOD: 5 PAIR LOOPS; SKI HOOKS CORROSION-RESISTANT GUNMETAL COATING; BRAIDED LACE; TOE CONSTRUCTION TYPE: STEEL CAP; MATERIAL: LEATHER FULL GRAIN OILY PULL-UP; TREAD SURFACE TYPE: POLYURETHANE/VIBRAM RUBBER; SRC SLIP RESISTANCE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; MODEL NO: 43606; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED	100	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

## Business Management System

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

		TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT		
0642364	BOOTS SFTY:12;STRD; STL;BROWN;34-232	BOOTS, SAFETY: STYLE: NEBULA; SIZE: 12; COLOR: BROWN; FASTENING METHOD: 5 PAIR LOOPS; SKI HOOKS CORROSION-RESISTANT GUNMETAL COATING; BRAIDED LACE; TOE CONSTRUCTION TYPE: STEEL CAP; MATERIAL: LEATHER FULL GRAIN OILY PULL-UP; TREAD SURFACE TYPE: POLYURETHANE/VIBRAM RUBBER; SRC SLIP RESISTANCE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; MODEL NO: 43606; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT	100	PAA
0757679	GUMBOOTS SFTY:STEEL CAP;3;GREEN	GUMBOOTS, SAFETY: TOE CAP: STEEL CAP; SIZE: 3; STYLE: CHEMICAL PROTECTIVE; COLOR: GREEN; MATERIAL: HAZMAX COMPOUND; TREAD TYPE: VULCANIZED RUBBER; MANUF P/N: B00854	50	PAA
0757680	GUMBOOTS SFTY:STEEL CAP;4;GREEN	GUMBOOTS, SAFETY: TOE CAP: STEEL CAP; SIZE: 4; STYLE: CHEMICAL PROTECTIVE; COLOR: GREEN; MATERIAL: HAZMAX COMPOUND; TREAD TYPE: VULCANIZED RUBBER; MANUF P/N: B00854	50	PAA

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

## Business Management System

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

0757693	GUMBOOTS SFTY:STEEL CAP;15;GREEN	GUMBOOTS, SAFETY: TOE CAP: STEEL CAP; SIZE: 15; STYLE: CHEMICAL PROTECTIVE; COLOR: GREEN; MATERIAL: HAZMAX COMPOUND; TREAD TYPE: VULCANIZED RUBBER; MANUF P/N: B00854	10	PAA
0757694	GUMBOOTS SFTY:STEEL CAP;14;GREEN	GUMBOOTS, SAFETY: TOE CAP: STEEL CAP; SIZE: 14; STYLE: CHEMICAL PROTECTIVE; COLOR: GREEN; MATERIAL: HAZMAX COMPOUND; TREAD TYPE: VULCANIZED RUBBER; MANUF P/N: B00854	10	PAA
0757695	GUMBOOTS SFTY:STEEL CAP;13;GREEN	GUMBOOTS, SAFETY: TOE CAP: STEEL CAP; SIZE: 13; STYLE: CHEMICAL PROTECTIVE; COLOR: GREEN; MATERIAL: HAZMAX COMPOUND; TREAD TYPE: VULCANIZED RUBBER; MANUF P/N: B00854	20	PAA
0757696	GUMBOOTS SFTY:STEEL CAP;12;GREEN	GUMBOOTS, SAFETY: TOE CAP: STEEL CAP; SIZE: 12; STYLE: CHEMICAL PROTECTIVE; COLOR: GREEN; MATERIAL: HAZMAX COMPOUND; TREAD TYPE: VULCANIZED RUBBER; MANUF P/N: B00854	50	PAA
0757697	GUMBOOTS SFTY:STEEL CAP;11;GREEN	GUMBOOTS, SAFETY: TOE CAP: STEEL CAP; SIZE: 11; STYLE: CHEMICAL PROTECTIVE; COLOR: GREEN; MATERIAL: HAZMAX COMPOUND; TREAD TYPE: VULCANIZED RUBBER; MANUF P/N: B00854	100	PAA
0757698	GUMBOOTS SFTY:STEEL CAP;10;GREEN	GUMBOOTS, SAFETY: TOE CAP: STEEL CAP; SIZE: 10; STYLE: CHEMICAL PROTECTIVE; COLOR: GREEN; MATERIAL: HAZMAX COMPOUND; TREAD TYPE: VULCANIZED RUBBER; MANUF P/N: B00854	100	PAA
0757699	GUMBOOTS SFTY:STEEL CAP;9;GREEN	GUMBOOTS, SAFETY: TOE CAP: STEEL CAP; SIZE: 9; STYLE: CHEMICAL PROTECTIVE; COLOR: GREEN;	100	PAA

### Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

## Business Management System

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

		MATERIAL: HAZMAX COMPOUND; TREAD TYPE: VULCANIZED RUBBER; MANUF P/N: B00854		
0757700	GUMBOOTS SFTY:STEEL CAP;8;GREEN	GUMBOOTS, SAFETY: TOE CAP: STEEL CAP; SIZE: 8; STYLE: CHEMICAL PROTECTIVE; COLOR: GREEN; MATERIAL: HAZMAX COMPOUND; TREAD TYPE: VULCANIZED RUBBER; MANUF P/N: B00854	100	PAA
0757701	GUMBOOTS SFTY:STEEL CAP;7;GREEN	GUMBOOTS, SAFETY: TOE CAP: STEEL CAP; SIZE: 7; STYLE: CHEMICAL PROTECTIVE; COLOR: GREEN; MATERIAL: HAZMAX COMPOUND; TREAD TYPE: VULCANIZED RUBBER; MANUF P/N: B00854	100	PAA
0757702	GUMBOOTS SFTY:STEEL CAP;6;GREEN	GUMBOOTS, SAFETY: TOE CAP: STEEL CAP; SIZE: 6; STYLE: CHEMICAL PROTECTIVE; COLOR: GREEN; MATERIAL: HAZMAX COMPOUND; TREAD TYPE: VULCANIZED RUBBER; MANUF P/N: B00854	100	PAA
0757704	GUMBOOTS SFTY:STEEL CAP;5;GREEN	GUMBOOTS, SAFETY: TOE CAP: STEEL CAP; SIZE: 5; STYLE: CHEMICAL PROTECTIVE; COLOR: GREEN; MATERIAL: HAZMAX COMPOUND; TREAD TYPE: VULCANIZED RUBBER; MANUF P/N: B00854	100	PAA
0758993	SHOES SFTY:GENERAL;5;BLACK/BROWN;LACE	SHOES, SAFETY: STYLE: GENERAL; SIZE: 5; COLOR: BLACK/BROWN; FASTENING METHOD: LACE; TOE CONSTRUCTION TYPE: STEEL OR CARBON FIBRE; MATERIAL: FULL GRAIN UPPER LEATHER; TREAD SURFACE TYPE: OIL RESISTANT LEVEL 4; SLIP RESISTANT LEVEL 3; WATER RESISTANT LEVEL 3; HEAT RESISTANT LEVEL 4; ABRASION RESISTANT LEVEL 4; WITH PENETRATION RESISTANT INSERT; SPECIFICATION: SABS SANS 20345 MARK OF APPROVAL; ONLY LOCALLY	3 000	PAA

### Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.



**Business Management System**

Supply Chain Management

Warehouse Scope of Work for PPE Footwear

		PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; BOOTS MUST COMPLY TO ESKOM PPE STANDARD 240-44175132 REV 2		
0760351	BOOTS:FIREFIGHTER;12;BLACK AND YELLOW	BOOTS: TYPE: FIREFIGHTER; SIZE: 12; COLOR: BLACK AND YELLOW; MATERIAL: KEVLAR NOMEX LINING; SOLE MATERIAL: STEEL MID SOLE; OIL RESISTANT AND FLAME RETARDANT; STYLE: ART: 9679; CE/CSA CLASS I/ ANSI AND NFPA CONFORMANCE; FLAME RETARDANT HEAVY-DUTY PULL-ON STRAPS; FLAME RETARDANT UPPER COMPUND; SHIN GUARD; FOAM MIDLEG PADDING FOR EXTRA WARMTH AND LONGER DURATION; LEG LINING WITH KEVLAR NOMEX AND INTERLINING MATERIAL FOR HEAT RESISTANT; STEEL TO CAP CSA GRADE 1; ANSIZ41P101; BS EN 12565:1998; 200 JOULES AND COMPRESSION ENGERGY 15000 NEWTONS; ANGLE PADDING; TOP AND IDE HI-VISIBILITY REFLECTOR; BUILT IN CUSHION SPONGE INSOLE; SOLE ELECTRIC SHOCK RESISTANT; RUST PROOF STEEL SHANK	50	PAA

Compiled By: Linda de Necker

Checked By: Cynthia Tsotetsi

Approved By: Boitshoko Mokolobate

Signature... *L de Necker* .....

Signature... *C Tsotetsi* .....

Signature... *Boitshoko Mokolobate* .....

Date...02/10/2025.....

Date...02/10/2025.....

Date...02/10/2025.....

**Controlled Disclosure**

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.