


ELEVATION OF BRIDGE
SCALE 1:150




PLAN
1:200

STRUCTURAL DRAWINGS FOR TENDER

DRAWING TITLE	Rev.	SHEET	DRAWING NO.
General Arrangement (Sheet 1 of 2)	V1	1 of 12	49217
General Arrangement (Sheet 2 of 2)	V1	2 of 12	49217
Foundation Concrete Details	V1	3 of 12	49217
Pier Concrete Details	V1	4 of 12	49217
Abutment A & Wingwall Details	V1	5 of 12	49217
Abutment B & Wingwall Details	V1	6 of 12	49217
Deck Concrete Details	V1	7 of 12	49217
Construction Sequence Details	V1	8 of 12	49217
Miscellaneous & Curved Handrail Coping Details	V1	9 of 12	49217
F Shape Barrier & Endblock Concrete Details	V1	10 of 12	49217
Lighting Details for Barrier	V1	11 of 12	49217
Pedestrian Steel Fence Details	V1	12 of 12	49217

ISSUED FOR TENDER
DETAILS SUBJECT TO CHANGE



V1	01/06/2023	FOR TENDER PURPOSES
Revision	Date	Description
		NOTE: No construction work to commence until land and servitude acquisitions have been completed.
		Acquisitions completed
Date	Engineer	UNDERGROUND SERVICES CHECKED
		SERVICE DATE SIGNATURE
		S.W. DRAINS
		WATER MAINS
		G.P.O. CABLES
		ELECTRIC CABLES
		S.A.R. CABLES
		E.S.C. CABLES
		ON PIPE LINE

NOTE: Only underground services affected by new construction work are shown. Care must be taken during excavations for road foundations, trenches etc. to avoid damage to underground services such as sewers, drains, cables, water mains and connections. Wherever possible these must be located before work proceeds.


Contract No. 1R- 23757

Project Title
FLOOD DAMAGE
REMEDIAION -
SHALLCROSS/BLUNDELL
ROAD AND BRIDGE
CONSTRUCTION, WARD 63


Drawing Title
GENERAL ARRANGEMENT
(SHEET 1 OF 2)

SCALES	AS SHOWN	Date:	01/06/2023
Designed:	J.HARRIPERSHAD	Checked:	P.G. FENTON
Drawn:	L.SULLAPHEN	Surveyed:	-
Manager:	Structures P.G. Fenton		
Deputy Head :	Roads Provision		


HEAD : ENGINEERING			
Drawing No.	49217	Sheet of	12
		Rev.	V1




PLAN OF FOUNDATION
SCALE 1:150




SECTION A-A
SCALE 1:25



SECTION B-B
SCALE 1:25




SECTION C-C
SCALE 1:50



SECTION D-D
SCALE 1:25


NOTES	
1. MATERIAL STRENGTHS & STRESSES	
CONCRETE:	CLASS:
BLINDING	- C12/15-20
MASS CONCRETE	- C12/15-50
FOUNDATIONS	- C32/40-20
PLUM CONCRETE	- C25/30-20 & C12/15-50
2. CONCRETE FINISHES TO FORMED & UNFORMED SURFACES	
ELEMENT:	FINISH:
FOUNDATIONS	F1 (HIDDEN)
	F3/F2 (EXPOSED)
CHAMFERS TO ALL EXPOSED SHARP CORNERS (INCLUDES FOUNDATIONS)	
	- 25 x 25mm
3. CONCRETE COVER	
CAST AGAINST EARTH & PILES	- 75mm
FOUNDATIONS / PILECAPS (SHUTTERED)	- 50mm
EXPOSED SURFACES (ELSEWHERE)	- 40mm
4. FOUNDING	
PIERS & ABUTMENTS - FOUNDING MATERIAL - MEDIUM TO HARD NATAL GROUP SANDSTONE.	
PAD OR SPREAD FOOTINGS ON ROCK, MASS CONCRETE MAY BE REQUIRED.	
DOWELS INTO ROCK SHALL BE CONFIRMED ON SITE.	
GEOTECHNICAL ENGINEERING SPECIALIST TO INSPECT SITE AND BASES BEFORE ANY BLINDING OR CONCRETE POURED AND BEARING CAPACITY CONFIRMED.	

ISSUED FOR TENDER
DETAILS SUBJECT TO CHANGE




eTHEKWINI MUNICIPALITY
PROCUREMENT AND INFRASTRUCTURE CLUSTER
ENGINEERING UNIT
ROADS PROVISION DEPARTMENT
STRUCTURES BRANCH

REDUCED PLAN USE SCALE BELOW



70mm ON ORIGINAL PLAN

V1	01/06/2023	FOR TENDER PURPOSES
Revision	Date	Description
		NOTE: No construction work to commence until land and servitude acquisitions have been completed
		Acquisitions completed
Date	Engineer	UNDERGROUND SERVICES CHECKED
		SERVICE DATE SIGNATURE
		S.W DRAINS
		SEWERS
		WATER MAINS
		G.P.O CABLES
		ELECTRIC CABLES
		S.A.R. CABLES
		E.S.C. CABLES
		ON PIPE LINE
NOTE: Only underground services affected by new construction work are shown. Care must be taken during excavations for road foundations, trenches etc. to avoid damage to underground services such as sewers, drains, cables, water mains and connections. Whenever possible these must be located before work proceeds.		
Contract No. 1R- 23757		
Project Title FLOOD DAMAGE REMEDIATION - SHALLCROSS/BLUNDELL ROAD AND BRIDGE CONSTRUCTION, WARD 63		
Drawing Title FOUNDATION CONCRETE DETAILS		
SCALES	AS SHOWN	Date: 01/06/2023
Designed: J.HARRIPERSHAD	Checked: P.G. FENTON	
Drawn: L REID	Surveyed: -	
Manager: Structures P.G. Fenton		
Deputy Head : Roads Provision		
HEAD : ENGINEERING		
Drawing No. 49217	Sheet of 12	Rev. V1




FRONT ELEVATION OF ABUTMENT B

SCALE 1:50

NOTE: LEVELS ARE TAKEN AT THE CENTRE LINE OF ABUTMENT


(GEOTECHNICAL ENGINEERING SPECIALIST TO INSPECT SITE AND BASES BEFORE ANY BLINDING OR CONCRETE POURED AND BEARING CAPACITY CONFIRMED).



SECTION A-A

SCALE 1:50

NOTE: APPROACH SLAB OMITTED FOR CLARIFICATION PURPOSES



TYPICAL DRAINAGE DETAIL BEHIND ABUTMENT & WALLS

SCALE 1:10


- LEGEND
- 300mm WIDE FILTER ELEMENTS SECURED TO BACK FACE OF STRUCTURE AT 45° SLOPE.
 - CONCRETE NAILS WITH 25 x 25mm HOOP IRON WASHERS TO SECURE FILTER ELEMENTS TO STRUCTURE AT ± 1 000mm CENTRES.
 - CONCRETE SCREED TO GRADE AND LEVEL OF DRAINAGE PIPES PRIOR TO PLACING OF DRAINAGE PIPES.
 - 65mm dia PERFORATED DRAINAGE PIPES WRAPPED IN GEOTEXTILE. THE GEOTEXTILE SHALL HAVE AN OVERLAP OF NOT LESS THAN 150mm AND BE TIED AT CENTRES NOT GREATER THAN 200mm.
 - 3.15mm dia STAINLESS STEEL WIRE BARRIER.
 - 50mm dia uPVC WEEPHOLES AT CENTRES SHOWN. THE CONTRACTOR SHALL ENSURE THAT THE WEEPHOLES ARE CLEAR AND APPROVED BY THE ENGINEER BEFORE THE FILTER ELEMENTS ARE INSTALLED.
 - TEMPORARY POLYSTYRENE PLUG TO PREVENT INGRESS OF GROUT DURING PLACING OF THE CONCRETE.
 - 200mm WIDE FILTER ELEMENT SECURED TO BACK FACE OF STRUCTURE AT SAME GRADE AS WEEPHOLES
 - EXTENSION OF WEEPHOLES TO EMBANKMENT



ROCK FINISH (WINGWALLS ONLY)




ROCK FINISH DETAIL (WINGWALLS ONLY)



PLAN OF ABUTMENT B

SCALE 1:50




ELEVATION B-B

SCALE 1:50

SECTION D-D

SCALE 1:50



ELEVATION C-C

SCALE 1:50

WATERTIGHT CONCRETE

THE SUBSTRUCTURE CONCRETE SHALL INCORPORATE A CRYSTALLINE PERMEABILITY REDUCING ADDITIVE, SUCH AS PENETRON OR AN ALTERNATIVE TECHNOLOGY WITH PROVEN EFFECTIVENESS AGAINST HYDROSTATIC PRESSURE, APPROVED BY THE ENGINEER. THE INTEGRAL PERMEABILITY REDUCING TECHNOLOGY SHALL HAVE DEMONSTRABLE BENEFITS PROVING SELF HEALING CAPABILITY, IMPROVED CHEMICAL RESISTANCE TO SULPHURIC ACID EXPOSURE, IMPROVED COMPRESSIVE STRENGTH, AND CERTIFIED APPROVAL FOR USE ON STRUCTURES HOLDING POTABLE WATER. THE DOSAGE OF THE INTEGRAL PERMEABILITY REDUCING TECHNOLOGY SHALL BE RECOMMENDED BY THE PRODUCT MANUFACTURER BUT SHALL NOT BE LESS THAN THE FOLLOWING:

WATER-CEMENT RATIO	MINIMUM DOSAGE OF INTEGRAL PERMEABILITY REDUCING TECHNOLOGY (% WEIGHT OF CEMENT)
LESS THAN 0.40	0.8%
0.40 - 0.49	1.0%
0.50 - 0.54	1.5%
0.55 - 0.59	2.0%
0.60 - OR GREATER	3.0%

CONCRETE NOTES

1. MATERIAL STRENGTHS & STRESSES

CONCRETE:	CLASS:
BLINDING	- C12/15-20
MASS CONCRETE	- C12/15-30
FOUNDATIONS	- C32/40-20
ABUTMENT	- C32/40-20 (WATERTIGHT)
WINGWALLS	- C32/40-20

3. CONCRETE FINISHES

FOUNDATIONS	F1 (HIDDEN) & F3/F2 (EXPOSED)
ABUTMENTS BURIED & HIDDEN SURFACES	F1
ABUTMENTS (EXPOSED)	F3 & ROCK FINISH ON WINGWALLS

4. CHAMFERS

ALL SHARP EDGES TO BE CHAMFERED 25mm X 25mm

5. CONCRETE COVER


CAST AGAINST EARTH & PILES	- 75mm
FOUNDATIONS / PILECAPS (SHUTTERED)	- 50mm
EXPOSED SURFACES (ELSEWHERE)	- 40mm

6. CONSTRUCTION

THE ABUTMENTS SHALL ONLY BE BACKFILLED AFTER THE ENTIRE DECK HAS BEEN CAST AND SHALL BE UNDERTAKEN SIMULTANEOUSLY ON BOTH ENDS OF THE BRIDGE SO THAT THE FILL MATERIAL LOAD AGAINST THE TWO ABUTMENTS SHALL BE BALANCED. THE FILL SHALL BE COMPACTED GRADUALLY IN MATCHING LAYERS OF 300mm EACH SIDE

THE ABUTMENTS SHALL BE POURED DURING THE NIGHT OR EARLY MORNINGS (SUBJECT TO RELATIVELY LOW VOLUME CONCRETE POURS) AT LOW TEMPERATURES WHEN THE FORMWORK IS RELATIVELY COOL. DETAILED HOURS OF NIGHT POUR SHALL BE CONFIRMED WITH THE ENGINEER DURING CONSTRUCTION AS THIS DEPENDS ON SEASONAL TEMPERATURES AT THAT SPECIFIC TIME OF THE SEASON AND EXACT LOCATION ETC. THE CONTRACTOR SHALL ENSURE ALL PROVISIONS FOR THE NIGHT POURS OR EARLY MORNINGS ARE IN ORDER.

ISSUED FOR TENDER
DETAILS SUBJECT TO CHANGE



70mm ON ORIGINAL PLAN

V1 01/06/2023 FOR TENDER PURPOSES

Revision	Date	Description
1	01/06/2023	NOTE: No construction work to commence until land and servitude acquisitions have been completed

Acquisitions completed

Date: 01/06/2023

Engineer: N. NINENGELA

SERVICE: UNDERGROUND SERVICES CHECKED

DATE: 01/06/2023

SIGNATURE: P. G. FENTON

S.W. DRAINS

WATER MAINS

G.P.O. CABLES

ELECTRIC CABLES

S.A.R. CABLES

E.S.C. CABLES

ON PIPE LINE

NOTE: Only underground services affected by new construction work are shown. Care must be taken during excavations for road foundations, trenches etc. to avoid damage to underground services such as sewers, drains, cables, water mains and connections. Whenever possible these must be located before work proceeds.

Contract No. 1R- 23757

Project Title

FLOOD DAMAGE

REMEDATION -

SHALLCROSS/BLUNDELL

ROAD AND BRIDGE

CONSTRUCTION, WARD 63

Drawing Title

ABUTMENT B &

WINGWALL DETAILS

SCALES AS SHOWN

Date: 01/06/2023

Designed: J. HARRIPERSHAD

Checked: P. G. FENTON

Drawn: N. NINENGELA

Surveyed: -

Manager: Structures

P. G. Fenton



Deputy Head : Roads Provision

HEAD : ENGINEERING

Drawing No. 49217

Sheet of 12

Rev. V1




LEGEND

1. uPVC HEAVY DUTY PIPE (DIAMETER AND SPACING ON CONSTRUCTION DRAWINGS)

2. uPVC SINGLE SOCKET OR 45° ELBOW AS INDICATED.

3. DRIP RECESS AT OUTLET FORMED USING 22mm THICK MULTI-PLY SHUTTER BOARD.

4. uPVC PIPE EXTENSION GLUED TO SOCKET WITH SOLVENT CEMENT TO A WATERTIGHT CONNECTION AFTER REMOVAL OF DECK SHUTTERS.



**CAST IN-SITU V-DRAIN
SECURING PRECAST COPING
TO TOP OF WINGWALLS**

The diagram illustrates a cross-section of a wing wall. Key dimensions include:

- Total height: 910
- Top horizontal width segments: 375, 250, and 50.
- Vertical distance from top to coping base: 260.
- Coping thickness: 120.
- Height from coping base to bottom of wall: 170.
- Overall height from coping base to bottom of wall: 500.

The coping is shown as a precast element secured to the cast-in-situ wing wall by a V-drain system.

25x25 CHAMFER

POLISHED PRECAST
MULTI-RADIUS COPING DETAIL
- V-DRAIN ATTACHMENT

SCALE 1 : 10

1700-1850

750

500

300

PREFORMED ATTACHMENT
DETAIL FOR PEDESTRIAN
FENCING TO BE CONFIRMED WITH
SUPPLIER

400

250

1000

1300

25
BLINDING


BRIDGE NUMBER EXAMPLE SIZE -
TO BE RECESSED INTO CONCRETE HANDRAIL ENDBLOCK x 2NO.
SCALE 1:5

WIDTH (W) AND SPACING (S) OF NUMBERS								
	L TH NUMBER FOLLOWED BY							
(N-TH)	0	1	2	3	4	5	6	7
0								
1								
2								
3								
4								
5								
6								
7								
8								
9								

1 2 3 4 5 A B C
6 7 8 9 0 D I S

1. GENERAL
 - 1.1 LETTERS AND NUMERALS SHALL BE TYPE 'B' LETTERS TO DIN 1451 PART 2.
 - 1.2 THE DATE ON THE BRIDGE NUMBERS SHALL BE THE YEAR IN WHICH THE BRIDGE WAS COMPLETED.
2. CONSTRUCTION
 - 2.1. THE BRIDGE NUMBER SHALL BE POSITIONED AS SHOWN ON CONSTRUCTION DRAWINGS AND CONFIRMED BY THE ENGINEER (x2NO. 2nd HANDRAIL PANEL ENDBLOCK UPON ENTERING BRIDGE
 - 2.2. THE NUMBER SHALL BE CAST INTO THE CONCRETE

ISSUED FOR TENDER
DETAILS SUBJECT TO CHANGE



Revision	Date	Description
NOTE: No construction work to commence until land and servitude acquisitions have been completed		
Acquisitions completed:		
Date	Engineer	
UNDERGROUND SERVICES CHECKED		
SERVICE	DATE	SIGNATURE
S W DRAINS		
SEWERS		
WATER MAINS		
G.P.O CABLES		
ELECTRIC CABLES		
S.A.R. CABLES		
E.S.C. CABLES		


NOTE: Only underground services affected by new construction work are shown. Care must be taken during excavations for road foundations, trenches etc, to avoid damage to underground services such as sewers, drains, cables, water mains and connections. Wherever possible these must be located before work proceeds.

Project Title

FLOOD DAMAGE
REMEDICATION -
SHALLCROSS/BLUNDELL
ROAD AND BRIDGE
CONSTRUCTION, WARD 63


Drawing Title

MISCELLANEOUS & CURVED HANDRAIL COPING DETAILS



SCALES AS SHOWN	Date: 01-06-2023
Designed: J.HARRIPERSHAD	Checked: P. G. FENTON
Drawn: J.HARRIPERSHAD	Surveyed: -
Manager: Structures P.G. Fenton	
Deputy Head : Roads Provision	

HEAD : ENGINEERING

Drawing No.	49217	Sheet of	09 12	Rev.	V1
-------------	-------	----------	-------	------	----




RADIUS DETAIL
SETTING OUT DETAILS
SCALE 1:5




INSIDE ELEVATION OF BARRIER


SCALE 1:15




INSIDE ELEVATION OF BARRIER ON DECK
SCALE 1:25




SECTION A-A
SCALE 1:10



TYPICAL JOINT DETAIL
SCALE 1:1




DOWEL DETAILS BETWEEN BARRIERS




JOINT DETAILS

SCALE 1:10




BACKING PLATE DETAIL


SCALE 1:5




ANCHOR PLATE DETAIL
SCALE 1:5



ELEVATION B-B
SCALE 1:10




SECTION C-C
SCALE 1:10



SECTION J - J

SCALE 1:5



GUARDRAIL APPROACH & DEPARTURE DETAILS

PLAN OF GUARDRAILS TO BARRIER END BLOCK (x 4NO)

NOTES

1. **GENERAL**
- 1.1 INSPECTION EYES SHALL BE PROVIDED AT DISTANCES NOT EXCEEDING 5m
- 1.2 THE RECESSES FOR EXPANSION JOINT CONSTRUCTION AND THE EXPANSION JOINT COVER PLATES ARE SUBJECT TO THE DETAILS OF THE EXPANSION JOINT SYSTEM FINALLY APPROVED. THE CONTRACTOR SHALL CONFIRM THE DIMENSIONS OF THE RECESSES WITH THE ENGINEER PRIOR TO THE CASTING OF THE BARRIER.
- 1.3 "T = 60mm Min (20mm LEVELLING COURSE + 40mm ASPHALT)"
2. **MATERIAL AND FINISHES**
- 2.1 THE MATERIAL AND WORK SHALL COMPLY WITH THE RELEVANT CLAUSES OF THE BRITISH STANDARD SPECIFICATIONS, THE PROJECT SPECIFICATIONS AND SHALL INCLUDE THE FOLLOWING:
 - 2.1.1 SERVICE DUCTS : 110 Ø 40 PVC NORMAL DUTY (SDR 51) PPES TO SANS 791:2004
 - 2.1.2 CONCRETE CLASS (MPa/mm) : 40/19)
 - 2.1.3 SURFACE FINISHES : (EXPPOSED FACES)
 - 2.1.3.1 CLASS (3a)
 - 2.1.3.2 CLASS (3a)
 - 2.1.4 ALL EXPOSED VERTICAL, SHARP CORNERS SHALL BE CHAMFERED 20 x 20mm AND ROUNDED 20mm HORIZONTALLY EXCEPT WHERE OTHERWISE INDICATED ON DETAIL DRAWING.
 - 2.1.5 THE DRAW WIRE PROVIDED IN THE SERVICE DUCTS SHALL BE IN ONE CONTINUOUS LENGTH, EXTENDING NOT LESS THAN 3m BEYOND THE END OF THE ABUTMENT END BLOCKS. THE DRAW WIRE SHALL BE NOT LESS CORRODABLE NYLON ROPE OR PVC COATED STEEL WIRE OF NOT LESS THAN 500N TENSILE STRENGTH.
- 2.7 **CURING**
PARKING AREAS ARE TO BE CURED BY ANY METHOD AS AGREED WITH THE ENGINEER.
3. **TOLERANCES**
- 3.1 TOLERANCES APPLICABLE TO ERECTION OF UNITS:
 - 3.1.1 DIMENSION FROM SETTING OUT LINE TO FRONT FACES :
10mm Outwards, 0mm Inwards
 - 3.1.2 STEP IN CONCRETE FRONT FACES AT ABUTTING UNITS : 3mm

ISSUED FOR TENDER
DETAILS SUBJECT TO CHANGE

V1	01/06/2023	FOR TENDER PURPOSES

Revision	Date	Description
NOTE: No construction work to commence until land and servitude acquisitions have been completed		
Acquisitions completed:		
Date _____ Engineer _____		
UNDERGROUND SERVICES CHECKED		
SERVICE	DATE	SIGNATURE
S.W. WORKS		
SEWERS		
WATER MAINS		
G.P.O. CABLES		
ELECTRIC CABLES		
S.A.R. CABLES		
E.S.C. CABLES		
ON PIPELINE		

NOTE: Only underground services affected by new construction work are shown. Care must be taken during excavations for road foundations, trenches etc, to avoid damage to underground services such as sewers, drains, cables, water mains and connections. Wherever possible these must be located before work proceeds.

Contract No. 1R-23757

Project Title

FLOOD DAMAGE
REMEDICATION -
SHALLCROSS/BLUNDELL
ROAD AND BRIDGE
CONSTRUCTION, WARD 63

Drawing Title

**'F SHAPED' BARRIER &
END BLOCK
CONCRETE DETAILS**

SCALES AS SHOWN	Date: 01/06/2023


Designed: J. HARRIPERSHAD	Checked: P. G. FENTON
Drawn: J. HARRIPERSHAD L. SULLAPHEN	Surveyed:

Manager: Structures 

Deputy Head : Roads Provision

HEAD : ENGINEERING			
Drawing	10017	Sheet of	Rev.

NOTE:
ALL DIMENSIONS TO BE CHECKED ON SITE BEFORE ANY WORK IS
PUT IN HAND. REFER ANY DISCREPANCIES TO THE ENGINEER.



**eTHEKWINI
MUNICIPALITY**







**PROCUREMENT AND
INFRASTRUCTURE CLUSTER**

ENGINEERING UNIT

ROADS PROVISION DEPARTMENT

STRUCTURES BRANCH

REDUCED PLAN USE SCALE BELOW





NOTES

- GENERAL**
- 1.1 INSPECTION EYES SHALL BE PROVIDED AT DISTANCES NOT EXCEEDING 50m.
- 1.2 THE RECESSES FOR EXPANSION JOINT CONSTRUCTION AND THE EXPANSION JOINT COVER PLATES ARE SUBJECT TO THE DESIGN OF THE EXPANSION JOINT SYSTEM FINALLY APPROVED. THE CONTRACTOR SHALL CONFIRM THE DIMENSIONS OF THE RECESSES WITH THE ENGINEER PRIOR TO THE CASTING OF THE BARRIER.
- MATERIAL AND FINISHES**
- 2.1 THE MATERIAL AND WORK SHALL COMPLY WITH THE RELEVANT CLAUSES OF THE CITY OF DURBAN STANDARD ENGINEERING SPECIFICATIONS, THE PROJECT SPECIFICATIONS AND SHALL INCLUDE THE FOLLOWING.
- 2.2 SERVICE DUCTS : 110 Ø pPVC NORMAL DUTY (SDR 51) PIPES TO SANS 791:2004
- 2.3 CONCRETE CLASS (MPa/mm) : 40/19
- 2.4 REINFORCEMENT: HIGH-YIELD STRESS STEEL 450MPa (GALVANIZED)
- 2.5 SURFACE FINISHES : (EXPOSED FACES)
- CLASS 3a - STEEL SHUTTER FINISH
 - CLASS 3a - STEEL TROWEL FINISH
- 2.6 ALL EXPOSED VERTICAL SHARP CORNERS SHALL BE CHAMFERED 20 x 20mm AND ROUNDED 20mm HORIZONTALLY EXCEPT WHERE OTHERWISE INDICATED ON DETAIL DRAWING.
- 2.7 THE DRAW WIRE PROVIDED IN THE SERVICE DUCTS SHALL BE IN ONE CONTINUOUS LENGTH. EXTENDING NOT LESS THAN 100mm BEYOND THE END FACE OF THE ABUTMENT END BLOCKS. THE DRAW WIRE SHALL BE NON CORRODABLE NYLON ROPE OR PVC COATED STEEL WIRE OF NOT LESS THAN 5000N TENSILE STRENGTH.


NOTES

1. ENTIRE BOLT GROUP ASSEMBLY TO BE HOT-DIP GALVANISED.
2. BOLTS TO BE GRADE 8.8.
3. LIGHT MASTS TO BE A MAXIMUM OF 10m ABOVE THE DECK LEVEL.

ISSUED FOR TENDER
DETAILS SUBJECT TO CHANGE


V1	01/06/2023	FOR TENDER PURPOSES	
Revision	Date	Description	
NOTE: No construction work to commence until land and servitude acquisitions have been completed			
Acquisitions completed:			
Date	Engineer		
UNDERGROUND SERVICES CHECKED			
SERVICE	DATE	SIGNATURE	
S.W DRAINS			
SEWERS			
WATER MAINS			
G.P.O CABLES			
ELECTRIC CABLES			
S.A.R. CABLES			
E.S.C. CABLES			
OIL PIPE LINE			
NOTE: Only underground services affected by new construction work are shown. Care must be taken during excavation for road foundations, trenches etc. to avoid damage to underground services such as sewers, drains, cables, water mains and connections. Wherever possible these must be located before work proceeds.			
Contract No.		1R- 23757	
Project Title			
<p style="text-align: center;">FLOOD DAMAGE REMEDIATION - SHALLCROSS/BLUNDELL ROAD AND BRIDGE CONSTRUCTION, WARD 63</p>			
Drawing Title			
<p style="text-align: center;">LIGHTING DETAILS FOR BARRIER</p>			
SCALES	AS SHOWN	Date:	01/06/2023
Designed:	J. HARRISPERSHAD	Checked:	P. G. FENTON
Drawn:	J. HARRISPERSHAD	Surveyed:	
Manager: Structures			
Deputy Head : Roads Provision			
HEAD : ENGINEERING			

NOTE:
ALL DIMENSIONS TO BE CHECKED ON SITE BEFORE ANY WORK IS
PUT IN HAND. REFER ANY DISCREPANCIES TO THE ENGINEER.




**eTHEKWINI
MUNICIPALITY**
PROCUREMENT AND
INFRASTRUCTURE CLUSTER
ENGINEERING UNIT
ROADS PROVISION DEPARTMENT
STRUCTURES BRANCH


REDUCED PLAN USE SCALE BELOW




70mm ON ORIGINAL PLAN




**ELEVATION OF PEDESTRIAN
SCREEN FENCING ON BRIDGE**
SCALE 1:150




TYPICAL ELEVATION OF PEDESTRIAN SCREEN FENCING
SCALE 1:50



**FENCE SUPPORTS MOUNTED ON
DECK COPING**
SCALE 1:10



**FENCE SUPPORTS MOUNTED ON
WINGWALL COPING**
SCALE 1:10



**FENCE SUPPORTS MOUNTED ON
CONCRETE PLINTH**
SCALE 1:10

MESH SCREEN FENCE AND STRUCTURAL STEEL SUPPORTS

THE CONTRACTOR SHALL PROVIDE A DESIGN FOR A STRUCTURAL STEEL AND WIRE MESH PROTECTION SCREEN.

THE DESIGN, FABRICATION AND INSTALLATION OF ALL WORK SHALL COMPLY WITH SANS 10162-1 AND THE REQUIREMENTS OF THE STANDARD SPECIFICATIONS PART C13.9 AND C13.10.

SHOP DETAILS SHALL BE APPROVED BY THE ENGINEER PRIOR TO THE FABRICATION OF ANY ITEMS.

THE WIRE USED IN THE MESH SCREEN SYSTEM IS TO HAVE A MINIMUM DIAMETER OF 3.96MM (HORIZONTAL AND VERTICAL WIRES). THE MESH PANELS SHALL BE MANUFACTURED FROM HIGH TENSILE GALFAN GLASS A COATED WIRE IN ACCORDANCE WITH THE STANDARDS IN SANS 10244-2:2004 WITH THE MINIMUM TENSILE STRENGTH OF 400MPa. CENTRE-TO-CENTRE WIRE APERTURE SPACING SHALL BE A MAXIMUM OF 76.2MM X 50MM WITH A TOLERANCE IN CONSTRUCTION OF ±2MM. THE TOTAL WIRE DIAMETER (INCLUDING THE PVC COATING SYSTEM) SHALL BE NOT LESS THAN 4.6MM, AND NOT MORE THAN 4.6MM. THE UV RESISTANCE OF THE PVC COATING SYSTEM SHALL COMPLY WITH THE STANDARDS OF TESTING AS DESCRIBED IN ASTM G 53 AND ASTM G 154. THE PVC COATING SHALL COMPLY WITH EN 10245-1. A SAMPLE SHALL BE PROVIDED TO THE ENGINEER FOR APPROVAL PRIOR TO FABRICATION.

THE STEEL DETAILS OF A PROVEN ATTACHMENT SYSTEM FOR FIXING THE MESH TO THE SUPPORTS SHALL BE PROVIDED BY THE CONTRACTOR. THE DETAIL SHALL BE TAMPER-PROOF AND ABLE TO DISTRIBUTE A 0.5kN/m LOAD APPLIED TO THE MESH SURFACE TO THE FRAME SUPPORT POINTS. THE CORROSION PROTECTION SYSTEM FOR THE FIXING WILL BE EQUIVALENT TO THE MESH.

THE FENCING SUPPLIER SHALL BE AN ISO ACCREDITED SUPPLIER AND SHALL MEET THE STANDARDS OF ISO 9001:2000.

**ISSUED FOR TENDER
DETAILS SUBJECT TO CHANGE**

Revision	Date	Description
----------	------	-------------

NOTE: No construction work to commence until land and servitude acquisitions have been completed.

Acquisitions completed.

Date: Engineer: UNDERGROUND SERVICES CHECKED

SERVICE	DATE	SIGNATURE
S.W DRAINS		
SEWERS		
WATER MAINS		
G.P.O CABLES		
ELECTRIC CABLES		
S.A.R. CABLES		
E.S.C. CABLES		
ON PIPE LINE		

NOTE: Only underground services affected by new construction work are shown. Care must be taken during excavations for road foundations, trenches etc. to avoid damage to underground services such as sewers, drains, cables, water mains and connections. Whenever possible these must be located before work proceeds.

Contract No. **1R- 23757**

Project Title
**FLOOD DAMAGE
REMEDATION -
SHALLCROSS/BLUNDELL
ROAD AND BRIDGE
CONSTRUCTION, WARD 63**

Drawing Title

**PEDESTRIAN
STEEL FENCE
DETAILS**

SCALES AS SHOWN Date: 01/06/2023

Designed: J.HARRIPERSHAD Checked: P.G. FENTON

Drawn: L.SULLAPHEN Surveyed: -

Manager: Structures
P.G. Fenton

Deputy Head : Roads Provision

HEAD : ENGINEERING

Drawing No. 49217 Sheet 12 of 12 Rev. V1