

Business Management System

Supply Chain Management

Warehouse

Scope of work for Plumbing

Short Text	Long Text	Quantity Requested	Unit of Measure
LOCK:ENTRANCE	LOCK: ENTRANCE	833	EA
LOCK:GOWER 3 LEVER;153 X 41 MM;CR SATIN	LOCK: TYPE: GOWER 3 LEVER, DIMENSIONS: 153 X 41 MM, MATERIAL: CR SATIN, COLOR: SILVER, SPECIFICATION: SABS APPROVED; MANUF P/N: C26822452CH	1667	EA
LOCK:UNION 3 LEVER;SS;SILVER	LOCK: UNION 3 LEVER, WD 75 X LG 100 X THK 14 MM, SS, COLOR: SILVER, SPECIFICATION: SABS APPROVED; MANUF P/N: 2252-76SS	1250	EA
LOCK MRTS:2 LEVER	LOCK MRTS:2 LEVER	1250	EA
ROLLER PAINT:EEZYPILE;WD 100 MM	ROLLER, PAINT: TYPE: EEZYPILE; WIDTH: 100 MM; HANDLE MATERIAL: STEEL AND PLASTIC; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE)	500	EA
ROLLER PAINT:EEZYPILE;WD 225 MM	ROLLER, PAINT: TYPE: EEZYPILE, WIDTH: 225 MM, HANDLE MATERIAL: STEEL AND PLASTIC; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE)	583	EA

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

Business Management System

Supply Chain Management

Warehouse

Scope of Work for Plumbing

ROLLER PAINT:MOHAIR;WD 225 MM	ROLLER, PAINT: TYPE: MOHAIR, WIDTH: 225 MM, HANDLE MATERIAL: STEEL AND PLASTIC; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE)	667	EA
ROLLER PAINT:SHEEP SKIN;WD 225 MM	ROLLER, PAINT: TYPE: SHEEP SKIN; WIDTH: 225 MM; HANDLE MATERIAL: STEEL AND PLASTIC; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE)	1000	EA
ROLLER:PAINT REFILL;MOHAIR 2	ROLLER: PAINT REFILL, MOHAIR 2	500	EA
SADDLE PIPE:25 MM;GALV;WD 22 MM;LG 89 MM	SADDLE, PIPE: NOMINAL SIZE: 25 MM, MATERIAL: GALV, WIDTH: 22 MM, LENGTH: 89 MM; C/W BAR	417	EA
LATCH DOOR:NIGHT		1167	EA
HOLDER:TOILET ROLL;SS 430		1667	EA

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

Business Management System

Supply Chain Management

Warehouse

Scope of Work for Plumbing

SEAT TOLT:ADULT;WHITE;THERMOPLASTIC	SEAT, TOILET: TYPE: ADULT; COLOR: WHITE; MATERIAL: THERMOPLASTIC; INSIDE DIAMETER: 290 MM; SHAPE: OVAL; SPECIAL FEATURES: ADJUSTABLE; MOUNTING METHOD: ADJUSTABLE HINGES & SCREWS; STANDARD: ISO9001; REFERENCE NO: LUX2000	1250	EA
TAP WTR:EXTENDED BIP;CR PLTD;15 MM	SADDLE: TYPE: SUPPORT, DIMENSIONS: 20 MM, MATERIAL: PVC; CONTACT PERSON: LEON PRUIS; CONTACT NUMBER 011-629-8245	1250	EA
TAP WTR:BIP;CR PLTD;15 MM	TAP, WATER: TYPE: BIP, MATERIAL: CR PLTD, INLET CONNECTION: 15 MM; MANUF P/N: 3306SB-15	1667	EA
TAP WTR:PILLAR;CR PLTD;15 MM	TAP, WATER: PILLAR, CR PLTD, INLET CONNECTION: 15 MM; MANUF P/N: 3311SB-15	833	EA
TAP WTR:BASIN MIXER;SS; CHROME;15 MM	TAP, WATER: TYPE: BASIN MIXER, MATERIAL: SS; CHROME, INLET CONNECTION: 15 MM; MANUF P/N: 33925T; SINGLE HOLE	1250	EA
TAP WTR:BATH DIVERTED MIXER;SS; CHROME	TAP, WATER: TYPE: BATH DIVERTED MIXER, MATERIAL: SS; CHROME, INLET CONNECTION: 15 MM, OUTLET CONNECTION: CONCEALED; MANUF P/N: 3351ST-15-HQ; WALL TYPE	1250	EA

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

Business Management System

Supply Chain Management

Warehouse

Scope of Work for Plumbing

TAP WTR:BATH MIXER;INTERNALS BRS CR PLTD	TAP, WATER: TYPE: BATH MIXER, MATERIAL: INTERNALS BRS CR PLTD, INLET CONNECTION: 1/2 IN, OUTLET CONNECTION: PLAIN; SUPPLIED COMPLETE WITH SHOWER KIT AND INSTALLATION INSTRUCTION	1000	EA
TAP WTR:GARDEN;BRS;3/4 IN;THREADED	TAP, WATER: TYPE: GARDEN, MATERIAL: BRS, INLET CONNECTION: 3/4 IN, OUTLET CONNECTION: THREADED	1250	EA
TAP WTR:KITCHEN MIXER;CR PLTD;PLAIN	TAP, WATER: TYPE: KITCHEN MIXER, MATERIAL: CR PLTD, INLET CONNECTION: MALE 1/2 IN, OUTLET CONNECTION: PLAIN	1250	EA
TAP WTR:MIXER SWIREL OPERATED;SS; CHROME	TAP, WATER: TYPE: MIXER SWIREL OPERATED, MATERIAL: SS; CHROME, INLET CONNECTION: 15 MM; MANUF P/N: 296CA; SINGLE HOLE	1250	EA
TAP WTR:SINK DIVERTED MIXER;SS; CHROME	TAP, WATER: TYPE: SINK DIVERTED MIXER, MATERIAL: SS; CHROME, INLET CONNECTION: 15 MM, OUTLET CONNECTION: CONCEALED; MANUF P/N: 3366/041/10ST; WALL TYPE	1667	EA
TAP,WATER:106CA-15;BIP;CHROME PLATED	TAP, WATER: BIP, CR PLTD, INLET CONNECTION: 15 MM; MANUF P/N: 106CA-15	1667	EA

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

Business Management System

Supply Chain Management

Warehouse

Scope of Work for Plumbing

VLV FLUSH:EXPOSED;JUNIOR;BALL O STOP	VALVE, FLUSH: TYPE: EXPOSED, SIZE: JUNIOR, STYLE: BALL O STOP, PRESSURE RATING: 600 KPA, FLOW RATE: 65 L+RS/MIN, CONNECTION SIZE: 3/4, CONNECTION TYPE: FLANGE, OPERATED: MANUAL, BODY MATERIAL: BRUHD CROME, TRIM: INTEGRAL VACUUM BREAKER, DIAPHRAGM, APPLICATION: TOILET, SPECIFICATION: SANS1240; MANUF P/N: FJ2000	1667	EA
VLV FLUSH:EXPOSED;JUNIOR;BALL O STOP	VALVE, FLUSH: TYPE: EXPOSED, SIZE: JUNIOR, STYLE: BALL O STOP, PRESSURE RATING: 600 KPA, FLOW RATE: 65 L+RS/MIN, CONNECTION SIZE: 3/4, CONNECTION TYPE: FLANGE, OPERATED: MANUAL, BODY MATERIAL: BRUSHED CROME, APPLICATION: URINAL, SPECIFICATION: SABS1240; MANUF P/N: FJ6.001	1667	EA
KIT:PUSHBUTTON ASS	KIT: COMPRISING: PUSHBUTTON ASS; MANUF P/N: FJ8-21	1667	EA
KIT:PISTON REPAIR;URINALS;C-FJ8.11	KIT: TYPE: PISTON REPAIR, APPLICATION: URINALS; REFERENCE NO: C-FJ8.11; FLUSHMASTER JUNIOR	1667	EA
KIT:PUSH BUTTON ASSY;UNIRALS;C-FJ8.20	KIT: TYPE: PUSH BUTTON ASSY, APPLICATION: UNIRALS; REFERENCE NO: C-FJ8.20; FLUSHMASTER JUNIOR	11000	EA

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

Business Management System

Supply Chain Management

Warehouse

Scope of Work for Plumbing

TAPE THRD:SEAL;WD 12 MM;PTFE;WHITE	TAPE, THREAD: TYPE: SEAL, WIDTH: 12 MM, MATERIAL: PTFE, COLOR: WHITE, GRADE: DENSITY 0.25 GCM3; NOTE: MUST BE ISO 9001 CERTIFIED	1167	EA
TAP WTR:PILLER;1/2 IN	TAP, WATER: TYPE: PILLER, INLET CONNECTION: 1/2 IN; BATH	1667	EA
ADAPTOR:CONEX FEMALE;BRASS;15 MM	ADAPTOR: TYPE: CONEX FEMALE, MATERIAL: BRASS, SIZE: 15 MM; MEDUPI CONTACT PERSON: RALPH SCHOLTZ TEL NO 082 603 2560	1667	EA
ADAPTOR:CONEX FEMALE;BRASS;22 MM	ADAPTOR: TYPE: CONEX FEMALE, MATERIAL: BRASS, SIZE: 22 MM	1667	EA
ADAPTOR:CONEX MALE;BRASS;15 MM	ADAPTOR: TYPE: CONEX MALE, MATERIAL: BRASS, SIZE: 15 MM	3333	EA
ADAPTOR:WELD ON FEMALE;COPPER;15 MM	ADAPTOR: TYPE: WELD ON FEMALE, MATERIAL: COPPER, SIZE: 15 MM	2500	EA
ADAPTOR:WELD ON FEMALE;COPPER;22 MM	ADAPTOR: TYPE: WELD ON FEMALE, MATERIAL: COPPER, SIZE: 22 MM	3333	EA
ADAPTOR:WELD ON MALE;COPPER;15 MM	ADAPTOR: TYPE: WELD ON MALE, MATERIAL: COPPER, SIZE: 15 MM	2500	EA
ADAPTOR:WELD ON MALE;COPPER;22 MM	ADAPTOR: TYPE: WELD ON MALE, MATERIAL: COPPER, SIZE: 22 MM	2500	EA
ARM:15MM SHOWER ARM;WD 15 X LG 150 MM;SS	ARM: TYPE: 15MM SHOWER ARM, DIMENSIONS: WD 15 X LG 150 MM, MATERIAL: SS	2500	EA

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

Business Management System

Supply Chain Management

Warehouse

Scope of Work for Plumbing

ARM:COBRA AL FP 23 D/A;WD 15 X LG 150 MM	ARM: TYPE: COBRA AL FP 23 D/A, DIMENSIONS: WD 15 X LG 150 MM, MATERIAL: SS	1667	EA
BALL VLV:MALE 15 MM;200 MM	BALL, VALVE: VALVE SIZE: MALE 15 MM, DIAMETER: 200 MM, MATERIAL: PLASTIC, ORANGE; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE)	1250	EA
BREAKER VACM:COMPLETE FITTING; PLUMBING	BREAKER, VACUUM: TYPE: COMPLETE FITTING; PLUMBING, VALVE SIZE: 15/22 MM, CONNECTION TYPE: FEMALE, PRESSURE RATING: 4 BAR, BODY MATERIAL: BRASS	1250	EA
BUSH:PLUMBING;ID 15 MM;OD 16 MM;LG 50 MM	BUSH: TYPE: PLUMBING, INSIDE DIAMETER: 15 MM, OUTSIDE DIAMETER: 16 MM, LENGTH: 50 MM, MATERIAL: GALVANIZED	2500	EA
CAP:END;20 MM;GALVANIZED	CAP: TYPE: END, DIMENSIONS: 20 MM, MATERIAL: GALVANIZED	2500	EA
CLAMP HOSE:ADJUSTABLE;ID 14-27 MM;SS	CLAMP, HOSE: TYPE: ADJUSTABLE, INSIDE DIAMETER: 14-27 MM, WIDTH: 12 MM, MATERIAL: SS	2500	EA
CLAMP HOSE:ADJUSTABLE;ID 19-44 MM;SS	CLAMP, HOSE: TYPE: ADJUSTABLE, INSIDE DIAMETER: 19-44 MM, WIDTH: 12 MM, MATERIAL: SS	2500	EA

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

Business Management System

Supply Chain Management

Warehouse

Scope of Work for Plumbing

CLAMP HOSE:ADJUSTABLE;ID 60-80 MM;SS	CLAMP, HOSE: TYPE: ADJUSTABLE, INSIDE DIAMETER: 60-80 MM, WIDTH: 12 MM, MATERIAL: SS	2500	EA
COMPRESSOR:1/4 HP TGH1374YFS;FRIDGE	COMPRESSOR: TYPE: 1/4 HP TGH1374YFS;FRIDGE; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE)	3333	EA
CONNECTOR:BRAIDED; FLEXI;15 X 15 MM	CONNECTOR: TYPE: BRAIDED; FLEXI, DIMENSIONS: 15 X 15 MM, MATERIAL: FLEXI STEEL WIRE WITH SS THREAD ENDS	2500	EA
CONNECTOR:PAN; PLUMBING;PVC;SPEC SG 40	CONNECTOR: TYPE: PAN; PLUMBING, DIMENSIONS: 147 X 116 X 110 MM, MATERIAL: PVC, SPECIFICATION: SG 40	10000	EA
COUPLER:CONEX STRAIGHT;15 MM;SCREW ON	COUPLER: TYPE: CONEX STRAIGHT, SIZE: 15 MM, CONNECTION: SCREW ON, MATERIAL: BRASS; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE)	5000	EA

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

Business Management System

Supply Chain Management

Warehouse

Scope of Work for Plumbing

COUPLER:CONEX STRAIGHT;22 MM;SCREW ON	COUPLER: TYPE: CONEX STRAIGHT, SIZE: 22 MM, CONNECTION: SCREW ON, MATERIAL: BRASS; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE)	5000	EA
COUPLER:PVC STRAIGHT;50 MM;GLUE ON;PVC	COUPLER: TYPE: PVC STRAIGHT, SIZE: 50 MM, CONNECTION: GLUE ON, MATERIAL: PVC; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE)	5000	EA
COUPLER:STRAIGHT;15 MM;WELD ON;COPPER	COUPLER: TYPE: STRAIGHT, SIZE: 15 MM, CONNECTION: WELD ON, MATERIAL: COPPER; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE)	5000	EA
COUPLER:STRAIGHT;22 MM;WELD ON;COPPER	COUPLER: TYPE: STRAIGHT, SIZE: 22 MM, CONNECTION: WELD ON, MATERIAL: COPPER; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE)	4167	EA

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

Business Management System

Supply Chain Management

Warehouse

Scope of Work for Plumbing

DOOR:SHOWER, ADJUSTABLE	DOOR: TYPE: SHOWER, ADJUSTABLE, DIMENSIONS: WD 900MM X HT 1.85M, MATERIAL: AL FRAME, GLASS DOOR	4167	EA
DOOR:SHOWER, EXPANDABLE	DOOR: TYPE: SHOWER, EXPANDABLE, DIMENSIONS: WD 900MM X HT 1.85M, MATERIAL: AL FRAME, GLASS DOOR	4167	EA
ELBOW:CONEX;15 MM;SCREW ON;BRASS;90 DEG	ELBOW: TYPE: CONEX, SIZE: 15 MM, CONNECTION: SCREW ON, MATERIAL: BRASS, DEGREE: 90 DEG	4167	EA
ELBOW:CONEX;22 MM;SCREW ON;BRASS;90 DEG	ELBOW: TYPE: CONEX, SIZE: 22 MM, CONNECTION: SCREW ON, MATERIAL: BRASS, DEGREE: 90 DEG	3333	EA
ELBOW:PLUMBING;15 MM;GLUE ON;PVC;90 DEG	ELBOW: TYPE: PLUMBING, SIZE: 15 MM, CONNECTION: GLUE ON, MATERIAL: PVC, DEGREE: 90 DEG	3333	EA
ELBOW:PLUMBING;20 MM;GLUE ON;PVC;90 DEG	ELBOW: TYPE: PLUMBING, SIZE: 20 MM, CONNECTION: GLUE ON, MATERIAL: PVC, DEGREE: 90 DEG	3333	EA
ELBOW:PLUMBING;22 MM;MALE SCREW IN	ELBOW: TYPE: PLUMBING, SIZE: 22 MM, CONNECTION: MALE SCREW IN, MATERIAL: GALVANIZED, DEGREE: 90 DEG	3333	EA
ELBOW:PLUMBING;22 MM;WELD ON;COPPER	ELBOW: TYPE: PLUMBING, SIZE: 22 MM, CONNECTION: WELD ON, MATERIAL: COPPER, DEGREE: 90 DEG	5000	EA

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

Business Management System

Supply Chain Management

Warehouse

Scope of Work for Plumbing

ELBOW:PLUMBING;22 TO 15 MM;WELD ON	ELBOW: TYPE: PLUMBING, SIZE: 22 TO 15 MM, CONNECTION: WELD ON, MATERIAL: COPPER, DEGREE: 90 DEG	2500	EA
ELBOW:PLUMBING;50 MM;COUPLER;PVC	ELBOW: TYPE: PLUMBING, SIZE: 50 MM, CONNECTION: COUPLER, MATERIAL: PVC, DEGREE: 87.5 DEG; INCLUDES INSPECTION EYE	2500	EA
ELBOW:WALL PLATE;22 MM;BRASS;90 DEG	ELBOW: TYPE: WALL PLATE, SIZE: 22 MM, CONNECTION: SCREW ON AND FEMALE SCREW IN, MATERIAL: BRASS, DEGREE: 90 DEG	2500	EA
END:CAP;15 MM;COPPER	END: TYPE: CAP, DIMENSIONS: 15 MM, MATERIAL: COPPER	2500	EA
EYE:INSPECTION; PLUMBING;110 MM;PVC	EYE: TYPE: INSPECTION; PLUMBING, SIZE: 110 MM, MATERIAL: PVC; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE)	2500	EA
EYE:RODDING; PLUMBING;110 MM	EYE: TYPE: RODDING; PLUMBING; SIZE: 110 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE)	2500	EA

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

Business Management System

Supply Chain Management

Warehouse

Scope of Work for Plumbing

FITTING:STRAP ON BOSS;50 MM;PVC	FITTING: TYPE: STRAP ON BOSS, SIZE: 50 MM, MATERIAL: PVC	2500	EA
GASKET:FLANGE;RADIUS 70 X THK 6 MM	GASKET: TYPE: FLANGE, DIMENSIONS: RADIUS 70 X THK 6 MM, MATERIAL: RUBBER, HOLES: 6 X DIA 11MM	2500	EA
HANDLE:ZINK MIXER;15 MM;PLASTIC (HARD)	HANDLE: TYPE: ZINK MIXER, DIMENSIONS: 15 MM, MATERIAL: PLASTIC (HARD); VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE)	1667	EA
HOLDER:HOLDER BAT; PLUMBING;15 MM	HOLDER: TYPE: HOLDER BAT; PLUMBING, DIMENSIONS: 15 MM, MATERIAL: PVC PLASTIC/STL; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE)	833	EA
HOLDER:HOLDER BAT; PLUMBING;22 MM	HOLDER: TYPE: HOLDER BAT; PLUMBING, DIMENSIONS: 22 MM, MATERIAL: PVC PLASTIC/STL; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE)	833	EA

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

Business Management System

Supply Chain Management

Warehouse

Scope of Work for Plumbing

HOLDER:SOAP;WD 60 X LG 100 MM;STL	HOLDER: TYPE: SOAP, DIMENSIONS: WD 60 X LG 100 MM, MATERIAL: STL; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE)	1667	EA
HOSE:HAND SHOWER;ID 6-8 MM;OD 15 MM	HOSE: TYPE: HAND SHOWER, INSIDE DIAMETER: 6-8 MM, OUTSIDE DIAMETER: 15 MM, LENGTH: 1.25 M, MATERIAL: FLEXI STEEL	1250	EA
JUNCTION:ACCESS Y-JUNCTION;110 MM	JUNCTION: TYPE: ACCESS Y-JUNCTION, RATING: 110 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE)	833	EA
NIPPLE:PLUMBING;ID 15 MM;LG 25 MM	NIPPLE: TYPE: PLUMBING, INSIDE DIAMETER: 15 MM, LENGTH: 25 MM, MATERIAL: GALVANIZED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE)	833	EA
PIPE NON MTLC:110 MM;PVC;LG 6 M;2.5 MM	PIPE, NON METALLIC: NOMINAL PIPE SIZE DESIGNATION: 110 MM, MATERIAL: PVC, LENGTH: 6 M, WALL THICKNESS: 2.5 MM, TYPE: WASTE	833	M

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

Business Management System

Supply Chain Management

Warehouse

Scope of Work for Plumbing

PIPE NON MTLC:15 MM;PLASTIC HD;LG 50 M	PIPE, NON METALLIC: NOMINAL PIPE SIZE DESIGNATION: 15 MM, MATERIAL: PLASTIC HD, LENGTH: 50 M, WALL THICKNESS: 2 MM	1667	M
PIPE NON MTLC:15 MM;POLYPROPYLENE;TUBE	PIPE, NON METALLIC: NOMINAL PIPE SIZE DESIGNATION: 15 MM, MATERIAL: POLYPROPYLENE, LENGTH: 100 M, WALL THICKNESS: 2.1 MM, CONSTRUCTION: TUBE, TYPE: POLYCOP	1667	M
PIPE:ID 15 MM;LG 6 M;COPPER	PIPE: INSIDE DIAMETER: 15 MM, LENGTH: 6 M, MATERIAL: COPPER	1667	EA
PIPE:ID 22 MM;LG 6 M;COPPER	PIPE: INSIDE DIAMETER: 22 MM, LENGTH: 6 M, MATERIAL: COPPER	833	EA
PLUG:HOLLOW;15 MM;GALVANIZED;PLUMBING	PLUG: TYPE: HOLLOW, SIZE: 15 MM, MATERIAL: GALVANIZED, APPLICATION: PLUMBING	833	EA
PLUG:HOLLOW;22 MM;GALVANIZED;PLUMBING	PLUG: TYPE: HOLLOW, SIZE: 22 MM, MATERIAL: GALVANIZED, APPLICATION: PLUMBING	1667	EA
REDUCER:CONEX;22 TO 15 MM;SCREW IN;BRASS	REDUCER: TYPE: CONEX, NOMINAL SIZE: 22 TO 15 MM, CONNECTION: SCREW IN, MATERIAL: BRASS; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE)	1667	EA

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

Business Management System

Supply Chain Management

Warehouse

Scope of Work for Plumbing

REDUCER:ECCENTRIC;50 TO 40 MM;GLUE ON	REDUCER: TYPE: ECCENTRIC, NOMINAL SIZE: 50 TO 40 MM, CONNECTION: GLUE ON, MATERIAL: PVC; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE)	1667	EA
REDUCER:PIPE;22 TO 15 MM;WELD ON;BRASS	REDUCER: TYPE: PIPE, NOMINAL SIZE: 22 TO 15 MM, CONNECTION: WELD ON, MATERIAL: BRASS; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE)	1667	EA
REDUCER:PLUMBING;35 TO 15 MM;WELD ON	REDUCER: TYPE: PLUMBING, NOMINAL SIZE: 35 TO 15 MM, CONNECTION: WELD ON, MATERIAL: COPPER; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE)	1667	EA
RING:COMPRESSION;ID 22 MM;OD 23.5 MM	RING: TYPE: COMPRESSION, INSIDE DIAMETER: 22 MM, OUTSIDE DIAMETER: 23.5 MM, WIDTH: 6 MM, MATERIAL: COPPER	1667	EA
RING:PLUMBING;ID 19 MM;OD 21 MM;WD 8 MM	RING: TYPE: PLUMBING, INSIDE DIAMETER: 19 MM, OUTSIDE DIAMETER: 21 MM, WIDTH: 8 MM, MATERIAL: BRASS	1667	EA

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

Business Management System

Supply Chain Management

Warehouse

Scope of Work for Plumbing

RING:PLUMBING;ID 26 MM;OD 28 MM;WD 8 MM	RING: TYPE: PLUMBING, INSIDE DIAMETER: 26 MM, OUTSIDE DIAMETER: 28 MM, WIDTH: 8 MM, MATERIAL: BRASS	3333	EA
SADDLE PIPE:15 MM;COPPER	SADDLE, PIPE: NOMINAL SIZE: 15 MM, MATERIAL: COPPER	3333	EA
SADDLE PIPE:22 MM;COPPER	SADDLE, PIPE: NOMINAL SIZE: 22 MM, MATERIAL: COPPER	1667	EA
SEAL:PAN RING;110 MM;WAX	SEAL: TYPE: PAN RING, DIMENSIONS: 110 MM, MATERIAL: WAX	1667	EA
SEALANT:FIX-ALL;PLASTIC ROUND TUBE	SEALANT: TYPE: FIX-ALL, CONTAINER: PLASTIC ROUND TUBE, MATERIAL: SILICON, COLOR: WHITE	1667	EA
SEALANT:MARINE;PLASTIC ROUND TUBE;CLEAR	SEALANT: TYPE: MARINE, CONTAINER: PLASTIC ROUND TUBE, MATERIAL: SILICON, WATERPROOF, COLOR: CLEAR	1667	EA
SEAT TOLT:PLUMBING;WHITE;WOOD;OVAL	SEAT, TOILET: TYPE: PLUMBING, COLOR: WHITE, MATERIAL: WOOD, SHAPE: OVAL	1667	EA
SHOWER:HAND;LG 150MM; HEAD 50MM	SHOWER: TYPE: HAND, DIMENSIONS: LG 150MM; HEAD 50MM	1667	EA
SHOWER:TRAY;SQ 800 X HT 120 MM	SHOWER: TYPE: TRAY, DIMENSIONS: SQ 800 X HT 120 MM	1667	EA

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

Business Management System

Supply Chain Management

Warehouse

Scope of Work for Plumbing

SHWR HD:PLUMBING;15 MM;NON ADJUSTABLE	SHOWER HEAD: TYPE: PLUMBING, INDUSTRIAL PIPE FITTING SIZE DESIGNATION: 15 MM, SPRAY TYPE: NON ADJUSTABLE, MOUNTING METHOD: SCREW IN, MATERIAL: SS	1667	EA
SOCKET:SINGLE; MALE ADAPTOR;50 MM;PVC	SOCKET: TYPE: SINGLE; MALE ADAPTOR, SIZE: 50 MM, MATERIAL: PVC	1250	EA
STOP:CONEX END;WD 25 X LG 22 MM;PVC	STOP: TYPE: CONEX END; DIMENSIONS: WD 25 X LG 22 MM; MATERIAL: PVC; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE)	1250	EA
STOP:CONEX END;WD 32 X LG 20 MM;PVC	STOP: TYPE: CONEX END, DIMENSIONS: WD 32 X LG 20 MM, MATERIAL: PVC; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE)	833	EA
SWIVEL:HAND CP COMPLETE FP 391;SS	TANK: TYPE: GEASER HEADER, CAPACITY: 2 L, DIMENSIONS: WD 100 X HT 200 X LG 200 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE)	833	EA

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

Business Management System

Supply Chain Management

Warehouse

Scope of Work for Plumbing

TANK:GEASER HEADER;2 L	TANK: TYPE: GEASER HEADER, CAPACITY: 2 L, DIMENSIONS: WD 100 X HT 200 X LG 200 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE)	2500	EA
TAP WTR:BATH PILLAR TRIUPH;SS;SCREW IN	TAP, WATER: TYPE: BATH PILLAR TRIUPH, MATERIAL: SS, INLET CONNECTION: SCREW IN, OUTLET CONNECTION: 15 MM	2500	EA
TAP WTR:COBRA;BRASS;15MM MALE	TAP, WATER: TYPE: COBRA, MATERIAL: BRASS, INLET CONNECTION: 15MM MALE	2500	EA
TAP WTR:COBRA;BRASS;22MM MALE	TAP, WATER: TYPE: COBRA, MATERIAL: BRASS, INLET CONNECTION: 22MM MALE	2500	EA
TAP WTR:CORAL RANGE; ZINK WALL, TRIUMPH	TAP, WATER: TYPE: CORAL RANGE; ZINK WALL, TRIUMPH, MATERIAL: SS, INLET CONNECTION: 15MM MALE	2500	EA
TAP WTR:CXC CACHET UNDERTILE STOP;SS	TAP, WATER: TYPE: CXC CACHET UNDERTILE STOP, MATERIAL: SS, INLET CONNECTION: 15MM MALE	2500	EA
TAP WTR:TRI BATH WALL ISCA;SS;15MM MALE	TAP, WATER: TYPE: TRI BATH WALL ISCA, MATERIAL: SS, INLET CONNECTION: 15MM MALE	3333	EA
TEE PIPE:15 X 15 X 15 MM;SCREW IN CONEX	TEE, PIPE: SIZE: 15 X 15 X 15 MM, CONNECTION: SCREW IN CONEX, MATERIAL: BRASS	3333	EA

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

Business Management System

Supply Chain Management

Warehouse

Scope of Work for Plumbing

TEE PIPE:22 X 22 X 15 MM;CONEX SCREW IN	TEE, PIPE: SIZE: 22 X 22 X 15 MM, CONNECTION: CONEX SCREW IN, MATERIAL: BRASS	3333	EA
TEE PIPE:22 X 22 X 22 MM;CONEX SCREW IN	TEE, PIPE: SIZE: 22 X 22 X 22 MM, CONNECTION: CONEX SCREW IN, MATERIAL: BRASS	2500	EA
TEE PIPE:22 X 22 X 22 MM;MALE SCREW IN	TEE, PIPE: SIZE: 22 X 22 X 22 MM, CONNECTION: MALE SCREW IN, MATERIAL: GALVANIZED	2500	EA
TEE PIPE:50 X 50 X 50 MM;GLUE ON;PVC	TEE, PIPE: SIZE: 50 X 50 X 50 MM, CONNECTION: GLUE ON, MATERIAL: PVC	2500	EA
TEE, SOLDER JOINT:22 X 22 X 22 MM	TEE, SOLDER JOINT: SIZE: 22 X 22 X 22 MM, CONNECTION: WELD ON, MATERIAL: COPPER	2500	EA
TEE, SOLDER JOINT:35 X 35 X 15 MM	TEE, SOLDER JOINT: SIZE: 35 X 35 X 15 MM, CONNECTION: WELD ON, MATERIAL: COPPER	833	EA
TRAP STEAM:HP GEYSER;22 MM;600 KPA	TRAP, STEAM: TYPE: HP GEYSER, CONNECTION: 22 MM, PRESSURE RATING: 600 KPA, MATERIAL: STL GALV; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE)	833	EA

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

Business Management System

Supply Chain Management

Warehouse

Scope of Work for Plumbing

TRAP:COMBINATION; PLUMBING;40 MM	TRAP: TYPE: COMBINATION; PLUMBING, SIZE: 40 MM, MATERIAL: RUBBER; BLACK; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE)	833	EA
TRAP:P-TRAP; PLUMBING;40 X 40 MM	TRAP: TYPE: P-TRAP; PLUMBING, SIZE: 40 X 40 MM, MATERIAL: RUBBER; BLACK; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE)	833	EA
TRAP:S-TRAP; PLUMBING;40 X 40 MM	TRAP: TYPE: S-TRAP; PLUMBING, SIZE: 40 X 40 MM, MATERIAL: RUBBER; BLACK; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE)	833	EA
TRAP:WASHER (FP 32); PLUMBING;32 MM	TRAP: TYPE: WASHER (FP 32); PLUMBING, SIZE: 32 MM, MATERIAL: STL ZN PLTD; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE)	2500	EA

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

Business Management System

Supply Chain Management

Warehouse

Scope of Work for Plumbing

TRAP:WASHER; PLUMBING;32 MM;STL ZN PLTD	TRAP: TYPE: WASHER; PLUMBING, SIZE: 32 MM, MATERIAL: STL ZN PLTD; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE)	2500	EA
TRAP:WASHER; PLUMBING;40 MM;STL ZN PLTD	TRAP: TYPE: WASHER; PLUMBING, SIZE: 40 MM, MATERIAL: STL ZN PLTD; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE)	2500	EA
TRAP:WASHER; PLUMBING;45 MM;STL ZN PLTD	TRAP: TYPE: WASHER; PLUMBING, SIZE: 45 MM, MATERIAL: STL ZN PLTD; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE)	833	EA
TUBE GLS:SOLAR GEYSER VACUUM;ID 45 MM	TUBE, GLASS: TYPE: SOLAR GEYSER VACUUM, INSIDE DIAMETER: 45 MM, OUTSIDE DIAMETER: 58 MM, LENGTH: 1.81 M	1667	EA
UNIT:FRONT FLUSH;TOILET	UNIT: TYPE: FRONT FLUSH, APPLICATION: TOILET	1667	EA

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

Business Management System

Supply Chain Management

Warehouse

Scope of Work for Plumbing

VALVE BALL:15 MM;4 BAR;COLD WATER;BRASS	VALVE, BALL: VALVE SIZE: 15 MM, DESIGN RATING: 4 BAR, TEMPERATURE RATING: COLD WATER, CONNECTION: 15MM MALE, BODY MATERIAL: BRASS, FACE TO FACE LENGTH: 250 MM, OPERATED: WATER FLOW	1667	EA
VALVE BALL:15 MM;4 BAR;COLD WATER;BRASS	VALVE, BALL: VALVE SIZE: 15 MM, DESIGN RATING: 4 BAR, TEMPERATURE RATING: COLD WATER, CONNECTION: 15MM MALE, BODY MATERIAL: BRASS, FACE TO FACE LENGTH: 250 MM, OPERATED: WATER FLOW, APPLICATION: FP3 SIDE INLET	1667	EA
VALVE BALL:15 MM;4 BAR;COLD WATER;SS	VALVE, BALL: VALVE SIZE: 15 MM, DESIGN RATING: 4 BAR, TEMPERATURE RATING: COLD WATER, CONNECTION: 15MM FEMALE, BODY MATERIAL: SS, FACE TO FACE LENGTH: 100 MM, OPERATED: HAND, APPLICATION: BALLO STOP MXF	1667	EA
VALVE GATE:15 MM;TAP;4 BAR;22 MM;117 MM	VALVE, GATE: VALVE SIZE: 15 MM, TYPE: TAP, DESIGN PRESSURE: 4 BAR, DESIGN TEMPERATURE: -10 TO 40 DEG C, CONNECTION: 22 MM, FACE TO FACE LENGTH: 117 MM, BODY MATERIAL: BRASS, TRIM: CR13 FOR 13 PCT, OPERATED: MANUAL	1667	EA

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

Business Management System

Supply Chain Management

Warehouse

Scope of Work for Plumbing

VALVE GATE:15 MM;TAP;4 BAR;15 MM;100 MM	VALVE, GATE: VALVE SIZE: 15 MM, TYPE: TAP, DESIGN PRESSURE: 4 BAR, DESIGN TEMPERATURE: -10 TO 40 DEG C, CONNECTION: 15 MM, FACE TO FACE LENGTH: 100 MM, BODY MATERIAL: BRASS, TRIM: CR 13 FOR 13%, OPERATED: MANUAL	1667	EA
VALVE RELF:22 MM;4 BAR;40 DEG C;MALE	VALVE, RELIEF: VALVE SIZE: 22 MM, SET PRESSURE: 4 BAR, TEMPERATURE RATING: 40 DEG C, CONNECTION: MALE, BODY MATERIAL: BRASS, TRIM: CR 13 FOR 13%, FACE TO FACE LENGTH: 100 MM, OPERATED: PRESSURE, APPLICATION: GEYSER LATCO, DESIGN RATING: 400 KPA	1667	EA
VALVE RELF:22 MM;400 KPA;40 DEG C;BRASS	VALVE, RELIEF: VALVE SIZE: 22 MM, SET PRESSURE: 400 KPA, TEMPERATURE RATING: 40 DEG C, CONNECTION: MALE 20MM, BODY MATERIAL: BRASS, TRIM: CR 13 FOR 13%, FACE TO FACE LENGTH: 100 MM, OPERATED: PRESSURE, APPLICATION: TEMP/PRESS RELIEF	1667	EA

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

Business Management System

Supply Chain Management

Warehouse

Scope of Work for Plumbing

VALVE RELF:22 MM;400 KPA;40 DEG C;FEMALE	VALVE, RELIEF: VALVE SIZE: 22 MM, SET PRESSURE: 400 KPA, TEMPERATURE RATING: 40 DEG C, CONNECTION: FEMALE, BODY MATERIAL: BRASS, TRIM: CR 13 FOR 13%, FACE TO FACE LENGTH: 100 MM, OPERATED: PRESSURE, APPLICATION: PRESS RELIEF	1667	EA
VALVE RELF:22 MM;400 KPA;40 DEG C;MALE	VALVE, RELIEF: VALVE SIZE: 22 MM, SET PRESSURE: 400 KPA, TEMPERATURE RATING: 40 DEG C, CONNECTION: MALE, BODY MATERIAL: BRASS, TRIM: CR 13 FOR 13%, FACE TO FACE LENGTH: 100 MM, OPERATED: PRESSURE, APPLICATION: TEMP RELIEF	1667	EA
VALVE:JOLLY FILLER;15 MM;4 BAR;PVC	VALVE: TYPE: JOLLY FILLER, VALVE SIZE: 15 MM, DESIGN RATING: 4 BAR, TEMPERATURE RATING: COLD WATER, CONNECTION: 15MM FEMALE, OPERATED: PRESSURE, BODY MATERIAL: PVC	1667	EA
VALVE:NON RETURN;15 MM;4 BAR;COLD WATER	VALVE: TYPE: NON RETURN, VALVE SIZE: 15 MM, DESIGN RATING: 4 BAR, TEMPERATURE RATING: COLD WATER, CONNECTION: 15MM FEMALE TO FEMALE, OPERATED: PRESSURE, BODY MATERIAL: BRS	1667	EA

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

Business Management System

Supply Chain Management

Warehouse

Scope of Work for Plumbing

VALVE:STOP;15 MM;4 BAR;COLD WATER;SS	VALVE: TYPE: STOP, VALVE SIZE: 15 MM, DESIGN RATING: 4 BAR, TEMPERATURE RATING: COLD WATER, CONNECTION: 15MM FEMALE TO FEMALE, OPERATED: HANDLE, BODY MATERIAL: SS	1667	EA
VLV FLOAT:BETA; PLUMBING;15 MM;4 BAR	VALVE, FLOAT: TYPE: BETA; PLUMBING, SIZE: 15 MM, PRESSURE RATING: 4 BAR, CONNECTION TYPE: SCREW IN/ON	1667	EA
VLV FLOAT:BOTTOM INLET MK2-FP61;25 MM	VALVE, FLOAT: TYPE: BOTTOM INLET MK2-FP61, SIZE: 25 MM, PRESSURE RATING: 4 BAR, CONNECTION TYPE: MALE	1667	EA
VLV FLOAT:C/W INLET VALVE; PLUMBING	VALVE, FLOAT: TYPE: C/W INLET VALVE; PLUMBING, SIZE: 15 MM, PRESSURE RATING: 4 BAR, CONNECTION TYPE: BOTTOM CONNECT	1667	EA
VLV FLOAT:SIDE INLET, BRASS; PLUMBING	VALVE, FLOAT: TYPE: SIDE INLET, BRASS; PLUMBING, SIZE: 30 MM, PRESSURE RATING: 4 BAR, CONNECTION TYPE: MALE SCREW ON	1667	EA
WASHER:TAP;15 MM;ID 6 MM;OD 15 MM	0667444	1000	EA
WASHER:TAP;22 MM;ID 6 MM;OD 22 MM	WASHER: TYPE: TAP, NOMINAL SIZE: 22 MM, INSIDE DIAMETER: 6 MM, OUTSIDE DIAMETER: 22 MM, THICKNESS: 6 MM, MATERIAL: RUBBER	1000	EA

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

Business Management System

Supply Chain Management

Warehouse

Scope of Work for Plumbing

Complied By: Cynthia Tsotetsi

Signature.....*C. Tsotetsi*

Date...21/02/2023.....

Approved By: Boitshoko Mokolobate

Signature.....

Date...21/02/2023.....

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.