

**SPECIFICATION:****SUPPLY OF ELECTRICAL MATERIAL: AS AND WHEN CONTRACT AT PRASA CRES SGR****Contents**

-
1. Scope
 2. General
 3. Terms Of Payment
 4. Bill Of Quantities
-
-

ANNEXTURE : A**Scope Of Work**

- 1.1. The works entails the supply and delivery of Electrical Material on the As and When Requested basis as per specified items in the Bill Of Quantities. The location where the material is to be delivered is Gauteng South Elandsfontein and Langlaagte PRASA CRES Facilities Depots.

2. General

- 2.1. Only quality and SABS approved material must be quoted for, material of inferior quality will not be accepted and the replacement of such material will be to the contractors' cost.
- 2.2. The service will be required on the As and When basis and depending on the urgency of the material required, PRASA-CRES may at other instances collect the material from the contractors premises.
- 2.3. All material requests will be in the form of a Purchase Order from PRASA-CRES Supply Chain Management department to the contractor. The contractor is expected to deliver the material within 2-days from the time of receiving a Purchase Order.
- 2.4. Material request and the delivery of such material will only be during normal working hours i.e. from Monday to Friday (07h30 to 16h00).

2.5. The contractor will ensure that material delivered is the material requested and false deliveries will be corrected at the contractor own cost.

3. Terms Of Payment

3.1. The terms of payment will be monthly and upon receiving the invoice, PRASA-CRES shall pay the contractor within 30 days. This is subject to the invoicing being both correct and free from anomalies.

3.2. Invoices shall show the clear description of the material requested and contract rates. A copy of the signed delivery notice will be attached and invoice as a supporting document.

3.3. If invoices are presented which do not fully comply with the format as detailed, they will be rejected and PRASA-CRES will accept no liability and/or responsibility for the late payment of the invoices which have been incorrectly addressed by the Contractor.

3.4. No payment shall be made by PRASA-CRES for any unauthorized service performed by the Contractor.

4. Bill Of Quantities

Item No	Description	Unit	Rate (Vat Excl.)
1.0	LIGHTING		
1.1	LAMP PL 9 COOL WHITE DULUX S 923 TYPE OSRAM	Ea	
1.2	LAMP PL13 2PIN ENERGY SAVING	Ea	
1.3	LAMP PL18 4PIN ENERGY SAVING	Ea.	
1.4	LAMP PL18 2PIN ENERGY SAVER	Ea	
1.5	LAMP PL26, 2PIN ENERGY SAVING	Ea	
1.6	LAMP 2 D 16 WATT OSRAM	Ea	
1.7	LAMP 2 D 28 WATT	Ea	
1.8	12W LED round downlight panel	Ea	
1.9	9W ES LED STICKS DAY LIGHT	Ea	
1.10	LAMP. 70 W FOR ONE TYPE HS. SON-E 230 V, 50HZ (INTERNAL IGNITOR)	Ea	
1.11	LAMP, SODIUM VAPOUR. E40 BASE 400 W HIGH PRESSURE, TUBULAR. 230V. 47 MM DIA X 283 MM LONG.(55/32906-BAL)	Ea	
1.12	LAMP, SODIUM VAPOUR. E40 BASE, 250 W HIGH PRESSURE, TUBULAR. UNIVERSAL BURNING 220V - 230V. USERS DESCRIPTION 47 MM DIA X 257 MM LONG.	Ea	



1.3	LAMP, SODIUM VAPOUR. E27 BASE, 70 W HIGH PRESSURE, ELLIPTICAL. INCORPORATING INTERNAL IGNITION DEVICE. UNIVERSAL BURNING 220 - 230V. USERS DESCRIPTION 71 MM DIA X 156 MM	Ea	
1.14	LAMP. 70 W FOR ONE TYPE HS. SON-E E-27 230 V, 50HZ (EXTERNAL IGNITOR)	Ea	
1.15	LAMP, FLUORESCENT. 1,2 M LONG X 26 MM DIA 36 W COOL WHITE, SWITCH START	Ea	
1.16	LAMP, FLUORESCENT 590 MM LONG X 26 MM DIA 18 W ,WHITE, SWITCH START	Ea	
1.17	LAMP, FLUORESCENT. 1,5 M LONG X 26 MM DIA.58 W COOL WHITE, SWITCH START ONLY.	Ea	
1.18	54 W T5 FLUORESCENT TUBE, 4100 LM, 1200MM	Ea	
1.19	35 W T5 FLUORESCENT TUBE, 3300 LM, 1450MM	Ea	
1.20	FLUORESCENT LAMP T5 28 WATT COOL WHITE 1150MM	Ea	
1.21	14 W T5 FLUORESCENT TUBE, 1100 LM, 550MM,	Ea	
1.22	18 W T8 LED 4 FOOT TUBE	Ea	
1.23	20W T5 LED TUBE 5FEET	Ea	
1.24	50W LED SPORTLIGHT	Ea	
1.25	100W LED SPORTLIGHT	Ea	
1.26	150W LED SPORTLIGHT	Ea	
1.27	LAMPHOLDER. 250 V. BAYONET-CAP. B.22. BRASS, THREADED 20 MM FOR ELECTRICAL CONDUIT, WITH SHADE RING.	Ea	
1.28	LAMPHOLDER. 250 V, EDISON SCREW E.27, PORCELAIN, NON-SKIRTED, BATTEN TYPE, WITH A BASE AND MOUNTING FACILITIES ON THE OUTSIDE	Ea	
1.29	LAMPHOLDER. 250 V,GOLIATH EDISON SCREW E40 PORCELAIN, NON-SKIRTED.	Ea	
1.30	LAMPHOLDER. 250 V, BAYONET-CAP, B.22, BRASS, THREADED 1/2 (26 TPI), WITH SHADE RING,	Ea	
1.31	LAMPHOLDER. 250 V, BAYONET-CAP, B.22, PORCELAIN, NON-SKIRTED, BATTEN TYPE.	Ea	
1.32	BALLAST FLUORESCENT 13 WATT FOR 1 * PL/2D LAMP. HARPER NR. C31B1230 OR SIMILAR. 0.17 AMPS. LOW POWER FACTOR	Ea	
1.33	BALLAST FOR 2 x 1.200 METRE 36W 230W ELECTRONIC INSTANT START	Ea	
1.34	80W T5 ELECTRONICS BALLAST	Ea	
1.35	CAPACITOR FIXED, 250 VOLT AC. 50 HZ.20 UF SUITABLE FOR 250 W. MERCURY VAPOUR AND 35/55 W. LOW PRESSURE SODIUM VAPOUR LAMPS.	Ea	



1.36	IGNITOR. FOR 250 & 400 WATT METAL HALIDE & HIGH PRESSURE SODIUM LAMPS UP TO 6A.	Ea	
1.37	IGNITOR. FOR 250 & 400 WATT METAL HALIDE & HIGH PRESSURE SODIUM LAMPS UP TO 6A.	Ea	
2.0			
2.1	WIRE ELECTRICAL. EARTHING WIRE 4 SQ MM STRANDED ANNEALED COPPER CONDUCTORS. USERS DESCRIPTION EARTHING WIRE	M	
2.2	WIRE ELECTRICAL. 600/1 000 VOLTS 1,5 SQ MM SINGLE CORE. STRANDED ANNEALED COPPER CONDUCTORS. PVC INSULATED RED, WHITE AND BLACK UNSHEATHED	M	
2.3	WIRE ELECTRICAL. 600/1 000 VOLTS 2,5 SQ MM SINGLE CORE. STRANDED ANNEALED COPPER CONDUCTORS. PVC INSULATED RED, WHITE AND BLACK UNSHEATHED	M	
2.4	WIRE ELECTRICAL. 600/1 000 VOLTS 4 SQ MM SINGLE CORE. STRANDED ANNEALED COPPER CONDUCTORS, PVC INSULATED RED, WHITE AND BLACK UNSHEATHED.	M	
2.5	WIRE ELECTRICAL. 600/1 000 VOLTS 6 SQ MM SINGLE CORE. STRANDED ANNEALED COPPER CONDUCTORS, PVC INSULATED RED, WHITE AND BLACK UNSHEATHED.	M	
2.6	WIRE ELECTRICAL. 600/1 000 VOLTS 1,5 SQ MM SINGLE CORE. STRANDED ANNEALED COPPER CONDUCTORS, PVC INSULATED GREEN AND YELLOW UNSHEATHED.	M	
2.7	WIRE ELECTRICAL. 600/1 000 VOLTS 2,5 SQ MM SINGLE CORE. STRANDED ANNEALED COPPER CONDUCTORS, PVC INSULATED GREEN AND YELLOW UNSHEATHED.	M	
2.8	WIRE ELECTRICAL. 600/1 000 VOLTS 4 SQ MM SINGLE CORE. STRANDED ANNEALED COPPER CONDUCTORS, PVC INSULATED GREEN AND YELLOW UNSHEATHED.	M	
2.9	WIRE ELECTRICAL. 600/1 000 VOLTS 6 SQ MM SINGLE CORE. STRANDED ANNEALED COPPER CONDUCTORS, PVC INSULATED GREEN AND YELLOW UNSHEATHED.	M	
2.10	WIRE ELECTRICAL. 600/1 000 VOLTS 1.5 SQ MM TWO CORE PLUS EARTH FLAT SUFFIX WIRE.	M	
2.11	WIRE ELECTRICAL. 600/1 000 VOLTS 2.5 SQ MM TWO CORE PLUS EARTH FLAT SUFFIX WIRE.	M	



2.12	WIRE ELECTRICAL. 600/1 000 VOLTS 4 SQ MM TWO CORE PLUS EARTH FLAT SUFFIX WIRE.	M	
2.13	WIRE ELECTRICAL. 600/1 000 VOLTS 6 SQ MM TWO CORE PLUS EARTH FLAT SUFFIX WIRE.	M	
3.0	CABLE ELECTRICAL		
3.1	CABLE ELECTRICAL. 600/1 000 VOLTS 6 SQ MM FOUR CORE. STRANDED COPPER CONDUCTORS, ANNEALED. PVC INSULATED, PVC BEDDED ECC/SWA PVC SHEATHED.	M	
3.2	CABLE ELECTRICAL. 600/1 000 VOLTS 10 SQ MM FOUR CORE. STRANDED COPPER CONDUCTORS, PVC INSULATED, PVC BEDDED. ECC/SWA PVC SHEATHED	M	
3.3	CABLE ELECTRICAL. 600/1 000 VOLTS 16 SQ MM FOUR CORE. STRANDED COPPER CONDUCTORS PVC INSULATED, PVC BEDDED. ECC/SWA PVC SHEATHED	M	
3.4	CABLE ELECTRICAL. 600/1 000 VOLTS 25 SQ MM FOUR CORE. STRANDED COPPER CONDUCTORS. PVC INSULATED PVC BEDDED. ECC/SWA, PVC SHEATHED.	M	
3.5	CABLE ELECTRICAL. 600/1 000 VOLTS 35 SQ MM FOUR CORE. STRANDED COPPER CONDUCTORS. PVC INSULATED PVC BEDDED. ECC/SWA, PVC SHEATHED.	M	
3.6	CABLE ELECTRICAL. 600/1 000 VOLTS 50 SQ MM FOUR CORE. STRANDED COPPER CONDUCTORS. PVC INSULATED PVC BEDDED. ECC/SWA, PVC SHEATHED	M	
3.7	CABLE ELECTRICAL. 600/1 000 VOLTS 70 SQ MM FOUR CORE. STRANDED COPPER CONDUCTORS. PVC INSULATED PVC BEDDED. ECC/SWA, PVC SHEATHED	M	
3.8	CABLE ELECTRICAL. 600/1 000 VOLTS 95 SQ MM FOUR CORE. STRANDED COPPER CONDUCTORS. PVC INSULATED PVC BEDDED. ECC/SWA, PVC SHEATHED	M	
3.9	CABLE ELECTRICAL. 600/1 000 VOLTS 120 SQ MM FOUR CORE. STRANDED COPPER CONDUCTORS. PVC INSULATED PVC BEDDED. ECC/SWA, PVC SHEATHED	M	
3.10	CABLE ELECTRICAL. 600/1 000 VOLTS 185 SQ MM FOUR CORE. STRANDED COPPER CONDUCTORS. PVC INSULATED PVC BEDDED. ECC/SWA, PVC SHEATHED	M	
4.0	CONDUIT AND ACCESSORIES		
4.1	CONDUIT BEND GALVANISED, INSPECTION BEND. SCREWED-END 20 MM BEND,	Ea	
4.2	CONDUIT BOX. GALVANISED, MILD STEEL, WITHOUT COVER. SCREWED-END. 20 MM CONDUIT OUTLET	Ea	
4.3	CONDUIT BOX. GALVANISED, MILD STEEL, WITHOUT COVER. THREE-WAY. SCREWED-END. 20 MM CONDUIT OUTLET	Ea	



4.4	CONDUIT,NIPPLE BRASS,HEXAGON HEAD, EXTERNALLY THREADED 20 MM, 11,1 MM LONG.	Ea	
4.5	CONDUIT,NIPPLE BRASS,HEXAGON HEAD, EXTERNALLY THREADED 25 MM, 11,1 LONG.	Ea	
4.6	CONDUIT BUSH BRASS, WITH INTERNAL THREAD, SCREWED 20 MM BUSHING.	Ea	
4.7	CONDUIT BUSH BRASS, WITH INTERNAL THREAD, SCREWED 25 MM BUSHING	Ea	
4.8	CONDUIT SADDLE BLACK ENAMELLED,MILD STEEL,FULL SADDLE,25 MM STRAP,	Ea	
4.9	CONDUIT, RIGID GALVANISED, MILD STEEL, WELDED SEAM, TYPE A. SCREWED-END.20 MM FITTED WITH COUPLER AT ONE END AND PLASTIC END CAP OTHER END. CONDUIT,METAL,RIGID	Ea	
4.10	CONDUIT,METAL,RIGID GALVANISED, MILD STEEL, WELDED SEAM, TYPE A. SCREWED-END. 50 MM FITTED WITH COUPLER AT ONE END AND PLASTIC END CAP OTHER END.	Ea	
4.11	CONDUIT BEND GALVANISED, MILD STEEL, INSPECTION BEND. COMPLETE WITH COVER AND SCREWS TYPE A. SCREWED-END20 MM BEND	Ea	
4.12	CONDUIT BOX. GALVANISED, MILD STEEL, WITHOUT COVER. SMALL CIRCULAR TERMINAL. TYPE A SCREWED-END.20 MM CONDUIT OUTLET	Ea	
4.13	CONDUIT BOX. GALVANISED, MILD STEEL, WITHOUT COVER. SMALL CIRCULAR THREE-WAY. TYPE A. SCREWED-END.20 MM CONDUIT OUTLET	Ea	
4.14	CONDUIT SADDLE GALVANISED,MILD STEEL,FLUTED FULL SADDLE,20 MM STRAP,RETAINING	Ea	
4.15	CONDUIT CHASE NIPPLE BRASS,HEXAGON HEAD, EXTERNALLY THREADED 20 MM, 11,1 MM LONG. CHASE NIPPLE,CONDUIT	Ea	
4.16	CONDUIT CHASE NIPPLE BRASS,HEXAGON HEAD, EXTERNALLY THREADED 25 MM, 11,1 LONG CHASE NIPPLE,CONDUIT	Ea	
4.17	CONDUIT BUSH BRASS, WITH INTERNAL THREAD, SCREWED 20 MM BUSHING,ELECTRICAL CONDUIT	Ea	
4.18	CONDUIT BUSH BRASS, WITH INTERNAL THREAD, SCREWED 25 MM BUSHING,ELECTRICAL CONDUIT	Ea	
4.19	CONDUIT SADDLE BLACK ENAMELLED,MILD STEEL, FLUTED,FULL SADDLE,25 MM STRAP,RETAINING	Ea	
4.20	CONDUIT BOX. PVC, CIRCULAR BOX, 20 MM, TEE- THREE WAY. TO QUOTED PART NUMBER OR EQUAL CONDUIT OUTLET	Ea	



4.21	CONDUIT BOX. PVC, CIRCULAR BOX, 20 MM, TERMINAL-ONE WAY.	Ea	
4.22	CONDUIT BOX PVC, CIRCULAR BOX, 25 MM THROUGH-TWO WAY.	Ea	
4.23	CONDUIT COUPLING. PVC 20 MM	Ea	
4.24	CONDUIT ELBOW, ELECTRICAL WHITE P.V.C. 20 MM. COMPLETE WITH COVER & SCREWS	Ea	
4.25	CONDUIT BEND PVC. INSPECTION BEND, 20 MM, COMPLETE WITH COVER & SCREWS	Ea	
4.26	CONDUIT TEE PVC, INSPECTION TYPE, 20 MM, COMPLETE WITH COVER & SCREWS	Ea	
4.27	CONDUIT, RIGID PVC, HEAVY GAUGE, 20 MM. 4 METRE LENGTHS	Ea	
4.28	CONDUIT SADDLE 20 MM PVC STRAP SADDLE	Ea	
4.29	CONDUIT BOX. PVC, CIRCULAR BOX, 20 MM, TEE-THREE WAY.	Ea	
4.30	CONDUIT BOX. PVC. CIRCULAR BOX. 20 MM. INTERSECTION-FOUR WAY	Ea	
4.31	CONDUIT COUPLING. PVC 20 MM TO QUOTED PART NUMBER OR EQUAL COUPLING	Ea	
4.32	CONDUIT COUPLING PVC, 25 MM. TO QUOTED PART NUMBER OR EQUAL COUPLING	Ea	
4.33	CONNECTOR PLUG ELECTRICAL FEMALE 3 PIN 2 + E 250 V. 10 A CONNECTOR FOR CLASS 1 APPLIANCES FOR HOT CONDITIONS IN COMPLIANCE WITH GOVERNMENT NOTICE NO.1344 OF JUNE 1978 SCHEDULE 10.	Ea	
4.34	CONDUIT BOSAL 20MM GALVANIZED. 4 METRE LENGTHS	M	
4.35	CONDUIT, RIGID STEEL GALVANIZED, HEAVY GAUGE, 20 MM. 4 METRE LENGTHS	Ea.	
4.36	COUPLING BOSAL 20MM GALVANIZED	Ea	
4.37	CONDUIT BOX. PVC. CIRCULAR 4-WAY LOOP-IN BOX, 20 MM BACK OUTLET KNOCK-OUTS	Ea	
4.38	CONDUIT,RACEWAY,NON-METALLIC TRUNKING, WIRING AND CABLE TRUNKING PVC WHITE WIDTH 16 MM X DEPTH 16 MM X 2 METRE LONG, COMPLETE WITH SNAP ON LID	Ea	
4.39	CONDUIT BOX. PVC. CIRCULAR 4-WAY LOOP-IN BOX, 20 MM BACK OUTLET KNOCK-OUTS, TO QUOTED PART NUMBER OR EQUAL CONDUIT OUTLET	Ea	
5.0			
5.1	400 WATT, 41.08(VMP) SOLAR PANEL, MONO CELL	Ea	
5.2	105 A/H DEEP CYCLE BATTERIES	Ea	



5.3	INVERTOR 2000W	Ea	
6.0	FERRULES AND LUGS		
6.1	FERRULE, CRIMP TYPE SIZE 10 MM SPLICE, CONDUCTOR	Ea	
6.2	FERRULE, CRIMP TYPE SIZE 1,5 MM.SQ DESCRIPTION USERS IN ACCORDANCE WITH STAMCOR ELECTRIC DIMENSION CHART SPECIFICATIONSBS 2871	Ea	
6.3	FERRULE, CRIMP TYPE SIZE 2,5 MM. SQ DESCRIPTION USERS IN ACCORDANCE WITH STAMCOR ELECTRIC DIMENSION CHART SPECIFICATIONSBS 2871	Ea	
6.4	FERRULE, CRIMP TYPE SIZE 4,0 MM SQ DESCRIPTION USERS IN ACCORDANCE WITH STAMCOR ELECTRIC DIMENSION CHART SPECIFICATIONSBS 2871	Ea	
6.5	FERRULE, CRIMP TYPE DESCRIPTION USERS IN ACCORDANCE WITH STAMCOR ELECTRIC DIMENSION CHART SIZE 6MM SQ SPECIFICATIONSBS 2871	Ea	
6.6	FERRULE, CRIMP TYPE SIZE 10 MM SQ DESCRIPTION USERS IN ACCORDANC WITH STAMCOR ELECTRIC DIMENSION CHART SPECIFICATIONSBS 2871	Ea	
6.7	FERRULE, CRIMP TYPE SIZE 16 MM.SQ DESCRIPTION USERS IN ACCORDANCE WITH STAMCOR ELECTRIC DIMENSION CHART SPECIFICATIONSBS 2871	Ea	
6.8	FERRULE, CRIMP TYPE SIZE 25 MM.SQ DESCRIPTION USERS IN ACCORDANCE WITH STAMCOR ELECTRIC DIMENSION CHART SPECIFICATIONSBS 2871	Ea	
6.9	FERRULE, CRIMP TYPE SIZE 35 MM.SQ DESCRIPTION USERS IN ACCORDANCE WITH STAMCOR ELECTRIC DIMENSION CHART SPECIFICATIONSBS 2871	Ea	
6.10	FERRULE, CRIMP TYPE SIZE 50 MM.SQ DESCRIPTION USERS IN ACCORDANCE WITH STAMCOR ELECTRIC DIMENSION CHART SPECIFICATIONSBS 2871	Ea	
6.11	FERRULE, CRIMP TYPE SIZE 150 MM. SQ DESCRIPTION USERS IN ACCORDANCE WITH STAMCOR ELECTRIC DIMENSION CHART SPECIFICATIONSBS 2871	Ea	
6.12	CRIMPING LUG. CABLE SIZE 1,5 SQ MM CLEARANCE HOLE FOR STUD M4, TERMINAL,LUG	Ea	
6.13	CRIMPING LUG CABLE SIZE 1,5 SQ MM CLEARANCE HOLE FOR STUD M6, TERMINAL,LUG	Ea	
6.14	CRIMPING LUG. CABLE SIZE 2,5 SQ MM CLEARANCE HOLE FOR STUD M5. TERMINAL,LUG	Ea	
6.15	CRIMPING LUG. CABLE SIZE 4 SQ MM CLEARANCE HOLE FOR STUD M5. TERMINAL,LUG	Ea	
6.16	CRIMPING LUG. CABLE SIZE 4 SQ MM CLEARANCE HOLE FOR STUD M6, TERMINAL,LUG	Ea	



6.17	CRIMPING LUG. CABLE SIZE 6 SQ MM CLEARANCE HOLE FOR STUD M6, TERMINAL,LUG	Ea	
6.18	CRIMPING LUG. CABLE SIZE 10 SQ MM CLEARANCE HOLE FOR STUD M8,	Ea	
6.19	CRIMPING LUG. CABLE SIZE 16 SQ MM CLEARANCE HOLE FOR STUD M6, TERMINAL,LUG	Ea	
6.20	CRIMPING LUG. CABLE SIZE 16 SQ MM CLEARANCE HOLE FOR STUD M8,	Ea	
6.21	CRIMPING LUG. CABLE SIZE 25 SQ MM CLEARANCE HOLE FOR STUD M10,	Ea	
6.22	CRIMPING LUG. CABLE SIZE 35 SQ MM CLEARANCE HOLE FOR STUD M8,	Ea	
6.23	CRIMPING LUG. CABLE SIZE 35 SQ MM CLEARANCE HOLE FOR STUD M10,	Ea	
6.24	CRIMPING LUG. CABLE SIZE 50 SQ MM CLEARANCE HOLE FOR STUD M12,	Ea	
6.25	CRIMPING LUG. CABLE SIZE 95 SQ MM CLEARANCE HOLE FOR STUD M12,	Ea	
6.26	CRIMPING LUG, INSULATED. CABLE SIZES 1,5 TO 2,5 SQ MM CLEARANCE HOLE FOR STUD M3, COLOURED BLUE, SEAMED THIMBLE, RING PALM BETWEEN 8,0 MM AND 8,5 MM WIDE	Ea	
6.27	CRIMPING LUG. CABLE SIZE 25 SQ MM CLEARANCE HOLE FOR STUD M8,	Ea	
7.0	CONNECTOR STRIP		
7.1	CONNECTOR STRIP, (PVC). 12-WAY, 10 AMP.	Ea	
7.2	CONNECTOR STRIP, (PVC). 12-WAY, 15 AMP, WACO	Ea	
7.3	CONNECTOR STRIP, (PVC). 12-WAY, 30 AMP, WACO	Ea	
7.4	CONNECTOR STRIP, (PVC). 12-WAY, 6 AMP, WACO	Ea	
7.5	BLOCK CONNECTOR, (PORCELAIN). TWO-WAY, 6 AMP, WACO	Ea	
7.6	CONNECTOR, PLUG, ELECTRICAL ELECTRIC PLUG 3 PIN 250 V 16 A REWIRABLE, MATERIAL. CONNECTOR,PLUG	Ea	
7.7	QUICK CONNECT PUSH ON TYPE CABLE SIZES 0,75 TO 1,5 SQ MM FEMALE, 20 MM LONG. FOR 6 MM TAB MALE TERMINAL , UTILUX	Ea	
8.0	CABLE SPLICING KIT		
8.1	CABLE SPLICING KIT. SUITABLE FOR IN-LINE JOINTING OF PVC INSULATED, PVC BEDDED, SWA, PVC SHEATHED CABLE, RATED FOR 1 000 VOLTS WITH AN OD. BETWEEN 9 MM & 25 MM. MINIMUM MOULD LENGTH 240 MM. KIT TO BE COMPLETE WITH THE	Ea	

	NECESSARY MOULDS, RESINS AND TAPES		
8.2	CABLE SPLICING KIT. SUITABLE FOR IN-LINE JOINTING OF PVC INSULATED,PVC BEDDED SWA, PVC SHEATHED CABLE, RATED FOR 1 000 VOLTS WITH AN OD. BETWEEN 22 MM & 40 MM. KIT TO BE COMPLETE WITH THE NECESSARY MOULDS, RESINS AND TAPES.	Ea	
8.3	CABLE SPLICING KIT. HEAT SHRINK TYPE 6 - 16 MMSQ. 3 CORE 1000 VOLT ARMoured PVC CABLE COMPLETE WITH ALL COMPONENTS	Ea	
8.4	HT CABLE SPLICING KIT. SUITABLE FOR IN-LINE JOINTING OF PVC INSULATED, PVC SHEATHED CABLE, RATED FOR 1 000 VOLTS WITH AN OD. BETWEEN 29 MM & 52 MM. KIT TO BE COMPLETE WITH THE NECESSARY MOULDS, RESINS AND TAPES	Ea	
9.0	SOCKET-OUTLETS AND SWITCH-DISCONNECTORS		
9.1	SOCKET-OUTLET 250 VOLT AC. (3 PIN)16 A FLUSH MOUNTING,	Ea	
9.2	SWITCHED SOCKET-OUTLET 250 VOLT AC. (3 PIN)16 A FLUSH MOUNTING, RED, DOUBLESWITCHED-SOCKET OUTLET COMPLETE METAL COVER AND COVER SCREWS,	Ea	
9.3	SWITCHED SOCKET-OUTLET 250 VOLT AC. (3 PIN) 16 A (DOUBLE) SURFACE MOUNTING, SHUTTERED, INDUSTRIAL TYPE,	Ea	
9.4	SWITCHED SOCKET-OUTLET 250 VOLT AC. (3 PIN) 16 A (SINGLE) SURFACE MOUNTING, INDUSTRIAL TYPE,	Ea	
9.5	SWITCH-DISCONNECTOR. 500 VOLT AC. 60 AMP THREE-POLE MOULDED CASE SCREW-FIXING TYPE EQUAL TO AND INTERCHANGEABLE WITH SWITCH-KING SK3-60. SWITCH,LEVER SWITCH-KING	Ea	
9.6	SWITCH-DISCONNECTOR. 500 VOLT AC. 60 AMP TWO-POLE, MOULDED CASE SCREW-FIXING TYPE EQUAL TO OR INTERCHANGEABLE WITH SWITCH-KING SK2-60. SWITCH,LEVER SWITCH-KING	Ea	
9.7	SWITCH-DISCONNECTOR. 500 VOLT AC. 45 AMP TWO-POLE, MOULDED CASE SCREW-FIXING TYPE EQUAL TO AND INTERCHANGEABLE WITH SWITCH KING SK2-45. USERS DESCRIPTION STOVE-ISOLATOR. SWITCH,LEVER SWITCH-KING	Ea	
10.0	CIRCUIT BREAKERS		
10.1	EARTH LEAKAGE UNIT. WITH OVERLOAD PROTECTION. SINGLE PHASE AND NEUTRAL. 240 VOLT AC. 5 KA 60A 30MA SENSITIVITY.(HEINEMANN)	Ea	



10.2	PHOTOELECTRIC CONTROL UNIT, THERMAL TYPE, 230 V, 10 AMP,	Ea	
10.3	CONTACTOR 40A 1POLE	Ea.	
10.4	MINIATURE CIRCUIT BREAKER. SINGLE PHASE. 230 VOLTS AC. 5A 1POLE 3KA	Ea	
10.5	MINIATURE CIRCUIT BREAKER. SINGLE PHASE. 230 VOLTS AC. 10A 1POLE 3KA	Ea	
10.6	MINIATURE CIRCUIT BREAKER. SINGLE PHASE. 230 VOLTS AC. 15A 1POLE 3KA	Ea	
10.7	MINIATURE CIRCUIT BREAKER. SINGLE PHASE. 230 VOLTS AC. 30A 1POLE 3KA	Ea	
10.8	MINIATURE CIRCUIT BREAKER. SINGLE PHASE. 230 VOLTS AC. 40A 1POLE 3KA	Ea	
10.9	MINIATURE CIRCUIT BREAKER. SINGLE PHASE. 230 VOLTS AC. 60A 1POLE 3KA	Ea	
10.10	MINIATURE CIRCUIT BREAKER. SINGLE PHASE. 230 VOLTS AC. 80A 1POLE 3KA	Ea	
10.11	MINIATURE CIRCUIT BREAKER. SINGLE PHASE AND NEUTRAL. 230 VOLTS AC. 60A 1POLE + N 3KA	Ea	
10.12	MINIATURE CIRCUIT BREAKER. SINGLE PHASE AND NEUTRAL. 230 VOLTS AC. 80A 1POLE + N 3KA	Ea	
10.13	MINIATURE CIRCUIT BREAKER. THREE PHASE. 400 VOLTS AC. 20A 3POLE	Ea	
10.14	MINIATURE CIRCUIT BREAKER. THREE PHASE. 400 VOLTS AC. 30A 3POLE	Ea	
10.15	MINIATURE CIRCUIT BREAKER. THREE PHASE. 400 VOLTS AC. 40A 3POLE	Ea	
10.16	MINIATURE CIRCUIT BREAKER. THREE PHASE. 400 VOLTS AC. 60A 3POLE	Ea	
10.17	MINIATURE CIRCUIT BREAKER. THREE PHASE. 400 VOLTS AC. 80A 3POLE	Ea	
10.18	MINIATURE CIRCUIT BREAKER. THREE PHASE. 400 VOLTS AC. 125A 3POLE	Ea	
10.19	MINIATURE CIRCUIT BREAKER. THREE PHASE. 400 VOLTS AC. 150A 3POLE	Ea	
10.20	MINIATURE CIRCUIT BREAKER. THREE PHASE. 400 VOLTS AC. 250A 3POLE	Ea	
11.0	MISCELLANEOUS		
11.1	GEYSER, ELECTRIC, WATER, SABS 151 / LATEST 150 LITRE, 230 V, 3 W HIGH PRESSURE GEYSER, TYPE 3 WORKING PRESSURE 400 KPA, HORIZONTAL OR VERTICAL INSTALLATION	Ea	
11.2	THERMOSTAT. FAIL-SAFE TYPE. 250 V WITH 279 MM LONG STEM RANGE 20 TO 75 DEG. CELSIUS.	Ea	



11.3	BATTERY PRIMARY DRY CELL 1,5 VOLT ALKALINE(AAA) ONE MAKERS PART NUMBER MN2400	Ea	
11.4	BATTERY,PRIMARY DRY CELL 9 VOLT MINIATURE	Ea	
11.5	BATTERY,PRIMARY DRY CELL 1,5 VOLT ALKALINE PENLIGHT FOR TEST EQUIPMENT	Ea	
11.6	ELEMENT 3 KW FOR 230 V GEYSER 150 LITRE, LOW PRESSURE GEYSER, TYPE 3, WITH COPPER INNER CYLINDER, INLET/OUTLET CONNECTIONS TO BE 20 MM ISO/R228 MALE THREADS HORIZONTEL FLOOR MOUNTING	Ea	
11.7	ELEMENT, GEYSER. 230 VOLTS 2 KW 280 MM IMMERSED LENGTH, COPPER SHEATH NICKEL PLATED, WITH THERMOSTAT POCKET BUT WITHOUT THERMOSTAT BRASS BOSS 1 1/4" BSP	Ea	
11.8	Transformer oil	p/l	
11.9	Silica gel	p/kg	
11.10	110m PVC SLEEVE PIPE	M	
12.	Mark up on Material that the supplier will outsource, or the material not specified on the list	%	
13.	Transport Rate	R/ KM	
	SUB TOTAL	R	
	VAT @ 15 %	R	
	TOTAL	R	