

## Technical Specification

### Truck Tractor 6x4 < 28000 kg GVM < 75000 kg GCM

<b>Vehicle Job Description</b>	Required for carrying Goods & equipment of up to 75000 kg GCM on all types of road surfaces short & long distance
<b>Technical Specification</b>	KW output: Minimum 320 kw Torque: Minimum 2100 nm Diesel Powered ( Turbo) Permissible Front axle Rating "max 7500 kg" Permissible Rear axle Rating "max 18000 kg" D/T Rating: "56000kg to 75000Kg" Wheel base: "max 3900 mm" Air Conditioner Factory fitted Driver and passenger airbags Driver and passenger seatbelt reminder indicator / alarm Head light reminder indicator/alarm ABS brakes Power steering Two emergency triangles Wheel base (Center front axle to center of rear axle unit) (Min) 4800 mm" Manufactures approved Engine Protection Device Chassis to facilitate the fitting of hydraulic crane Fully Synchromesh Brakes to be air assisted or full air dual system Trailer brake control Fitted towing/recovery facility on front 5 <sup>th</sup> wheel manufactures approved Tyres: As per Manufactures Specifications Noise Level: not to exceed 75db Reverse alarm / beeper
	<b>Permitted Ancillaries</b>
<b>Required Ancillaries</b>	1. Air conditioner 2. Truck Mounted Crane Max 17 Ton Metre range 3. Hour meter 4. Inter lock hand brake system 5. Tool Boxes 6. Working Lights 7. Wheel Flaps: SABS 1496 specification (Jan 1999) 8. Yellow reflective tape that must be fitted. (Road traffic Act and Regulations No. 192A)

Drafted by Mike Masondo

Date 13/07/2021

Signature 