Door schedule

NOTE:DOOR HAND TO BE VERIFIED FOR EACH INDIVIDUAL DOOR AS PER FLOOR PLAN BY CONTRACTOR



TYPE D01

POSITION:	O.DOCKET ROOM
LEVEL:	GROUND FLOOR
TYPE MARK:	D01
TYPE:	D01 - 1600 x 2030 mm
DESCRIPTION:	1600 x 2030 X 40mm THICK SOLIDCORE TIMBER DOOR, SUITABLE FOR PAINTING. PREPARE, SAND AND CLEAN APPLY 1x COAT UNDERCOAT, SAND LIGHTLY. APPLY 2x COATS IN STRICT ACCORDANCE WITH MANUFACTURERS SPECIFICATIONS. SAND LIGHTLY BETWEEN COATS.COLOUR TO BE APPROVED BY ARCHITECT.
FIRE RATING:	NONE
CONSTRUCTION TYPE:	230 MM MASONRY WALL JAMBS CONTRACTOR TO CONFIRM PRIOR MANUFACTURING
FRAME TYPE:	1.2MM DOUBLE REBATED RED-OXIDE DIPPED STEEL DOOR FRAME, WITH 2 HINGES TO ACCOMADATE 40MM THICK DOOR
HEAD HEIGHT:	2030mm
COUNT:	1
IRONMONGERY:	REFER TO SCHEDULE

NOTE:DOOR HAND TO BE VERIFIED FOR EACH INDIVIDUAL DOOR AS PER FLOOR PLAN BY CONTRACTOR



TYPE D02

POSITION:	COURTYARD, C.BATHROOM, TREATMENT ROOM, C.COUNSELLING ROOM, C. RECEPTION & WAITING, A. KITCHEN, WC, A. REST ROOM FOR SHIFT WORKERS, REST ROOM FOYER, STATEMENT AND DRAFTING AREA, CASE TERMINAL OFFICES, RADIO ROOM, B. MALE PUBLIC ABLUTION WC, B. DISABLED WC, B. FEMALE PUBLIC WC, PUBLIC ABLUTION DUCT, CIRCULATION, MALE WC, FEMALE WC, KITCHEN 2, TEMP SAP B STORE, N. MEMBER OFFICE, N. REGISTRATION, STATIONERY STORE, H, J, M. MEMBER OFFICE, D. STATION COMMENDER OFFICE, J. DATA TYPIST, J. TYPIST, K. SUB-SECTION COMMENDER, FEMALE WC, MIP WC, MALE WC, KITCHEN 2, J.TYPIST, E.SECCTION COMMENDER OFFICE 2 (LVL-6), E. SECTION COMMENDER (LVL 7), I.SECTION OFFICE 1, STATEMENT OFFICE 1, G.MEMBER OFFICE, E.SUB-SECTION OFFICE 1,3,4, O. STATIONERY STORE, SERVER ROOM, F. MEMBER OFFICE, O. GENERAL STORE, O.SAPS B STORE (SMALL ITEMS), O.SAPS B STORE (LARGE ITEMS), O.CLEAN EQUIPMENT, O.WALK-IN AREA
LEVEL:	GROUND FLOOR
TYPE MARK:	D02
TYPE:	D02- 813 x 2032 mm DOOR
DESCRIPTION:	813 x 2032 x 40mm THICK HOLLOWCORE DOOR SUITABLE FOR PAINTING. PREPARE, SAND AND CLEAN. APPLY 1x COAT UNDERCOAT, SAND LIGHTLY. APPLY 2x COATS IN STRICT ACCORDANCE WITH MANUFACTURERS SPECIFICATIONS. SAND LIGHTLY BETWEEN COATS.COLOUR TO BE APPROVED BY ARCHITECT.
FIRE RATING:	TO MANUFACTURERS SPEC.
CONSTRUCTION TYPE:	230 MM MASONRY WALL JAMBS CONTRACTOR TO CONFIRM PRIOR MANUFACTURING
FRAME TYPE:	1.2MM DOUBLE REBATED RED-OXIDE DIPPED STEEL DOOR FRAME, WITH 2 HINGES TO ACCOMADATE 40MM THICK DOOR
HEAD HEIGHT:	2040mm
COUNT:	58
IRONMONGERY:	REFER TO SCHEDULE

NOTE:DOOR HAND TO BE VERIFIED FOR EACH INDIVIDUAL DOOR AS PER FLOOR PLAN BY CONTRACTOR



TYPE D03

POSITION:	CIRCULATION
LEVEL:	GROUND FLOOR
TYPE MARK:	D3
TYPE:	D3- 1250 x 2040 mm DOOR
DESCRIPTION:	1250 x 2040mm high EXTERNAL ALUMINIUM DOUBLE DOOR , POWDER COATED ALUMINIUM (CHARCOAL), GLAZING TO STRICTLY CONFORM TO SANS 204 SUPPLIED FENESTRATION CLCULATION SHEET, COMPLYING WITH SANS 10400XA
FIRE RATING:	TO MANUFACTURERS SPEC.
CONSTRUCTION TYPE:	230MM MASONRY WALL JAMBS CONTRACTOR TO CONFIRM PRIOR MANUFACTURING
FRAME TYPE:	POWDER COATED ALUMINIUM (CHARCOAL) TO SPECIALIST, COLOUR TO ARCHITECT'S APPROVAL
HEAD HEIGHT:	2040mm
COUNT:	6
IRONMONGERY:	REFER TO SCHEDULE

NOTE:DOOR HAND TO BE VERIFIED FOR EACH INDIVIDUAL DOOR AS PER FLOOR PLAN BY CONTRACTOR



TYPE D04

POSITION:	O. GARDEN STORE
LEVEL:	GROUND FLOOR
TYPE MARK:	D04
TYPE:	D04- 954 x 1988 mm DOOR
DESCRIPTION:	813 x 2023mm MILD STEEL PRIMED AND PAINTED TRANSFORMER DOOR FITTED WITH FACTORY LOUVRE & PADLOCK LATCH.
FIRE RATING:	TO MANUFACTURERS SPEC.
CONSTRUCTION TYPE:	WALL JAMBS CONTRACTOR TO CONFIRM PRIOR MANUFACTURING
FRAME TYPE:	1.2MM DOUBLE REBATED RED-OXIDE DIPPED STEEL DOOR FRAME, WITH 2 HINGES TO ACCOMADATE 40MM THICK DOOR
HEAD HEIGHT:	2032mm
COUNT:	1
IRONMONGERY:	REFER TO SCHEDULE

NOTE:DOOR HAND TO BE VERIFIED FOR EACH INDIVIDUAL DOOR AS PER FLOOR PLAN BY CONTRACTOR



TYPE D05

POSITION:	FEMALE WC, MALE WC, B. FEMALE PUBLIC WC 1, B. MALE PUBLIC WC, WC, C.BATHROOOM
LEVEL:	GROUND FLOOR
TYPE MARK:	D05
TYPE:	D05- 850 x 2032 mm DOOR
DESCRIPTION:	850 x 2032 x 40mm THICK HORIZONTAL SLATTED TIMBER DOOR PANEL WITH LOUVRES SUITABLE FOR PAINTING. PREPARE, SAND AND CLEAN. APPLY 1x COAT UNDERCOAT, SAND LIGHTLY. APPLY 2x COATS IN STRICT ACCORDANCE WITH MANUFACTURERS SPECIFICATIONS. SAND LIGHTLY BETWEEN COATS.COLOUR TO BE APPROVED BY ARCHITECT.
FIRE RATING:	TO MANUFACTURERS SPEC.
CONSTRUCTION TYPE:	WALL JAMBS CONTRACTOR TO CONFIRM PRIOR MANUFACTURING
FRAME TYPE:	1.2MM DOUBLE REBATED RED-OXIDE DIPPED STEEL DOOR FRAME, WITH 2 HINGES TO ACCOMADATE 40MM THICK DOOR
HEAD HEIGHT:	2032mm
COUNT:	11
IRONMONGERY:	REFER TO SCHEDULE

NOTE:DOOR HAND TO BE VERIFIED FOR EACH INDIVIDUAL DOOR AS PER FLOOR PLAN BY CONTRACTOR



TYPE G01

POSITION:	O. GARDEN STORE, O.SAPS 13 STORE (SMALL ITEMS), O.SAPS 13 STORE (LARGE ITEMS), O. GENERAL STORE, TEMPORARY SAPS 13 STORE , A STATEMENT DRAFTING AREA, A. WORK SPACE FRONT OF COUNTER,
LEVEL:	GROUND FLOOR
TYPE MARK:	GD1
TYPE:	GD1- REFER TO DWG A-630: GALVANIZED STEEL DOOR WITH VIEWING PANEL, MADE TO FIT OPENING ON SITE. TYPE AND DESIGN AS PER DEVELOPER DETAILS
DESCRIPTION:	REFER TO DWG A-630: GALVANIZED STEEL DOOR WITH VIEWING PANEL, MADE TO FIT OPENING ON SITE. TYPE AND DESIGN AS PER DEVELOPER DETAILS
FIRE RATING:	TO MANUFACTURERS SPEC.
CONSTRUCTION TYPE:	WALL JAMBS CONTRACTOR TO CONFIRM PRIOR MANUFACTURING
FRAME TYPE:	REFER TO DWG A-630: GALVANIZED STEEL GATE MADE TO FIT OPENING ON SITE. TYPE AND DESIGN AS PER DEVELOPER DETAILS
HEAD HEIGHT:	2000mm
COUNT:	7
IRONMONGERY:	REFER TO DWG A-630: GALVANIZED STEEL DOOR WITH VIEWING PANEL, MADE TO FIT OPENING ON SITE. TYPE AND DESIGN AS PER DEVELOPER DETAILS

NOTE:DOOR HAND TO BE VERIFIED FOR EACH INDIVIDUAL DOOR AS PER FLOOR PLAN BY CONTRACTOR



TYPE DS01

POSITION:	O. FIRE ARM SAFE, O AMMUNITION SAFE
LEVEL:	GROUND FLOOR
TYPE MARK:	DS01
TYPE:	1930 x 850mm
DESCRIPTION:	REFER TO DWG A-630: GALVANIZED STEEL DOOR WITH VIEWING PANEL, MADE TO FIT OPENING ON SITE. TYPE AND DESIGN AS PER DEVELOPER DETAILS
FIRE RATING:	TO MANUFACTURERS SPEC.
CONSTRUCTION TYPE:	WALL JAMBS CONTRACTOR TO CONFIRM PRIOR MANUFACTURING
FRAME TYPE:	REFER TO DWG A-630: GALVANIZED STEEL GATE MADE TO FIT OPENING ON SITE. TYPE AND DESIGN AS PER DEVELOPER DETAILS
HEAD HEIGHT:	2000mm
COUNT:	2
IRONMONGERY:	THIS IS A NEW DOOR TYPE THAT NEEDS TO BE SPECIFIED BY IRONMONGERY SPECIALIST.

NOTE:DOOR HAND TO BE VERIFIED FOR EACH INDIVIDUAL DOOR AS PER FLOOR PLAN BY CONTRACTOR



TYPE DSD01

POSITION:	A. REST ROOM FOR SHIFT WORKERS
LEVEL:	GROUND FLOOR
TYPE MARK:	DSD01
TYPE:	DSD01 - 900 x 2040 mm
DESCRIPTION:	813 x 2040 x 40mm THICK HOLLOWCORE SLIDING DOOR WITH TIMBER SLIDING RAIL HUNG SURFACE PREPARED, SAND AND CLEAN APPLY 1x COAT UNDERCOAT, SAND LIGHTLY. APPLY 2x COATS IN STRICT ACCORDANCE WITH MANUFACTURERS SPECIFICATIONS. SAND LIGHTLY BETWEEN COATS.COLOUR TO BE APPROVED BY ARCHITECT.
FIRE RATING:	TO MANUFACTURERS SPEC.
CONSTRUCTION TYPE:	WALL JAMBS CONTRACTOR TO CONFIRM PRIOR MANUFACTURING
FRAME TYPE:	SUPPILIED WITH DOOR
HEAD HEIGHT:	2030mm
COUNT:	1
IRONMONGERY:	REFER TO IRONMONGERY SCHEDULE

NOTE:DOOR HAND TO BE VERIFIED FOR EACH INDIVIDUAL DOOR AS PER FLOOR PLAN BY CONTRACTOR



TYPE RSD01

POSITION:	O.SAPS 13 STORE (LARGE ITEMS)
LEVEL:	GROUND FLOOR
TYPE MARK:	RSD01
TYPE:	RSD01 - 2500 x 2100mm
DESCRIPTION:	2500 x 2100mm HIGHER HYDRO THUNDERSTORM ALUZINK ROLL-UP MANUALLY OPERATED GARAGE DOOR TO SUIT OPENING WITH 220mm WIDE NIBS TO BOTH SIDES, OPENING TO BE 2100mm CLEARANCE FROM HIGHEST POINT OF OPEN DOOR AND FLOOR, SUPPLIED AND INSTALLED ACCORDING TO MANUFACTURER'S RECOMMENDATIONS.
FIRE RATING:	TO MANUFACTURERS SPEC.
CONSTRUCTION TYPE:	WALL JAMBS CONTRACTOR TO CONFIRM PRIOR MANUFACTURING
FRAME TYPE:	AS SUPPLIED WITH DOOR
HEAD HEIGHT:	2100mm
COUNT:	1
IRONMONGERY:	REFER TO IRONMONGERY SCHEDULE

NOTE:DOOR HAND TO BE VERIFIED FOR EACH INDIVIDUAL DOOR AS PER FLOOR PLAN BY CONTRACTOR



TYPE ALSD01

POSITION:	C.BATHROOM
LEVEL:	GROUND FLOOR
TYPE MARK:	ALSD01
TYPE:	ALSD01-900 x 2040mm
DESCRIPTION:	ALUMINIUM FRAMED SHOWER PIVOT DOOR
FIRE RATING:	TO MANUFACTURERS SPEC.
CONSTRUCTION TYPE:	WALL JAMBS CONTRACTOR TO CONFIRM PRIOR MANUFACTURING
FRAME TYPE:	TO MANUFACTURERS SPEC.
HEAD HEIGHT:	2000mm
COUNT:	1
IRONMONGERY:	AS SUPPLIED WITH DOOR

NOTE:DOOR HAND TO BE VERIFIED FOR EACH INDIVIDUAL DOOR AS PER FLOOR PLAN BY CONTRACTOR



TYPE SF01D01

POSITION:	BOARDROOM
LEVEL:	GROUND FLOOR
TYPE MARK:	SF01D01
TYPE:	SF01D01- 1415 x 2365mm
DESCRIPTION:	1415 x 2365mm ALUMINIUM FRAMED DOUBLE SWINGING DOOR WITH FRAME OF SHOPFRONT, SIZES ACCORDING TO SCHEDULED DRAWINGS,GLAZED IN ACCORDANCE WITH SANS 10400 Part N SCHEDULE 1 AND SANS 10137:2011, FITTED WITH FRICTION STAYS, GLAZING BEADS WITH VINYL AND FINPILE SEALS PLUGGED AND SCREWES TO BRICKWORK OR CONCRETE, ALL IN ACCORDANCE WITH AAMSA SELECTION GUIDE FOR GLAZED ARCHITECTURAL ALUMINIUM PRODUCTS - JUNE 2008. COLOUR: CHARCOAL POWDERCOATED OR SIMILAR APPROVED SHOPFRONTS.
FIRE RATING:	TO MANUFACTURERS SPEC.
CONSTRUCTION TYPE:	WALL JAMBS CONTRACTOR TO CONFIRM PRIOR MANUFACTURING
FRAME TYPE:	TO MANUFACTURERS SPEC.
HEAD HEIGHT:	2365mm
COUNT:	1
IRONMONGERY:	REFER TO IRONMONGERY SCHEDULE

NOTE:DOOR HAND TO BE VERIFIED FOR EACH INDIVIDUAL DOOR AS PER FLOOR PLAN BY CONTRACTOR



TYPE SLD01

POSITION:	BOARDROOM
LEVEL:	GROUND FLOOR
TYPE MARK:	SLD01
TYPE:	SLD01- 1415 x 2365mm
DESCRIPTION:	1800 x 2032mm, POWDER COAT ALUMINIUM COATED SLIDING DOOR, DITTED WITH EXTERIOR THRESHOLD, WITH IRONMENGERY TO MANUFACTURER'S SPEC & DETAIL.
FIRE RATING:	TO MANUFACTURERS SPEC.
CONSTRUCTION TYPE:	WALL JAMBS CONTRACTOR TO CONFIRM PRIOR MANUFACTURING
FRAME TYPE:	TO MANUFACTURERS SPEC.
HEAD HEIGHT:	2040mm
COUNT:	1
IRONMONGERY:	AS SUPPLIED WITH DOOR

NOTE:DOOR HAND TO BE VERIFIED FOR EACH INDIVIDUAL DOOR AS PER FLOOR PLAN BY CONTRACTOR



TYPE SRD01

POSITION:	BROOM CLOSET, MAIN DB
LEVEL:	GROUND FLOOR
TYPE MARK:	SRD01
TYPE:	SRD01- 1250 x 1400mm
DESCRIPTION:	1250 x 1400 x 40mm (640mm AFFL) CUSTOM SEMI-SOLID DOUBLE TIMBER DOOR, WITH SURFACE PREPARED FOR PAINTING, PAINT COLOUR TO ARCHITECT'S SPEC AND APPROVAL
FIRE RATING:	TO MANUFACTURERS SPEC.
CONSTRUCTION TYPE:	WALL JAMBS CONTRACTOR TO CONFIRM PRIOR MANUFACTURING
FRAME TYPE:	CUSTOM 1.2MM DOUBLE REBATED RED-OXIDE DIPPED STEEL DOOR FRAME, WITH 2 HINGES TO ACCOMADATE 40MM THICK DOOR
HEAD HEIGHT:	2040mm
COUNT:	2
IRONMONGERY:	AS SUPPLIED WITH DOOR

NOTE:DOOR HAND TO BE VERIFIED FOR EACH INDIVIDUAL DOOR AS PER FLOOR PLAN BY CONTRACTOR



TYPE B/AD01

POSITION:	A. STATEMENT DRAFTING AREA AND A. WORK SPACE FRONT OF COUNTER
LEVEL:	GROUND FLOOR
TYPE MARK:	B/AD01
TYPE:	B/AD01 - 813 x 2030 mm
DESCRIPTION:	813 x 2030mm ARMOR PROOF LEAFED DOOR IN ACCORDANCE TO SAPS SECURITY UPGRADE GUIDELINES, INSTALLED BY SPECIALIST AND ACCORDING TO THE MANUFACTURER'S SPEC AND DETAIL WITH COMPLIANCE CERTIFICATE ISSUED AFTER INSTALLATION.COLOUR TO BE APPROVED BY ARCHITECT.
FIRE RATING:	TO MANUFACTURERS SPEC.
CONSTRUCTION TYPE:	WALL JAMBS CONTRACTOR TO CONFIRM PRIOR MANUFACTURING
FRAME TYPE:	SUPPILIED WITH DOOR
HEAD HEIGHT:	2030mm
COUNT:	2
IRONMONGERY:	REFER TO IRONMONGERY SCHEDULE

NOTE:DOOR HAND TO BE VERIFIED FOR EACH INDIVIDUAL DOOR AS PER FLOOR PLAN BY CONTRACTOR



TYPE P/D01

POSITION:	MIP WC, B. DISABLED WC.
LEVEL:	GROUND FLOOR
TYPE MARK:	P/D01
TYPE:	P/D01 - 915 x 2030 mm
DESCRIPTION:	915 x 2030 X 40mm THICK HOLLOWCORE DOOR AND KICKPLATE, DOOR MUST BE SUITABLE FOR PAINTING. PREPARE, SAND AND CLEAN. APPLY 1x COAT UNDERCOAT, SAND LIGHTLY. APPLY 2x COATS IN STRICT ACCORDANCE WITH MANUFACTURERS SPECIFICATIONS. SAND LIGHTLY BETWEEN COATS.COLOUR TO BE APPROVED BY ARCHITECT.
FIRE RATING:	TO MANUFACTURERS SPEC.
CONSTRUCTION TYPE:	WALL JAMBS CONTRACTOR TO CONFIRM PRIOR MANUFACTURING
FRAME TYPE:	SUPPILIED WITH DOOR
HEAD HEIGHT:	2030mm
COUNT:	2
IRONMONGERY:	IN ACCORDANCE TO THE LATEST SANS 10400-S

NOTE:DOOR HAND TO BE VERIFIED FOR EACH INDIVIDUAL DOOR AS PER FLOOR PLAN BY CONTRACTOR



TYPE AC/D01

POSITION:	CIRCULATION
LEVEL:	GROUND FLOOR
TYPE MARK:	AC/D01
TYPE:	AC/D01- 1250 x 2040 mm DOOR
DESCRIPTION:	1250 x 2040mm high EXTERNAL ALUMINIUM FRAMED ACCESS CONTROL DOUBLE DOOR TO MECH. ENG. SPEC AND DETAIL, FRAME TO BE POWDER COATED ALUMINIUM (CHARCOAL), GLAZING TO STRICTLY CONFORM TO SANS 204 SUPPLIED FENESTRATION CLCULATION SHEET, COMPLYING WITH SANS 10400XA
FIRE RATING:	TO MANUFACTURERS SPEC.
CONSTRUCTION TYPE:	230MM MASONRY WALL JAMBS CONTRACTOR TO CONFIRM PRIOR MANUFACTURING
FRAME TYPE:	POWDER COATED ALUMINIUM (CHARCOAL) TO SPECIALIST, COLOUR TO ARCHITECT'S APPROVAL
HEAD HEIGHT:	2040mm
COUNT:	4
IRONMONGERY:	REFER TO SCHEDULE

NOTE:DOOR HAND TO BE VERIFIED FOR EACH INDIVIDUAL DOOR AS PER FLOOR PLAN BY CONTRACTOR



TYPE G02

POSITION:	DUCT,
LEVEL:	GROUND FLOOR
TYPE MARK:	G02
TYPE:	GD1- REFER TO DWG A-630: GALVANIZED STEEL GATE, MADE TO FIT OPENING ON SITE. TYPE AND DESIGN AS PER DEVELOPER DETAILS
DESCRIPTION:	G02 - 813 x 2002mm HIGH GALVANIZED STEEL DOOR WITH SHEET CLADDING LAZER CUT TO MIMICK HIT AND MISS FACEBRICK DETAIL, MADE TO FIT OPENING ON SITE. TYPE AND DESIGN AS PER DEVELOPER DETAILS
FIRE RATING:	TO MANUFACTURERS SPEC.
CONSTRUCTION TYPE:	STEEL FRAME JAMBS, CONTRACTOR TO CONFIRM PRIOR MANUFACTURING
FRAME TYPE:	REFER TO DWG A-630: GALVANIZED STEEL GATE MADE TO FIT OPENING ON SITE. TYPE AND DESIGN AS PER DEVELOPER DETAILS
HEAD HEIGHT:	2000mm
COUNT:	1
IRONMONGERY:	REFER TO DWG A-630: GALVANIZED STEEL DOOR WITH VIEWING PANEL, MADE TO FIT OPENING ON SITE. TYPE AND DESIGN AS PER DEVELOPER DETAILS

Door schedule
1 : 50

REVISION SCHEDULE

REV	WORKS DESCRIPTION	DATE
D	STAGE 4.2 SUBMISSION FOR TENDER	2025 09 12
C	STAGE 4.2 SAPS SUBMISSION COMMENTS AFTER 07/22 ONLINE (MS TEAMS) MEETING	2025 07 29
B	STAGE 4.2 SUBMISSION COMMENTS	2025 04 02
A	STAGE 4.1 SUBMISSION	2024.08.23

FOR TENDER

A0

CLIENT/SERVICE:

BLOCK A,4TH FLOOR, ROOM 545
THE DIVISIONAL COMMISSIONER
SA POLICE SERVICE
117 CRESSWELL ROAD
SILVERTON
PRETORIA
0184

TEL: +27-12-845-8678

CONSULTANTS:

takgalang CONSULTING

SUITE 16C, FIRST FLOOR
HEUWELSIG OFFICE PARK
6763
SEEDCRACKER STREET
HEUWELSIG ESTATE
CENTURION

TEL: +27-12-656-8179

COPYRIGHT
THIS DRAWING IS PRIVATE PROPERTY AND MAY NOT BE COPIED OR REPRODUCED IN ANY MANNER WHATSOEVER WITHOUT THE OWNER'S WRITTEN CONSENT

DESCRIPTION
PROPOSED MARITE SAPS ON REMAINING EXTENT OF PORTION 1 OF THE FARM WATERVAL 273 KU

PROJECT NUMBER	19/1/9/1/72TB(22)	PROJECT NAME	MARITE SAPS	DRAWING NUMBER	A-600
CLIENT NAME	SAPS	DRAWING NAME	STATION BLOCK-DOOR SCHEDULES	DRAWING SCALE	1 : 50
WORK STAGE	4.2	BUILDING NAME	STATION BLOCK	DRAWING REVISION	D
DRAWING AUTHOR	DW	PROJECT LEADER	KSP	DRAWING DATE	2025 09 12