

Hydraulics Tender Clarification - Spares

Description	Specification
S3 Buffalo feeders	OUPLING, SHAFT: TYPE: ROTA FREE; BORE: 70 X 50 MM; OUTSIDE DIAMETER: 225 MM; LENGTH: 270 MM; MATERIAL: STL; MANUF P/N: 30-8526-RFC 45/80; REAMER TO SUIT SHAFT
S4 Buffalo feeders	CHAIN, CONVEYOR: TYPE: LH/RH; PITCH: 4 IN; WIDTH: 1 IN; MATERIAL: STAINLESS STEEL; LENGTH: 58 MM; APPLICATION: BUFFALO FEEDER; REFERENCE NO: 30-3427 HDM; CHAIN ASSEMBLIES WITH 47 FLIGHT BARS; TYPE: B520 RF - DCD RECLAIMER FEEDER; CHAIN SIZES: 4" (101.6MM) WIDTH: 1190 MM WITH FLIGHT BARS, STRANDS:2
Coal Stacker Reclaimer Inner bearing replacement	BEARING, ROLLER: TYPE: SPHERICAL; INSIDE DIAMETER: 320 MM; OUTSIDE DIAMETER: 480 MM; WIDTH: 121 MM; ROW: DOUBLE; BORE SHAPE: TAPER; STYLE: SELF RETAINING; CAGE MATERIAL: BRASS; ROLLING ELEMENT: ROLLER SPHERICAL; SPECIFICATION: DIN 623-1; DIN ISO 281/492/683-17; OEM P/N: 23064E1AKMB1C3
Machining and brushing of grid couplings	COUPLING, SHAFT HALF: TYPE: HUB; BORE: 239.85 X 250.85 MM; OUTSIDE DIAMETER: 445 MM; LENGTH: 220 MM; MATERIAL: STL; REFERENCE NO: 1170T; 1170T-HUB; CONSIST OF ONE HALF (GEARBOX SITE) 250.85MM; ONE HALF (PULLEY SITE) 239.85; KEYWAY: 56MM WIDE; 13MM DEPTH/HEIGHT; ADDITIONS: GRID SPRINGS STH2170 GSK; GRID HORIZONTAL COVER STH2170 CC; USED WITH FALK STEELFLEX COUPLING TYPE 170T; COUPLING MATERIAL DATASHEET FOR GRID COUPLING TO BE PROVIDED ON DELIVERY OF COUPLING.
Re-engineer Shiftable 25 p/block c/w bearings	BEARING, TAKE UP: INSIDE DIAMETER: 65 MM; HOUSING SIZE: WD 120 X LG 165 MM; SLOT WIDTH: 26 MM; FRAME: WD 165 X LG 220 MM; ROLLING ELEMENT: BALL; STYLE: SEALED; HOUSING MATERIAL: CI; REFERENCE NO: UCT213

Repair rescue equipment	All the rescue equipment is Holmatro Hydraulic pump, powered by petrol engine Spreaders, sheers, and rams
Fiber glass repairs-WTP	Insulation material in Square meter.
Repair RCS7 Cylinder	L-420MM, W-105MM, H-105MM, Piston head-55MM, Bore – 170MM
Repair RCH202 Cylinder	L-390MM, W-95MM, H-95MM, Piston head -50MM, Bore – 150MM
Repair 8 inch pneumatic cylinder	L-940MM, W-270MM, H-270MM, Piston head -175MM, Bore – 168MM
Repair 10 inch pneumatic cylinder	L-1030MM, W-322MM, H-322MM, Piston head -185MM, Bore – 280MM
Repair 4 inch pneumatic cylinder	L-355MM, W-110MM, H-110MM, Piston head -40MM, Bore – 215MM
Repair Reynek Cylinder (clarifies 10 inches)	L-1030MM, W-322MM, H-322MM, Piston head -185MM, Bore – 280MM
Repair Reynek Cylinder (sand filters 5 inches)	L-590MM, W-220MM, H-220MM, Piston head -45MM, Bore – 170MM
Repair Reynek Cylinder (Effluent samps 3 inches)	L-350MM, W-100MM, H-100MM, Piston head -40MM, Bore – 210MM