



NEC3 Supply Contract (SC3)

Between **ESKOM HOLDINGS SOC Ltd**
(Reg No. 2002/015527/30)

and [Insert at award stage]
(Reg No. _____)

for **SUPPLY AND DELIVERY OF SEALS, GASKETS, O-RINGS
AND PACKINGS FOR FIVE (5) YEARS AT KRIEL POWER
STATION ON AN "AS AND WHEN" REQUIRED BASIS.**

Contents:	No of pages
Part C1 Agreements & Contract Data	20
Part C2 Pricing Data	94
Part C3 Scope of Work	9

CONTRACT No. [Insert at award stage]

PART C1: AGREEMENTS & CONTRACT DATA

Contents:	No of pages
C1.1 Form of Offer and Acceptance	3
C1.2a Contract Data provided by the <i>Purchaser</i>	15
C1.2b Contract Data provided by the <i>Supplier</i>	2

C1.1 Form of Offer & Acceptance

Offer

The *Purchaser*, identified in the Acceptance signature block, has solicited offers to enter into a contract for the procurement of:

SUPPLY AND DELIVERY OF SEALS, GASKETS, O-RINGS AND PACKINGS FOR FIVE (5) YEARS AT KRIEL POWER STATION ON AN "AS AND WHEN" REQUIRED BASIS.

The tenderer, identified in the Offer signature block, has

<i>either</i>	examined the documents listed in the Tender Data and addenda thereto as listed in the Returnable Schedules, and by submitting this Offer has accepted the Conditions of Tender.
<i>or</i>	examined the draft contract as listed in the Acceptance section and agreed to provide this Offer.

By the representative of the tenderer, deemed to be duly authorised, signing this part of this Form of Offer and Acceptance the tenderer offers to perform all of the obligations and liabilities of the *Supplier* under the contract including compliance with all its terms and conditions according to their true intent and meaning for an amount to be determined in accordance with the *conditions of contract* identified in the Contract Data.

	The offered total of the Prices exclusive of VAT is	R [•]
	Value Added Tax @ 15% is	R [•]
	The offered total of the amount due inclusive of VAT is ¹	R [•]
	(in words) [•]	

This Offer may be accepted by the *Purchaser* by signing the Acceptance part of this Form of Offer and Acceptance and returning one copy of this document including the Schedule of Deviations (if any) to the tenderer before the end of the period of validity stated in the Tender Data, or other period as agreed, whereupon the tenderer becomes the party named as the *Supplier* in the *conditions of contract* identified in the Contract Data.

Signature(s)

Name(s)

Capacity

**For the
tenderer:**

(Insert name and address of organisation)

Name &
signature of
witness

Date

¹ This total is required by the *Purchaser* for budgeting purposes only. Actual amounts due will be assessed in terms of the *conditions of contract*.

Acceptance

By signing this part of this Form of Offer and Acceptance, the *Purchaser* identified below accepts the tenderer's Offer. In consideration thereof, the *Purchaser* shall pay the Supplier the amount due in accordance with the *conditions of contract* identified in the Contract Data. Acceptance of the tenderer's Offer shall form an agreement between the *Purchaser* and the tenderer upon the terms and conditions contained in this agreement and in the contract that is the subject of this agreement.

The terms of the contract, are contained in:

Part C1	Agreements and Contract Data, (which includes this Form of Offer and Acceptance)
Part C2	Pricing Data
Part C3	Scope of Work: Goods Information including Supply Requirements

and drawings and documents (or parts thereof), which may be incorporated by reference into the above listed Parts.

Deviations from and amendments to the documents listed in the Tender Data and any addenda thereto listed in the Returnable Schedules as well as any changes to the terms of the Offer agreed by the tenderer and the *Purchaser* during this process of offer and acceptance, are contained in the Schedule of Deviations attached to and forming part of this Form of Offer and Acceptance. No amendments to or deviations from said documents are valid unless contained in this Schedule.

The tenderer shall within two weeks of receiving a completed copy of this agreement, including the Schedule of Deviations (if any), contact the *Purchaser's* agent (whose details are given in the Contract Data) to arrange the delivery of any securities, bonds, guarantees, proof of insurance and any other documentation to be provided in terms of the *conditions of contract* identified in the Contract Data at, or just after, the date this agreement comes into effect. Failure to fulfil any of these obligations in accordance with those terms shall constitute a repudiation of this agreement.

Notwithstanding anything contained herein, this agreement comes into effect on the date when the tenderer receives one fully completed and signed original copy of this document, including the Schedule of Deviations (if any).

Signature(s)

Name(s)

Capacity

**for the
Purchaser**

**Eskom Holdings SOC Ltd, Megawatt Park, Maxwell Drive, Sandton, Johannesburg,
2199**

(Insert name and address of organisation)

Name &
signature of
witness

Date

Note: If a tenderer wishes to submit alternative tenders, use another copy of this Form of Offer and Acceptance.

Schedule of Deviations to be completed by the *Purchaser* prior to contract award

Note:

1. This part of the Offer & Acceptance would not be required if the contract has been developed by negotiation between the Parties and is not the result of a process of competitive tendering.
2. The extent of deviations from the tender documents issued by the Purchaser prior to the tender closing date is limited to those permitted in terms of the Conditions of Tender.
3. A tenderer's covering letter must not be included in the final contract document. Should any matter in such letter, which constitutes a deviation as aforesaid be the subject of agreement reached during the process of Offer and Acceptance, the outcome of such agreement shall be recorded here and the final draft of the contract documents shall be revised to incorporate the effect of it.

No.	Subject	Details
1	[•]	[•]
2	[•]	[•]
3	[•]	[•]
4	[•]	[•]
5	[•]	[•]
6	[•]	[•]
7	[•]	[•]

By the duly authorised representatives signing this Schedule of Deviations below, the *Purchaser* and the tenderer agree to and accept this Schedule of Deviations as the only deviations from and amendments to the documents listed in the Tender Data and any addenda thereto listed in the Tender Schedules, as well as any confirmation, clarification or changes to the terms of the Offer agreed by the tenderer and the *Purchaser* during this process of Offer and Acceptance.

It is expressly agreed that no other matter whether in writing, oral communication or implied during the period between the issue of the tender documents and the receipt by the tenderer of a completed signed copy of this Form shall have any meaning or effect in the contract between the parties arising from this Agreement.

For the tenderer:**For the *Purchaser***

Signature

Name

Capacity

On behalf
of

(Insert name and address of organisation)

**Eskom Holdings SOC Ltd, Megawatt
Park, Maxwell Drive, Sandton,
Johannesburg, 2199**
Name &
signature
of witness

Date

C1.2 SC3 Contract Data

Part one - Data provided by the *Purchaser*

Clause	Statement	Data
1	General	
	The <i>conditions of contract</i> are the core clauses and the clauses for Options	
		X1: Price adjustment for inflation X2: Changes in the law X7: Delay damages X17: Low performance damages Z: Additional conditions of contract
	of the NEC3 Supply Contract (April 2013) ¹	(If the December 2009 edition is to be used delete April 2013 and replace by December 2013)
10.1	The <i>Purchaser</i> is (name):	Eskom Holdings SOC Ltd (reg no: 2002/015527/30), a state owned company incorporated in terms of the company laws of the Republic of South Africa
	Address	Registered office at Megawatt Park, Maxwell Drive, Sandton, Johannesburg
	Tel No.	+27 11 871 3706
10.1	The <i>Supply Manager</i> is (name):	Samuel Mophuting
	Address	Eskom Holdings SOC Limited Kriel Power Station Generation, Group, Cluster 3 Ogies/Bethal Road, Kriel
	Tel	+27 17 615 2008
	e-mail	Mophutsp@eskom.co.za
11.2(13)	The <i>goods</i> are	Seals, Gaskets, O-rings and Packings
11.2(13)	The <i>services</i> are	Not applicable to this contract.
11.2(14)	The following matters will be included in the Risk Register	<ul style="list-style-type: none"> - Any matter that has cost implication outside agreed terms. - Any matter that may cause delay in the delivery. - Any quality related issues. - Any matter that deviates from the specification.

¹ Available from Engineering Contract Strategies Tel 011 803 3008 Fax 086 539 1902, www.ecs.co.za.

- Any force majeure issues such as protests, covid restrictions.

11.2(15)	The Goods Information is in	Part C3: Scope of Work	
11.2(15)	The Supply Requirements as part of the Goods Information is in	Annexure A (page 13-14)	
12.2	The <i>law of the contract</i> is the law of	the Republic of South Africa	
13.1	The <i>language of this contract</i> is	English	
13.3	The <i>period for reply</i> is	Within 24 hours after notification of communication.	
2	The <i>Supplier's</i> main responsibilities	Data required by this section of the core clauses is provided by the <i>Supplier</i> in Part 2 and terms in italics used in this section are identified elsewhere in this Contract Data.	
3	Time		
30.1	The <i>starting date</i> is.	Contract signature date (date of the last party signing the contract)	
30.1	The <i>delivery date</i> of the <i>goods and services</i> is:	<i>goods and services</i>	<i>delivery date</i>
		1	Seals, Gaskets, O-rings and Packings
			As per the purchase order date.
30.2	The <i>Supplier</i> does not bring the <i>goods</i> to the Delivery Place more than one week before the Delivery Date.	[no data required]	
31.1	The <i>Supplier</i> is to submit a first programme for acceptance within	within two (2) days after order placement and to fit within the delivery times after order placement as per 30.1	
32.2	The <i>Supplier</i> submits revised programmes at intervals no longer than	Two (2) working days following the accepted revision to the first programme and the delivery times after order placement as per 30.1	
4	Testing and defects		
42	The <i>defects date</i> is	4 weeks after installation in a plant	
43.2	The <i>defect correction period</i> is	2 days Seals, Gaskets, O-rings and Packings	
	except that the <i>defect correction period</i> for	Purchaser's fault is 3 days	
	and the <i>defect correction period</i> for	Not applicable	
42.2	The <i>defects access period</i> is	1 day after notification	
	except that the <i>defect access period</i> for	Purchaser's fault is 2 days	
	and the <i>defect access period</i> for	Not Applicable	

5	Payment	
50.1	The <i>assessment interval</i> is	Within a week after the delivery and acceptance of goods.
51.1	The <i>currency of this contract</i> is the	South African Rand
51.2	The period within which payments are made is	4 weeks.
51.4	The <i>interest rate</i> is	<p>the publicly quoted prime rate of interest (calculated on a 365 day year) charged from time to time by the Standard Bank of South Africa Limited (as certified, in the event of any dispute, by any manager of such bank, whose appointment it shall not be necessary to prove) for amounts due in Rands and</p> <p>(ii) the LIBOR rate applicable at the time for amounts due in other currencies. LIBOR is the 6 month London Interbank Offered Rate quoted under the caption "Money Rates" in The Wall Street Journal for the applicable currency or if no rate is quoted for the currency in question then the rate for United States Dollars, and if no such rate appears in The Wall Street Journal then the rate as quoted by the Reuters Monitor Money Rates Service (or such service as may replace the Reuters Monitor Money Rates Service) on the due date for the payment in question, adjusted <i>mutatis mutandis</i> every 6 months thereafter and as certified, in the event of any dispute, by any manager employed in the foreign exchange department of The Standard Bank of South Africa Limited, whose appointment it shall not be necessary to prove.</p>
6	Compensation events	There is no reference to Contract Data in this section of the core clauses and terms in italics used in this section are identified elsewhere in this Contract Data.
7	Title	There is no reference to Contract Data in this section of the core clauses and terms in italics used in this section are identified elsewhere in this Contract Data.
8	Risks, liabilities, indemnities and insurance	
80.1	These are additional <i>Purchaser's</i> risks	<p>1. Early depletion of contracts funds due to high spares consumption than planned.</p> <p>2. Non-adherence to agreed/ delivery target timelines dates.</p>
88.1	The <i>Supplier's</i> liability to the <i>Purchaser</i> for indirect or consequential loss, including loss of profit, revenue and goodwill is limited to	R0.0 (zero Rand)

88.2	For any one event, the <i>Supplier's</i> liability to the <i>Purchaser</i> for loss of or damage to the <i>Purchaser's</i> property is limited to	<p>(1) for the <i>Purchaser's</i> existing and surrounding property in the care, custody and control of the <i>Supplier</i> the amount of the deductible (first amount payable) relevant to the event and</p> <p>(2) for all other existing <i>Purchaser's</i> property the applicable deductible as at contract date</p>
88.3	The <i>Supplier's</i> liability for Defects due to his design which are not notified before the last <i>defects date</i> is limited to:	The total of the Prices
88.4	The <i>Supplier's</i> total liability to the <i>Purchaser</i> , for all matters arising under or in connection with this contract, other than the excluded matters, is limited to	The total of the Prices
88.5	The <i>end of liability date</i> is	A month after the contract end date
9	Termination and dispute resolution	
94.1	The <i>Adjudicator</i> is	the person selected from the ICE-SA Division (or its successor body) of the South African Institution of Civil Engineering Panel of Adjudicators by the Party intending to refer a dispute to him. (see www.ice-sa.org.za). If the Parties do not agree on an Adjudicator the Adjudicator will be appointed by the Arbitration Foundation of Southern Africa (AFSA).
	Address	To be known once the dispute arises
	Tel No.	To be known once the dispute arises
	Fax No.	To be known once the dispute arises
	e-mail	To be known once the dispute arises
94.2(3)	The <i>Adjudicator nominating body</i> is:	the Chairman of ICE-SA, a Division of the South African Institution of Civil Engineering, or its successor body (See www.ice-sa.org.za)
94.4(2)	The <i>tribunal</i> is:	arbitration
94.4(5)	The <i>arbitration procedure</i> is	the latest edition of Rules for the Conduct of Arbitrations published by The Association of Arbitrators (Southern Africa) or its successor body.
94.4(5)	The place where arbitration is to be held is	South Africa
	The person or organisation who will choose an arbitrator	
	- if the Parties cannot agree a choice or	
	- if the arbitration procedure does not state who selects an arbitrator, is	the <i>Chairman</i> for the time being or his nominee of the Association of <i>Arbitrators</i> (Southern Africa) or its successor body.

10	Data for Option clauses			
X1	Price adjustment for inflation			
X1.1	The <i>base date</i> for indices is	Month prior the starting date of the contract		
	The proportions used to calculate the Price Adjustment Factor are:	proportion	linked to index for	Index prepared by
		0.65	Labour Table C-3	SEIFSA
		0.20	Transport Table 1(A)	SEIFSA
		0.15	non-adjustable	
		1.00		
X2	Changes in the law			
X2.1	A change in the law of	South Africa is a compensation event if it occurs after the Contract Date		
X7	Delay damages			
X7.1	Delay damages for Delivery are	Delivery of	amount per day	
		Seals, Gaskets, O-rings and Packings	10% per day of the total purchase order value	
X17	Low performance damages			
X17.1	The amounts for low performance damages are:	Amount	performance level	
		10% of the total purchase order value	For material that does not meet the quality required. (Material not working as specified)	
		10% of the total purchase order value	Not adhering to the Safety, Health and Environmental requirements.	
Z	The <i>additional conditions of contract</i> are			
	Z1 to Z15 always apply for Eskom			

Z1 Cession delegation and assignment

- Z1.1 The *Supplier* does not cede, delegate or assign any of its rights or obligations to any person without the written consent of the *Purchaser*.
- Z1.2 Notwithstanding the above, the *Purchaser* may on written notice to the *Supplier* cede and delegate its rights and obligations under this contract to any of its subsidiaries or any of its present divisions or operations which may be converted into separate legal entities as a result of the restructuring of the Electricity Supply Industry.

Z2 Joint ventures

- Z2.1 If the *Supplier* constitutes a joint venture, consortium or other unincorporated grouping of two or more persons or organisations then these persons or organisations are deemed to be jointly and severally liable to the *Purchaser* for the performance of this contract.
- Z2.2 Unless already notified to the *Purchaser*, the persons or organisations notify the *Supply Manager* within two weeks of the Contract Date of the key person who has the authority to bind the *Supplier* on their behalf.
- Z2.3 The *Supplier* does not alter the composition of the joint venture, consortium or other unincorporated grouping of two or more persons without the consent of the *Purchaser* having been given to the *Supplier* in writing.

Z3 Change of Broad Based Black Economic Empowerment (B-BBEE) status

- Z3.1 Where a change in the *Supplier's* legal status, ownership or any other change to his business composition or business dealings results in a change to the *Supplier's* B-BBEE status, the *Supplier* notifies the *Purchaser* within seven days of the change.
- Z3.2 The *Supplier* is required to submit an updated verification certificate and necessary supporting documentation confirming the change in his B-BBEE status to the *Supply Manager* within thirty days of the notification or as otherwise instructed by the *Supply Manager*.
- Z3.3 Where, as a result, the *Supplier's* B-BBEE status has decreased since the Contract Date the *Purchaser* may either re-negotiate this contract or alternatively, terminate the *Supplier's* obligation to Provide the Goods and Services.
- Z3.4 Failure by the *Supplier* to notify the *Purchaser* of a change in its B-BBEE status may constitute a reason for termination. If the *Purchaser* terminates in terms of this clause, the procedures on termination are P1, P2 and P3 as stated in clause 92, and the amount due is A1 and A3 as stated in clause 93.

Z4 Confidentiality

- Z4.1 The *Supplier* does not disclose or make any information arising from or in connection with this contract available to Others. This undertaking does not, however, apply to information which at the time of disclosure or thereafter, without default on the part of the *Supplier*, enters the public domain or to information which was already in the possession of the *Supplier* at the time of disclosure (evidenced by written records in existence at that time). Should the *Supplier* disclose information to Others in terms of clause 23.1, the *Supplier* ensures that the provisions of this clause are complied with by the recipient.
- Z4.2 If the *Supplier* is uncertain about whether any such information is confidential, it is to be regarded as such until notified otherwise by the *Supply Manager*.
- Z4.3 In the event that the *Supplier* is, at any time, required by law to disclose any such information which is required to be kept confidential, the *Supplier*, to the extent permitted by law prior to disclosure, notifies the *Purchaser* so that an appropriate protection order and/or any other action can be taken if possible, prior to any disclosure. In the event that such protective order is not, or cannot, be obtained, then the *Supplier* may disclose that portion of the information which it is required to be disclosed by law and uses reasonable efforts to obtain assurances that confidential treatment will be afforded to the information so disclosed.
- Z4.4 The taking of images (whether photographs, video footage or otherwise) of the *goods* or any portion thereof, in the course of Providing the Goods and Services and after Delivery, requires the prior written consent of the *Supply Manager*. All rights in and to all such images vests exclusively in the *Purchaser*.

Z4.5 The *Supplier* ensures that all his subcontractors abide by the undertakings in this clause.

Z5 Waiver and estoppel: Add to core clause 12.3:

Z5.1 Any extension, concession, waiver or relaxation of any action stated in this contract by the Parties, the *Supply Manager* or the *Adjudicator* does not constitute a waiver of rights, and does not give rise to an estoppel unless the Parties agree otherwise and confirm such agreement in writing.

Z6 Health, safety and the environment: Add to core clause 25.4

Z6.1 The *Supplier* undertakes to take all reasonable precautions to maintain the health and safety of persons in and about the provision of the *goods* and execution of the *services*.

Without limitation the *Supplier*:

- warrants that the total of the Prices as at the Contract Date includes a sufficient amount for proper compliance with all applicable health & safety laws and regulations and the health and safety rules, guidelines and procedures provided for in this contract and generally for the proper maintenance of health & safety in and about the execution of supply and
- undertakes, in and about the execution of the supply, to comply with all applicable health & safety laws and regulations and rules, guidelines and procedures otherwise provided for under this contract and ensures that his Subcontractors, employees and others under the *Supplier's* direction and control, likewise observe and comply with the foregoing.

Z6.2 The *Supplier*, in and about the execution of the supply, complies with all applicable environmental laws and regulations and rules, guidelines and procedures otherwise provided for under this contract and ensures that his Subcontractors, employees and others under the *Supplier's* direction and control, likewise observe and comply with the foregoing.

Z7 Provision of a Tax Invoice and interest. Add to core clause 51

Z7.1 Within one week of receiving a payment certificate from the *Supply Manager* in terms of core clause 51.1, the *Supplier* provides the *Purchaser* with a tax invoice in accordance with the *Purchaser's* procedures stated in the Goods Information, showing the amount due for payment equal to that stated in the payment certificate.

Z7.2 If the *Supplier* does not provide a tax invoice in the form and by the time required by this contract, the time by when the *Purchaser* is to make a payment is extended by a period equal in time to the delayed submission of the correct tax invoice. Interest due by the *Purchaser* in terms of core clause 51.2 is then calculated from the delayed date by when payment is to be made.

Z7.3 The *Supplier* (if registered in South Africa in terms of the companies Act) is required to comply with the requirements of the Value Added Tax Act, no 89 of 1991 (as amended) and to include the *Purchaser's* VAT number 4740101508 on each invoice he submits for payment.

Z8 Notifying compensation events

Z8.1 Delete from the last sentence in core clause 61.3 the words, "unless the event arises from the *Supply Manager* giving an instruction, changing an earlier decision or correcting an assumption".

Z9 Purchaser's limitation of liability

Z9.1 The *Purchaser's* liability to the *Supplier* for the *Supplier's* indirect or consequential loss is limited to R0.00 (zero Rand)

Z9.2 The *Supplier's* entitlement under the indemnity in 83.1 is provided for in 60.1(12) and the *Purchaser's* liability under the indemnity is limited.

Z10 Termination: Add to core clause 91.1, at the second main bullet point, fourth sub-bullet point, after the words "against it":

Z10.1 or had a business rescue order granted against it.

Z11 Addition to secondary Option X7 Delay damages (if applicable in this contract)

Z11.1 If the amount due for the *Supplier's* payment of delay damages reaches the limits stated in this Contract Data for Option X7, the *Purchaser* may terminate the *Supplier's* obligation to Provide the Goods and Services using the same procedures and payment on termination as those applied for reasons R1 to R15 or R18 stated in the Termination Table.

Z12 Ethics

For the purposes of this Z-clause, the following definitions apply:

Affected Party	means, as the context requires, any party, irrespective of whether it is the <i>Supplier</i> or a third party, such party's employees, agents, or Subcontractors or Subcontractor's employees, or any one or more of all of these parties' relatives or friends,
Coercive Action	means to harm or threaten to harm, directly or indirectly, an Affected Party or the property of an Affected Party, or to otherwise influence or attempt to influence an Affected Party to act unlawfully or illegally,
Collusive Action	means where two or more parties co-operate to achieve an unlawful or illegal purpose, including to influence an Affected Party to act unlawfully or illegally,
Committing Party	means, as the context requires, the <i>Supplier</i> , or any member thereof in the case of a joint venture, or its employees, agents, or Subcontractors or the Subcontractor's employees,
Corrupt Action	means the offering, giving, taking, or soliciting, directly or indirectly, of a good or service to unlawfully or illegally influence the actions of an Affected Party,
Fraudulent Action	means any unlawfully or illegally intentional act or omission that misleads, or attempts to mislead, an Affected Party, in order to obtain a financial or other benefit or to avoid an obligation or incurring an obligation,
Obstructive Action	means a Committing Party unlawfully or illegally destroying, falsifying, altering or concealing information or making false statements to materially impede an investigation into allegations of Prohibited Action, and
Prohibited Action	means any one or more of a Coercive Action, Collusive Action Corrupt Action, Fraudulent Action or Obstructive Action.

Z12.1 A Committing Party may not take any Prohibited Action during the course of the procurement of this contract or in execution thereof.

Z12.2 The *Purchaser* may terminate the *Supplier's* obligation to Provide the Services if a Committing Party has taken such Prohibited Action and the *Supplier* did not take timely and appropriate action to prevent or remedy the situation, without limiting any other rights or remedies the *Purchaser* has. It is not required that the Committing Party had to have been found guilty, in

court or in any other similar process, of such Prohibited Action before the *Purchaser* can terminate the *Supplier's* obligation to Provide the Services for this reason.

Z12.3 If the *Purchaser* terminates the *Supplier's* obligation to Provide the Services for this reason, the amounts due on termination are those intended in core clauses 92.1 and 92.2.

Z12.4 A Committing Party co-operates fully with any investigation pursuant to alleged Prohibited Action. Where the *Purchaser* does not have a contractual bond with the Committing Party, the *Supplier* ensures that the Committing Party co-operates fully with an investigation.

Z13Insurance

Z 13.1 Replace core clause 84 with the following:

Insurance cover 84

84.1 When requested by a Party, the other Party provides certificates from his insurer or broker stating that the insurances required by this contract are in force.

84.2 The *Supplier* provides the insurances stated in the Insurance Table A for events which are at the *Supplier's* risk from the *starting date* until the last *defects date* or a termination certificate has been issued.

INSURANCE TABLE A

Insurance against	Minimum amount of cover or minimum limit of indemnity
Loss of or damage to the <i>goods</i> , plant and materials	The replacement cost where not covered by the <i>Purchaser's</i> insurance. The <i>Purchaser's</i> policy deductible as at Contract Date, where covered by the <i>Purchaser's</i> insurance.
Liability for loss of or damage to property (except the <i>goods</i> , plant and materials and equipment) and liability for bodily injury to or death of a person (not an employee of the <i>Supplier</i>) caused by activity in connection with this contract	<u>Loss of or damage to property</u> <u>Purchaser's property</u> The replacement cost where not covered by the <i>Purchaser's</i> insurance. The <i>Purchaser's</i> policy deductible as at Contract Date, where covered by the <i>Purchaser's</i> insurance. <u>Other property</u> The replacement cost <u>Death of or bodily injury</u> The amount required by the applicable law.
Liability for death of or bodily injury to employees of the <i>Supplier</i> arising out of and in the course of their employment in connection with this contract	The amount required by the applicable law

Z 13.2 Replace core clause 87 with the following:**Insurance by the *Purchaser***

87

87.1 The *Purchaser* provides the insurances stated in the Insurance Table B**INSURANCE TABLE B**

Insurance against or name of policy	Minimum amount of cover or minimum of indemnity
Assets All Risk	Per the insurance policy document
Contract Works insurance	Per the insurance policy document
Environmental Liability	Per the insurance policy document
General and Public Liability	Per the insurance policy document
Transportation (Marine)	Per the insurance policy document
Motor Fleet and Mobile Plant	Per the insurance policy document
Terrorism	Per the insurance policy document
Cyber Liability	Per the insurance policy document
Nuclear Material Damage and Business Interruption	Per the insurance policy document

Nuclear Material Damage Terrorism	Per the insurance policy document
--------------------------------------	-----------------------------------

Z14 Nuclear Liability

- Z14.1 The *Purchaser* is the operator of the Koeberg Nuclear Power Station (KNPS), a nuclear installation, as designated by the National Nuclear Regulator of the Republic of South Africa, and is the holder of a nuclear licence in respect of the KNPS.
- Z14.2 The *Purchaser* is solely responsible for and indemnifies the *Supplier* or any other person against any and all liabilities which the *Supplier* or any person may incur arising out of or resulting from nuclear damage, as defined in Act 47 of 1999, save to the extent that any liabilities are incurred due to the unlawful intent of the *Supplier* or any other person or the presence of the *Supplier* or that person or any property of the *Supplier* or such person at or in the KNPS or on the KNPS site, without the permission of the *Purchaser* or of a person acting on behalf of the *Purchaser*.
- Z14.3 Subject to clause Z14.4 below, the *Purchaser* waives all rights of recourse, arising from the aforesaid, save to the extent that any claims arise or liability is incurred due or attributable to the unlawful intent of the *Supplier* or any other person, or the presence of the *Supplier* or that person or any property of the *Supplier* or such person at or in the KNPS or on the KNPS site, without the permission of the *Purchaser* or of a person acting on behalf of the *Purchaser*.
- Z14.4 The *Purchaser* does not waive its rights provided for in section 30 (7) of Act 47 of 1999, or any replacement section dealing with the same subject matter.
- Z14.5 The protection afforded by the provisions hereof shall be in effect until the KNPS is decommissioned.

Z15 Asbestos

For the purposes of this Z-clause, the following definitions apply:

AAIA	means approved asbestos inspection authority.
ACM	means asbestos containing materials.
AL	means action level, i.e. a level of 50% of the OEL, i.e. 0.1 regulated asbestos fibres per ml of air measured over a 4 hour period. The value at which proactive actions is required in order to control asbestos exposure to prevent exceeding the OEL.
Ambient Air	means breathable air in area of work with specific reference to breathing zone, which is defined to be a virtual area within a radius of approximately 30cm from the nose inlet.
Compliance Monitoring	means compliance sampling used to assess whether or not the personal exposure of workers to regulated asbestos fibres is in compliance with the Standard's requirements for safe processing, handling, storing, disposal and phase-out of asbestos and asbestos containing material, equipment and articles.
OEL	means occupational exposure limit.
Parallel Measurements	means measurements performed in parallel, yet separately, to existing measurements to verify validity of results.
Safe Levels	means airborne asbestos exposure levels conforming to the Standard's

requirements for safe processing, handling, storing, disposal and phase-out of asbestos and asbestos containing material, equipment and articles.

Standard means the *Purchaser's* Asbestos Standard 32-303: Requirements for Safe Processing, Handling, Storing, Disposal and Phase-out of Asbestos and Asbestos Containing Material, Equipment and Articles.

SANAS means the South African National Accreditation System.

TWA means the average exposure, within a given workplace, to airborne asbestos fibres, normalised to the baseline of a 4 hour continuous period, also applicable to short term exposures, i.e. 10-minute TWA.

Z15.1 The *Purchaser* ensures that the Ambient Air in the area where the *Supplier* will Provide the Services conforms to the acceptable prescribed South African standard for asbestos, as per the regulations published in GNR 155 of 10 February 2002, under the Occupational Health and Safety Act, 1993 (Act 85 of 1993) ("Asbestos Regulations"). The OEL for asbestos is 0.2 regulated asbestos fibres per millilitre of air as a 4-hour TWA, averaged over any continuous period of four hours, and the short term exposure limit of 0.6 regulated asbestos fibres per millilitre of air as a 10-minute TWA, averaged over any 10 minutes, measured in accordance with HSG248 and monitored according to HSG173 and OESSM.

Z15.2 Upon written request by the *Supplier*, the *Purchaser* certifies that these conditions prevail. All measurements and reporting are effected by an independent, competent, and certified occupational hygiene inspection body, i.e. a SANAS accredited and Department of Employment and Labour approved AAIA. The *Supplier* may perform Parallel Measurements and related control measures at the *Supplier's* expense. For the purposes of compliance the results generated from Parallel Measurements are evaluated only against South African statutory limits as detailed in clause Z15.1. Control measures conform to the requirements stipulated in the AAIA-approved asbestos work plan.

Z15.3 The *Purchaser* manages asbestos and ACM according to the Standard.

Z15.4 In the event that any asbestos is identified while Providing the Services, a risk assessment is conducted and if so required, with reference to possible exposure to an airborne concentration of above the AL for asbestos, immediate control measures are implemented and relevant air monitoring conducted in order to declare the area safe.

Z15.5 The *Supplier's* personnel are entitled to stop working and leave the contaminated area forthwith until such time that the area of concern is declared safe by either Compliance Monitoring or an AAIA approved control measure intervention, for example, per the emergency asbestos work plan, if applicable.

Z15.6 The *Supplier* continues to Provide the Services, without additional control measures presented, on presentation of Safe Levels. The contractually agreed dates to Provide the Services, including the Completion Date, are adjusted accordingly. The contractually agreed dates are extended by the notification periods required by regulations 3 and 21 of the Asbestos Regulations.

Z15.7 Any removal and disposal of asbestos, asbestos containing materials and waste, is done by a registered asbestos contractor, instructed by the *Purchaser* at the *Purchaser's* expense, and conducted in line with South African legislation.

Annexure A: Supply Requirements

[Notes: The example given in the NEC3 Supply Contract Guidance Notes pages 15 to 20 inclusive is based on Incoterms 2000. However users will probably wish to use Incoterms 2010 which the details below are based on. Users may need to adjust the information to comply with actual requirements. First decide whether Incoterms will be used or not, then delete the arrangement below which does not apply and delete these notes]

The Supply Requirements for this contract are based on the use of INCOTERMS:

The *Supplier* supplies the *goods* in accordance with INCOTERMS 2010² as follows:

[Select the group and then term within the group which applies and state the applicable delivery place. Delete all the other groups and this note]

Group	Category	Term	Delivery Place
E	departure	EXW	
F	main carriage unpaid	FCA, FAS, FOB	
C	main carriage paid	CFR, CIF, CPT, CIP	
D	arrival	DAT, DAP, DDP	

The Parties obligations described in Incoterms for the category and term selected are now incorporated into this contract as part of the Supply Requirements and hence the Goods Information.

The obligations of seller and buyer for the selected Incoterm determine each Party's costs, risks and insurance requirements incidental to the supply and transport of the *goods* from *Supplier* to *Purchaser*.

For each of the thirteen terms, Incoterms set out obligations of the seller (the *Supplier*) in ten paragraphs identified as A1 to A10 and the corresponding obligations of the buyer (the *Purchaser*) in paragraphs B1 to B10. These obligations cover the following subjects:

A	The <i>Supplier's</i> obligations	B	The <i>Purchaser's</i> obligations
A1	Provision of goods in conformity with contract	B1	Payment of the price
A2	Licences, authorisations and formalities	B2	Licences, authorisations and formalities
A3	Contracts of carriage and insurance	B3	Contracts of carriage and insurance
A4	Delivery	B4	Taking delivery
A5	Transfer of risks	B5	Transfer of risks
A6	Division of costs	B6	Division of costs
A7	Notice to the buyer	B7	Notice to the seller
A8	Proof of delivery, transport document or equivalent electronic message	B8	Proof of delivery, transport document or equivalent electronic message
A9	Checking - packing - marking	B9	Inspection of goods
A10	Other obligations	B10	Other obligations

[Should there be a need to amplify any of the published obligations listed above for the chosen INCOTERM, add them here.]

All other information NOT pertinent to the above is given in the balance of the Goods Information

² International Chamber of Commerce, Incoterms 2010, Paris, January 2011

The Supply Requirements for this contract are as follows:

[Use these when INCOTERMS do not apply].

1. The requirements for the supply are	[State the constraints on how the <i>Supplier</i> manufactures, prototypes, tests and stores the <i>goods</i> including order and timing]	
2. The requirements for transport are	[State the extent to which the <i>Supplier</i> transports the <i>goods</i> and the mode of transport]	
3. The delivery place is	[State the location where the <i>goods</i> are to be placed by the <i>Supplier</i> , such as whether it is a dispatch department at the <i>Supplier's</i> premises, the <i>Purchaser</i> is to collect or other location the <i>Purchaser</i> may require. If the delivery place for the <i>services</i> is different to the <i>goods</i> state it here]	
4. Actions of the Parties during supply	Action	Party which does it
	Giving notice of Delivery	
	Checking packing and marking before dispatch	
	Contracting for transport	
	Pay costs of transport	
	Arrange access to delivery place	
	Loading the <i>goods</i>	
	Unloading the <i>goods</i>	
For international procurement	Undertake export requirements	
	Undertake import requirements	
5. Information to be provided by the <i>Supplier</i>	Title of document	
	Packing lists for cases and their contents	
	Copy of invoice for the <i>goods</i>	
	Delivery Note	
	Test results and maintenance manuals	
For international procurement	Licences, authorisations and other formalities associated with export of the <i>goods</i>	
	Air Waybill or Bill of Lading with associated landing, delivery and forwarding order	
	The Bill of Entry endorsed by the importation authority	
	Customs work sheets, showing tax, duties and surcharges which the law of the country into which the <i>goods</i> are being imported requires the importer to pay	
	Invoice from the importation clearing agent showing airline fees, landing charges, wharfage and dock dues as applicable	
	Specify other import documents required by authorised officials.	

All other information NOT pertinent to the above is given in the balance of the Goods Information

C1.2 Contract Data

Part two - Data provided by the *Supplier*

[Instructions to the contract compiler: (delete this note before issue to tenderers with an enquiry)

Whenever a cell is shaded in the left hand column it denotes this data is optional and would be required in relation to the option selected. In the event that the option is not required select and delete the whole row.]

Notes to a tendering supplier:

1. Please read both the NEC3 Supply Contract (SC3)¹ and the relevant parts of its Guidance Notes (SC3-GN)² in order to understand the implications of this Data which the tenderer is required to complete.
2. The number of the clause which requires the data is shown in the left hand column for each statement however other clauses may also use the same data
3. Where a form field like this [] appears, data is required to be inserted relevant to the option selected. Click on the form field **once** and type in the data. Otherwise complete by hand and in ink.

Completion of the data in full, according to Options chosen, is essential to create a complete contract.

Clause	Statement	Data												
10.1	The <i>Supplier</i> is (Name): Address Tel No. Fax No.													
11.2(8)	The Goods Information for the <i>Supplier's</i> design is in:													
11.2(11)	The tendered total of the Prices is	R , (in words)												
11.2(12)	The <i>price schedule</i> is in:													
11.2(14)	The following matters will be included in the Risk Register													
25.2	The restrictions to access for the <i>Supply Manager</i> and Others to work being done for this contract are													
30.1	The <i>delivery date</i> of the <i>goods and services</i> is:	<table><thead><tr><th></th><th><i>goods and services</i></th><th><i>delivery date</i></th></tr></thead><tbody><tr><td>1</td><td>[•]</td><td>[•]</td></tr><tr><td>2</td><td>[•]</td><td>[•]</td></tr><tr><td>3</td><td>[•]</td><td>[•]</td></tr></tbody></table>		<i>goods and services</i>	<i>delivery date</i>	1	[•]	[•]	2	[•]	[•]	3	[•]	[•]
	<i>goods and services</i>	<i>delivery date</i>												
1	[•]	[•]												
2	[•]	[•]												
3	[•]	[•]												
31.1	The programme identified in the Contract Data is contained in:													

¹ Either April 2013 or December 2009 Edition as stated by *Purchaser* in Contract Data part 1.

² Available from Engineering Contract Strategies Tel 011 803 3008, Fax 086 539 1902, or www.ecs.co.za

63.2

The *percentage for overheads and profit*
added to the Defined Cost is

%

PART 2: PRICING DATA

NEC3 Supply Contract

Document reference	Title	No of pages
	This cover page.	1
C2.1	Pricing assumptions	2
C2.2	The <i>price schedule</i>	91

C2.1 Pricing assumptions

1. How *goods* and *services* are priced and assessed for payment

Clause 11 in NEC3 Supply Contract, (SC3) core clauses states:

Identified and defined terms	11	
	11.2	(11) The Prices are the amounts stated in the price column of the Price Schedule. Where a quantity is stated for an item in the Price Schedule, the Price is calculated by multiplying the quantity by the rate.
		(12) The Price Schedule is the <i>price schedule</i> unless later changed in accordance with this contract.
Assessing the amount due	50.2	The amount due is
		<ul style="list-style-type: none"> the Price for each lump sum item in the Price Schedule which the <i>Supplier</i> has completed, where a quantity is stated for an item in the Price Schedule, an amount calculated by multiplying the quantity which the <i>Supplier</i> has completed by the rate, plus other amounts to be paid to the <i>Supplier</i>, less amounts to be paid by or retained from the <i>Supplier</i>. <p>Any tax which the law requires the <i>Purchaser</i> to pay to the <i>Supplier</i> is included in the amount due.</p>

This confirms that the Supply Contract is a priced contract where the Prices are derived from a list of items of *goods* and *services* which can be priced as lump sums or as expected quantities of *goods* and *services* multiplied by a rate, or a mix of both.

2. Function of the Price Schedule

Clause 53.1 states: "Information in the Price Schedule is not Goods Information". This confirms that instructions to do work or how it is to be done are not included in the Price Schedule but in the Goods Information. This is further confirmed by Clause 20.1 which states, "The *Supplier* Provides the Goods and Services in accordance with the Goods Information". Hence the *Supplier* does **not** Provide the Goods and Services in accordance with the Price Schedule. The Price Schedule is only a pricing document.

3. Preparing the *price schedule*

Items in the *price schedule* may have been inserted by the *Purchaser* and the tendering supplier should insert any additional items which he considers necessary. Whichever party provides the items in the *price schedule* the total of the Prices is assumed to be fully inclusive of everything necessary to Provide the Goods and Services as described at the time of entering into this contract.

It will be assumed that the tendering supplier has

- Read Pages 8, 11, 12 and Appendix 5 of the SC3 Guidance Notes before preparing the *price schedule*;
- Included in his Prices and rates for correction of Defects (core clause 43.1) as there is no compensation event for this unless the Defect is due to a *Supplier's* risk;

- Spread the cost of doing work he chooses not to list as separate items in the *price schedule* across other Prices and rates in order to fulfil the obligation to Provide the Goods and Services for the tendered total of the Prices;
- Understood that there is no adjustment to lump sum prices in the *price schedule* if the amount, or quantity, of work within that lump sum item later turns out to be different to that which the *Supplier* estimated at time of tender. The only basis for a change to the Prices is as a result of a compensation event per clause 60.1;
- Understood that the *Supplier* does not have to allow in his Prices and rates for matters that may arise as a result of a compensation event.

3.1. Format of the *price schedule*

Entries in the first four columns in the *price schedule* in section C2.2 are made either by the *Purchaser* or the tendering supplier.

If the *Supplier* is to be paid an amount for the item which is not adjusted if the quantity of work in the item changes, the tendering supplier enters the amount in the Price column only, the Unit, Quantity and Rate columns being left blank.

If the *Supplier* is to be paid an amount for the item which is the rate for the item multiplied by the quantity completed, the tendering *Supplier* enters the rate which is then multiplied by the Quantity to produce the Price, which is also entered.

If the *Supplier* is to be paid an amount for an item proportional to the length of time for which the *goods* and *services* are provided, a unit of time is stated in the Unit column and the length of time (as a quantity of the stated units of time) is stated in the Quantity column.

C2.2 the *price schedule*

SUPPLY AND DELIVERY OF GASKETS, PACKINGS, SEALS & O-RINGS ON AS WHEN REQUIRED BASIS AT KRIEL POWER STATION FOR A PERIOD OF FIVE YEARS.

Description	Material No	Unit	Qty	Price per Unit	TOTAL
<u>GASKETS (314)</u>					
GASKET, PRE CUT: TYPE: RING; DRAWING NO: BBT HTGD 90265 POS 8 REV 1; FOR HP TURBINE STARTING PROBE	20584	EA	75		
GASKET: TYPE: IP TURBINE STARTING PROBE; SHAPE: RING; DRAWING NO: HTGD 90265 POS 8 REV 1	20588	EA	75		
GASKET, MECHANICAL T8B1/GR171/S	38179	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 76 X OD 82 X THK 3 MM; TYPE: CASING; MATERIAL: CU; SHAPE: RD; SUPPL P/N: X1498T10 I-R; REFERENCE NO: X1498T10; FOR INGERSOLL RAND COMPRESSOR XLE	42545	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 129 X OD 141 X THK 2 MM; TYPE: DRYER; MATERIAL: ASB; SHAPE: RD	42570	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 80 MM; OUTER RING OUTSIDE DIAMETER: 114 MM; FILLER MATERIAL: ASB; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; SIZE: 4.5MM THK	60484	EA	75		
GASKET, PRE CUT: DIMENSIONS: THK 3 MM; TYPE: IR FACE PLATE; MATERIAL: RUBBER; SHAPE: D; TYPE: JOINTS, FOR USE WITH 100MM DELUGE WET VALVE	73545	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 131 X OD 169 X THK 3 MM; TYPE: COOLER TO COVER; MATERIAL: RUBBER; SHAPE: RD; DRAWING NO: 1698B6-1 REV 1; REFERENCE NO: CC0761; CC0780; MODEL CENTAC C30EMX4, INGERSOLL RAND	97649	EA	75		
GASKET, PRE CUT: DIMENSIONS: THK 12 MM; TYPE: WAFFLE COOLER; MATERIAL: RUBBER; SHAPE: IRREGULAR; SUPPL P/N: 2-001-044-16; REFERENCE NO: CC0780/CC0761; FOR INGERSOLL-RAND COMPRESSOR, CENTAC C30EMX4; OLD S P/N 2-001-044-2	97650	EA	75		
GASKET, PRE CUT: DIMENSIONS: THK 2 MM; TYPE: DOOR TO CASING COVER; MATERIAL: VELLUMOID; SHAPE: IRREGULAR; DRAWING NO: CC0780 REV 1; CC0761 REV 1; REFERENCE NO: 1089C6-1; FOR INGERSOLL RAND COMPRESSOR CENTAC C30EMX4	97651	EA	75		

GASKET, PRE CUT: DIMENSIONS: THK 1.5 MM; TYPE: INSPECT AIR PORT; MATERIAL: KLINGERITE; SHAPE: IRREGULAR; SUPPL P/N: 2.001.044-16; DRAWING NO: 996C6-1 REV 1; REFERENCE NO: CC0761; CC0780; FOR INGERSOLL-RAND COMPRESSOR, CENTAC C30EMX4	97653	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 32 X SQ 41 X THK 0.5 MM; TYPE: COVER; MATERIAL: AFM34; SHAPE: SQ; SUPPL P/N: 096679; MODEL NO: SVB600/250; SVC600/250; FOR USE ON COMPRESSOR, POS 16 AND 17/811	97986	EA	75		
GASKET, PRE CUT: DIMENSIONS: OD 545 X THK 1 MM; MATERIAL: LEAD; PLATE, 600MM SQUARE X 1MM THICK, FOR BFPT RUPTURE DIAPHRAGM SEAL	98268	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 73 X OD 88 X THK 1 MM; TYPE: BODY; MATERIAL: GRAPHITE; SHAPE: RD; FOR STEAM VALVE TYPE 241-1/271/746-3/50, FOR SO3 PLANT	98911	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 30 X OD 35 X THK 1.5 MM; MATERIAL: PTFE; SHAPE: RD; REFERENCE NO: 42-43-0300-302; FOR DURCO DOZING PUMP MODEL K2/61-14, ON SO3 PLANT	98917	EA	75		
GASKET SET: APPLICATION: STEAM TRAP; QUANTITY: 3; COMPLETE F 10-4.5 TV FOR SO3 PLANT; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	98918	EA	75		
GASKET, PRE CUT: DIMENSIONS: THK 0.5 MM; TYPE: CYLINDER HEAD COVER; MATERIAL: AFM34; SHAPE: IRREGULAR; SUPPL P/N: 029734; MODEL NO: SVC600/250; SVB600/250; FOR USE ON BECKER AND SOHNE COMPRESSOR, POS NO 10/214	98922	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 33 X OD 40 X THK 1 MM; TYPE: RING; MATERIAL: CU; SHAPE: RD; SUPPL P/N: 029416; MODEL NO: SVC600/250; SVB600/250; FOR USE ON BECKER AND SOHNE COMPRESSOR, POS NO 12/249	98925	EA	75		
GASKET, PRE CUT: DIMENSIONS: THK 0.5 MM; TYPE: CYLINDER HEAD COVER; MATERIAL: AFM34; SHAPE: IRREGULAR; SUPPL P/N: 030198; MODEL NO: SVB600/250; SVC600/250; FOR USE ON BECKER AND SOHNE COMPRESSOR, POS NO 8/189	98928	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 32 X OD 50 X THK 9 MM; TYPE: VALVE; MATERIAL: BAKELITE; SHAPE: RD; REFERENCE NO: 046051EB29; SAME AS 90539	99684	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 14.2 X OD 19 X THK 0.5 MM; TYPE: RING; MATERIAL: CU; SHAPE: RD; SUPPL P/N: 028223; MODEL NO: SVB600/250; SVC600/250; FOR USE ON BECKER AND SOHNE COMPRESSOR, POS NO 12/252	99886	EA	75		

GASKET, PRE CUT: DIMENSIONS: ID 25 X SQ 42 X THK 0.5 MM; TYPE: COVER; MATERIAL: AFM34; SHAPE: SQ; SUPPL P/N: 029505; MODEL NO: SVB600/250; SVC600/250; FOR USE ON BECKER AND SOHNE COMPRESSOR, POS NO 16 AND 17/841	99898	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 36 X OD 42 X THK 2 MM; TYPE: RING; MATERIAL: CU; SHAPE: RD; SUPPL P/N: 076201; MODEL NO: SVB600/250; SVC600/250; FOR USE ON BECKER AND SOHNE COMPRESSOR, POS NO 3/134	99900	EA	75		
GASKET, PRE CUT: DIMENSIONS: WD 355 X LG 405 X THK 0.3 MM; TYPE: SPLIT LINE; MATERIAL: PAPER; SHAPE: RECT; FIG NO: 11; MODEL NO: TZ1253; REFERENCE NO: 14-3-47; FOR DRY DUST PLANT COMPRESSOR	100211	EA	75		
GASKET SET: APPLICATION: OIL COOLER; FIG NO: 13; MODEL NO: TZ1253; REFERENCE NO: P1405680-00001; FOR COMPRESSOR; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	100219	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 210 X OD 235 X THK 3 MM; TYPE: OIL MIST FILTER SHELL; MATERIAL: SPONGE; SHAPE: RD; FIG NO: 10; REFERENCE NO: 14.2.25.03; FOR NEW DRY DUST PLANT COMPRESSOR DEMAC MODEL TZ1253	100221	EA	75		
GASKET, PRE CUT: DIMENSIONS: THK 2 MM; TYPE: INTER COOLER REAR HEADER; MATERIAL: KLINGERITE; SHAPE: IRREGULAR; SUPPL P/N: 12026674; 14 1 03; FIG NO: 13; MODEL NO: TZ1253; FOR DRY DUST TURBO COMPRESSOR	100224	EA	75		
GASKET, PRE CUT: DIMENSIONS: THK 1.5 MM; TYPE: INTER COOLER FRONT TUBE SHEET; MATERIAL: KLINGERITE; SHAPE: IRREGULAR; SUPPL P/N: 14-1-08; MODEL NO: TZ1253; REFERENCE NO: 12026574; FOR TURBO COMPRESSOR FOR DRY DUST, DEMAG	100226	EA	75		
GASKET, PRE CUT: DIMENSIONS: THK 1.5 MM; TYPE: INTER COOLER FRONT HEADER; MATERIAL: KLINGERITE; SHAPE: IRREGULAR; SUPPL P/N: 14-1-09; MODEL NO: TZ1253; RIGHT SIDE, FOR DRY DUST TURBO COMPRESSOR	100227	EA	75		
GASKET, PRE CUT: DIMENSIONS: THK 1.5 MM; TYPE: INTER COOLER FRONT HEADER; MATERIAL: VELLUMOID; FIG NO: TZ 1253; MODEL NO: TZ 1253; REFERENCE NO: 14-1-10; SHAPE IRREGULAR, LEFT SIDE, FOR TURBO COMPRESSOR, DEMAG, FOR DRY DUST PLANT	100228	EA	75		
GASKET: TYPE: HP CONNECTION; DRAWING NO: BBT HTGD 90313 POS 4 REV 1	100746	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 186 X OD 250 X THK 0.4 MM; MATERIAL: VELLUMOID; SHAPE: RD; PRESSURE RATING: 5 BAR; PCD: 221 MM; HOLES: (4) DIA 15 MM; WORKING TEMP 0-90 DEG C, MATERIAL; KLINGER SIL C-4400, FOR 100MM INLET DOME VALVE	100852	EA	200		

GASKET, PRE CUT: DIMENSIONS: ID 186 X OD 250 X THK 0.8 MM; MATERIAL: VELLUMOID; SHAPE: RD; PRESSURE RATING: 5 BAR; PCD: 221 MM; HOLES: (4) DIA 15 MM; WORKING TEMP 0-90 DEG C, MATERIAL; KLINGER SIL C-4400, FOR 100MM INLET DOME VALVE	100853	EA	200		
GASKET, PRE CUT: DIMENSIONS: ID 186 X OD 250 X THK 1.5 MM; MATERIAL: VELLUMOID; SHAPE: RD; PRESSURE RATING: 5 BAR; PCD: 221 MM; HOLES: (4) DIA 15 MM; WORKING TEMP 0-90 DEG C, MATERIAL; KLINGER SIL C-4400, FOR 100MM INLET DOME VALVE	100854	EA	200		
GASKET, PRE CUT: DIMENSIONS: ID 242 X OD 325 X THK 0.4 MM; MATERIAL: KLINGERITE SIL C4400; SHAPE: RD; PRESSURE RATING: 5 BAR; PCD: 284 MM; HOLES: (6) DIA 18 MM; WORKING TEMP 0-90 DEG C, FOR 150MM INLINE DOME VALVE	100855	EA	200		
GASKET, PRE CUT: DIMENSIONS: ID 242 X OD 325 X THK 0.8 MM; MATERIAL: KLINGERITE SIL C4400; SHAPE: RD; PRESSURE RATING: 5 BAR; PCD: 284 MM; HOLES: (6) DIA 18 MM; WORKING TEMP 0-90 DEG C, FOR 150MM INLINE DOME VALVE	100856	EA	200		
GASKET, PRE CUT: DIMENSIONS: ID 242 X OD 325 X THK 1.5 MM; MATERIAL: KLINGERITE SIL C4400; SHAPE: RD; PRESSURE RATING: 5 BAR; PCD: 284 MM; HOLES: (6) DIA 18 MM; WORKING TEMP 0-90 DEG C, FOR 150MM INLINE DOME VALVE	100857	EA	200		
GASKET, PRE CUT: DIMENSIONS: ID 320 X OD 410 X THK 0.4 MM; MATERIAL: KLINGERITE SIL C4400; SHAPE: RD; PRESSURE RATING: 5 BAR; PCD: 360 MM; HOLES: (8) DIA 21 MM; WORKING TEMP 0-90 DEG C, FOR 200MM INLET DOME VALVE	100858	EA	200		
GASKET, PRE CUT: DIMENSIONS: ID 320 X OD 410 X THK 0.8 MM; MATERIAL: VELLUMOID; SHAPE: RD; PRESSURE RATING: 5 BAR; PCD: 360 MM; HOLES: (8) DIA 21 MM; CUT, WORKING TEMP 0-90 DEG C, MATERIAL; KLINGER SIL C-4400, FOR 200MM INLET DOME VALVE	100859	EA	200		
GASKET, PRE CUT: DIMENSIONS: ID 317 X OD 440 X THK 1.5 MM; MATERIAL: KLINGERITE SIL C4400; SHAPE: RD; PRESSURE RATING: 5 BAR; PCD: 360 MM; HOLES: (8) DIA 21 MM; WORKING TEMP 0-90 DEG C, FOR 200MM DOME VALVE	100860	EA	300		
GASKET, PRE CUT: DIMENSIONS: ID 430 X OD 560 X THK 0.4 MM; MATERIAL: KLINGERITE SIL C4400; SHAPE: RD; PRESSURE RATING: 5 BAR; PCD: 510 MM; HOLES: (12) DIA 22 MM; WORKING TEMP 0-90 DEG C, FOR 300MM INLINE DOME VALVE	100861	EA	1000		
GASKET, PRE CUT: DIMENSIONS: ID 430 X OD 560 X THK 0.8 MM; MATERIAL: KLINGERITE SIL C4400; SHAPE: RD; PRESSURE RATING: 5 BAR; TEMPERATURE RATING: 0-90 DEG C; PCD: 510 MM; HOLES: (12) DIA 22 MM; PRESSURE, FOR 300 MM INLINE DOME VALVE	100862	EA	1000		
GASKET, PRE CUT: DIMENSIONS: ID 430 X OD 560 X THK 1.5 MM; MATERIAL: KLINGERITE SIL C4400; SHAPE: RD; PRESSURE RATING: 5 BAR; PCD: 510 MM; HOLES: (12) DIA 22 MM; WORKING TEMP 0-90 DEG C, FOR 300MM DOME VALVE	100863	EA	1000		

GASKET, PRE CUT: DIMENSIONS: THK 1 MM; TYPE: AIR HEAD; MATERIAL: BUNA-N; SHAPE: IRREGULAR; REFERENCE NO: W75496; 31517931; FOR INGERSOLL-RAND COMPRESSOR TYPE T-30 MODEL 15T4	101101	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 128 X OD 210 X THK 1 MM; MATERIAL: BUNA-N; SHAPE: RD; SUPPL P/N: 30294193; MODEL NO: 15T4; REFERENCE NO: 30294193; FOR INGERSOLL-RAND COMPRESSOR TYPE T-30	101102	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 57 X OD 68 X THK 1 MM; TYPE: CAP; MATERIAL: VELLUMOID; SHAPE: RD; DRAWING NO: 3B/3BE111/C REV 1; REFERENCE NO: 16; FOR BAILEY BIRKETT RELIEF VALVE USED ON FUEL OIL PRESSURE RELIEF VALVES	101275	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 491 MM; OUTER RING OUTSIDE DIAMETER: 521 MM; SHAPE: ROUND; FLEXITALLIC, (METAFLEX JOINT), NOTE: ITEM MUST BE PROTECTIVE PACKED; SIZE: 4.5MM THK	101471	EA	75		
GASKET, PRE CUT: MATERIAL: KAMBOND 156; REFERENCE NO: K201; KTG191; PRECIPITATOR TORQUE INSULATOR DOOR, FOR BABCOCK BOILER 12C, NOTE: MATERIAL MUST BE BUBBLE PACKED (RAP SEPARATE)	101645	EA	75		
GASKET SET: TYPE: CONTROL VALVE 11N; APPLICATION: FEEDWATER; QUANTITY: 4; MODEL NO: 644ED; REFERENCE NO: RGASKETX162; COMPRISING OFF; BONNET GASKET, SHIM, SPIRAL WOUND GASKET, SEAT RING GASKET, TO BE PACKED INDIVIDUAL SETS AND MARKED AS A SET; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	101683	EA	75		
GASKET SET: TYPE: SEALING; APPLICATION: CONTROL VALVE; QUANTITY: 4; SUPPL P/N: X172; MODEL NO: 644 ED; FOR USE ON 1.5 CONTROL VALVE; RGASKET; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	101684	EA	75		
GASKET SET: APPLICATION: VALVE; MODEL NO: 46049; FOR INJECTION DESUPER HEATER CONTROL; 1 SET CONSIST OF: 2 PACKING RINGS ITEM 18 MATERIAL GRAPHITE; 1 SEAL RING TYPE MLA-002-953-04-05-4 ITEM 28 MATERIAL PTFE; 9 SEAL RINGS 12 X 16 X 7 ITEM 30 MATERIAL GRAPHITE; 4 SEAL RING 22 X 34 X 9 ITEM 31 MATERIAL GRAPHITE; 1 SEAL RING 50 X 60 X 7 ITEM 32 MATERIAL GRAPHITE; 1 SEAL RING 55 X 65 X 7 ITEM 33 MATERIAL GRAPHITE; NOTE - ALL PARTS IS NEED TO MAKE UP A SET AND TO BE PACKED TOGETHER; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	101728	EA	75		

GASKET, SPIRAL WOUND: STYLE: CG; INNER RING INSIDE DIAMETER: 80 MM; OUTER RING OUTSIDE DIAMETER: 138.5 MM; PRESSURE RATING: PN64; FILLER MATERIAL: ASB; WINDING MATERIAL: SS GR 304; SHAPE: ROUND; FLEXITALLIC, OUTER RING MILD STL; FOR SEMPELL VARITEMP INJECTION DESUPER HEATER CONTROL VALVE MODEL 46049; NOTE: ITEM TO BE BUBBLE PACKED; SIZE: 4.5MM THK	101730	EA	75		
GASKET SET: APPLICATION: CLEANOUT CONVEYOR REDUCER; SUPPL P/N: AW8987; AW8986; DRAWING NO: BABCOCK L-D8261 REV 1; SUPPLIER NOTE - THE ITEM MUST BE PROTECTIVE PACKED AND CLEARLY MARKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104461	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 125 X OD 150 X THK 15 MM; TYPE: COVER; MATERIAL: RUBBER; SHAPE: RD; DRAWING NO: L-C6171-0 REV 1; BULLS EYE, FOR STOCK EQUIPMENT VOLUMETRIC COAL FEEDER MODEL 44115	104462	EA	75		
GASKET: TYPE: CAP; APPLICATION: CYLINDER; SUPPL P/N: GH 6207	104468	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 95 X OD 125 X THK 0.5 MM; TYPE: ENGINE CASE; MATERIAL: PLASTIC; SHAPE: RD; REFERENCE NO: GH6208A	104469	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 100 X OD 428 X THK 4 MM; TYPE: ENGINE CASE; MATERIAL: PLASTIC; SHAPE: RD; REFERENCE NO: GH6208B	104470	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 100 X OD 126 X THK 0.1 MM; TYPE: ENGINE CASE; MATERIAL: PLASTIC; SHAPE: RD; REFERENCE NO: GH6208C	104471	EA	75		
GASKET, PRE CUT: DIMENSIONS: THK 1 MM; TYPE: ENGINE CASE; MATERIAL: GRAPHITE; SHAPE: IRREGULAR	104472	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 70 MM; OUTER RING OUTSIDE DIAMETER: 150 MM; FILLER MATERIAL: ASB; WINDING MATERIAL: STL; SHAPE: ROUND; FLEX; SIZE: 4.4MM THK	104492	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 255 X OD 330 X THK 1.2 MM; MATERIAL: VELLUMOID; SHAPE: RD; REFERENCE NO: 104-944-227-205; FOR 50PCT BOOSTER PUMP SULZER TYPE HZB 253-640	104494	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 83 X OD 133 X THK 1 MM; TYPE: COVER/FRAHE; MATERIAL: KLINGERITE; SHAPE: RD; DRAWING NO: 1W25089 REV 1; FLOAT VALVE, XLE NL 7 IN STROKE INGERSOLL RAND	104495	EA	75		
GASKET, PRE CUT: DIMENSIONS: WD 165 X LG 210 X THK 1 MM; TYPE: VALVE BODY; MATERIAL: ASB; SHAPE: RECT; REFERENCE NO: 1W31470; FOR INGERSOLL RAND COMPRESSOR TYPE XLE SIZE 14-1/2 - 9X7	104496	EA	75		

GASKET, PRE CUT: DIMENSIONS: THK 0.8 MM; TYPE: CYLINDER TO FRONT EXTENSION; MATERIAL: VELLUMOID; SHAPE: IRREGULAR; DRAWING NO: 1W27698 REV 1; HP CYLIN- DER, XLE NL 7 IN STROKE	104497	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 110 X OD 174 X THK 1 MM; TYPE: COVER; MATERIAL: VELLUMOID; SHAPE: RD; SUPPL P/N: 1W23840; FOR INGERSOLL-RAND COMPRESSOR XLE, LP CYLINDER	104498	EA	75		
GASKET, PRE CUT: DIMENSIONS: THK 0.5 MM; TYPE: COVER; MATERIAL: ASB; SHAPE: IRREGULAR; DRAWING NO: 1R43816 REV 1; LP AND HP CYLINDER, XLE NL 7 IN STROKE	104499	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 148 MM; OUTER RING OUTSIDE DIAMETER: 154 MM; FILLER MATERIAL: GRAPHITE; WINDING MATERIAL: CU; SHAPE: ROUND; REFERENCE NO: X1014T60-57; VALVE COVER; FOR LP CYLINDER ON INGERSOLL RAND COMPRESSOR XLE; SIZE: 2.5MM THK	104500	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 134 MM; OUTER RING OUTSIDE DIAMETER: 143 MM; FILLER MATERIAL: GRAPHITE; WINDING MATERIAL: CU; SHAPE: ROUND; REFERENCE NO: X1014T56-51; VALVE SEAT, LP CYLINDER, FOR INGERSOLL RAND COMPRESSOR XLE; SIZE: 2MM THK	104501	EA	75		
GASKET, PRE CUT: TYPE: HEAD; SUPPL P/N: 1W25414; FOR INGERSOLL-RAND COMPRESSOR XLE	104503	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 114 MM; OUTER RING OUTSIDE DIAMETER: 120 MM; FILLER MATERIAL: GRAPHITE; WINDING MATERIAL: CU; SHAPE: ROUND; SUPPL P/N: 30550842; REFERENCE NO: X1014T47-44; VALVE COVER, HP CYLINDER, FOR INGERSOLL-RAND COMPRESSOR XLE NL 7 IN STROKE; SIZE: 2MM THK; OLD S P/N X1014T47-44	104504	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 102 X OD 110 X THK 2 MM; TYPE: VALVE SEAT; MATERIAL: CU; SHAPE: RD; REFERENCE NO: X1014T43-39; FOR INGERSOLL-RAND COMPRESSOR TYPE XLE	104505	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 202 X OD 268 X THK 0.7 MM; TYPE: OIL PUMP HOUSING; MATERIAL: VELLUMOID; SHAPE: RD; DRAWING NO: 1W31430P1 REV 1; XLE NL 7 IN STROKE	104506	EA	75		
GASKET, PRE CUT: DIMENSIONS: THK 0.7 MM; TYPE: OIL PUMP; MATERIAL: VELLUMOID; SHAPE: IRREGULAR; DRAWING NO: 1W29721P1 REV 1; XLE NL 7 IN STROKE	104507	EA	75		
GASKET, PRE CUT: DIMENSIONS: THK 0.6 MM; TYPE: COVER; MATERIAL: VELLUMOID; SHAPE: IRREGULAR; DRAWING NO: 1W87288 REV 1; OIL PUMP, XLE NL 7 IN STROKE	104508	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 38 X OD 50 X THK 1.7 MM; TYPE: VALVE BODY; MATERIAL: CU; SHAPE: RD; DRAWING NO: X1214T15 REV 1; OIL PUMP, XLE NL 7 IN STROKE	104509	EA	75		

GASKET, PRE CUT: DIMENSIONS: ID 23.8 X OD 31.2 X THK 1.7 MM; TYPE: BODY CAP; MATERIAL: CU; SHAPE: RD; DRAWING NO: X1013T88 REV 1; OIL PUMP, XLE NL 7 IN STROKE	104511	EA	75		
GASKET, PRE CUT: DIMENSIONS: THK 1.6 MM; TYPE: COMPRESSOR; MATERIAL: VELLUMOID; SHAPE: IRREGULAR; SUPPL P/N: 30413876; INSIDE WATER HEAD FOR INGERSOLL-RAND, XLE; OLD S P/N 1W43286	104513	EA	75		
GASKET, PRE CUT: DIMENSIONS: OD 406 X THK 1.6 MM; MATERIAL: VELLUMOID; SHAPE: RD; SUPPL P/N: 1R23599; REFERENCE NO: 1R23599; OUTSIDE WATER HEAD GASKET, FOR INGERSOLL-RAND COMPRESSOR XLE	104514	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 330 X OD 405 X THK 0.7 MM; TYPE: FRONT TO TAIL PLATE; MATERIAL: VELLUMOID; SHAPE: RD; SUPPL P/N: 1W36432; FOR INGERSOLL RAND COMPRESSOR XLE, SUPPLIER NOTE: THE ITEM MUST BE PROTECTIVE PACKED, SEALED AND CLEARLY MARKED	104515	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 25 X OD 32 X THK 1 MM; TYPE: VALVE CAGE; MATERIAL: LEATHER; SHAPE: RD; DRAWING NO: 1R5785-274 REV 1; MOISTURETRAP, XLE NL 7 IN STROKE	104516	EA	75		
GASKET, PRE CUT: DIMENSIONS: OD 145 X WD 82 X THK 0.7 MM; TYPE: VALVE PLUNGER GUIDE; MATERIAL: CORK; SHAPE: RECT; REFERENCE NO: UF4-15; FOR INGERSOLL RAND COMPRESSOR XLE SIZE 14-1/2 - 9X7 SERIAL V1AFTNL 454	104517	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 10 X OD 16 X THK 0.8 MM; TYPE: ORIFICE COVER PLUG; MATERIAL: GRAPHITE; SHAPE: RD; REFERENCE NO: UF3-37; FOR INGERSOLL RAND COMPRESSOR XLE, 7 IN STROKE	104518	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID (18 X 35) X OD 27 X THK 1 MM; TYPE: METERING PIN SEAT; MATERIAL: GRAPHITE; SHAPE: RD; REFERENCE NO: UF1-31; SUPERSEDE BY W90674, FOR INGERSOLL-RAND COMPRESSOR XLE	104519	EA	75		
GASKET, PRE CUT: DIMENSIONS: SQ 48 X THK 0.6 MM; MATERIAL: VELLUMOID; SHAPE: SQ; DRAWING NO: 1W26700 REV 1; PILOT AIR FILTER COVER, REGULATOR, XLE NL 7 IN STROKE, INGERSOLL RAND	104520	EA	75		
GASKET, PRE CUT: DIMENSIONS: WD 48 X LG 133 X THK 0.7 MM; TYPE: GAGE MANIFOLD; MATERIAL: VELLUMOID; SHAPE: RECT; REFERENCE NO: 1W34929; FOR INGERSOLL RAND COMPRESSOR XLE	104522	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 20 X OD 80 X THK 17 MM; TYPE: AGITATOR; MATERIAL: NYLON; SHAPE: RD; AGT	104526	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 17 X OD 21 X THK 2 MM; MATERIAL: CU; SHAPE: RD; 1/4 IN	104529	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 78 X OD 82 X THK 2 MM; MATERIAL: RUBBER; SHAPE: RD; REFERENCE NO: 8H1778	104539	EA	75		

GASKET, PRE CUT: DIMENSIONS: ID 41 X OD 56 X THK 3 MM; TYPE: CLEANOUT CONVEYOR GEARBOX; MATERIAL: RUBBER; SHAPE: RD; SUPPL P/N: 1-W9339; DRAWING NO: L-D8258-C REV 1; MODEL NO: 44115; OUTER, DIGHT GAUGE	104540	EA	75		
GASKET: APPLICATION: SIGHT GAGE; DRAWING NO: L-D8258-C REV 1; MODEL NO: 44115; INNER, FOR CLEANOUT CONVEYOR GEARBOX, VOLUMETRIC COAL FEEDER, STOCK EQUIPMENT	104541	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 49.5 X OD 65 X THK 41.2 MM; MATERIAL: TEFLON GRAPHITE IMPREGNATED; SUPPL P/N: 8909; K 331 B; CHEVRON PACKING ASSEMBLY, FOR SOOTBLOWERS, SPLIT RING, STYLE 3000, NOTE - THE ITEM MUST BE PROTECTIVE PACKED AND CLEARLY MARKED	104583	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 71 MM; OUTER RING OUTSIDE DIAMETER: 84 MM; FILLER MATERIAL: ASB; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; METAFLEX; SIZE: 5MM THK	104585	EA	75		
GASKET, SPIRAL WOUND: STYLE: F/22/36/119; INNER RING INSIDE DIAMETER: 95 MM; OUTER RING OUTSIDE DIAMETER: 112 MM; SHAPE: ROUND; METAFLEX; SIZE: 5MM THK	104586	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 60 MM; OUTER RING OUTSIDE DIAMETER: 85 MM; FILLER MATERIAL: ASB; WINDING MATERIAL: STL; SHAPE: ROUND; METAFLEX; SIZE: 5MM THK	104587	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 64 MM; OUTER RING OUTSIDE DIAMETER: 78 MM; FILLER MATERIAL: ASB; WINDING MATERIAL: STL; SHAPE: ROUND; METAFLEX; SIZE: 5MM THK	104588	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 143 MM; OUTER RING OUTSIDE DIAMETER: 162 MM; FILLER MATERIAL: ASB; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; METAFLEX, SIZE 3MM THK; SIZE: 4.5MM THK	104589	EA	400		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 662 MM; OUTER RING OUTSIDE DIAMETER: 722 MM; FILLER MATERIAL: GRAPHITE; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; DRAWING NO: 510 71470 01 REV 1; METAFLEX, FOR BOILER CIRCULATING PUMP KSB TYPE LUV 200/415/1; SIZE: 5MM THK	104590	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 76 MM; OUTER RING OUTSIDE DIAMETER: 100 MM; FILLER MATERIAL: ASB; WINDING MATERIAL: STL; SHAPE: ROUND; SIZE: 5MM THK	104591	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 214 MM; OUTER RING OUTSIDE DIAMETER: 268 MM; FILLER MATERIAL: NON ASB; WINDING MATERIAL: STL; SHAPE: ROUND; ITEM MUST BE PROTECTIVE PACKED; SIZE: 4MM THK	104592	EA	75		

GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 280 MM; OUTER RING OUTSIDE DIAMETER: 314 MM; FILLER MATERIAL: ASB; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; METAFLEX; SIZE: 5MM THK	104593	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 226 MM; OUTER RING OUTSIDE DIAMETER: 245 MM; FILLER MATERIAL: ASB; WINDING MATERIAL: STL; SHAPE: ROUND; 4.5; SIZE: 4MM THK	104594	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 395 MM; OUTER RING OUTSIDE DIAMETER: 405 MM; FILLER MATERIAL: GRAPHITE; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; SUPPL P/N: 33572-532; METAFLEX, SIZE: 375MM ID, FOR 300MM HOPKINSON VALVE FIGURE 3642CU (6) SA 483; SIZE: 5MM THK	104595	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 96 MM; OUTER RING OUTSIDE DIAMETER: 108 MM; FILLER MATERIAL: ASB; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; REFERENCE NO: 33571-405; SIZE: 5MM THK	104596	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 218 MM; OUTER RING OUTSIDE DIAMETER: 245 MM; FILLER MATERIAL: ASB; WINDING MATERIAL: STL; SHAPE: ROUND; METAFLEX; SIZE: 4.5MM THK	104597	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 642 MM; OUTER RING OUTSIDE DIAMETER: 672 MM; FILLER MATERIAL: VELLUMOID; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; 648X675X5.0; SIZE: 5MM THK	104598	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 585 MM; OUTER RING OUTSIDE DIAMETER: 618 MM; FILLER MATERIAL: VELLUMOID; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; SIZE: 5MM THK	104599	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 54 MM; OUTER RING OUTSIDE DIAMETER: 66 MM; SHAPE: ROUND; METAFLEX; SIZE: 3.5MM THK	104600	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 74 MM; OUTER RING OUTSIDE DIAMETER: 88 MM; SHAPE: ROUND; METAFLEX, SIZE: 3.5MM THK	104601	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 27 MM; OUTER RING OUTSIDE DIAMETER: 37 MM; FILLER MATERIAL: ASB; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; METAFLEX; SIZE: 3MM THK	104602	EA	75		

GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 220 MM; OUTER RING OUTSIDE DIAMETER: 240 MM; FILLER MATERIAL: GRAPHITE; SHAPE: ROUND; DRAWING NO: KANTECH KTDF/23 REV 1; PREFORMED SEAL, 45 DEG SHAMFER FROM INSIDE DIA TO LEAVE 2MM OF WALL THICKNESS AND 12MM OF HEIGHT; NOTE: SEAL MUST BE PROTECTIVE PACKED; SIZE: 20MM THK	104603	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 145 X OD 160 X THK 15 MM; MATERIAL: GRAPHITE; SHAPE: RD; PRESSURE RATING: PN320; DRAWING NO: Z 0.47498E POS 10073 REV 1; KANTECH KTDF/18 REV 1; 45DEG INSIDE SHAMFER, FOR WELLAND AND TUXHORN 33PCT REGULATING DRAIN VALVE DN150/250, NOTE: SEAL TO BE MANUFACTURED TO NU-CLEAR STANDARDS AND BUBBLE PACKED FOR PROTECTION	104605	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 32 X OD 68 X THK 4.5 MM; MATERIAL: VELLUMOID; SHAPE: RD; ENVELOPE, PTFE	104606	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 35 X OD 63 X THK 1 MM; MATERIAL: KLINGERITE; SHAPE: RD; HNGT304803 POS 6	104607	EA	75		
GASKET, PRE CUT: DIMENSIONS: THK 1 MM; TYPE: LP CYLINDER TO FRONT EXTENSION; MATERIAL: VELLUMOID; SHAPE: IRREGULAR; DRAWING NO: 1W31365 REV 1; XLE NL 7 IN STROKE	104629	EA	75		
GASKET, PRE CUT: DIMENSIONS: WD 215 X LG 455 X THK 1 MM; TYPE: PORT; MATERIAL: GRAPHITE; SHAPE: RECT; REFERENCE NO: H8946H11135	104630	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 240 X OD 340 X THK 4.5 MM; MATERIAL: VELLUMOID; SHAPE: RD; REFERENCE NO: BE9-13A	104631	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 103 X OD 124 X THK 3 MM; TYPE: VACUUM MOTOR; MATERIAL: RUBBER; SHAPE: RD; REFERENCE NO: 26106	104640	EA	75		
GASKET, PRE CUT: DIMENSIONS: THK 1.5 MM; TYPE: CASING; MATERIAL: CORK; SHAPE: IRREGULAR; REFERENCE NO: 1J9691-0404	104647	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 13 X OD 44 X THK 1.5 MM; TYPE: BYPASS; MATERIAL: RUBBER; SHAPE: RD; REFERENCE NO: 1J9694-0413; FOR FISHER POSITIONER 3560 SERIES	104648	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 52 MM; OUTER RING OUTSIDE DIAMETER: 63 MM; FILLER MATERIAL: ASB; WINDING MATERIAL: PTFE LINED; SHAPE: ROUND; SUPPL P/N: JP-81646; FOR WALLACE AND TIERNAN METERING PUMP TYPE: G50-VSMD; SIZE: 2MM THK	104651	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 12 X OD 25 X THK 4.5 MM; TYPE: PUMP; MATERIAL: RUBBER; SHAPE: RD; REFERENCE NO: JPXK 81368; G500V MET P	104652	EA	75		

GASKET, PRE CUT: DIMENSIONS: ID 282 X OD 330 X THK 1 MM; TYPE: EXTRACTION PUMP; MATERIAL: KLINGERITE; SHAPE: RD	104662	EA	75		
GASKET, PRE CUT: DIMENSIONS: WD 470 X LG 115 X THK 20 MM; TYPE: DOOR; MATERIAL: RUBBER; SHAPE: RECT; DRAWING NO: L-D8357-A REV 1; MODEL NO: 44115; FEEDER END, VOLUMETRIC COAL FEEDER, STOCK EQUIPMENT	104663	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 91 X OD 95 X THK 0.5 MM; TYPE: VOLUTE FEEDER; MATERIAL: STL; SHAPE: RD	104667	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 350 MM; OUTER RING OUTSIDE DIAMETER: 860 MM; FILLER MATERIAL: ASB; WINDING MATERIAL: STAINLESS STEEL; SHAPE: IRREGULAR; SIZE: 5MM THK	104670	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 385 MM; OUTER RING OUTSIDE DIAMETER: 395 MM; FILLER MATERIAL: ASB; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; METAFLEX JOINTS; SIZE: 4MM THK	104671	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 435 MM; OUTER RING OUTSIDE DIAMETER: 455 MM; PRESSURE RATING: 40 BAR; FILLER MATERIAL: ASB; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; METAFLEX, TEMPERATURE 80 DEG C, FOR USE IN A 300MM GATE VALVE; SIZE: 5MM THK	104672	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 80 MM; OUTER RING OUTSIDE DIAMETER: 98 MM; SHAPE: ROUND; METAFLEX; SIZE: 3.2MM THK	104674	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 50 MM; OUTER RING OUTSIDE DIAMETER: 65 MM; FILLER MATERIAL: ASB; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; SIZE: 3MM THK	104675	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 86 MM; OUTER RING OUTSIDE DIAMETER: 105 MM; FILLER MATERIAL: ASB; WINDING MATERIAL: STL; SHAPE: ROUND; METAFLEX, SIZE 4.5MM THK; NOTE: ITEM MUST BE PROTECTIVE PACKED; SIZE: 4MM THK	104676	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 105 MM; OUTER RING OUTSIDE DIAMETER: 128 MM; SHAPE: ROUND; METAFLEX; SIZE: 4.5MM THK	104677	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 35 MM; OUTER RING OUTSIDE DIAMETER: 320 MM; FILLER MATERIAL: ASB; WINDING MATERIAL: SS; SHAPE: OVAL; 320X735X4.5; SIZE: 4.5MM THK	104678	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 76.5 MM; OUTER RING OUTSIDE DIAMETER: 88.8 MM; FILLER MATERIAL: ASB; WINDING MATERIAL: ALUMINIUM; SHAPE: ROUND; METAFLEX JOINTS, FOR USE WITH FISHER VALVE; SIZE: 5MM THK	104685	EA	75		

GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 199 MM; OUTER RING OUTSIDE DIAMETER: 216 MM; METAFLEX JOINT, GRAPHITE, SIZE: 5.8MM THK	104686	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 128 MM; OUTER RING OUTSIDE DIAMETER: 141 MM; FILLER MATERIAL: ASB; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; TYPE: METAFLEX JOINTS; SIZE: 4.8MM THK	104687	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 90.4 MM; OUTER RING OUTSIDE DIAMETER: 102.5 MM; FILLER MATERIAL: GRAPHITE; WINDING MATERIAL: STL; SHAPE: ROUND; METAFLEX, FOR USE ON FISHER VALVES; SIZE: 4.76MM THK	104688	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 230 X OD 330 X THK 1.2 MM; MATERIAL: KLINGERITE; SHAPE: RD	104718	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 592 MM; OUTER RING OUTSIDE DIAMETER: 619 MM; FILLER MATERIAL: ASB; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; SIZE: 4.4MM THK	104726	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 585 MM; OUTER RING OUTSIDE DIAMETER: 615 MM; FILLER MATERIAL: ASB; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; METALFEX JOINT; SIZE: 4.4MM THK	104727	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 216.7 MM; OUTER RING OUTSIDE DIAMETER: 248.4 MM; FILLER MATERIAL: ASB; WINDING MATERIAL: STL; SHAPE: ROUND; 216 X 248 X 5MM; SIZE: 5MM THK	104728	EA	75		
SHEET, GASKET: THICKNESS: 50 MM; LENGTH: 5 M; WIDTH: 950 MM; MATERIAL: FELT; TYPE INSULATION	104732	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 25 X OD 33 X THK 4 MM; TYPE: GEKA COUPLING; MATERIAL: RUBBER; SHAPE: RD	104733	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 115 X OD 165 X THK 0.2 MM; TYPE: VOLUMETRIC COAL FEEDER; MATERIAL: PTFE; SHAPE: RD; SUPPL P/N: 1-W9204; MODEL NO: 44115	104736	EA	75		
GASKET, PRE CUT: DIMENSIONS: WD (1.3 X 1.04) M X LG (1.75 X 1.54) M X THK 8 MM; TYPE: BALL MILL DOOR COVER; MATERIAL: ASB BRAIDED SI RUBBERIZED; SHAPE: RECT	104743	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 11.5 X OD 22.5 X THK 2 MM; MATERIAL: KLINGERITE; SHAPE: RD; REFERENCE NO: BP-310-418; BALZIER GAS PUMP 3	104745	EA	75		
GASKET, PRE CUT: DIMENSIONS: WD 45 X LG 122 X THK 2 MM; MATERIAL: KLINGERITE; SHAPE: IRREGULAR; BALZIER GAS PUMP 6	104746	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 92 MM; OUTER RING OUTSIDE DIAMETER: 115 MM; SHAPE: ROUND; METAFLEX; SIZE: 4.75MM THK	104755	EA	75		

GASKET, PRE CUT: DIMENSIONS: ID 118 X OD 140 X THK 3 MM; TYPE: SIGHT GLASS; MATERIAL: RUBBER; SHAPE: RD; DRAWING NO: AE070/BS REV 1; FOR TAPROGGE DISTRIBUTOR ND65 AND ND80	104756	EA	75		
GASKET, PRE CUT: DIMENSIONS: THK 3 MM; MATERIAL: CORK; SHAPE: IRREGULAR; FOR CABLE MONO BLOCK INSULATOR TYPE 557688, T1-OFF, 11KV, 90 AMP, FOR GEC OCB	104757	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 180 X OD 240 X THK 3 MM; MATERIAL: CORK; SHAPE: RD; FOR BUSBAR MONO BLOCK 561606, FOR GEC TYPE T1-OFF, 11KV, 90AMP, OCB	104758	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 265 X OD 290 X THK 18 MM; MATERIAL: NEOPRENE; SHAPE: RD; REFERENCE NO: 562610; FOR BUSBAR MONO BLOCK BLANK OFF COVERS, ON GEC OIL OPERATED CIRCUIT BREAKER TYPE:- T1-0F, RATING:- 11KV 90AMP	104759	EA	75		
GASKET, PRE CUT: DIMENSIONS: WD (200 X 77) X LG 250 X THK 3 MM; TYPE: ISOLATOR BARRIER BLOCK; MATERIAL: CORK; SHAPE: RECT; REFERENCE NO: 555703; ISOLATOR FUSE, MONO BLOCK, FOR GEC TYPE T1-OFF, 11KV, 90 AMP, OCB	104760	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 246.5 MM; OUTER RING OUTSIDE DIAMETER: 263.5 MM; FILLER MATERIAL: ASB; WINDING MATERIAL: STL; SHAPE: ROUND; METAFLEX; NOTE: ITEM MUST BE PROTECTIVE PACKED; SIZE: 4.5MM THK	104764	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 71.5 MM; OUTER RING OUTSIDE DIAMETER: 83.5 MM; METAFLEX, SIZE: 4.5MM THK; NOTE: ITEM MUST BE PROTECTIVE PACKED	104765	EA	75		
GASKET, SPIRAL WOUND: STYLE: R; INNER RING INSIDE DIAMETER: 216 MM; OUTER RING OUTSIDE DIAMETER: 243 MM; FILLER MATERIAL: ASB; WINDING MATERIAL: ALUMINIUM; SHAPE: ROUND; REFERENCE NO: 304SS/ASB; METAFLEX, SIZE: 4MM THK	104766	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 435 X OD 479 X THK 0.8 MM; MATERIAL: KLINGERITE; SHAPE: RD; SUPPL P/N: 11.61; 104 133 305 004; FOR SULZER PUMP HPT POK 32-25	104771	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 250 MM; OUTER RING OUTSIDE DIAMETER: 269 MM; FILLER MATERIAL: ASB; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; SUPPL P/N: 104 139 047 004; SPIRAL, FOR SULZER PUMP HPT POK 32-25; SIZE: 0.8MM THK	104773	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 451.63 MM; OUTER RING OUTSIDE DIAMETER: 473.07 MM; FILLER MATERIAL: GRAPHITE; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; SUPPL P/N: 104 133 499 012; REFERENCE NO: 25.00; FLEXITALLIC SEAL, FOR SULZER PUMP HPT POK 32-25; SIZE: 4.44MM THK	104774	EA	75		

GASKET * 112 X 77 X 1 * ARTICLE NUMBER: 104 133 499 014 * FOR SULZER PUMP HPT POK 32-25 *	104775	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 45 X OD 65 X THK 1 MM; MATERIAL: VELLUMOID; SHAPE: RD; FOR SULZER PUMP HPT POK 32-25	104776	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 40 X OD 49.5 X THK 0.5 MM; MATERIAL: VELLUMOID; SHAPE: RD; SUPPL P/N: 104 133 371 004; FOR SULZER PUMP HPT POK 32-25	104778	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 87 MM; OUTER RING OUTSIDE DIAMETER: 103 MM; FILLER MATERIAL: GRAPHITE; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; SUPPL P/N: 104 133 381 002; 11.46.5; FLEXITALLIC SEAL, FOR SULZER PUMP HPT POK 32-25; SIZE: 4.4MM THK	104779	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 195 MM; OUTER RING OUTSIDE DIAMETER: 213 MM; SHAPE: ROUND	104786	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 256.5 MM; OUTER RING OUTSIDE DIAMETER: 269 MM; FILLER MATERIAL: ASB; WINDING MATERIAL: STL; SHAPE: ROUND; SAFETY VALVE; SIZE: 5MM THK	104787	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 645 MM; OUTER RING OUTSIDE DIAMETER: 674 MM; FILLER MATERIAL: ASB; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; HT WINDING, WITHOUT FRAME, ITEM MUST BE PROTECTIVE PACKED; SIZE: 4.4MM THK	104788	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 182 X OD 200 X THK 8 MM; MATERIAL: BAKELITE; SHAPE: RD; 12	104790	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 102 MM; OUTER RING OUTSIDE DIAMETER: 119 MM; FILLER MATERIAL: ASB; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; METAFLEX, SIZE: 4MM THK	104791	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 171 X OD 221 X THK 0.8 MM; TYPE: STUFFER; MATERIAL: VELLUMOID; SHAPE: RD; REFERENCE NO: 1W36154; FOR INGERSOLL RAND COMPRESSOR XLE SIZE 14-1/2 - 9X7	104793	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 155 X OD 180 X THK 1.5 MM; TYPE: CASING; MATERIAL: VELLUMOID; SHAPE: RD; REFERENCE NO: 315085; FOR MOTOFLO PUMP TYPE 32MO/220	104796	EA	75		
SEAL, MECHANICAL: SHAFT DIAMETER: 55 MM; BODY MATERIAL: STAINLESS STEEL; MODEL NO: NNP 90-110; TYPE D5, FOR MAAG GEAR PUMP, CONSISTING OF FOLLOWING: SPRING ELEMENT PART NO: 8-890-5377-01, RING PART NO: 8-890-5371-01, O-RING PART NO: 8-801-4207-01, SEAT PART NO: 8-890-5344-21, COVER GASKET PART NO: 8-890-3345-62; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION	104801	EA	75		

NUMBER (IF APPLICABLE).					
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 196 MM; OUTER RING OUTSIDE DIAMETER: 216 MM; FILLER MATERIAL: ASB; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; METAFLEX; SIZE: 5MM THK	104803	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 79 MM; OUTER RING OUTSIDE DIAMETER: 98 MM; SHAPE: ROUND; REFERENCE NO: 1P5911-99102; FOR FISHER CONTROL VALVE ON MAIN CONDENSER LEVEL CONTROLLER, ITEM 11; SIZE: 3MM THK	104807	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 45 X OD 55 X THK 2 MM; THICKNESS: 2 MM; TYPE: WATER; MATERIAL: CU; SHAPE: ROUND; PRESSURE RATING: 395 BAR; TEMPERATURE RATING: 245 DEG C; REFERENCE NO: 0.40024E; APPLICATION: SUPERHEATERS; USED FOR WATER SEALING PURPOSES; MATERIAL CUF20; FOR WELLAND AND TUXHORN HP SPRAY WATER CONTROL VALVE	104810	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 110 X OD 120 X THK 12 MM; TYPE: BOTTOM LEAK OFF; MATERIAL: STAINLESS STEEL CAP GRAPHITE; SHAPE: RD; DRAWING NO: 0.42092-EB REV 1; REFERENCE NO: 119023061724; 45 INNER LEVEL STAINLESS STEEL CAP; TYPE R.G.K, SUPPLIER NOTE: THE ITEM MUST BE PROTECTIVE PACKED, SEALED AND CLEARLY MARKED WITH MATERIAL NUMBER 0104811	104811	EA	75		
GASKET, PRE CUT: DIMENSIONS: LG 1.524 M X THK 15 MM; MATERIAL: RUBBER; SHAPE: RD; BUTTERFLY VALVE 1524MM	104819	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 335 X OD 375 X THK 31 MM; MATERIAL: GRAPHITE; SHAPE: RD; FIG NO: 640AC; FOR 300MM PERSTA SWING CHECK VALVE, PLANT POSITION ASV 92, NOTE: ITEM MUST BE PROTECTIVE PACKED	104820	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 240 X OD 280 X THK 30 MM; MATERIAL: GRAPHITE; SHAPE: RD; REFERENCE NO: KTDF53; NOTE: ITEM MUST BE PROTECTIVE PACKED	104823	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 120 X OD 140 MM; THICKNESS: 12 MM; TYPE: LEAK-OFF PRESSURE SEAL; MATERIAL: GRAPHITE; SHAPE: RD; DRAWING NO: 0.42092-EB REV 0; REFERENCE NO: O901/B6; KTDF30A; KTDF/30B; 119023061724; 45DEG INNER BEVEL SS CAP; NOTE: ITEM MUST BE PROTECTIVE PACKED	104824	EA	75		

GASKET, PRE CUT: DIMENSIONS: ID 17 X OD 24 X THK 5 MM; TYPE: VALVE; MATERIAL: STAINLESS STEEL; SHAPE: RD; 25 BLR FEED VV244	104828	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 95 MM; OUTER RING OUTSIDE DIAMETER: 114 MM; FILLER MATERIAL: ASB; WINDING MATERIAL: STL; SHAPE: ROUND; METAFLEX; SIZE: 5MM THK	104830	EA	75		
GASKET, SPIRAL WOUND: STYLE: K; INNER RING INSIDE DIAMETER: 338 MM; OUTER RING OUTSIDE DIAMETER: 360 MM; FILLER MATERIAL: ASB; WINDING MATERIAL: ALUMINIUM; SHAPE: ROUND; 357MMIDX4MM THK; SIZE: 5MM THK	104831	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 145 X OD 170 X THK 35 MM; TYPE: LID; MATERIAL: BRASS; SHAPE: RD; SUPPL P/N: 35152G-108; FIG NO: 24950W; REFERENCE NO: SA-400; SEALING, FOR HOPKINSON PARALLEL SLIDE VALVE, SIZE:- 5"	104838	EA	75		
GASKET, RING JOINT: INSIDE DIAMETER: 319 X 273 MM; OUTSIDE DIAMETER: 325 MM; MATERIAL: BRASS; FIG NO: 23928W; FOR 8 IN HOPKINSON PARRALEL SLIDE VALVE FIGURE 23928W	104839	EA	75		
GASKET, RING JOINT: INSIDE DIAMETER: 228 X 200 MM; OUTSIDE DIAMETER: 240 MM; MATERIAL: BRASS; SUPPL P/N: 35152128; DRAWING NO: 24950W REV 1; R540B-88 REV 1; LID SEAL; FOR HOPKINSON VALVE SIZE: 9 IN	104840	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 11 X OD 17 X THK 1 MM; TYPE: VALVE; MATERIAL: NEOPRENE; SHAPE: RD; REFERENCE NO: 1C4957-04022	104844	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 60 X OD 70 X THK 0.5 MM; TYPE: VALVE; MATERIAL: NEOPRENE; SHAPE: RD; REFERENCE NO: 1C1280-03012	104845	EA	75		
GASKET * ITEM 11 * PART NUMBER IP5911- 9910 * FOR USE WITH TURBINE PLANT CONDENSER * LEVEL CONTROL VALVE NUMBER CB7337 * FISHER TYP E 476-4-8-UR * DRAWING NUMBER VB10361 *	104846	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 11 X OD 25 X THK 1 MM; TYPE: VALVE; MATERIAL: RUBBER; SHAPE: RD; REFERENCE NO: 1H2696-0301	104853	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 58 X OD 77 X THK 1 MM; TYPE: VALVE; MATERIAL: RUBBER; SHAPE: RD; SUPPL P/N: 1K7002-0414; TOP	104854	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 39 X OD 48 X THK 1 MM; TYPE: VALVE; MATERIAL: RUBBER; SHAPE: RECT; REFERENCE NO: 1C3286-0301	104857	EA	75		

GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 50 MM; OUTER RING OUTSIDE DIAMETER: 65 MM; FILLER MATERIAL: ASB; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; THICKNESS: 5 MM; FIG NO: 800 GJ21/2; REFERENCE NO: 22000; SIZE: ID 50MM OD 65MM THICK 5MM; FOR 25MM NB, DEUTSCHE BABCOCK GATE VALVE, FOR CV160 CV189 BY-PASS	104860	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 65 X OD 77 X THK 1.5 MM; MATERIAL: ASB; SHAPE: RD; REFERENCE NO: 13061; 65MM VALVE	104861	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 45.1 X OD 54.4 X THK 1 MM; MATERIAL: CU CUF20; SHAPE: RD; PRESSURE RATING: PN400; DRAWING NO: 0.40021E POS 8043 REV 1; FOR WELLAND AND TUXHORN SUPER HEATER SPRAY WATER REGULATING VALVE DN50	104870	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 45 X OD 55 X THK 1 MM; MATERIAL: CU; SHAPE: RD; DRAWING NO: 0.41002A-COM: 23678 REV 1; MATERIAL CUF20, SIZE 63.2MM OUTSIDE DIA X 54.3MM INSIDE DIA X 0.9MM THICK, FOR WELLAND AND TUXHORN REGULATING VALVE	104871	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 12 X OD 24 X THK 2 MM; TYPE: VALVE; MATERIAL: STAINLESS STEEL; SHAPE: RD; GROOVED	104872	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 246.5 MM; OUTER RING OUTSIDE DIAMETER: 269 MM; FILLER MATERIAL: GRAPHITE; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; FOR REHEAT SAFETY VALVE MSV 200/2, NOTE: ITEM MUST BE PROTECTIVE PACKED, SEPARATE; SIZE: 4.5MM THK	104873	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 27 X OD 35 X THK 2 MM; TYPE: ENVELOPE; MATERIAL: PTFE ACID RESISTANCE FILLED; SHAPE: RD; SUPPL P/N: JPBX81645; FOR PRECISION DOSING PUMP G50V, NOTE: EACH ITEM MUST BE PROTECTIVE PACKED AND SEALED	104875	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 338 MM; OUTER RING OUTSIDE DIAMETER: 356 MM; FILLER MATERIAL: ASB; WINDING MATERIAL: STAINLESS STEEL; SHAPE: ROUND; SUPPL P/N: 351; METAFLEX, FOR APE GOULD PUMP 3736; SIZE: 4MM THK	104877	EA	75		
GASKET, PRE CUT: DIMENSIONS: THK 2.5 MM; TYPE: VALVE; MATERIAL: RUBBER; SHAPE: IRREGULAR; REFERENCE NO: 27745; D/SYST, 3 IN B/VV	104881	EA	75		
GASKET, PRE CUT: DIMENSIONS: WD 242 X LG 385 X THK 1 MM; TYPE: FILTER; MATERIAL: KLINGERITE; SHAPE: RECT; DRAWING NO: BBT HTGD 90228 POS 42 REV 1; FOR BFPT LUB OIL, 16 L/SEC	104885	EA	75		
GASKET, PRE CUT: DIMENSIONS: WD 38 X LG 48 X THK 1 MM; TYPE: BOILER; MATERIAL: CORK; SHAPE: RECT	104887	EA	75		

GASKET, PRE CUT: DIMENSIONS: ID 21 X OD 27 X THK 7 MM; MATERIAL: STL; SHAPE: RD; REFERENCE NO: 7M41590-ODA; FOR USE WITH VALVE BLOCK TYPE 7MF9006-4AA	104888	EA	75		
GASKET, PRE CUT: DIMENSIONS: WD 230 X LG 450 X THK 1 MM; MATERIAL: KLINGERITE; SHAPE: RECT; DRAWING NO: BBT HTGD 90228 POS 42 REV 1; FOR MAIN TURBINE LUB OIL FILTER, 25 L/S, SCHEMATIC POS 5765/5766	104892	EA	75		
SHEET, GASKET: THICKNESS: 5 MM; WIDTH: 7 MM; MATERIAL: RUBBER; FOR O RING 50 TURBINE	104893	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 50 X OD 60 X THK 1 MM; MATERIAL: KLINGERITE; SHAPE: RD; DRAWING NO: BBT HTGD 90228 POS 45 REV 1; FOR MAIN AND BFP TLUB OIL FILTER 16 AND 25 L/S	104894	EA	75		
GASKET, PRE CUT: DIMENSIONS: WD 330 X LG 240 X THK 3 MM; MATERIAL: RUBBER; SHAPE: RECT; REFERENCE NO: L1046; BETWEEN CHASSIS AND CONTROL UNIT, FOR PEABODY OIL BURNERS	104899	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 292 X OD 324 X THK 30 MM; TYPE: PARALLEL SLIDE; MATERIAL: GRAPHITE; SHAPE: RD; SUPPL P/N: KTDF61; FIG NO: 23928W; REFERENCE NO: 38211-680; 200MM HOPKINSON, SUPPLIER NOTE: THE ITEM MUST BE PROTECTIVE PACKED, SEALED AND CLEARLY MARKED	104918	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 80 X OD 120 X THK 0.5 MM; TYPE: ACTUATOR; MATERIAL: CALBRITAL; SHAPE: RD; REFERENCE NO: 1-70; 1.7MM; G/BOX	104919	EA	75		
GASKET, PRE CUT: TYPE: SEAT RING; REFERENCE NO: 1R28620402	104942	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 35 X OD 51 X THK 1 MM; TYPE: FILTER; MATERIAL: FELT; SHAPE: RD; REFERENCE NO: 3000094; FOR KENT ZIRCONIA OXYGEN ANALYSER PROBE	104943	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 65 X OD 105 X THK 2 MM; MATERIAL: GRAPHITE; SHAPE: RD; REFERENCE NO: 3000096; FOR KENT ZIRCONIA OXYGEN ANALYSER PROBE	104944	EA	75		
GASKET, PRE CUT: DIMENSIONS: THK 6 MM; MATERIAL: RUBBER; SHAPE: IRREGULAR; DRAWING NO: BBT HTGD 90228 POS 43 REV 1; FOR BFPT LUB OIL FILTER 16 L/S	104946	EA	75		
GASKET, PRE CUT: DIMENSIONS: THK 6 MM; TYPE: MAIN TURBINE LUBE OIL FILTER; MATERIAL: RUBBER; SHAPE: IRREGULAR; DRAWING NO: HTGD 90228 POS 5765/5766 REV 1; BBT HTGD 90228 POS 43 REV 1; 25 L/S	104948	EA	75		
GASKET, PRE CUT: DIMENSIONS: THK 1 MM; TYPE: SWITCH PLATE; MATERIAL: NEOPRENE; SHAPE: IRREGULAR; REFERENCE NO: 1D3971-0301; KEY 19, FOR FISHER MULTITROL CONTROLLER 2516	104951	EA	75		

GASKET, PRE CUT: DIMENSIONS: WD 24 X LG 38 X THK 1 MM; TYPE: RELAY KEY; MATERIAL: RUBBER; SHAPE: RECT; REFERENCE NO: 22	104952	EA	75		
GASKET, PRE CUT: DIMENSIONS: WD 27 X LG 94 X THK 1 MM; TYPE: RELAY; MATERIAL: RUBBER; SHAPE: RECT; BASE KEY 24 FISH	104953	EA	75		
GASKET, PRE CUT: DIMENSIONS: WD 25 X LG 107 X THK 1 MM; TYPE: BELLOW FRAME KEY; MATERIAL: RUBBER; SHAPE: RECT	104954	EA	75		
SHEET, GASKET: THICKNESS: 3.17 MM; LENGTH: 1.82 M; WIDTH: 1.2 M; MATERIAL: NEOPRENE; IN 50KG ROLL	104966	EA	75		
SHEET, GASKET: THICKNESS: 6 MM; LENGTH: 1.82 M; WIDTH: 1.2 M; MATERIAL: NEOPRENE; IN 50KG ROLL	104967	EA	75		
GASKET SET: TYPE: MEASURING TERMINAL; APPLICATION: PRECIPITATOR; SUPPL P/N: 19/21/21S; REFERENCE NO: K2-37217; TYPE 12 X 22 X 11S; 3 PER SET; FOR SINGLE PHASE TRANSFORMER SEMICONDUCTOR, TYPE G-H-E 8000/1-68C-92625; 380 VOLT; 75KV; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104984	EA	75		
GASKET, PRE CUT: DIMENSIONS: THK 1.5 MM; TYPE: MAIN OIL PUMP; MATERIAL: RUBBER; SHAPE: IRREGULAR; DRAWING NO: 2984C6-1 REV 1; FOR INGERSOLL RAND COMPRESSOR MODEL CENTAC 1-C30EMX4	105751	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 5 X OD 15 X THK 1 MM; TYPE: BELLOWS; MATERIAL: RUBBER; SHAPE: RD; SUPPL P/N: 1D3970-0301; FOR FISHER PRESSURE CONTROLLER MODEL 4162 AND MULTITROL CONTROLLER	106295	EA	75		
SHEET, GASKET: THICKNESS: 10 MM; LENGTH: 2.4 M; WIDTH: 1 M; MATERIAL: RUBBER LINATEX RED	107226	EA	75		
SHEET GSKT:THK 2 MM;LG 2.03 M;WD 1.345 M	135211	EA	75		
SHEET, GASKET: THICKNESS: 12.7 MM; LENGTH: 1.22 M; WIDTH: 1.22 M; MATERIAL: TUFNOL KITE; TYPE INSULATION, MEDIUM WEAVE	135230	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 21 X OD 24 X THK 3 MM; TYPE: DIAPHRAGM; MATERIAL: SILICON; SHAPE: RD; FIG NO: DETAPI 3; REFERENCE NO: 2000-3868; KEY NO:- 21, FOR DELTAPI PNEUMATIC TRANSDUCER MODEL NO:- N-AA	150108	EA	75		
GASKET, PRE CUT: DIMENSIONS: THK 1 MM; TYPE: FRONT COVER; MATERIAL: CORK; SHAPE: IRREGULAR; REFERENCE NO: 3102-0017; FOR DELTAPI TRANSMITTER MODEL:- E-AA 03/1	155596	EA	75		
GASKET, PRE CUT: DIMENSIONS: THK 1 MM; TYPE: BACK COVER; MATERIAL: CORK; SHAPE: IRREGULAR; REFERENCE NO: 3102-0132; FOR DELTAPI TRANSMITTER, MODEL:- E-AA 03/1	155597	EA	75		

COMPOUND, SEALING: TYPE: GASKET/JOINT; COLOR: BLUE UNIVERSAL; CONTAINER: TUBE 100 G; MATERIAL: POLYESTER URETHANE; SUPPL P/N: PL32M; CLAUSE: 1: PLEASE ENSURE THAT SHELF LIFE HISTORY AND EXPIRY DATES ARE DISPLAYED, 2: ITEMS SUBJECTED TO SHELF LIFE WILL NOT BE ACCEPTED TO ESKOM IF MORE THAN 25 PCT OF THE SHELF LIFE HAS ALREADY EXPIRED PRIOR TO DELIVERY; MATERIAL SAFETY DATA SHEETS WITH ENVIRONMENTAL INFORMATION IN THE 16 POINT FORMAT TO BE PROVIDED WITH EVERY DELIVERY AS REQUIRED BY THE OCCUPATIONAL HEALTH AND SAFETY ACT	160266	EA	75		
SHEET, GASKET: THICKNESS: 0.25 MM; LENGTH: 30 M; WIDTH: 3.7 M; MATERIAL: PLASTIC; ROLL	161735	M	200		
SHEET, PLASTIC: WIDTH: 1.22 MM; LENGTH: 1.83 M; THICKNESS: 1.5 MM; MATERIAL: PERSPEX; COLOR: CLEAR; ACRYLIC TYPE, WITHOUT FILLER OR BASE, PROTECTED WITH SELLOPHANE	161745	EA	75		
SHEET, PLASTIC: WIDTH: 1.22 M; LENGTH: 1.83 M; THICKNESS: 3.1 MM; MATERIAL: PERSPEX; COLOR: CLEAR; REFERENCE NO: 3,1MM; (C.O.C; Q4:NSF:NC:NEV); ACRYLIC TYPE; PROTECTED WITH SELLOPHANE	161746	EA	75		
SHEET, PLASTIC: WIDTH: 1.22 MM; LENGTH: 1.83 M; THICKNESS: 6.3 MM; MATERIAL: PERSPEX; COLOR: CLEAR; ACRYLIC TYPE, PROTECTED WITH SELLOPHANE	161747	EA	75		
SHEET, METAL: WIDTH: 925 MM; LENGTH: 1.83 M; THICKNESS: 0.5 MM; MATERIAL: STL; SURFACE TREATMENT: GALV; FLAT; SIZE: 915 MM X 0.71 MM (22WG)	162365	EA	75		
SHEET, METAL: WIDTH: 915 MM; LENGTH: 1.83 M; THICKNESS: 0.91 MM; MATERIAL: CS LOW; SURFACE TREATMENT: GALV; TYPE: FLAT	162367	EA	75		
SHEET, METAL: WIDTH: 195 MM; LENGTH: 300 MM; THICKNESS: 3 MM; MATERIAL: MS; DRAWING NO: ESKOM 13-45/526 REV 1	162404	EA	75		
SHEET, METAL: WIDTH: 200 MM; LENGTH: 1 M; THICKNESS: 3 MM; MATERIAL: MS; DRAWING NO: ESKOM 13-45/526 REV 1	162418	EA	75		
SHEET, METAL: WIDTH: 762 MM; LENGTH: 1.524 M; THICKNESS: 0.71 MM; MATERIAL: STL; SURFACE TREATMENT: GALV; ST	162496	EA	75		
PERFORATED SHEET * STAINLESS STEEL * GRADE 304 * SIZE 1829 X 914 X 1MM THICK WITH 8MM HOLE X 10MM PITCH * 1 sheet = 1.672 m ² PERFORATED SHEET * STAINLESS STEEL * GRADE 304 * SIZE 1829 X 914 X 1MM THICK WITH 8MM HOLE X 10MM PITCH * 1 sheet = 1.672 m ²	162546	EA	75		
SHEET, METAL: WIDTH: 1 M; LENGTH: 2 M; THICKNESS: 1.21 MM; MATERIAL: SS GR 304; FABRICATION METHOD: COLD ROLLED; (18SWG)	162551	EA	300		

SHEET, METAL: WIDTH: 1 M; LENGTH: 2 M; THICKNESS: 0.71 MM; MATERIAL: SS GR 304; SURFACE CONDITION: MILL FINISHED; SPECIFICATION: BS 970-1972; TYPE: (22SWG), NOTE: MATERIAL IDENTIFICATION MUST BE MARKED ON MATERIAL AND SUPPLY WITH CERTIFICATE	162552	EA	300		
SHEET, METAL: WIDTH: 1 M; LENGTH: 2 M; THICKNESS: 0.5 MM; MATERIAL: SS GR 304; FABRICATION METHOD: COLD ROLLED; SPECIFICATION: BS 970-1972 PART 4; (24SWG)	162553	EA	200		
SHEET, METAL: WIDTH: 1 M; LENGTH: 2 M; THICKNESS: 3 MM; MATERIAL: STL 3CR12; NOTE: MATERIAL IDENTIFICATION MUST BE MARKED ON MATERIAL AND SUPPLIED WITH CERTIFICATE	162554	EA	300		
SHEET, METAL: LENGTH: 2.5 M; WIDTH: 1.2 M; THICKNESS: 3 MM; MATERIAL: 15M03; SIZE: 1250 X 2500 X 5.0MM THK; NOTE! MATERIAL IDENTIFICATION MUST BE MARKED ON MATERIAL AND SUPPLY WITH CERTIFICATE VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER.	162566	EA	75		
SHEET, METAL: WIDTH: 1 M; LENGTH: 1 M; THICKNESS: 3 MM; MATERIAL: BRASS	162865	EA	300		
SHEET, GASKET: THICKNESS: 1.5 MM; LENGTH: 1 M; WIDTH: 1 M; MATERIAL: GRAPHITE; REFERENCE NO: V15011Z31; SIGRAFLEX HOCHDRUCK ONLY; 0.5 MM SEAMLESS INTERLEAVED WITH 0.1 MM SS SHEETS	197973	EA	75		
SHEET, GASKET: THICKNESS: 3 MM; LENGTH: 1 M; WIDTH: 1 M; MATERIAL: GRAPHITE; REFERENCE NO: V30011Z31; 0.5 MM SEAMLESS INTERLEAVED WITH 0.1 MM SS SHEETS	197975	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 91 X OD 125 X THK 0.5 MM; TYPE: SEAL; MATERIAL: OILITE; SHAPE: RD; SUPPL P/N: TC424904GR; MODEL NO: APE 125/250 2F; FOR USE ON RITZ 125-250 2F PUMP	206271	EA	75		
GASKET, PRE CUT: TYPE: IMPELLER; MATERIAL: KLINGERSIL; SHAPE: RD; SUPPL P/N: HG250; PPD 005680; FOR USE ON METSO GRAVEL PUMP, FRAME 600	207094	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 200 X OD 273 X THK 6 MM; TYPE: OUTLET; MATERIAL: PU; SHAPE: RD; SUPPL P/N: HG250; PHD 731032; FOR USE ON METSO GRAVEL PUMP, FRAME 600	207204	EA	75		
SHEET, GASKET: THICKNESS: 0.5 MM; LENGTH: 2 M; WIDTH: 1.5 M; MATERIAL: GLASS FIBER/NBR; SUPPL P/N: WEBAGL; NOTE ONLY BURGMANN BRAND ACCEPTABLE, STEAM AND WATER APPLICATION, TEMPERATURE: 440 DEG C, PRESSURE: 100 BAR/1450 PSI	210351	EA	75		

SHEET, GASKET: THICKNESS: 0.8 MM; LENGTH: 2 M; WIDTH: 1.5 M; MATERIAL: GLASS FIBER/NBR; SUPPL P/N: WEBAGL; NOTE ONLY BURGMANN BRAND ACCEPTABLE, STEAM AND WATER APPLICATION, TEMPERATURE: 440 DEG C, PRESSURE: 100 BAR/1450 PSI	210352	EA	75		
SHEET, GASKET: THICKNESS: 3 MM; LENGTH: 2 M; WIDTH: 1.5 M; MATERIAL: ARAMID FIBER/NBR; SUPPL P/N: WEBA401; NOTE ONLY BURGMANN BRAND ACCEPTABLE, APPLICATION: OIL, TEMPERATURE: 350 DEG C, PRESSURE: 50 BAR/725 PSI	210353	EA	75		
SHEET, GASKET: THICKNESS: 1.5 MM; LENGTH: 1.5 M; WIDTH: 1.5 M; MATERIAL: GLASS FIBER/NBR; SUPPL P/N: WEBAGL; NOTE ONLY BURGMANN BRAND ACCEPTABLE, STEAM AND WATER APPLICATION, TEMPERATURE: 440 DEG C, PRESSURE: 100 BAR/1450 PSI	210354	EA	75		
SHEET, GASKET: THICKNESS: 2 MM; LENGTH: 2 M; WIDTH: 1.5 M; MATERIAL: GLASS FIBER/NBR; SUPPL P/N: WEBAGL; NOTE ONLY BURGMANN BRAND ACCEPTABLE, STEAM AND WATER APPLICATION, TEMPERATURE: 440 DEG C, PRESSURE: 100 BAR/1450 PSI	210355	EA	75		
SHEET, GASKET: THICKNESS: 3 MM; LENGTH: 1.5 M; WIDTH: 1.5 M; MATERIAL: GLASS FIBER/NBR; SUPPL P/N: WEBAGL; NOTE ONLY BURGMANN BRAND ACCEPTABLE, STEAM AND WATER APPLICATION, TEMPERATURE: 440 DEG C, PRESSURE: 100 BAR/1450 PSI	210356	EA	75		
SHEET, GASKET: THICKNESS: 0.5 MM; LENGTH: 2 M; WIDTH: 1.5 M; MATERIAL: NBR/WOOL MINERAL FIBER; SUPPL P/N: WEBA6000; SUPPLIER NOTE ONLY BURGMANN BRAND ACCEPTABLE, STEAM APPLICATION: PEAK TEMPERATURE; 440 DEG C, CONTINUOUS TEMPERATURE; 350 DEG C, TEMPERATURE WITH STEAM; 300 DEG C, PRESSURE: 120 BAR/1740 PSI	210357	EA	75		
SHEET, GASKET: THICKNESS: 0.8 MM; LENGTH: 2 M; WIDTH: 1.5 M; MATERIAL: NBR/WOOL MINERAL FIBER; SUPPL P/N: WEBA6000; SUPPLIER NOTE ONLY BURGMANN BRAND ACCEPTABLE, STEAM APPLICATION: PEAK TEMPERATURE; 440 DEG C, CONTINUOUS TEMPERATURE; 350 DEG C, TEMPERATURE WITH STEAM; 300 DEG C, PRESSURE: 120 BAR/1740 PSI	210358	EA	75		
SHEET, GASKET: THICKNESS: 1 MM; LENGTH: 2 M; WIDTH: 1.5 M; MATERIAL: NBR/WOOL MINERAL FIBER; SUPPL P/N: WEBA6000; SUPPLIER NOTE ONLY BURGMANN BRAND ACCEPTABLE, STEAM APPLICATION: PEAK TEMPERATURE; 440 DEG C, CONTINUOUS TEMPERATURE; 350 DEG C, TEMPERATURE WITH STEAM; 300 DEG C, PRESSURE: 120 BAR/1740 PSI	210359	EA	75		

SHEET, GASKET: THICKNESS: 1.5 MM; LENGTH: 2 M; WIDTH: 1.5 M; MATERIAL: NBR/WOOL MINERAL FIBER; SUPPL P/N: WEBA6000; SUPPLIER NOTE ONLY BURGMANN BRAND ACCEPTABLE, STEAM APPLICATION: PEAK TEMPERATURE; 440 DEG C, CONTINUOUS TEMPERATURE; 350 DEG C, TEMPERATURE WITH STEAM; 300 DEG C, PRESSURE: 120 BAR/1740 PSI	210360	EA	75		
SHEET, GASKET: THICKNESS: 2 MM; LENGTH: 2 M; WIDTH: 1.5 M; MATERIAL: NBR/WOOL MINERAL FIBER; SUPPL P/N: WEBA6000; SUPPLIER NOTE ONLY BURGMANN BRAND ACCEPTABLE, STEAM APPLICATION: PEAK TEMPERATURE; 440 DEG C, CONTINUOUS TEMPERATURE; 350 DEG C, TEMPERATURE WITH STEAM; 300 DEG C, PRESSURE: 120 BAR/1740 PSI	210361	EA	75		
SHEET, GASKET: THICKNESS: 0.5 MM; LENGTH: 2 M; WIDTH: 1.5 M; MATERIAL: ARAMID FIBER/NBR; SUPPL P/N: WEBA203; NOTE ONLY BURGMANN BRAND ACCEPTABLE, APPLICATION: OIL AND WATER, TEMPERATURE: 250 DEG C, PRESSURE: 50 BAR/725 PSI	210363	EA	75		
SHEET, GASKET: THICKNESS: 0.8 MM; LENGTH: 2 M; WIDTH: 1.5 M; MATERIAL: ARAMID FIBER/NBR; SUPPL P/N: WEBA203; NOTE ONLY BURGMANN BRAND ACCEPTABLE, APPLICATION: OIL AND WATER, TEMPERATURE: 250 DEG C, PRESSURE: 50 BAR/725 PSI	210364	EA	75		
SHEET, GASKET: THICKNESS: 1 MM; LENGTH: 2 M; WIDTH: 1.5 M; MATERIAL: ARAMID FIBER/NBR; SUPPL P/N: WEBA203; NOTE ONLY BURGMANN BRAND ACCEPTABLE, APPLICATION: OIL AND WATER, TEMPERATURE: 250 DEG C, PRESSURE: 50 BAR/725 PSI	210365	EA	75		
SHEET, GASKET: THICKNESS: 1.5 MM; LENGTH: 2 M; WIDTH: 1.5 M; MATERIAL: ARAMID FIBER/NBR; SUPPL P/N: WEBA203; NOTE ONLY BURGMANN BRAND ACCEPTABLE, APPLICATION: OIL AND WATER, TEMPERATURE: 250 DEG C, PRESSURE: 50 BAR/725 PSI	210366	EA	75		
SHEET, GASKET: THICKNESS: 2 MM; LENGTH: 2 M; WIDTH: 1.5 M; MATERIAL: ARAMID FIBER/NBR; SUPPL P/N: WEBA203; NOTE ONLY BURGMANN BRAND ACCEPTABLE, APPLICATION: OIL AND WATER, TEMPERATURE: 250 DEG C, PRESSURE: 50 BAR/725 PSI	210367	EA	75		
SHEET, GASKET: THICKNESS: 0.5 MM; LENGTH: 2 M; WIDTH: 1.5 M; MATERIAL: ARAMID FIBER/NBR; SUPPL P/N: WEBA401; NOTE ONLY BURGMANN BRAND ACCEPTABLE, APPLICATION: OIL, TEMPERATURE: 350 DEG C, PRESSURE: 50 BAR/725 PSI	210373	EA	75		
SHEET, GASKET: THICKNESS: 0.8 MM; LENGTH: 2 M; WIDTH: 1.5 M; MATERIAL: ARAMID FIBER/NBR; SUPPL P/N: WEBA401; NOTE ONLY BURGMANN BRAND ACCEPTABLE, APPLICATION: OIL, TEMPERATURE: 350 DEG C, PRESSURE: 50 BAR/725 PSI	210374	EA	75		

SHEET, GASKET: THICKNESS: 1 MM; LENGTH: 2 M; WIDTH: 1.5 M; MATERIAL: ARAMID FIBER/NBR; SUPPL P/N: WEBA401; NOTE ONLY BURGMANN BRAND ACCEPTABLE, APPLICATION: OIL, TEMPERATURE: 350 DEG C, PRESSURE: 50 BAR/725 PSI	210375	EA	75		
HEET, GASKET: THICKNESS: 1.5 MM; LENGTH: 2 M; WIDTH: 1.5 M; MATERIAL: ARAMID FIBER/NBR; SUPPL P/N: WEBA401; NOTE ONLY BURGMANN BRAND ACCEPTABLE, APPLICATION: OIL, TEMPERATURE: 350 DEG C, PRESSURE: 50 BAR/725 PSI	210376	EA	75		
SHEET, GASKET: THICKNESS: 2 MM; LENGTH: 2 M; WIDTH: 1.5 M; MATERIAL: ARAMID FIBER/NBR; SUPPL P/N: WEBA401; NOTE ONLY BURGMANN BRAND ACCEPTABLE, APPLICATION: OIL, TEMPERATURE: 350 DEG C, PRESSURE: 50 BAR/725 PSI	210377	EA	75		
SHEET, GASKET: THICKNESS: 0.5 MM; LENGTH: 2 M; WIDTH: 1.5 M; MATERIAL: ARAMID FIBER/CMS; SUPPL P/N: WEBAA301; NOTE ONLY BURGMANN BRAND ACCEPTABLE, APPLICATION: ACIDS AND ALKALINE, TEMPERATURE: 200 DEG C, PRESSURE: 60 BAR/870 PSI	210379	EA	75		
SHEET, GASKET: THICKNESS: 0.8 MM; LENGTH: 2 M; WIDTH: 1.5 M; MATERIAL: ARAMID FIBER/CMS; SUPPL P/N: WEBAA301; NOTE ONLY BURGMANN BRAND ACCEPTABLE, APPLICATION: ACIDS AND ALKALINE, TEMPERATURE: 200 DEG C, PRESSURE: 60 BAR/870 PSI	210380	EA	75		
SHEET, GASKET: THICKNESS: 1 MM; LENGTH: 2 M; WIDTH: 1.5 M; MATERIAL: ARAMID FIBER/CMS; SUPPL P/N: WEBAA301; NOTE ONLY BURGMANN BRAND ACCEPTABLE, APPLICATION: ACIDS AND ALKALINE, TEMPERATURE: 200 DEG C, PRESSURE: 60 BAR/870 PSI	210381	EA	75		
SHEET, GASKET: THICKNESS: 1.5 MM; LENGTH: 2 M; WIDTH: 1.5 M; MATERIAL: ARAMID FIBER/CMS; SUPPL P/N: WEBAA301; NOTE ONLY BURGMANN BRAND ACCEPTABLE, APPLICATION: ACIDS AND ALKALINE, TEMPERATURE: 200 DEG C, PRESSURE: 60 BAR/870 PSI	210382	EA	75		
SHEET, GASKET: THICKNESS: 2 MM; LENGTH: 2 M; WIDTH: 1.5 M; MATERIAL: ARAMID FIBER/CMS; SUPPL P/N: WEBAA301; NOTE ONLY BURGMANN BRAND ACCEPTABLE, APPLICATION: ACIDS AND ALKALINE, TEMPERATURE: 200 DEG C, PRESSURE: 60 BAR/870 PSI	210383	EA	75		
SHEET, GASKET: THICKNESS: 3 MM; LENGTH: 2 M; WIDTH: 1.5 M; MATERIAL: ARAMID FIBER/CMS; SUPPL P/N: WEBAA301; NOTE ONLY BURGMANN BRAND ACCEPTABLE, APPLICATION: ACIDS AND ALKALINE, TEMPERATURE: 200 DEG C, PRESSURE: 60 BAR/870 PSI	210384	EA	75		
SHEET, GASKET: THICKNESS: 0.4 MM; LENGTH: 1 M; WIDTH: 1 M; MATERIAL: VELLUMOID; SUPPL P/N: STATITE; SUPPLIER NOTE: EACH ROLL TO BE SEALED IN A PLASTIC BAG AND CLEARLY MARKED	210819	EA	250		

SHEET, GASKET: THICKNESS: 0.8 MM; LENGTH: 10 M; WIDTH: 1 M; MATERIAL: VELLUMOID; SUPPLIER NOTE: EACH ROLL MUST BE SEALED IN A PLASTIC BAG AND CLEARLY MARKED	210820	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 57.2 X OD 63 X THK 0.5 MM; TYPE: RING; MATERIAL: CU; SHAPE: RD; REFERENCE NO: BZ-2R-A2-N94; FOR USE ON BECKER AND SOHNE COMPRESSOR, POS NO 8/185	212652	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 42.2 X OD 47 X THK 0.5 MM; TYPE: RING; MATERIAL: CU; SHAPE: RD; SUPPL P/N: 028185; MODEL NO: SVC600/250; FOR USE ON BECKER AND SOHNE COMPRESSOR, POS NO 10/210	212653	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 21.2 X OD 28 X THK 1 MM; TYPE: RING; MATERIAL: CU; SHAPE: RD; SUPPL P/N: 028215; MODEL NO: SVC600/250; FOR USE ON BECKER AND SOHNE COMPRESSOR, POS NO 11/232	212656	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 28 X OD 34 X THK 1 MM; TYPE: RING; MATERIAL: CU; SHAPE: RD; SUPPL P/N: 172465; MODEL NO: SVC600/250; FOR USE ON BECKER AND SOHNE COMPRESSOR, POS NO 11/237	212657	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 11.2 X OD 19 X THK 0.5 MM; TYPE: RING; MATERIAL: CU; SHAPE: RD; SUPPL P/N: 028231; MODEL NO: SVC600/250; FOR USE ON BECKER AND SOHNE COMPRESSOR, POS NO 12/253	212660	EA	75		
SHEET, GASKET: THICKNESS: 1 MM; LENGTH: 2 M; WIDTH: 1.5 M; MATERIAL: MICA WIRE REINFORCED; ONLY KLINGER TOP-MIC BRAND ACCEPTABLE, A COMBINATION OF SPECIALLY SELECTED MICA, SYNTHETIC FIBERS AND FILLERS TO GIVE A SEALING MATERIAL WITH OUTSTANDING FLEXIBILITY AND EXCELLENT STABILITY IN STEAM, ACCEPTABLE FOR USE ON 5MPA/425 DEG C, FOR USE ON HIGHER PRESSURE AND TEMPERATURE CONTACT KRIEL ENGINEERING	213835	EA	75		
SHEET, GASKET: THICKNESS: 1.5 MM; LENGTH: 2 M; WIDTH: 1.5 M; MATERIAL: MICA WIRE REINFORCED; ONLY KLINGER TOP-MIC BRAND ACCEPTABLE, A COMBINATION OF SPECIALLY SELECTED MICA, SYNTHETIC FIBERS AND FILLERS TO GIVE A SEALING MATERIAL WITH OUTSTANDING FLEXIBILITY AND EXCELLENT STABILITY IN STEAM, ACCEPTABLE FOR USE ON 5 MPA/425 DEG C, FOR USE ON HIGHER PRESSURE AND TEMPERATURE CONTACT KRIEL ENGINEERING	213836	EA	75		

SHEET, GASKET: THICKNESS: 2 MM; LENGTH: 2 M; WIDTH: 1.5 M; MATERIAL: MICA WIRE REINFORCED; ONLY KLINGER TOP-MIC BRAND ACCEPTABLE, A COMBINATION OF SPECIALLY SELECTED MICA, SYNTHETIC FIBERS AND FILLERS TO GIVE A SEALING MATERIAL WITH OUTSTANDING FLEXIBILITY AND EXCELLENT STABILITY IN STEAM, ACCEPTABLE FOR USE ON 5 MPA/425 DEG C, FOR USE ON HIGHER PRESSURE AND TEMPERATURE CONTACT KRIEL ENGINEERING	213837	EA	75		
SHEET, GASKET: THICKNESS: 3 MM; LENGTH: 2 M; WIDTH: 1.5 M; MATERIAL: MICA WIRE REINFORCED; ONLY KLINGER TOP-MIC BRAND ACCEPTABLE, A COMBINATION OF SPECIALLY SELECTED MICA, SYNTHETIC FIBERS AND FILLERS TO GIVE A SEALING MATERIAL WITH OUTSTANDING FLEXIBILITY AND EXCELLENT STABILITY IN STEAM, ACCEPTABLE FOR USE ON 5 MPA/425 DEG C, FOR USE ON HIGHER PRESSURE AND TEMPERATURE CONTACT KRIEL ENGINEERING	213838	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 228 X OD 250 X THK 2 MM; TYPE: TURBO GENERATORS; SUPPL P/N: GME0810014 R0001	230439	EA	75		
KIT, COMPRESSOR REPAIR: TYPE: GASKET; APPLICATION: CENTRAL COMPRESSOR; SUPPL P/N: 901 528 44; SHAPE ROUND, FOR THE SEALING, MATERIAL RUBBER	231601	EA	75		
SHEET, GASKET: LENGTH: 1 M; WIDTH: 1 M; MATERIAL: GRAPHITE; REFERENCE NO: PRODUCT 359; REINFORCED WITH SS FOIL, 870 DEG C, NON-OXIDISING AND 425 DEG C, OXIDIZING ATMOSPHERE, 140 BAR MAXIMUM PRESSURE, 35 PCT COMPRESSIBILITY	253238	EA	75		
SEAL: TYPE: SYNTHETIC GASKET; DIMENSIONS: DIA 500 X HT 100 MM; MATERIAL: NEOPRENE; APPLICATION: BUSBAR ENCLOSURE; SUPPL P/N: P G 41054	256217	EA	75		
GASKET, PRE CUT: DIMENSIONS: SQ 1.5 M X THK 1.5 MM; TYPE: STEAM; MATERIAL: FIBER; SHAPE: RECT; SUPPL P/N: BLUE-GARD 3400; APPLICATION: TURBINE GENERATOR	256709	EA	300		
SEAL: TYPE: GASKET; DIMENSIONS: DIA 500 X HT 100 MM; MATERIAL: NEOPRENE; APPLICATION: BUSBAR ENCLOSURE; 18KV; COMES IN 50 M ROLL	527982	EA	75		
SEALANT: TYPE: GASKET MAKER; CONTAINER: TUBE; MATERIAL: SILICON; COLOR: RED; TEMPERATURE RATING: +300 DEG C; ACETOXY 100%	597292	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 1.484 X OD 1.534 M; THICKNESS: 5 MM; TYPE: ISOLATION; MATERIAL: CERAMIC FIBER; SHAPE: ROUND; TEMPERATURE RATING: 0-1100 DEG C; ISOPLAN 1100; LYTHERM; DATA SHEET REQUIRED FOR QUALITY AND CERTIFICATION PURPOSES; GASKET IS 5 TIMES SEGMENTED; CONVERTOR GASKET LID	608937	EA	75		

GASKET, PRE CUT: DIMENSIONS: ID 330 X OD 390 MM; THICKNESS: 5 MM; TYPE: INSULATOR; MATERIAL: CERAMIC FIBER; SHAPE: ROUND; TEMPERATURE RATING: 0-1100 DEG C; ISOPLAN 1100; LYTHERM; ISOPLAN 1100; DATA SHEET REQUIRED FOR QUALITY AND CERTIFICATION PURPOSES; CONVERTOR OUTLET	608940	EA	75		
GASKET, SPIRAL WOUND: INNER RING INSIDE DIAMETER: 35 MM; FILLER OUTSIDE DIAMETER: 90 MM; FILLER INSIDE DIAMETER: 35 MM; OUTER RING OUTSIDE DIAMETER: 90 MM; PRESSURE RATING: 10 BAR; FILLER MATERIAL: GRAPHITE; WINDING MATERIAL: GRAPHITE/STL; SHAPE: ROUND; THICKNESS: 3 MM; TEMPERATURE RATING 550 DEG C	608945	EA	75		
GASKET, PRE CUT: DIMENSIONS: SQ 1 M; THICKNESS: 5; TYPE: INSULATION; MATERIAL: LYTHERM CERAMIC; SHAPE: SQ; SPECIFICATION: ISO PLAN 1100 CERENZECIT; ISSUE AS A SET; S03 GASKET SHEET; FRENZELIT ISOPLAN 1100 DATA SHEET REQUIRED FOR QUALITY AND CERTIFICATION PURPOSE; GASKET TO BE PACKAGED SECURLEY TO LIMIT DAMAGED AS IT IS VERY BRITTLE	611527	EA	75		
GASKET, SPIRAL WOUND: STYLE: TANGED METAL CORE; INNER RING INSIDE DIAMETER: 800 X 800 MM; OUTER RING OUTSIDE DIAMETER: 1 X 1 M; PRESSURE RATING: 20; FILLER MATERIAL: GRAPHITE; WINDING MATERIAL: SS GR 316; SHAPE: SQ; THICKNESS: 3 MM; SO3 GRAPHITE SHEET; TECHNICAL DATA SHEET TO BE SUPPLIED TOGETHER WITH THE GASKET; TEMPERATURE 550 DEGREE CEL; GASKET TO BE SUPPLIED AS A SHEET	611528	EA	75		
GASKET: TYPE: NRV; DIMENSIONS: ID 140 X OD 152 X THK 45 MM; MATERIAL: CU ANNEALED; SUPERHEATER SPRAYWATER NRV	624590	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 12 X OD 16 MM; THICKNESS: 8 MM; TYPE: SEAL; MATERIAL: GRAPHITE; SHAPE: RD; PRESSURE RATING: 18 MPA; TEMPERATURE RATING: 300 DEG C	654420	EA	75		
GASKET, PRE CUT: DIMENSIONS: WD 75 X LG 312 MM; THICKNESS: 2 MM; TYPE: MODULE; MATERIAL: MAX GUMMI; SHAPE: RECTANGULAR; SPECIFICATION: 52900; SUPPL P/N: 004.1468; MOUNTING PLATE	658308	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 258.5 X OD 320 MM; THICKNESS: 5 MM; TYPE: METALFLEX SEAL; MATERIAL: GRAPHITE/SS; SHAPE: RD; PRESSURE RATING: 2 MPA; TEMPERATURE RATING: 300 DEG C	659248	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 260 X OD 380 MM; THICKNESS: 31 MM; TYPE: COVER PLATE; MATERIAL: GRAPHITE	662366	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 61 X OD 80 MM; THICKNESS: 4.5 MM; TYPE: PREFORMED SEAL; MATERIAL: GRAPHITE/SS GR 304; SHAPE: ROUND; PRESSURE RATING: 2 MPA; TEMPERATURE RATING: 500 DEG C;	662431	EA	75		

SPECIFICATION: CRIR80X61X43X30X4.5S/S					
GASKET, PRE CUT: DIMENSIONS: ID 15 X OD 25 MM; THICKNESS: 10 MM; TYPE: OIL COOLER FRONT AND REAR; MATERIAL: GRAPHITE; SHAPE: CIRCULAR; SPECIFICATION: TA3000; SUPPL P/N: AAP1405680-00001	664381	EA	75		
GASKET, PRE CUT: DIMENSIONS: ID 71.2 X OD 81.24 MM; THICKNESS: 2 MM; TYPE: SEAL; MATERIAL: HARDEN PAPER; SHAPE: RD; HOLES: 4; DRAWING NO: 28.45/59290 REV 0; HOLE SIZE: 14MM	666812	EA	75		
GASKET, SPIRAL WOUND: STYLE: CR; INNER RING INSIDE DIAMETER: 400.1 MM; FILLER OUTSIDE DIAMETER: 466.6 MM; FILLER INSIDE DIAMETER: 422.4 MM; OUTER RING OUTSIDE DIAMETER: 514.4 MM; NOMINAL FLANGE SIZE: NB400; PRESSURE RATING: 0.5 MPA; INNER RING MATERIAL: SS 304; FILLER MATERIAL: GRAPHITE; WINDING MATERIAL: CARBON STL; SHAPE: CIRCULAR; SPECIFICATION: ASME B16.2; THICKNESS: 3.2 MM; TEMPERATURE RATED: 500DEG C; CL105	667383	EA	75		
GASKET, SPIRAL WOUND: STYLE: CRIR; INNER RING INSIDE DIAMETER: 349.3 MM; FILLER OUTSIDE DIAMETER: 406.4 MM; FILLER INSIDE DIAMETER: 371.6 MM; OUTER RING OUTSIDE DIAMETER: 450.9 MM; NOMINAL FLANGE SIZE: NB350; PRESSURE RATING: 0.5 MPA; INNER RING MATERIAL: SS 304; FILLER MATERIAL: GRAPHITE; WINDING MATERIAL: CARBON STL; SHAPE: CIRCULAR; SPECIFICATION: ASME B16.2; THICKNESS: 3.2 MM; TEMPERATURE RATED: 500DEG C; CL105	667384	EA	75		
GASKET, SPIRAL WOUND: STYLE: CRIR; INNER RING INSIDE DIAMETER: 57 MM; FILLER OUTSIDE DIAMETER: 84 MM; FILLER INSIDE DIAMETER: 66 MM; OUTER RING OUTSIDE DIAMETER: 134 MM; PRESSURE RATING: 5.5 BAR; INNER RING MATERIAL: SS 304; FILLER MATERIAL: GRAPHITE; WINDING MATERIAL: SS 304; SHAPE: RD; SPECIFICATION: ASME B16.20; THICKNESS: 4.5 MM	670570	EA	75		
GASKET, SPIRAL WOUND: STYLE: CRIR; INNER RING INSIDE DIAMETER: 57 MM; FILLER OUTSIDE DIAMETER: 84 MM; FILLER INSIDE DIAMETER: 66 MM; OUTER RING OUTSIDE DIAMETER: 150 MM; PRESSURE RATING: 5.5 BAR; INNER RING MATERIAL: SS 304; FILLER MATERIAL: GRAPHITE; WINDING MATERIAL: SS 304; SHAPE: RD; SPECIFICATION: ASME B16.20; THICKNESS: 4.5 MM	670571	EA	75		
GASKET: TYPE: RING; DIMENSIONS: OD 10 IN X THK 1.5 MM; MATERIAL: C4400; SHAPE: CIRCULAR; APPLICATION: SEAL FOR DESICCANT TOWERS; MANUF P/N: D71132; GREEN IN COLOUR	711383	EA	75		

GASKET: TYPE: RING; DIMENSIONS: OD 1 IN X THK 1.5 MM; MATERIAL: C4400; SHAPE: CIRCULAR; APPLICATION: SEAL FOR 4 WAY VALVE; MANUF P/N: D52564; GREEN	711386	EA	75		
SUBTOTAL					
<u>PACKINGS (123)</u>					
PACKING, PREFORMED: INSIDE DIAMETER: 110 MM; OUTSIDE DIAMETER: 130 MM; THICKNESS: 10 MM; MATERIAL: GRAPHITE; DRAWING NO: A50300-202 REV 1; SEAL, SQUARE PROFILE, FOR MAIN FEED WATER BYPASS REGULATING VALVE; NOTE - ITEM MUST BE PROTECTIVE PACKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	19843	EA	75		
PACKING, PREFORMED: INSIDE DIAMETER: 210 MM; OUTSIDE DIAMETER: 225 MM; THICKNESS: 34 MM; TYPE: RING; MATERIAL: GRAPHITE; SUPPL P/N: X1630T3B; REFERENCE NO: X1630T3B; RIDER HP PISTON CYLINDER, FOR COMPRESSOR XLE; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	42523	EA	75		
PACKING: TYPE: SHAFT OIL PUMP; DRAWING NO: R403838 POS 569 REV 1; SHAFT; FOR LEAKAGE OIL PUMP; TYPE- NDF 25-3	45517	EA	75		
PACKING, PREFORMED: INSIDE DIAMETER: 22 MM; OUTSIDE DIAMETER: 35 MM; THICKNESS: 13 MM; TYPE: VALVE RING; MATERIAL: GRAPHITE; SUPPL P/N: 38213-506; FIG NO: 8609W; MODEL NO: 61-36-1; REFERENCE NO: 38213-506; USE ON KORUTE BLOCKS; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	71013	EA	75		
PACKING, PREFORMED: INSIDE DIAMETER: 25 MM; OUTSIDE DIAMETER: 45 MM; THICKNESS: 15 MM; TYPE: RECT RING VALVE; MATERIAL: GRAPHITE; FIG NO: 26428W; 21928W/26428W; 21928W; REFERENCE NO: 38214-104; KORUTE BLOCK, FOR 3/4 INCH VALVES; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	71014	EA	75		
PACKING, PREFORMED: INSIDE DIAMETER: 15.5 MM; OUTSIDE DIAMETER: 31.8 MM; THICKNESS: 10 MM; TYPE: RING; MATERIAL: GRAPHITE; FIG NO: 86514W; REFERENCE NO: 38213-112; SHAPE KORUTE BLOCK, FOR 20MM VALVE; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	71088	EA	75		

PACKING, PREFORMED: INSIDE DIAMETER: 32 MM; OUTSIDE DIAMETER: 50 MM; THICKNESS: 12 MM; TYPE: RING; MATERIAL: GRAPHITE; FIG NO: 24940W; REFERENCE NO: 38214-155; 38214-116; SHAPE KORUTE BLOCK FOR 5 INCH VALVE; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	71090	EA	75		
PACKING, PREFORMED: INSIDE DIAMETER: 34.8 MM; OUTSIDE DIAMETER: 55 MM; THICKNESS: 15.5 MM; MATERIAL: GRAPHITE; FIG NO: 21928W; REFERENCE NO: 38214-503B; 38214-527; KORUTE BLOCK, FOR 2 IN HOPKINSON PARALLEL SLIDE VALVE; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	71091	EA	75		
PACKING, PREFORMED: INSIDE DIAMETER: 12.5 MM; OUTSIDE DIAMETER: 22.4 MM; THICKNESS: 8 MM; TYPE: RING; MATERIAL: GRAPHITE; SUPPL P/N: 38213-111; FIG NO: 86260; KORUTE BLOCK PACKING, FOR 1/4 INCH VALVE; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	71149	EA	75		
PACKING, PREFORMED: INSIDE DIAMETER: 22 MM; OUTSIDE DIAMETER: 41.5 MM; THICKNESS: 10 MM; TYPE: RING; MATERIAL: GRAPHITE; MODEL NO: 38213-512; KORUTE BLOCK PACKING, FOR 1-1/4 INCH VALVE; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	71150	EA	75		
PACKING, PREFORMED: INSIDE DIAMETER: 47 MM; OUTSIDE DIAMETER: 74 MM; THICKNESS: 16 MM; TYPE: RING; MATERIAL: GRAPHITE; FIG NO: 24950W; REFERENCE NO: 38215-503; KORUTE BLOCK, FOR 9 INCH VALVE, NOTE - ITEM MUST BE PROTECTED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	71306	EA	75		
PACKING, PREFORMED: INSIDE DIAMETER: 80 MM; OUTSIDE DIAMETER: 112 MM; THICKNESS: 12.5 MM; TYPE: RING; MATERIAL: GRAPHITE; FIG NO: 23928W; REFERENCE NO: 38216-507; SHAPE RECTANGULAR, KORUTE BLOCK, FOR 8 INCH HOPKINSON VALVE; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	71307	EA	75		

PACKING, PREFORMED: INSIDE DIAMETER: 29 MM; OUTSIDE DIAMETER: 60 MM; THICKNESS: 13 MM; TYPE: RING; MATERIAL: GRAPHITE; FIG NO: 86528W; 38214-158; REFERENCE NO: 38214-158; 86528W; KORUTE BLOCK, CAF, FOR 2 INCH STOP VALVE; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	71401	EA	75		
PACKING, PREFORMED: INSIDE DIAMETER: 60 MM; OUTSIDE DIAMETER: 80 MM; MATERIAL: PTFE; DRAWING NO: 0.42092-EB REV 1; REFERENCE NO: 119023062055; STUFFING BOX, SHAPE ROUND, CONSISTS OF SEVEN PIECES, SUPPLIER NOTE - THE ITEM MUST BE PROTECTIVE PACKED, SEALED AND CLEARLY MARKED WITH MATERIAL NUMBER 0073759; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	73759	EA	75		
PACKING, PREFORMED: INSIDE DIAMETER: 25 MM; OUTSIDE DIAMETER: 38 MM; TYPE: RING; MATERIAL: PTFE; REFERENCE NO: 2445; SB175254; LG 71MM; FOR BUTTERFLY VALVES, TYPE 7610Z, SIZE 250, ORDER NUMBER 53/7304-3062 B2 ITEM 10, AS DETAILED IN FISCHER BOOKLET NUMBER 2445 DATED APRIL 1972; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	73821	EA	75		
PACKING, PREFORMED: INSIDE DIAMETER: 25 MM; OUTSIDE DIAMETER: 45 MM; THICKNESS: 10 MM; TYPE: RING; MATERIAL: GRAPHITE; SUPPL P/N: 1D7518-01052; VALVE, SHAPE FOR FISHER CONTROL VALVE 657-AR, BSV 7343, SIZE 12 X 8 INCH; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	73851	EA	75		
PACKING, PREFORMED: INSIDE DIAMETER: 32 MM; OUTSIDE DIAMETER: 48 MM; THICKNESS: 8 MM; TYPE: RING; MATERIAL: NITRILE; FOR SULZER SERVO MOTOR, ASM160, SHAPE, COMPRISING OF 4 PIECES, SUPPLIER NOTE - THE ITEM MUST BE PROTECTIVE PACKED AND CLEARLY MARKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	74308	EA	75		
PACKING, BULK: MATERIAL: GRAPHITE; TYPE: FLAKE; SUPPL P/N: CPL333; TO BE SUPPLIED IN 5KG PLASTIC BAGS	97623	KG	75		

PACKING, PREFORMED: INSIDE DIAMETER: 70 MM; OUTSIDE DIAMETER: 80 MM; THICKNESS: 10 MM; TYPE: SOLID RING; MATERIAL: GRAPHITE; DRAWING NO: WELLAND AND TUXHORN 0.46060/1E REV 1; REFERENCE NO: KTDF/59; SEAL, 45 DEGREES INSIDE CHAMFER; FOR WELLAND AND TUXHORN INJECTION CONTROL VALVE DN32 DN40 PN160; NOTE - ITEM MUST BE PROTECTIVE PACKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	98165	EA	75		
PACKING, PREFORMED: INSIDE DIAMETER: 60 MM; OUTSIDE DIAMETER: 70 MM; THICKNESS: 8.5 MM; MATERIAL: GRAPHITE; DRAWING NO: 0.46060/1E REV 1; REFERENCE NO: KTDF/6; SEAL; SOLID; 45 DEGREE INSIDE CHAMFER; FOR WELLAND AND TUXHORN INJECTION CONTROL VALVE; TYPE DN32 DN40 PN160; NOTE - ITEM MUST BE PROTECTIVE PACKED; SHAPE: RING; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	98166	EA	75		
PACKING, PREFORMED: SIZE 24.5MM X 30.5MM ID X 40MM X 41.5MM OD X 55.5MM THK, SHAPE ROUND, DIN NUMBER 32; FOR SO3 PLANT; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	98912	EA	75		
PACKING: MATERIAL: TEFLON; SET, FOR SULPHUR COCK DN 50; FOR SO3 PLANT	98913	EA	75		
PACKING, PREFORMED: INSIDE DIAMETER: ID (54 X 49.5) X OD (75.5 X 49.5) X THK 120 MM; TYPE: RING; MATERIAL: TEFLON; SET, FOR SULPHUR COCK DN 80; FOR SO3 PLANT; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	98914	EA	75		
PACKING, PREFORMED: INSIDE DIAMETER: 35 MM; OUTSIDE DIAMETER: 54 MM; THICKNESS: 70 MM; TYPE: V RING; MATERIAL: TEFLON; MODEL NO: K2/61-14; DURCO DOSING PUMP, ON SO3 PLANT, NOTE - ITEM MUST BE PROTECTIVE PACKED, SEALED AND MARKED WITH MATERIAL NUMBER 0098915; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	98915	EA	75		

PACKING, PREFORMED: INSIDE DIAMETER: 110 MM; OUTSIDE DIAMETER: 120 MM; THICKNESS: 12 MM; TYPE: BOTTOM LEAK OFF; MATERIAL: GRAPHITE; COLOR: BLACK; REFERENCE NO: 119-023-061-724; FOR USE ON WELLAND AND TUXHORN LEAK-OFF VALVE DN150, PN320, DN100, PN400 AND DN400, PN400, THE ITEM MUST BE PROTECTIVE PACKED, SEALED AND CLEARLY MARKED WITH MATERIAL NUMBER 0099894; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	99894	EA	75		
PACKING, PREFORMED: INSIDE DIAMETER: 195 MM; OUTSIDE DIAMETER: 210 MM; THICKNESS: 16 MM; MATERIAL: GRAPHITE; DRAWING NO: WELLAND AND TUXHORN Z NO 0.47499-E REV 1; REFERENCE NO: KTDF/56; SHAPE CHAMFER RING, SEAL 7.5MM WALL THICKNESS; SHAMFER SIZE 8MM ON INSIDE DIA X 16MM ON OUTSIDE DIA; ANGLE 45 DEG; FOR 66PCT DRAIN OUTFLOW CONTROL VALVE BODY; DN200/250; PN320; POSITION 10063; NOTE - SEAL TO BE MANUFACTURED TO NUCLEAR STANDARDS AND PROTECTIVE PACKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	100010	EA	75		
PACKING, PREFORMED: INSIDE DIAMETER: 175 MM; OUTSIDE DIAMETER: 190 MM; THICKNESS: 7.5 MM; TYPE: RING; MATERIAL: GRAPHITE; DRAWING NO: WELLAND/TUXHORN Z 0.47499-E POS 10063 REV 1; REFERENCE NO: KTDF/57; SHAPE CHAMFER SEAL; WALL THICKNESS X 16MM HIGH; CHAMFER SIZE 8MM ON INSIDE DIA X 16MM ON OUTSIDE DIA; ANGLE 45 DEGREE; FOR WELLAND AND TUXHORN 66PCT DRAIN OUTFLOW CONTROL VALVE SEAT SEAL; DN200/250; PN320; NOTE - SEAL TO BE MANUFACTURED TO NUCLEAR STANDARDS AND PROTECTIVE PACKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	100011	EA	75		
PACKING, PREFORMED: INSIDE DIAMETER: 110 MM; OUTSIDE DIAMETER: 130 MM; THICKNESS: 10 MM; TYPE: RING; REFERENCE NO: 6226; 6232.; SET GLAND COMPRISING OF: 7 BURGMANN RINGS PRE PRESSED AND SLANTED 45 DEGREES, 2 BURGMANN RINGS PRE PRESSED AND SLANTED 45 DEGREES, FOR WELLAND AND TUXHORN ELECTRICAL FEED PUMP CONTROL VALVE, SUPPLIED IN A SEALED PACKET; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	100167	EA	75		

PACKING, PREFORMED: INSIDE DIAMETER: 100 MM; OUTSIDE DIAMETER: 120 MM; THICKNESS: 92 MM; TYPE: RING; MATERIAL: ASB; REFERENCE NO: 6226; 6232; SET GLAND; SIZE 120 X 100 X 10MM; COMPRISING OF 7 BURGMANN RINGS PRE PRESSED AND SLANTED 45 DEGREES; 2 BURGMANN RINGS PRE PRESSED AND SLANTED 45 DEGREE; FOR WELLAND AND TUXHORN MAIN FEED WATER CONTROL VALVE; SUPPLIED IN A SEALED PACKET; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	100168	EA	75		
PACKING: MATERIAL: ASB/GRAPHITE; SHAPE: RING; SUPPL P/N: 6226; 6232; SET, COMPRISING OF 7 BURGMANN RINGS PRE PRESSED AND SLANTED 45 DEGREES, 2 BURGMANN RINGS PRE PRESSED AND SLANTED 45 DEGREES, SUPPLIED IN A SEALED PACKET; DIMENSIONS: ID 90 X OD 110 X THK 95 MM	100169	EA	75		
PACKING, PREFORMED: INSIDE DIAMETER: 25 MM; OUTSIDE DIAMETER: 54 MM; THICKNESS: 71 MM; TYPE: V RING; MATERIAL: TEFLON; MODEL NO: K2/61-14; SET TFE, ITEM 14, FOR SULPHUR INJECTION PUMP; DURCO METER; TYPE G11304010; SIZE PLGR 1-3/8 IN; 1 HP; FEED A; DELIVERY 25 GAL/HR; PRESSURE 510 PSI; OPP TEMP 180 DEG C; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	100730	EA	75		
PACKING, PREFORMED: INSIDE DIAMETER: 260 MM; OUTSIDE DIAMETER: 280 MM; THICKNESS: 20 MM; MATERIAL: GRAPHITE; SUPPL P/N: 5HKS1-400-250-01; SHAPE ROUND, COVER SEAL, FOR NON RETURN VALVE, VALVE NO 516 466/1/1, FOR EFP DISCHARGE NRV; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	100865	EA	75		
PACKING: WIDTH: 16 MM; MATERIAL: KAMBOND; SHAPE: SQ; SUPPL P/N: KTG58.16; FLOPAC STYLE 143; NOTE - ITEM MUST BE ORGINALY PACKED AND MARKED	101016	KG	75		
PACKING: WIDTH: 19 MM; MATERIAL: KAMBOND; SHAPE: SQ; THICKNESS: 19 MM; SUPPL P/N: KTG58.19; FLOPAC STYLE 143; NOTE - ITEM MUST BE ORGINAL PACKED AND MARKED	101017	KG	75		
PACKING, BULK: LENGTH: 30 M; MATERIAL: NON ASB GLASS BASED; TYPE: BRAIDED ROPE; SHAPE: RD; NON ASBESTOS, SOFT WHITE, SIZE 20MM DIA, ROLL +- 6.2KG	101237	KG	2000		

PACKING, PREFORMED: INSIDE DIAMETER: 57 MM; OUTSIDE DIAMETER: 65 MM; THICKNESS: 10 MM; TYPE: VALVE; MATERIAL: GRAPHITE; REFERENCE NO: C9362-014; SHAPE ROUND, PURE PRESSURE SEAL WITH 45 DEGREE INSIDE SHAMFER; TYPE KTDF/83; FOR HOPKINSON VALVE 20-M264420 WFBC1 BPEV FB F22B/W; NOTE - ITEM MUST BE PROTECTIVE PACKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	101496	EA	75		
PACKING: TYPE: MERKEL LEAK OFF GLAND; LENGTH: 40 MM; WIDTH: 80 MM; MATERIAL: PTFE; SHAPE: RING; THICKNESS: 40 MM; SPECIFICATION: ISO 9001; DIAMETER: 60 MM; OEM P/N: DN400PN400, OEM: KULKONI SA (PTY) LTD; FOR USE ON WELLAND AND TUXHORN LEAK OFF VALVE DN100PN400 AND DN400PN400; DIMENSIONS: ID 60 X OD 80 MM	101579	EA	75		
PACKING: TYPE: VALVE LOWER; MATERIAL: GRAPHITE; SHAPE: RD; THICKNESS: 16 MM; DIAMETER: ID 10 X OD 220 MM; MODEL NO: 644ED; REFERENCE NO: 119-023-061-845; FOR USE ON DIFFERENTIAL PRESSURE GOVERNORS ON 1 INCH AND 1.5 INCH FISHER CONTROL	101685	EA	75		
PACKING: TYPE: CONTROL; LENGTH: 24.5 MM; WIDTH: 1-1/2 IN; MATERIAL: PTFE; SHAPE: V; THICKNESS: 1 IN; SPECIFICATION: ISO 9001; DIAMETER: 22 MM; SUPPL P/N: 1R2900-0101 2; MODEL NO: 644ED; FOR USE ON FISHER VALVE	101693	EA	75		
PACKING, BULK: WIDTH: 6 MM; THICKNESS: 6 MM; MATERIAL: ASB GRAPHITE IMPREGNATED; SHAPE: SQ; SUPPL P/N: 1500; CHESTERTON STYLE	101783	KG	75		
PACKING, BULK: WIDTH: 9.5 MM; THICKNESS: 9.5 MM; MATERIAL: ASB YARN INCONEL LUBRICATED; TYPE: BRAIDED; SHAPE: SQ; SUPPL P/N: 1500; CHESTERTON STYLE	101784	KG	75		
PACKING: TYPE: VALVE; MATERIAL: GRAPHITE; THICKNESS: 16 MM; DIAMETER: ID 63.5 X OD 92.5 MM; KORUTE BLOCK	101872	EA	75		
PACKING, BULK: WIDTH: 13 MM; THICKNESS: 0.38 MM; LENGTH: 7.5 M; MATERIAL: GRAPHITE; SHAPE: RECTANGULAR; SUITABLE FOR ALL TEMPERATURES, HEAVY DUTY	101898	EA	75		
PACKING, BULK: WIDTH: 20 MM; THICKNESS: 0.38 MM; LENGTH: 15 M; MATERIAL: GRAPHITE; TYPE: TAPE; SUITABLE FOR ALL TEMPERATURES, HEAVY DUTY	101899	EA	75		
PACKING, BULK: WIDTH: 25 MM; THICKNESS: 0.4 MM; LENGTH: 15.2 M; MATERIAL: GRAPHITE; TYPE: TAPE; ALL TEMPERATURE; HEAVY DUTY	101900	EA	75		
PACKING, BULK: WIDTH: 4.8 MM; THICKNESS: 4.8 MM; SHAPE: SQ; MANUF P/N: 1500; NOTE - ITEM MUST BE ORIGINAL PACKED	101901	KG	75		
PACKING, BULK: WIDTH: 6 MM; THICKNESS: 6 MM; MATERIAL: ASB OIL IMPREGNATED; TYPE: CHESTERTON STYLE; SHAPE: SQ; SUPPL P/N: 1722	101902	KG	75		

PACKING, BULK: WIDTH: 19 MM; THICKNESS: 19 MM; MATERIAL: NON ASB OIL IMPREGNATED/PTFE; SHAPE: SQ; SUPPL P/N: 1722; CHESTERTON STYLE	101908	KG	75		
PACKING, BULK: WIDTH: 8 MM; THICKNESS: 8 MM; MATERIAL: ASB OIL IMPREGNATED/PTFE; SHAPE: SQ; SUPPL P/N: 1722	102066	KG	75		
PACKING, PREFORMED: INSIDE DIAMETER: 45 MM; OUTSIDE DIAMETER: 55 MM; THICKNESS: 12.5 MM; TYPE: V-RING; MATERIAL: RUBBER; REFERENCE NO: V50; SHAPE V RING; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	102128	EA	75		
PACKING: MATERIAL: RUBBER; SHAPE: RD; THICKNESS: 5 MM; DIAMETER: ID 77 X OD 82 MM; REFERENCE NO: 66555	104487	EA	75		
PACKING, BULK: MATERIAL: WOOL; APPLICATION: PILOT AIR FILTER; DRAWING NO: 1W100590 REV 1; REGULATOR; XLE NL 7 IN STROKE	104521	EA	75		
PACKING: TYPE: CHEVRON; MATERIAL: GRAPHITE; SHAPE: RD; THICKNESS: 33 MM; DIAMETER: ID 25.4 X OD 44.45 MM	104571	EA	75		
PACKING, PREFORMED: INSIDE DIAMETER: 43 MM; OUTSIDE DIAMETER: 55.5 MM; THICKNESS: 50 MM; TYPE: CHEVRON; MATERIAL: GRAPHITE; SHAPE ROUND, SETS; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104573	EA	75		
PACKING: TYPE: SEAL; MATERIAL: RUBBER; SHAPE: RING; THICKNESS: 27 MM; DIAMETER: ID 70 X OD 90 MM; UNEEPAC MAXI-SEAL; COMPRISING OF 5 RINGS AND 1 PACKING RING CODE NO 7, FOR SULZER SERVO MOTOR TYPE ASM 250 F	104575	EA	75		
PACKING: MATERIAL: RUBBER; SHAPE: RING; THICKNESS: 13.3 MM; DIAMETER: ID 18 X OD 32 MM; REFERENCE NO: 85-30-7; UNEEPAC; COMPRISING OF 5 RINGS, CODE 7, FOR SULZER SERVO MOTOR ASM 63	104576	EA	75		
PACKING, PREFORMED: INSIDE DIAMETER: 48 MM; OUTSIDE DIAMETER: 63 MM; THICKNESS: 7.4 MM; TYPE: RING; SUPPL P/N: 85/30-17; COMPRISING OF TWO RINGS CODE 17; FOR SERVO MOTOR ASM 63; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104577	EA	75		
PACKING: MATERIAL: RUBBER; SHAPE: RING; THICKNESS: 22 MM; DIAMETER: ID 28 X OD 44 MM; UNEEPAC, COMPRISING OF 4 RINGS AND 1 BASE RING CODE 7, FOR SULZER SERVO MOTOR TYPE ASM 100	104579	EA	75		

PACKING: TYPE: SEAL; MATERIAL: RUBBER; SHAPE: RING; THICKNESS: 17.5 MM; DIAMETER: ID 135 X OD 160 MM; SUPPL P/N: JM14566; UNEEPAC; FOR SERVO MOTOR; 1 SET COMPRISING OF 3 RINGS; FABRIC TYPE; JM JOHNS-MANVILLE ONLY	104580	EA	75		
PACKING, PREFORMED: INSIDE DIAMETER: 45 MM; OUTSIDE DIAMETER: 61 MM; THICKNESS: 22 MM; TYPE: RING; REFERENCE NO: CH 237.175; COMPRISING OF: 1 BASE RING, 4 PACKING RINGS, 1 HEADER; FOR SERVO MOTOR TYPE ASM 160, AS PER SPARTAN FLUID SEALING; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104581	EA	75		
PACKING, PREFORMED: INSIDE DIAMETER: 184 MM; OUTSIDE DIAMETER: 200 MM; THICKNESS: 15 MM; MATERIAL: GRAPHITE; DRAWING NO: SIEMENS Z 0.41533 REV 1; SHAPE ROUND, PURE PRESSURE SEAL 185MM INSIDE DIA X 45MM DEG INSIDE CHAMFER; USED WITH OLD TYPE 66PCT DRAIN REGULATING VALVE; NOTE - STRESS REQUIRED TO ACTIVATE SEAL IS 15N/MM SQ; TABILITY UNDER COMPRESSIVE DIN 53913 GREATER THAN 48N/MM SQ AND IN ACCORDANCE WITH MARINE SPECIFICATION 39622-43110; NOTE - ITEM MUST BE PROTECTIVE PACKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104604	EA	75		
PACKING, BULK: WIDTH: 20 MM; THICKNESS: 20 MM; LENGTH: 8.5 M; MATERIAL: ASB YARN GRAPHITE IMPREGNATED; TYPE: GLAND; SHAPE: SQ; TYPE 3517, ITEM MUST BE ORIGINAL PACKED	104661	EA	75		
PACKING: MATERIAL: PLASTIC; THICKNESS: 2.2 MM; DIAMETER: ID 3 X OD 7.2 MM; D0117LN FOX/CONT; SHAPE RING	104668	EA	75		
PACKING, PREFORMED: INSIDE DIAMETER: 148 MM; OUTSIDE DIAMETER: 170 MM; THICKNESS: 28 MM; TYPE: RING; MATERIAL: STL; SUPPL P/N: 541-01; MODEL NO: HPT POK 32-25; REFERENCE NO: 104-608-259-001; FOR SULZER PUMP; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104753	EA	75		
RING: TYPE: PACKING; INSIDE DIAMETER: 204 MM; OUTSIDE DIAMETER: 240 MM; WIDTH: 35 MM; MATERIAL: STL; SUPPL P/N: 502-02; MODEL NO: HPTPK32; REFERENCE NO: 104-608-261-001; FOR USE ON SULZER ELECTRIC FEED PUMP	104770	EA	75		

PACKING, PREFORMED: INSIDE DIAMETER: 245 MM; OUTSIDE DIAMETER: 280 MM; THICKNESS: 32 MM; DRAWING NO: KANTECH KTDF/25A REV 1; SHAPE ROUND, PURE SEAL; FOR ELECTRIC FEED PUMP DISCHARGE STOP VALVE; FV238; NOTE - STRESS REQUIRED TO ACTIVATE SEAL IS 15N/MM SQ; STABILITY UNDER COMPRESSIVE DIN53913 GREATER THAN 48N/MM SQ AND IN ACCORDANCE WITH MARINE SPECIFICATION 39622-43110; NOTE - SEAL MUST BE PROTECTIVE PACKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104797	EA	75		
PACKING, PREFORMED: INSIDE DIAMETER: 380 MM; OUTSIDE DIAMETER: 350 MM; THICKNESS: 20 MM; MATERIAL: GRAPHITE; REFERENCE NO: 05 1344 000; SHAPE ROUND, PURE PRESSURE SEAL; FOR CIRCULATING PUMP SUCTION STRAINER COVER; NOTE - ITEM MUST BE PROTECTIVE PACKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104802	EA	75		
PACKING, PREFORMED: INSIDE DIAMETER: 43 MM; OUTSIDE DIAMETER: 55 MM; THICKNESS: 24 MM; TYPE: VALVE; MATERIAL: TEFLON; SUPPL P/N: 1R5161-01012; REFERENCE NO: SC205427; SHAPE V RING, ITEM 24, ON CONDENSOR LEVEL CONTROLLER, SUPPLIER NOTE - THE ITEM MUST BE PROTECTIVE PACKED AND CLEARLY MARKED, ACT LEV VAL; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104808	EA	75		
PACKING, PREFORMED: INSIDE DIAMETER: 130 MM; OUTSIDE DIAMETER: 140 MM; THICKNESS: 12 MM; TYPE: TOP LEAK OFF; MATERIAL: GRAPHITE; COLOR: BLACK; DRAWING NO: 0.42090-EB REV 1; REFERENCE NO: 119-023-061-600; WITH 45 DEGREE INSIDE TAPER AND STAINLESS STEEL CAPS; TYPE P55K; THE ITEM MUST BE PROTECTIVE PACKED, SEALED AND CLEARLY MARKED WITH MATERIAL NUMBER 0104812; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104812	EA	75		

PACKING, PREFORMED: INSIDE DIAMETER: 112 MM; OUTSIDE DIAMETER: 132 MM; THICKNESS: 18 MM; MATERIAL: GRAPHITE; MODEL NO: KTD/F 27A; SHAPE ROUND, PURE PRESSURE SEAL; FOR 100MM BABCOCK PERSTA GLOBE VALVE; USED AS SFP LEAK OFF ISOLATING VALVE POS FV275; NOTE - STRESS REQUIRED TO ACTIVATE SEAL IS 15N/MM SQUARE; STABILITY UNDER COMPRESSIVE DIN53913 GREATER THAN 48N/MM SQUARE AND IN ACCORDANCE WITH MARINE SPECIFICATION 39622-43110; NOTE - ITEM MUST BE PROTECTIVE PACKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104813	EA	75		
PACKING, PREFORMED: INSIDE DIAMETER: 85 MM; OUTSIDE DIAMETER: 100 MM; THICKNESS: 20 MM; MATERIAL: GRAPHITE; DRAWING NO: NN 345 010 P/N 6 REV 1; REFERENCE NO: KTD/F 26A; SHAPE ROUND, PURE PRESSURE SEAL; FOR 80MM BABCOCK GLOBE VALVE; USED AS EFP LEAK OFF ISOLATING VALVE; NOTE - STRESS REQUIRED TO ACTIVATE SEAL IS 15N/MM SQUARE; STABILITY UNDER COMPRESSIVE DIN53913 GREATER THAN 48N/MM SQUARE AND IN ACCORDANCE WITH MARINE SPECIFICATION 39622-43110; NOTE - ITEM MUST BE PROTECTIVE PACKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104814	EA	75		
PACKING, PREFORMED: INSIDE DIAMETER: 180 MM; OUTSIDE DIAMETER: 210 MM; THICKNESS: 17.5 MM; TYPE: VALVE; MATERIAL: GRAPHITE; SHAPE ROUND, SEAL PELSTA 125MM BORE, TWO INTERLOCKING; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104815	EA	75		
PACKING, PREFORMED: INSIDE DIAMETER: 40 MM; OUTSIDE DIAMETER: 50 MM; THICKNESS: 10 MM; MATERIAL: GRAPHITE; SUPPL P/N: 05-1410-000; SHAPE ROUND, FOR SEMPELL VALVE ON TURBINE, SUPPLIER NOTE - THE ITEM MUST BE PROTECTIVE PACKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104866	EA	75		
PACKING, PREFORMED: INSIDE DIAMETER: 50 MM; OUTSIDE DIAMETER: 60 MM; THICKNESS: 10 MM; MATERIAL: GRAPHITE; SHAPE ROUND, SEAL WITH 6MM LONG 45 DEGREE SHAMFER ON INSIDE DIA; FOR SEMPELL VALVES FV 231/FV 235 SIDE COVERS; NOTE - ITEM MUST BE PROTECTIVE PACKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104867	EA	75		

PACKING, PREFORMED: INSIDE DIAMETER: 260 MM; OUTSIDE DIAMETER: 280 MM; THICKNESS: 31 MM; TYPE: METAL CAPPED; MATERIAL: GRAPHITE; REFERENCE NO: KTDF/54; 45 DEGREE INSIDE SHAMFER, FOR USE ON SEMPLE VALVE HKS1.7.250.01, FV 236, KANTECH; NOTE - ITEM MUST BE PROTECTIVE PACKED; SHAPE ROUND; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104868	EA	75		
PACKING, PREFORMED: INSIDE DIAMETER: 30 MM; OUTSIDE DIAMETER: 40 MM; THICKNESS: 10 MM; MATERIAL: GRAPHITE; SUPPL P/N: 05.1412.000; SHAPE ROUND, PURE SEAL, FOR VALVE PLANT POSITION FV231; NOTE - ITEM MUST BE PROTECTIVE PACKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104869	EA	75		
PACKING: TYPE: RING; MATERIAL: RUBBER; SHAPE: RD; THICKNESS: 7.5 MM; DIAMETER: ID 23.5 X OD 44.5 MM; SUPPL P/N: 17202 TRB; REFERENCE NO: 17202	104897	EA	75		
PACKING, BULK: LENGTH: 30 M; MATERIAL: GLASS FIBER WOVEN BASED; TYPE: BRAIDED ROPE; TYPE SOFT WHITE, ROLL 4.5KG; SIZE 16MM DIA	104926	KG	2000		
PACKING, BULK: LENGTH: 30 M; MATERIAL: NON ASB GLASS BASED BRAIDED; TYPE: ROPE; SHAPE: RD; SOFT WHITE, ROLL 12KG, SIZE 25MM DIA	104927	KG	4000		
PACKING, BULK: LENGTH: 30 M; MATERIAL: NON ASB GLASS BASED; TYPE: BRAIDED ROPE; IN ROLL 2.5KG; SIZE 13MM DIA	104929	KG	75		
PACKING MATERIAL: MATERIAL: GRAPHITE FIBER; IN 500 GRAM CONTAINERS; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104960	KG	75		
PACKING, BULK: WIDTH: 40 MM; THICKNESS: 3 MM; LENGTH: 30 M; MATERIAL: NON ASB GLASS BASED; TYPE: BRAIDED; TEMPERATURE RISITANCE UP TO 550 DEGREES CELSIUS; TAPE	104961	KG	1000		
PACKING, BULK: WIDTH: 75 MM; THICKNESS: 3 MM; LENGTH: 30 M; MATERIAL: NON ASB GLASS BASED; TYPE: TAPE; LADDER; NON ASBESTOS; TEMPERATURE RISISTANCE UP TO 550 DEGREES CELSIUS	104962	KG	400		
PACKING, BULK: WIDTH: 12 MM; THICKNESS: 0.38 MM; LENGTH: 15 M; MATERIAL: GRAPHITE; TYPE: TAPE; CAT NO: BESTOBEL SG6350; REFERENCE NO: SG6350; SELF ADHESIVE SHAPE	104963	EA	75		
PACKING, BULK: WIDTH: 25 MM; THICKNESS: 0.38 MM; LENGTH: 15 M; MATERIAL: GRAPHITE; REFERENCE NO: SG6360; TAPE, SELF ADHESIVE ROLL; 25 X 1500 X 0.38MM	104964	EA	75		

PACKING, BULK: WIDTH: 16 MM; THICKNESS: 16 MM; LENGTH: 20 KG; MATERIAL: RUBBER; SHAPE: SQ; SUPPL P/N: 888W; OBLONG SEAL FOR MILLS REJECT DOOR, TYPE CRANE, IN 5 KG	104965	KG	1000		
PACKING, PREFORMED: INSIDE DIAMETER: 300 MM; OUTSIDE DIAMETER: 320 MM; THICKNESS: 20 MM; TYPE: CUP RING; MATERIAL: GRAPHITE; REFERENCE NO: FV231; KTDF/14; 05-1341-00-0; COVER SEAL FOR SEMPLE VALVE HKS1-7-300-300-01; PLANT FV231; NOTE - ITEM MUST BE BUBBLE PACKED FOR PROTECTION; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	106387	EA	75		
PACKING, PREFORMED: TYPE: VALVE; MATERIAL: SS GR 420; DRAWING NO: HTGR-412450 POS 976 REV 1; HTGR-412450 REV 1; HTGR-412450 POS 7235/7236 REV 1; MODEL NO: RSK-G 630 40/400; SHAPE RING, FOR POWER ASSISTED CHECK IN HP EXHAUST; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	113836	EA	75		
PACKING, BULK: WIDTH: 6 MM; THICKNESS: 6 MM; MATERIAL: CARBON FIBER; APPLICATION: PUMP AND VALVE; MAX PRESSURE: 250 BAR; PH VALUE RANGE: 0-13; TYPE: GENERAL SERVICE; SHAPE: SQ; SUPPL P/N: 477-1; MUST BE ASBESTOS FREE	172804	KG	75		
PACKING, BULK: WIDTH: 7.9 MM; THICKNESS: 7.9 MM; MATERIAL: CARBON FIBER; APPLICATION: PUMP AND VALVE; MAX PRESSURE: 250 BAR; PH VALUE RANGE: 0-13; TYPE: GENERAL SERVICE; SHAPE: SQ; SUPPL P/N: 477-1; MUST BE ASBESTOS FREE	172805	KG	75		
PACKING, BULK: WIDTH: 9.5 MM; THICKNESS: 9.5 MM; LENGTH: 9.3 M; MATERIAL: CARBON FIBER; APPLICATION: PUMP AND VALVE; MAX PRESSURE: 250 BAR; PH VALUE RANGE: 0-13; TYPE: GENERAL SERVICE; SHAPE: SQ; SUPPL P/N: 477-1	172806	KG	75		
PACKING, BULK: WIDTH: 10 MM; THICKNESS: 10 MM; MATERIAL: CARBON FIBER; SHAPE: SQ; SUPPL P/N: 477-1; MUST BE ASBESTOS FREE, NOTE - ITEM MUST BE ORIGINAL PACKED	172807	KG	75		
PACKING, BULK: WIDTH: 12.7 MM; THICKNESS: 12.7 MM; MATERIAL: CARBON FIBER; APPLICATION: PUMP AND VALVE; MAX PRESSURE: 250 BAR; PH VALUE RANGE: 0-13; TYPE: GENERAL SERVICE; SHAPE: SQ; SUPPL P/N: 477-1; MUST BE ASBESTOS FREE; NOTE - ITEM MUST BE ORIGINAL PACKED	172808	KG	75		
PACKING, BULK: WIDTH: 14 MM; THICKNESS: 14 MM; MATERIAL: CARBON FIBER; SHAPE: SQ; SUPPL P/N: 477-1; MUST BE ASBESTOS FREE, NOTE - ITEM MUST BE ORIGINAL PACKED	172809	KG	75		

PACKING, BULK: WIDTH: 3.2 MM; THICKNESS: 3.2 MM; MATERIAL: GRAPHITE; TYPE: BRAIDED; SHAPE: SQ; SUPPL P/N: 3300G; SLADE FOIL, FOR PUMP AND VALVE PURPOSES, TEMPERATURE NON OXIDIZER, -240 DEGREE CELSIUS TO 3000 DEGREE CELSIUS, APPLICATION CHEMICALS, STEAM, HYDROCARBON, SUPPLIER NOTE - THE ITEM MUST BE ORIGINAL PACKED, 0.5 KG PER BOX	182803	KG	75		
PACKING, BULK: THICKNESS: 4.8 MM; MATERIAL: GRAPHITE; APPLICATION: PUMP/VALVE; TEMPERATURE RANGE: -240 TO 3000 DEG C; TYPE: MOLDED CHEMICAL/HYDROCARBON/STEAM; SHAPE: SQ; MANUF P/N: 3300G; TEMPERATURE NON-OXIDIZER ITEM MUST BE ORIGINAL PACKED-2.5 KG PER BOX	182804	KG	75		
PACKING, BULK: THICKNESS: 6 MM; MATERIAL: GRAPHITE; APPLICATION: PUMP/VALVE; TEMPERATURE RANGE: -240 TO 3000 DEG C; TYPE: MOLDED CHEMICAL/HYDROCARBON/STEAM; SHAPE: SQ; MANUF P/N: 3300G; TEMPERATURE NON-OXIDIZER ITEM MUST BE ORIGINAL PACKED- 5 KG PER BOX	182805	KG	75		
PACKING, BULK: THICKNESS: 8 MM; MATERIAL: GRAPHITE; APPLICATION: PUMP/VALVE; TEMPERATURE RANGE: -240 TO 3000 DEG C; TYPE: MOLDED CHEMICAL/HYDROCARBON/STEAM; SHAPE: SQ; MANUF P/N: 3300G; TEMPERATURE NON-OXIDIZER ITEM MUST BE ORIGINAL PACKED- 5 KG PER BOX	182806	KG	75		
PACKING, BULK: WIDTH: 9.5 MM; THICKNESS: 9.5 MM; MATERIAL: GRAPHITE MOLDED; SHAPE: SQ; SLADE 3300G, FOR PUMP AND VALVE PURPOSE, TEMPERATURE: NON OXIDIZER -240 TO 3000 DEG C, APPLICATION CHEMICALS, STEAM, HYDROCARBON, ITEM MUST BE ORIGINAL PACKED, 10 KG PER BOX	182807	KG	75		
PACKING, BULK: THICKNESS: 10 MM; MATERIAL: GRAPHITE; APPLICATION: PUMP/VALVE; TEMPERATURE RANGE: -240 TO 3000 DEG C; TYPE: MOLDED CHEMICAL/HYDROCARBON/STEAM; SHAPE: SQ; MANUF P/N: 3300G; TEMPERATURE NON-OXIDIZER ITEM MUST BE ORIGINAL PACKED-10 KG PER BOX	182808	KG	75		
PACKING, BULK: WIDTH: 12.7 MM; THICKNESS: 12.7 MM; MATERIAL: GRAPHITE MOLDED; SHAPE: SQ; SLADE 3300G, FOR PUMP AND VALVE PURPOSE, TEMPERATURE NON OXIDIZER -240 TO 3000 DEG C, APPLICATION: CHEMICALS, STEAM, HYDROCARBON, ITEM MUST BE ORIGINAL PACKED, 15 KG PER BOX	182809	KG	75		

PACKING, BULK: WIDTH: 14.3 MM; THICKNESS: 14.3 MM; MATERIAL: GRAPHITE; SHAPE: SQ; SUPPL P/N: 3300G; MOLDED, TEMPERATURE NON OXIDIZER -240 DEG C TO 3000 DEG C, APPLICATION CHEMICALS, STEAM, HYDROCARBON, FOR PUMPS AND VALVES PURPOSES, ITEM MUST BE ORIGINAL PACKED, 15 KG PER BOX	182810	KG	75		
PACKING, BULK: WIDTH: 16 MM; THICKNESS: 16 MM; MATERIAL: GRAPHITE; SHAPE: SQ; SUPPL P/N: 3300G; SLADE BRAND, MOLDED, TEMPERATURE NON OXIDIZER -240 DEG C TO 3000 DEG C, APPLICATION CHEMICALS, STEAM, HYDROCARBON, FOR PUMPS AND VALVES PURPOSES; ITEM MUST BE ORIGINAL PACKED, 15KG PER BOX	182811	KG	75		
PACKING, BULK: THICKNESS: 19 MM; MATERIAL: GRAPHITE; APPLICATION: PUMP/VALVE; TEMPERATURE RANGE: -240 TO 3000 DEG C; TYPE: MOLDED CHEMICAL/HYDROCARBON/STEAM; SHAPE: SQ; MANUF P/N: 3300G; TEMPERATURE NON-OXIDIZER ITEM MUST BE ORIGINAL PACKED-15 KG PER BOX	182812	KG	75		
PACKING: WIDTH: 12 MM; MATERIAL: GRAPHITE; SHAPE: SQ; THICKNESS: 12 MM; SLADE 3300CJK; ITEM MUST BE ORIGINAL PACKED AND MARKED	184220	KG	75		
PACKING: WIDTH: 15.8 MM; MATERIAL: GRAPHITE; SHAPE: SQ; THICKNESS: 15.8 MM; SLADE 3300CJK; ITEM MUST BE ORIGINAL PACKED AND MARKED	184221	KG	75		
PACKING, BULK: WIDTH: 5.6 MM; THICKNESS: 5.6 MM; LENGTH: 7.5 M; MATERIAL: PTFE; TYPE: TWISTED; SHAPE: RD; SUPPL P/N: TEADIT 2124; TO BE PACKED PER BOX	206291	M	75		
PACKING, BULK: WIDTH: 12.7 MM; THICKNESS: 12.7 MM; LENGTH: 8 M; MATERIAL: GRAPHITE; SHAPE: SQ; SUPPL P/N: G57; ONLY JOHN CRANE BRAND ACCEPTABLE, NOTE - THE ITEM MUST BE PROTECTIVE PACKED AND CLEARLY MARKED	210338	EA	75		
PACKING, BULK: WIDTH: 12.7 MM; THICKNESS: 12.7 MM; LENGTH: 8 M; MATERIAL: CARBON GRAPHITE; SHAPE: SQ; SUPPL P/N: 774; ONLY JOHN CRANE BRAND ACCEPTABLE, NOTE - THE ITEM MUST BE PROTECTIVE PACKED AND CLEARLY MARKED	210339	EA	75		
PACKING, PREFORMED: TYPE: RING; SUPPL P/N: NO18; DRAWING NO: BAAN 5267671 REV 1; NOTE THE ITEM MUST BE PROTECTIVE PACKED AND CLEARLY MARKED; TYPE: STEM VARITEMP V/V; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	210724	EA	75		
PACKING: SUPPL P/N: NO31; DRAWING NO: BAAN 5267671 REV 1; STEM VARITEMP V/V, NOTE - THE ITEM MUST BE PROTECTIVE PACKED AND CLEARLY MARKED	210739	EA	75		

PACKING, BULK: WIDTH: 6 MM; THICKNESS: 6 MM; LENGTH: 8 M; MATERIAL: GRAPHITE; TYPE: BRAIDED; SHAPE: SQ; SUPPL P/N: C1065; NOTE - ONLY JOHN CRANE BRAND ACCEPTABLE, THE ITEM MUST BE PROTECTIVE PACKED AND CLEARLY MARKED	210849	EA	75		
PACKING, BULK: WIDTH: 8 MM; THICKNESS: 8 MM; LENGTH: 8 M; MATERIAL: GRAPHITE; TYPE: BRAIDED; SHAPE: SQ; SUPPL P/N: C1065; NOTE - ONLY JOHN CRANE BRAND ACCEPTABLE, THE ITEM MUST BE PROTECTIVE PACKED AND CLEARLY MARKED	210850	EA	75		
PACKING, BULK: WIDTH: 10 MM; THICKNESS: 10 MM; LENGTH: 8 M; MATERIAL: GRAPHITE; TYPE: BRAIDED; SHAPE: SQ; SUPPL P/N: C1065; NOTE - ONLY JOHN CRANE BRAND ACCEPTABLE, THE ITEM MUST BE PROTECTIVE PACKED AND CLEARLY MARKED	210851	EA	75		
PACKING, BULK: WIDTH: 12 MM; THICKNESS: 12 MM; LENGTH: 8 M; MATERIAL: GRAPHITE; TYPE: BRAIDED; SHAPE: SQ; SUPPL P/N: C1065; NOTE - ONLY JOHN CRANE BRAND ACCEPTABLE, THE ITEM MUST BE PROTECTIVE PACKED AND CLEARLY MARKED	210852	EA	75		
PACKING, BULK: WIDTH: 24 MM; THICKNESS: 24 MM; LENGTH: 8 M; MATERIAL: GRAPHITE; TYPE: BRAIDED; SHAPE: SQ; SUPPL P/N: C1065; NOTE - ONLY JOHN CRANE BRAND ACCEPTABLE, THE ITEM MUST BE PROTECTIVE PACKED AND CLEARLY MARKED	210853	EA	75		
PACKING, BULK: WIDTH: 9.5 MM; THICKNESS: 9.5 MM; LENGTH: 13.3 M; MATERIAL: INCONEL; MAX PRESSURE: 315 BAR; PH VALUE RANGE: 0-14; TEMPERATURE RANGE: 680 DEG C; LUBRICATION MATERIAL: GRAPHITE; SHAPE: SQ; REFERENCE NO: STYLE9001C	500984	EA	75		
PACKING, BULK: WIDTH: 5 MM; THICKNESS: 5 MM; LENGTH: 32 M; MATERIAL: INCONEL WIRE REINFORCED; MAX PRESSURE: 315 BAR; PH VALUE RANGE: 0-14; TEMPERATURE RANGE: 680 DEG C; LUBRICATION MATERIAL: GRAPHITE; SHAPE: SQ; REFERENCE NO: STYLE9001C	500985	EA	75		
PACKING, BULK: WIDTH: 30 MM; THICKNESS: 30 MM; LENGTH: 120 MM; MATERIAL: GRAPHITE BRAIDED; MAX PRESSURE: 315 BAR; PH VALUE RANGE: 0-14; TEMPERATURE RANGE: 680 DEG C; TYPE: VALVE; SHAPE: TRIANGLE; MANUF P/N: 77HT	500995	EA	75		
PACKING, BULK: WIDTH: 19 MM2; THICKNESS: 19 MM2; LENGTH: 9.2 M; MATERIAL: AERO DRUM; APPLICATION: ASH; WATER; SLURRY; MAX PRESSURE: 56 BAR; PH VALUE RANGE: 3-12; TEMPERATURE RANGE: 260 DEG C; TYPE: CARRIER; LUBRICATION MATERIAL: GRAPHITE/PTFE; SHAPE: SQ; STYLE 99; 2.5 KG BOX	563904	EA	75		

PACKING, PREFORMED: INSIDE DIAMETER: 57 MM; OUTSIDE DIAMETER: 65 MM; THICKNESS: 9 MM; TYPE: PRESSURE SEAL; MATERIAL: GRAPHITE; WITHSTAND 45 DEG C; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	659537	EA	75		
PACKING, PREFORMED: INSIDE DIAMETER: 75 MM; OUTSIDE DIAMETER: 85 MM; THICKNESS: 10 MM; TYPE: PRESSURE SEAL; MATERIAL: GRAPHITE; WTHSTAND 45 DEG C; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	659538	EA	75		
PACKING, BULK: WIDTH: 11.1 MM; THICKNESS: 11.1 MM; LENGTH: 8 M; MATERIAL: CARBON YARN; APPLICATION: FOR HIGH PRESSURE GENERAL VALVE SERVICE; MAX PRESSURE: 250 BAR; PH VALUE RANGE: 0-13; SPECIFICATION: ISO9001/14001; TEMPERATURE RANGE: 566 DEG C; LUBRICATION MATERIAL: PTFE; SHAPE: SQUARE; SUPPL P/N: 004737; STYLE: 447-1; 15.85LB PER BOX	667570	EA	75		
SUBTOTAL					
<u>SEALS (212)</u>					
SEAL, OIL: INSIDE DIAMETER: 40 MM; OUTSIDE DIAMETER: 60 MM; WIDTH: 10 MM; MATERIAL: RUBBER SYNTHETIC; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; SUPPL P/N: BA40-60-10	1315	EA	75		
SEAL, OIL: WIDTH: 4 MM; MATERIAL: ALUMINIUM; DRAWING NO: BBT HTGD90302 REV 1; LH AND VH; FOR BEARING PEDESTAL; FOR DOUBLE INSULATED JOURNAL BEARING NUMBER 7, RETAINING	20045	EA	75		
SEAL, RING: INSIDE DIAMETER: 38 MM; OUTSIDE DIAMETER: 69 MM; THICKNESS: 15.5 MM; MATERIAL: STL; SUPPL P/N: 95092615; SET RENEWEL PACKING AND SPRING, FOR COMPRESSOR XLE, PART NUMBER 1A11T25 SUPERCEDED	104502	EA	75		
STRIP: TYPE: SEAL; HP ROTOR SEALING, BBT 500MW TURBO GEN, UNIT 1 TO 6, BOX NO 191, CONSIST OF: HP ROTOR SEALING, ROW 3 - 20, DIMENSION: 0,5MM THICK X 9,4MM HIGH X 730MM DIA, HP ROTOR BALANCE PISTON SEALING, DIMENSION: 0,5MM THICK X 6,8MM HIGH X 855MM DIA, HP ROTOR GLAND SEAL, FRONT PISTON, DIMENSION: 0,5MM THICK X 6,2MM HIGH X 395MM DIA	20593	EA	75		
STRIP: TYPE: SEAL; HP ROTOR SEALING; FOR BBT 500MW TURBO GEN; UNIT 1 TO 6	20594	EA	75		
STRIP: TYPE: SEAL; IP ROTOR; FOR BBT 500MW TURBO GEN, UNIT 1 TO 6, BOX NO 193	20595	EA	75		

STRIP: TYPE: SEAL; IP CYLINDER; BBT 500MW TURBO GEN; UNIT 1 TO 6; BOX 194; CONSIST OF: H/RING; ROW 3 - 4; DIMENSION: 0.5MM THICK X 10.5MM HIGH X 1210MM DIA; H/RING; ROW 4 - 5; DIMENSION: 0.5MM THICK X 10.5MM HIGH X 1227MM DIA; H/RING; ROW 5 - 6; DIMENSION: 0.5MM THICK X 10.5MM HIGH X 1260MM DIA; H/RING; ROW 6 - 7, DIMENSION: 0.5MM THICK X 10.5MM HIGH X 1277MM DIA; H/RING; ROW 11 - 12; DIMENSION: 0.5MM THICK X 11.2MM HIGH X 1510MM DIA	20596	EA	75		
STRIP: TYPE: SEAL; LP ROTOR; FOR BBT 500MW TURBO GEN; UNIT 1 TO 6	20597	EA	75		
STRIP: TYPE: SEAL; LP ROTOR; FOR 500MW BBT TURBO GEN; UNIT 1 TO 6	20598	EA	75		
SEAL, RING: TYPE: RELAY; MATERIAL: RUBBER; DRAWING NO: BBT R 402776 POS 306 REV 1; FOR PRESSURE GRADIENT, SCHEMATIC POS 1200	22813	EA	75		
SEAL, RING: INSIDE DIAMETER: 80 MM; OUTSIDE DIAMETER: 102 MM; MATERIAL: STL; DRAWING NO: BBT HTGR 204194 POS 272 REV 1; HTGR 204194 REV 1; FOR IP STOP VALVE; VALVE DIA 355MM	23860	EA	75		
SEAL, RING: DRAWING NO: L-A13058-0 REV 1; REFERENCE NO: 1W8774; FOR VOLUMETRIC COAL FEEDER; MODEL 44115; STOCK EQUIPMENT	26438	EA	75		
SEAL: DIMENSIONS: ID 170 X OD 206.5 X THK 7 MM; MATERIAL: TEFLON; APPLICATION: BALL VALVE; SUPPL P/N: KTM85B; 1V6289X0042; MODEL NO: 476U-8-UR; FOR FISHER BALL CONTROL CLC, 8 IN (200MM) , FISHER OR KANTECH	32298	EA	75		
SEAL, RING: TYPE: FLARE; INSIDE DIAMETER: 5.5 MM; OUTSIDE DIAMETER: 9.2 MM; THICKNESS: 2 MM; MATERIAL: CU	39683	EA	75		
SEAL, OIL: TYPE: SPLIT; INSIDE DIAMETER: 330 MM; OUTSIDE DIAMETER: 350 MM; WIDTH: 30 MM; MATERIAL: BRASS; FOR DE AND NDE BEARINGS ON FD AND ID FAN MOTOR; NOTE ITEM MUST BE PROTECTIVE PACKED	40582	EA	75		
SEAL, RING: INSIDE DIAMETER: 25 MM; OUTSIDE DIAMETER: 32 MM; THICKNESS: 1.5 MM; MATERIAL: RUBBER; APPLICATION: COMPRESSOR; SUPPL P/N: 1W50061; NON EXTRUSION, TYPE C, FOR XLE NL 7 STROKE	42527	EA	75		
SEAL, RING: TYPE: DRIVING; INSIDE DIAMETER: 405 MM; OUTSIDE DIAMETER: 465 MM; THICKNESS: 61 MM; MATERIAL: STL; DRAWING NO: X-9803 REV 1; 5713 REV 1; MODEL NO: D334; SP-214-P1; TWIN DISC CLUTCH, CATERPILLAR ENGINE	42572	EA	75		

SEAL, RING: INSIDE DIAMETER: 7.5 MM; OUTSIDE DIAMETER: 38 MM; THICKNESS: 4 MM; MATERIAL: FELT; APPLICATION: WIPER; SUPPL P/N: 1J8726-06332; MODEL NO: 644ED; REFERENCE NO: 7643425; TYPE: UPPER, FOR FISHER CONTROL VALVE TYPE, SIZE: 1-1/2 IN (38MM), FOR WATER CONTROL VALVE ON 100PCT BOILER FEED PUMP	42600	EA	75		
SEAL, MECHANICAL: SHAFT DIAMETER: 3/4 IN; BODY MATERIAL: STL; DRAWING NO: CF-D-1197-1C REV 1; REFERENCE NO: BF1C1CP; T21, FOR PA FAN MECHANICAL LUB OIL PUMP; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	44586	EA	75		
SEAL, OIL: INSIDE DIAMETER: 150 MM; OUTSIDE DIAMETER: 180 MM; WIDTH: 15 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; GARLOCK SPLIT, USE ON 12E MILL GEARBOXES, GARLOCK BRAND ONLY	44587	EA	75		
SEAL, RING: INSIDE DIAMETER: 140 MM; OUTSIDE DIAMETER: 164 MM; MATERIAL: CI; DRAWING NO: HTGR 204194 REV 1; BBT HTGR 204194 POS 242 REV 1; FOR IP STOP VALVE DIA 355MM	44643	EA	75		
SEAL, MECHANICAL: SHAFT DIAMETER: 80 MM; BODY MATERIAL: STAINLESS STEEL; SUPPL P/N: 502-GR1X1/BO; FOR USE WITH NEUTRALISATION PUMP; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	45304	EA	75		
SEAL, RING: INSIDE DIAMETER: 30 MM; OUTSIDE DIAMETER: 28 MM; MATERIAL: TEFLON; APPLICATION: PUMP; SUPPL P/N: 431; DRAWING NO: 1211.001-5 REV 1; MODEL NO: CZ 80-250	45767	EA	75		
SEAL: TYPE: BUSH; REFERENCE NO: 327-41; D N R O - OB STOCK -MMD; SUCTION; FOR SPARGO ASH PUMP; TYPE 300 X 300; FRAME 50	47791	EA	75		
SEAL: DIMENSIONS: ID 55 X OD 100 X THK 22 MM; MATERIAL: RUBBER; CORNER RING ON CAUSTIC SODA PUMP	47849	EA	75		
SEAL, MECHANICAL: SHAFT DIAMETER: 5/8 IN; BODY MATERIAL: STAINLESS STEEL; APPLICATION: FLYGT PUMP; TYPE 43 06 353/CH, NOTE: ITEM MUST BE ORIGINAL PACKED AND SEALED FOR PROTECTION; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	47850	EA	75		
SEAL, RING: TYPE: DOUBLE BALL; INSIDE DIAMETER: 33 MM; OUTSIDE DIAMETER: 50 MM; THICKNESS: 25 MM; MATERIAL: STAINLESS STEEL; SUPPL P/N: JPXJ81741; LANTERN	47902	EA	75		
SEAL, RING: INSIDE DIAMETER: 90 MM; OUTSIDE DIAMETER: 112 MM; MATERIAL: BRASS	47933	EA	75		
SEAL, RING: TYPE: V RING; INSIDE DIAMETER: 65 MM; OUTSIDE DIAMETER: 75 MM; THICKNESS: 10 MM; MATERIAL: RUBBER; REFERENCE NO: V70	47953	EA	75		

SEAL, OIL: TYPE: ENCASED; INSIDE DIAMETER: 35 MM; OUTSIDE DIAMETER: 52 MM; WIDTH: 7 MM; MATERIAL: NITRILE; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; SUPPL P/N: BAU3SL	48100	EA	75		
SEAL, RING: TYPE: RUBBING THROAT; FOR AIR HEATER	53841	EA	75		
SEAL, RING: TYPE: BOTTOM PLATE; INSIDE DIAMETER: 99 MM; OUTSIDE DIAMETER: 127 MM; MATERIAL: RUBBER	54215	EA	75		
SEAL, RING: INSIDE DIAMETER: 75 MM; OUTSIDE DIAMETER: 100 MM; THICKNESS: 20 MM; MATERIAL: RUBBER	54685	EA	75		
SEAL, RING: TYPE: MAIN COVER; INSIDE DIAMETER: 260 MM; OUTSIDE DIAMETER: 280 MM; THICKNESS: 20 MM; MATERIAL: GRAPHITE; APPLICATION: CHECK VALVE; HKS1.400.250, POSIITON FV236 ON ELECTRICAL FEED PUMP DISCHARGE NON RETURN, NUMBER 5/443416/2/1	73656	EA	75		
SEAL: TYPE: VALVE PRESSURE; DIMENSIONS: ID 280 X OD 300 X THK 21.5 MM; MATERIAL: GRAPHITE; DRAWING NO: KTDF-11 REV 1; 45 GRADE ANGLE, FOR 300MM 3-WAY SEMPELL, PLANT POSITION FV256A AND B, AS PER KANTECH DRAWING, NOTE: SEAL MUST BE PROTECTIVE PACKED	73773	EA	75		
SEAL, RING: TYPE: VALVE; INSIDE DIAMETER: 32.5 MM; OUTSIDE DIAMETER: 48 MM; THICKNESS: 5 MM; MATERIAL: RUBBER; REFERENCE NO: 25127-125; ACT VV	73808	EA	75		
SEAL, RING: TYPE: VALVE; INSIDE DIAMETER: 20 MM; OUTSIDE DIAMETER: 32 MM; THICKNESS: 3 MM; MATERIAL: RUBBER; REFERENCE NO: 25127-116	73810	EA	75		
BELLOWS: TYPE: SEALING; MATERIAL: RUBBER; REFERENCE NO: 85-30/4; FOR SULZER SERVO MOTOR ASM 63; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	73894	EA	75		
SEAL, RING: INSIDE DIAMETER: 64.5 MM; OUTSIDE DIAMETER: 80 MM; THICKNESS: 10 MM; MATERIAL: GRAPHITE; DRAWING NO: 0.36521A REV 1; 0.40025 REV 1; REFERENCE NO: 9143; BETWEEN SEAT AND HOUSING; FOR WELLAND AND TUXHORN CONTROL VALVE SIZE 25MM OD; NW 40; ND 160; POS 9143	74022	EA	75		
SEAL, RING: TYPE: COVER; INSIDE DIAMETER: 85 MM; OUTSIDE DIAMETER: 95 MM; THICKNESS: 12 MM; MATERIAL: GRAPHITE PURE; REFERENCE NO: 8; KTDF-47; FOR FEED WATER SWING CHECK VALVE 80MM, ITEM PACKED AND SEAL FOR PROTECTION	74126	EA	75		
SEAL: TYPE: VALVE COVER; DIMENSIONS: ID 85 X OD 95 X THK 8 MM; MATERIAL: GRAPHITE; MODEL NO: FV266; HKS1.250.80-01; REFERENCE NO: 05-1319-000; 80 MM, ITEM PACKED FOR PROTECTION	74127	EA	75		

SEAL: TYPE: COVER; DIMENSIONS: ID 40 X OD 50 X THK 5 MM; MATERIAL: CS; MODEL NO: VV FV269; FOR USE ON RE HEAT SPRAY WATER ISOLATING VALVE	74131	EA	75		
SEAL, RING: INSIDE DIAMETER: 155 MM; OUTSIDE DIAMETER: 172 MM; THICKNESS: 15 MM; MATERIAL: GRAPHITE; FOR 125MM NRV, PLANT POSITION FV 268	74134	EA	75		
SEAL: TYPE: VALVE COVER; DIMENSIONS: ID 34.5 X OD 50 X THK 5 MM; MATERIAL: STL; SUPPL P/N: 05.1324.000; FOR HKS 1.250.125.01 FV 268; USE WITH SEMPELL VALVES ON TURBINE PLANT; SUPPLIER NOTE THE ITEM MUST BE PROTECTIVE PACKED AND CLEARLY MARKED	74135	EA	75		
SEAL, RING: INSIDE DIAMETER: 130 MM; OUTSIDE DIAMETER: 140 MM; THICKNESS: 13 MM; MATERIAL: GRAPHITE PURE; APPLICATION: PRESSURE VALVE; SUPPL P/N: KTD-F 28; 45DEG INSIDE SHAMFER, KANTECH TYPE, USED ON SEMPELL VALVE GES 1 80NB P/N11, USED AS EFP A AND B REHEAT SPRAYWATER ISOLATING VALVE POS. FV267, NOTE: STRESS REQUIRED TO ACTIVATE, IS 15N/MM SQUARE, STABILITY UNDER COMPRESSIVE (DIN53913) GREATER THAN 48N/MM SQUARE AND IN ACCORDANCE WITH MARINE SPECIFICATION 39622-43110, NOTE: ITEM MUST BE PROTECTIVE PACKED	74141	EA	75		
SEAL: MATERIAL: RUBBER; 3050MM VALVE	74159	EA	75		
SEAL, RING: TYPE: VALVE BUTTERFLY; INSIDE DIAMETER: 145 MM; OUTSIDE DIAMETER: 185 MM; THICKNESS: 10 MM; MATERIAL: RUBBER	74161	EA	75		
SEAL: TYPE: VALVE SPINDLE; DIMENSIONS: ID 16 MM; MATERIAL: PTFE; 3 IN	74176	EA	75		
SEAL, RING: TYPE: SEAT; INSIDE DIAMETER: 60 MM; OUTSIDE DIAMETER: 95 MM; THICKNESS: 13.5 MM; MATERIAL: PTFE; APPLICATION: 3 IN VALVE	74398	EA	75		
SEAL, OIL: INSIDE DIAMETER: 145 MM; OUTSIDE DIAMETER: 175 MM; WIDTH: 12 MM; MATERIAL: RUBBER; SEALING MEMBER: DOUBLE LIP; SPRING LOADED: YES; NOTE: EACH ITEM MUST BE PROTECTIVE PACKED AND SEALED	91898	EA	75		
SEAL, OIL: INSIDE DIAMETER: 6 MM; OUTSIDE DIAMETER: 10 MM; WIDTH: 2 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; REFERENCE NO: G61002INA	91899	EA	75		
SEAL, OIL: INSIDE DIAMETER: 14 MM; OUTSIDE DIAMETER: 20 MM; WIDTH: 5 MM; MATERIAL: RUBBER SYNTHETIC; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; 3 SD14203	91900	EA	75		
SEAL, OIL: TYPE: SHAFT; INSIDE DIAMETER: 15 MM; OUTSIDE DIAMETER: 32 MM; WIDTH: 9.5 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; 900711C; FOR DRY DUST	94057	EA	75		

SEAL, OIL: INSIDE DIAMETER: 33.33 MM; OUTSIDE DIAMETER: 57.15 MM; WIDTH: 12.7 MM; MATERIAL: RUBBER SYNTHETIC; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; REFERENCE NO: 137-225-16RF	94270	EA	75		
SEAL, OIL: TYPE: SINGLE LIP; INSIDE DIAMETER: 34 MM; OUTSIDE DIAMETER: 52 MM; WIDTH: 8 MM; MATERIAL: RUBBER SYNTHETIC; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; REFERENCE NO: SMIM3452/8	94281	EA	75		
SEAL, OIL: INSIDE DIAMETER: 13 MM; OUTSIDE DIAMETER: 28.57 MM; WIDTH: 7 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; SIZE 14.288MM ID X 28.575MM OD X 6.35MM THICK	94287	EA	75		
SEAL, OIL: INSIDE DIAMETER: 22 MM; OUTSIDE DIAMETER: 38 MM; WIDTH: 10 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; REFERENCE NO: S2509; SIZE 0.87 X 1.50 X 0.37 IN (22.23X38.10X9.52MM)	94344	EA	75		
SEAL, OIL: TYPE: PLAIN; INSIDE DIAMETER: 82.6 MM; OUTSIDE DIAMETER: 108 MM; WIDTH: 12.7 MM; MATERIAL: RUBBER SYNTHETIC; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; SIZE 82.55MM, MOULDED-IN REINFORCEMENT	94386	EA	75		
SEAL, OIL: INSIDE DIAMETER: 60 MM; OUTSIDE DIAMETER: 85 MM; WIDTH: 10 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; NOTE: EACH ITEM MUST BE PROTECTIVE PACKED AND SEALED	94403	EA	75		
SEAL, OIL: INSIDE DIAMETER: 28.57 MM; OUTSIDE DIAMETER: 57.1 MM; WIDTH: 9.53 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES	94422	EA	75		
SEAL, OIL: INSIDE DIAMETER: 63.5 MM; OUTSIDE DIAMETER: 82.7 MM; WIDTH: 9.53 MM; MATERIAL: RUBBER SYNTHETIC; SEALING MEMBER: DOUBLE LIP; SPRING LOADED: YES; SUPPL P/N: MIS28; SHAPE ROUND	94432	EA	75		
SEAL, OIL: INSIDE DIAMETER: 76.2 MM; OUTSIDE DIAMETER: 101.6 MM; WIDTH: 12.7 MM; MATERIAL: RUBBER; SEALING MEMBER: DOUBLE LIP; SPRING LOADED: YES	94438	EA	75		
SEAL, OIL: INSIDE DIAMETER: 20 MM; OUTSIDE DIAMETER: 30 MM; WIDTH: 7 MM; MATERIAL: RUBBER SYNTHETIC; SEALING MEMBER: DOUBLE LIP; SPRING LOADED: YES; REFERENCE NO: SM203007; SM20307	94475	EA	75		
SEAL, OIL: INSIDE DIAMETER: 50 MM; OUTSIDE DIAMETER: 65 MM; WIDTH: 8 MM; MATERIAL: RUBBER SYNTHETIC; SEALING MEMBER: DOUBLE LIP; SPRING LOADED: YES; REFERENCE NO: SM506508; BA50658; MIM5065; SM50658; WITH SPRING MOULDED ELEMENT	94478	EA	75		
SEAL, OIL: TYPE: PLAIN; INSIDE DIAMETER: 49.21 MM; OUTSIDE DIAMETER: 69.85 MM; WIDTH: 9.52 MM; MATERIAL: RUBBER SYNTHETIC; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES	94525	EA	75		

SEAL, OIL: INSIDE DIAMETER: 17 MM; OUTSIDE DIAMETER: 30 MM; WIDTH: 7 MM; MATERIAL: RUBBER SYNTHETIC; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; CB 17307	94528	EA	75		
SEAL, OIL: INSIDE DIAMETER: 22 MM; OUTSIDE DIAMETER: 32 MM; WIDTH: 7 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; REFERENCE NO: SM22327	94563	EA	75		
SEAL, OIL: INSIDE DIAMETER: 50 MM; OUTSIDE DIAMETER: 72 MM; WIDTH: 10 MM; MATERIAL: RUBBER SYNTHETIC; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; REFERENCE NO: CB507210	94565	EA	75		
SEAL: TYPE: BLOCK; DIMENSIONS: ID 26.8 X OD 45.4 X THK 14 MM; MATERIAL: RUBBER; KORUTE	94576	EA	75		
SEAL, OIL: INSIDE DIAMETER: 1-3/4 IN; OUTSIDE DIAMETER: 2-3/4 IN; WIDTH: 1/2 IN; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; REFERENCE: ENCSO, ENCASED, SYNTHETIC SEALING ELEMENT	94579	EA	75		
SEAL, OIL: INSIDE DIAMETER: 150 MM; OUTSIDE DIAMETER: 180 MM; WIDTH: 15 MM; MATERIAL: RUBBER SYNTHETIC; SEALING MEMBER: DOUBLE LIP; SPRING LOADED: YES; REFERENCE NO: SM15018015; NOTE: EACH ITEM MUST BE PROTECTIVE PACKED AND SEALED	97370	EA	75		
SEAL, OIL: INSIDE DIAMETER: 16 MM; OUTSIDE DIAMETER: 35 MM; WIDTH: 7 MM; MATERIAL: NEOPRENE; SEALING MEMBER: DOUBLE LIP; SPRING LOADED: YES	97432	EA	75		
SEAL, MECHANICAL: SHAFT DIAMETER: 30 MM; BODY MATERIAL: STAINLESS STEEL; REFERENCE NO: 310-76323F0; MAXMECH ONLY; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	97537	EA	75		
SEAL: TYPE: DUST; DIMENSIONS: SQ 40 MM X LG 1.95 M; MATERIAL: SBR; SOFT SONDAR, ONLY THIS TYPE FOR ELECTRIC MOTORS	97608	M	75		
SEAL, MECHANICAL: TYPE: PUMP; SHAFT DIAMETER: 110 MM; BODY MATERIAL: STAINLESS STEEL; APPLICATION: BOOSTER; SUPPL P/N: H74G15S1-115; MODEL NO: HZB302-580; CARTRIDGE UNIT, SUPPLIER NOTE: THE ITEM MUST BE PROTECTIVE PACKED IN A WOODEN BOX AND CLEARLY MARKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	98079	EA	75		
SEAL, OIL: INSIDE DIAMETER: 110 MM; OUTSIDE DIAMETER: 130 MM; WIDTH: 12 MM; MATERIAL: RUBBER SYNTHETIC; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; REFERENCE NO: SM11013012	98538	EA	75		

SEAL, OIL: INSIDE DIAMETER: 63.5 MM; OUTSIDE DIAMETER: 82.7 MM; WIDTH: 9.53 MM; MATERIAL: RUBBER; SEALING MEMBER: DOUBLE LIP; SPRING LOADED: YES; SUPPL P/N: 1X136; MODEL NO: C30EMX4; REFERENCE NO: 24899; FOR INGERSOLL RAND COMPRESSOR CENTAC	99030	EA	75		
SEAL: TYPE: CONVEX; DIMENSIONS: ID 15 X OD 25 X THK 8.5 MM; MATERIAL: STAINLESS STEEL; SUPPL P/N: 35/03-622-650; FOR SEMPELL HIGH PRESSURE HEATER BYPASS VALVES AVS 4 AND 5	99601	EA	75		
SEAL: TYPE: PRESSURE; DIMENSIONS: ID 115 X OD 146 X THK 24 MM; MATERIAL: GRAPHITE; SUPPL P/N: KTDF131A; KTDF131B; REFERENCE NO: KTDF131A/KTDF131B; PACKING SHAPE ROUND, ONE SET COMPRISING OF MALE/FEMALE, SUPPLIER NOTE - THE ITEM MUST BE PROTECTIVE PACKED, SEALED AND CLEARLY MARKED	189954	EA	75		
SEAL, MECHANICAL: SHAFT DIAMETER: 50 MM; BODY MATERIAL: STAINLESS STEEL; APPLICATION: HEATER DRAIN PUMP; REFERENCE NO: 310B76328SQ7; SULZER HZ 81-3251; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	99687	EA	75		
SEAL, RING: TYPE: BODY REGULATING VALVE; INSIDE DIAMETER: 155 MM; OUTSIDE DIAMETER: 170 MM; THICKNESS: 15 MM; MATERIAL: GRAPHITE PREFORMED; DRAWING NO: SIEMENS 0.47498-E POS 10073 REV 1; KANTECH KTDF/1 REV 1; REFERENCE NO: Z0-47498EITEM13; FOR WELLAND AND TUXHORN 33PCT EMERGENCY DRAIN (MODIFIED VERSION), DN150/250, PN320, NOTE: TO BE MANUFACTURED TO NU-CLEAR STANDARDS AND BUBBLE PACKED FOR PROTECTION	100044	EA	75		
SEAL, MECHANICAL: TYPE: PUMP; SHAFT DIAMETER: 100 MM; BODY MATERIAL: STAINLESS STEEL; APPLICATION: 50PCT BOOSTER PUMP; SPECIFICATION: H7AG15/105-E1; SULZER EFP, HZB 253-640, NOTE: ITEM MUST BE PROTECTIVE PACKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	100098	EA	75		
SEAL: TYPE: BULLGEAR; DIMENSIONS: ID 69 X OD 98.5 X THK 14 MM; MATERIAL: AVALON 50; FIG NO: 11; MODEL NO: TZ1253; REFERENCE NO: 14-3-41; FOR DRY DUST PLANT COMPRESSOR, DEMAG MODEL	100209	EA	75		
SEAL, OIL: TYPE: COMPRESSOR; INSIDE DIAMETER: 47.5 MM; OUTSIDE DIAMETER: 200 MM; WIDTH: 37.5 MM; MATERIAL: KLINGERITE; FIG NO: 11; MODEL NO: TZ1253; REFERENCE NO: 14-3-25; 2ND STAGE, FOR DRY DUST PLANT	100212	EA	75		

SEAL, OIL: TYPE: COMPRESSOR; INSIDE DIAMETER: 54 MM; OUTSIDE DIAMETER: 205 MM; WIDTH: 37.5 MM; MATERIAL: STAINLESS STEEL; FIG NO: 11; MODEL NO: TZ1253; REFERENCE NO: 14-3-24; 1ST STAGE, FOR DRY DUST PLANT	100213	EA	75		
SEAL, RING: TYPE: AIR; INSIDE DIAMETER: 54.5 MM; OUTSIDE DIAMETER: 201 MM; THICKNESS: 24 MM; MATERIAL: ALUMINIUM; FIG NO: 11; MODEL NO: TZ1253; REFERENCE NO: 14.3.22; TYPE: 2ND STAGE, FOR DRY DUST PLANT COMPRESSOR	100214	EA	75		
SEAL, RING: TYPE: AIR; INSIDE DIAMETER: 61 MM; OUTSIDE DIAMETER: 203 MM; THICKNESS: 33 MM; MATERIAL: STAINLESS STEEL; APPLICATION: COMPRESSOR; DRAWING NO: 11 REV 1; MODEL NO: TZ1253; REFERENCE NO: 14-2-21; A3406534-0041; TYPE: 1ST STAGE, FOR DRY DUST PLANT	100215	EA	75		
SEAL, OIL: TYPE: MIST FILTER ELEMENT; INSIDE DIAMETER: 45 MM; OUTSIDE DIAMETER: 76 MM; WIDTH: 10 MM; FIG NO: 10; REFERENCE NO: 14.2.25.02; FOR DEMAG TURBO COMPRESSOR MODEL: TZ1253; NEW DRY DUST PLANT; REPLACED BY AAP1404987-0014	100220	EA	75		
SEAL, OIL: TYPE: OIL COOLER BYPASS; MATERIAL: RUBBER; FIG NO: 13; REFERENCE NO: 14.1.07; FOR DRY DUST TURBO COMPRESSOR MODEL TZ1253	100225	EA	75		
SEAL, MECHANICAL: SHAFT DIAMETER: 30 MM; BODY MATERIAL: STAINLESS STEEL; APPLICATION: PUMP; REFERENCE NO: 025-194-12; FOR DRAINAGE, TYPE TSURUMI KTZ-110H; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	100248	EA	75		
SEAL, OIL: INSIDE DIAMETER: 32 MM; OUTSIDE DIAMETER: 84 MM; WIDTH: 8 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; REINFORCED	100249	EA	75		
SEAL, RING: TYPE: STUFFING BOX; INSIDE DIAMETER: 460 MM; OUTSIDE DIAMETER: 416 MM; THICKNESS: 8 MM; MATERIAL: RUBBER; SUPPL P/N: PHD740022; FOR USE ON METSO GRAVEL PUMP HG 250, FRAME 600	100251	EA	75		
SEAL: TYPE: CASING; DIMENSIONS: OD 8.5 MM; MATERIAL: RUBBER; REFERENCE NO: 19210-711050; FOR COARSE ASH PUMP TYPE DENVER-ORION 300 X 250; ON KRIEL ASH HANDLING PLANT PHASE II	100252	EA	75		
SEAL, MECHANICAL: SHAFT DIAMETER: 50 MM; BODY MATERIAL: SS GR 316; APPLICATION: PUMP; SUPPL P/N: 50T4610ASX1S1; 50MM/AFI/42287; CARTRIDGE, NOTE: ITEM MUST BE ORIGINAL PACKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	100742	EA	75		

SEAL, MECHANICAL: SHAFT DIAMETER: 20 MM; BODY MATERIAL: STAINLESS STEEL; APPLICATION: PUMP; COMPLETE WITH F0/7 NI-RESIST SEAT; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	100809	EA	75		
SEAL, MECHANICAL: TYPE: COVER; SHAFT DIAMETER: 30 MM; BODY MATERIAL: STL; MODEL NO: HKS1-320-300-10; FOR SEMPELL NON RETURN VALVE, VALVE NO:- 532 740/5/1, FOR CIRCULATING PUMP DISCHARGE NRV; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	100864	EA	75		
SEAL: TYPE: MANIFOLD; DIMENSIONS: ID 18.5 X OD 24 X THK 3 MM; MATERIAL: TEFLON; FOR 3-WAY EQUALIZING, USED ON FUJI FLOW AND LEVEL TRANSMITTER	100904	EA	1500		
SEAL, MECHANICAL: SHAFT DIAMETER: 35 MM; BODY MATERIAL: STAINLESS STEEL; APPLICATION: PUMP; REFERENCE NO: T100BFS; SHAFT, ONLY TYPE H/0350/3999/A, FOR ALLWEILER FUEL OIL, NOTE: ITEM MUST BE ORIGINAL PACKED FOR IDENTIFICATION AND PROTECTION; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	100938	EA	75		
SEAL, MECHANICAL: SHAFT DIAMETER: 40 MM; BODY MATERIAL: STL; APPLICATION: PUMP; MODEL NO: CSAI-321211; CARTRIDGE MOUNTED, SEALTEC TYPE ONLY; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	101007	EA	75		
SEAL, MECHANICAL: TYPE: PUMP; SHAFT DIAMETER: 50 MM; BODY MATERIAL: STAINLESS STEEL; REFERENCE NO: MG912G50-50MM AQEGG; FOR COOLING WATER BOOSTER; MATING RING: TUNGSTEN CARBIDE; PRIMARY RING: TUNGSTEN; GLAND PLATE: SS316; SLEEVE: SS316; O-RINGS: NITRIDE; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	101008	EA	75		
SEAL, OIL: INSIDE DIAMETER: 42 MM; OUTSIDE DIAMETER: 56 MM; WIDTH: 7 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; DRAWING NO: BBT TGR 305725 POS 337 REV 1; MOULDED REINFORCEMENT, FOR ELECTRO HYDRAULIC CONVERTOR	101064	EA	75		
SEAL, OIL: INSIDE DIAMETER: 22 MM; OUTSIDE DIAMETER: 35 MM; WIDTH: 7 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; DRAWING NO: TGR 305725 REV 1; MOULDED REINFORCEMENT, FOR ELECTRO HYDRAULIC CONVERTOR	101065	EA	75		

STRIP: TYPE: SEAL; WIDTH: 500 MM; THICKNESS: 3 MM; MATERIAL: RUBBER; REFERENCE NO: 5285466; C.N. PILLAR; REMA TIP-TOP; FOR USE ON CONVEYOR BELTING REPAIRS	101129	M	75		
SEAL, MECHANICAL: SHAFT DIAMETER: 34 MM; BODY MATERIAL: STAINLESS STEEL; APPLICATION: PUMP; REFERENCE NO: 35; FOR AMMONIA MAKE-UP TYPE B0102, AT WATER PURIFICATION PLANT (LAB), NOTE: ITEM MUST BE PROTECTED PACKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	101150	EA	75		
SEAL, OIL: TYPE: PILLOW BLOCK; MATERIAL: RUBBER; SUPPL P/N: TSN 515G; U-LOCK, FOUR HALFS PER SEALED PACKED	101178	EA	75		
SEAL, OIL: TYPE: PILLOW BLOCK; MATERIAL: RUBBER; SUPPL P/N: TSN 520G; U-LOCK, FOUR HALFS PER SEALED PACKED	101179	EA	75		
SEAL, MECHANICAL: SHAFT DIAMETER: 30 MM; BODY MATERIAL: STAINLESS STEEL; APPLICATION: PUMP; ONLY TYPE AES P05 ACCEPTABLE, SUPPLIER NOTE: THE ITEM MUST BE ORIGINAL PROTECTIVE PACKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	101272	EA	75		
SEAL: TYPE: HIGH PRESSURE; DIMENSIONS: ID 60 X OD 80 X THK 10 MM; MATERIAL: GRAPHITE; REFERENCE NO: KTDF38; FOR BYPASS SPRAYWATER REGULATING AND STOP VALVE, SULZER TYPE A20, NOTE: ITEM MUST BE PROTECTIVE PACKED, SEPARATE	101302	EA	75		
SEAL: TYPE: PRECIPITATOR DOOR; DIMENSIONS: ID 576 X OD 600 X THK 16 MM; MATERIAL: KAMBOND 156; SUPPL P/N: KTG190; DRAWING NO: K200 REV 1; FOR BABCOCK BOILER 12C, TYPE KANTECK, NOTE: MATERIAL MUST BE PACKED IN BUBBLE PACK (WRAP SEPARATE)	101644	EA	75		
SEAL, OIL: MATERIAL: STAINLESS STEEL; SEALING MEMBER: SINGLE LIP; MODEL NO: GN60; REFERENCE NO: 119-023-061-861; FOR USE ON MECHANICAL/AUX LUB OIL PUMP ON MAAG GEARBOX; SHAFT DIAMETER: 55 MM	101704	EA	75		
SEAL: DIMENSIONS: WD 130 X LG 330 X THK 13 MM; MATERIAL: KAMBOND 156; APPLICATION: DOOR; REFERENCE NO: KTG193(K202); MILL REJECT AND BOILER PEEP HOLE, SIZE 295 LONG X 95 X 16 WIDE X 12 HIGH, NOTE: TO BE BUBBLE PACKED SEPARATE	101715	EA	75		
SEAL, OIL: INSIDE DIAMETER: 3-3/4 IN; OUTSIDE DIAMETER: 4-3/4 IN; WIDTH: 1/2 IN; MATERIAL: RUBBER SYNTHETIC; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; REFERENCE NO: MIS312	101890	EA	75		

SEAL, OIL: INSIDE DIAMETER: 78 MM; OUTSIDE DIAMETER: 100 MM; WIDTH: 10 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; NOTE: EACH ITEM MUST BE PROTECTIVE PACKED AND SEALED	101936	EA	75		
SEAL, OIL: INSIDE DIAMETER: 125 MM; OUTSIDE DIAMETER: 150 MM; WIDTH: 12 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; NOTE: EACH ITEM MUST BE PROTECTIVE PACKED AND SEALED	101937	EA	75		
SEAL, OIL: INSIDE DIAMETER: 52 MM; OUTSIDE DIAMETER: 68 MM; WIDTH: 8 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; REFERENCE NO: SM52688	101938	EA	75		
SEAL, OIL: INSIDE DIAMETER: 60 MM; OUTSIDE DIAMETER: 80 MM; WIDTH: 8 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; NOTE: EACH ITEM MUST BE PROTECTIVE PACKED AND SEALED	101939	EA	75		
SEAL, OIL: INSIDE DIAMETER: 70 MM; OUTSIDE DIAMETER: 85 MM; WIDTH: 8 MM; MATERIAL: RUBBER SYNTHETIC; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; NOTE: EACH ITEM MUST BE PROTECTIVE PACKED AND SEALED	101940	EA	75		
SEAL, OIL: INSIDE DIAMETER: 70 MM; OUTSIDE DIAMETER: 90 MM; WIDTH: 10 MM; MATERIAL: RUBBER SYNTHETIC; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; NOTE: EACH ITEM MUST BE PROTECTIVE PACKED AND SEALED	101941	EA	75		
SEAL, OIL: INSIDE DIAMETER: 30 MM; OUTSIDE DIAMETER: 42 MM; WIDTH: 8 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; REFERENCE NO: CC304208	101942	EA	75		
SEAL, OIL: INSIDE DIAMETER: 35 MM; OUTSIDE DIAMETER: 52 MM; WIDTH: 7 MM; MATERIAL: RUBBER SYNTHETIC; SPRING LOADED: YES; SUPPL P/N: SM35527; DPSM35527	101944	EA	75		
SEAL, OIL: INSIDE DIAMETER: 37 MM; OUTSIDE DIAMETER: 52 MM; WIDTH: 8 MM; MATERIAL: RUBBER SYNTHETIC; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES	101945	EA	75		
SEAL, OIL: INSIDE DIAMETER: 45 MM; OUTSIDE DIAMETER: 60 MM; WIDTH: 8 MM; MATERIAL: RUBBER; SEALING MEMBER: DOUBLE LIP; SPRING LOADED: YES; REFERENCE NO: DPSM45608	101947	EA	75		
SEAL, OIL: INSIDE DIAMETER: 20 MM; OUTSIDE DIAMETER: 32 MM; WIDTH: 7 MM; MATERIAL: RUBBER; SEALING MEMBER: DOUBLE LIP; SPRING LOADED: YES; REFERENCE NO: SM 203207	101948	EA	75		
SEAL, OIL: INSIDE DIAMETER: 20 MM; OUTSIDE DIAMETER: 35 MM; WIDTH: 7 MM; MATERIAL: RUBBER SYNTHETIC; SEALING MEMBER: DOUBLE LIP; SPRING LOADED: YES; REFERENCE NO: SM203507	101949	EA	75		
SEAL, OIL: INSIDE DIAMETER: 22 MM; OUTSIDE DIAMETER: 40 MM; WIDTH: 7 MM; MATERIAL: RUBBER SYNTHETIC; SEALING MEMBER: DOUBLE LIP; SPRING LOADED: YES	101950	EA	75		

SEAL, OIL: INSIDE DIAMETER: 45 MM; OUTSIDE DIAMETER: 60 MM; WIDTH: 10 MM; MATERIAL: RUBBER SYNTHETIC; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; REFERENCE NO: 45X60X10R4	101951	EA	75		
SEAL, OIL: INSIDE DIAMETER: 11 MM; OUTSIDE DIAMETER: 22 MM; WIDTH: 7 MM; MATERIAL: RUBBER SYNTHETIC; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; REFERENCE NO: SM11227	101954	EA	75		
SEAL, OIL: INSIDE DIAMETER: 4 IN; OUTSIDE DIAMETER: 5 IN; WIDTH: 1/2 IN; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; NOTE: EACH ITEM MUST BE PROTECTIVE PACKED AND SEALED	101955	EA	75		
SEAL, OIL: INSIDE DIAMETER: 52 MM; OUTSIDE DIAMETER: 72 MM; WIDTH: 8 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; REFERENCE NO: SM52728	101956	EA	75		
SEAL, OIL: INSIDE DIAMETER: 35 MM; OUTSIDE DIAMETER: 47 MM; WIDTH: 7 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; REFERENCE NO: SM 35477; CFW1-35-47-7	101959	EA	75		
SEAL, OIL: INSIDE DIAMETER: 85 MM; OUTSIDE DIAMETER: 110 MM; WIDTH: 12 MM; MATERIAL: RUBBER SYNTHETIC; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; NOTE: EACH ITEM MUST BE PROTECTIVE PACKED AND SEALED	101960	EA	75		
SEAL, OIL: INSIDE DIAMETER: 12 MM; OUTSIDE DIAMETER: 22 MM; WIDTH: 7 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES	102014	EA	75		
SEAL, OIL: INSIDE DIAMETER: 15 MM; OUTSIDE DIAMETER: 30 MM; WIDTH: 8 MM; SUPPL P/N: JU80757; USED ON W AND T METERING PUMP G300 V 7MB	102015	EA	75		
SEAL, OIL: INSIDE DIAMETER: 15 MM; OUTSIDE DIAMETER: 30 MM; WIDTH: 7 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; FOR WALLACE AND TIERNAN METERING PUMP G50 V 5MD, NOTE: EACH ITEM MUST BE PROTECTIVE PACKED AND SEALED	102016	EA	75		
SEAL, OIL: INSIDE DIAMETER: 26 MM; OUTSIDE DIAMETER: 51 MM; WIDTH: 9 MM; MATERIAL: RUBBER SYNTHETIC; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES	102018	EA	75		
SEAL, OIL: INSIDE DIAMETER: 27 MM; OUTSIDE DIAMETER: 40 MM; WIDTH: 7 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; REFERENCE NO: CFWA3; PLAIN	102019	EA	75		
SEAL, OIL: INSIDE DIAMETER: 32 MM; OUTSIDE DIAMETER: 47 MM; WIDTH: 7 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES	102020	EA	75		

SEAL, OIL: INSIDE DIAMETER: 35 MM; OUTSIDE DIAMETER: 52 MM; WIDTH: 11 MM; MATERIAL: RUBBER SYNTHETIC; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; REFERENCE NO: AD355211; MOULDED-IN REINFORCEMENT	102021	EA	75		
SEAL, OIL: TYPE: PLAIN; INSIDE DIAMETER: 45 MM; OUTSIDE DIAMETER: 66 MM; WIDTH: 6 MM; MATERIAL: RUBBER SYNTHETIC; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; REFERENCE NO: SMIM4566/10; MOULD-IN REINFORCEMENT	102023	EA	75		
SEAL, OIL: INSIDE DIAMETER: 55 MM; OUTSIDE DIAMETER: 70 MM; WIDTH: 8 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; NOTE: EACH ITEM MUST BE PROTECTIVE PACKED AND SEALED	102026	EA	75		
SEAL, OIL: INSIDE DIAMETER: 60 MM; OUTSIDE DIAMETER: 75 MM; WIDTH: 8 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; NOTE: EACH ITEM TO BE PROTECTIVE PACKED AND SEALED	102027	EA	75		
SEAL, OIL: INSIDE DIAMETER: 62 MM; OUTSIDE DIAMETER: 80 MM; WIDTH: 10 MM; MATERIAL: RUBBER SYNTHETIC; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; NOTE: EACH ITEM MUST BE PROTECTIVE PACKED AND SEALED	102028	EA	75		
SEAL, OIL: INSIDE DIAMETER: 80 MM; OUTSIDE DIAMETER: 100 MM; WIDTH: 13 MM; MATERIAL: RUBBER SYNTHETIC; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; REFERENCE NO: GOETZ8227SV	102030	EA	75		
SEAL, OIL: INSIDE DIAMETER: 15 MM; OUTSIDE DIAMETER: 30 MM; WIDTH: 10 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; REFERENCE NO: SMIM1530/10	102041	EA	75		
SEAL, OIL: INSIDE DIAMETER: 5/8 IN; OUTSIDE DIAMETER: 1-1/4 IN; WIDTH: 1/4 IN; MATERIAL: RUBBER SYNTHETIC; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; NOTE: EACH ITEM TO BE PROTECTIVE PACKED AND SEALED	102042	EA	75		
SEAL, OIL: INSIDE DIAMETER: 25 MM; OUTSIDE DIAMETER: 47 MM; WIDTH: 7 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; REFERENCE NO: SM25477	102043	EA	75		
SEAL, OIL: INSIDE DIAMETER: 53 MM; OUTSIDE DIAMETER: 73 MM; WIDTH: 11 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES	102047	EA	75		
SEAL, OIL: TYPE: STL INSERT; INSIDE DIAMETER: 51 MM; OUTSIDE DIAMETER: 78 MM; WIDTH: 7.9 MM; MATERIAL: STL/METAL CASE RUBBER; SPECIFICATION: 901 ERSB 032R 1SC2 (CRWH1 R); SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; SUPPL P/N: RG49; DRAWING NO: L-D8266-A REV 1; MODEL NO: 44115; SHAFT, FOR STOCK EQUIPMENT VOLUMETRIC COAL FEEDER; WORM GEAR OUTPUT	102048	EA	75		

SEAL, OIL: INSIDE DIAMETER: 55 MM; OUTSIDE DIAMETER: 75 MM; WIDTH: 8 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES	102049	EA	75		
SEAL, OIL: TYPE: INSERT; INSIDE DIAMETER: 100 MM; OUTSIDE DIAMETER: 124 MM; WIDTH: 16 MM; MATERIAL: METAL CASE/RUBBER INSERT; SPECIFICATION: 808 ZRQE 080P 1SC1 (CRW1 R); SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; (SIZE 4 IN X 4-7/8 IN X 1/2 IN), FOR STOCK EQUIPMENT VOLUMETRIC COAL FEEDER GEARBOX, NOTE: EACH ITEM MUST BE PROTECTIVE PACKED AND SEALED	102051	EA	75		
SEAL, OIL: INSIDE DIAMETER: 125 MM; OUTSIDE DIAMETER: 150 MM; WIDTH: 14 MM; MATERIAL: RUBBER SYNTHETIC; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; NOTE: EACH ITEM MUST BE PROTECTIVE PACKED AND SEALED	102052	EA	75		
SEAL, OIL: INSIDE DIAMETER: 30 MM; OUTSIDE DIAMETER: 51 MM; WIDTH: 9 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; MIS13	102227	EA	75		
SEAL, RING: TYPE: PIPE COUPLING; INSIDE DIAMETER: 232 MM; OUTSIDE DIAMETER: 252 MM; THICKNESS: 26.5 MM; MATERIAL: RUBBER	104463	EA	75		
SEAL, RING: TYPE: PIPE COUPLING; INSIDE DIAMETER: 324 MM; OUTSIDE DIAMETER: 344 MM; THICKNESS: 26.5 MM; MATERIAL: RUBBER	104464	EA	75		
SEAL, RING: TYPE: PIPE COUPLING; INSIDE DIAMETER: 458 MM; OUTSIDE DIAMETER: 478 MM; THICKNESS: 26.5 MM; MATERIAL: RUBBER; FOR ASH WATER RETURN LINE	104465	EA	75		
SEAL: DIMENSIONS: ID 930 MM; MATERIAL: RUBBER; APPLICATION: COUPLING; FOR 930MM OD PIPE	104466	EA	400		
SEAL, RING: TYPE: LABYRINTH AIR; INSIDE DIAMETER: 1398 MM; OUTSIDE DIAMETER: 1840 MM; THICKNESS: 25 MM; MATERIAL: AL AND BRASS; APPLICATION: 10.8E MILL; DRAWING NO: ESKOM 13.45/305 REV 2 REV 0; ESKOM 13.45/304 REV 4 REV 0; FOR BABCOCK 10.8E MILLS, CASTING IN FOUR SECTIONS, LABYRINTH SEAL TO BE SUPPLIED ASSEMBLED WITH SHIMS INSTALLED, ON DRAWING ITEMS 1 AND 5 CASTED WITH PHOSPHOR BRONZE TO SPECIFICATION BS EN 1400:1973, ITEM 2 CASTED WITH ALUMINIUM TO SPECIFICATION LM4 (EN 1976 AC-45200)	104474	EA	75		
SEAL, OIL: TYPE: SPLIT; INSIDE DIAMETER: 4 IN; OUTSIDE DIAMETER: 5 IN; WIDTH: 7/16 IN	104475	EA	75		
SEAL, RING: TYPE: STEAM PIPE; INSIDE DIAMETER: 290 MM; OUTSIDE DIAMETER: 310 MM; THICKNESS: 45 MM; MATERIAL: BRASS	104484	EA	75		

SEAL, RING: TYPE: GAGE; INSIDE DIAMETER: 11.5 MM; OUTSIDE DIAMETER: 19.5 MM; THICKNESS: 2.5 MM; MATERIAL: STL RUBBER LINED; REFERENCE NO: 1W100589; MANIFOLD CAP SCREW DYNA, FOR INGERSOLL RAND COMPRESSOR XLE	104523	EA	75		
SEAL, OIL: INSIDE DIAMETER: 7/8 IN; OUTSIDE DIAMETER: 1-1/2 IN; WIDTH: 3/8 IN; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES	104530	EA	75		
SEAL, OIL: INSIDE DIAMETER: 62 MM; OUTSIDE DIAMETER: 81 MM; WIDTH: 13 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; RG49 ITO M2B341	104532	EA	75		
SEAL: TYPE: PISTON; APPLICATION: PEABODY OIL BURNER; REFERENCE NO: G3N	104535	EA	400		
SEAL, RING: INSIDE DIAMETER: 30 MM; OUTSIDE DIAMETER: 94 MM; THICKNESS: 10 MM; MATERIAL: PTFE PURE; APPLICATION: PRECIPITATOR	104542	EA	75		
STRIP: TYPE: SEAL; WIDTH: 18 MM; LENGTH: 305 MM; THICKNESS: 45 MM; MATERIAL: PTFE; DISCS TEFLON	104543	EA	75		
SEAL: SUPPL P/N: P34530B; 663B	104561	EA	75		
SEAL, OIL: INSIDE DIAMETER: 45 MM; OUTSIDE DIAMETER: 62 MM; WIDTH: 10 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES	104564	EA	75		
SEAL, OIL: INSIDE DIAMETER: 48 MM; OUTSIDE DIAMETER: 65 MM; WIDTH: 10 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; MOULDED IN REINFORCEMENT	104565	EA	75		
SEAL, OIL: INSIDE DIAMETER: 60 MM; OUTSIDE DIAMETER: 75 MM; WIDTH: 8 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; NOTE: EACH ITEM TO BE PROTECTIVE PACKED AND SEALED	104566	EA	75		
SEAL, OIL: INSIDE DIAMETER: 20 MM; OUTSIDE DIAMETER: 35 MM; WIDTH: 7 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; REFERENCE NO: CB20350768	104567	EA	75		
SEAL, OIL: INSIDE DIAMETER: 130 MM; OUTSIDE DIAMETER: 160 MM; WIDTH: 13 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES	104568	EA	75		
SEAL, RING: INSIDE DIAMETER: 20 MM; OUTSIDE DIAMETER: 34 MM; THICKNESS: 18 MM; MATERIAL: RUBBER; REFERENCE NO: 6021; UNEEPAC, COMPRISING OF TWO RINGS; FOR SULZER SERVO MOTOR ASM63-10/6021	104569	EA	75		
KIT: TYPE: SEAL; COMPRISING: GLAND RING; HEADER INTERMEDIATE RING; WASHER SS; PTFE CHEVRON SIZE 34.92MM OD X 19.05MM ID X 20MM HEIGHT; ONE STAINLESS STEEL WASHER 1MM THICK GRADE 304	104570	EA	75		

KIT: TYPE: SEAL; COMPRISING: GLAND RING; HEADER INTERMEDIATE RING; WASHER SS; CHEVRON SET, 25.40MM OD X 12.70MM ID X 23MM HEIGHT; EACH SET PTFE; STAINLESS STEEL GRADE 304 1MM THICK	104572	EA	75		
SEAL, RING: INSIDE DIAMETER: 225 MM; OUTSIDE DIAMETER: 250 MM; THICKNESS: 19 MM; MATERIAL: RUBBER; SUPPL P/N: 7-EA85-56-17; MODEL NO: ASM 250F; UNEEPAC, CODE NO 17, FOR FOR SULZER SERVO MOTOR TYPE ASM 250F	104574	EA	75		
SEAL, RING: INSIDE DIAMETER: 80 MM; OUTSIDE DIAMETER: 100 MM; THICKNESS: 16 MM; MATERIAL: RUBBER; UNEEPAC; CODE 17; FOR SULZER SERVO MOTOR TYPE ASM 100	104578	EA	75		
SEAL, MECHANICAL: SHAFT DIAMETER: 40 MM; BODY MATERIAL: STAINLESS STEEL; APPLICATION: PUMP; ONLY TYPE AES P01 ACCEPTABLE, SUPPLIER NOTE: THE ITEM MUST BE ORIGINAL PROTECTIVE PACKED, SEALED AND CLEARLY MARKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104608	EA	200		
SEAL, MECHANICAL: SHAFT DIAMETER: 5/8 IN; BODY MATERIAL: STAINLESS STEEL; APPLICATION: PUMP; REFERENCE NO: T2/BR371/W; CRANE; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104610	EA	75		
SEAL, MECHANICAL: SHAFT DIAMETER: 40 MM; BODY MATERIAL: STAINLESS STEEL; APPLICATION: PUMP; REFERENCE NO: MG9; JOHN CRANE TYPE T502/GR1C1/BO WITH COLLAR, TO DIN 24250, ITEM MUST BE ORIGINAL PACKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104641	EA	75		
SEAL, MECHANICAL: SHAFT DIAMETER: 50 MM; BODY MATERIAL: STAINLESS STEEL; APPLICATION: PUMP; ONLY TYPE AES P02 ACCEPTABLE, SUPPLIER NOTE: THE ITEM MUST BE ORIGINAL PROTECTIVE PACKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104643	EA	200		
SEAL, LABYRINTH: DIMENSIONS: ID 725 X OD 890 X THK 45.5 MM; MATERIAL: BRASS; ITEM 54	104734	EA	75		
SEAL, LABYRINTH: DIMENSIONS: ID 622 X OD 775 X THK 44.5 MM; MATERIAL: BRASS; ITEM 33	104735	EA	75		
SEAL, OIL: INSIDE DIAMETER: 32 MM; OUTSIDE DIAMETER: 48 MM; WIDTH: 11.2 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; 0.87X1.25X0.37 FKM	104795	EA	75		

SEAL, RING: TYPE: COVER; INSIDE DIAMETER: 260 MM; OUTSIDE DIAMETER: 281 MM; THICKNESS: 21 MM; MATERIAL: GRAPHITE; REFERENCE NO: 05-1341-00-0; FOR SEMPELL VALVE FV.242-AVS.5-07; NOTE ITEM MUST BE PROTECTIVE PACKED SEPARATE	104826	EA	75		
SEAL, RING: INSIDE DIAMETER: 117.6 MM; OUTSIDE DIAMETER: 171.6 MM; MATERIAL: STL; 2 BOILER PLANT	104832	EA	75		
SEAL, OIL: INSIDE DIAMETER: 100 MM; OUTSIDE DIAMETER: 120 MM; WIDTH: 13 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; DRAWING NO: F105/223 REV 1; 9152 REV 1; REFERENCE NO: A3; MAIN SHAFT, FOR HOPKINSON VALVE ACTUATOR	104864	EA	75		
SEAL, RING: INSIDE DIAMETER: 3.2 MM; MATERIAL: PTFE; APPLICATION: VALVE	104876	EA	75		
SEAL, RING: TYPE: TURBINE; INSIDE DIAMETER: 25 MM; OUTSIDE DIAMETER: 31 MM; THICKNESS: 3.5 MM; MATERIAL: RUBBER	104882	EA	75		
SEAL: TYPE: DUST CAP; MATERIAL: 21CRM0V57V; APPLICATION: POWER ASSISTED CHECK VALVE; DRAWING NO: R 405721/133 REV 0; EXTRACTION 5 SERVO MOTOR; POS 7207/7208	104889	EA	75		
SEAL, OIL: INSIDE DIAMETER: 124 MM; OUTSIDE DIAMETER: 150 MM; WIDTH: 11.5 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; DRAWING NO: BBT TGD90102 POS 8 REV 1; FOR TURNING GEAR 12SK	104895	EA	75		
SEAL, OIL: INSIDE DIAMETER: 125 MM; OUTSIDE DIAMETER: 150 MM; WIDTH: 12 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; TYPE GACO, NOTE: THE ITEM MUST BE PROTECTIVE PACKED AND CLEARLY MARKED	104896	EA	75		
SEAL, OIL: INSIDE DIAMETER: 58 MM; OUTSIDE DIAMETER: 83 MM; WIDTH: 13 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES	104910	EA	75		
SEAL, OIL: INSIDE DIAMETER: 18 MM; OUTSIDE DIAMETER: 24 MM; WIDTH: 3 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES	104914	EA	75		
SEAL, OIL: INSIDE DIAMETER: 14 MM; OUTSIDE DIAMETER: 24 MM; WIDTH: 7 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES	104915	EA	75		
SEAL, OIL: INSIDE DIAMETER: 30 MM; OUTSIDE DIAMETER: 40 MM; WIDTH: 7 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; REFERENCE NO: W15711827R4; MOULDED IN REINFORCEMENT	104917	EA	75		
SEAL, OIL: INSIDE DIAMETER: 10 MM; OUTSIDE DIAMETER: 24 MM; WIDTH: 7 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; NOTE: EACH ITEM MUST BE PROTECTIVE PACKED AND SEALED	104940	EA	75		

SEAL, OIL: INSIDE DIAMETER: 38 MM; OUTSIDE DIAMETER: 48 MM; WIDTH: 6 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES	104969	EA	75		
SEAL, OIL: INSIDE DIAMETER: 70 MM; OUTSIDE DIAMETER: 95 MM; WIDTH: 13 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; NOTE: EACH ITEM TO BE PROTECTIVE PACKED AND SEALED	104970	EA	75		
SEAL, OIL: INSIDE DIAMETER: 54 MM; OUTSIDE DIAMETER: 73 MM; WIDTH: 12 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; NOTE: EACH ITEM MUST BE PROTECTIVE PACKED AND SEALED	104973	EA	75		
SEAL, OIL: INSIDE DIAMETER: 11 MM; OUTSIDE DIAMETER: 30 MM; WIDTH: 7 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES	104975	EA	75		
SEAL, OIL: INSIDE DIAMETER: 25 MM; OUTSIDE DIAMETER: 40 MM; WIDTH: 9 MM; MATERIAL: RUBBER; SEALING MEMBER: DOUBLE LIP; SPRING LOADED: YES	104979	EA	75		
SEAL, OIL: INSIDE DIAMETER: 62 MM; OUTSIDE DIAMETER: 82 MM; WIDTH: 12 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; DRAWING NO: 1X136 REV 1; MODEL NO: C30EMX4; REFERENCE NO: MIS27; MAIN PUMP SHAFT	104980	EA	75		
SEAL, OIL: INSIDE DIAMETER: 130 MM; OUTSIDE DIAMETER: 160 MM; WIDTH: 12 MM; MATERIAL: RUBBER SYNTHETIC; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES	105652	EA	75		
SEAL, OIL: INSIDE DIAMETER: 15 MM; OUTSIDE DIAMETER: 30 MM; WIDTH: 7 MM; MATERIAL: RUBBER SYNTHETIC; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; REFERENCE NO: JU80757; USED WITH WALLACE AND TIERNAN METERING PUMP	105708	EA	75		
SEAL, OIL: INSIDE DIAMETER: 68.5 MM; OUTSIDE DIAMETER: 89 MM; WIDTH: 9.5 MM; MATERIAL: RUBBER SYNTHETIC; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; SUPPL P/N: RG101; DRAWING NO: L-A13060-A REV 1; D-8261-A REV 1; GREASE (CAM SIDE OF SHAFT) CR 27268, FOR VOLUMETRIC COAL FEEDER MODEL 44115, DESIGN 1969	106318	EA	75		
SEAL, OIL: INSIDE DIAMETER: 65 MM; OUTSIDE DIAMETER: 90 MM; WIDTH: 10 MM; MATERIAL: RUBBER; SEALING MEMBER: SINGLE LIP; SPRING LOADED: YES; NOTE: EACH ITEM MUST BE PROTECTIVE PACKED AND SEALED	108462	EA	75		
SEAL: DIMENSIONS: DIA 10 X THK 4 MM; MATERIAL: LEAD; APPLICATION: WIRE	108837	KG	75		
SEAL, RING: INSIDE DIAMETER: 50 MM; OUTSIDE DIAMETER: 72 MM; MATERIAL: STL; SUPPL P/N: 2800; RUBBER; FOR MONO PUMP D60	113824	EA	75		

SEAL, RING: TYPE: PRESSURE; INSIDE DIAMETER: 312 MM; OUTSIDE DIAMETER: 356 MM; THICKNESS: 21 MM; MATERIAL: GRAPHITE; SUPPL P/N: RL805001; FIG NO: 2495W; ONLY BURGMANN BRAND ACCEPTABLE, KRIEL POWER STATION, NOTE: THE ITEM MUST BE PROTECTIVE PACKED AND CLEARLY MARKED	207955	EA	75		
SEAL: TYPE: IP GLAND; DIMENSIONS: ID 620 X OD 660 X THK 8 MM; MATERIAL: STL; DRAWING NO: HTGD 90144 REV 1; CYLINDRICAL THRUST, INSERT RING, USED ON TURBINE	235940	EA	75		
SEAL, RING: TYPE: IP PIPING; INSIDE DIAMETER: 430 MM; OUTSIDE DIAMETER: 472 MM; THICKNESS: 18 MM; MATERIAL: STL; DRAWING NO: HTGD 90158-1 REV 1; 01TGD 04071587 REV 1; PISTON EXTRACTION 5, LOCATION GUARD, USED ON TURBINE	236039	EA	75		
SEAL, BEARING ISOLATOR: TYPE: BEARING; INSIDE DIAMETER: 168 MM; OUTSIDE DIAMETER: 270 MM; WIDTH: 61 MM; MATERIAL: STL; DRAWING NO: 0-45/54963 REV 0; ASH CONDITIONER; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	572308	EA	75		
SUBTOTAL					
<u>RINGS (206)</u>					
O RING: INSIDE DIAMETER: 52 MM; WIDTH: 5.5 MM; MATERIAL: RUBBER; APPLICATION: TEST VALVE; DRAWING NO: R407997 POS 724 REV 1; R407997 REV 1; SCHEMATIC POSITION 4203; OD 63MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	48168	EA	75		
O RING: INSIDE DIAMETER: 100 MM; WIDTH: 150 MM; MATERIAL: RUBBER; REFERENCE NO: A1/A/K; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	54703	EA	75		
O RING: INSIDE DIAMETER: 211 MM; WIDTH: 7 MM; MATERIAL: NEOPRENE; APPLICATION: VACUUM BREAKER; DRAWING NO: BBT R401 200 POS 589 REV 1; SIZE: 225MM OUTSIDE DIAL; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	73562	EA	75		

O RING: INSIDE DIAMETER: 240.67 MM; WIDTH: 6.99 MM; MATERIAL: NEOPRENE; INDUSTRY STANDARD: 2-448; DRAWING NO: BBT R 401200 POS 590 REV 1; REFERENCE NO: 590R401200; R401200; OD 248 X WD 7MM; FOR VACUUM BREAKER TYPE 180MM DIA; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	73565	EA	75		
O RING: INSIDE DIAMETER: 65 MM; DRAWING NO: AE070/BS REV 1; DN80; FOR KRIEL POWER STATION TAPROGGE SYSTEM; IN BBC MANUAL F; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	90580	EA	75		
O RING, CORD: MATERIAL: NEOPRENE; THICKNESS: 2.4 MM; SHORE HARDNESS: 75 DEG; SUPPL P/N: 2-4MMDIA; ROLL, SHELF LIFE, DATE OF MANUFACTURE AND METHOD OF STORAGE REQUIRED WITH DELIVERY; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	94229	EA	75		
O RING, CORD: MATERIAL: RUBBER NATURAL; THICKNESS: 6.4 MM; SHORE HARDNESS: 75 DEG; BLACK, SHELF LIFE, DATE OF MANUFACTURE AND METHOD OF STORAGE REQUIRED WITH DELIVERY; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	94232	EA	75		
O RING, CORD: MATERIAL: NEOPRENE; THICKNESS: 9.5 MM; SHORE HARDNESS: 75 DEG; BLACK, SHELF LIFE, DATE OF MANUFACTURE AND METHOD OF STORAGE REQUIRED WITH DELIVERY; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	94308	EA	250		
O RING, CORD: MATERIAL: NEOPRENE; THICKNESS: 12.7 MM; SHORE HARDNESS: 75 DEG; BLACK; SHELF LIFE, DATE OF MANUFACTURE AND METHOD OF STORAGE REQUIRED WITH DELIVERY; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	94310	EA	75		
O RING: INSIDE DIAMETER: 18.72 MM; WIDTH: 2.62 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-116; REFERENCE NO: P4070333PV; ITEMS 28+37 V/PMP; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	97230	EA	75		

O RING: INSIDE DIAMETER: 13.94 MM; WIDTH: 2.62 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-113; REFERENCE NO: P4070259PV; ITEMS 20+21 V/PMP; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	97231	EA	75		
O RING: INSIDE DIAMETER: 6.02 MM; WIDTH: 2.62 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-108; ITEMS 32 AND 35 V/PMP; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	97232	EA	75		
O RING: INSIDE DIAMETER: 10.69 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-205; REFERENCE NO: P4070166PV; RUB ITEMS 43 AND 45 V/PMP; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	97233	EA	75		
O RING: INSIDE DIAMETER: 40.64 MM; WIDTH: 5.33 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-326; REFERENCE NO: P4070645; ITEMS 55 AND 204 V/PMP; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	97234	EA	75		
O RING: INSIDE DIAMETER: 50.39 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-226; REFERENCE NO: 030A; 2311-2314; NUMBER P4070779PV; ITEM 178; FOR ROTARY VANE VACUUM PUMP; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	97235	EA	75		
O RING: INSIDE DIAMETER: 78.74 MM; WIDTH: 5.33 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-338; REFERENCE NO: P4071079PV; 030A; 78 X 5; ITEM 99; FOR ROTARY VANE VACUUM PUMP; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	97236	EA	75		
O RING: INSIDE DIAMETER: 91.67 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-239; DRAWING NO: HOPKINSON F129B/221 REV 1; FIG NO: HOPKINSON 9151; REFERENCE NO: 25126-070; 49; BRISCH; FOR ACTUATOR; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	97240	EA	75		
O RING: INSIDE DIAMETER: 107.54 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-244; APPLICATION: BEARING; DRAWING NO: 20A11EM233 REV 1; MODEL NO: C30EMX4; REFERENCE NO: CC0780; CC0761; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF	97642	EA	75		

APPLICABLE).					
O RING: MATERIAL: RUBBER; DRAWING NO: 20A11EM032 REV 1; MODEL NO: C30EMX4; REFERENCE NO: CC0761; CC0780; CARBON CARTRIDGE; CENTAC; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	97643	EA	75		
O RING: INSIDE DIAMETER: 50.52 MM; WIDTH: 1.78 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-033; DRAWING NO: 20A11EM033 REV 1; MODEL NO: C30EMX4; REFERENCE NO: CC0780; CC0761; CARBON CARTRIDGE; CENTAC; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	97644	EA	75		
O RING: WIDTH: 6.99 MM; MATERIAL: RUBBER; DRAWING NO: CC0780 REV 1; CC0761 REV 1; REFERENCE NO: 20A11EM459; DIFFUSER COVER 1ST AND 2ND, FOR INGERSOLL RAND COMPRESSOR CENTAG C30EMX4; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	97645	EA	75		
O RING: INSIDE DIAMETER: 266.07 MM; WIDTH: 6.99 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-450; REFERENCE NO: 20A11EM450; C30EMX4; CC0761; CC0780; FOR DIFFUSER COVER 3RD AND 4TH CENTAG COMPRESSOR C30EMX4; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	97646	EA	75		
O RING: INSIDE DIAMETER: 304.17 MM; WIDTH: 6.99 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-453; DRAWING NO: CC0761 REV 1; CC0780 REV 1; REFERENCE NO: 20A11EM434; DIFFUSER TO COOLER; FOR INGERSOLL RAND COMPRESSOR CENTAG C30EMX4; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	97647	EA	75		
O RING: WIDTH: 6.99 MM; MATERIAL: RUBBER; DRAWING NO: CC0780/ CC0761 REV 1; REFERENCE NO: 20A11EMS1001; C30EMX4; FOR COMPRESSOR CENTAG; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	97648	EA	75		
O RING, CORD: MATERIAL: NEOPRENE; THICKNESS: 10 MM; BLACK; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	98464	EA	1400		

O RING: INSIDE DIAMETER: 104.37 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-243; CAT NO: 9350/12/1; REFERENCE NO: 95602-0091; FOR REAVELL H2 COMPRESSOR VMP12-5212 SECOND STAGE CYLINDER LINER; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	98513	EA	75		
O RING: INSIDE DIAMETER: 10 MM; WIDTH: 3 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-111; SUPPL P/N: 072737; MODEL NO: SVB600/250; SVC600/250; FOR USE ON BECKER AND SOHNE COMPRESSOR, POS NO 16 AND 17/822; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	99891	EA	75		
O RING SET: APPLICATION: PUMP; QUANTITY: 11; REFERENCE NO: 2-151-142445-1; COMPRISING:- 4 OFF PART NO. 412.1; 4 OFF PART NO. 412.2; 2 OFF PART NO. 412.3; 1 OFF PART NO. 412.4; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	99982	EA	75		
O RING, CORD: MATERIAL: RUBBER; THICKNESS: 3.53 MM; REFERENCE NO: SC 3291/0233/104; M1382C; FOR 300MM DOME VALVE; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	100103	EA	250		
O RING: INSIDE DIAMETER: 69.22 MM; WIDTH: 5.33 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-335; REFERENCE NO: M1298; SC 3291/0233/105; 3291/0233/105; FOR 300MM DOME VALVE; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	100104	EA	75		
O RING: INSIDE DIAMETER: 53.34 MM; WIDTH: 5.33 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-330; REFERENCE NO: M1162; FOR 200MM DOME VALVE; SC NO:- 3291/0233/114; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	100105	EA	75		
O RING: INSIDE DIAMETER: 40.64 MM; WIDTH: 5.33 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-326; REFERENCE NO: M2085; SC NO:- 3291/0233/124; FOR 150MM DOME VALVE ON NEW DRY DUST PLANT; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	100106	EA	75		

O RING: INSIDE DIAMETER: 28.17 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-216; REFERENCE NO: 3291/0233/134; SC 3291/0233/134; M1242; FOR 100 MM DOME VALVE; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	100107	EA	75		
O RING, CORD: THICKNESS: 3.53 MM; REFERENCE NO: M1382; SC 3291/0233/123; FOR 150MM DOME VALVE; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	100108	EA	75		
O RING, CORD: MATERIAL: RUBBER; THICKNESS: 3.53 MM; SUPPL P/N: M1382; REFERENCE NO: SC 3291/0233/133; FOR 100MM DOME VALVE; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	100109	EA	75		
O RING: INSIDE DIAMETER: 88.57 MM; WIDTH: 2.62 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-153; MODEL NO: TZ1253; REFERENCE NO: 14.3.36; FOR 1ST AND 2ND STAGE BEARING ON TURBO COMPRESSOR MODEL NUMBER: TZ1253; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	100208	EA	75		
O RING: INSIDE DIAMETER: 550 MM; WIDTH: 5 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-256; FIG NO: 11; MODEL NO: TZ1253; REFERENCE NO: 14-3-43; TYPE: BULLGEAR RETAINER, FOR DRY DUST PLANT COMPRESSOR; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	100210	EA	75		
O RING: WIDTH: 3.53 MM; MATERIAL: RUBBER; FIG NO: 11; REFERENCE NO: 14.3.09; 2ND STAGE INLET; FOR DRY DUST PLANT COMPRESSOR MODEL NO:- TZ1253; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	100217	EA	75		
O RING: WIDTH: 5.33 MM; MATERIAL: RUBBER; FIG NO: 11; REFERENCE NO: 14-3-07TZ1253FIG11; 14.3.07; 2ND STAGE INLET COVER; FOR DRY DUST PLANT COMPRESSOR MODEL NO TZ1253; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	100218	EA	75		

O RING: INSIDE DIAMETER: 103 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-274; MODEL NO: TZ1253; REFERENCE NO: 14-2-15-02; TYPE: OIL PUMP, FOR TURBO COMPRESSOR, FOR DRY DUST PLANT; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	100222	EA	75		
O RING: INSIDE DIAMETER: 148 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-278; FIG NO: 6; TZ 1253; REFERENCE NO: 14-2-15-04; TYPE: RETAINER, FOR TURBO COMPRESSOR, FOR DRY DUST PLANT; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	100223	EA	75		
O RING: WIDTH: 5.33 MM; MATERIAL: RUBBER; REFERENCE NO: TZ1253 FIG 11; 14.3.02; 14.03.02; 1ST STAGE INLET; FOR TURBO COMPRESSOR MODEL TZ 1253; FOR DRY DUST PLANT; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	100229	EA	75		
O RING: INSIDE DIAMETER: 104.37 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-243; SUPPL P/N: 19210-740050; SHAFT SLEEVE; FOR COARSE ASH PUMP TYPE DENVER-ORION 300 X 250; ON KRIEL ASH HANDLING PLANT PHASE II; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	100253	EA	75		
O RING: INSIDE DIAMETER: 196.22 MM; WIDTH: 6.99 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-444; SUPPL P/N: 95622182; REFERENCE NO: 95622182; FOR INGERSOLL RAND COMPRESSOR TYPE T-30 MODEL 15T4; OLD S P/N 37790177; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	101103	EA	75		
O RING: INSIDE DIAMETER: 190.09 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-264; MODEL NO: 15T4; REFERENCE NO: 95018420; FOR COMPRESSOR; TYPE:- T-30; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	101104	EA	75		
O RING: INSIDE DIAMETER: 26.57 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-215; MODEL NO: 15T4; REFERENCE NO: 95028486; FOR INGERSOLL RAND COMPRESSOR, TYPE:- T-30; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	101105	EA	75		

O RING: INSIDE DIAMETER: 97.79 MM; WIDTH: 5.33 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-344; DRAWING NO: BBT R 304508 POS 711 REV 1; FOR MULTIPLICATION RELAY, SCHEMATIC POSITION 1230; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	101165	EA	75		
O RING: INSIDE DIAMETER: 84.6 MM; WIDTH: 5.35 MM; MATERIAL: NITRILE; DRAWING NO: R 304508 POS 719 REV 1; REFERENCE NO: 1230; (70/SHORE); FOR MULTIPLICATION RELAY; SCHEMATIC POSITION; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	101169	EA	75		
O RING: INSIDE DIAMETER: 16.81 MM; WIDTH: 5.33 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-313; SUPPL P/N: P44121; FOR CHLORINATOR FLOWMETER; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	102983	EA	75		
O RING: INSIDE DIAMETER: 110 MM; WIDTH: 5.35 MM; MATERIAL: NITRILE; FOR HP STOP VALVE SERVO MOTOR AND BBC PULSATOR; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104493	EA	75		
O RING: INSIDE DIAMETER: 28.17 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-216; REFERENCE NO: 20A11CM217; VALVE BODY; FOR INGERSOLL RAND COMPRESSOR XLE; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104510	EA	75		
O RING: INSIDE DIAMETER: 21.82 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-212; APPLICATION: SHAFT OIL PUMP; SUPPL P/N: 20A11CM214; FOR INGERSOLL-RAND COMPRESSOR XLE; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104512	EA	75		
O RING: INSIDE DIAMETER: 215.27 MM; WIDTH: 6.99 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-446; DRAWING NO: 20A11CM333 REV 1; REFERENCE NO: X1514T327C; LP UNLOADER; XLE NL 7 IN STROKE INGERSOLL RAND; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104524	EA	75		

O RING: INSIDE DIAMETER: 43.82 MM; WIDTH: 5.35 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-327; APPLICATION: COMPRESSOR XLE; SUPPL P/N: X1514T327; 34129320; REFERENCE NO: AG413762P46; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104525	EA	75		
O RING: INSIDE DIAMETER: 21.82 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-212; REFERENCE NO: 0V-11-212E; INLE VAL; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104527	EA	75		
O RING: INSIDE DIAMETER: 37.47 MM; WIDTH: 5.33 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-325; REFERENCE NO: 0V 11-325E; 0V11-325E; INLE VAL; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104528	EA	75		
O RING: INSIDE DIAMETER: 88.49 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-238; REFERENCE NO: 5K1770; FOR OIL PUMP; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104531	EA	75		
O RING: INSIDE DIAMETER: 9/16 IN; WIDTH: 3/8 IN; MATERIAL: RUBBER; REFERENCE NO: G2A; IMPERIAL SIZE ONLY; FOR OIL BURNERS; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104533	EA	400		
O RING: INSIDE DIAMETER: 7/16 IN; WIDTH: 0.103 IN; MATERIAL: VITON; DRAWING NO: LD1840 REV 1; REFERENCE NO: G2B; 5/8 INCH OD; IMPERIAL SIZE ONLY; USED WITH OIL BURNER GUN; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104534	EA	1500		
O RING: INSIDE DIAMETER: 15.6 MM; WIDTH: 1.78 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-016; REFERENCE NO: 915001012ITCH832; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104536	EA	75		
O RING: INSIDE DIAMETER: 81.92 MM; WIDTH: 5.33 MM; MATERIAL: RUBBER; SUPPL P/N: AG413762P34 & P46; REFERENCE NO: AG413762P46; AG413762P34 (NEW); AG413762P46 (OLD); FOR MAIN CONTROL VALVE; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104537	EA	75		

O RING: INSIDE DIAMETER: 37.77 MM; WIDTH: 2.62 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-128; REFERENCE NO: AG432122P25; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104538	EA	75		
O RING: INSIDE DIAMETER: 46.99 MM; WIDTH: 5.33 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-328; REFERENCE NO: 20A11CM327; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104559	EA	75		
O RING: INSIDE DIAMETER: 9.25 MM; WIDTH: 1.78 MM; MATERIAL: VITON; INDUSTRY STANDARD: 2-012; SUPPL P/N: P26482; REFERENCE NO: P26482; FOR WALLACE AND TIERNAN A831 CHLORINATOR INJECTOR; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104560	EA	75		
O RING: INSIDE DIAMETER: 21.95 MM; WIDTH: 1.78 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-020; REFERENCE NO: 1940AM; 1940AM 7/8 X 1/16 I; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104611	EA	75		
O RING: INSIDE DIAMETER: 10.82 MM; WIDTH: 1.78 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-013; SUPPL P/N: 1940DD; REFERENCE NO: 1940D; 11.12MM X 1.5MM; USE WITH NORTHLANDS PORTABLE DISSOLVE OXYGEN MASTER; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104612	EA	75		
O RING: INSIDE DIAMETER: 25.12 MM; WIDTH: 1.78 MM; MATERIAL: NEOPRENE; INDUSTRY STANDARD: 2-022; 1-1/4 IN (31.75MM) ID X THK 1/16 IN (1.6MM); VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104613	EA	75		
O RING: INSIDE DIAMETER: 25.12 MM; WIDTH: 1.78 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-022; REFERENCE NO: 1940; 1 X 1/16FF; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104614	EA	75		
O RING: INSIDE DIAMETER: 17.17 MM; WIDTH: 1.78 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-017; REFERENCE NO: 1940CC; 7/16 X 1/16 1940 CC; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104615	EA	75		

O RING: INSIDE DIAMETER: 22.97 MM; WIDTH: 7 MM; MATERIAL: RUBBER; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104617	EA	75		
O RING: INSIDE DIAMETER: 94.92 MM; WIDTH: 2.62 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-154; REFERENCE NO: ASM100/20; RT3375; FOR ELECTRODE HYDRAULIC ACTUATOR TYPE ASM100; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104618	EA	75		
O RING: INSIDE DIAMETER: 50.39 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-226; REFERENCE NO: 160-6-49; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104619	EA	75		
O RING: INSIDE DIAMETER: 53.34 MM; WIDTH: 5.33 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-330; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104620	EA	75		
O RING: INSIDE DIAMETER: 145.42 MM; WIDTH: 6.99 MM; MATERIAL: NEOPRENE; INDUSTRY STANDARD: 2-435; ID 150MM X THK 7MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104621	EA	75		
O RING: INSIDE DIAMETER: 24 MM; WIDTH: 2.5 MM; MATERIAL: NITRILE 70; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104622	EA	75		
O RING: INSIDE DIAMETER: 194.5 MM; WIDTH: 3 MM; MATERIAL: NEOPRENE; FOR ASH HOPPER CYLINDER; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104623	EA	75		
O RING: WIDTH: 6 MM; MATERIAL: VITON; MOULDED T PIECE; ROUND RUBBER 6MM DIA, SIZE OF T PIECE-TOP SECTION 120MM LONG X BOTTOM SECTION 80MM LONG; TO PREVENT LEAKING OF HYDROGEN ON END SHIELDS OF BBT 500MW GENERATOR; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104624	EA	75		
O RING: INSIDE DIAMETER: 113 MM; WIDTH: 6 MM; MATERIAL: NEOPRENE; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104625	EA	75		

O RING: INSIDE DIAMETER: 32.92 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-219; REFERENCE NO: W400623; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104626	EA	75		
O RING: INSIDE DIAMETER: 43.82 MM; WIDTH: 5.33 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-327; MODEL NO: W402629; POSITION 2; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104627	EA	75		
O RING, CORD: MATERIAL: VITON; THICKNESS: 6 MM; REFERENCE NO: HMG010271-1; REQUIRED WITH DELIVERY DATE OF MANUFACTURE, SHELF LIFE AND STORAGE METHOD; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104628	EA	500		
O RING: INSIDE DIAMETER: 81.92 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; REFERENCE NO: 200-232; 4263; SIZE: 69.45MM ID X 3.53MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104633	EA	75		
O RING: INSIDE DIAMETER: 81.92 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-339; REFERENCE NO: 4264; 82-15X3-53; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104634	EA	75		
O RING: INSIDE DIAMETER: 15.5 MM; WIDTH: 1.78 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-016; REFERENCE NO: 1F4636-0699; FOR FISHER VALVE POSITIONER 3560; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104646	EA	75		
O RING: INSIDE DIAMETER: 94.84 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-239; REFERENCE NO: 200-240-4470; FOR ASH WATER RETURN PUMP; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104650	EA	75		
O RING: INSIDE DIAMETER: 40 MM; WIDTH: 4 MM; MATERIAL: RUBBER; SIZE 48MM OD; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104653	EA	75		
O RING: INSIDE DIAMETER: 695 MM; WIDTH: 7 MM; MATERIAL: RUBBER; EXT PUMP; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104654	EA	75		

O RING: INSIDE DIAMETER: 670 MM; WIDTH: 7 MM; MATERIAL: RUBBER; APPLICATION: EXT PUMP; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104655	EA	75		
O RING: INSIDE DIAMETER: 710 MM; WIDTH: 7 MM; MATERIAL: RUBBER; APPLICATION: EXT PUMP; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104656	EA	75		
O RING, CORD: MATERIAL: RUBBER; THICKNESS: 7 MM; FOR 354, 97IDX7DIA EXTRAC PUMP; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104658	EA	75		
O RING: INSIDE DIAMETER: 120.02 MM; WIDTH: 7 MM; MATERIAL: RUBBER; EXTRAC PUMP; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104659	EA	75		
O RING: INSIDE DIAMETER: 104.14 MM; WIDTH: 5.33 MM; MATERIAL: NEOPRENE; INDUSTRY STANDARD: 2-346; FOR EXTRACTION PUMP; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104660	EA	75		
O RING: INSIDE DIAMETER: 142.24 MM; WIDTH: 5.33 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-358; SUPPL P/N: P138; HTGR204625; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104665	EA	75		
O RING: INSIDE DIAMETER: 75.79 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-234; REFERENCE NO: 223406-14; PURIFIER; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104666	EA	75		
O RING: INSIDE DIAMETER: 23.39 MM; WIDTH: 3.53 MM; MATERIAL: VITON; INDUSTRY STANDARD: 2-213; SUPPL P/N: U21275; FOR CHLORINATOR; ITEMS MUST BE PACKED TOGETHER PER KIT; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104669	EA	75		
O RING: INSIDE DIAMETER: 6 MM; WIDTH: 1.78 MM; MATERIAL: NITRILE; INDUSTRY STANDARD: 2-010; (70/SHORE); VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104681	EA	75		

O RING: INSIDE DIAMETER: 15.5 MM; WIDTH: 1.85 MM; MATERIAL: RUBBER; OD 19.2MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104682	EA	75		
O RING: INSIDE DIAMETER: 34.52 MM; WIDTH: 3.53 MM; MATERIAL: NEOPRENE; INDUSTRY STANDARD: 2-220; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104689	EA	75		
O RING: INSIDE DIAMETER: 9.25 MM; WIDTH: 1.78 MM; MATERIAL: NEOPRENE; INDUSTRY STANDARD: 2-012; 70 DEGREES DURO HARDNESS; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104690	EA	75		
O RING: INSIDE DIAMETER: 151.77 MM; WIDTH: 6.99 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-437; 6-91C X 150MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104691	EA	75		
O RING: INSIDE DIAMETER: 126.37 MM; WIDTH: 6.99 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-429; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104692	EA	75		
O RING: INSIDE DIAMETER: 78.74 MM; WIDTH: 5.33 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-338; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104693	EA	75		
O RING: INSIDE DIAMETER: 88.27 MM; WIDTH: 5.33 MM; MATERIAL: VITON; INDUSTRY STANDARD: 2-341; SIZE 88.30MM X 5.30MM DIA; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104694	EA	75		
O RING: INSIDE DIAMETER: 28.7 MM; WIDTH: 3.53 MM; MATERIAL: NITRILE; INDUSTRY STANDARD: 2-216; (70/SHORE); VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104695	EA	75		
O RING: INSIDE DIAMETER: 43.82 MM; WIDTH: 5.33 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-327; 43.82MM OD; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104696	EA	75		

O RING: INSIDE DIAMETER: 69.22 MM; WIDTH: 5.33 MM; MATERIAL: NEOPRENE; INDUSTRY STANDARD: 2-335; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104697	EA	75		
O RING: INSIDE DIAMETER: 50.17 MM; WIDTH: 5.33 MM; MATERIAL: NEOPRENE; INDUSTRY STANDARD: 2-329; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104698	EA	75		
O RING: INSIDE DIAMETER: 17.04 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-209; 18.6MM ID X 3.4MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104699	EA	75		
O RING: INSIDE DIAMETER: 56.52 MM; WIDTH: 5.33 MM; MATERIAL: NEOPRENE; INDUSTRY STANDARD: 2-331; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104700	EA	75		
O RING: INSIDE DIAMETER: 9.25 MM; WIDTH: 1.78 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-012; ID 9MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104701	EA	75		
O RING: INSIDE DIAMETER: 15.6 MM; WIDTH: 1.78 MM; MATERIAL: RUBBER; 261MM X 14-95MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104702	EA	75		
O RING: INSIDE DIAMETER: 196.22 MM; WIDTH: 6.99 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-444; ID 195MM X THK 6.91MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104703	EA	75		
O RING: INSIDE DIAMETER: 81.92 MM; WIDTH: 5.33 MM; MATERIAL: RUBBER; ID 27.5MM X 5.35MM THICK; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104704	EA	75		
O RING: INSIDE DIAMETER: 189.87 MM; WIDTH: 6.99 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-443; 3.35MM X 21.25MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104705	EA	75		

O RING: INSIDE DIAMETER: 8.75 MM; WIDTH: 1.78 MM; MATERIAL: NBR; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104706	EA	75		
O RING: INSIDE DIAMETER: 85.09 MM; WIDTH: 5.35 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-340; FOR 50 PCT ELECTRIC FEED PUMP; SULZER TYPE HPT POK 32-25; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104707	EA	75		
O RING: INSIDE DIAMETER: 139.07 MM; WIDTH: 6.99 MM; MATERIAL: NITRILE; INDUSTRY STANDARD: 2-433; DRAWING NO: HTGR90058 POS 801A REV 1; REFERENCE NO: 3305-3306; 2311-2314; SIZE 140 X 7; USED WITH IP AND LP EMERGENCY STOP VALVE SERVO MOTOR; TYPE HAJ250; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104708	EA	75		
O RING: INSIDE DIAMETER: 240 MM; WIDTH: 6.91 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-448; 245MM ID; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104709	EA	75		
O RING: INSIDE DIAMETER: 189.87 MM; WIDTH: 6.99 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-443; 3.53 X 29 X 5; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104710	EA	75		
O RING: INSIDE DIAMETER: 10.77 MM; WIDTH: 2.62 MM; MATERIAL: NITRILE; INDUSTRY STANDARD: 2-111; 10.5 X 2.61MM THICK; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104711	EA	75		
O RING: INSIDE DIAMETER: 15.54 MM; WIDTH: 2.62 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-114; SIZE: 16MM X 2.61MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104712	EA	75		
O RING: INSIDE DIAMETER: 5.28 MM; WIDTH: 1.78 MM; MATERIAL: NITRILE; INDUSTRY STANDARD: 2-009; (70/SHORE) SIZE 5.70MM ID; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104713	EA	75		
O RING: INSIDE DIAMETER: 180 MM; WIDTH: 7 MM; MATERIAL: RUBBER; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104714	EA	75		

O RING: INSIDE DIAMETER: 21.82 MM; WIDTH: 3.53 MM; MATERIAL: NITRILE; INDUSTRY STANDARD: 2-212; SIZE 21.5MM ID X 3.53MM THICK; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104716	EA	75		
O RING: INSIDE DIAMETER: 88.49 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-238; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104717	EA	75		
O RING: INSIDE DIAMETER: 104.37 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-243; REFERENCE NO: 107-55; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104719	EA	75		
O RING: INSIDE DIAMETER: 113.89 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-246; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104720	EA	75		
O RING: INSIDE DIAMETER: 94.84 MM; WIDTH: 3.53 MM; MATERIAL: NEOPRENE; INDUSTRY STANDARD: 2-240; FOR PUMP HPT POK 32-25; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104721	EA	75		
O RING: INSIDE DIAMETER: 158.12 MM; WIDTH: 5.33 MM; MATERIAL: NEOPRENE; INDUSTRY STANDARD: 2-362; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104722	EA	75		
O RING: INSIDE DIAMETER: 266.7 MM; WIDTH: 5.33 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-378; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104723	EA	75		
O RING: INSIDE DIAMETER: 240.67 MM; WIDTH: 7 MM; MATERIAL: RUBBER; REFERENCE NO: 2-448 N674-70; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104724	EA	75		
O RING: INSIDE DIAMETER: 247.02 MM; WIDTH: 5.33 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-376; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104725	EA	75		

O RING: INSIDE DIAMETER: 96 MM; WIDTH: 7 MM; MATERIAL: RUBBER; 417-96X7 FEED PUMP; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104729	EA	75		
O RING: INSIDE DIAMETER: 622 MM; WIDTH: 8 MM; MATERIAL: RUBBER; REFERENCE NO: 412-1; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104730	EA	75		
O RING: INSIDE DIAMETER: 123.19 MM; WIDTH: 5.33 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-352; SUPPL P/N: 123-19X5-33MM59; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104731	EA	75		
O RING: INSIDE DIAMETER: 227.97 MM; WIDTH: 6.99 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-447; REFERENCE NO: 204-625-P74; 204-625P74; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104738	EA	75		
O RING: INSIDE DIAMETER: 329.57 MM; WIDTH: 6.99 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-455; REFERENCE NO: 204-625-P86; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104739	EA	75		
O RING: INSIDE DIAMETER: 164.17 MM; WIDTH: 6.99 MM; MATERIAL: NEOPRENE; INDUSTRY STANDARD: 2-439; REFERENCE NO: 1280; SIZE: 166MM ID X 6MM THICK; FOR GAS BALLAST PUMP; UNO.35; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104747	EA	75		
O RING: INSIDE DIAMETER: 60 MM; WIDTH: 4 MM; MATERIAL: NEOPRENE; FOR BALZIER GAS BALLAST PUMP UNO.35 SERIAL 1280; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104748	EA	75		
O RING: INSIDE DIAMETER: 40.64 MM; WIDTH: 5.33 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-326; 42 X 4MM; BALZIER GAS PUMP; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104749	EA	75		

O RING: INSIDE DIAMETER: 14 MM; WIDTH: 3 MM; MATERIAL: NEOPRENE; REFERENCE NO: 1280; FOR BALZIER GAS BALLAST PUMP UNO.35; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104750	EA	75		
O RING: INSIDE DIAMETER: 4.47 MM; WIDTH: 1.78 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-008; REFERENCE NO: 3582; IN423906382; FOR FISHER VALVE POSITIONER 3582; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104763	EA	75		
O RING, CORD: MATERIAL: RUBBER; THICKNESS: 6 MM; REFERENCE NO: 104 601 561 023; FOR SULZER PUMP HPT POK 32-25; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104772	EA	75		
O RING: INSIDE DIAMETER: 196.44 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-265; CAT NO: 021 702 020 009; REFERENCE NO: 52.23; 202-8; 202.8; ARTICLE; FOR PUMP HPT POK 32-25; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104780	EA	75		
O RING: INSIDE DIAMETER: 139.29 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-254; REFERENCE NO: 2-151-142 442/1; 412-1; NB80; FOR KSB PUMP TYPE LUVE 200-415/1; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104782	EA	75		
O RING: INSIDE DIAMETER: 80 MM; FOR PUMP TYPE LUVE 200-415/1, SERIAL: 2-151-142 442/1; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104783	EA	75		
O RING: INSIDE DIAMETER: 202.57 MM; WIDTH: 5.33 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-369; REFERENCE NO: 412.5; 2-151-142 442/1; NB70; FOR PUMP TYPE LUVE 200-415/1; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104784	EA	75		
O RING: WIDTH: 7.8 MM; MATERIAL: RUBBER; SUPPL P/N: 412.6; REFERENCE NO: 2-151-142 442/1; TYPE: NB70; FOR KSB PUMP; TYPE LUVE 200-415/1; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104785	EA	75		

O RING: INSIDE DIAMETER: 291.69 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-277; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104794	EA	75		
O RING: INSIDE DIAMETER: 5/8 IN; MATERIAL: VITON; APPLICATION: OIL BURNER; DRAWING NO: CD1840 REV 1; REFERENCE NO: G2G; SIZE: 13/16" OD; IMPERIAL SIZE ONLY; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104835	EA	700		
O RING: INSIDE DIAMETER: 1/2 IN; WIDTH: 0.7 IN; MATERIAL: VITON; REFERENCE NO: G2K; FOR PEABODY OIL BURNERS; OD 5/8 IN; IMPERIAL SIZE ONLY; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104836	EA	1000		
O RING: INSIDE DIAMETER: 2.9 MM; WIDTH: 1.78 MM; MATERIAL: RUBBER SYNTHETIC; INDUSTRY STANDARD: 2-006; SUPPL P/N: 1D1346-0699; FOR FISHER VALVE POSITIONER 3560 AND 3580; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104848	EA	75		
O RING: INSIDE DIAMETER: 6.07 MM; WIDTH: 1.78 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-010; REFERENCE NO: 1D6875-06992; FOR FISHER RELAY AND POSITIONERS; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104850	EA	75		
O RING: INSIDE DIAMETER: 44.04 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-224; REFERENCE NO: IE8458-06992; VALVE; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104851	EA	75		
O RING: INSIDE DIAMETER: 4.34 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-201; KEY 16; ITEM NUMBER: 1H2919-0699; FOR FISHER VALVE POSITIONER TYPE 836; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104852	EA	75		
O RING: INSIDE DIAMETER: 18.64 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-210; REFERENCE NO: 1C3762-0699; VALVE; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104856	EA	75		

O RING: INSIDE DIAMETER: 18.64 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-210; REFERENCE NO: 1E2226-0699; VALVE; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104858	EA	75		
O RING: INSIDE DIAMETER: 4.42 MM; WIDTH: 2.62 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-106; REFERENCE NO: 1D6825-0699; VALVE; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104859	EA	75		
O RING: REFERENCE NO: 1F1139-0699; VALVE; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104862	EA	75		
O RING: REFERENCE NO: 1H8619-0699; KEY 29C; FOR POSITIONER; TYPE 3570; CONDENSATION AND FEED HEATING; ITEM 1E2226-X0012; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104863	EA	75		
O RING: INSIDE DIAMETER: 266.29 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-275; REFERENCE NO: 34530000057; VV; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104874	EA	75		
O RING: INSIDE DIAMETER: 10.77 MM; WIDTH: 2.62 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-111; REFERENCE NO: 86-42/12; FOR ACTUATOR ASM160; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104878	EA	800		
O RING: INSIDE DIAMETER: 203.2 MM; WIDTH: 6 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104879	EA	75		
O RING: INSIDE DIAMETER: 100.97 MM; WIDTH: 5.33 MM; MATERIAL: NITRILE; INDUSTRY STANDARD: 2-345; (70/SHORE); VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104880	EA	75		
O RING: INSIDE DIAMETER: 215.27 MM; WIDTH: 6.99 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-446; 460MM ID; EXT PUMP; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104884	EA	75		

O RING: INSIDE DIAMETER: 24.99 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-214; 50 TURBINE; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104886	EA	75		
O RING SET: MATERIAL: RUBBER; DRAWING NO: BBT R 408728 POS 5731 REV 1; POS NO:- 207; IP CONTROL OIL FILTER 100PCT; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104891	EA	75		
O RING: INSIDE DIAMETER: 9.19 MM; WIDTH: 2.62 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-110; SUPPL P/N: R253A03834-36; REQUIRED WITH DELIVERY DATE OF MANUFACTURE, SHELF LIFE AND STORAGE METHOD; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104898	EA	75		
O RING: INSIDE DIAMETER: 75.57 MM; WIDTH: 5.33 MM; MATERIAL: VITON; INDUSTRY STANDARD: 2-337; SUPPL P/N: 66555; PURIFIER 103; 75.87MM X 86MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104900	EA	75		
O RING: INSIDE DIAMETER: 41 MM; WIDTH: 1.78 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-030; ID 40.87MM; FOR HIGH PRESSURE BYPASS VALVE A32-2 SERVO MOTOR ASM 100; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104902	EA	75		
O RING: INSIDE DIAMETER: 21.89 MM; WIDTH: 2.62 MM; MATERIAL: NITRILE; INDUSTRY STANDARD: 2-118; REFERENCE NO: 85-54-11; 21.89MMOUTSIDE DIA; 85 DEGREES DURO HARDNESS; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104903	EA	75		
O RING: INSIDE DIAMETER: 78.74 MM; WIDTH: 5.33 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-338; SUPPL P/N: 021 501 007 801; FOR SULZER SERVO MOTOR ASM 250F; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104904	EA	75		
O RING: INSIDE DIAMETER: 228.27 MM; WIDTH: 6.99 MM; MATERIAL: NITRILE; INDUSTRY STANDARD: 2-175; REFERENCE NO: ASM 250F; SIZE 227.97 X 7MM; FOR USE ON SERVO MOTOR; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104905	EA	75		

O RING: INSIDE DIAMETER: 94.62 MM; WIDTH: 5.33 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-343; REFERENCE NO: 85-56-49; 91.44MM OD; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104906	EA	75		
O RING: INSIDE DIAMETER: 50.39 MM; WIDTH: 3.53 MM; MATERIAL: NEOPRENE; INDUSTRY STANDARD: 2-226; SUPPL P/N: 85-66/6; REFERENCE NO: ASM 160A; SIZE 53.57; FOR REHEAT SAFETY VALVE MSV 200 SERVO MOTOR; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104907	EA	75		
O RING: INSIDE DIAMETER: 53.57 MM; WIDTH: 3.53 MM; MATERIAL: NEOPRENE; INDUSTRY STANDARD: 2-227; REFERENCE NO: 85-66-11; 53.35MM X 5.35MM THICK; FOR USE ON SERVO MOTOR ASM 160A; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104908	EA	75		
O RING: INSIDE DIAMETER: 145.42 MM; WIDTH: 6.99 MM; MATERIAL: NEOPRENE; INDUSTRY STANDARD: 2-435; REFERENCE NO: ASM 160A; 85-66-20; MSV 200; SIZE: 148.6MM X 70MM; FOR REHEAT SAFETY VALVE SERVO MOTOR; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104909	EA	75		
O RING: INSIDE DIAMETER: 24.99 MM; WIDTH: 3.53 MM; REFERENCE NO: 85-30-6; FOR HIGH PRESSURE SPRAYWATER VALVE A20-5 SERVO MOTOR ASM 63; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104911	EA	75		
O RING: INSIDE DIAMETER: 209.14 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-267; REFERENCE NO: 85-30-20; 56.74MM; FOR SULZER SERVO MOTOR ASM 63 AND ACTUATOR ASM 163-10; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104912	EA	75		
O RING: REFERENCE NO: 200-336-4490; ACT 30A; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104916	EA	75		
O RING: INSIDE DIAMETER: 158.42 MM; WIDTH: 2.62 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-164; REFERENCE NO: 2X166-1.71; 2X166-1.71 ACTUATOR; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104920	EA	75		

O RING: INSIDE DIAMETER: 9.19 MM; WIDTH: 2.62 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-110; 12.2MM VALVE; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104925	EA	75		
O RING: INSIDE DIAMETER: 177.17 MM; WIDTH: 6.99 MM; MATERIAL: NEOPRENE; INDUSTRY STANDARD: 2-441; REFERENCE NO: 16L/S; 50HTGD90228-16L/S; FOR BOILER FEED PUMP LUB OIL FILTER; 16L/SEC; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104947	EA	75		
O RING: INSIDE DIAMETER: 240.67 MM; WIDTH: 6.99 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-448; DRAWING NO: BBT HTGD 90228 POS 50 REV 1; FOR MAIN TURBINE LUB OIL FILTER, 25 L/S, SCHEMATIC POS; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104949	EA	75		
O RING, CORD: MATERIAL: NEOPRENE; THICKNESS: 1.5 MM; BLACK; REQUIRED WITH DELIVERY DATE OF MANUFACTURE, SHELF LIFE AND STORAGE METHOD; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104968	EA	75		
O RING: INSIDE DIAMETER: 9.25 MM; WIDTH: 1.78 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-012; SUPPL P/N: 3.61; MODEL NO: B932; M76344; REFERENCE NO: B932; 306-097; 9.5 X 1.6; FOR LINEAR ACTUATOR M76344-C7336-B932; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104987	EA	75		
O RING: INSIDE DIAMETER: 28.17 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-216; REFERENCE NO: 2640-123-135; SIZE5-1/8; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104990	EA	75		
O RING: INSIDE DIAMETER: 126.59 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-216; REFERENCE NO: 2450/123/135; SIZE5-1/8; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104992	EA	75		

O RING SET: TYPE: SEAL WATER; APPLICATION: PUMP; SUPPL P/N: JSG/363/98; MODEL NO: KTM82; MBX80-3; CONSISTS OF: 2 O RINGS OD 188 KANTINOL, 3 O RINGS OD 273 KANTINOL KTM83, 2 O RINGS ID 131 KANTINOL KTM84, 2 FLANGE RINGS ID 50MM, ITEMS MUST BE PROTECTIVE PACKED PER INDIVIDUAL KIT AND MARKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	104993	EA	75		
O RING: INSIDE DIAMETER: 15.6 MM; WIDTH: 1.78 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-016; SUPPL P/N: 3.63; MODEL NO: M76341-E AND M76344 C7336 B932; REFERENCE NO: C71121-Z101-A299; 16 X 1.25; FOR ACTUATOR; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	105843	EA	75		
O RING: INSIDE DIAMETER: 89.01 MM; WIDTH: 6.99 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-341; NEOPRENE; SIZE 89MM ID X 7MM THICK; REQUIRED WITH DELIVERY DATE OF MANUFACTURE; SHELF LIFE AND STORAGE METHOD; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	106225	EA	75		
O RING: INSIDE DIAMETER: 98.02 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER SYNTHETIC; INDUSTRY STANDARD: 2-241; SUPPL P/N: 200-241-9775; REQUIRED WITH DELIVERY DATE; SHELF LIFE AND STORAGE METHOD; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	106246	EA	75		
O RING: INSIDE DIAMETER: 2.9 MM; WIDTH: 1.78 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-006; REFERENCE NO: 0B43; CHLORINATOR; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	107221	EA	75		
O RING: INSIDE DIAMETER: 10.82 MM; WIDTH: 1.78 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-013; REFERENCE NO: 0B44; CHLORINATOR; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	107222	EA	75		
O RING: INSIDE DIAMETER: 15.6 MM; WIDTH: 1.78 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-016; APPLICATION: CHLORINATOR; REFERENCE NO: 0B45; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	107223	EA	75		

O RING: INSIDE DIAMETER: 37.69 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-222; APPLICATION: CHLORINATOR; REFERENCE NO: 0B47; OB47; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	107224	EA	75		
O RING: INSIDE DIAMETER: 177.39 MM; WIDTH: 3.53 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-262; REFERENCE NO: OB49; CHLORINATOR; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	107225	EA	75		
O RING: INSIDE DIAMETER: 126.59 MM; WIDTH: 2.62 MM; MATERIAL: RUBBER; INDUSTRY STANDARD: 2-250; DRAWING NO: BBT TGR 305551 POS 94 REV 1; FOR HP.IP AND LP BYPASS CONTROL VALVE TYPE:- AVES 315/125; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	119230	EA	75		
O RING: INSIDE DIAMETER: 60 MM; WIDTH: 2.5 MM; MATERIAL: RUBBER; SUPPL P/N: 162423; MODEL NO: SVC600/250; FOR USE ON BECKER AND SOHNE COMPRESSOR, POS NO 18/856; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	212670	EA	75		
O RING: INSIDE DIAMETER: 51 MM; WIDTH: 2.5 MM; MATERIAL: RUBBER; SUPPL P/N: 173592; MODEL NO: SVC600/250; FOR USE ON BECKER AND SOHNE COMPRESSOR, POS NO 18/857; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	212671	EA	75		
O RING: INSIDE DIAMETER: 74 MM; WIDTH: 4 MM; MATERIAL: RUBBER; SUPPL P/N: 169531; MODEL NO: SVC600/250; FOR USE ON BECKER AND SOHNE COMPRESSOR, POS NO 21/906; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	212672	EA	75		
O RING: INSIDE DIAMETER: 110 MM; WIDTH: 3 MM; MATERIAL: RUBBER; SUPPL P/N: PDZ70040; MODEL NO: HG250; FOR USE ON ASH PUMP TYPE FRAME 600, MODEL NUMBER: HG250; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	218963	EA	75		
O RING: INSIDE DIAMETER: 3.2 MM; MATERIAL: NEOPRENE; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	219662	EA	1400		

O RING: INSIDE DIAMETER: 145.42 MM; WIDTH: 6.99 MM; MATERIAL: NBR 90; FOR USE ON FD, ID AND AIR HEATER BOWMAN LUBRICATING OIL COOLERS; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	219959	EA	75		
O RING SET: TYPE: SEALING; APPLICATION: STRAINER; QUANTITY: 8; MATERIAL: VITON; SIZE RANGE: ID 52 X OD 60 X THK 4 MM; MATERIAL AND TECHNICAL DATA SHEET TO BE PROVIDED WITH THE O-RINGS; SULPHUR DUPLEX; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	611529	EA	75		
O RING: INSIDE DIAMETER: 9.6 MM; WIDTH: 20 M; MATERIAL: VITON; INDUSTRY STANDARD: ISO 37; ISO 868; COLOR: BLACK; APPLICATION: GENERATOR HYDROGEN COOLER; SHORE HARDNESS: G70-034; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	724858	EA	75		
SUBTOTAL					
GRAND TOTAL(TOTAL OF THE SUBTOTAL)					

ESKOM HOLDINGS SOC Ltd CONTRACT NUMBER _____
CONTRACT TITLE: SUPPLY AND DELIVERY OF SEALS, GASKETS, O-RINGS, AND PACKINGS FOR FIVE (5) YEARS AT KRIEL
POWER STATION ON AN "AS AND WHEN" REQUIRED BASIS.

Document reference	Title	No of pages
	This cover page	1
C3.1	<i>Purchaser's</i> Goods Information	7
C3.2	<i>Supplier's</i> Goods Information	1
	Total number of pages	9

C3.1: *PURCHASER'S* GOODS INFORMATION

Contents

Part 3: Scope of Work	1
C3.1: <i>Purchaser's</i> Goods Information	2
1 Overview and purpose of the <i>goods</i> and <i>services</i>	4
2 Specification and description of the <i>goods</i>	4
2.1 <i>Purchaser's</i> design	4
2.2 Procedure for submission and acceptance of <i>Supplier's</i> design	4
2.3 Other requirements of the <i>Supplier's</i> design	4
2.4 Use of <i>Supplier's</i> design	4
2.5 Manufacture & fabrication	4
2.6 Factory acceptance testing (FAT)	4
2.7 Other tests and inspections and commissioning in place of use	5
2.8 Operating manuals and maintenance schedules	5
3 Supply Requirements	5
4 Specification of the <i>services</i> to be provided	5
5 Constraints on how the <i>Supplier</i> Provides the Goods	5
5.1 Programming constraints	5
5.2 Work to be done by the Delivery Date	5
5.3 Marking the <i>goods</i>	5
5.4 Constraints at the delivery place and place of use	5
5.5 Cooperating with Others	6
5.6 Services & other things to be provided by the <i>Purchaser</i> or <i>Supplier</i>	6
5.7 Management meetings	6
5.8 Documentation control	6
5.9 Health and safety risk management	6
5.10 Environmental constraints and management	7
5.11 Quality	7
5.12 Invoicing and payment	7
5.13 Insurance provided by the <i>Purchaser</i>	8
5.14 Contract change management	8
5.15 Provision of bonds and guarantees	8
5.16 Records of Defined Cost, payments & assessments of compensation events to be kept by the <i>Supplier</i>	8
6 Procurement	8
6.1 Subcontracting	8

6.1.1	Preferred subcontractors	8
6.1.2	Limitations on subcontracting	8
6.1.3	Spares and consumables	8
6.1.4	Other requirements related to procurement.....	8
6.1.5	Cataloguing requirements by the <i>Supplier</i>	8
	Not Applicable to this contract.....	8
7	List of drawings.....	8
7.1	Drawings issued by the <i>Purchaser</i>	8
C3.2	Supplier's Goods Information	9

1 Overview and purpose of the *goods and services*

Kriel Power Station is faced with unnecessary UCLF (Unavailability Capability Loss Factor) due to unavailability of spares. Therefore, to mitigate this, a decision was made by the business to set up a supply and delivery Gaskets, Packings, Seals and O-rings on an as and when required basis to ensure that Kriel Power Station have the right spares when needed. To minimise disruption to the production and leaving output levels uncompromised.

The benefits of spares contract are as follows:

- a) **Reduces downtime** (With the parts you need already at your disposal, you can minimise the time for repair).
- b) **Increases productivity** (With reduced downtime comes increased productivity, it enables you to fix issues quickly when they do happen).
- c) **Better inventory** (This means that no matter what issue occurs, you have the necessary means to repair it).
- d) **Limited costs** (To ensure the availability of spares for maintenance and repairs of the plant as and when required at an optimum/best cost).

2 Specification and description of the *goods*

2.1 *Purchaser's design*

Not applicable to this contract.

2.2 *Procedure for submission and acceptance of Supplier's design*

Not applicable to this contract.

2.3 *Other requirements of the Supplier's design*

Not applicable to this contract.

2.4 *Use of Supplier's design*

Not applicable to this contract.

2.5 *Manufacture & fabrication*

Not applicable to this contract.

2.6 *Factory acceptance testing (FAT)*

Not applicable to this contract.

2.7 Other tests and inspections and commissioning in place of use

Not applicable to this contract.

2.8 Operating manuals and maintenance schedules

Not applicable to this contract.

3 Supply Requirements

All Spares to be supplied as per supplied Scope of Work.

4 Specification of the services to be provided

Not applicable to this contract.

5 Constraints on how the *Supplier* Provides the Goods

5.1 Programming constraints

<i>goods and services</i>	Delivery Date
SEALS, GASKETS, O-RINGS, AND PACKINGS	Within 1 week after placement of order

5.2 Work to be done by the Delivery Date

All Spares to be supplied as per supplied scope of work.

5.3 Marking the *goods*

Supplier shall mark and package goods in a manner that the information for each spare will be easily identifiable.

5.4 Constraints at the delivery place and place of use

- a) All deliveries shall be arranged within Kriel Power Station normal working hours as stipulated in section 3 of this document.
- b) The *Supplier* applies for temporary access permits (Contractor's Permit) at the Security gate, prior to the Possession Date.
- c) The *Supplier's* personnel are required to be in possession of Permit at all times.
- d) All *Supplier's* personnel are issued with a temporary access permit which contains the following information:
 - Name
 - ID Number
 - Company
 - Validity date
- e) No unauthorised vehicles are allowed on site.

5.5 Cooperating with Others

- a) The *Supplier* cooperates with the stores personnel during Delivery.
- b) The *Supplier* co-operates with the *Purchaser's* team in ensuring that the goods are delivered in accordance to all requirements.

5.6 Services & other things to be provided by the *Purchaser* or *Supplier*

- a) The availability of rigging equipment, cranes or forklift and the relevant operators must be confirmed with the Kriel Power Station (*Purchaser*) before dispatching the goods.
- b) The *Supplier* provides offloading people to assist with offloading at receiving. NB: The *Supplier* offloading team names must be part of the valid approved safety file.

5.7 Management meetings

Regular meetings of a general nature may be convened and chaired by the *Supply Manager* as follows:

Title and purpose	Approximate time & interval	Location	Attendance by:
Risk register and compensation events	When the need arises	TBC	<i>Purchaser, Supplier, and Cross functional team members</i>
Overall contract progress and feedback	Quarterly or as and when urgent need arises	TBC	<i>Purchaser, Supplier, and CFT</i>

Meetings of a specialist nature may be convened as specified elsewhere in this Goods Information or if not so specified by persons and at times and locations to suit the Parties, the nature and the progress of the manufacture of the *goods*. Records of these meetings shall be submitted to the *Supply Manager* by the person convening the meeting within five days of the meeting.

All meetings shall be recorded using minutes or a register prepared and circulated by the person who convened the meeting. Such minutes or register shall not be used for the purpose of confirming actions or instructions under the contract as these shall be done separately by the person identified in the *conditions of contract* to carry out such actions or instructions.

5.8 Documentation control

All contractual communications will be in the form of properly compiled letters or forms attached to e-mails and not as a message in the e mail itself.

5.9 Health and safety risk management

- a) The *Supplier* complies with Section 10 of Occupational Health and Safety Act (Act No.85 of 1993) when manufacturing any *goods* for this Contract.
- b) The *Supplier* shall comply with Site health and safety requirements for Kriel Power Station when delivering *goods*.
- c) Site Delivery safety requirements to be adhered to - And can be obtained through the *Purchaser's Manager* In line with the SHE specification
- d) The *Supplier* submits safety file for approval before access is granted
- e) The *Supplier* maintains the safety file validity in line with Site requirements
- f) The mode of transport for Delivery should comply with Site requirement in line with issued SHE specification
- g) *Supplier* to update their safety file yearly and each time they make changes on their staff or personnel

h) The Supplier ensures that when changing a team member, the new team gets inducted and all process of safety file approval is adhered to- before gaining access to site

The *Supplier* shall comply with the health and safety requirements contained in Annexure A to this Goods Information.

The *Supplier* shall comply with the health and safety requirements [stated here or contained in Annexure A to this Goods Information.

5.10 Environmental constraints and management

The *Supplier* shall comply with the environmental criteria and constraints when doing deliveries at Kriel Power Station premises regarding:

a) The vehicle used for Delivery; by ensuring that there are no oil spillages, and the vehicle emission is not emitting beyond limits.

b) The material used for supporting the *goods* being delivered are correctly disposed and are without harm to environment. The *Supplier* must comply with Site Environmental management plan (EMP) and other requirement.

c) The *Supplier* complies with Environmental aspect and impact register

d) The *Supplier* complies with all Site environmental management procedures, especially the waste management and oil spillages.

The *Supplier* shall comply with the environmental criteria and constraints contained in Annexure B

5.11 Quality

a) The *Supplier* compiles the baseline Quality Control plan

b) Quality Control Plan (QCP) must be approved by both the *Suppliers*, Eskom engineer and QC inspector before commencing with any deliveries at the beginning of the contract

c) Material certificates, mechanical testing certificate and NDT certificates should be part of the data package accompanying the QCPs.

d) All delivered goods will be subjected to QC verification by an Employer's Quality personnel at receiving at per detailed item description found in heading 2 table

e) The *Supplier* must comply with Eskom's Supply Quality Management Specification (Document No: 240-105658000) and ISO 9001:2015 requirements.

f) The *Employer* will on frequent basis conduct the *Supplier's* performance/ compliance in accordance to QM 58 and ISO 9001 and NCR will be raised for non-compliance be raised for non-compliance The *Supplier* shall comply with the quality criteria and constraints contained in Annexure C of the Invitation

to Tender

5.12 Invoicing and payment

Within one week of receiving a payment certificate from the *Purchaser Manager* in terms of core clause 51.1, the *Contractor* provides the *Employer* with a tax invoice showing the amount due for payment equal to that stated in the *Service Manager's* payment certificate.

The *Contractor* shall address the tax invoice to

Invoiceseskomlocal@eskom.co.za

and include on each invoice the following information:

- Name and address of the *Contractor* and the *Service Manager*;
- The contract number and title;
- *Contractor's* VAT registration number;
- The *Employer's* VAT registration number 4740101508;
- Description of service provided for each item invoiced based on the Price List;
- Total amount invoiced excluding VAT, the VAT and the invoiced amount including VAT;
- Purchase order number
- Invoice number
- GR Number
- Supplier's Banking details

5.13 Insurance provided by the *Purchaser*

Not applicable to this contract.

5.14 Contract change management

Any changes related to this official contract to be communicated to *Purchase Manager*

5.15 Provision of bonds and guarantees

Not applicable to this contract.

5.16 Records of Defined Cost, payments & assessments of compensation events to be kept by the *Supplier*

The *Supplier* is required to keep records of accounts of payment of Defined Cost, proof that payments have been made, communications about and assessments.

6 Procurement

6.1 Subcontracting

6.1.1 Preferred subcontractors

Not applicable to this contract.

6.1.2 Limitations on subcontracting

Not applicable to this contract.

6.1.3 Spares and consumables

Not applicable to this contract.

6.1.4 Other requirements related to procurement

The Following is SD&L/ CSI Requirement:

The CSI target for this tender is 0.5% of the local content value (contracted amount minus the foreign portion) if applicable

6.1.5 Cataloguing requirements by the *Supplier*

Not Applicable to this contract

7 List of drawings

7.1 Drawings issued by the *Purchaser*

Not applicable. Reference number provided with the materials to be utilised.

C3.2 *SUPPLIER'S* GOODS INFORMATION

This section of the Goods Information will always be contract specific depending on the nature of the *goods* and *services*.

It is most likely to be required for supply contracts where the tendering supplier will have proposed specifications and schedules for the *goods* and *services*, which once accepted by the *Purchaser* prior to award of contract now become obligations of the *Supplier* per core clause 20.1.

This section could also be compiled as a separate file.
