

		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17																					
A																																							
B																																							
C																																							
D																																							
E																																							
F																																							
G																																							
H																																							
J																																							
K																																							
L																																							
M																																							
DOOR SCHEDULE MASTER																																							
ALL DIMENSIONS TO BE CHECKED ON SITE BEFORE CONSTRUCTION COMMENCES																																							
DOOR FRAME (1)		1.17	Purpose made Single rebate hot dip galv. steel door frame with 30 x 32mm rebate to receive door panel from 16mm mild steel for 110mm wall size. 3 sets of hinges, min 2mm plate & min 5.7mm pin. Frame to fit door panels with rubber seals.	1.8	12mm single rebate steel door frame from 1.6mm galv. mild steel for 110mm wall size with lock box & ss strike plate. 3 sets of hinges, min 2mm plate & min 5.7mm pin. Frame to fit door panel with rubber seals.	PAINT FINISH: All steelwork to be painted, except where otherwise indicated. The following paint is to be strictly applied according to manufacturer's specifications. Exterior: Interthane 990 with Plascolthane 9000 Interior: Plascoguard Gehopon 3000 WB Series																																	
IRON MONGERY (3)		3.10	DORMA TH120 SS handle with matching DCE-002 escutcheon pair with UNION L-22315-76 with 3x8 cylinder with rebate striker plate. Masterkey. Second opening panel with rebate mounted flush DFB-S-027160 @ top and DFB-SS-028300 @ bottom with DPS-SS-032 Dust keep in floor. MATADOR weather strip to full length of door panel. Summary: Standard double door, exterior	3.39	DORMA TH120 SS handle with matching DCE-002 escutcheon pair with UNION L-22315-76 with 3x8 cylinder with rebate striker plate & Masterkey. Summary: Substation Single Door	Single door dust proof galv. steel frame, 110																																	
PANEL FINISH (5)		5.1	Prepare surface, apply PLASCON oil wood primer (UC2UC17) and 2 Final coats PLASCON Velvaglo (VLO) colour to be finalised on site			Summary: Painted																																	
FRAME FINISH (6)		6.1	Prepare, apply PLASCON : 1 coat NAMELCOTE (UC53) 1 coat MERIT UNIVERSAL undercoat (UC1). 2 Final coats VELVAGLO colour to be finalised			Summary: Steel primer, Painted																																	
DOOR PANEL (2)		2.93	Custom hardwood door 2178x866x46mm thick frame, 16mm louvres, 150x44mm head rail, 114x22mm intermediate and lock rails, 228x22mm bottom rail 114x22mm diagonal braces, 22mm V-jointed T&G battens in selected brown Meranti hardwood. Aluminium frame & louvres to be fitted in door.			Aluminium frame & louvres to be fitted in door.																																	
DOOR SCHEDULE SCALE 1:50						NOTE: Rev 10: Cover back of aluminium louvre frame with a 3mm thick sheet of metal, to match size of frame, and pop rivet to fit tight FFL																																	
ALL DIMENSIONS TO BE CHECKED ON SITE BEFORE CONSTRUCTION COMMENCES																																							
DOOR SCHEDULE																																							
DOOR FRAME (1)		1.17	Purpose made Single rebate hot dip galv. steel door frame with 30 x 32mm rebate to receive door panel from 16mm galv. mild steel for 110mm wall size. 3 sets of hinges, min 2mm plate & min 5.7mm pin. Frame to fit door panels with rubber seals.	1.8	12mm single rebate steel door frame from 1.6mm galv. mild steel for 110mm wall size with lock box & ss strike plate. 3 sets of hinges, min 2mm plate & min 5.7mm pin. Frame to fit door panel with rubber seals.	PAINT FINISH: All steelwork to be painted, except where otherwise indicated. The following paint is to be strictly applied according to manufacturer's specifications. Exterior: Interthane 990 with Plascolthane 9000 Interior: Plascoguard Gehopon 3000 WB Series																																	
IRON MONGERY (3)		3.10	DORMA TH120 SS handle with matching DCE-002 escutcheon pair with UNION L-22315-76 with 3x8 cylinder with rebate striker plate. Masterkey. Second opening panel with rebate mounted flush DFB-S-027160 @ top and DFB-SS-028300 @ bottom with DPS-SS-032 Dust keep in floor. MATADOR weather strip to full length of door panel. Summary: Standard double door, exterior	3.39	DORMA TH120 SS handle with matching DCE-002 escutcheon pair with UNION L-22315-76 with 3x8 cylinder with rebate striker plate & Masterkey. Summary: Substation Single Door	Single door dust proof galv. steel frame, 110																																	
PANEL FINISH (5)		5.1	Prepare surface, apply PLASCON oil wood primer (UC2UC17) and 2 Final coats PLASCON Velvaglo (VLO) colour to be finalised on site			Summary: Painted																																	
FRAME FINISH (6)		6.1	Prepare, apply PLASCON : 1 coat NAMELCOTE (UC53) 1 coat MERIT UNIVERSAL undercoat (UC1). 2 Final coats VELVAGLO colour to be finalised			Summary: Steel primer, Painted																																	
DOOR PANEL (2)		2.93	Custom hardwood door 2178x866x46mm thick frame, 16mm louvres, 150x44mm head rail, 114x22mm intermediate and lock rails, 228x22mm bottom rail 114x22mm diagonal braces, 22mm V-jointed T&G battens in selected brown Meranti hardwood. Aluminium frame & louvres to be fitted in door.			Aluminium frame & louvres to be fitted in door.																																	
DOOR SCHEDULE						NOTE: Rev 10: Cover back of aluminium louvre frame with a 3mm thick sheet of metal, to match size of frame, and pop rivet to fit tight FFL																																	
ALL DIMENSIONS TO BE CHECKED ON SITE BEFORE CONSTRUCTION COMMENCES																																							
DOOR SCHEDULE																																							
DOOR FRAME (1)		1.17	Purpose made Single rebate hot dip galv. steel door frame with 30 x 32mm rebate to receive door panel from 16mm galv. mild steel for 110mm wall size. 3 sets of hinges, min 2mm plate & min 5.7mm pin. Frame to fit door panels with rubber seals.	1.8	12mm single rebate steel door frame from 1.6mm galv. mild steel for 110mm wall size with lock box & ss strike plate. 3 sets of hinges, min 2mm plate & min 5.7mm pin. Frame to fit door panel with rubber seals.	PAINT FINISH: All steelwork to be painted, except where otherwise indicated. The following paint is to be strictly applied according to manufacturer's specifications. Exterior: Interthane 990 with Plascolthane 9000 Interior: Plascoguard Gehopon 3000 WB Series																																	
IRON MONGERY (3)		3.10	DORMA TH120 SS handle with matching DCE-002 escutcheon pair with UNION L-22315-76 with 3x8 cylinder with rebate striker plate. Masterkey. Second opening panel with rebate mounted flush DFB-S-027160 @ top and DFB-SS-028300 @ bottom with DPS-SS-032 Dust keep in floor. MATADOR weather strip to full length of door panel. Summary: Standard double door, exterior	3.39	DORMA TH120 SS handle with matching DCE-002 escutcheon pair with UNION L-22315-76 with 3x8 cylinder with rebate striker plate & Masterkey. Summary: Substation Single Door	Single door dust proof galv. steel frame, 110																																	
PANEL FINISH (5)		5.1	Prepare surface, apply PLASCON oil wood primer (UC2UC17) and 2 Final coats PLASCON Velvaglo (VLO) colour to be finalised on site			Summary: Painted																																	
FRAME FINISH (6)		6.1	Prepare, apply PLASCON : 1 coat NAMELCOTE (UC53) 1 coat MERIT UNIVERSAL undercoat (UC1). 2 Final coats VELVAGLO colour to be finalised			Summary: Steel primer, Painted																																	
DOOR PANEL (2)		2.93	Custom hardwood door 2178x866x46mm thick frame, 16mm louvres, 150x44mm head rail, 114x22mm intermediate and lock rails, 228x22mm bottom rail 114x22mm diagonal braces, 22mm V-jointed T&G battens in selected brown Meranti hardwood. Aluminium frame & louvres to be fitted in door.			Aluminium frame & louvres to be fitted in door.																																	
DOOR SCHEDULE																																							