



- NOTES
1. CONCRETE STRENGTH CLASS 'A' THROUGHOUT (30 MPa)
 2. COVER TO REINFORCEMENT 40mm THROUGHOUT EXCEPT FOR BOTTOM STEEL IN FLOOR SLABS OF STORE ROOM, CONVEYOR BELT & CONVEYOR FLOOR WHICH WILL BE 40mm.
 3. ALL SETTING OUT TO BE FROM BEACONS.
 4. ALL OUTER BEAMS TO HAVE DRIP GROOVES.
 5. FOR STEEL FLOOR ARRANGEMENT & COL/FLOOR CONNECTIONS REFER TO DRAWINGS 1145/50/01, 02, 03, 04, 05, 06, 07, 08, 09, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100.

REV	DATE	BY	CHKD	DESCRIPTION
01	11/11/03
02	11/11/03

REV	DATE	BY	CHKD	DESCRIPTION
01	11/11/03
02	11/11/03

REV	DATE	BY	CHKD	DESCRIPTION
01	11/11/03
02	11/11/03

REV	DATE	BY	CHKD	DESCRIPTION
01	11/11/03
02	11/11/03

KEEVE STEYN & VENNOR INC
 Radianco and Engineers en Projectbestuurders
 Consulting Engineers & Project Managers
 Johannesburg tel 28-5733 Durban tel 6-1545

THUTHA POWER STATION
 PROJECT NO. 1145/50/04
 SHEET NO. 1145/50/04-1