



NEC3 Supply Contract (SC3)

Between **ESKOM HOLDINGS SOC LIMITED**
(Reg No. 2002/015527/30)

and (Reg No. _____)

for **Manufacture, Supply and Delivery to site of Personal Protective Equipment Clothing for Matimba Power Station over a period of five years on as and when required basis.**

Contents:	Page
Part C1 Agreements & Contract Data	2
Part C2 Pricing Data	17
Part C3 Scope of Work	23

CONTRACT No.

PART C1: AGREEMENTS & CONTRACT DATA

Contents:	Page
C1.1 Form of Offer and Acceptance	3
[to be inserted from Returnable Documents at award stage]	
C1.2a Contract Data provided by the <i>Purchaser</i>	6
C1.2b Contract Data provided by the <i>Supplier</i>	15

C1.1 Form of Offer & Acceptance

Offer

The Purchaser, identified in the Acceptance signature block, has solicited offers to enter into a contract for the procurement of: **Manufacture, Supply and Delivery to site of Personal Protective Equipment Clothing for Matimba Power Station over a period of five years on as and when required basis**

	The offered total of the Prices exclusive of VAT is	R
	Value Added Tax @ 15% is	R
	The offered total of the amount due inclusive of VAT is ¹	R

This Offer may be accepted by the Purchaser by signing the Acceptance part of this Form of Offer and Acceptance and returning one copy of this document including the Schedule of Deviations (if any) to the tenderer before the end of the period of validity stated in the Tender Data, or other period as agreed, whereupon the tenderer becomes the party named as the *Supplier* in the *conditions of contract* identified in the Contract Data.

Signature(s)

Name(s)

Capacity

For the tenderer:

Name & signature of witness

Date

Acceptance

By signing this part of this Form of Offer and Acceptance, the Purchaser identified below accepts the tenderer's Offer. In consideration thereof, the Purchaser shall pay the Supplier the amount due in accordance with the *conditions of contract* identified in the Contract Data. Acceptance of the tenderer's Offer shall form an agreement between the Purchaser and the tenderer upon the terms and conditions contained in this agreement and in the contract that is the subject of this agreement.

The terms of the contract, are contained in:

- Part C1 Agreements and Contract Data, (which includes this Form of Offer and Acceptance)
- Part C2 Pricing Data
- Part C3 Scope of Work: Goods Information including Supply Requirements

and drawings and documents (or parts thereof), which may be incorporated by reference into the above listed Parts.

¹ This total is required by the *Purchaser* for budgeting purposes only. Actual amounts due will be assessed in terms of the *conditions of contract*.

Deviations from and amendments to the documents listed in the Tender Data and any addenda thereto listed in the Returnable Schedules as well as any changes to the terms of the Offer agreed by the tenderer and the Purchaser during this process of offer and acceptance, are contained in the Schedule of Deviations attached to and forming part of this Form of Offer and Acceptance. No amendments to or deviations from said documents are valid unless contained in this Schedule.

The tenderer shall within two weeks of receiving a completed copy of this agreement, including the Schedule of Deviations (if any), contact the Purchaser’s agent (whose details are given in the Contract Data) to arrange the delivery of any securities, bonds, guarantees, proof of insurance and any other documentation to be provided in terms of the *conditions of contract* identified in the Contract Data at, or just after, the date this agreement comes into effect. Failure to fulfil any of these obligations in accordance with those terms shall constitute a repudiation of this agreement.

Notwithstanding anything contained herein, this agreement comes into effect on the date when the tenderer receives one fully completed original copy of this document, including the Schedule of Deviations (if any).

Signature(s)

Name(s) _____ Capacity _____ for the Purchaser	_____ F Munyai _____ Procurement Manager _____ Eskom Holdings SOC Ltd (Reg No 2002/015527/30) Matimba Power Station Private Bag x215,Lephalale 0555 _____
---	---

Name & signature of witness _____	Date _____
---	------------

Note: If a tenderer wishes to submit alternative tenders, use another copy of this Form of Offer and Acceptance.

Schedule of Deviations to be completed by the *Purchaser* prior to contract award

No.	Subject	Details
1		
2.		
3		
4		
5		
6		
7		

By the duly authorised representatives signing this Schedule of Deviations below, the Purchaser and the tenderer agree to and accept this Schedule of Deviations as the only deviations from and amendments to the documents listed in the Tender Data and any addenda thereto listed in the Tender Schedules, as well as any confirmation, clarification or changes to the terms of the Offer agreed by the tenderer and the Purchaser during this process of Offer and Acceptance.

It is expressly agreed that no other matter whether in writing, oral communication or implied during the period between the issue of the tender documents and the receipt by the tenderer of a completed signed copy of this Form shall have any meaning or effect in the contract between the parties arising from this Agreement.

For the tenderer:

For the Purchaser

Signature

.....

.....

Name

.....

F Munyai

Capacity

.....

Procurement Manager

On behalf of

.....

Eskom Holdings SOC Ltd
 (Reg No 2002/015527/30)
 Matimba Power Station
 Private Bag x215, Lephalale
 0555

Name & signature of witness

.....

.....

Date

.....

.....

C1.2 SC3 Contract Data

Part one - Data provided by the *Purchaser*

Clause	Statement	Data
1	General	
	The <i>conditions of contract</i> are the core clauses and the clauses for Options	
		<p>X1: Price adjustment for inflation</p> <p>X2: Changes in the law</p> <p>X7 Delay damages</p> <p>X17 Low performance damages</p> <p>X20 Key performance Indicators</p> <p>Z: <i>Additional conditions of contract</i></p>
	of the NEC3 Supply Contract (April 2013) ²	
10.1	The <i>Purchaser</i> is (name):	Eskom Holdings SOC Limited (Reg No: 2002/015527/06), a juristic person incorporated in terms of the company laws of the Republic of South Africa
	Address	Registered office at Megawatt Park, Maxwell Drive, Sandton, Johannesburg
	Tel No.	014 763 8067
	Fax No.	014 763 8444
10.1	The <i>Supply Manager</i> is (name):	D. Makgamatha
	Address	Eskom Holdings SOC Limited (Reg No: 2002/015527/06) Matimba Power Station Private Bag x215,Lephalale 0555
	Tel	014 763 8067
	Fax	014 763 8444
	e-mail	Makgamdl@eskom.co.za
11.2(13)	The <i>goods</i> are	Personal Protective Equipment's /Clothing
11.2(13)	The <i>services</i> are	Supply and deliver on site Matimba Power Station, Main Stores Receiving
11.2(14)	The following matters will be included in the Risk Register	N/A
11.2(15)	The Goods Information is in	Part 3: Scope of Work and all documents and drawings to which it makes reference.
11.2(15)	The Supply Requirements as part of the	Annexure A to this Contract Data

² Available from Engineering Contract Strategies Tel 011 803 3008 Fax 011 803 3009, www.ecs.co.za.

Goods Information is in

12.2	The <i>law of the contract</i> is the law of	the Republic of South Africa
13.1	The <i>language of this contract</i> is	English
13.3	The <i>period for reply</i> is	1 weeks
2	The Supplier's main responsibilities	Data required by this section of the core clauses is provided by the <i>Supplier</i> in Part 2 and terms in italics used in this section are identified elsewhere in this Contract Data.
3	Time	
30.1	The <i>starting date</i> is.	2022.06.01
30.1	The <i>delivery date</i> of the <i>goods</i> and <i>services</i> is:	Stated in every purchase order
30.2	The <i>Supplier</i> does not bring the <i>goods</i> to the Delivery Place more than one week before the Delivery Date.	N/A
31.1	The <i>Supplier</i> is to submit a first programme for acceptance within	N/A
32.2	The <i>Supplier</i> submits revised programmes at intervals no longer than	N/A
4	Testing and defects	
42	The <i>defects date</i> is	2 weeks after delivery
43.2	The <i>defect correction period</i> is	4 weeks
	except that the <i>defect correction period</i> for	4 weeks
	and the <i>defect correction period</i> for	4 weeks
42.2	The <i>defects access period</i> is	5 days or as agreed by the parties
	except that the <i>defect access period</i> for	5 days or as agreed by the parties
	and the <i>defect access period</i> for	5 or as agreed by the parties
5	Payment	
50.1	The <i>assessment interval</i> is	Between 30 day of each successive month
51.1	The <i>currency of this contract</i> is the	ZAR
51.2	The period within which payments are made is	4 weeks.
51.4	The <i>interest rate</i> is	N/A
6	Compensation events	There is no reference to Contract Data in this section of the core clauses and terms in italics used in this section are identified elsewhere in this Contract Data.
7	Title	There is no reference to Contract Data in this section of the core clauses and terms in italics used in this section are identified elsewhere in this Contract Data.

8 Risks, liabilities, indemnities and insurance

80.1	These are additional <i>Purchaser's</i> risks	None
84.1	The <i>Purchaser</i> provides these insurances from the Insurance Table	N/A
	1. Insurance against	N/A
	Cover / indemnity is	N/A
	The deductibles are	N/A
84.1	The <i>Supplier</i> provides these additional insurances	N/A
84.2	The minimum amount of cover for loss of or damage to any plant and materials provided by the <i>Purchaser</i> is:	The greater of the total of the prices and the Generation asset property damage insurance deductible in the amount of R25 Million
84.2	The minimum limit of indemnity for insurance in respect of loss of or damage to property (except the <i>goods</i> , plant and materials and equipment) and liability for bodily injury to or death of a person (not an employee of the <i>Supplier</i>) caused by activity in connection with this contract for any one event is:	<p>Whatever the <i>Supplier</i> deems necessary in addition to that provided by the <i>Purchaser</i> for any one event with cross liability so that the insurance applies to the Parties separately.</p> <p>The minimum cover for the <i>Purchaser's</i> property, notwithstanding anything stated to the contrary in the <i>Purchaser's</i> insurances, this insurance procured by the supplier will be required to indemnify the <i>Purchaser</i> for loss of or damage to the purchasers' property.</p> <p>Consequently, the cover limit should be in an amount not less than:</p> <p>For any one occurrence or series of occurrences arising out of one but unlimited during the period of insurance:</p> <ul style="list-style-type: none"> R25 million(twenty five million Rand) for Generation property;
84.2	The minimum limit of indemnity for insurance in respect of death of or bodily injury to employees of the <i>Supplier</i> arising out of and in the course of their employment in connection with this contract for any one event is:	As prescribed by the Compensation for Occupational Injuries and Diseases Act No.130 of 1993 and the Contractor's common law liability for people falling outside the scope of the Act with a limit of Indemnity of not less than R500 000(five hundred thousand Rand) and or As provided by the laws of the Country in which the supplier's employees are domiciled
88.1	The <i>Supplier's</i> liability to the <i>Purchaser</i> for indirect or consequential loss, including loss of profit, revenue and goodwill is limited to	R0.00(zero Rand)
88.2	For any one event, the <i>Supplier's</i> liability to the <i>Purchaser</i> for loss of or damage to the <i>Purchaser's</i> property is limited to	<p>To be provided by the <i>supplier</i></p> <ul style="list-style-type: none"> for the <i>Purchaser's</i> existing and surrounding property in the care, custody and control of the supplier: the amount of the deductible(first amount payable) relevant to the event described in the "Format A" insurance policy available on request from Eskom Insurance Management Services. or all other existing <i>Purchaser's</i> property <p>For any one occurrence or series of occurrences arising out of one event but unlimited during the period of contract:</p>

- o R25 million (twenty five million Rand) for Generation property;

88.3	The <i>Supplier's</i> liability for Defects due to his design which are not notified before the last <i>defects date</i> is limited to:	<p>The greater of</p> <ul style="list-style-type: none"> • the total of the Prices or where a claim is made against the <i>Purchaser's</i> insurance the amounts excluded and unrecoverable from the <i>Purchaser's</i> insurance (other than the resulting physical damage to the <i>Purchaser's</i> property which is not excluded) <p>plus,</p> <p>where a claim is made against the <i>Purchaser's</i> assets policy, the highest applicable deductible (first amount payable) namely:</p> <ul style="list-style-type: none"> o R25 Million for Generation property o Distribution of all other <i>Purchasers</i> property
88.4	The <i>Supplier's</i> total liability to the <i>Purchaser</i> , for all matters arising under or in connection with this contract, other than the excluded matters, is limited to	<p>The total of the price at the completion other than for the additional excluded matters.</p> <p>The <i>Supplier's</i> total liability for the additional excluded matters is not limited.</p> <p>The additional excluded matters are amounts for which the <i>Supplier</i> is liable under this contract for:</p> <ul style="list-style-type: none"> • Loss of or damage to property (other than the works, <i>Purchaser's</i> property, Plant and Materials. • Death or injury to a person and infringement of an intellectual property right.
88.5	The <i>end of liability date</i> is	1 years after expiry of contract

9 Termination and dispute resolution

94.1	The <i>Adjudicator</i> is (Name)	To be appointed when a dispute arises by mutual agreement of both parties. If the parties are unable to agree then an adjudicator will be appointed by the Chairman of ICE- SA.
94.2(3)	The <i>Adjudicator nominating body</i> is:	the Chairman of ICE-SA, a Division of the South African Institution of Civil Engineering, or its successor body.
94.4(2)	The <i>tribunal</i> is:	arbitration
94.4(5)	The <i>arbitration procedure</i> is	the latest edition of Rules for the Conduct of Arbitrations published by The Association of Arbitrators (Southern Africa) or its successor body.
94.4(5)	The place where arbitration is to be held is The person or organisation who will choose an arbitrator - if the Parties cannot agree a choice or - if the arbitration procedure does not state who selects an arbitrator, is	Johannesburg, South Africa the Chairman for the time being or his nominee of the Association of Arbitrators (Southern Africa) or its successor body.

10 Data for Option clauses

X1	Price adjustment for inflation
-----------	---------------------------------------

X1.1	The <i>base date</i> for indices is The proportions used to calculate the Price Adjustment Factor are:	proportion	linked to index for	Index prepared by
		100%		
X2	Changes in law			
X2 1	A change in law	Is a compensation event if it occurs after the contract date		
X7	Delay damages	Will be determined as per NCR raised		
X7.1	Delay damages for Delivery are	Delivery of Incorrect items or late delivery	amount	10% of purchase order value
X17	Low performance damages			
X17 1	The amounts for low performance damages are	Amount R50 000.00	Performance Level For each low performance product	
X20	Key Performance Indicator(not used when Option X12 applies)			
X20 2	A report of performance against each KPI is provided at intervals of	10 months		
Z	The additional conditions of contract are	Z1 to Z12 always apply for Eskom		

Z1 Cession delegation and assignment

- Z1.1 The *Supplier* does not cede, delegate or assign any of its rights or obligations to any person without the written consent of the *Purchaser*.
- Z1.2 Notwithstanding the above, the *Purchaser* may on written notice to the *Supplier* cede and delegate its rights and obligations under this contract to any of its subsidiaries or any of its present divisions or operations which may be converted into separate legal entities as a result of the restructuring of the Electricity Supply Industry and the Electricity Distribution Industry.

Z2 Joint ventures

- Z2.1 If the *Supplier* constitutes a joint venture, consortium or other unincorporated grouping of two or more persons or organisations then these persons or organisations are deemed to be jointly and severally liable to the *Purchaser* for the performance of this contract.
- Z2.2 Unless already notified to the *Purchaser*, the persons or organisations notify the *Supply Manager* within two weeks of the Contract Date of the key person who has the authority to bind the *Supplier* on their behalf.
- Z2.3 The *Supplier* does not substantially alter the composition of the joint venture, consortium or other unincorporated grouping of two or more persons without the consent of the *Purchaser* having been given to the *Supplier* in writing.

Z3 Change of Broad Based Black Economic Empowerment (B-BBEE) status

- Z3.1 Where a change in the *Supplier's* legal status, ownership or any other change to his business composition or business dealings results in a change to the *Supplier's* B-BBEE status, the *Supplier* notifies the *Purchaser* within seven days of the change.
- Z3.2 The *Supplier* is required to submit an updated verification certificate and necessary supporting documentation confirming the change in his B-BBEE status to the *Supply Manager* within thirty days of the notification or as otherwise instructed by the *Supply Manager*.
- Z3.3 Where, as a result, the *Supplier's* B-BBEE status has decreased since the Contract Date the *Purchaser* may either re-negotiate this contract or alternatively, terminate the *Supplier's* obligation to Provide the Goods and Services.
- Z3.4 Failure by the *Supplier* to notify the *Purchaser* of a change in its B-BBEE status may constitute a reason for termination. If the *Purchaser* terminates in terms of this clause, the procedures on termination are P1, P2 and P3 as stated in clause 92, and the amount due is A1 and A3 as stated in clause 93.

Z4 Ethics

- Z4.1 Any offer, payment, consideration, or benefit of any kind made by the *Supplier*, which constitutes or could be construed either directly or indirectly as an illegal or corrupt practice, as an inducement or reward for the award or in execution of this contract constitutes grounds for terminating the *Supplier's* obligation to Provide the Goods and Services or taking any other action as appropriate against the *Supplier* (including civil or criminal action).
- Z4.2 The *Purchaser* may terminate the *Supplier's* obligation to Provide the Goods and Services if the *Supplier* (or any member of the *Supplier* where the *Supplier* constitutes a joint venture, consortium or other unincorporated grouping of two or more persons or organisations) is found guilty by a competent court, administrative or regulatory body of participating in illegal or corrupt practices.
- Such practices include making of offers, payments, considerations, or benefits of any kind or otherwise, whether in connection with any procurement process or contract with the *Purchaser* or other people or organisations and including in circumstances where the *Supplier* or any such member is removed from the an approved vendor data base of the *Purchaser* as a consequence of such practice.
- Z4.3 Notwithstanding the provisions of core clause 90.2, the procedures on termination in terms of this clause are P1, P2 and P3 as stated in the core clause 92 and the amount due is A1 and A3 as stated in core clause 93.

Z5 Confidentiality

- Z5.1 The *Supplier* does not disclose or make any information arising from or in connection with this contract available to Others. This undertaking does not, however, apply to information which at the time of disclosure or thereafter, without default on the part of the *Supplier*, enters the public domain or to information which was already in the possession of the *Supplier* at the time of disclosure (evidenced by written records in existence at that time). Should the *Supplier* disclose information to Others in terms of clause 23.1, the *Supplier* ensures that the provisions of this clause are complied with by the recipient.
- Z5.2 If the *Supplier* is uncertain about whether any such information is confidential, it is to be regarded as such until notified otherwise by the *Supply Manager*.
- Z5.3 In the event that the *Supplier* is, at any time, required by law to disclose any such information which is required to be kept confidential, the *Supplier*, to the extent permitted by law prior to disclosure, notifies the *Purchaser* so that an appropriate protection order and/or any other action can be taken if possible, prior to any disclosure. In the event that such protective order is not, or cannot, be obtained, then the *Supplier* may disclose that portion of the information which it is required to be disclosed by law and uses reasonable efforts to obtain assurances that confidential treatment will be afforded to the information so disclosed.
- Z5.5 The *Supplier* ensures that all his subcontractors abide by the undertakings in this clause.

Z6 Waiver and estoppel: Add to core clause 12.3:

- Z6.1 Any extension, concession, waiver or relaxation of any action stated in this contract by the Parties, the *Supply Manager* or the *Adjudicator* does not constitute a waiver of rights, and does not give rise to an estoppel unless the Parties agree otherwise and confirm such agreement in writing.

Z8 Provision of a Tax Invoice and interest. Add to core clause 51

- Z8.1 Within one week of receiving a payment certificate from the *Supply Manager* in terms of core clause 51.1, the *Supplier* provides the *Purchaser* with a tax invoice in accordance with the *Purchaser's* procedures stated in the Goods Information, showing the amount due for payment equal to that stated in the payment certificate.
- Z8.2 If the *Supplier* does not provide a tax invoice in the form and by the time required by this contract, the time by when the *Purchaser* is to make a payment is extended by a period equal in time to the delayed submission of the correct tax invoice. Interest due by the *Purchaser* in terms of core clause 51.2 is then calculated from the delayed date by when payment is to be made.
- Z8.3 The *Supplier* (if registered in South Africa in terms of the companies Act) is required to comply with the requirements of the Value Added Tax Act, no 89 of 1991 (as amended) and to include the *Purchaser's* VAT number 4740101508 on each invoice he submits for payment.

Z9 Notifying compensation events

- Z9.1 Delete from the last sentence in core clause 61.3, "unless the *Supply Manager* should have notified the event to the *Supplier* but did not".

Z10 Purchaser's limitation of liability

- Z10.1 The *Purchaser's* liability to the *Supplier* for the *Supplier's* indirect or consequential loss is limited to R0.00 (zero Rand)

Z10.2 The *Supplier's* entitlement under the indemnity in 83.1 is provided for in 60.1(12) and the *Purchaser's* liability under the indemnity is limited.

Z11 Termination: Add to core clause 91.1, at the second main bullet point, fourth sub-bullet point, after the words "against it":

Z11.1 or had a judicial management order granted against it.

Z12 Addition to secondary Option X7 Delay damages (if applicable in this contract)

Z12.1 If the amount due for the *Supplier's* payment of delay damages reaches the limits stated in this Contract Data for Option X7, the *Purchaser* may terminate the *Supplier's* obligation to Provide the Goods and Services using the same procedures and payment on termination as those applied for reasons R1 to R15 or R18 stated in the Termination Table.

Annexure A: Supply Requirements

The Supply Requirements for this contract are as follows:

The Supplier supplies the goods in accordance with INCOTERMS **2010** as follows

Group	Category	Term	Delivery Place
E	Departure	EXW	
F	Main carriage unpaid	FCA, FAS, FOB	
C	Main carriage paid	CFR, CIF, CPT, CIP	
D	Arrival	DAT, DAP, DDP	

The parties obligations described in Incoterms for the category and term selected are now incorporated into this contract as part of the Supply Requirements and hence the Goods Information.

The obligations of the seller and buyer for the selected Incoterm determine each party's costs, risks and insurance requirements incidental to the supply and transport of the goods from *Supplier* to *Purchaser*.

For each of the thirteen terms, Incoterms set out obligations of the Seller (the Supplier) in ten paragraphs identified as A1 to A10 and the corresponding obligations of the buyer (the *Purchaser*) in paragraphs B1 to B10, These obligations covers the following subjects:

The Supply Requirements for this contract are as follows:

1. The requirements for the supply are	Personal Protective Equipment's / Clothing	
2. The requirements for transport are	Delivered and off – loaded at Matimba Power Station Main Stores Receiving	
3. The delivery place is	Matimba Power Station	
4. Actions of the Parties during supply	Action	Party which does it
	Giving notice of Delivery	Supplier

	Checking packing and marking before dispatch	Supplier
	Contracting for transport	Supplier
	Pay costs of transport	Purchaser /Supplier
	Arrange access to delivery place	Purchaser
	Loading the <i>goods</i>	Supplier
	Unloading the <i>goods</i>	Purchaser
For international procurement	Undertake export requirements	Supplier
	Undertake import requirements	Supplier
5. Information to be provided by the Supplier	Title of document	
	Packing lists for cases and their contents	
	Copy of electronic invoice to Finance Shared Services	
	Delivery Note	
	Test results and maintenance manuals were applicable	

Annexure C: The Purchaser's Panel of Adjudicators

The following persons listed in alphabetical order of their surname have indicated their willingness to be included in the *Purchaser's* Panel of Adjudicators. Their CV's may be obtained by using the contact details provided.

Name	Location	Contact details (phone & e mail)
Nigel ANDREWS	Gauteng	+27 11 836-6760 nigela@quoin.net
Andrew BAIRD	Gauteng	+27 11 803 3008 andrewbaird@ecsconsult.co.za
Christopher BINNINGTON	Gauteng	+27 11 888-6141 cdb@bca.co.za
Peter HIGGINS	UK	+44 1293 873 868 peterhiggins@pdconsult.co.uk
Adv. Bruce LEECH	Gauteng	+27 11 290 4000 leech@counsel.co.za
Nigel NILEN	Gauteng	+27 11 465 3601; nilences@global.co.za
Peter THURLOW	Gauteng	+27 11 787 6226 info@thurlowassoc.com

C1.2 Contract Data

Part two - Data provided by the *Supplier*

Clause	Statement	Data
10.1	The <i>Supplier</i> is (Name): Address Tel No. Fax No.	
11.2(8)	The Goods Information for the <i>Supplier's</i> design is in:	Annexure A
11.2(11)	The tendered total of the Prices is	R (in words)
11.2(12)	The <i>price schedule</i> is in:	
11.2(14)	The following matters will be included in the Risk Register	N/A
25.2	The restrictions to access for the <i>Supply Manager</i> and Others to work being done for this contract are	None
30.1	The <i>delivery date</i> of the goods and services is:	Stated in every purchase order
63.2	The <i>percentage for overheads and profit</i> added to the Defined Cost is	N/A

C2.1 pricing assumptions

The *conditions of contract*

How goods and services are priced and assessed for payment

Clause 11 in NEC3 Supply Contract, December 2009 (SC3) core clauses states:

- Identified and defined terms**
- 11
 - 11.2 (11) The Prices are the amounts stated in the price column of the Price Schedule. Where a quantity is stated for an item in the Price Schedule, the Price is calculated by multiplying the quantity by the rate.
 - (12) The Price Schedule is the *price schedule* unless later changed in

accordance with this contract.

Assessing the amount due 50.2

The amount due is

- the Price for each lump sum item in the Price Schedule which the *Supplier* has completed,
- where a quantity is stated for an item in the Price Schedule, an amount calculated by multiplying the quantity which the *Supplier* has completed by the rate,
- plus other amounts to be paid to the *Supplier*,
- less amounts to be paid by or retained from the *Supplier*.

Any tax which the law requires the *Purchaser* to pay to the *Supplier* is included in the amount due.

This confirms that the Supply Contract is a priced contract where the Prices are derived from a list of items of *goods* and *services* which can be priced as lump sums or as expected quantities of *goods* and *services* multiplied by a rate, or a mix of both.

Function of the Price Schedule

Clause 53.1 states: "Information in the Price Schedule is not Goods Information". This confirms that instructions to do work or how it is to be done are not included in the Price Schedule but in the Goods Information. This is further confirmed by Clause 20.1 which states, "The *Supplier* Provides the Goods and Services in accordance with the Goods Information". Hence the *Supplier* does **not** Provide the Goods and Services in accordance with the Price Schedule. The Price Schedule is only a pricing document.

Preparing the *price schedule*

It will be assumed that the tendering supplier has read Pages 11 and 12 and Appendix 5 of the SC3 Guidance Notes before preparing the *price schedule*. Items in the *price schedule* may have been inserted by the *Purchaser* and the tendering supplier should insert any additional items which he considers necessary. Whichever party provides the items in the *price schedule* the total of the Prices is assumed to be fully inclusive of everything necessary to Provide the Goods and Services as described at the time of entering into this contract.

1 As the *Supplier* has an obligation to correct Defects (core clause 43.1) and there is no compensation event for this unless the Defect was due to a *Supplier's* risk, the lump sum Prices and rates must also include for the correction of Defects.

2 If the *Supplier* has decided not to identify a particular item in the *price schedule* at the time of tender the cost to the *Supplier* of doing the work is assumed to be included in, or spread across, the other Prices and rates in the *price schedule* in order to fulfil the obligation to Provide the Goods and Services for the tendered total of the Prices.

3 There is no adjustment to lump sum prices in the *price schedule* if the amount, or quantity, of work within that lump sum item of *goods* or *services* later turns out to be different to that which the *Supplier* estimated at time of tender. The only basis for a change to the Prices is as a result of a compensation event. See Clause 60.1.

4 Hence the Prices and rates tendered by the *Supplier* in the *price schedule* are inclusive of everything necessary and incidental to Providing the Goods and Services in accordance with the Goods Information, as it was at the time of tender, as well as correct any Defects not caused by a *Purchaser's* risk.

5 The *Supplier* does not have to allow in his Prices and rates for matters that may arise as a result of a compensation event. It should be noted that the list of compensation events includes those arising as a result of a *Purchaser's* risk event listed in core clause 80.1.

Format of the *price schedule*

(From Appendix 5 on page 78 of the SC3 Guidance Notes)

Entries in the first four columns in the *price schedule* in section C2.2 are made either by the *Purchaser* or the tendering supplier.

If the *Supplier* is to be paid an amount for the item which is not adjusted if the quantity of work in the item changes, the tendering supplier enters the amount in the Price column only, the Unit, Quantity and Rate columns being left blank.

If the *Supplier* is to be paid an amount for the item which is the rate for the item multiplied by the quantity completed, the tendering *Supplier* enters the rate which is then multiplied by the Quantity to produce the Price, which is also entered.

If the *Supplier* is to be paid an amount for an item proportional to the length of time for which the *goods* and *services* are provided, a unit of time is stated in the Unit column and the length of time (as a quantity of the stated units of time) is stated in the Quantity column.

2 the *price schedule*

Item nr	Material number	Material Description and Texts	UMC	QTY	Unit Price
00010	0642826	COVERALL:ACID RESIST;102;POLYCOTTON	EA	120	
00020	0642827	COVERALL:ACID RESIST;107;POLYCOTTON	EA	80	
00030	0642828	COVERALL:ACID RESIST;112;POLYCOTTON	EA	80	
00040	0642829	COVERALL:ACID RESIST;117;POLYCOTTON	EA	80	
00050	0642830	COVERALL:ACID RESIST;122;POLYCOTTON	EA	60	
00060	0642831	COVERALL:ACID RESIST;127;POLYCOTTON	EA	60	
00070	0642832	COVERALL:ACID RESIST;132;POLYCOTTON	EA	60	
00080	0642833	COVERALL:ACID RESIST;137;POLYCOTTON	EA	60	

00090	0642834	COVERALL:ACID RESIST;142;POLYCOTTON	EA	60	
00100	0642835	COVERALL:ACID RESIST;147;POLYCOTTON	EA	60	
00110	0642836	COVERALL:ACID RESIST;152;POLYCOTTON	EA	60	
00120	0642837	COVERALL:ACID RESIST;157;POLYCOTTON	EA	60	
00130	0642821	COVERALL:ACID RESIST;77;POLYCOTTON	EA	120	
00140	0642822	COVERALL:ACID RESIST;82;POLYCOTTON	EA	120	
00150	0642823	COVERALL:ACID RESIST;87;POLYCOTTON	EA	120	
00160	0642824	COVERALL:ACID RESIST;92;POLYCOTTON	EA	120	
00170	0642825	COVERALL:ACID RESIST;97;POLYCOTTON	EA	120	
00180	0566588	COVERALL:ARTISAN BOILER SUIT;102 CM	EA	360	
00190	0566591	COVERALL:ARTISAN BOILER SUIT;107 CM	EA	240	
00200	0566598	COVERALL:ARTISAN BOILER SUIT;112 CM	EA	120	
00210	0566589	COVERALL:ARTISAN BOILER SUIT;117 CM	EA	360	
00220	0566599	COVERALL:ARTISAN BOILER SUIT;122 CM	EA	120	
00230	0566593	COVERALL:ARTISAN BOILER SUIT;127 CM	EA	60	
00240	0566592	COVERALL:ARTISAN BOILER SUIT;132 CM	EA	60	

00250	0566590	COVERALL:ARTISAN BOILER SUIT;137	EA	60	
00260	0566595	COVERALL:ARTISAN BOILER SUIT;142 CM	EA	60	
00270	0222529	COVERALL:ARTISAN BOILER SUIT;77 CM	EA	120	
00280	0222530	COVERALL:ARTISAN BOILER SUIT;82 CM	EA	120	
00290	0222531	COVERALL:ARTISAN BOILER SUIT;87 CM	EA	120	
00300	0222533	COVERALL:ARTISAN BOILER SUIT;92 CM	EA	180	
00310	0222534	COVERALL:ARTISAN BOILER SUIT;97 CM	EA	120	
00320	0222534	COVERALL:ARTISAN BOILER SUIT;97 CM	EA	320	
00330	0222352	HAT:SOFT BUSH;L; 58;BLUE NAVY	EA	1 000	
00340	0222351	HAT:SOFT BUSH;M; 57;BLUE NAVY	EA	1 000	
00350	0222349	HAT:SOFT BUSH;S; 56;BLUE NAVY	EA	1 000	
00360	0222353	HAT:SOFT BUSH;XL; 59;BLUE NAVY	EA	1 000	
00370	0643003	JACKET OVRL:ACID RESIST;102;POLYCOTTON	EA	380	
00380	0643004	JACKET OVRL:ACID RESIST;107;POLYCOTTON	EA	320	
00390	0643005	JACKET OVRL:ACID RESIST;112;POLYCOTTON	EA	320	
00440	0643006	JACKET OVRL:ACID RESIST;117;POLYCOTTON	EA	80	

00410	0643007	JACKET OVRL:ACID RESIST;122;POLYCOTTON	EA	60	
00420	0643008	JACKET OVRL:ACID RESIST;127;POLYCOTTON	EA	60	
00430	0643009	JACKET OVRL:ACID RESIST;132;POLYCOTTON	EA	60	
00440	0643010	JACKET OVRL:ACID RESIST;137;POLYCOTTON	EA	60	
00450	0643011	JACKET OVRL:ACID RESIST;142;POLYCOTTON	EA	60	
00460	0643012	JACKET OVRL:ACID RESIST;147;POLYCOTTON	EA	60	
00470	0642998	JACKET OVRL:ACID RESIST;77;POLYCOTTON	EA	300	
00480	0642999	JACKET OVRL:ACID RESIST;82;POLYCOTTON	EA	380	
00490	0643000	JACKET OVRL:ACID RESIST;87;POLYCOTTON	EA	380	
00550	0643001	JACKET OVRL:ACID RESIST;92;POLYCOTTON	EA	380	
00510	0643002	JACKET OVRL:ACID RESIST;97;POLYCOTTON	EA	380	
00520	0566494	JACKET UTIL:OPERATING;102 CM	EA	640	
00530	0222537	JACKET UTIL:OPERATING;107 CM	EA	680	
00540	0566503	JACKET UTIL:OPERATING;112 CM	EA	520	
00550	0222538	JACKET UTIL:OPERATING;117 CM	EA	840	
00560	0222539	JACKET UTIL:OPERATING;122 CM	EA	420	

00570	0566511	JACKET UTIL:OPERATING;127 CM	EA	320	
00580	0222540	JACKET UTIL:OPERATING;132 CM	EA	420	
00590	0172193	JACKET UTIL:OPERATING;137 CM	EA	60	
00600	0566512	JACKET UTIL:OPERATING;142 CM	EA	60	
00610	0172192	JACKET UTIL:OPERATING;147 CM	EA	60	
00620	0566513	JACKET UTIL:OPERATING;152 CM	EA	60	
00630	0566481	JACKET UTIL:OPERATING;77 CM	EA	600	
00640	0566482	JACKET UTIL:OPERATING;82 CM	EA	600	
00650	0222535	JACKET UTIL:OPERATING;87 CM	EA	420	
00660	0566544	JACKET UTIL:OPERATING;92 CM	EA	360	
00670	0222536	JACKET UTIL:OPERATING;97 CM	EA	680	
00680	0222559	JACKET UTIL:THERMAL;3XL	EA	180	
00690	0187793	JACKET UTIL:THERMAL;4XL	EA	60	
00700	0186009	JACKET UTIL:THERMAL;5XL	EA	60	
00710	0222555	JACKET UTIL:THERMAL;L; 42; 107	EA	280	
00720	0222553	JACKET UTIL:THERMAL;S; 34; 87	EA	320	

00730	0222556	JACKET UTIL:THERMAL;XL; 46; 117	EA	120	
00740	0222558	JACKET UTIL:THERMAL;XXL; 48; 122	EA	120	
00750	0566739	MASK RSPTR:DISPOSABLE;ADJUSTABLE;WHITE	EA	76 000	
00760	0566738	MASK RSPTR:HALF DISPOSABLE;ADJUSTABLE	EA	76 000	
00770	0566747	MASK RSPTR:HALF FACE;ADJUSTABLE;BLACK	EA	300	
00780	0552823	PROTECTOR HEARNG:FOAM;SNR 37;2112003	EA	4 000	
00790	0222568	RAINWEAR:2 PIECE SUIT;2XL;BLUE NAVY	EA	280	
00800	0222569	RAINWEAR:2 PIECE SUIT;3XL;BLUE NAVY	EA	180	
00810	0565711	RAINWEAR:2 PIECE SUIT;4XL;BLUE NAVY	EA	60	
00820	0222566	RAINWEAR:2 PIECE SUIT;L;BLUE NAVY	EA	180	
00830	0222561	RAINWEAR:2 PIECE SUIT;S;BLUE NAVY	EA	180	
00840	0222561	RAINWEAR:2 PIECE SUIT;S;BLUE NAVY	EA	120	
00850	0222567	RAINWEAR:2 PIECE SUIT;XL;BLUE NAVY	EA	280	
00860	0222405	SHIRT WMAN:LONG;102 CM;GRAY;COTTON	EA	90	
00870	0222406	SHIRT WMAN:LONG;107 CM;GRAY;COTTON	EA	120	
00880	0222407	SHIRT WMAN:LONG;112 CM;GRAY;COTTON	EA	80	

00890	0222402	SHIRT WMAN:LONG;82 CM;GRAY;COTTON	EA	80	
00900	0222404	SHIRT WMAN:LONG;92 CM;GRAY;COTTON	EA	100	
00910	0565829	SHIRT WMAN:LONG;97 CM;GRAY;COTTON	EA	60	
00920	0222419	SHIRT WMAN:SHORT;102 CM;GRAY;COTTON	EA	100	
00930	0222420	SHIRT WMAN:SHORT;107 CM;GRAY;COTTON	EA	60	
00940	0222421	SHIRT WMAN:SHORT;112 CM;GRAY;COTTON	EA	60	
00950	0222422	SHIRT WMAN:SHORT;117 CM;GRAY;COTTON	EA	90	
00960	0222416	SHIRT WMAN:SHORT;82 CM;GRAY;COTTON	EA	140	
00970	0222417	SHIRT WMAN:SHORT;87 CM;GRAY;COTTON	EA	60	
00980	0222418	SHIRT WMAN:SHORT;92 CM;GRAY;COTTON	EA	60	
00990	0565830	SHIRT WMAN:SHORT;97 CM;GRAY;COTTON	EA	60	
01000	0222367	SHIRT:MEN L/SLEEVE;36 CM;COTTON;GRAY	EA	420	
01010	0222370	SHIRT:MEN L/SLEEVE;37 CM;COTTON;GRAY	EA	120	
01020	0222371	SHIRT:MEN L/SLEEVE;38 CM;COTTON;GRAY	EA	80	
01030	0222372	SHIRT:MEN L/SLEEVE;39 CM;COTTON;GRAY	EA	80	
01040	0222374	SHIRT:MEN L/SLEEVE;40 CM;COTTON;GRAY	EA	80	

01050	0222375	SHIRT:MEN L/SLEEVE;41 CM;COTTON;GRAY	EA	80	
01060	0222376	SHIRT:MEN L/SLEEVE;42 CM;COTTON;GRAY	EA	80	
01070	0222377	SHIRT:MEN L/SLEEVE;43 CM;COTTON;GRAY	EA	180	
01080	0222378	SHIRT:MEN L/SLEEVE;44 CM;COTTON;GRAY	EA	80	
01090	0222379	SHIRT:MEN L/SLEEVE;45 CM;COTTON;GRAY	EA	80	
01100	0222380	SHIRT:MEN L/SLEEVE;46 CM;COTTON;GRAY	EA	60	
01110	0222381	SHIRT:MEN L/SLEEVE;47 CM;COTTON;GRAY	EA	120	
01120	0222382	SHIRT:MEN L/SLEEVE;48 CM;COTTON;GRAY	EA	60	
01130	0222383	SHIRT:MEN L/SLEEVE;49 CM;COTTON;GRAY	EA	80	
01140	0222384	SHIRT:MEN S/SLEEVE;36 CM;COTTON;GRAY	EA	460	
01150	0222386	SHIRT:MEN S/SLEEVE;37 CM;COTTON;GRAY	EA	60	
01160	0222387	SHIRT:MEN S/SLEEVE;38 CM;COTTON;GRAY	EA	460	
01170	0222389	SHIRT:MEN S/SLEEVE;39 CM;COTTON;GRAY	EA	160	
01180	0222390	SHIRT:MEN S/SLEEVE;40 CM;COTTON;GRAY	EA	380	
01190	0222391	SHIRT:MEN S/SLEEVE;41 CM;COTTON;GRAY	EA	80	
01200	0222392	SHIRT:MEN S/SLEEVE;42 CM;COTTON;GRAY	EA	160	

01210	0222394	SHIRT:MEN S/SLEEVE;44 CM;COTTON;GRAY	EA	200	
01220	0222395	SHIRT:MEN S/SLEEVE;45 CM;COTTON;GRAY	EA	100	
01230	0222396	SHIRT:MEN S/SLEEVE;46 CM;COTTON;GRAY	EA	260	
01240	0222398	SHIRT:MEN S/SLEEVE;48 CM;COTTON;GRAY	EA	120	
01250	0222399	SHIRT:MEN S/SLEEVE;49 CM;COTTON;GRAY	EA	300	
01260	0565721	SUIT CHEM PRTCTV:2XL;YELLOW;ACID PROOF	EA	60	
01270	0565718	SUIT CHEM PRTCTV:L;YELLOW;ACID PROOF	EA	60	
01280	0565717	SUIT CHEM PRTCTV:M;YELLOW;ACID PROOF	EA	60	
01290	0565716	SUIT CHEM PRTCTV:S;YELLOW;ACID PROOF	EA	60	
01300	0565719	SUIT CHEM PRTCTV:XL;YELLOW;ACID PROOF	EA	60	
01310	0643020	TROUSERS:ACID RESIST;102;GREEN BOTTLE	EA	320	
01320	0643021	TROUSERS:ACID RESIST;107;GREEN BOTTLE	EA	240	
01330	0643022	TROUSERS:ACID RESIST;112;GREEN BOTTLE	EA	240	
01340	0643023	TROUSERS:ACID RESIST;117;GREEN BOTTLE	EA	80	
01350	0643024	TROUSERS:ACID RESIST;122;GREEN BOTTLE	EA	120	
01360	0643025	TROUSERS:ACID RESIST;127;GREEN BOTTLE	EA	120	

01370	0643026	TROUSERS:ACID RESIST;132;GREEN BOTTLE	EA	120	
01380	0643027	TROUSERS:ACID RESIST;137;GREEN BOTTLE	EA	160	
01390	0643028	TROUSERS:ACID RESIST;142;GREEN BOTTLE	EA	60	
01400	0643015	TROUSERS:ACID RESIST;77;GREEN BOTTLE	EA	600	
01410	0643016	TROUSERS:ACID RESIST;82;GREEN BOTTLE	EA	600	
01420	0643017	TROUSERS:ACID RESIST;87;GREEN BOTTLE	EA	600	
01430	0643018	TROUSERS:ACID RESIST;92;GREEN BOTTLE	EA	480	
01440	0643019	TROUSERS:ACID RESIST;97;GREEN BOTTLE	EA	480	
01450	0566680	TROUSERS:CLEAN CONDITION;92 CM;WHITE	EA	120	
01460	0222500	TROUSERS:LADIES LONG;28; 72;BLUE NAVY	EA	60	
01470	0222501	TROUSERS:LADIES LONG;30; 77;BLUE NAVY	EA	180	
01480	0222502	TROUSERS:LADIES LONG;32; 82;BLUE NAVY	EA	120	
01490	0222503	TROUSERS:LADIES LONG;34; 87;BLUE NAVY	EA	420	
01500	0222504	TROUSERS:LADIES LONG;36; 92;BLUE NAVY	EA	380	
01510	0222505	TROUSERS:LADIES LONG;38; 97;BLUE NAVY	EA	120	
01520	0222506	TROUSERS:LADIES LONG;40; 102;BLUE NAVY	EA	120	

01530	0222507	TROUSERS:LADIES LONG;42; 107;BLUE NAVY	EA	120	
01540	0222508	TROUSERS:LADIES LONG;44; 112;BLUE NAVY	EA	120	
01550	0222509	TROUSERS:LADIES LONG;46; 117;BLUE NAVY	EA	120	
01560	0222510	TROUSERS:LADIES LONG;48; 122;BLUE NAVY	EA	120	
01570	0222472	TROUSERS:MEN LONG;102 CM;BLUE NAVY	EA	1 200	
01580	0222473	TROUSERS:MEN LONG;107 CM;BLUE NAVY	EA	980	
01590	0222474	TROUSERS:MEN LONG;112 CM;BLUE NAVY	EA	980	
01600	0222476	TROUSERS:MEN LONG;117 CM;BLUE NAVY	EA	580	
01610	0222477	TROUSERS:MEN LONG;122 CM;BLUE NAVY	EA	340	
01620	0222478	TROUSERS:MEN LONG;127 CM;BLUE NAVY	EA	320	
01630	0222479	TROUSERS:MEN LONG;132 CM;BLUE NAVY	EA	120	
01640	0222480	TROUSERS:MEN LONG;137 CM;BLUE NAVY	EA	120	
01650	0222481	TROUSERS:MEN LONG;142 CM;BLUE NAVY	EA	120	
01670	0222467	TROUSERS:MEN LONG;77 CM;BLUE NAVY	EA	220	
01680	0222468	TROUSERS:MEN LONG;82 CM;BLUE NAVY	EA	1 200	
01690	0222469	TROUSERS:MEN LONG;87 CM;BLUE NAVY	EA	980	

01700	0222470	TROUSERS:MEN LONG;92 CM;BLUE NAVY	EA	980	
01710	0222471	TROUSERS:MEN LONG;97 CM;BLUE NAVY	EA	980	
01720	0565550	VEST HIGH VIS:EMPLOYEE AT WORK;2XL;NYLON	EA	120	
01730	0565551	VEST HIGH VIS:EMPLOYEE AT WORK;3XL;NYLON	EA	120	
01740	0565548	VEST HIGH VIS:EMPLOYEE AT WORK;L;NYLON	EA	120	
01750	0565547	VEST HIGH VIS:EMPLOYEE AT WORK;M;NYLON	EA	120	
01760	0237954	VEST HIGH VIS:EMPLOYEE AT WORK;S;NYLON	EA	320	
01770	0565549	VEST HIGH VIS:EMPLOYEE AT WORK;XL;NYLON	EA	120	
01780	0239867	VEST HIGH VIS:EVACUATION;L;NYLON	EA	120	
01790	0565615	VEST HIGH VIS:FIRE PROTECTION;2XL;NYLON	EA	60	
01800	0565613	VEST HIGH VIS:FIRE PROTECTION;L;NYLON	EA	120	
01810	0565612	VEST HIGH VIS:FIRE PROTECTION;M;NYLON	EA	120	
01820	0565611	VEST HIGH VIS:FIRE PROTECTION;S;NYLON	EA	120	
01830	0565614	VEST HIGH VIS:FIRE PROTECTION;XL;NYLON	EA	80	
01840	0565635	VEST HIGH VIS:FIRST AID;L;NYLON	EA	60	
01850	0565628	VEST HIGH VIS:FIRST AID;M;NYLON	EA	60	

01860	0565627	VEST HIGH VIS:FIRST AID;S;NYLON	EA	60	
-------	---------	---------------------------------	----	----	--

PART 3: SCOPE OF WORK

C3.1: PURCHASER'S GOODS INFORMATION

Specifications of the goods and services

Item No	Material number	Material Description and Texts	UMC
00010	0642826	COVERALL: TYPE: ACID RESIST; SIZE: 102; MATERIAL: POLYCOTTON; COLOUR: BOTTLE GREEN; TO COMPLY WITH ESKOM PPE SPECIFICATION 240-44175132; MATERIAL TO POLY COTTON 65/35 FABRIC	EA
00020	0642827	COVERALL: TYPE: ACID RESIST; SIZE: 107; MATERIAL: POLYCOTTON; COLOUR: BOTTLE GREEN; TO COMPLY WITH ESKOM PPE SPECIFICATION 240-44175132; MATERIAL TO POLY COTTON 65/35 FABRIC	EA
00030	0642828	COVERALL: TYPE: ACID RESIST; SIZE: 112; MATERIAL: POLYCOTTON; COLOUR: BOTTLE GREEN; TO COMPLY WITH ESKOM PPE SPECIFICATION 240-44175132; MATERIAL TO POLY COTTON 65/35 FABRIC	EA

00040	0642829	COVERALL: TYPE: ACID RESIST; SIZE: 117; MATERIAL: POLYCOTTON; COLOUR: BOTTLE GREEN; TO COMPLY WITH ESKOM PPE SPECIFICATION 240-44175132; MATERIAL TO POLY COTTON 65/35 FABRIC	EA
00050	0642830	COVERALL: TYPE: ACID RESIST; SIZE: 122; MATERIAL: POLYCOTTON; COLOUR: BOTTLE GREEN; TO COMPLY WITH ESKOM PPE SPECIFICATION 240-44175132; MATERIAL TO POLY COTTON 65/35 FABRIC	EA
00060	0642831	COVERALL: TYPE: ACID RESIST; SIZE: 127; MATERIAL: POLYCOTTON; COLOUR: BOTTLE GREEN; TO COMPLY WITH ESKOM PPE SPECIFICATION 240-44175132; MATERIAL TO POLY COTTON 65/35 FABRIC	EA
00070	0642832	COVERALL: TYPE: ACID RESIST; SIZE: 132; MATERIAL: POLYCOTTON; COLOUR: BOTTLE GREEN; TO COMPLY WITH ESKOM PPE SPECIFICATION 240-44175132; MATERIAL TO POLY COTTON 65/35 FABRIC	EA
00080	0642833	COVERALL: TYPE: ACID RESIST; SIZE: 137; MATERIAL: POLYCOTTON; COLOUR: BOTTLE GREEN; TO COMPLY WITH ESKOM PPE SPECIFICATION 240-44175132; MATERIAL TO POLY COTTON 65/35 FABRIC	EA
00090	0642834	COVERALL: TYPE: ACID RESIST; SIZE: 142; MATERIAL: POLYCOTTON; COLOUR: BOTTLE GREEN; TO COMPLY WITH ESKOM PPE SPECIFICATION 240-44175132; MATERIAL TO POLY COTTON 65/35 FABRIC	EA
00100	0642835	COVERALL: TYPE: ACID RESIST; SIZE: 147; MATERIAL: POLYCOTTON; COLOUR: BOTTLE GREEN; TO COMPLY WITH ESKOM PPE SPECIFICATION 240-44175132; MATERIAL TO POLY COTTON 65/35 FABRIC	EA
00110	0642836	COVERALL: TYPE: ACID RESIST; SIZE: 152; MATERIAL: POLYCOTTON; COLOUR: BOTTLE GREEN; TO COMPLY WITH ESKOM PPE SPECIFICATION 240-44175132; MATERIAL TO POLY COTTON 65/35 FABRIC	EA
00120	0642837	COVERALL: TYPE: ACID RESIST; SIZE: 157; MATERIAL: POLYCOTTON; COLOUR: BOTTLE GREEN; TO COMPLY WITH ESKOM PPE SPECIFICATION 240-44175132; MATERIAL TO POLY COTTON 65/35 FABRIC	EA
00130	0642821	COVERALL: TYPE: ACID RESIST; SIZE: 77; MATERIAL: POLYCOTTON; COLOUR: BOTTLE GREEN; TO COMPLY WITH ESKOM PPE SPECIFICATION 240-44175132; MATERIAL TO POLY COTTON 65/35 FABRIC	EA
00140	0642822	COVERALL: TYPE: ACID RESIST; SIZE: 82; MATERIAL: POLYCOTTON; COLOUR: BOTTLE GREEN; TO COMPLY WITH ESKOM PPE SPECIFICATION 240-44175132; MATERIAL TO POLY COTTON 65/35 FABRIC	EA
00150	0642823	COVERALL: TYPE: ACID RESIST; SIZE: 87; MATERIAL: POLYCOTTON; COLOUR: BOTTLE GREEN; TO COMPLY WITH ESKOM PPE SPECIFICATION 240-44175132; MATERIAL TO POLY COTTON 65/35 FABRIC	EA
00160	0642824	COVERALL: TYPE: ACID RESIST; SIZE: 92; MATERIAL: POLYCOTTON; COLOUR: BOTTLE GREEN; TO COMPLY WITH ESKOM PPE SPECIFICATION 240-44175132; MATERIAL TO POLY COTTON 65/35 FABRIC	EA
00170	0642825	COVERALL: TYPE: ACID RESIST; SIZE: 97; MATERIAL: POLYCOTTON; COLOUR: BOTTLE GREEN; TO COMPLY WITH ESKOM PPE SPECIFICATION 240-44175132; MATERIAL TO POLY COTTON 65/35 FABRIC	EA
00180	0566588	COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 102 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE	EA

		<p>JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>	
00190	0566591	<p>COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 107 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED</p>	EA

		<p>WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>	
00200	0566598	<p>COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 112 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO</p>	EA

		<p>ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>	
<p>00210</p>	<p>0566589</p>	<p>COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 117 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A</p>	<p>EA</p>

		<p>FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>	
00220	0566599	<p>COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 122 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE</p>	EA

		<p>POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>	
<p>00230</p>	<p>0566593</p>	<p>COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 127 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A</p>	<p>EA</p>

		<p>SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>	
00240	0566592	<p>COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 132 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING</p>	EA

		<p>FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>	
<p>00250</p>	<p>0566590</p>	<p>COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 137; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM</p>	<p>EA</p>

		<p>ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>	
<p>00260</p>	<p>0566595</p>	<p>COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 142 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE</p>	<p>EA</p>

		STITCHED DOWN OF WIDTH AT LEAST 10 MM	
00270	0222529	<p>COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 77 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>	EA

00280	0222530	<p>COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 82 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>	EA
00290	0222531	<p>COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 87 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM</p>	EA

		<p>TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>	
00300	0222533	<p>COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 92 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT</p>	EA

		<p>BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>	
00310	0222534	<p>COVERALL: TYPE: ARTISAN BOILER SUIT; SIZE: 97 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON;</p>	EA

		<p>POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM</p>	
00320	0222352	<p>HAT: TYPE: SOFT BUSH; SIZE: L; 58; COLOR: BLUE NAVY; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, WOVEN PRE SHRUNK; THE ESKOM LOGO SHALL BE EMBROIDERED ON THE FRONT OF THE HAT AND THE ZERO HARM IDENTIFICATION SHALL BE EMBROIDERED ON THE REAR OF THE HAT AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; SOFT HATS SHALL HAVE A REINFORCED STIFFENED BROAD BRIM OF AT LEAST 80 MM; STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD SHALL COMPLY WITH SANS 1362; ALL GARMENTS MUST BEAR THE S.A.B.S. MARK OF APPROVAL; FULL WASHING INSTRUCTIONS; SIZE AND TRACEABILITY SHALL BE MARKED WITH SANS 432 INDELIBLE MARKING INK FOR TEXTILE FABRICS ON HAT; UNIQUE IDENTIFIER 240-44175132</p>	EA
00330	0222351	<p>HAT: TYPE: SOFT BUSH; SIZE: M; 57; COLOR: BLUE NAVY; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, WOVEN PRE SHRUNK; THE ESKOM LOGO SHALL BE EMBROIDERED ON THE FRONT OF THE HAT AND THE ZERO HARM IDENTIFICATION SHALL BE EMBROIDERED ON THE REAR OF THE HAT AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; SOFT HATS SHALL HAVE A REINFORCED STIFFENED BROAD BRIM OF AT LEAST 80 MM; STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD SHALL COMPLY WITH SANS 1362; ALL GARMENTS MUST BEAR THE S.A.B.S. MARK OF APPROVAL; FULL WASHING INSTRUCTIONS; SIZE AND TRACEABILITY SHALL BE MARKED WITH SANS 432 INDELIBLE MARKING INK FOR TEXTILE FABRICS ON HAT; UNIQUE IDENTIFIER 240-</p>	EA

		44175132	
00340	0222349	HAT: TYPE: SOFT BUSH; SIZE: S; 56; COLOR: BLUE NAVY; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, WOVEN PRE SHRUNK; THE ESKOM LOGO SHALL BE EMBROIDERED ON THE FRONT OF THE HAT AND THE ZERO HARM IDENTIFICATION SHALL BE EMBROIDERED ON THE REAR OF THE HAT AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; SOFT HATS SHALL HAVE A REINFORCED STIFFENED BROAD BRIM OF AT LEAST 80 MM; STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD SHALL COMPLY WITH SANS 1362; ALL GARMENTS MUST BEAR THE S.A.B.S. MARK OF APPROVAL; FULL WASHING INSTRUCTIONS; SIZE AND TRACEABILITY SHALL BE MARKED WITH SANS 432 INDELIBLE MARKING INK FOR TEXTILE FABRICS ON HAT; UNIQUE IDENTIFIER 240-44175132	EA
00350	0222353	HAT: TYPE: SOFT BUSH; SIZE: XL; 59; COLOR: BLUE NAVY; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, WOVEN PRE SHRUNK; THE ESKOM LOGO SHALL BE EMBROIDERED ON THE FRONT OF THE HAT AND THE ZERO HARM IDENTIFICATION SHALL BE EMBROIDERED ON THE REAR OF THE HAT AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; SOFT HATS SHALL HAVE A REINFORCED STIFFENED BROAD BRIM OF AT LEAST 80 MM; STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD SHALL COMPLY WITH SANS 1362; ALL GARMENTS MUST BEAR THE S.A.B.S. MARK OF APPROVAL; FULL WASHING INSTRUCTIONS; SIZE AND TRACEABILITY SHALL BE MARKED WITH SANS 432 INDELIBLE MARKING INK FOR TEXTILE FABRICS ON HAT; UNIQUE IDENTIFIER 240-44175132	EA
00360	0643003	JACKET, OVERALL: TYPE: ACID RESIST; SIZE: 102; MATERIAL: POLYCOTTON; COLOR: GREEN BOTTLE; COMPLY WITH ESKOM PPE SPECIFICATION; MATERIAL TO BE POLY COTTON FABRIC (65/35)	EA
00370	0643004	JACKET, OVERALL: TYPE: ACID RESIST; SIZE: 107; MATERIAL: POLYCOTTON; COLOR: GREEN BOTTLE; COMPLY WITH ESKOM PPE SPECIFICATION; MATERIAL TO BE POLY COTTON FABRIC (65/35)	EA
00380	0643005	JACKET, OVERALL: TYPE: ACID RESIST; SIZE: 112; MATERIAL: POLYCOTTON; COLOR: GREEN BOTTLE; COMPLY WITH ESKOM PPE SPECIFICATION; MATERIAL TO BE POLY COTTON FABRIC (65/35)	EA
00390	0643006	JACKET, OVERALL: TYPE: ACID RESIST; SIZE: 117; MATERIAL: POLYCOTTON; COLOR: GREEN BOTTLE; COMPLY WITH ESKOM PPE SPECIFICATION; MATERIAL TO BE POLY COTTON FABRIC (65/35)	EA
00440	0643007	JACKET, OVERALL: TYPE: ACID RESIST; SIZE: 122; MATERIAL: POLYCOTTON; COLOR: GREEN BOTTLE; COMPLY WITH ESKOM PPE SPECIFICATION; MATERIAL TO BE POLY COTTON FABRIC (65/35)	EA
00410	0643008	JACKET, OVERALL: TYPE: ACID RESIST; SIZE: 127; MATERIAL: POLYCOTTON; COLOR: GREEN BOTTLE; COMPLY WITH ESKOM PPE SPECIFICATION; MATERIAL TO BE POLY COTTON FABRIC (65/35)	EA
00420	0643009	JACKET, OVERALL: TYPE: ACID RESIST; SIZE: 132; MATERIAL: POLYCOTTON; COLOR: GREEN BOTTLE; COMPLY WITH ESKOM PPE SPECIFICATION; MATERIAL TO BE POLY COTTON FABRIC (65/35)	EA

00430	0643010	JACKET, OVERALL: TYPE: ACID RESIST; SIZE: 137; MATERIAL: POLYCOTTON; COLOR: GREEN BOTTLE; COMPLY WITH ESKOM PPE SPECIFICATION; MATERIAL TO BE POLY COTTON FABRIC (65/35)	EA
00440	0643011	JACKET, OVERALL: TYPE: ACID RESIST; SIZE: 142; MATERIAL: POLYCOTTON; COLOR: GREEN BOTTLE; COMPLY WITH ESKOM PPE SPECIFICATION; MATERIAL TO BE POLY COTTON FABRIC (65/35)	EA
00450	0643012	JACKET, OVERALL: TYPE: ACID RESIST; SIZE: 147; MATERIAL: POLYCOTTON; COLOR: GREEN BOTTLE; COMPLY WITH ESKOM PPE SPECIFICATION; MATERIAL TO BE POLY COTTON FABRIC (65/35)	EA
00460	0642998	JACKET, OVERALL: TYPE: ACID RESIST; SIZE: 77; MATERIAL: POLYCOTTON; COLOR: GREEN BOTTLE; COMPLY WITH ESKOM PPE SPECIFICATION; MATERIAL TO BE POLY COTTON FABRIC (65/35)	EA
00470	0642999	JACKET, OVERALL: TYPE: ACID RESIST; SIZE: 82; MATERIAL: POLYCOTTON; COLOR: GREEN BOTTLE; COMPLY WITH ESKOM PPE SPECIFICATION; MATERIAL TO BE POLY COTTON FABRIC (65/35)	EA
00480	0643000	JACKET, OVERALL: TYPE: ACID RESIST; SIZE: 87; MATERIAL: POLYCOTTON; COLOR: GREEN BOTTLE; COMPLY WITH ESKOM PPE SPECIFICATION; MATERIAL TO BE POLY COTTON FABRIC (65/35)	EA
00490	0643001	JACKET, OVERALL: TYPE: ACID RESIST; SIZE: 92; MATERIAL: POLYCOTTON; COLOR: GREEN BOTTLE; COMPLY WITH ESKOM PPE SPECIFICATION; MATERIAL TO BE POLY COTTON FABRIC (65/35)	EA
00550	0643002	JACKET, OVERALL: TYPE: ACID RESIST; SIZE: 97; MATERIAL: POLYCOTTON; COLOR: GREEN BOTTLE; COMPLY WITH ESKOM PPE SPECIFICATION; MATERIAL TO BE POLY COTTON FABRIC (65/35)	EA
00510	0566494	JACKET, UTILITY: TYPE: OPERATING; SIZE: 102 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH	EA

		AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM	
00520	0222537	JACKET, UTILITY: TYPE: OPERATING; SIZE: 107 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM	EA
00530	0566503	JACKET, UTILITY: TYPE: OPERATING; SIZE: 112 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF	EA

		<p>STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM</p>	
00540	0222538	<p>JACKET, UTILITY: TYPE: OPERATING; SIZE: 117 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM</p>	EA
00550	0222539	<p>JACKET, UTILITY: TYPE: OPERATING; SIZE: 122 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822;</p>	EA

		<p>SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM</p>	
00560	0566511	<p>JACKET, UTILITY: TYPE: OPERATING; SIZE: 127 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH</p>	EA

		AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM	
00570	0222540	JACKET, UTILITY: TYPE: OPERATING; SIZE: 132 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM	EA
00580	0172193	JACKET, UTILITY: TYPE: OPERATING; SIZE: 137 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF	EA

		STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM	
00590	0566512	JACKET, UTILITY: TYPE: OPERATING; SIZE: 142 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM	EA
00600	0172192	JACKET, UTILITY: TYPE: OPERATING; SIZE: 147 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822;	EA

		<p>SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM</p>	
<p>00610</p>	<p>0566513</p>	<p>JACKET, UTILITY: TYPE: OPERATING; SIZE: 152 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH</p>	<p>EA</p>

		AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM	
00620	0566481	JACKET, UTILITY: TYPE: OPERATING; SIZE: 77 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM	EA
00630	0566482	JACKET, UTILITY: TYPE: OPERATING; SIZE: 82 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING	EA

		ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM	
00640	0222535	JACKET, UTILITY: TYPE: OPERATING; SIZE: 87 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM	EA
00650	0566544	JACKET, UTILITY: TYPE: OPERATING; SIZE: 92 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE	EA

		<p>IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM</p>	
00660	0222536	<p>JACKET, UTILITY: TYPE: OPERATING; SIZE: 97 CM; MATERIAL: COTTON 100 PCT, SANS 1387-4 D59, SOFT WOVEN PRE SHRUNK, FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: (1) CHEST, (2) SIDE; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH</p>	EA

		AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM	
00670	0222559	JACKET, UTILITY: TYPE: THERMAL; SIZE: 3XL; MATERIAL: COTTON, D59, FLAME RETARDANT; COLOR: BLUE PANTO 19-3920; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INSULATED WITH PRE-SHRUNK HOLLOW FIBRE OR A NON-FLAMMABLE MATERIAL; WITH THE OUTER COVERING MADE OF PRE-SHRUNK 100 % WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; JACKET LENGTH TO REACH BELOW THE BUTTOCKS; POCKETS ONE CHEST POCKET SHALL BE BELLOWS TYPE - 15CM DEEP AND 14CM WIDE; 4 SIDE POCKETS; POCKETS TO HAVE FLAPS WITH CUT-OFF EDGES THAT CAN BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; THE SIDE POCKET SHALL BE THE BELLOWS TYPE WITH A SIDE ENTRY INTO ANOTHER SEPARATE POCKET AND SHALL BE 22CM DEEP AND 21CM WIDE; JACKETS SHALL HAVE NON-CONDUCTIVE PRESS STUDS DOWN THE FRONT ON A DOUBLE PANEL STRIP AS WELL AS A NON-CONDUCTIVE ZIP; THE SLEEVE CUFFS SHALL HAVE TWO NON-CONDUCTIVE PRESS STUDS AT THE END OF THE SLEEVE SO THAT THE SIZE CAN BE ADJUSTED; IDENTIFICATION: INDELIBLE MNFRS TRADEMARK REF NO. AND CLEANING INSTRUCTIONS INSIDE COLLAR ON JACKETS AND SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS; REFER TO UNIQUE IDENTIFIER 240-44175132	EA
00680	0187793	JACKET, UTILITY: TYPE: THERMAL; SIZE: 4XL; MATERIAL: COTTON, D59, FLAME RETARDANT; COLOR: BLUE PANTO 19-3920; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INSULATED WITH PRE-SHRUNK HOLLOW FIBRE OR A NON-FLAMMABLE MATERIAL; WITH THE OUTER COVERING MADE OF PRE-SHRUNK 100 % WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; JACKET LENGTH TO REACH BELOW THE BUTTOCKS; POCKETS ONE CHEST POCKET SHALL BE BELLOWS TYPE - 15CM DEEP AND 14CM WIDE; 4 SIDE POCKETS; POCKETS TO HAVE FLAPS WITH CUT-OFF EDGES THAT CAN BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; THE SIDE POCKET SHALL BE THE BELLOWS TYPE WITH A SIDE ENTRY INTO ANOTHER SEPARATE POCKET AND SHALL BE 22CM DEEP AND 21CM WIDE; JACKETS SHALL HAVE NON-CONDUCTIVE PRESS STUDS DOWN THE FRONT ON A DOUBLE PANEL STRIP AS WELL AS A NON-CONDUCTIVE ZIP; THE SLEEVE CUFFS SHALL HAVE TWO NON-CONDUCTIVE PRESS STUDS AT THE END OF THE SLEEVE SO THAT THE SIZE CAN BE ADJUSTED; IDENTIFICATION: INDELIBLE MNFRS TRADEMARK REF NO. AND CLEANING INSTRUCTIONS INSIDE COLLAR ON JACKETS AND SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS; REFER TO UNIQUE IDENTIFIER 240-44175132	EA
00690	0186009	JACKET, UTILITY: TYPE: THERMAL; SIZE: 5XL; MATERIAL: COTTON, D59, FLAME RETARDANT; COLOR: BLUE PANTO 19-3920; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INSULATED WITH PRE-SHRUNK HOLLOW FIBRE OR A NON-FLAMMABLE MATERIAL; WITH THE OUTER COVERING MADE OF PRE-SHRUNK 100 % WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; JACKET LENGTH TO REACH BELOW THE BUTTOCKS; POCKETS ONE CHEST POCKET SHALL BE BELLOWS TYPE - 15CM DEEP AND 14CM WIDE; 4 SIDE POCKETS; POCKETS TO HAVE FLAPS WITH CUT-OFF EDGES THAT CAN BE FASTENED BY MEANS OF NON-CONDUCTIVE	EA

		BUTTONS; THE SIDE POCKET SHALL BE THE BELLOWS TYPE WITH A SIDE ENTRY INTO ANOTHER SEPARATE POCKET AND SHALL BE 22CM DEEP AND 21CM WIDE; JACKETS SHALL HAVE NON-CONDUCTIVE PRESS STUDS DOWN THE FRONT ON A DOUBLE PANEL STRIP AS WELL AS A NON-CONDUCTIVE ZIP; THE SLEEVE CUFFS SHALL HAVE TWO NON-CONDUCTIVE PRESS STUDS AT THE END OF THE SLEEVE SO THAT THE SIZE CAN BE ADJUSTED; IDENTIFICATION: INDELIBLE MNFRS TRADEMARK REF NO. AND CLEANING INSTRUCTIONS INSIDE COLLAR ON JACKETS AND SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS; REFER TO UNIQUE IDENTIFIER 240-44175132	
00700	0222555	JACKET, UTILITY: TYPE: THERMAL; SIZE: L; 42; 107; MATERIAL: COTTON, D59, FLAME RETARDANT; COLOR: BLUE PANTO 19-3920; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INSULATED WITH PRE-SHRUNK HOLLOW FIBRE OR A NON-FLAMMABLE MATERIAL; WITH THE OUTER COVERING MADE OF PRE-SHRUNK 100 % WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; JACKET LENGTH TO REACH BELOW THE BUTTOCKS; POCKETS ONE CHEST POCKET SHALL BE BELLOWS TYPE - 15CM DEEP AND 14CM WIDE; 4 SIDE POCKETS; POCKETS TO HAVE FLAPS WITH CUT-OFF EDGES THAT CAN BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; THE SIDE POCKET SHALL BE THE BELLOWS TYPE WITH A SIDE ENTRY INTO ANOTHER SEPARATE POCKET AND SHALL BE 22CM DEEP AND 21CM WIDE; JACKETS SHALL HAVE NON-CONDUCTIVE PRESS STUDS DOWN THE FRONT ON A DOUBLE PANEL STRIP AS WELL AS A NON-CONDUCTIVE ZIP; THE SLEEVE CUFFS SHALL HAVE TWO NON-CONDUCTIVE PRESS STUDS AT THE END OF THE SLEEVE SO THAT THE SIZE CAN BE ADJUSTED; IDENTIFICATION: INDELIBLE MNFRS TRADEMARK REF NO. AND CLEANING INSTRUCTIONS INSIDE COLLAR ON JACKETS AND SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS; REFER TO UNIQUE IDENTIFIER 240-44175132	EA
00710	0222553	JACKET, UTILITY: TYPE: THERMAL; SIZE: S; 34; 87; MATERIAL: COTTON, D59, FLAME RETARDANT; COLOR: BLUE PANTO 19-3920; INSULATED WITH PRE-SHRUNK HOLLOW FIBRE OR A NON-FLAMMABLE MATERIAL; WITH THE OUTER COVERING MADE OF PRE-SHRUNK 100 PCT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; JACKET LENGTH: TO REACH BELOW THE BUTTOCKS; POCKETS: ONE CHEST POCKET SHALL BE BELLOWS TYPE - 15CM DEEP AND 14CM WIDE; 4 SIDE POCKETS; POCKETS TO HAVE FLAPS WITH CUT-OFF EDGES THAT CAN BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; THE SIDE POCKET SHALL BE THE BELLOWS TYPE WITH A SIDE ENTRY INTO ANOTHER SEPARATE POCKET AND SHALL BE 22CM DEEP AND 21CM WIDE; JACKETS SHALL HAVE NON-CONDUCTIVE PRESS STUDS DOWN THE FRONT ON A DOUBLE PANEL STRIP; AS WELL AS A NON-CONDUCTIVE ZIP; THE SLEEVE CUFFS SHALL HAVE TWO NON-CONDUCTIVE PRESS STUDS AT THE END OF THE SLEEVE SO THAT THE SIZE CAN BE ADJUSTED; IDENTIFICATION: INDELIBLE MNFRS TRADEMARK; REF NO. AND CLEANING INSTRUCTIONS INSIDE COLLAR ON JACKETS AND SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS; REFER TO UNIQUE IDENTIFIER 240-44175132	EA
00720	0222556	JACKET, UTILITY: TYPE: THERMAL; SIZE: XL; 46; 117; MATERIAL: COTTON, D59, FLAME RETARDANT; COLOR: BLUE PANTO 19-3920; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INSULATED WITH PRE-SHRUNK HOLLOW FIBRE OR A NON-FLAMMABLE MATERIAL; WITH THE OUTER COVERING MADE OF PRE-SHRUNK 100 % WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; JACKET LENGTH TO REACH BELOW THE BUTTOCKS; POCKETS ONE CHEST POCKET SHALL BE BELLOWS TYPE - 15CM DEEP	EA

		AND 14CM WIDE; 4 SIDE POCKETS; POCKETS TO HAVE FLAPS WITH CUT-OFF EDGES THAT CAN BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; THE SIDE POCKET SHALL BE THE BELLOWS TYPE WITH A SIDE ENTRY INTO ANOTHER SEPARATE POCKET AND SHALL BE 22CM DEEP AND 21CM WIDE; JACKETS SHALL HAVE NON-CONDUCTIVE PRESS STUDS DOWN THE FRONT ON A DOUBLE PANEL STRIP AS WELL AS A NON-CONDUCTIVE ZIP; THE SLEEVE CUFFS SHALL HAVE TWO NON-CONDUCTIVE PRESS STUDS AT THE END OF THE SLEEVE SO THAT THE SIZE CAN BE ADJUSTED; IDENTIFICATION: INDELIBLE MNFRS TRADEMARK REF NO. AND CLEANING INSTRUCTIONS INSIDE COLLAR ON JACKETS AND SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS; REFER TO UNIQUE IDENTIFIER 240-44175132	
00730	0222558	JACKET, UTILITY: TYPE: THERMAL; SIZE: XXL; 48; 122; MATERIAL: COTTON, D59, FLAME RETARDANT; COLOR: BLUE PANTO 19-3920; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INSULATED WITH PRE-SHRUNK HOLLOW FIBRE OR A NON-FLAMMABLE MATERIAL; WITH THE OUTER COVERING MADE OF PRE-SHRUNK 100 % WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; JACKET LENGTH TO REACH BELOW THE BUTTOCKS; POCKETS ONE CHEST POCKET SHALL BE BELLOWS TYPE - 15CM DEEP AND 14CM WIDE; 4 SIDE POCKETS; POCKETS TO HAVE FLAPS WITH CUT-OFF EDGES THAT CAN BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; THE SIDE POCKET SHALL BE THE BELLOWS TYPE WITH A SIDE ENTRY INTO ANOTHER SEPARATE POCKET AND SHALL BE 22CM DEEP AND 21CM WIDE; JACKETS SHALL HAVE NON-CONDUCTIVE PRESS STUDS DOWN THE FRONT ON A DOUBLE PANEL STRIP AS WELL AS A NON-CONDUCTIVE ZIP; THE SLEEVE CUFFS SHALL HAVE TWO NON-CONDUCTIVE PRESS STUDS AT THE END OF THE SLEEVE SO THAT THE SIZE CAN BE ADJUSTED; IDENTIFICATION: INDELIBLE MNFRS TRADEMARK REF NO. AND CLEANING INSTRUCTIONS INSIDE COLLAR ON JACKETS AND SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS; REFER TO UNIQUE IDENTIFIER 240-44175132	EA
00740	0566739	MASK, RESPIRATOR: DESIGN FORM: DISPOSABLE; USAGE DESIGN: DUST/MIST/BIO AGENTS; SIZE: ADJUSTABLE; COLOR: WHITE; MANUF P/N: FFP2N/V; DISPOSABLE PARTICULATE MASK WITHOUT VALVE FOR PROTECTION AGAINST SOLID AND NON-VOLATILE LIQUID PARTICLES ONLY; EN 149:2001+A1 2009 FFP2 NR D CE 0086; PROTECTION FACTOR 10 X WEL MATERIAL THAT HAS LOW BREATHING RESISTANCE WITH EFFECTIVE PROTECTION AGAINST: SUB-MICRON PARTICLES; FINE DUSTS NON-VOLATILE LIQUID MISTS AND BIOLOGICAL AGENTS; UNIQUE IDENTIFIER 240-44175132	EA
00750	0566738	MASK, RESPIRATOR: DESIGN FORM: HALF DISPOSABLE; USAGE DESIGN: DUST/MIST/BIO AGENTS; SIZE: ADJUSTABLE; COLOR: WHITE; MANUF P/N: 5261FFP2 NR D; REFERENCE NO: 1005600; DISPOSABLE PARTICULATE MASK WITH VALVE FOR PROTECTION AGAINST SOLID AND NON-VOLATILE LIQUID PARTICLES ONLY; EN 149:2001+A1 2009 FFP2 NR D CE 0086; PROTECTION FACTOR 10 X WEL MATERIAL THAT HAS LOW BREATHING RESISTANCE WITH EFFECTIVE PROTECTION AGAINST: SUB-MICRON PARTICLES; FINE DUSTS; NON-VOLATILE LIQUID MISTS AND BIOLOGICAL AGENTS; UNIQUE IDENTIFIER 240-44175132	EA
00760	0566747	MASK, RESPIRATOR: DESIGN FORM: HALF FACE; USAGE DESIGN: DUST; ORGANIC VAPOURS; ACID; GASES; SIZE: ADJUSTABLE; COLOR: BLACK; RESPIRATORY PROTECTIVE DEVICE ACCESSORY; DOUBLE HALF MASK CARTRIDGE AND PARTICULATE FILTER COMBINATION; SANS 50140; BS EN 14387:2004+A1:2008; SANS 50143; MSA FILTER TYPE: A - COLOUR BROWN; ORGANIC GASES AND VAPOURS; INORGANIC GASES TYPE B -	EA

		SILVERY/GREY; TYPE K - GREEN AMMONIA; DUST; TYPE E - COLOUR YELLOW SULFUR DIOXIDE AND HYDROGEN CHLORIDE; UNIQUE IDENTIFIER 240-44175132	
00770	0552823	PROTECTOR, HEARING: TYPE: X-FIT DISPOSABLE EARPLUG; MATERIAL: FOAM; NOISE REDUCTION RATING: SNR 37; REFERENCE NO: 2112003; FOR HIGH ATTENUATION LEVEL; ONE PACK =200 EARPLUGS	EA
00780	0222568	RAINWEAR: TYPE: 2 PIECE SUIT; SIZE: 2XL; MATERIAL: POLYESTER 100 PCT PLAIN WEAVE, 180 GM/2 MIN; COLOR: BLUE NAVY; MATERIAL: MINIMUM 180 GRAMS PER M/3 FACE SIDE 100% POLYESTER; PLAIN WEAVE WITH 170 THREADS PER M/3 INCH WITH WATER RESISTANT COATING; UNDER SIDE LAMINATED WITH PVC COATING; SEAMS STRENGTH 50KPA; CONVERTS TO 50KNM/2; LINING 80% POLYESTER 20% COTTON; SIZE TO SANS 434 SIZE CHART ANNEX E FOR RAIN WEAR; JACKET SHALL HAVE A NYLON SPIRAL ZIP WITH CLOSED FLY FRONT SECURED BY NON-CONDUCTIVE PRESS-STUDS; COMPLY WITH SANS 1822 TYPE 5; HOOD ATTACHED TO THE JACKET; JACKET TO COVER THE BUTTOCKS; FALSE ELASTIC SLEEVE AT THE END MADE OF SOFTER MATERIAL; PANTS SHALL HAVE SIDE SLITS AND ELASTIC WAIST; REFLECTIVE STRIPS TO BE FITTED ON BOTH SLEEVES ON THE UPPER ARM, AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SIDE OF THE SLEEVE AND THE ESKOM LOGO SHALL BE SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON THE FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; UNIQUE IDENTIFIER 240-44175132	EA
00790	0222569	RAINWEAR: TYPE: 2 PIECE SUIT; SIZE: 3XL; MATERIAL: POLYESTER 100 PCT PLAIN WEAVE, 180 GM/2 MIN; COLOR: BLUE NAVY; MATERIAL: MINIMUM 180 GRAMS PER M/3 FACE SIDE 100% POLYESTER; PLAIN WEAVE WITH 170 THREADS PER M/3 INCH WITH WATER RESISTANT COATING; UNDER SIDE LAMINATED WITH PVC COATING; SEAMS STRENGTH 50KPA; CONVERTS TO 50KNM/2; LINING 80% POLYESTER 20% COTTON; SIZE TO SANS 434 SIZE CHART ANNEX E FOR RAIN WEAR; JACKET SHALL HAVE A NYLON SPIRAL ZIP WITH CLOSED FLY FRONT SECURED BY NON-CONDUCTIVE PRESS-STUDS; COMPLY WITH SANS 1822 TYPE 5; HOOD ATTACHED TO THE JACKET; JACKET TO COVER THE BUTTOCKS; FALSE ELASTIC SLEEVE AT THE END MADE OF SOFTER MATERIAL; PANTS SHALL HAVE SIDE SLITS AND ELASTIC WAIST; REFLECTIVE STRIPS TO BE FITTED ON BOTH SLEEVES ON THE UPPER ARM, AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SIDE OF THE SLEEVE AND THE ESKOM LOGO SHALL BE SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON THE FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; UNIQUE IDENTIFIER 240-44175132	EA
00800	0565711	RAINWEAR: TYPE: 2 PIECE SUIT; SIZE: 4XL; MATERIAL: POLYESTER 100 PCT PLAIN WEAVE, 180 GM/2 MIN; COLOR: BLUE NAVY; MATERIAL: MINIMUM 180 GRAMS PER M/3 FACE SIDE 100% POLYESTER; PLAIN WEAVE WITH 170 THREADS PER M/3 INCH WITH WATER RESISTANT COATING; UNDER SIDE LAMINATED WITH PVC COATING; SEAMS STRENGTH 50KPA; CONVERTS TO 50KNM/2; LINING 80% POLYESTER 20% COTTON; SIZE TO SANS 434 SIZE CHART ANNEX E FOR RAIN WEAR; JACKET SHALL HAVE A NYLON SPIRAL ZIP WITH CLOSED FLY FRONT SECURED BY NON-CONDUCTIVE PRESS-STUDS; COMPLY WITH SANS 1822 TYPE 5; HOOD ATTACHED TO THE JACKET; JACKET TO COVER THE BUTTOCKS; FALSE ELASTIC SLEEVE AT THE END MADE OF SOFTER MATERIAL; PANTS SHALL HAVE SIDE SLITS AND ELASTIC WAIST;	EA

		REFLECTIVE STRIPS TO BE FITTED ON BOTH SLEEVES ON THE UPPER ARM, AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SIDE OF THE SLEEVE AND THE ESKOM LOGO SHALL BE SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON THE FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; UNIQUE IDENTIFIER 240-44175132	
00810	0222566	RAINWEAR: TYPE: 2 PIECE SUIT; SIZE: L; MATERIAL: POLYESTER 100 PCT PLAIN WEAVE, 180 GM/2 MIN; COLOR: BLUE NAVY; MATERIAL: MINIMUM 180 GRAMS PER M/3 FACE SIDE 100% POLYESTER; PLAIN WEAVE WITH 170 THREADS PER M/3 INCH WITH WATER RESISTANT COATING; UNDER SIDE LAMINATED WITH PVC COATING; SEAMS STRENGTH 50KPA; CONVERTS TO 50KNM/2; LINING 80% POLYESTER 20% COTTON; SIZE TO SANS 434 SIZE CHART ANNEX E FOR RAIN WEAR; JACKET SHALL HAVE A NYLON SPIRAL ZIP WITH CLOSED FLY FRONT SECURED BY NON-CONDUCTIVE PRESS-STUDS; COMPLY WITH SANS 1822 TYPE 5; HOOD ATTACHED TO THE JACKET; JACKET TO COVER THE BUTTOCKS; FALSE ELASTIC SLEEVE AT THE END MADE OF SOFTER MATERIAL; PANTS SHALL HAVE SIDE SLITS AND ELASTIC WAIST; REFLECTIVE STRIPS TO BE FITTED ON BOTH SLEEVES ON THE UPPER ARM, AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SIDE OF THE SLEEVE AND THE ESKOM LOGO SHALL BE SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON THE FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; UNIQUE IDENTIFIER 240-44175132	EA
00820	0222561	RAINWEAR: TYPE: 2 PIECE SUIT; SIZE: S; MATERIAL: POLYESTER 100 PCT PLAIN WEAVE, 180 GM/2 MIN; COLOR: BLUE NAVY; MATERIAL: MINIMUM 180 GRAMS PER M/3 FACE SIDE 100% POLYESTER; PLAIN WEAVE WITH 170 THREADS PER M/3 INCH WITH WATER RESISTANT COATING; UNDER SIDE LAMINATED WITH PVC COATING; SEAMS STRENGTH 50KPA; CONVERTS TO 50KNM/2; LINING 80% POLYESTER 20% COTTON; SIZE TO SANS 434 SIZE CHART ANNEX E FOR RAIN WEAR; JACKET SHALL HAVE A NYLON SPIRAL ZIP WITH CLOSED FLY FRONT SECURED BY NON-CONDUCTIVE PRESS-STUDS; COMPLY WITH SANS 1822 TYPE 5; HOOD ATTACHED TO THE JACKET; JACKET TO COVER THE BUTTOCKS; FALSE ELASTIC SLEEVE AT THE END MADE OF SOFTER MATERIAL; PANTS SHALL HAVE SIDE SLITS AND ELASTIC WAIST; REFLECTIVE STRIPS TO BE FITTED ON BOTH SLEEVES ON THE UPPER ARM, AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SIDE OF THE SLEEVE AND THE ESKOM LOGO SHALL BE SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON THE FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; UNIQUE IDENTIFIER 240-44175132	EA
00830	0222567	RAINWEAR: TYPE: 2 PIECE SUIT; SIZE: XL; MATERIAL: POLYESTER 100 PCT PLAIN WEAVE, 180 GM/2 MIN; COLOR: BLUE NAVY; MATERIAL: MINIMUM 180 GRAMS PER M/3 FACE SIDE 100% POLYESTER; PLAIN WEAVE WITH 170 THREADS PER M/3 INCH WITH WATER RESISTANT COATING; UNDER SIDE LAMINATED WITH PVC COATING; SEAMS STRENGTH 50KPA; CONVERTS TO 50KNM/2; LINING 80% POLYESTER 20% COTTON; SIZE TO SANS 434 SIZE CHART ANNEX E FOR RAIN WEAR; JACKET SHALL HAVE A NYLON SPIRAL ZIP WITH CLOSED FLY FRONT SECURED BY NON-CONDUCTIVE PRESS-STUDS; COMPLY WITH SANS 1822 TYPE 5; HOOD ATTACHED TO THE JACKET; JACKET TO COVER THE BUTTOCKS; FALSE ELASTIC SLEEVE AT THE END MADE OF SOFTER MATERIAL; PANTS SHALL HAVE SIDE SLITS AND ELASTIC WAIST; REFLECTIVE STRIPS TO BE FITTED	EA

		ON BOTH SLEEVES ON THE UPPER ARM, AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SIDE OF THE SLEEVE AND THE ESKOM LOGO SHALL BE SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON THE FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; UNIQUE IDENTIFIER 240-44175132	
00840	0222405	SHIRT, WOMAN: SLEEVE TYPE: LONG; SIZE: 102 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE LONG SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF 65 MM WIDE; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132	EA
00850	0222406	SHIRT, WOMAN: SLEEVE TYPE: LONG; SIZE: 107 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE LONG SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF 65 MM WIDE; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132	EA
00860	0222407	SHIRT, WOMAN: SLEEVE TYPE: LONG; SIZE: 112 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE LONG SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM	EA

		LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF 65 MM WIDE; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132	
00870	0222402	SHIRT, WOMAN: SLEEVE TYPE: LONG; SIZE: 82 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE LONG SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF 65 MM WIDE; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132	EA
00880	0222404	SHIRT, WOMAN: SLEEVE TYPE: LONG; SIZE: 92 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE LONG SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF 65 MM WIDE; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132	EA
00890	0565829	SHIRT, WOMAN: SLEEVE TYPE: LONG; SIZE: 97 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE LONG SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND	EA

		14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF 65 MM WIDE; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132	
00900	0222419	SHIRT, WOMAN: SLEEVE TYPE: SHORT; SIZE: 102 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE SHORT SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132	EA
00910	0222420	SHIRT, WOMAN: SLEEVE TYPE: SHORT; SIZE: 107 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE SHORT SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132	EA
00920	0222421	SHIRT, WOMAN: SLEEVE TYPE: SHORT; SIZE: 112 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE SHORT SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR	EA

		WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132	
00930	0222422	SHIRT, WOMAN: SLEEVE TYPE: SHORT; SIZE: 117 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE SHORT SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132	EA
00940	0222416	SHIRT, WOMAN: SLEEVE TYPE: SHORT; SIZE: 82 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE SHORT SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132	EA
00950	0222417	SHIRT, WOMAN: SLEEVE TYPE: SHORT; SIZE: 87 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE SHORT SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST	EA

		AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132	
00960	0222418	SHIRT, WOMAN: SLEEVE TYPE: SHORT; SIZE: 92 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE SHORT SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132	EA
00970	0565830	SHIRT, WOMAN: SLEEVE TYPE: SHORT; SIZE: 97 CM; COLOR: GRAY; TYPE: FLAME RETARDANT; MATERIAL: COTTON; ALL SHIRTS SHALL BE MADE OF ZERO FLAME T006 SATIN WEAVE 100% COTTON FABRIC TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1423-1; THE SHIRT SIZES SHALL COMPLY TO ANNEX A; THE FRONT OF THE SHORT SLEEVED SHIRTS SHALL BE BUTTON DOWN PLAIN COLLAR WITH BUST AND WAIST DARTS; TWO BREAST POCKETS SHALL BE 14CM DEEP AND 14.5 CM WIDE; THE POCKETS AND FLAPS SHALL HAVE CUT EDGES; THE POCKET SHALL BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET; THE COLLAR SHALL BE A STANDARD SHIRT COLLAR; THE SHIRT SHALL BE CORPORATE SAND STONE; PANTONE 8004 C; THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND THE BUTTONS SHALL BE NON-CONDUCTIVE; THE BUTTON HOLES SHALL BE 1.2 CM SHIRT TYPE BUTTON HOLES; THE HEM SHALL BE PLAIN FINISHED AND SHALL BE 1.5 CM IN WIDTH; THE STITCHING SHALL COMPLY WITH SANS 10101; THE THREAD USED SHALL COMPLY WITH SANS 1362; UNIQUE IDENTIFIER 240-44175132	EA
00980	0222367	SHIRT: TYPE: MEN L/SLEEVE; SIZE: 36 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP	EA

		AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF- 65 MM WIDE SET IN LONG SLEEVE WITH TWO KNIFE PLEATS SEPARATE THE CUFF WITH BUTTON CLOSURE OF NON-CONDUCTIVE BUTTONS; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER; SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132	
00990	0222370	SHIRT: TYPE: MEN L/SLEEVE; SIZE: 37 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF- 65 MM WIDE SET IN LONG SLEEVE WITH TWO KNIFE PLEATS SEPARATE THE CUFF WITH BUTTON CLOSURE OF NON-CONDUCTIVE BUTTONS; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER; SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132	EA
01000	0222371	SHIRT: TYPE: MEN L/SLEEVE; SIZE: 38 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF- 65 MM WIDE SET IN LONG SLEEVE WITH TWO KNIFE PLEATS SEPARATE THE CUFF WITH BUTTON CLOSURE OF NON-CONDUCTIVE BUTTONS; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER; SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132	EA

01010	0222372	<p>SHIRT: TYPE: MEN L/SLEEVE; SIZE: 39 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF- 65 MM WIDE SET IN LONG SLEEVE WITH TWO KNIFE PLEATS SEPARATE THE CUFF WITH BUTTON CLOSURE OF NON-CONDUCTIVE BUTTONS; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER; SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132</p>	EA
01020	0222374	<p>SHIRT: TYPE: MEN L/SLEEVE; SIZE: 40 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF- 65 MM WIDE SET IN LONG SLEEVE WITH TWO KNIFE PLEATS SEPARATE THE CUFF WITH BUTTON CLOSURE OF NON-CONDUCTIVE BUTTONS; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER; SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-4417532</p>	EA
01030	0222375	<p>SHIRT: TYPE: MEN L/SLEEVE; SIZE: 41 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF- 65 MM WIDE SET IN LONG SLEEVE WITH TWO KNIFE PLEATS SEPARATE THE CUFF WITH BUTTON CLOSURE OF NON-CONDUCTIVE BUTTONS; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS</p>	EA

		SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER; SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132	
01040	0222376	SHIRT: TYPE: MEN L/SLEEVE; SIZE: 42 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF- 65 MM WIDE SET IN LONG SLEEVE WITH TWO KNIFE PLEATS SEPARATE THE CUFF WITH BUTTON CLOSURE OF NON-CONDUCTIVE BUTTONS; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER; SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132	EA
01050	0222377	SHIRT: TYPE: MEN L/SLEEVE; SIZE: 43 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF- 65 MM WIDE SET IN LONG SLEEVE WITH TWO KNIFE PLEATS SEPARATE THE CUFF WITH BUTTON CLOSURE OF NON-CONDUCTIVE BUTTONS; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER; SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132	EA
01060	0222378	SHIRT: TYPE: MEN L/SLEEVE; SIZE: 44 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE	EA

		AT BACK; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF- 65 MM WIDE SET IN LONG SLEEVE WITH TWO KNIFE PLEATS SEPARATE THE CUFF WITH BUTTON CLOSURE OF NON-CONDUCTIVE BUTTONS; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER; SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132	
01070	0222379	SHIRT: TYPE: MEN L/SLEEVE; SIZE: 45 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF- 65 MM WIDE SET IN LONG SLEEVE WITH TWO KNIFE PLEATS SEPARATE THE CUFF WITH BUTTON CLOSURE OF NON-CONDUCTIVE BUTTONS; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER; SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132	EA
01080	0222380	SHIRT: TYPE: MEN L/SLEEVE; SIZE: 46 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF- 65 MM WIDE SET IN LONG SLEEVE WITH TWO KNIFE PLEATS SEPARATE THE CUFF WITH BUTTON CLOSURE OF NON-CONDUCTIVE BUTTONS; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER; SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132	EA
01090	0222381	SHIRT: TYPE: MEN L/SLEEVE; SIZE: 47 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED	EA

		<p>TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF- 65 MM WIDE SET IN LONG SLEEVE WITH TWO KNIFE PLEATS SEPARATE THE CUFF WITH BUTTON CLOSURE OF NON-CONDUCTIVE BUTTONS; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER; SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132</p>	
01100	0222382	<p>SHIRT: TYPE: MEN L/SLEEVE; SIZE: 48 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF- 65 MM WIDE SET IN LONG SLEEVE WITH TWO KNIFE PLEATS SEPARATE THE CUFF WITH BUTTON CLOSURE OF NON-CONDUCTIVE BUTTONS; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER; SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132</p>	
01110	0222383	<p>SHIRT: TYPE: MEN L/SLEEVE; SIZE: 49 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; LONG-SLEEVED SHIRTS SHALL HAVE A CUFF- 65 MM WIDE SET IN LONG SLEEVE WITH TWO KNIFE PLEATS SEPARATE THE CUFF WITH BUTTON CLOSURE OF NON-CONDUCTIVE BUTTONS; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER; SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362;</p>	EA

		UNIQUE IDENTIFIER 240-44175132	
01120	0222384	SHIRT: TYPE: MEN S/SLEEVE; SIZE: 36 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE, ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER, SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132	EA
01130	0222386	SHIRT: TYPE: MEN S/SLEEVE; SIZE: 37 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE, ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER, SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132	EA
01140	0222387	SHIRT: TYPE: MEN S/SLEEVE; SIZE: 38 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE, ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER, SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132	EA

01150	0222389	SHIRT: TYPE: MEN S/SLEEVE; SIZE: 39 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE, ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER, SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132	EA
01160	0222390	SHIRT: TYPE: MEN S/SLEEVE; SIZE: 40 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE, ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER, SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132	EA
01170	0222391	SHIRT: TYPE: MEN S/SLEEVE; SIZE: 41 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE, ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER, SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132	EA
01180	0222392	SHIRT: TYPE: MEN S/SLEEVE; SIZE: 42 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS	EA

		1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE, ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER, SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132	
01190	0222394	SHIRT: TYPE: MEN S/SLEEVE; SIZE: 44 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE, ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER, SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132	EA
01200	0222395	SHIRT: TYPE: MEN S/SLEEVE; SIZE: 45 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE, ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER, SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132	EA
01210	0222396	SHIRT: TYPE: MEN S/SLEEVE; SIZE: 46 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP	EA

		AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE, ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER, SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132	
01220	0222398	SHIRT: TYPE: MEN S/SLEEVE; SIZE: 48 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE, ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER, SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132	EA
01230	0222399	SHIRT: TYPE: MEN S/SLEEVE; SIZE: 49 CM; MATERIAL: COTTON; COLOR: GRAY; MATERIAL ZERO FLAME T006 SATIN WEAVE 100% COTTON TREATED WITH A FLAME RETARDANT FINISH THAT COMPLIES WITH SANS 1432-1; SHIRTS TO COMPLY WITH REQUIREMENTS AND SIZES REFERRED TO ANNEX A; BUTTON FRONT WITH YOKE AND TWO BREAST POCKETS AND FLAPS TO BUTTON CLOSURE; THE POCKETS SHALL BE 16 CM DEEP AND 14 CM WIDE; POCKETS AND FLAPS SHALL HAVE CUT EDGES WITH A PEN DIVISION; FRONT POCKET SHALL BE FASTENED BY NON-CONDUCTIVE BUTTONS; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET COLLAR SHALL BE A STANDARD SHIRT COLLAR; SHIRT SHALL HAVE AN INVERTED PLEAT WITH HANGER LOOP AND YOKE AT BACK; SLEEVE OPENING BOUND WITH BINDING; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE, ESKOM LOGO EMBROIDERED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON LEFT TOP POCKET THE FRONT BUTTONS SHALL BE SEWN ONTO A STRENGTHENED FRONT AND SHALL BE NON-CONDUCTIVE; SEAMS SHOULDER, SLEEVE AND BACK YOKE POSTED; SIDE SEAM AND UNDER ARM SAFETY STITCH; HEMS FINISHED 10MM; STITCHING SHALL COMPLY TO SANS 10101 AND THREADS TO SANS 1362; UNIQUE IDENTIFIER 240-44175132	EA
01240	0565721	SUIT, CHEMICAL PROTECTIVE: GARMENT SIZE: 2XL; COLOR: YELLOW; MATERIAL: PVC COATED POLYESTER 400GRAM P/M3; TYPE: ACID PROOF; TEAR STRENGTH WELF 40N WARP 30N; BURST STRENGTH WELF 655N/50MM WARP 1232N/50MM; COATING ADHESIVE 15N/50MM; BASE FABRIC 100% POLYESTER WEIGHT 80 GRAMS PER M/3; YARN/CM 16 X 14.5; HOOK AND LOOP TAPE 20MM-WHITE; DRAW CORD 3MM POLYESTER;	EA

		SEAMS HIGH FREQUENCY WELDED; NYLON SPIRAL ZIP CLOSED FLY FRONT WITH ACID RESISTANT PRESS-STUDS; HOOD ATTACHED TO JACKET; JACKET TO COVER BUTTOCKS; FALSE ELASTIC SLEEVE OF SOFT MATERIAL TO PREVENT CHEMICALS ENTERING SLEEVE; PANTS SHALL HAVE ELASTICISED WAIST WITH NO SIDE SLITS AND NO POCKETS; SUIT TO BE YELLOW HIGH VISIBILITY MATERIAL; REFLECTIVE STRIPS ON BOTH SLEEVES UPPER ARM; AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; COMPLY WITH SANS 1822 TYPE 5 CHEMICAL TESTED TO ASTM P903-96; UNIQUE IDENTIFIER 240-44175132	
01250	0565718	SUIT, CHEMICAL PROTECTIVE: GARMENT SIZE: L; COLOR: YELLOW; MATERIAL: PVC COATED POLYESTER 400GRAM P/M3; TYPE: ACID PROOF; TEAR STRENGTH WELF 40N WARP 30N; BURST STRENGTH WELF 655N/50MM WARP 1232N/50MM; COATING ADHESIVE 15N/50MM; BASE FABRIC 100% POLYESTER WEIGHT 80 GRAMS PER M/3; YARN/CM 16 X 14.5; HOOK AND LOOP TAPE 20MM-WHITE; DRAW CORD 3MM POLYESTER; SEAMS HIGH FREQUENCY WELDED; NYLON SPIRAL ZIP CLOSED FLY FRONT WITH ACID RESISTANT PRESS-STUDS; HOOD ATTACHED TO JACKET; JACKET TO COVER BUTTOCKS; FALSE ELASTIC SLEEVE OF SOFT MATERIAL TO PREVENT CHEMICALS ENTERING SLEEVE; PANTS SHALL HAVE ELASTICISED WAIST WITH NO SIDE SLITS AND NO POCKETS; SUIT TO BE YELLOW HIGH VISIBILITY MATERIAL; REFLECTIVE STRIPS ON BOTH SLEEVES UPPER ARM; AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; COMPLY WITH SANS 1822 TYPE 5 CHEMICAL TESTED TO ASTM P903-96; UNIQUE IDENTIFIER 240-44175132	EA
01260	0565717	SUIT, CHEMICAL PROTECTIVE: GARMENT SIZE: M; COLOR: YELLOW; MATERIAL: PVC COATED POLYESTER 400GRAM P/M3; TYPE: ACID PROOF; TEAR STRENGTH WELF 40N WARP 30N; BURST STRENGTH WELF 655N/50MM WARP 1232N/50MM; COATING ADHESIVE 15N/50MM; BASE FABRIC 100% POLYESTER WEIGHT 80 GRAMS PER M/3; YARN/CM 16 X 14.5; HOOK AND LOOP TAPE 20MM-WHITE; DRAW CORD 3MM POLYESTER; SEAMS HIGH FREQUENCY WELDED; NYLON SPIRAL ZIP CLOSED FLY FRONT WITH ACID RESISTANT PRESS-STUDS; HOOD ATTACHED TO JACKET; JACKET TO COVER BUTTOCKS; FALSE ELASTIC SLEEVE OF SOFT MATERIAL TO PREVENT CHEMICALS ENTERING SLEEVE; PANTS SHALL HAVE ELASTICISED WAIST WITH NO SIDE SLITS AND NO POCKETS; SUIT TO BE YELLOW HIGH VISIBILITY MATERIAL; REFLECTIVE STRIPS ON BOTH SLEEVES UPPER ARM; AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; COMPLY WITH SANS 1822 TYPE 5 CHEMICAL TESTED TO ASTM P903-96; UNIQUE IDENTIFIER 240-44175132	EA
01270	0565716	SUIT, CHEMICAL PROTECTIVE: GARMENT SIZE: S; COLOR: YELLOW; MATERIAL: PVC COATED POLYESTER 400GRAM P/M3; TYPE: ACID PROOF; TEAR STRENGTH WELF 40N WARP 30N; BURST STRENGTH WELF 655N/50MM WARP 1232N/50MM; COATING ADHESIVE 15N/50MM; BASE FABRIC 100% POLYESTER WEIGHT 80 GRAMS PER M/3; YARN/CM 16 X 14.5; HOOK AND LOOP TAPE 20MM-WHITE; DRAW CORD 3MM POLYESTER;	EA

		SEAMS HIGH FREQUENCY WELDED; NYLON SPIRAL ZIP CLOSED FLY FRONT WITH ACID RESISTANT PRESS-STUDS; HOOD ATTACHED TO JACKET; JACKET TO COVER BUTTOCKS; FALSE ELASTIC SLEEVE OF SOFT MATERIAL TO PREVENT CHEMICALS ENTERING SLEEVE; PANTS SHALL HAVE ELASTICISED WAIST WITH NO SIDE SLITS AND NO POCKETS; SUIT TO BE YELLOW HIGH VISIBILITY MATERIAL; REFLECTIVE STRIPS ON BOTH SLEEVES UPPER ARM; AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; COMPLY WITH SANS 1822 TYPE 5 CHEMICAL TESTED TO ASTM P903-96; UNIQUE IDENTIFIER 240-44175132	
01280	0565719	SUIT, CHEMICAL PROTECTIVE: GARMENT SIZE: XL; COLOR: YELLOW; MATERIAL: PVC COATED POLYESTER 400GRAM P/M3; TYPE: ACID PROOF; TEAR STRENGTH WELF 40N WARP 30N; BURST STRENGTH WELF 655N/50MM WARP 1232N/50MM; COATING ADHESIVE 15N/50MM; BASE FABRIC 100% POLYESTER WEIGHT 80 GRAMS PER M/3; YARN/CM 16 X 14.5; HOOK AND LOOP TAPE 20MM-WHITE; DRAW CORD 3MM POLYESTER; SEAMS HIGH FREQUENCY WELDED; NYLON SPIRAL ZIP CLOSED FLY FRONT WITH ACID RESISTANT PRESS-STUDS; HOOD ATTACHED TO JACKET; JACKET TO COVER BUTTOCKS; FALSE ELASTIC SLEEVE OF SOFT MATERIAL TO PREVENT CHEMICALS ENTERING SLEEVE; PANTS SHALL HAVE ELASTICISED WAIST WITH NO SIDE SLITS AND NO POCKETS; SUIT TO BE YELLOW HIGH VISIBILITY MATERIAL; REFLECTIVE STRIPS ON BOTH SLEEVES UPPER ARM; AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SLEEVE; ESKOM LOGO SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; COMPLY WITH SANS 1822 TYPE 5 CHEMICAL TESTED TO ASTM P903-96; UNIQUE IDENTIFIER 240-44175132	EA
01290	0222478	TROUSERS: MEN LONG; SIZE: 127 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132	EA
01300	0643020	TROUSERS: TYPE: ACID RESIST; SIZE: 102; COLOR: GREEN BOTTLE; MATERIAL: POLYCOTTON; TO COMPLY WITH ESKOM SPECIFICATION 240-44175132; MATERIAL TO BE POLY COTTON FABRIC (65/35)	EA
01310	0643021	TROUSERS: TYPE: ACID RESIST; SIZE: 107; COLOR: GREEN BOTTLE; MATERIAL: POLYCOTTON; TO COMPLY WITH ESKOM SPECIFICATION 240-44175132; MATERIAL TO BE POLY COTTON FABRIC (65/35)	EA
01320	0643022	TROUSERS: TYPE: ACID RESIST; SIZE: 112; COLOR: GREEN BOTTLE; MATERIAL: POLYCOTTON; TO COMPLY WITH ESKOM SPECIFICATION 240-44175132; MATERIAL TO BE POLY COTTON FABRIC (65/35)	EA

01330	0643023	TROUSERS: TYPE: ACID RESIST; SIZE: 117; COLOR: GREEN BOTTLE; MATERIAL: POLYCOTTON; TO COMPLY WITH ESKOM SPECIFICATION 240-44175132; MATERIAL TO BE POLY COTTON FABRIC (65/35)	EA
01340	0643024	TROUSERS: TYPE: ACID RESIST; SIZE: 122; COLOR: GREEN BOTTLE; MATERIAL: POLYCOTTON; TO COMPLY WITH ESKOM SPECIFICATION 240-44175132; MATERIAL TO BE POLY COTTON FABRIC (65/35)	EA
01350	0643025	TROUSERS: TYPE: ACID RESIST; SIZE: 127; COLOR: GREEN BOTTLE; MATERIAL: POLYCOTTON; TO COMPLY WITH ESKOM SPECIFICATION 240-44175132; MATERIAL TO BE POLY COTTON FABRIC (65/35)	EA
01360	0643026	TROUSERS: TYPE: ACID RESIST; SIZE: 132; COLOR: GREEN BOTTLE; MATERIAL: POLYCOTTON; TO COMPLY WITH ESKOM SPECIFICATION 240-44175132; MATERIAL TO BE POLY COTTON FABRIC (65/35)	EA
01370	0643027	TROUSERS: TYPE: ACID RESIST; SIZE: 137; COLOR: GREEN BOTTLE; MATERIAL: POLYCOTTON; TO COMPLY WITH ESKOM SPECIFICATION 240-44175132; MATERIAL TO BE POLY COTTON FABRIC (65/35)	EA
01380	0643028	TROUSERS: TYPE: ACID RESIST; SIZE: 142; COLOR: GREEN BOTTLE; MATERIAL: POLYCOTTON; TO COMPLY WITH ESKOM SPECIFICATION 240-44175132; MATERIAL TO BE POLY COTTON FABRIC (65/35)	EA
01390	0643015	TROUSERS: TYPE: ACID RESIST; SIZE: 77; COLOR: GREEN BOTTLE; MATERIAL: POLYCOTTON; TO COMPLY WITH ESKOM SPECIFICATION 240-44175132; MATERIAL TO BE POLY COTTON FABRIC (65/35)	EA
01400	0643016	TROUSERS: TYPE: ACID RESIST; SIZE: 82; COLOR: GREEN BOTTLE; MATERIAL: POLYCOTTON; TO COMPLY WITH ESKOM SPECIFICATION 240-44175132; MATERIAL TO BE POLY COTTON FABRIC (65/35)	EA
01410	0643017	TROUSERS: TYPE: ACID RESIST; SIZE: 87; COLOR: GREEN BOTTLE; MATERIAL: POLYCOTTON; TO COMPLY WITH ESKOM SPECIFICATION 240-44175132; MATERIAL TO BE POLY COTTON FABRIC (65/35)	EA
01420	0643018	TROUSERS: TYPE: ACID RESIST; SIZE: 92; COLOR: GREEN BOTTLE; MATERIAL: POLYCOTTON; TO COMPLY WITH ESKOM SPECIFICATION 240-44175132; MATERIAL TO BE POLY COTTON FABRIC (65/35)	EA
01430	0643019	TROUSERS: TYPE: ACID RESIST; SIZE: 97; COLOR: GREEN BOTTLE; MATERIAL: POLYCOTTON; TO COMPLY WITH ESKOM SPECIFICATION 240-44175132; MATERIAL TO BE POLY COTTON FABRIC (65/35)	EA
01440	0566680	TROUSERS: TYPE: CLEAN CONDITION; SIZE: 92 CM; COLOR: WHITE; MATERIAL: COTTON 100% D59 PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE SPECIFICATION REQUIREMENTS FOR SIZES UNDER SECTION 2.6 (OVERALL-BOILER SUITS OR 2 PIECE WORK WEAR SUITS) SHALL APPLY; MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE TROUSER SHALL HAVE NO POCKETS; NO BUTTONS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH DRAW CORD 10MM COTTON BELT STRING FOR FASTENING AND WITHOUT ZIP ON THE FRONT NO METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE RIGHT BACK IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE LEFT BACK SIDE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH LEGS CIRCUMFERENCE ON	EA

		THE INNER UPPER LEG; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS ALL RELAVANT ITEMS TO COMPLY AS PER UNIQUE IDENTIFIER 240-44175132	
01450	0222500	TROUSERS: TYPE: LADIES LONG; SIZE: 28; 72; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY	EA
01460	0222501	TROUSERS: TYPE: LADIES LONG; SIZE: 30; 77; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY	EA
01470	0222502	TROUSERS: TYPE: LADIES LONG; SIZE: 32; 82; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY	EA

01480	0222503	TROUSERS: TYPE: LADIES LONG; SIZE: 34; 87; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY	EA
01490	0222504	TROUSERS: TYPE: LADIES LONG; SIZE: 36; 92; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY	EA
01500	0222505	TROUSERS: TYPE: LADIES LONG; SIZE: 38; 97; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY	EA
01510	0222506	TROUSERS: TYPE: LADIES LONG; SIZE: 40; 102; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE	EA

		A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY	
01520	0222507	TROUSERS: TYPE: LADIES LONG; SIZE: 42; 107; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY	EA
01530	0222508	TROUSERS: TYPE: LADIES LONG; SIZE: 44; 112; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY	EA
01540	0222509	TROUSERS: TYPE: LADIES LONG; SIZE: 46; 117; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE	EA

		OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY	
01550	0222510	TROUSERS: TYPE: LADIES LONG; SIZE: 48; 122; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY	EA
01560	0222472	TROUSERS: TYPE: MEN LONG; SIZE: 102 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132	EA
01570	0222473	TROUSERS: TYPE: MEN LONG; SIZE: 107 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132	EA
01580	0222474	TROUSERS: TYPE: MEN LONG; SIZE: 112 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY	EA

		INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132	
01590	0222476	TROUSERS: TYPE: MEN LONG; SIZE: 117 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132	EA
01600	0222477	TROUSERS: TYPE: MEN LONG; SIZE: 122 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132	EA
01610	0222479	TROUSERS: TYPE: MEN LONG; SIZE: 132 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132	EA
01620	0222480	TROUSERS: TYPE: MEN LONG; SIZE: 137 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132	EA
01630	0222481	TROUSERS: TYPE: MEN LONG; SIZE: 142 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59	EA

		FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132	
01640	0222467	TROUSERS: TYPE: MEN LONG; SIZE: 77 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132	EA
01650	0222468	TROUSERS: TYPE: MEN LONG; SIZE: 82 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132	EA
01670	0222469	TROUSERS: TYPE: MEN LONG; SIZE: 87 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132	EA
01680	0222470	TROUSERS: TYPE: MEN LONG; SIZE: 92 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132	EA

01690	0222471	TROUSERS: TYPE: MEN LONG; SIZE: 97 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132	EA
01700	0565550	VEST, HIGH VISIBILITY: TYPE: EMPLOYEE AT WORK; SIZE: 2XL; MATERIAL: NYLON; COLOR: ORANGE LIGHT B26 NCS-1673-Y48R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A4 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A4; POCKET TYPE: LEFT TOP; EMPLOYEE AT WORK TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A4; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A4 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS	EA
01710	0565551	VEST, HIGH VISIBILITY: TYPE: EMPLOYEE AT WORK; SIZE: 3XL; MATERIAL: NYLON; COLOR: ORANGE LIGHT B26 NCS-1673-Y48R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A4 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A4; POCKET TYPE: LEFT TOP; EMPLOYEE AT WORK TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A4; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A4 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS	EA
01720	0565548	VEST, HIGH VISIBILITY: TYPE: EMPLOYEE AT WORK; SIZE: L; MATERIAL: NYLON; COLOR: ORANGE LIGHT B26 NCS-1673-Y48R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A4 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A4; POCKET TYPE: LEFT TOP; EMPLOYEE AT WORK TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM	EA

		LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A4; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A4 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS	
01730	0565547	VEST, HIGH VISIBILITY: TYPE: EMPLOYEE AT WORK; SIZE: M; MATERIAL: NYLON; COLOR: ORANGE LIGHT B26 NCS-1673-Y48R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A4 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A4; POCKET TYPE: LEFT TOP; EMPLOYEE AT WORK TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A4; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A4 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS	EA
01740	0237954	VEST, HIGH VISIBILITY: TYPE: EMPLOYEE AT WORK; SIZE: S; MATERIAL: NYLON; COLOR: ORANGE LIGHT B26 NCS-1673-Y48R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A4 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A4; POCKET TYPE: LEFT TOP; EMPLOYEE AT WORK TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A4; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A4 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS	EA
01750	0565549	VEST, HIGH VISIBILITY: TYPE: EMPLOYEE AT WORK; SIZE: XL; MATERIAL: NYLON; COLOR: ORANGE LIGHT B26 NCS-1673-Y48R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A4 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A4; POCKET TYPE: LEFT TOP; EMPLOYEE AT WORK TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM	EA

		<p>LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A4; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A4 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS</p>	
01760	0239867	<p>VEST, HIGH VISIBILITY: TYPE: EVACUATION; SIZE: L; MATERIAL: NYLON; COLOR: WHITE CLOUD G80 NCS0704G28Y; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; EVACUATION CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS</p>	EA
01770	0565615	<p>VEST, HIGH VISIBILITY: TYPE: FIRE PROTECTION; SIZE: 2XL; MATERIAL: NYLON; COLOR: SIGNAL RED A11 NCS-1678-Y86R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; FIRE PROTECTION CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS</p>	EA
01780	0565613	<p>VEST, HIGH VISIBILITY: TYPE: FIRE PROTECTION; SIZE: L; MATERIAL: NYLON; COLOR: SIGNAL RED A11 NCS-1678-Y86R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; FIRE PROTECTION CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT</p>	EA

		TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS	
01790	0565612	VEST, HIGH VISIBILITY: TYPE: FIRE PROTECTION; SIZE: M; MATERIAL: NYLON; COLOR: SIGNAL RED A11 NCS-1678-Y86R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; FIRE PROTECTION CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS	EA
01800	0565611	VEST, HIGH VISIBILITY: TYPE: FIRE PROTECTION; SIZE: S; MATERIAL: NYLON; COLOR: SIGNAL RED A11 NCS-1678-Y86R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; FIRE PROTECTION CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS	EA
01810	0565614	VEST, HIGH VISIBILITY: TYPE: FIRE PROTECTION; SIZE: XL; MATERIAL: NYLON; COLOR: SIGNAL RED A11 NCS-1678-Y86R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; FIRE PROTECTION CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT	EA

		TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS	
01820	0565635	VEST, HIGH VISIBILITY: TYPE: FIRST AID; SIZE: L; MATERIAL: NYLON; COLOR: EMERALD GREEN E14 NCS-3745-B99G; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; FIRST AID CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS	EA
01830	0565628	VEST, HIGH VISIBILITY: TYPE: FIRST AID; SIZE: M; MATERIAL: NYLON; COLOR: EMERALD GREEN E14 NCS-3745-B99G; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; FIRST AID CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS	EA
01840	0565627	VEST, HIGH VISIBILITY: TYPE: FIRST AID; SIZE: S; MATERIAL: NYLON; COLOR: EMERALD GREEN E14 NCS-3745-B99G; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A3 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A3; POCKET TYPE: LEFT TOP; FIRST AID CO-ORDINATOR TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP;	EA

	<p>ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A3; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A3 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS</p>	
--	---	--

Quality assurance requirements

Goods will go through quality check process before accepted and if not accepted, must be replaced by a new one.

Vendors are responsible for ensuring that they are performing against the correct drawing revision if applicable

Invoicing and payment

Detailed tax invoice, clearly showing: Eskom Holdings SOC LTD
Electronic copy to Finance Shared Services
Megawatt Park

The *Supplier* shall address the tax invoice to *Purchaser* and include on each invoice the following information:

- Name and address of the *Supplier* and the *Supply Manager*;
- The contract number and title;
- *Supplier's* VAT registration number;
- The *Purchaser's* VAT registration number.
- Description of *goods* and *services* provided for each item invoiced based on the Price Schedule;
- Total amount invoiced excluding VAT, the VAT and the invoiced amount including VAT;

Plant and Materials

Quality

Temporary works, Site services & construction constraints.

The following Eskom Life Saving Rules applies when entering premises.

- a. Open, isolate, earth, bond or and isolate before touch.
- b. Hook up at heights.
- c. Buckle up.
- d. Be sober.
- e. Permit to work.

Compliance requirements.

Eskom reserves the right to commercially and technically disqualify a tender.
 Suppliers are responsible to establish their own sources of supply.
 CPA will only be applied at the agreed period only no ad hoc price adjustment will be permitted.
 Failure to comply with the above will result in tender being disqualified.

Accelerated Shared Growth Initiative – South Africa (ASGI-SA) /SDL & I

The Contractor complies with and fulfils the Contractor’s obligations in respect of the Accelerated and Shared Growth Initiative - South Africa in accordance with and as provided for in the Contractor’s SD&L Compliance Schedule.

Local Content and Production

This Project contains items that has been designated for Local Production and Content, therefore a specific bidding condition that only locally produced goods or services with a stipulated minimum threshold for Local Production and Content will be considered.

Commodity	Components	Local Content Threshold
PPE	Reflector Vests, Jackets, Boots, Textiles, Clothing, Leather & Footwear, etc.	100%

BBBEE and preferencing scheme

The company shall maintain or improve upon their current B-BBEE Contribution level for the duration of the contract. The supplier will be required to submit a new B-BBEE certificate within 3 months, should ownership of the company change during the life of the contract.