

## PART 2: PRICING DATA

### NEC3 Supply Contract

Document reference	Title	No of pages
C2.1	Pricing assumptions	2
C2.2	The <i>price schedule</i>	2-7

## C2.1 Pricing assumptions

### 1. How *goods* and *services* are priced and assessed for payment

Clause 11 in NEC3 Supply Contract, (SC3) core clauses states:

<b>Identified and defined terms</b>	11	
	11.2	(11) The Prices are the amounts stated in the price column of the Price Schedule. Where a quantity is stated for an item in the Price Schedule, the Price is calculated by multiplying the quantity by the rate.  (12) The Price Schedule is the <i>price schedule</i> unless later changed in accordance with this contract.
<b>Assessing the amount due</b>	50.2	<p>The amount due is</p> <ul style="list-style-type: none"><li>• the Price for each lump sum item in the Price Schedule which the <i>Supplier</i> has completed,</li><li>• where a quantity is stated for an item in the Price Schedule, an amount calculated by multiplying the quantity which the <i>Supplier</i> has completed by the rate,</li><li>• plus other amounts to be paid to the <i>Supplier</i>,</li><li>• less amounts to be paid by or retained from the <i>Supplier</i>.</li></ul> <p>Any tax which the law requires the <i>Purchaser</i> to pay to the <i>Supplier</i> is included in the amount due.</p>

This confirms that the Supply Contract is a priced contract where the Prices are derived from a list of items of *goods* and *services* which can be priced as lump sums or as expected quantities of *goods* and *services* multiplied by a rate, or a mix of both.

### 2. Function of the Price Schedule

Clause 53.1 states: "Information in the Price Schedule is not Goods Information". This confirms that instructions to do work or how it is to be done are not included in the Price Schedule but in the Goods Information. This is further confirmed by Clause 20.1 which states, "The *Supplier* Provides the Goods and Services in accordance with the Goods Information". Hence the *Supplier* does **not** Provide the Goods and Services in accordance with the Price Schedule. The Price Schedule is only a pricing document.

### 3. Preparing the *price schedule*

Items in the *price schedule* may have been inserted by the *Purchaser* and the tendering supplier should insert any additional items which he considers necessary. Whichever party provides the items in the *price schedule* the total of the Prices is assumed to be fully inclusive of everything necessary to Provide the Goods and Services as described at the time of entering into this contract.

It will be assumed that the tendering supplier has

- Read Pages 8, 11, 12 and Appendix 5 of the SC3 Guidance Notes before preparing the *price schedule*;
- Included in his Prices and rates for correction of Defects (core clause 43.1) as there is no compensation event for this unless the Defect is due to a *Supplier's* risk;
- Spread the cost of doing work he chooses not to list as separate items in the *price schedule* across other Prices and rates in order to fulfil the obligation to Provide the Goods and Services for the tendered total of the Prices;
- Understood that there is no adjustment to lump sum prices in the *price schedule* if the amount, or quantity, of work within that lump sum item later turns out to be different to that which the *Supplier* estimated at time of tender. The only basis for a change to the Prices is as a result of a compensation event per clause 60.1;
- Understood that the *Supplier* does not have to allow in his Prices and rates for matters that may arise as a result of a compensation event.

#### 3.1. Format of the *price schedule*

Entries in the first four columns in the *price schedule* in section C2.2 are made either by the *Purchaser* or the tendering supplier.

If the *Supplier* is to be paid an amount for the item which is not adjusted if the quantity of work in the item changes, the tendering supplier enters the amount in the Price column only, the Unit, Quantity and Rate columns being left blank.

If the *Supplier* is to be paid an amount for the item which is the rate for the item multiplied by the quantity completed, the tendering *Supplier* enters the rate which is then multiplied by the Quantity to produce the Price, which is also entered.

If the *Supplier* is to be paid an amount for an item proportional to the length of time for which the *goods* and *services* are provided, a unit of time is stated in the Unit column and the length of time (as a quantity of the stated units of time) is stated in the Quantity column.

## C2.2 the *price schedule*

Material NO:	Description	Quantity	Unit	Price
0222478	TROUSERS:MEN LONG;127 CM;BLUE NAVY	833	EA	
0172193	JACKET UTIL:OPERATING;137 CM	833	EA	
0179714	JACKET UTIL:OPERATING;157 CM	833	EA	
0222468	TROUSERS:MEN LONG;82 CM;BLUE NAVY	1 667	EA	
0222469	TROUSERS:MEN LONG;87 CM;BLUE NAVY	1 667	EA	
0222470	TROUSERS:MEN LONG;92 CM;BLUE NAVY	1 667	EA	

Material NO:	Description	Quantity	Unit	Price
0222471	TROUSERS:MEN LONG;97 CM;BLUE NAVY	1 667	EA	
0222472	TROUSERS:MEN LONG;102 CM;BLUE NAVY	1 667	EA	
0222473	TROUSERS:MEN LONG;107 CM;BLUE NAVY	1 333	EA	
0222474	TROUSERS:MEN LONG;112 CM;BLUE NAVY	1 333	EA	
0222476	TROUSERS:MEN LONG;117 CM;BLUE NAVY	667	EA	
0222477	TROUSERS:MEN LONG;122 CM;BLUE NAVY	667	EA	
0222479	TROUSERS:MEN LONG;132 CM;BLUE NAVY	667	EA	
0222480	TROUSERS:MEN LONG;137 CM;BLUE NAVY	667	EA	
0222481	TROUSERS:MEN LONG;142 CM;BLUE NAVY	667	EA	
0222482	TROUSERS:MEN LONG;147 CM;BLUE NAVY	667	EA	
0222535	JACKET UTIL:OPERATING;87 CM	1 667	EA	
0222536	JACKET UTIL:OPERATING;97 CM	1 667	EA	
0222537	JACKET UTIL:OPERATING;107 CM	1 667	EA	
0222538	JACKET UTIL:OPERATING;117 CM	1 000	EA	
0222539	JACKET UTIL:OPERATING;122 CM	667	EA	
0222540	JACKET UTIL:OPERATING;132 CM	667	EA	
0566481	JACKET UTIL:OPERATING;77 CM	667	EA	
0566482	JACKET UTIL:OPERATING;82 CM	833	EA	
0566494	JACKET UTIL:OPERATING;102 CM	1 667	EA	
0566503	JACKET UTIL:OPERATING;112 CM	1 667	EA	
0566511	JACKET UTIL:OPERATING;127 CM	833	EA	
0566512	JACKET UTIL:OPERATING;142 CM	667	EA	
0566513	JACKET UTIL:OPERATING;152 CM	667	EA	
0566544	JACKET UTIL:OPERATING;92 CM	1 667	EA	
0566736	TROUSERS:MEN LONG;152 CM;BLUE NAVY	333	EA	
0566737	TROUSERS:MEN LONG;157 CM;BLUE NAVY	333	EA	
0222499	TROUSERS:LADIES LONG;26; 67;BLUE NAVY	333	EA	
0222500	TROUSERS:LADIES LONG;28; 72;BLUE NAVY	417	EA	
0222501	TROUSERS:LADIES LONG;30; 77;BLUE NAVY	417	EA	
0222502	TROUSERS:LADIES LONG;32; 82;BLUE NAVY	417	EA	
0222503	TROUSERS:LADIES LONG;34; 87;BLUE NAVY	417	EA	
0222504	TROUSERS:LADIES LONG;36; 92;BLUE NAVY	417	EA	
0222505	TROUSERS:LADIES LONG;38; 97;BLUE NAVY	417	EA	
0222506	TROUSERS:LADIES LONG;40; 102;BLUE NAVY	333	EA	
0222507	TROUSERS:LADIES LONG;42; 107;BLUE NAVY	333	EA	
0222508	TROUSERS:LADIES LONG;44; 112;BLUE NAVY	333	EA	
0222509	TROUSERS:LADIES LONG;46; 117;BLUE NAVY	333	EA	
0222510	TROUSERS:LADIES LONG;48; 122;BLUE NAVY	333	EA	
0222511	TROUSERS:LADIES LONG;50; 127;BLUE NAVY	333	EA	
0222512	TROUSERS:LADIES LONG;52; 132;BLUE NAVY	333	EA	
0222513	TROUSERS:LADIES LONG;54; 137;BLUE NAVY	333	EA	
0566548	JACKET UTIL:ACID/ALKALI;102 CM	833	EA	
0566454	JACKET UTIL:ACID/ALKALI;107 CM	833	EA	
0566552	JACKET UTIL:ACID/ALKALI;112 CM	833	EA	
0566455	JACKET UTIL:ACID/ALKALI;117 CM	833	EA	

Material NO:	Description	Quantity	Unit	Price
0566456	JACKET UTIL:ACID/ALKALI;122 CM	833	EA	
0566549	JACKET UTIL:ACID/ALKALI;127 CM	833	EA	
0566457	JACKET UTIL:ACID/ALKALI;132 CM	833	EA	
0566458	JACKET UTIL:ACID/ALKALI;137 CM	833	EA	
0566550	JACKET UTIL:ACID/ALKALI;142 CM	583	EA	
0566459	JACKET UTIL:ACID/ALKALI;147 CM	583	EA	
0566551	JACKET UTIL:ACID/ALKALI;152 CM	333	EA	
0566460	JACKET UTIL:ACID/ALKALI;157 CM	333	EA	
0566545	JACKET UTIL:ACID/ALKALI;77 CM	833	EA	
0566546	JACKET UTIL:ACID/ALKALI;82 CM	833	EA	
0566452	JACKET UTIL:ACID/ALKALI;87 CM	833	EA	
0566547	JACKET UTIL:ACID/ALKALI;92 CM	833	EA	
0566453	JACKET UTIL:ACID/ALKALI;97 CM	833	EA	
0576288	TROUSERS:ACID/ALKALI;87 CM;GREEN BOTTLE	833	EA	
0576301	TROUSERS:ACID/ALKALI;92 CM;GREEN BOTTLE	833	EA	
0576295	TROUSERS:ACID/ALKALI;127 CM;GREEN BOTTLE	500	EA	
0576297	TROUSERS:ACID/ALKALI;137 CM;GREEN BOTTLE	417	EA	
0576286	TROUSERS:ACID/ALKALI;77;GREEN BOTTLE	833	EA	
0576293	TROUSERS:ACID/ALKALI;117 CM;GREEN BOTTLE	833	EA	
0576294	TROUSERS:ACID/ALKALI;122 CM;GREEN BOTTLE	833	EA	
0576299	TROUSERS:ACID/ALKALI;147 CM;GREEN BOTTLE	333	EA	
0576296	TROUSERS:ACID/ALKALI;132 CM;GREEN BOTTLE	833	EA	
0576287	TROUSERS:ACID/ALKALI;82 CM;GREEN BOTTLE	833	EA	
0576291	TROUSERS:ACID/ALKALI;107 CM;GREEN BOTTLE	833	EA	
0576290	TROUSERS:ACID/ALKALI;102 CM;GREEN BOTTLE	833	EA	
0576298	TROUSERS:ACID/ALKALI;142 CM;GREEN BOTTLE	500	EA	
0576289	TROUSERS:ACID/ALKALI;97 CM;GREEN BOTTLE	833	EA	
0576292	TROUSERS:ACID/ALKALI;112 CM;GREEN BOTTLE	833	EA	
0576302	TROUSERS:ACID/ALKALI;157 CM;GREEN BOTTLE	333	EA	
0576300	TROUSERS:ACID/ALKALI;152 CM;GREEN BOTTLE	333	EA	
0566600	COVERALL:ACID/ALKALI;77 CM	333	EA	
0566601	COVERALL:ACID/ALKALI;82 CM	333	EA	
0566602	COVERALL:ACID/ALKALI;87 CM	333	EA	
0566603	COVERALL:ACID/ALKALI;92 CM	333	EA	
0566604	COVERALL:ACID/ALKALI;97 CM	333	EA	
0566605	COVERALL:ACID/ALKALI;102 CM	333	EA	
0566606	COVERALL:ACID/ALKALI;107 CM	333	EA	
0566607	COVERALL:ACID/ALKALI;112 CM	333	EA	
0566608	COVERALL:ACID/ALKALI;117 CM	333	EA	
0566609	COVERALL:ACID/ALKALI;122 CM	333	EA	
0566610	COVERALL:ACID/ALKALI;127 CM	333	EA	
0566611	COVERALL:ACID/ALKALI;132 CM	333	EA	
0566612	COVERALL:ACID/ALKALI;137	333	EA	
0566613	COVERALL:ACID/ALKALI;142 CM	333	EA	
0566614	COVERALL:ACID/ALKALI;147 CM	333	EA	

Material NO:	Description	Quantity	Unit	Price
0566615	COVERALL:ACID/ALKALI;152 CM	333	EA	
0566616	COVERALL:ACID/ALKALI;157 CM	333	EA	
0222553	JACKET UTIL:THERMAL;S; 34; 87	833	EA	
0222554	JACKET UTIL:THERMAL;M; 38; 97	833	EA	
0222555	JACKET UTIL:THERMAL;L; 42; 107	833	EA	
0222556	JACKET UTIL:THERMAL;XL; 46; 117	667	EA	
0222558	JACKET UTIL:THERMAL;XXL; 48; 122	250	EA	
0222559	JACKET UTIL:THERMAL;3XL	250	EA	
0222561	RAINWEAR:2 PIECE SUIT;S;BLUE NAVY	1 000	EA	
0225676	RAINWEAR:2 PIECE SUIT;M;BLUE NAVY	1 000	EA	
0222566	RAINWEAR:2 PIECE SUIT;L;BLUE NAVY	1 000	EA	
0222567	RAINWEAR:2 PIECE SUIT;XL;BLUE NAVY	1 000	EA	
0222568	RAINWEAR:2 PIECE SUIT;2XL;BLUE NAVY	667	EA	
0222569	RAINWEAR:2 PIECE SUIT;3XL;BLUE NAVY	500	EA	
0565711	RAINWEAR:2 PIECE SUIT;4XL;BLUE NAVY	417	EA	
0237954	VEST HIGH VIS:EMPLOYEE AT WORK;S;NYLON	1 000	EA	
0565547	VEST HIGH VIS:EMPLOYEE AT WORK;M;NYLON	1 667	EA	
0565548	VEST HIGH VIS:EMPLOYEE AT WORK;L;NYLON	2 500	EA	
0565549	VEST HIGH VIS:EMPLOYEE AT WORK;XL;NYLON	2 500	EA	
0565550	VEST HIGH VIS:EMPLOYEE AT WORK;2XL;NYLON	417	EA	
0565551	VEST HIGH VIS:EMPLOYEE AT WORK;3XL;NYLON	417	EA	
0565552	VEST HIGH VIS:EMPLOYEE AT WORK;4XL;NYLON	333	EA	
0565553	VEST HIGH VIS:EMPLOYEE AT WORK;5XL;NYLON	333	EA	
0017014	GUMBOOTS SFTY:STL;7;KNEE HEIGHT;BLACK	167	PAA	
0017015	GUMBOOTS SFTY:STL;8;KNEE HEIGHT;BLACK	167	PAA	
0017016	GUMBOOTS SFTY:STL;9;KNEE HEIGHT;BLACK	167	PAA	
0017017	GUMBOOTS SFTY:STL;10;KNEE HEIGHT;BLACK	167	PAA	
0017018	GUMBOOTS SFTY:STL;11;KNEE HEIGHT;BLACK	83	PAA	
0035314	ARRSTR FLSHBCK:GAS/OXYGEN WELDING;3/8 IN	17	EA	
0040995	LENS SFTY EQP:WELDING GOGGLES;CLEAR	67	EA	
0041001	HELMET WELDG:PP	33	EA	
0041004	SPECTACLE SFTY:INDOOR/OUTDOOR;VARIABLE	3 333	EA	
0041080	GOGGLES INDSTR:CHEMICAL/DUST;CLEAR;PC	667	EA	
0041081	SPECTACLE SFTY:GAS WELDING;GREEN;104 MM	83	EA	
0041093	SHIELD SFTY EQP:FACE;WD 250 X LG 450 MM	33	EA	
0041094	SHIELD SFTY EQP:FACE;WD 250 X LG 450 MM	33	EA	
0041102	GOGGLES:WELDERS;GREEN SHADE 6;PC	33	EA	
0041109	SHIELD SFTY EQP:FACE;GREEN DARK;PC	33	EA	
0041117	MASK RSPT:R:DUST;UNIVERSAL;PAPER	5 833	EA	
0041128	LENS SFTY EQP:WELDING GOGGLES;NO 6;GLASS	67	EA	
0041168	PROTECTOR HEARNG:EARMUFF;CUSHIONS	5 000	EA	
0160593	WADER:FISHERMANS;7;PVC;GREEN OLIVE	250	PAA	
0160594	WADER:FISHERMANS;8;PVC;GREEN OLIVE	500	PAA	
0160595	WADER:FISHERMANS;9;PVC;GREEN OLIVE	250	PAA	
0160596	WADER:FISHERMANS;10;PVC;GREEN OLIVE	250	PAA	

Material NO:	Description	Quantity	Unit	Price
0160597	WADER:FISHERMANS;11;PVC;GREEN OLIVE	167	PAA	
0160683	PROTECTOR:ANKLE SPATS;LG 320 X HT 250 MM	167	PAA	
0160854	GLOVE WLDR:10;LG 300 MM;PIG SKIN;BEIGE	33 333	PAA	
0160938	GLOVE CHEM PROTCTV:ACID RESISTANT;L;PVC	417	PAA	
0160939	GLOVE CHEM PROTCTV:ACID RESISTANT;L;PVC	250	PAA	
0161000	GUMBOOTS SFTY:STL;12;KNEE HEIGHT;BLACK	33	PAA	
0161108	GUMBOOTS SFTY:STL;6;KNEE HEIGHT;BLACK	133	PAA	
0161114	GUMBOOTS SFTY:STL;13;KNEE HEIGHT;BLACK	33	PAA	
0172739	MASK RSPTR:HALF DISPOSABLE;DUST/MIST	50 000	EA	
0180140	SPECTACLE SFTY:CLEAR;U9168T ASTROSPEC	1 333	EA	
214494	TOWEL BATH:LG 1.25 M;WD 700 MM;THK 5 MM	2 500	EA	
0226674	SHIELD SFTY EQP:FACE;CLEAR;PERSPEX	33	EA	
0241157	HELMET SFTY:530-630 MM;WHITE	6 667	EA	
0242722	GLOVE:PRECISION;S;LG 230 MM;55 MM;BLACK	10 000	PAA	
242723	GLOVE:PRECISION;M;LG 230 MM;55 MM;BLACK	10 000	PAA	
0242724	GLOVE:PRECISION;L;LG 230 MM;230 MM;BLACK	10 000	PAA	
0242725	GLOVE:PRECISION;XL;LG 230 MM;55 MM;BLACK	10 000	PAA	
0249397	SPECTACLE SFTY:INDOOR/OUTDOOR;SILVER;STD	5 000	EA	
0503021	RESPIRATOR:FULL FACE;ADJUSTABLE	10 000	EA	
0552719	HELMET SFTY:HEIGHT THREE POINT;WHITE	8 333	EA	
0552722	STRAP:THREE-POINT CHIN BLACK	167	EA	
0552723	STRAP:SINGLE POINT CHIN BLACK	167	EA	
0565295	GLOVE WLDR:L;LG 8 IN;LEATHER;GREEN;GP	1 667	PAA	
0566206	GUMBOOTS SFTY:STL;3;KNEE HEIGHT;BLACK	17	PAA	
0566207	GUMBOOTS SFTY:STL;4;KNEE HEIGHT;BLACK	25	PAA	
0566208	GUMBOOTS SFTY:STL;5;KNEE HEIGHT;BLACK	50	PAA	
0566383	WADER:FISHERMANS;6;PVC;GREEN OLIVE	33	PAA	
0566391	WADER:FISHERMANS;12;PVC;GREEN OLIVE	25	PAA	
0566392	WADER:FISHERMANS;13;PVC;GREEN OLIVE	17	PAA	
0566629	JACKET OVRL:CLEAN CONDITION;77 CM;WHITE	133	EA	
0566630	JACKET OVRL:CLEAN CONDITION;82 CM;WHITE	250	EA	
0566631	JACKET OVRL:CLEAN CONDITION;87 CM;WHITE	250	EA	
0566632	JACKET OVRL:CLEAN CONDITION;92 CM;WHITE	250	EA	
0566633	JACKET OVRL:CLEAN CONDITION;97 CM;WHITE	250	EA	
0566634	JACKET OVRL:CLEAN CONDITION;102 CM;WHITE	167	EA	
0566635	JACKET OVRL:CLEAN CONDITION;107 CM;WHITE	167	EA	
0566636	JACKET OVRL:CLEAN CONDITION;112 CM;WHITE	167	EA	
0566637	JACKET OVRL:CLEAN CONDITION;117 CM;WHITE	167	EA	
0566638	JACKET OVRL:CLEAN CONDITION;122 CM;WHITE	167	EA	
0566639	JACKET OVRL:CLEAN CONDITION;127 CM;WHITE	133	EA	
0566640	JACKET OVRL:CLEAN CONDITION;132 CM;WHITE	83	EA	
0566641	JACKET OVRL:CLEAN CONDITION;137 CM;WHITE	83	EA	
0566642	JACKET OVRL:CLEAN CONDITION;142 CM;WHITE	83	EA	
0566643	JACKET OVRL:CLEAN CONDITION;147 CM;WHITE	83	EA	
0566644	JACKET OVRL:CLEAN CONDITION;152 CM;WHITE	83	EA	

Material NO:	Description	Quantity	Unit	Price
0566645	JACKET OVRL:CLEAN CONDITION;157 CM;WHITE	83	EA	
0566676	TROUSERS:CLEAN CONDITION;77 CM;WHITE	133	EA	
0566677	TROUSERS:CLEAN CONDITION;82 CM;WHITE	250	EA	
0566678	TROUSERS:CLEAN CONDITION;87 CM;WHITE	250	EA	
0566680	TROUSERS:CLEAN CONDITION;92 CM;WHITE	250	EA	
0566681	TROUSERS:CLEAN CONDITION;97 CM;WHITE	250	EA	
0566682	TROUSERS:CLEAN CONDITION;102 CM;WHITE	167	EA	
0566683	TROUSERS:CLEAN CONDITION;107 CM;WHITE	167	EA	
0566684	TROUSERS:CLEAN CONDITION;112 CM;WHITE	167	EA	
0566685	TROUSERS:CLEAN CONDITION;117 CM;WHITE	167	EA	
0566686	TROUSERS:CLEAN CONDITION;122 CM;WHITE	167	EA	
0566687	TROUSERS:CLEAN CONDITION;127 CM;WHITE	133	EA	
0566688	TROUSERS:CLEAN CONDITION;132 CM;WHITE	83	EA	
0566689	TROUSERS:CLEAN CONDITION;137 CM;WHITE	83	EA	
0566690	TROUSERS:CLEAN CONDITION;142 CM;WHITE	83	EA	
0566691	TROUSERS:CLEAN CONDITION;147 CM;WHITE	83	EA	
0566692	TROUSERS:CLEAN CONDITION;152 CM;WHITE	83	EA	
0566693	TROUSERS:CLEAN CONDITION;157 CM;WHITE	83	EA	
0566738	MASK RSPT:HALF DISPOSABLE;ADJUSTABLE	66 667	EA	
0566568	BOOTS SFTY:3;STRD; STL OR CARBON FIBER	300	PAA	
0222581	BOOTS SFTY:4;STRD; STL OR CARBON FIBER	300	PAA	
0222582	BOOTS SFTY:5;STRD; STL OR CARBON FIBER	500	PAA	
0222583	BOOTS SFTY:6;STRD; STL OR CARBON FIBER	600	PAA	
0222584	BOOTS SFTY:7;STRD; STL OR CARBON FIBER	1 000	PAA	
0222585	BOOTS SFTY:8;STRD; STL OR CARBON FIBER	1 000	PAA	
0222586	BOOTS SFTY:9;STRD; STL OR CARBON FIBER	800	PAA	
0222587	BOOTS SFTY:10;STRD; STL OR CARBON FIBER	500	PAA	
0566564	BOOTS SFTY:11;STRD; STL OR CARBON FIBER	250	PAA	
0566565	BOOTS SFTY:12;STRD; STL OR CARBON FIBER	150	PAA	
0566569	BOOTS SFTY:13;STRD; STL OR CARBON FIBER	100	PAA	
0566572	SHOES SFTY:3;STRD; STL OR CARBON FIBER	300	PAA	
0235901	SHOES SFTY:4;STRD; STL OR CARBON FIBER	300	PAA	
0566573	SHOES SFTY:13;STRD; STL OR CARBON FIBER	100	PAA	
0235903	SHOES SFTY:6;STRD; STL OR CARBON FIBER	600	PAA	
0235904	SHOES SFTY:7;STRD; STL OR CARBON FIBER	1 000	PAA	
0235905	SHOES SFTY:8;STRD; STL OR CARBON FIBER	1 000	PAA	
0235906	SHOES SFTY:9;STRD; STL OR CARBON FIBER	800	PAA	
0235907	SHOES SFTY:10;STRD; STL OR CARBON FIBER	500	PAA	
0566575	SHOES SFTY:11;STRD; STL OR CARBON FIBER	250	PAA	
0566576	SHOES SFTY:12;STRD; STL OR CARBON FIBER	150	PAA	
0235902	SHOES SFTY:5;STRD; STL OR CARBON FIBER	500	PAA	

Note:

- The above prices exclude VAT, but include consumable, accommodation (if applicable), bonuses (if applicable) transport & travelling costs and all other associated costs.
- ♦ **Suppliers are not, under any circumstances, to deviate from the required stipulated format for the provision of pricing.**

## PART 3: SCOPE OF WORK

### SUPPLY AND DELIVER ITEMS LISTED ON THE PRICE SCHEDULE

- Drawings will be provided Annexure C : **Not Applicable**

Document reference	Title
	This cover page
C3.1	<i>Purchaser's</i> Goods Information
C3.2	<i>Supplier's</i> Goods Information

### C3.1: *PURCHASER'S* GOODS INFORMATION

#### Contents

**Part 3: Scope of Work** Error! Bookmark not defined.

#### **C3.1: *Purchaser's* Goods Information** 8

<b>1</b>	<b>Overview and purpose of the <i>goods</i> and <i>services</i></b>	Error! Bookmark not defined.
<b>2</b>	<b>Specification and description of the <i>goods</i></b>	Error! Bookmark not defined.
2.1	<i>Purchaser's</i> design .....	62
2.2	Procedure for submission and acceptance of <i>Supplier's</i> design .....	62
2.3	Other requirements of the <i>Supplier's</i> design .....	62
2.4	Use of <i>Supplier's</i> design .....	62
2.5	Manufacture & fabrication .....	62
2.6	Factory acceptance testing (FAT) .....	62
2.7	Other tests and inspections and commissioning in place of use .....	62
2.8	Operating manuals and maintenance schedules .....	63
<b>3</b>	<b>Supply Requirements</b>	<b>63</b>
<b>4</b>	<b>Specification of the <i>services</i> to be provided</b>	<b>63</b>
<b>5</b>	<b>Constraints on how the <i>Supplier</i> Provides the Goods</b>	<b>63</b>
5.1	Programming constraints .....	63
5.2	Work to be done by the Delivery Date .....	63
5.3	Marking the <i>goods</i> .....	63
5.4	Constraints at the delivery place and place of use .....	63
5.5	Cooperating with Others .....	63
5.6	Services & other things to be provided by the <i>Purchaser</i> or <i>Supplier</i> .....	63



5.7	Management meetings .....	<b>Error! Bookmark not defined.</b>
5.8	Documentation control .....	<b>Error! Bookmark not defined.</b>
5.9	Health and safety risk management .....	63
5.10	Environmental constraints and management .....	64
5.11	Quality .....	64
5.12	Invoicing and payment .....	66
5.13	Insurance provided by the <i>Purchaser</i> .....	67
5.14	Contract change management .....	67
5.15	Provision of bonds and guarantees .....	67
5.16	Records of Defined Cost, payments & assessments of compensation events to be kept by the <i>Supplier</i> .....	67
<b>6</b>	<b>Procurement</b> .....	<b>Error! Bookmark not defined.</b>
	<b>6.1 Subcontracting</b> .....	<b>Error! Bookmark not defined.</b>
	6.1.1 Preferred subSuppliers .....	<b>Error! Bookmark not defined.</b>
	6.1.2 Limitations on subcontracting .....	<b>Error! Bookmark not defined.</b>
	6.1.3 Spares and consumables .....	<b>Error! Bookmark not defined.</b>
	6.1.4 Other requirements related to procurement .....	<b>Error! Bookmark not defined.</b>
	6.1.5 Cataloguing requirements .....	<b>Error! Bookmark not defined.</b>
<b>7</b>	<b>List of drawings</b> .....	<b>Error! Bookmark not defined.</b>
	7.1 Drawings issued by the <i>Purchaser</i> .....	<b>Error! Bookmark not defined.</b>
<b>C3.2</b>	<b>Supplier's Goods Information</b> .....	<b>Error! Bookmark not defined.</b>

## 1 Overview and purpose of the *goods and services*

- Supply and delivery of EFP Leak-Off valve spares at Hendrina Power Station- Main Stores on an "as and when required" basis.

## 2 Specification and description of the *goods*

- As per full technical specification given on Goods Information / Price schedule Specifications (include Environmental specification) and drawing Numbers (where applicable).The *Supplier* implements a quality system and maintains the quality system until the delivery of all consumables. The system will be to the *Purchaser's* satisfaction and will be accepted prior to the signing of the *contract*. The *Supplier* will be subject to periodic audits by the *Purchaser* in order to ensure compliance with the system. Any deviations will be corrected to the *Purchaser's* satisfaction.

## Technical Specifications

Material	Short Text	Short Text
0222478	TROUSERS:MEN LONG;127 CM;BLUE NAVY	TROUSERS: TYPE: MEN LONG; SIZE: 127 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0172193	JACKET,UTILITY:OPERATING;137 CM	JACKET, UTILITY: TYPE: OPERATING; SIZE: 137 CM; MATERIAL: FABRIC COTTON 100 PCT SANS1387-4 D59 SOFT WOVEN PRE-SHRUNK FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: CHEST 1, SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM ; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0179714	JACKET,UTILITY:OPERATING;157 CM	JACKET, UTILITY: TYPE: OPERATING; SIZE: 157 CM; MATERIAL: FABRIC COTTON 100 PCT SANS1387-4 D59 SOFT WOVEN PRE-SHRUNK FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: CHEST 1, SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH

		<p>HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM ; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).</p>
0222468	TROUSERS:MEN LONG;82 CM;BLUE NAVY	<p>TROUSERS: TYPE: MEN LONG; SIZE: 82 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).</p>
0222469	TROUSERS:MEN LONG;87 CM;BLUE NAVY	<p>TROUSERS: TYPE: MEN LONG; SIZE: 87 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).</p>
0222470	TROUSERS:MEN LONG;92 CM;BLUE NAVY	<p>TROUSERS: TYPE: MEN LONG; SIZE: 92 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).</p>
0222471	TROUSERS:MEN LONG;97 CM;BLUE NAVY	<p>TROUSERS: TYPE: MEN LONG; SIZE: 97 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).</p>
0222472	TROUSERS:MEN LONG;102 CM;BLUE NAVY	<p>TROUSERS: TYPE: MEN LONG; SIZE: 102 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).</p>
0222473	TROUSERS:MEN LONG;107 CM;BLUE NAVY	<p>TROUSERS: TYPE: MEN LONG; SIZE: 107 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS</p>

		TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0222474	TROUSERS:MEN LONG;112 CM;BLUE NAVY	TROUSERS: TYPE: MEN LONG; SIZE: 112 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0222476	TROUSERS:MEN LONG;117 CM;BLUE NAVY	TROUSERS: TYPE: MEN LONG; SIZE: 117 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0222477	TROUSERS:MEN LONG;122 CM;BLUE NAVY	TROUSERS: TYPE: MEN LONG; SIZE: 122 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0222479	TROUSERS:MEN LONG;132 CM;BLUE NAVY	TROUSERS: TYPE: MEN LONG; SIZE: 132 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0222480	TROUSERS:MEN LONG;137 CM;BLUE NAVY	TROUSERS: TYPE: MEN LONG; SIZE: 137 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0222481	TROUSERS:MEN LONG;142 CM;BLUE NAVY	TROUSERS: TYPE: MEN LONG; SIZE: 142 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0222482	TROUSERS:MEN LONG;147 CM;BLUE NAVY	TROUSERS: TYPE: MEN LONG; SIZE: 147 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET

		AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OF APPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0222535	JACKET,UTILITY:OPERATING;87 CM	JACKET, UTILITY: TYPE: OPERATING; SIZE: 87 CM; MATERIAL: FABRIC COTTON 100 PCT SANS1387-4 D59 SOFT WOVEN PRE-SHRUNK FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: CHEST 1, SIDE 2; GARMENT CLOSING METHOD: ZIP SANS1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM ; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER.
0222536	JACKET,UTILITY:OPERATING;97 CM	JACKET, UTILITY: TYPE: OPERATING; SIZE: 97 CM; MATERIAL: FABRIC COTTON 100 PCT SANS1387-4 D59 SOFT WOVEN PRE-SHRUNK FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: CHEST 1, SIDE 2; GARMENT CLOSING METHOD: ZIP SANS1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP

		THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER.
0222537	JACKET,UTILITY:OPERATING;107 CM	JACKET, UTILITY: TYPE: OPERATING; SIZE: 107 CM; MATERIAL: FABRIC COTTON 100 PCT SANS1387-4 D59 SOFT WOVEN PRE-SHRUNK FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: CHEST 1, SIDE 2; GARMENT CLOSING METHOD: ZIP SANS1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM ; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION
0222538	JACKET,UTILITY:OPERATING;117 CM	JACKET, UTILITY: TYPE: OPERATING; SIZE: 117 CM; MATERIAL: FABRIC COTTON 100 PCT SANS1387-4 D59 SOFT WOVEN PRE-SHRUNK FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: CHEST 1, SIDE 2; GARMENT CLOSING METHOD: ZIP SANS1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST

		30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM ; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION
0222539	JACKET,UTILITY:OPERATING;122 CM	JACKET, UTILITY: TYPE: OPERATING; SIZE: 122 CM; MATERIAL: FABRIC COTTON 100 PCT SANS1387-4 D59 SOFT WOVEN PRE-SHRUNK FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: CHEST 1, SIDE 2; GARMENT CLOSING METHOD: ZIP SANS1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMaking AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM ; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER.
0222540	JACKET,UTILITY:OPERATING;132 CM	JACKET, UTILITY: TYPE: OPERATING; SIZE: 132 CM; MATERIAL: FABRIC COTTON 100 PCT SANS1387-4 D59 SOFT WOVEN PRE-SHRUNK FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: CHEST 1, SIDE 2; GARMENT CLOSING METHOD: ZIP SANS1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMaking AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN

		THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM ; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION
0566481	JACKET,UTILITY:OPERATING;77 CM	JACKET, UTILITY: TYPE: OPERATING; SIZE: 77 CM; MATERIAL: FABRIC COTTON 100 PCT SANS1387-4 D59 SOFT WOVEN PRE-SHRUNK FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER
0566482	JACKET,UTILITY:OPERATING;82 CM	JACKET, UTILITY: TYPE: OPERATING; SIZE: 82 CM; MATERIAL: FABRIC COTTON 100 PCT SANS1387-4 D59 SOFT WOVEN PRE-SHRUNK FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET



		<p>FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER</p>
0566494	JACKET,UTILITY:OPERATING;102 CM	<p>JACKET, UTILITY: TYPE: OPERATING; SIZE: 102 CM; MATERIAL: FABRIC COTTON 100 PCT SANS1387-4 D59 SOFT WOVEN PRE-SHRUNK FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER</p>
0566503	JACKET,UTILITY:OPERATING;112 CM	<p>JACKET, UTILITY: TYPE: OPERATING; SIZE: 112 CM; MATERIAL: FABRIC COTTON 100 PCT SANS1387-4 D59 SOFT WOVEN PRE-SHRUNK FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND</p>

		GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER
0566511	JACKET,UTILITY:OPERATING;127 CM	JACKET, UTILITY: TYPE: OPERATING; SIZE: 127 CM; MATERIAL: FABRIC COTTON 100 PCT SANS1387-4 D59 SOFT WOVEN PRE-SHRUNK FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER
0566512	JACKET,UTILITY:OPERATING;142 CM	JACKET, UTILITY: TYPE: OPERATING; SIZE: 142 CM; MATERIAL: FABRIC COTTON 100 PCT SANS1387-4 D59 SOFT WOVEN PRE-SHRUNK FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE

		<p>THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER</p>
0566513	JACKET,UTILITY:OPERATING;152 CM	<p>JACKET, UTILITY: TYPE: OPERATING; SIZE: 152 CM; MATERIAL: FABRIC COTTON 100 PCT SANS1387-4 D59 SOFT WOVEN PRE-SHRUNK FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER</p>
0566544	JACKET,UTILITY:OPERATING;92 CM	<p>JACKET, UTILITY: TYPE: OPERATING; SIZE: 92 CM; MATERIAL: FABRIC COTTON 100 PCT SANS1387-4 D59 SOFT WOVEN PRE-SHRUNK FLAME RETARDANT; COLOR: BLUE SANS CKS129-179C-2006; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS</p>

		GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMaking AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER
0566736	TROUSERS:MEN LONG;152 CM;BLUE NAVY	TROUSERS: TYPE: MEN LONG; SIZE: 152 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0566737	TROUSERS:MEN LONG;157 CM;BLUE NAVY	TROUSERS: TYPE: MEN LONG; SIZE: 157 CM; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; PANTONE 19 - 3920; MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE) TYPE D59 FLAME RETARDANT; STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO ON RIGHT BACK POCKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS; TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELEVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0222499	TROUSERS:LADIES LONG;26; 67;BLUE NAVY	TROUSERS: TYPE: LADIES LONG; SIZE: 26; 67; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0222500	TROUSERS:LADIES LONG;28; 72;BLUE NAVY	TROUSERS: TYPE: LADIES LONG; SIZE: 28; 72; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0222501	TROUSERS:LADIES LONG;30; 77;BLUE NAVY	TROUSERS: TYPE: LADIES LONG; SIZE: 30; 77; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE

		PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0222502	TROUSERS:LADIES LONG;32; 82;BLUE NAVY	TROUSERS: TYPE: LADIES LONG; SIZE: 32; 82; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0222503	TROUSERS:LADIES LONG;34; 87;BLUE NAVY	TROUSERS: TYPE: LADIES LONG; SIZE: 34; 87; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE)
0222504	TROUSERS:LADIES LONG;36; 92;BLUE NAVY	TROUSERS: TYPE: LADIES LONG; SIZE: 36; 92; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0222505	TROUSERS:LADIES LONG;38; 97;BLUE NAVY	TROUSERS: TYPE: LADIES LONG; SIZE: 38; 97; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0222506	TROUSERS:LADIES LONG;40; 102;BLUE NAVY	TROUSERS: TYPE: LADIES LONG; SIZE: 40; 102; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0222507	TROUSERS:LADIES LONG;42; 107;BLUE NAVY	TROUSERS: TYPE: LADIES LONG; SIZE: 42; 107; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF

		THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0222508	TROUSERS:LADIES LONG;44; 112;BLUE NAVY	TROUSERS: TYPE: LADIES LONG; SIZE: 44; 112; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0222509	TROUSERS:LADIES LONG;46; 117;BLUE NAVY	TROUSERS: TYPE: LADIES LONG; SIZE: 46; 117; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0222510	TROUSERS:LADIES LONG;48; 122;BLUE NAVY	TROUSERS: TYPE: LADIES LONG; SIZE: 48; 122; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0222511	TROUSERS:LADIES LONG;50; 127;BLUE NAVY	TROUSERS: TYPE: LADIES LONG; SIZE: 50; 127; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0222512	TROUSERS:LADIES LONG;52; 132;BLUE NAVY	TROUSERS: TYPE: LADIES LONG; SIZE: 52; 132; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE

		PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0222513	TROUSERS:LADIES LONG;54; 137;BLUE NAVY	TROUSERS: TYPE: LADIES LONG; SIZE: 54; 137; COLOR: BLUE NAVY; MATERIAL: COTTON, D59; SPECIFICATION: 240-44175132; FLAME RETARDANT SANS 1423-1 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; PANTONE REFERENCE 19-3920; THE SIZE SHALL COMPLY WITH THE SIZE SPECIFICATION IN ANNEX A; LONG PANTS SHALL HAVE REVERSE PLEATS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH A ZIP FRONT AND ONE BUTTON ON THE FRONT OF THE WAISTBAND AND A PLAIN BOTTOM; THE WAISTBAND SHALL BE 38-40 MM IN WIDTH; THE PANTS SHALL HAVE 2 SIDE POCKETS; THE STITCHING SHALL COMPLY WITH SANS 10101 AND THREADS TO SANS 1362; THE ZIP FASTENER SHALL COMPLY WITH SANS 1822 STYLE A FIGURE 3 AND BE OF A NON-CONDUCTIVE MATERIAL; REFLECTIVE STRIPS TO BE FITTED ON BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE LEFT BACK POCKET AND THE ESKOM LOGO SHALL BE EMBROIDERED ON THE RIGHT BACK POCKET IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0566548	JACKET,UTILITY:ACID/ALKALI;102 CM	JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 102 CM; MATERIAL: FABRIC COTTON 100 PCT SANS1387-4 D59 SOFT WOVEN PRE-SHRUNK FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMaking AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER
0566454	JACKET,UTILITY:ACID/ALKALI;107 CM	JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 107 CM; MATERIAL: FABRIC COTTON 100 PCT SANS1387-4 D59 SOFT WOVEN PRE-SHRUNK FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH

		<p>HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).</p>
0566552	JACKET,UTILITY:ACID/ALKALI;112 CM	<p>JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 112 CM; MATERIAL: FABRIC COTTON 100 PCT SANS1387-4 D59 SOFT WOVEN PRE-SHRUNK FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER</p>
0566455	JACKET,UTILITY:ACID/ALKALI;117 CM	<p>JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 117 CM; MATERIAL: FABRIC COTTON 100 PCT SANS1387-4 D59 SOFT WOVEN PRE-SHRUNK FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF</p>



		<p>WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMaking AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER</p>
0566456	JACKET,UTILITY:ACID/ALKALI;122 CM	<p>JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 122 CM; MATERIAL: FABRIC COTTON 100 PCT SANS1387-4 D59 SOFT WOVEN PRE-SHRUNK FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMaking AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER</p>
0566549	JACKET,UTILITY:ACID/ALKALI;127 CM	<p>JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 127 CM; MATERIAL: FABRIC COTTON 100 PCT SANS1387-4 D59 SOFT WOVEN PRE-SHRUNK FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE</p>

		<p>OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER</p>
0566457	JACKET,UTILITY:ACID/ALKALI;132 CM	<p>JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 132 CM; MATERIAL: FABRIC COTTON 100 PCT SANS1387-4 D59 SOFT WOVEN PRE-SHRUNK FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER</p>
0566458	JACKET,UTILITY:ACID/ALKALI;137 CM	<p>JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 137 CM; MATERIAL: FABRIC COTTON 100 PCT SANS1387-4 D59 SOFT WOVEN PRE-SHRUNK FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER;</p>

		<p>THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMaking AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER</p>
0566550	JACKET,UTILITY:ACID/ALKALI;142 CM	<p>JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 142 CM; MATERIAL: FABRIC COTTON 100 PCT SANS1387-4 D59 SOFT WOVEN PRE-SHRUNK FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMaking AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER</p>
0566459	JACKET,UTILITY:ACID/ALKALI;147 CM	<p>JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 147 CM; MATERIAL: FABRIC COTTON 100 PCT SANS1387-4 D59 SOFT WOVEN PRE-SHRUNK FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED</p>

		<p>TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).</p>
0566551	JACKET,UTILITY:ACID/ALKALI;152 CM	<p>JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 152 CM; MATERIAL: FABRIC COTTON 100 PCT SANS1387-4 D59 SOFT WOVEN PRE-SHRUNK FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).</p>
0566460	JACKET,UTILITY:ACID/ALKALI;157 CM	<p>JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 157 CM; MATERIAL: FABRIC COTTON 100 PCT SANS1387-4 D59 SOFT WOVEN PRE-SHRUNK FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS:</p>

		<p>THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).</p>
0566545	JACKET,UTILITY:ACID/ALKALI;77 CM	<p>JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 77 CM; MATERIAL: FABRIC COTTON 100 PCT SANS1387-4 D59 SOFT WOVEN PRE-SHRUNK FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).</p>
0566546	JACKET,UTILITY:ACID/ALKALI;82 CM	<p>JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 82 CM; MATERIAL: FABRIC COTTON 100 PCT SANS1387-4 D59 SOFT WOVEN PRE-SHRUNK FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN;</p>

		<p>FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).</p>
0566452	JACKET,UTILITY:ACID/ALKALI;87 CM	<p>JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 87 CM; MATERIAL: FABRIC COTTON 100 PCT SANS1387-4 D59 SOFT WOVEN PRE-SHRUNK FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM ; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).</p>
0566547	JACKET,UTILITY:ACID/ALKALI;92 CM	<p>JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 92 CM; MATERIAL: FABRIC COTTON 100 PCT SANS1387-4 D59 SOFT WOVEN PRE-SHRUNK FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS;</p>

		<p>THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMaking AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).</p>
0566453	JACKET,UTILITY:ACID/ALKALI;97 CM	<p>JACKET, UTILITY: TYPE: ACID/ALKALI; SIZE: 97 CM; MATERIAL: FABRIC COTTON 100 PCT SANS1387-4 D59 SOFT WOVEN PRE-SHRUNK FLAME RETARDANT; COLOR: BOTTLE GREEN 19_6110TC; POCKET TYPE: CHEST 1; SIDE 2; GARMENT CLOSING METHOD: ZIP SANS 1822; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE AN OPEN TYPE WITH FASTENINGS; THE JACKET BOTTOM SHALL HAVE A PLAIN HEM; WITHOUT SIDE VENTS; POCKETS SHALL BE AS REQUIRED (SEE ANNEX A) AND WITHOUT FLAPS; FOR BOTTOM POCKETS; SLEEVES SHALL BE ONE-PIECE LONG AND SET-IN; FRONT EDGES SHALL HAVE GROWN-ON FACINGS OF WIDTH AT LEAST 45 MM AND THE INSIDE EDGES NEATLY FINISHED; EACH FRONT PANEL SHALL NOT HAVE A YOKE AND BE AS FOLLOWS: A) SLIDE FASTENER FRONTS: THE FRONTS SHALL FASTEN WITH A SLIDE FASTENER THAT EXTENDS TO AT LEAST 90 MM ABOVE THE BOTTOM HEM; SLIDE FASTENER IS CONCEALED AND STITCHED DOWN; SLIDE FASTENERS SHALL BE SECURED TO THE FRONTS WITH TWO ROWS OF STITCHING ALONG EACH STRINGER; THE BACK SHALL BE PLAIN (NO CENTRE BACK SEAM); SLEEVES SHALL BE OF THE ONE-PIECE; THE END OF SLEEVE SHALL HAVE A PLAIN CUFF OF WIDTH AT LEAST 15 MM; POCKETS SHALL BE PATCH POCKETS OF OUTER MATERIAL AND SHALL HAVE ROUND BLUNTED CORNERS; POCKET MOUTH HEMS SHALL BE OF FINISHED WIDTH 10 MM OR 20 MM (SEE 4.5.14); BREAST AND SIDE POCKETS SHALL BE OF FINISHED MEASUREMENT AS GIVEN IN TABLE 6; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMaking AND GARMENT CONSTRUCTION PRACTICE; POCKET FLAPS A BREAST POCKET FLAP SHALL BE MITRED; LINED WITH OUTER MATERIAL AND FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; A FLAP SHALL BE OF DEPTH AT LEAST 50 MM AT THE MITRED POINT AND TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH LENGTH AS TO OVERLAP THE POCKET WIDTH; SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SHALL BE SECURELY TACKED AT EACH END; THE BOTTOM OF A JACKET SHALL BE FINISHED WITH A PLAIN HEM; THE BOTTOM OF A JACKET SHALL HAVE A DOUBLE FOLDED HEM OF FINISHED WIDTH AT LEAST 15 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).</p>
0576288	TROUSERS:ACID/ALKALI;87 CM;GREEN BOTTLE	<p>TROUSERS: TYPE: ACID/ALKALI; SIZE: 87 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434</p>

		(DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0576301	TROUSERS:ACID/ALKALI;92 CM;GREEN BOTTLE	TROUSERS: TYPE: ACID/ALKALI; SIZE: 92 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0576295	TROUSERS:ACID/ALKALI;127 CM;GREEN BOTTLE	TROUSERS: TYPE: ACID/ALKALI; SIZE: 127 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0576297	TROUSERS:ACID/ALKALI;137 CM;GREEN BOTTLE	TROUSERS: TYPE: ACID/ALKALI; SIZE: 137 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0576286	TROUSERS:ACID/ALKALI;77;GREEN BOTTLE	TROUSERS: TYPE: ACID/ALKALI; SIZE: 77; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; LEG LENGTH: LONG; FIT: REGULAR; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0576293	TROUSERS:ACID/ALKALI;117 CM;GREEN BOTTLE	TROUSERS: TYPE: ACID/ALKALI; SIZE: 117 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0576294	TROUSERS:ACID/ALKALI;122 CM;GREEN BOTTLE	TROUSERS: TYPE: ACID/ALKALI; SIZE: 122 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132;



		VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0576299	TROUSERS:ACID/ALKALI;147 CM;GREEN BOTTLE	TROUSERS: TYPE: ACID/ALKALI; SIZE: 147 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0576296	TROUSERS:ACID/ALKALI;132 CM;GREEN BOTTLE	TROUSERS: TYPE: ACID/ALKALI; SIZE: 132 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0576287	TROUSERS:ACID/ALKALI;82 CM;GREEN BOTTLE	TROUSERS: TYPE: ACID/ALKALI; SIZE: 82 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0576291	TROUSERS:ACID/ALKALI;107 CM;GREEN BOTTLE	TROUSERS: TYPE: ACID/ALKALI; SIZE: 107 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0576290	TROUSERS:ACID/ALKALI;102 CM;GREEN BOTTLE	TROUSERS: TYPE: ACID/ALKALI; SIZE: 102 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0576298	TROUSERS:ACID/ALKALI;142 CM;GREEN BOTTLE	TROUSERS: TYPE: ACID/ALKALI; SIZE: 142 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0576289	TROUSERS:ACID/ALKALI;97 CM;GREEN BOTTLE	TROUSERS: TYPE: ACID/ALKALI; SIZE: 97 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE

		GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0576292	TROUSERS:ACID/ALKALI;112 CM;GREEN BOTTLE	TROUSERS: TYPE: ACID/ALKALI; SIZE: 112 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0576302	TROUSERS:ACID/ALKALI;157 CM;GREEN BOTTLE	TROUSERS: TYPE: ACID/ALKALI; SIZE: 157 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0576300	TROUSERS:ACID/ALKALI;152 CM;GREEN BOTTLE	TROUSERS: TYPE: ACID/ALKALI; SIZE: 152 CM; COLOR: GREEN BOTTLE; MATERIAL: D59 FLAME RETARDANT; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INTERNATIONAL ACID RESISTANT MATERIAL BOTTLE GREEN PANTONE 19_6110TC: MINIMUM STANDARD SPECIFICATIONS FOR TROUSER AS PER SANS 434 (DRG.15289DA) FOR WORK WEAR SUITS (TWO PIECE); STANDARD SPEC: STITCHING SANS10101; ZIP FASTENER SANS1822 (NON-CONDUCTIVE MATERIAL); THREAD SANS1362; POCKETS TWO ON BACK TWO SWING AND ONE PATCH POCKET; ZERO HARM IDENTIFICATION ON THE LEFT BACKPOCKET AND THE ESKOM LOGO ON RIGHT BACK PACKET EMBROIDERED IDENTIFICATION INDELIBLE MNFRS TRADEMARK; SIZE/CLEANING/LAUNDRY INSTRUCTIONS/SABS MARK OFAPPROVAL ON ALL RELAVANT ITEMS AS PER UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0566600	COVERALL:ACID/ALKALI;77 CM	COVERALL: TYPE: ACID/ALKALI; SIZE: 77 CM; MATERIAL: COTTON 100 PCT D59 WOVEN PRESHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE

		<p>WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).</p>
0566601	COVERALL:ACID/ALKALI;82 CM	<p>COVERALL: TYPE: ACID/ALKALI; SIZE: 82 CM; MATERIAL: COTTON 100 PCT D59 WOVEN PRESHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY</p>

		ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0566602	COVERALL:ACID/ALKALI;87 CM	COVERALL: TYPE: ACID/ALKALI; SIZE: 87 CM; MATERIAL: COTTON 100 PCT D59 WOVEN PRESHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0566603	COVERALL:ACID/ALKALI;92 CM	COVERALL: TYPE: ACID/ALKALI; SIZE: 92 CM; MATERIAL: COTTON 100 PCT D59 WOVEN PRESHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF

		<p>ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14)</p> <p>BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).</p>
0566604	COVERALL:ACID/ALKALI;97 CM	<p>COVERALL: TYPE: ACID/ALKALI; SIZE: 97 CM; MATERIAL: COTTON 100 PCT D59 WOVEN PRESHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14)</p> <p>BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY;</p>

		<p>THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).</p>
0566605	COVERALL:ACID/ALKALI;102 CM	<p>COVERALL: TYPE: ACID/ALKALI; SIZE: 102 CM; MATERIAL: COTTON 100 PCT D59 WOVEN PRESHUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH</p>

		<p>WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).</p>
0566606	COVERALL:ACID/ALKALI;107 CM	<p>COVERALL: TYPE: ACID/ALKALI; SIZE: 107 CM; MATERIAL: COTTON 100 PCT D59 WOVEN PRESHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).</p>
0566607	COVERALL:ACID/ALKALI;112 CM	<p>COVERALL: TYPE: ACID/ALKALI; SIZE: 112 CM; MATERIAL: COTTON 100 PCT D59 WOVEN PRESHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM;</p>

		<p>THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).</p>
0566608	COVERALL:ACID/ALKALI;117 CM;THE FRONTS	<p>COVERALL: TYPE: ACID/ALKALI; SIZE: 117 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER</p>



		<p>MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).</p>
0566609	COVERALL:ACID/ALKALI;122 CM	<p>COVERALL: TYPE: ACID/ALKALI; SIZE: 122 CM; MATERIAL: COTTON 100 PCT D59 WOVEN PRESHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).</p>
0566610	COVERALL:ACID/ALKALI;127 CM	<p>COVERALL: TYPE: ACID/ALKALI; SIZE: 127 CM; MATERIAL: COTTON 100 PCT D59 WOVEN PRESHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH</p>

		<p>A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).</p>
0566611	COVERALL:ACID/ALKALI;132 CM;THE FRONTS	<p>COVERALL: TYPE: ACID/ALKALI; SIZE: 132 CM; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE</p>

		<p>POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).</p>
0566612	COVERALL:ACID/ALKALI;137;THE FRONTS	<p>COVERALL: TYPE: ACID/ALKALI; SIZE: 137; MATERIAL: COTTON 100 PCT, D59 WOVEN PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).</p>
0566613	COVERALL:ACID/ALKALI;142 CM	<p>COVERALL: TYPE: ACID/ALKALI; SIZE: 142 CM; MATERIAL: COTTON 100 PCT D59 WOVEN PRESHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING</p>

		<p>SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14)</p> <p>BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).</p>
0566614	COVERALL:ACID/ALKALI;147 CM	<p>COVERALL: TYPE: ACID/ALKALI; SIZE: 147 CM; MATERIAL: COTTON 100 PCT D59 WOVEN PRESHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14)</p> <p>BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH</p>

		<p>POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).</p>
0566615	COVERALL: ACID/ALKALI;152 CM	<p>COVERALL: TYPE: ACID/ALKALI; SIZE: 152 CM; MATERIAL: COTTON 100 PCT D59 WOVEN PRESHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM; VENDORS ARE RESPONSIBLE</p>

		FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0566616	COVERALL:ACID/ALKALI;157 CM	COVERALL: TYPE: ACID/ALKALI; SIZE: 157 CM; MATERIAL: COTTON 100 PCT D59 WOVEN PRESHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE FRONTS SHALL BE SHIRT-STYLE OPEN FRONTS WITH A COLLAR; THE BACK BE CUT IN ONE PIECE AND SHALL BE JOINED TO THE TROUSER SECTION BY MEANS OF A SEAM AT WAIST LEVEL; THE WAISTLINE SHALL REQUIRE ELASTICIZED FROM SIDE SEAM TO SIDE SEAM; THE COLLAR SHAPE SHALL BE SUCH AS TO BE ACCEPTABLE; THE WIDTH AT THE CENTRE BACK SHALL BE AT LEAST 80 MM AND THE STEPS SHALL BE OF WIDTH AT LEAST 35 MM; SLEEVES SET-IN SLEEVES SHALL BE OF ONE-PIECE CONSTRUCTION AND BE FITTED WITH A CUFF AT THE BOTTOM END; CUFFS PLAIN WITH A DOUBLE FOLDED TURNED-IN HEM OF AT LEAST 15 MM; THE FRONT FASTENING AT BOTTOM OF THE OPENING SHALL BE SECURELY BAR-TACKED; ALL RAW EDGES SHALL BE TURNED IN AND STITCHED; FLY FRONT SHALL FASTEN WITH A SLIDE FASTENER AS PER SANS 1822 FIGURE 4 TWO WAY FASTENER TYPE A; THE SLIDE FASTENER SHALL BE SECURED WITH TWO ROWS OF STITCHING ON EACH STRINGER; THE FRONT EDGES SHALL OVERLAP AT LEAST 35 MM AND THE FACING SHALL BE GROWN ON; POCKETS THE FINISHED WIDTH AND DEPTH OF A POCKET SHALL BE MEASURED FROM EDGE TO EDGE ON THE OUTSIDE OF THE POCKET WITH PENCIL POCKET; POCKET MOUTHS SHALL BE FINISHED WITH A HEM THAT IS DEEP ENOUGH TO ACCOMMODATE THE ATTACHMENT OF A FASTENING; AND SHALL BE ADEQUATELY SECURED (SEE 4.5.14) BREAST; HIP POCKETS: SHALL BE PATCH POCKETS; WITH ROUNDED BLUNTED CORNERS; THE SIDE AND BOTTOM EDGES OF A POCKET SHALL BE TURNED IN AT LEAST 10 MM AND STITCHED DOWN WITH TWO ROWS OF STITCHING OF AT LEAST 2 MM AND A MAXIMUM 10 MM RESPECTIVELY; THE MOUTH OF THE POCKET SHALL BE HEMMED AT EACH END OF THE POCKET MOUTH AND SHALL BE SECURELY BAR-TACKED; THE BREAST POCKET SHALL BE POSITIONED ABOVE THE SCYE LEVEL IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE; THE HIP POCKET SHALL BE POSITIONED APPROPRIATELY FROM THE SIDE SEAM IN ACCORDANCE WITH ACCEPTABLE PATTERNMAKING PRACTICE AND AT LEAST 60 MM FROM THE WAIST SEAM; SIDE POCKETS SHALL HAVE A SLANTED MOUTH OPENING OF MINIMUM FINISHED LENGTH 180 MM AND SHALL HAVE AN INSIDE PATCH POCKET OF OUTER MATERIAL; PENCIL POCKET SHALL FORM PART OF THE BREAST POCKET AND OF WIDTH AT LEAST 40 MM AND THE FULL DEPTH OF THE BREAST POCKET; AND SHALL BE POSITIONED AT THE CENTRE FRONT END OF BREAST POCKET; THE PENCIL POCKET SHALL BE FORMED BY A ROW OF VERTICAL STITCHING FROM THE FRONT EDGE; POCKET FLAPS SHALL BE MITRED; FLAPS SHALL BE LINED WITH OUTER MATERIAL AND SHALL FASTEN IN THE CENTRE WITH A BUTTON AND BUTTONHOLE; ALL FLAPS SHALL BE OF DEPTH AT LEAST 50 MM; AND A MITRED FLAP SHALL TAPER TO AT LEAST 30 MM AT THE ENDS; A FLAP SHALL BE OF SUCH WIDTH AS TO OVERLAP THE POCKET AT EACH SIDE AND SHALL BE POSITIONED AT LEAST 10 MM ABOVE THE POCKET MOUTH AND SECURELY TACKED AT EACH END; BUTTONHOLES SHALL BE LARGE ENOUGH TO NEATLY ACCOMMODATE THE BUTTONS AND SHALL BE AS FOLLOWS: IF FOUR-HOLE PLASTICS BUTTONS ARE USED; A SHIRT TYPE BUTTONHOLE MAY BE USED; THE BOTTOMS OF THE LEGS SHALL HAVE A PLAIN DOUBLE FOLDED HEM OF AT LEAST 15 MM; POCKET HEMS WITHOUT A FASTENER: SHALL BE STITCHED DOWN OF WIDTH AT LEAST 10 MM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0222553	JACKET UTIL:THERMAL;S; 34; 87	JACKET, UTILITY: TYPE: THERMAL; SIZE: S; 34; 87; MATERIAL: COTTON, D59, FLAME RETARDANT; COLOR: BLUE PANTO 19-3920; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INSULATED WITH PRE-SHRUNK HOLLOW FIBRE OR A NON-FLAMMABLE MATERIAL; WITH THE OUTER COVERING MADE OF PRE-SHRUNK 100 % WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59, AND FLAME RETARDANT; JACKET LENGTH: TO REACH BELOW THE BUTTOCKS; POCKETS: ONE CHEST POCKET SHALL BE BELLOWS TYPE - 15CM DEEP AND 14CM WIDE; 4 SIDE POCKETS; POCKETS TO HAVE FLAPS WITH CUT-OFF EDGES THAT CAN BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; THE SIDE POCKET SHALL BE THE BELLOWS TYPE WITH A SIDE ENTRY INTO ANOTHER SEPARATE POCKET AND SHALL BE 22CM DEEP AND 21CM WIDE; JACKETS SHALL HAVE NON-CONDUCTIVE PRESS STUDS DOWN THE FRONT ON A DOUBLE PANEL STRIP; AS WELL AS A NON-CONDUCTIVE ZIP; THE SLEEVE CUFFS SHALL HAVE TWO NON-CONDUCTIVE PRESS STUDS AT THE END OF THE SLEEVE SO THAT THE SIZE CAN BE ADJUSTED; IDENTIFICATION: INDELIBLE MNFRS TRADEMARK; REF NO. AND CLEANING INSTRUCTIONS INSIDE COLLAR ON JACKETS AND SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS; REFER TO UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).

0222554	JACKET UTIL:THERMAL;M; 38; 97	JACKET, UTILITY: TYPE: THERMAL; SIZE: M; 38; 97; MATERIAL: COTTON, D59, FLAME RETARDANT; COLOR: BLUE PANTO 19-3920; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INSULATED WITH PRE-SHRUNK HOLLOW FIBRE OR A NON-FLAMMABLE MATERIAL; WITH THE OUTER COVERING MADE OF PRE-SHRUNK 100 % WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; JACKET LENGTH TO REACH BELOW THE BUTTOCKS; POCKETS ONE CHEST POCKET SHALL BE BELLOWS TYPE - 15CM DEEP AND 14CM WIDE; 4 SIDE POCKETS; POCKETS TO HAVE FLAPS WITH CUT-OFF EDGES THAT CAN BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; THE SIDE POCKET SHALL BE THE BELLOWS TYPE WITH A SIDE ENTRY INTO ANOTHER SEPARATE POCKET AND SHALL BE 22CM DEEP AND 21CM WIDE; JACKETS SHALL HAVE NON-CONDUCTIVE PRESS STUDS DOWN THE FRONT ON A DOUBLE PANEL STRIP AS WELL AS A NON-CONDUCTIVE ZIP; THE SLEEVE CUFFS SHALL HAVE TWO NON-CONDUCTIVE PRESS STUDS AT THE END OF THE SLEEVE SO THAT THE SIZE CAN BE ADJUSTED; IDENTIFICATION: INDELIBLE MNFRS TRADEMARK REF NO. AND CLEANING INSTRUCTIONS INSIDE COLLAR ON JACKETS AND SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS; REFER TO UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0222555	JACKET UTIL:THERMAL;L; 42; 107	JACKET, UTILITY: TYPE: THERMAL; SIZE: L; 42; 107; MATERIAL: COTTON, D59, FLAME RETARDANT; COLOR: BLUE PANTO 19-3920; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INSULATED WITH PRE-SHRUNK HOLLOW FIBRE OR A NON-FLAMMABLE MATERIAL; WITH THE OUTER COVERING MADE OF PRE-SHRUNK 100 % WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; JACKET LENGTH TO REACH BELOW THE BUTTOCKS; POCKETS ONE CHEST POCKET SHALL BE BELLOWS TYPE - 15CM DEEP AND 14CM WIDE; 4 SIDE POCKETS; POCKETS TO HAVE FLAPS WITH CUT-OFF EDGES THAT CAN BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; THE SIDE POCKET SHALL BE THE BELLOWS TYPE WITH A SIDE ENTRY INTO ANOTHER SEPARATE POCKET AND SHALL BE 22CM DEEP AND 21CM WIDE; JACKETS SHALL HAVE NON-CONDUCTIVE PRESS STUDS DOWN THE FRONT ON A DOUBLE PANEL STRIP AS WELL AS A NON-CONDUCTIVE ZIP; THE SLEEVE CUFFS SHALL HAVE TWO NON-CONDUCTIVE PRESS STUDS AT THE END OF THE SLEEVE SO THAT THE SIZE CAN BE ADJUSTED; IDENTIFICATION: INDELIBLE MNFRS TRADEMARK REF NO. AND CLEANING INSTRUCTIONS INSIDE COLLAR ON JACKETS AND SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS; REFER TO UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0222556	JACKET UTIL:THERMAL;XL; 46; 117	JACKET, UTILITY: TYPE: THERMAL; SIZE: XL; 46; 117; MATERIAL: COTTON, D59, FLAME RETARDANT; COLOR: BLUE PANTO 19-3920; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INSULATED WITH PRE-SHRUNK HOLLOW FIBRE OR A NON-FLAMMABLE MATERIAL; WITH THE OUTER COVERING MADE OF PRE-SHRUNK 100 % WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; JACKET LENGTH TO REACH BELOW THE BUTTOCKS; POCKETS ONE CHEST POCKET SHALL BE BELLOWS TYPE - 15CM DEEP AND 14CM WIDE; 4 SIDE POCKETS; POCKETS TO HAVE FLAPS WITH CUT-OFF EDGES THAT CAN BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; THE SIDE POCKET SHALL BE THE BELLOWS TYPE WITH A SIDE ENTRY INTO ANOTHER SEPARATE POCKET AND SHALL BE 22CM DEEP AND 21CM WIDE; JACKETS SHALL HAVE NON-CONDUCTIVE PRESS STUDS DOWN THE FRONT ON A DOUBLE PANEL STRIP AS WELL AS A NON-CONDUCTIVE ZIP; THE SLEEVE CUFFS SHALL HAVE TWO NON-CONDUCTIVE PRESS STUDS AT THE END OF THE SLEEVE SO THAT THE SIZE CAN BE ADJUSTED; IDENTIFICATION: INDELIBLE MNFRS TRADEMARK REF NO. AND CLEANING INSTRUCTIONS INSIDE COLLAR ON JACKETS AND SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS; REFER TO UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0222558	JACKET UTIL:THERMAL;XXL; 48; 122	JACKET, UTILITY: TYPE: THERMAL; SIZE: XXL; 48; 122; MATERIAL: COTTON, D59, FLAME RETARDANT; COLOR: BLUE PANTO 19-3920; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INSULATED WITH PRE-SHRUNK HOLLOW FIBRE OR A NON-FLAMMABLE MATERIAL; WITH THE OUTER COVERING MADE OF PRE-SHRUNK 100 % WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; JACKET LENGTH TO REACH BELOW THE BUTTOCKS; POCKETS ONE CHEST POCKET SHALL BE BELLOWS TYPE - 15CM DEEP AND 14CM WIDE; 4 SIDE POCKETS; POCKETS TO HAVE FLAPS WITH CUT-OFF EDGES THAT CAN BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; THE SIDE POCKET SHALL BE THE BELLOWS TYPE WITH A SIDE ENTRY INTO ANOTHER SEPARATE POCKET AND SHALL BE 22CM DEEP AND 21CM WIDE; JACKETS SHALL HAVE NON-CONDUCTIVE PRESS STUDS DOWN THE FRONT ON A DOUBLE PANEL STRIP AS WELL AS A NON-CONDUCTIVE ZIP; THE SLEEVE CUFFS SHALL HAVE TWO NON-CONDUCTIVE PRESS STUDS AT THE END OF THE SLEEVE SO THAT THE SIZE CAN BE ADJUSTED; IDENTIFICATION: INDELIBLE MNFRS TRADEMARK REF NO. AND CLEANING INSTRUCTIONS INSIDE COLLAR ON JACKETS AND SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS; REFER TO UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0222559	JACKET UTIL:THERMAL;3XL;INSULATED	JACKET, UTILITY: TYPE: THERMAL; SIZE: 3XL; MATERIAL: COTTON, D59, FLAME RETARDANT; COLOR: BLUE PANTO 19-3920; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; INSULATED WITH PRE-SHRUNK HOLLOW FIBRE OR A NON-FLAMMABLE MATERIAL; WITH THE OUTER COVERING MADE OF PRE-SHRUNK 100 % WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; MATERIAL TYPE D59 AND FLAME RETARDANT; JACKET LENGTH TO REACH BELOW THE BUTTOCKS; POCKETS ONE CHEST POCKET SHALL BE BELLOWS TYPE - 15CM DEEP AND 14CM WIDE; 4 SIDE POCKETS; POCKETS TO HAVE FLAPS WITH CUT-OFF EDGES THAT CAN BE FASTENED BY MEANS OF NON-CONDUCTIVE BUTTONS; THE SIDE POCKET SHALL BE THE BELLOWS TYPE WITH A SIDE ENTRY INTO ANOTHER SEPARATE POCKET AND SHALL BE 22CM DEEP AND 21CM WIDE; JACKETS SHALL HAVE NON-CONDUCTIVE PRESS STUDS DOWN THE FRONT ON A DOUBLE PANEL STRIP AS WELL AS A NON-CONDUCTIVE ZIP; THE SLEEVE CUFFS SHALL HAVE TWO NON-CONDUCTIVE PRESS STUDS AT THE END OF THE

		SLEEVE SO THAT THE SIZE CAN BE ADJUSTED; IDENTIFICATION: INDELIBLE MNFRS TRADEMARK REF NO. AND CLEANING INSTRUCTIONS INSIDE COLLAR ON JACKETS AND SABS MARK OF APPROVAL ON ALL RELAVANT ITEMS; REFER TO UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0222561	RAINWEAR:2 PIECE SUIT;S;BLUE NAVY	RAINWEAR: TYPE: 2 PIECE SUIT; SIZE: S; MATERIAL: POLYESTER 100 PCT PLAIN WEAVE, 180 GM/2 MIN; COLOR: BLUE NAVY; MATERIAL: MINIMUM 180 GRAMS PER M/3 FACE SIDE 100% POLYESTER; PLAIN WEAVE WITH 170 THREADS PER M/3 INCH WITH WATER RESISTANT COATING; UNDER SIDE LAMINATED WITH PVC COATING; SEAMS STRENGTH 50KPA; CONVERTS TO 50KNM/2; LINING 80% POLYESTER 20% COTTON; SIZE TO SANS 434 SIZE CHART ANNEX E FOR RAIN WEAR; JACKET SHALL HAVE A NYLON SPIRAL ZIP WITH CLOSED FLY FRONT SECURED BY NON-CONDUCTIVE PRESS-STUDS; COMPLY WITH SANS 1822 TYPE 5; HOOD ATTACHED TO THE JACKET; JACKET TO COVER THE BUTTOCKS; FALSE ELASTIC SLEEVE AT THE END MADE OF SOFTER MATERIAL; PANTS SHALL HAVE SIDE SLITS AND ELASTIC WAIST; REFLECTIVE STRIPS TO BE FITTED ON BOTH SLEEVES ON THE UPPER ARM, AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SIDE OF THE SLEEVE AND THE ESKOM LOGO SHALL BE SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON THE FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0225676	RAINWEAR:2 PIECE SUIT;M;BLUE NAVY	RAINWEAR: TYPE: 2 PIECE SUIT; SIZE: M; MATERIAL: POLYESTER 100 PCT PLAIN WEAVE, 180 GM/2 MIN; COLOR: BLUE NAVY; MATERIAL: MINIMUM 180 GRAMS PER M/3 FACE SIDE 100% POLYESTER; PLAIN WEAVE WITH 170 THREADS PER M/3 INCH WITH WATER RESISTANT COATING; UNDER SIDE LAMINATED WITH PVC COATING; SEAMS STRENGTH 50KPA; CONVERTS TO 50KNM/2; LINING 80% POLYESTER 20% COTTON; SIZE TO SANS 434 SIZE CHART ANNEX E FOR RAIN WEAR; JACKET SHALL HAVE A NYLON SPIRAL ZIP WITH CLOSED FLY FRONT SECURED BY NON-CONDUCTIVE PRESS-STUDS; COMPLY WITH SANS 1822 TYPE 5; HOOD ATTACHED TO THE JACKET; JACKET TO COVER THE BUTTOCKS; FALSE ELASTIC SLEEVE AT THE END MADE OF SOFTER MATERIAL; PANTS SHALL HAVE SIDE SLITS AND ELASTIC WAIST; REFLECTIVE STRIPS TO BE FITTED ON BOTH SLEEVES ON THE UPPER ARM, AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SIDE OF THE SLEEVE AND THE ESKOM LOGO SHALL BE SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON THE FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0222566	RAINWEAR:2 PIECE SUIT;L;BLUE NAVY	RAINWEAR: TYPE: 2 PIECE SUIT; SIZE: L; MATERIAL: POLYESTER 100 PCT PLAIN WEAVE, 180 GM/2 MIN; COLOR: BLUE NAVY; MATERIAL: MINIMUM 180 GRAMS PER M/3 FACE SIDE 100% POLYESTER; PLAIN WEAVE WITH 170 THREADS PER M/3 INCH WITH WATER RESISTANT COATING; UNDER SIDE LAMINATED WITH PVC COATING; SEAMS STRENGTH 50KPA; CONVERTS TO 50KNM/2; LINING 80% POLYESTER 20% COTTON; SIZE TO SANS 434 SIZE CHART ANNEX E FOR RAIN WEAR; JACKET SHALL HAVE A NYLON SPIRAL ZIP WITH CLOSED FLY FRONT SECURED BY NON-CONDUCTIVE PRESS-STUDS; COMPLY WITH SANS 1822 TYPE 5; HOOD ATTACHED TO THE JACKET; JACKET TO COVER THE BUTTOCKS; FALSE ELASTIC SLEEVE AT THE END MADE OF SOFTER MATERIAL; PANTS SHALL HAVE SIDE SLITS AND ELASTIC WAIST; REFLECTIVE STRIPS TO BE FITTED ON BOTH SLEEVES ON THE UPPER ARM, AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SIDE OF THE SLEEVE AND THE ESKOM LOGO SHALL BE SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON THE FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0222567	RAINWEAR:2 PIECE SUIT;XL;BLUE NAVY	RAINWEAR: TYPE: 2 PIECE SUIT; SIZE: XL; MATERIAL: POLYESTER 100 PCT PLAIN WEAVE, 180 GM/2 MIN; COLOR: BLUE NAVY; MATERIAL: MINIMUM 180 GRAMS PER M/3 FACE SIDE 100% POLYESTER; PLAIN WEAVE WITH 170 THREADS PER M/3 INCH WITH WATER RESISTANT COATING; UNDER SIDE LAMINATED WITH PVC COATING; SEAMS STRENGTH 50KPA; CONVERTS TO 50KNM/2; LINING 80% POLYESTER 20% COTTON; SIZE TO SANS 434 SIZE CHART ANNEX E FOR RAIN WEAR; JACKET SHALL HAVE A NYLON SPIRAL ZIP WITH CLOSED FLY FRONT SECURED BY NON-CONDUCTIVE PRESS-STUDS; COMPLY WITH SANS 1822 TYPE 5; HOOD ATTACHED TO THE JACKET; JACKET TO COVER THE BUTTOCKS; FALSE ELASTIC SLEEVE AT THE END MADE OF SOFTER MATERIAL; PANTS SHALL HAVE SIDE SLITS AND ELASTIC WAIST; REFLECTIVE STRIPS TO BE FITTED ON BOTH SLEEVES ON THE UPPER ARM, AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SIDE OF THE SLEEVE AND THE ESKOM LOGO SHALL BE SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON THE FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0222568	RAINWEAR:2 PIECE SUIT;2XL;BLUE NAVY	RAINWEAR: TYPE: 2 PIECE SUIT; SIZE: 2XL; MATERIAL: POLYESTER 100 PCT PLAIN WEAVE, 180 GM/2 MIN; COLOR: BLUE NAVY; MATERIAL: MINIMUM 180 GRAMS PER M/3 FACE SIDE 100% POLYESTER; PLAIN WEAVE WITH 170 THREADS PER M/3 INCH WITH WATER RESISTANT COATING; UNDER SIDE LAMINATED WITH PVC COATING; SEAMS STRENGTH 50KPA; CONVERTS TO 50KNM/2; LINING 80% POLYESTER 20% COTTON; SIZE TO SANS 434 SIZE CHART ANNEX E FOR RAIN WEAR; JACKET SHALL HAVE A NYLON SPIRAL ZIP WITH CLOSED FLY FRONT SECURED BY NON-CONDUCTIVE PRESS-STUDS; COMPLY WITH SANS 1822 TYPE 5; HOOD ATTACHED TO



		THE JACKET; JACKET TO COVER THE BUTTOCKS; FALSE ELASTIC SLEEVE AT THE END MADE OF SOFTER MATERIAL; PANTS SHALL HAVE SIDE SLITS AND ELASTIC WAIST; REFLECTIVE STRIPS TO BE FITTED ON BOTH SLEEVES ON THE UPPER ARM, AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SIDE OF THE SLEEVE AND THE ESKOM LOGO SHALL BE SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON THE FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0222569	RAINWEAR:2 PIECE SUIT;3XL;BLUE NAVY	RAINWEAR: TYPE: 2 PIECE SUIT; SIZE: 3XL; MATERIAL: POLYESTER 100 PCT PLAIN WEAVE, 180 GM/2 MIN; COLOR: BLUE NAVY; MATERIAL: MINIMUM 180 GRAMS PER M/3 FACE SIDE 100% POLYESTER; PLAIN WEAVE WITH 170 THREADS PER M/3 INCH WITH WATER RESISTANT COATING; UNDER SIDE LAMINATED WITH PVC COATING; SEAMS STRENGTH 50KPA; CONVERTS TO 50KNM/2; LINING 80% POLYESTER 20% COTTON; SIZE TO SANS 434 SIZE CHART ANNEX E FOR RAIN WEAR; JACKET SHALL HAVE A NYLON SPIRAL ZIP WITH CLOSED FLY FRONT SECURED BY NON-CONDUCTIVE PRESS-STUDS; COMPLY WITH SANS 1822 TYPE 5; HOOD ATTACHED TO THE JACKET; JACKET TO COVER THE BUTTOCKS; FALSE ELASTIC SLEEVE AT THE END MADE OF SOFTER MATERIAL; PANTS SHALL HAVE SIDE SLITS AND ELASTIC WAIST; REFLECTIVE STRIPS TO BE FITTED ON BOTH SLEEVES ON THE UPPER ARM, AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SIDE OF THE SLEEVE AND THE ESKOM LOGO SHALL BE SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON THE FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0565711	RAINWEAR:2 PIECE SUIT;4XL;BLUE NAVY	RAINWEAR: TYPE: 2 PIECE SUIT; SIZE: 4XL; MATERIAL: POLYESTER 100 PCT PLAIN WEAVE, 180 GM/2 MIN; COLOR: BLUE NAVY; MATERIAL: MINIMUM 180 GRAMS PER M/3 FACE SIDE 100% POLYESTER; PLAIN WEAVE WITH 170 THREADS PER M/3 INCH WITH WATER RESISTANT COATING; UNDER SIDE LAMINATED WITH PVC COATING; SEAMS STRENGTH 50KPA; CONVERTS TO 50KNM/2; LINING 80% POLYESTER 20% COTTON; SIZE TO SANS 434 SIZE CHART ANNEX E FOR RAIN WEAR; JACKET SHALL HAVE A NYLON SPIRAL ZIP WITH CLOSED FLY FRONT SECURED BY NON-CONDUCTIVE PRESS-STUDS; COMPLY WITH SANS 1822 TYPE 5; HOOD ATTACHED TO THE JACKET; JACKET TO COVER THE BUTTOCKS; FALSE ELASTIC SLEEVE AT THE END MADE OF SOFTER MATERIAL; PANTS SHALL HAVE SIDE SLITS AND ELASTIC WAIST; REFLECTIVE STRIPS TO BE FITTED ON BOTH SLEEVES ON THE UPPER ARM, AND BOTH LEGS ABOVE THE KNEES; ZERO HARM IDENTIFICATION ON THE RIGHT SIDE OF THE SLEEVE AND THE ESKOM LOGO SHALL BE SILK-SCREENED IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY ON THE FRONT AND BACK; INDELIBLE MNFRS TRADEMARK; SIZE; CLEANING INSTRUCTIONS ON JACKET AND TROUSER WITH SABS MARK OF APPROVAL; UNIQUE IDENTIFIER 240-44175132; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0237954	VEST HIGH VIS:EMPLOYEE AT WORK;S;NYLON	VEST, HIGH VISIBILITY: TYPE: EMPLOYEE AT WORK; SIZE: S; MATERIAL: NYLON; COLOR: ORANGE LIGHT B26 NCS-1673-Y48R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A4 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A4; POCKET TYPE: LEFT TOP; EMPLOYEE AT WORK TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A4; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A4 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0565547	VEST HIGH VIS:EMPLOYEE AT WORK;M;NYLON	VEST, HIGH VISIBILITY: TYPE: EMPLOYEE AT WORK; SIZE: M; MATERIAL: NYLON; COLOR: ORANGE LIGHT B26 NCS-1673-Y48R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A4 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A4; POCKET TYPE: LEFT TOP; EMPLOYEE AT WORK TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A4; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A4 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0565548	VEST HIGH VIS:EMPLOYEE AT WORK;L;NYLON	VEST, HIGH VISIBILITY: TYPE: EMPLOYEE AT WORK; SIZE: L; MATERIAL: NYLON; COLOR: ORANGE LIGHT B26 NCS-1673-Y48R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A

		NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A4 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A4; POCKET TYPE: LEFT TOP; EMPLOYEE AT WORK TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A4; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A4 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0565549	VEST HIGH VIS:EMPLOYEE AT WORK;XL;NYLON	VEST, HIGH VISIBILITY: TYPE: EMPLOYEE AT WORK; SIZE: XL; MATERIAL: NYLON; COLOR: ORANGE LIGHT B26 NCS-1673-Y48R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A4 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A4; POCKET TYPE: LEFT TOP; EMPLOYEE AT WORK TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A4; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A4 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0565550	VEST HIGH VIS:EMPLOYEE AT WORK;2XL;NYLON	VEST, HIGH VISIBILITY: TYPE: EMPLOYEE AT WORK; SIZE: 2XL; MATERIAL: NYLON; COLOR: ORANGE LIGHT B26 NCS-1673-Y48R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A4 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A4; POCKET TYPE: LEFT TOP; EMPLOYEE AT WORK TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A4; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A4 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0565551	VEST HIGH VIS:EMPLOYEE AT WORK;3XL;NYLON	VEST, HIGH VISIBILITY: TYPE: EMPLOYEE AT WORK; SIZE: 3XL; MATERIAL: NYLON; COLOR: ORANGE LIGHT B26 NCS-1673-Y48R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A4 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A4; POCKET TYPE: LEFT TOP; EMPLOYEE AT WORK TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A4; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A4 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).
0565552	VEST HIGH VIS:EMPLOYEE AT WORK;4XL;NYLON	VEST, HIGH VISIBILITY: TYPE: EMPLOYEE AT WORK; SIZE: 4XL; MATERIAL: NYLON; COLOR: ORANGE LIGHT B26 NCS-1673-Y48R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A4 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A4; POCKET TYPE: LEFT TOP; EMPLOYEE AT WORK TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A4; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A4 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING

		REVISION NUMBER (IF APPLICABLE).
0565553	VEST HIGH VIS:EMPLOYEE AT WORK;5XL;NYLON	VEST, HIGH VISIBILITY: TYPE: EMPLOYEE AT WORK; SIZE: 5XL; MATERIAL: NYLON; COLOR: ORANGE LIGHT B26 NCS-1673-Y48R; GARMENT CLOSING METHOD: ZIP FASTENER WHICH SHALL COMPLY WITH SANS 1822 AND BE OF A NON CONDUCTIVE MATERIAL; USAGE DESIGN: FIG A4 ANEX A SANS 50471; REFLECTOR MARKING: REFER FIG A4; POCKET TYPE: LEFT TOP; EMPLOYEE AT WORK TO BE SILK SCREENED AT BACK; LABEL HOLDER WITH CLEAR PLASTIC WINDOW TO BE STITCHED ON LEFT TOP; ESKOM LOGO ABOVE LEFT HAND POCKET; ABOVE SHALL COMPLY TO SANS 50471 FOR HIGH VISIBILITY WARNING CLOTHING FOR PROFESSIONAL USE; VESTS/BIBS DESIGN SHALL COMPLY AS PER SANS 50471 ANNEXURE A FIGURE A4; RELECTIVE TAPE (RETRO REFLECTIVE MATERIAL) SHALL COMPLY WITH SANS 50471 AND SHALL BE A MINIMUM OF 50MM IN WIDTH AND COLOUR REQUIREMENTS FOR BACKGROUND AND COMBINED PERFORMANCE MATERIAL AS PER TABLE 2 AS PER SANS 50471; TEST/CERT, IDENTIFICATION AND SPECIFICATION REQUIREMENTS: MATERIAL SPEC: SANS 50471 AND FIGURE A4 ANNEXURE A; COLOUR SPEC: SANS 50471 TABLE 2 (FOR COLOUR REQUIREMENTS); UNIQUE IDENTIFIER 240-44175132; IDENTIFICATION: INDELIBLE MNFRS. TRADEMARK AND SIZE ON ALL ITEMS; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).

0017014	GUMBOOTS SFTY:STL;7;KNEE HEIGHT;BLACK	GUMBOOTS, SAFETY: TOE CAP: STL; SIZE: 7; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; SIZE 255; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT; NON SLIP SOLE; WATERPROOF CONSTRUCTION; BEARING SABS MARK OF APPROVAL
0017015	GUMBOOTS SFTY:STL;8;KNEE HEIGHT;BLACK	GUMBOOTS, SAFETY: TOE CAP: STL; SIZE: 8; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; SIZE 262; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT; NON SLIP SOLE; WATERPROOF CONSTRUCTION; TO SABS 20345
0017016	GUMBOOTS SFTY:STL;9;KNEE HEIGHT;BLACK	GUMBOOTS, SAFETY: TOE CAP: STL; SIZE: 9; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; SIZE 270; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT; NON SLIP SOLE; WATERPROOF CONSTRUCTION; TO SABS 20345
0017017	GUMBOOTS SFTY:STL;10;KNEE HEIGHT;BLACK	GUMBOOTS, SAFETY: TOE CAP: STL; SIZE: 10; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; SIZE 280; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT; NON SLIP SOLE; WATERPROOF CONSTRUCTION; TO SABS 20345
0017018	GUMBOOTS SFTY:STL;11;KNEE HEIGHT;BLACK	GUMBOOTS, SAFETY: TOE CAP: STL; SIZE: 11; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; SIZE: 290; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT; NON SLIP SOLE; WATERPROOF CONSTRUCTION; TO SABS 20345
0040995	LENS SFTY EQP:WELDING GOGGLES;CLEAR	LENS, SAFETY EQUIPMENT: TYPE: WELDING GOGGLES; SHADE: CLEAR; MATERIAL: GLASS; DIMENSIONS: DIA 50 X THK 1.5 MM; REFERENCE NO: 16218; NCE
0041001	HELMET WELDG:PP	HELMET, WELDING: MATERIAL: PP; WITH ADJUSTABLE NYLON HEAD GEAR, SEAMLESS, RIVETLESS LIFT FRONT LENS HOLDER, FILTER SHADE LENS, CLEAR PLASTIC COVER LENS, ARCRYLIC CHIPPING LENS, ITEM TO BE MARKED WITH SABS MARK OF APPROVAL, SABS 1400-1993
0041004	SPECTACLE SFTY:INDOOR/OUTDOOR;VARIABLE	SPECTACLE, SAFETY: TYPE: INDOOR/OUTDOOR; LENS COLOR: VARIABLE; LENS SIZE: STD; TEMPLE SIZE: ADJUSTABLE; SIDE SHIELDS: VENTILATED; REFERENCE NO: DV-326B-C-AF; WRAP AROUND BALLISTIC PROTECTION HARS INDUSTRIAL ENVIROMENTS; FRAME COLOUR BLACK VENTED; LENS TINT INDOOR/OUTDOOR; LENS COATING HARDCOAT; TEMPLE STYLE DROP WITH ADJUSTABLE LENGTHS; SOFT SELF-FITTING RUBBER NOSE BRIDGE; TEMPLE TO ADJUST TO 4 DIFFERENT LENGTHS; SUPERCOAT PROTECTION WITH ANTI-FOG; ANTI SCRATCH; ANTI-STATIC AND UV PROTECTION 100% ULTRAVIOLET PROTECTION; COMPLY TO ANSI Z87.1; MEET TRAFIC SIGNAL COLOR RECOGNITION REQUIREMENTS OF ANSI Z80.3-1996; EN-166; BALLISTIC RATED TO MIL PRF-31013 REQUIREMENT OF 360 FEET PER SECOND; UNIQUE IDENTIFIER 240-44175132

0041080	GOGGLES INDSTRL:CHEMICAL/DUST;CLEAR;PC	GOGGLES, INDUSTRIAL: TYPE: CHEMICAL/DUST; LENS COLOR: CLEAR; LENS TYPE: PC; SUPPL P/N: 9301603; ULTRA-VISION UVEX; 2CD ANTI-FOG AND APPROVED TO BS2092; 1CDM WITH OPTIDUR 4 C, AREAS OF USE; WORKING WITH ACIDS AND ALKALIS VERY DUSTY CONDITIONS
0041081	SPECTACLE SFTY:GAS WELDING;GREEN;104 MM	SPECTACLE, SAFETY: TYPE: GAS WELDING; LENS COLOR: GREEN; TEMPLE SIZE: 104 MM; REFERENCE NO: 9161.016; SHADE 4 100 PCT UV 92 PCT IR, PART OF LENS SIDE SHIELDS, WRAP-AROUND
0041093	SHIELD SFTY EQP:FACE;WD 250 X LG 450 MM	SHIELD, SAFETY EQUIPMENT: TYPE: FACE; DIMENSIONS: WD 250 X LG 450 MM; COLOR: CLEAR; MATERIAL: PLASTIC; REFERENCE NO: 10274; 10278; FOR USE WITH VISOR 25CM POLYCARB; N.B: CAP ATTACHMENT ONLY
0041094	SHIELD SFTY EQP:FACE;WD 250 X LG 450 MM	SHIELD, SAFETY EQUIPMENT: TYPE: FACE; DIMENSIONS: WD 250 X LG 450 MM; COLOR: CLEAR; MATERIAL: PC; REFERENCE NO: 10274; FOR USE WITH ATTACHMENT CAP REF: 10278
0041102	GOGGLES:WELDERS;GREEN SHADE 6;PC	GOGGLES: TYPE: WELDERS; LENS COLOR: GREEN SHADE 6; MATERIAL: PC; GAS CUTTING GOGGLE, COVER ALL TYPE, VENTILATED, LIFT FRONT LENS, CLEAR PLASTIC 1000 HOUR COVER LENS
0041109	SHIELD SFTY EQP:FACE;GREEN DARK;PC	SHIELD, SAFETY EQUIPMENT: TYPE: FACE; DIMENSIONS: WD 200 X LG 310 X THK 1 MM; COLOR: GREEN DARK; MATERIAL: PC; NOTE: ONLY GARDWELL BRAND ACCEPTABLE, WITH BROWGUARD, VISOR ALUMINIUM EDGED, HEAT RESISTANCE, SWIVELLING ON ADJUSTABLE HEAD BAND, SABS 1404, AND BEARING THE SABS MARK OF APPROVAL
0041117	MASK RSPTR:DUST;UNIVERSAL;PAPER	MASK, RESPIRATOR: USAGE DESIGN: DUST; SIZE: UNIVERSAL; MATERIAL: PAPER; MODEL NO: 8710; TYPE FF2, WITH DOUBLE BAND, SABS MARK
0041128	LENS SFTY EQP:WELDING GOGGLES;NO 6;GLASS	LENS, SAFETY EQUIPMENT: TYPE: WELDING GOGGLES; SHADE: NO 6; MATERIAL: GLASS; DIMENSIONS: DIA 50 X THK 3 MM; REFERENCE NO: M50
0041168	PROTECTOR HEARNG:EARMUFF;CUSHIONS	PROTECTOR, HEARING: TYPE: EARMUFF; EARCUP FORM: CUSHIONS; SPECIFICATION: 240-44575132; EARMUFF HIGH PERFORMANCE SMART FOLD OUT DESIGN DI-ELECTRIC CONSTRUCTION; MULTI POSITION USE WITHOUT SUPPORT; SELF-ALIGNING SUSPENSION; SOFT PLIABLE SUPER SEAL EAR CUSHIONS FOR LONG LASTING AND RESISTANT AGAINST BODY OIL AND SWEAT COLOUR BLACK/RED COMPLY TO CE SNR30 NRR28
0160593	WADER:FISHERMANS;7;PVC;GREEN OLIVE	WADER: TYPE: FISHERMANS; SIZE: 7; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132
0160594	WADER:FISHERMANS;8;PVC;GREEN OLIVE	WADER: TYPE: FISHERMANS; SIZE: 8; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132
0160595	WADER:FISHERMANS;9;PVC;GREEN OLIVE	WADER: TYPE: FISHERMANS; SIZE: 9; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132
0160596	WADER:FISHERMANS;10;PVC;GREEN OLIVE	WADER: TYPE: FISHERMANS; SIZE: 10; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132
0160597	WADER:FISHERMANS;11;PVC;GREEN OLIVE	WADER: TYPE: FISHERMANS; SIZE: 11; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132
0160683	PROTECTOR:ANKLE SPATS;LG 320 X HT 250 MM	PROTECTOR: TYPE: ANKLE SPATS; DIMENSIONS: LG 320 X HT 250 MM; MATERIAL: LEATHER CR; REFERENCE NO: G46; FLARED OVER TOP AND SIDE OF SHOE, WITH CLIP ON SPRING FRAME, ITEM TO BEAR SABS MARK OF APPROVAL
0160854	GLOVE WLDR:10;LG 300 MM;PIG SKIN;BEIGE	GLOVE, WELDER: GARMENT SIZE: 10; LENGTH: 300 MM; MATERIAL: PIG SKIN; COLOR: BEIGE; CUFF TYPE: PLAIN; GARMENT CLOSING METHOD: ELASTICATED; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; TYPE: TIG; MECHANICAL ABRASION EN LEVEL 1; CUT EN LEVEL 1; TEAR EN LEVEL 2; PUNCTURE EN LEVEL 1; HEAT SUITABLE FOR MINIMAL APPLICATION; COLD SUITABLE FOR MINIMAL APPLICATION; TO BE USED AS A GENERAL HANDLING GLOVE FOR RIGGING AND TIG WELDING; NOT TO BE USED WITH CHEMICALS

0160938	GLOVE CHEM PROTCTV:ACID RESISTANT;L;PVC	GLOVE, CHEMICAL PROTECTIVE: TYPE: ACID RESISTANT; SIZE: L; LENGTH: 35 CM; MATERIAL: PVC; COLOR: BLACK; CUFF TYPE: ROLLED; SUPPL P/N: 604K; 8 INCH CUFF, HEAVY WEIGHT, ITEM TO BE MARKED WITH SABS MARK OF APPROVAL
0160939	GLOVE CHEM PROTCTV:ACID RESISTANT;L;PVC	GLOVE, CHEMICAL PROTECTIVE: TYPE: ACID RESISTANT; SIZE: L; LENGTH: 27.9 CM; MATERIAL: PVC; COLOR: RED; CUFF TYPE: PLAIN; NEOPRENE, WRIST TYPE, CUFF LENGTH: 4CM
0161000	GUMBOOTS SFTY:STL;12;KNEE HEIGHT;BLACK	GUMBOOTS, SAFETY: TOE CAP: STL; SIZE: 12; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; SIZE 292; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT; NON SLIP SOLE; WATERPROOF CONSTRUCTION; TO SABS 20345
0161108	GUMBOOTS SFTY:STL;6;KNEE HEIGHT;BLACK	GUMBOOTS, SAFETY: TOE CAP: STL; SIZE: 6; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; SIZE 247; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT; NON SLIP SOLE; WATERPROOF CONSTRUCTION; TO SABS 20345
0161114	GUMBOOTS SFTY:STL;13;KNEE HEIGHT;BLACK	GUMBOOTS, SAFETY: TOE CAP: STL; SIZE: 13; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; SIZE 300; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT; NON SLIP SOLE; WATERPROOF CONSTRUCTION; TO SABS 20345
0172739	MASK RSPTR:HALF DISPOSABLE;DUST/MIST	MASK, RESPIRATOR: DESIGN FORM: HALF DISPOSABLE; USAGE DESIGN: DUST/MIST; REFERENCE NO: 8822; FFP2; DOUBLE BAND, PACKED 200 PER BOX
0180140	SPECTACLE SFTY:CLEAR;U9168T ASTROSPEC	SPECTACLE, SAFETY: LENS COLOR: CLEAR; REFERENCE NO: U9168T ASTROSPEC; AREA OF USE: LATHE, MILLING AND DRILLING MACHINES
214494	TOWEL BATH:LG 1.25 M;WD 700 MM;THK 5 MM	TOWEL, BATH: LENGTH: 1.25 M; WIDTH: 700 MM; THICKNESS: 5 MM; MATERIAL: COTTON 100 PCT; COLOR: BLUE PANTONE 287C ESKOM LOGO; COMPLETE WITH ESKOM LOGO EMBROIDED ON BOTTOM EDGE OF TOWEL; BEFORE ORDER EXECUTED A PROOF SAMPLE TO BE APPROVED BY COMMUNICATION DEPARTMENT; WITH EVERY DELIVERY QUALITY INSPECTION TO DONE BY COMMUNICATION DEPARTMENT
0226674	SHIELD SFTY EQP:FACE;CLEAR;PERSPEX	SHIELD, SAFETY EQUIPMENT: TYPE: FACE; DIMENSIONS: WD 200 X LG 415 X THK 2 MM; COLOR: CLEAR; MATERIAL: PERSPEX; MODEL NO: FS-16PC; NOT SHATTERPROOF, USE WITH GLASSES, SUPPLIED WITH VB10 BLOCK
0241157	HELMET SFTY:530-630 MM;WHITE	HELMET, SAFETY: SIZE: 530-630 MM; COLOR: WHITE; SIZE ADJUSTABLE, INCLUDING ATTACHMENT BRACKET D12702, USED FOR WORK AT HEIGHTS, ADJUSTABLE THREE POINT CHIN STRAP, SHORT SUN PEAK, LIMITED SIDE RIM, WEBBING SUSPENSION HARNESS, THICK SWEAT BAND OF 4.5CM, STANDARD ADJUSTABLE HEAD BAND, ATTACHMENT BRACKET FOR LAMP, MARKED AS PER SANS 1397 WITH ESKOM GENERATION LOGO, ROYAL BLUE LOGO AS PER CORPORATE IDENTITY, MATERIAL AS PER SANS 1397 SPECIFICATION
0242722	GLOVE:PRECISION;S;LG 230 MM;55 MM;BLACK	GLOVE: TYPE: PRECISION; SIZE: S; LENGTH: 230 MM; CUFF LENGTH: 55 MM; MATERIAL: NITRILE/PU FOAM; COLOR: BLACK; CUFF: KNITTED WRIST, WITH NITRILE DOTS; REFERENCE NO: 34-876
242723	GLOVE:PRECISION;M;LG 230 MM;55 MM;BLACK	GLOVE: TYPE: PRECISION; SIZE: M; LENGTH: 230 MM; CUFF LENGTH: 55 MM; MATERIAL: NITRILE/PU FOAM; COLOR: BLACK; CUFF: KNITTED WRIST, WITH NITRILE DOTS; REFERENCE NO: 34-876
0242724	GLOVE:PRECISION;L;LG 230 MM;230 MM;BLACK	GLOVE: TYPE: PRECISION; SIZE: L; LENGTH: 230 MM; CUFF LENGTH: 230 MM; MATERIAL: NITRILE/PU FOAM; COLOR: BLACK; CUFF: KNITTED WRIST, WITH NITRILE DOTS; REFERENCE NO: 34-876
0242725	GLOVE:PRECISION;XL;LG 230 MM;55 MM;BLACK	GLOVE: TYPE: PRECISION; SIZE: XL; LENGTH: 230 MM; CUFF LENGTH: 55 MM; MATERIAL: NITRILE/PU FOAM; COLOR: BLACK; CUFF: KNITTED WRIST, WITH NITRILE DOTS; REFERENCE NO: 34-876
0249397	SPECTACLE SFTY:INDOOR/OUTDOOR;SILVER;STD	SPECTACLE, SAFETY: TYPE: INDOOR/OUTDOOR; LENS COLOR: SILVER; LENS SIZE: STD; REFERENCE NO: 1015689; FLEXIBLE TEMPLES TO FIT EARS, SOFT BRIDGE TO PREVENT SLIPPAGE AND TO FIT NOSE, FRAME COLOR: METALLIC BLACK, FRAME MATERIAL: PLASTIC, WEIGHT: 27.5 GRAMS, SINGLE LENS, LENS COATING: ABRASION RESISTANT (ANTI-SCRATCH), LENS MARKING: 5-17B-D1F

0503021	RESPIRATOR:FULL FACE;ADJUSTABLE	RESPIRATOR: TYPE: FULL FACE; USE: ACID GAS/ORGANIC VAPOUR; SIZE: ADJUSTABLE; PREMIUM WELDING RESPIRATOR WITH OZONE PROTECTION;3M 9925; FFP2 EN 149:2001
0552719	HELMET SFTY:HEIGHT THREE POINT;WHITE	HELMET, SAFETY: TYPE: HEIGHT THREE POINT; SIZE: 530-630 MM; MATERIAL: PLASTIC MOLDED; COLOR: WHITE; SPECIFICATION: SANS 1397:2003; SPECIAL FEATURES: SHORT PEAK; ALL HARD HATS MUST BE IN ACCORDANCE WITH SANS 1397:2003 AND ESKOM SPECIFICATION; SUPPLIED WITH A BLACK ADJUSTABLE THREE POINT CHIN STRAP; MINIMUM HARD HAT ELECTRICAL INSULATION: 440 VAC; WITH A SHORTER PEAK AND A LIMITED SIDE BRIM; ITEM TO BE MARKED WITH SABS MARK OF APPROVAL; APPROVED ESKOM LOGO AND A ZERO HARM SLOGAN MUST BE POSITIONED ACCORDING TO THE ESKOM SPECIFICATION AND BE IN LINE WITH THE CORPORATE IDENTITY PROCEDURE; WHITE REFLECTIVE AND BLUE LETTERS EUROP ASSIST EMERGENCY NO 086 123 7566 MUST BE DISPLAYED ON THE BACK OF THE HELMETS
0552722	STRAP:THREE-POINT CHIN BLACK	STRAP: TYPE: THREE-POINT CHIN BLACK; MATERIAL: POLYVINYL WEBBING; SPECIFICATION: SANS 1397:2003; USED WITH ESKOM APPROVED SAFETY HELMET; WITH LOCK IN CLIP TYPE CONNECTORS AND A WEAK LINK TO ALLOW TEARING WHEN REQUIRED; COLOUR: BLACK; ALL CHIN STRAPS MUST BE IN ACCORDANCE WITH SANS 1397:2003 AND ESKOM SPECIFICATION; TEST CERTIFICATE TO BE SUPPLIED WITH EACH DELIVERY
0552723	STRAP:SINGLE POINT CHIN BLACK	STRAP: TYPE: SINGLE POINT CHIN BLACK; MATERIAL: POLYVINYL WEBBING; SPECIFICATION: SANS 1397:2003; USED WITH ESKOM APPROVED SAFETY HELMET; WITH LOCK IN CLIP TYPE CONNECTORS AND A WEAK LINK TO ALLOW TEARING WHEN REQUIRED; COLOUR: BLACK; ALL CHIN STRAPS MUST BE IN ACCORDANCE WITH SANS 1397:2003 AND ESKOM SPECIFICATION; TEST CERTIFICATE TO BE SUPPLIED WITH EACH DELIVERY
0565295	GLOVE WLDR:L;LG 8 IN;LEATHER;GREEN;GP	GLOVE, WELDER: GARMENT SIZE: L; LENGTH: 8 IN; MATERIAL: LEATHER; COLOR: GREEN; CUFF TYPE: STITCHED; SPECIFICATION: EN3 88; UNIQUE IDENTIFIER 240-44175132; TYPE: GENERAL PURPOSE; FULLY LINED; SABS APPROVED; PHYSICAL PROPERTIES: ALL COW LEATHER GLOVE WITH FULL COTTON LINING THAT CAN WITHSTAND HEAT BETWEEN 140-175 DEGREES CELSIUS; STANDARDS EN 388; MECHANICAL ABRASION EN LEVEL 3 CUT; EN LEVEL 1 TEAR EN LEVEL 4; PUNCTURE EN LEVEL 3; HEAT BURNING BEHAVIOUR EN LEVEL 4; CONTACT HEAT EN LEVEL 2; CONVECTIVE HEAT EN LEVEL 4; MOLTEN METAL DROPS EN LEVEL 4; COLD SUITABLE FOR GENERAL APPLICATION; USES TO BE USED AS GENERAL WELDING GLOVES CHEMICALS NOT SUITED FOR CHEMICALS
0566206	GUMBOOTS SFTY:STL;3;KNEE HEIGHT;BLACK	GUMBOOTS, SAFETY: TOE CAP: STL; SIZE: 3; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT; NON SLIP SOLE; WATERPROOF CONSTRUCTION; TO SABS 20345
0566207	GUMBOOTS SFTY:STL;4;KNEE HEIGHT;BLACK	GUMBOOTS, SAFETY: TOE CAP: STL; SIZE: 4; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT; NON SLIP SOLE; WATERPROOF CONSTRUCTION; TO SABS 20345
0566208	GUMBOOTS SFTY:STL;5;KNEE HEIGHT;BLACK	GUMBOOTS, SAFETY: TOE CAP: STL; SIZE: 5; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT; NON SLIP SOLE; WATERPROOF CONSTRUCTION; TO SABS 20345
0566383	WADER:FISHERMANS;6;PVC;GREEN OLIVE	WADER: TYPE: FISHERMANS; SIZE: 6; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132
0566391	WADER:FISHERMANS;12;PVC;GREEN OLIVE	WADER: TYPE: FISHERMANS; SIZE: 12; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132
0566392	WADER:FISHERMANS;13;PVC;GREEN OLIVE	WADER: TYPE: FISHERMANS; SIZE: 13; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132

0566629	JACKET OVRL:CLEAN CONDITION;77 CM;WHITE	JACKET, OVERALL: TYPE: CLEAN CONDITION; SIZE: 77 CM; MATERIAL: COTTON 100% D59 PRE-SHRUNK; COLOR: WHITE; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE A CLOSED ONE PANEL ONLY MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE JACKET SHALL HAVE NO POCKETS; NO BUTTONS METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE LEFT-HAND TOP CHEST IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE RIGHT SIDE SLEEVE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TOPS TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH SLEEVES CIRCUMFERENCE ON THE INNER UPPER ARM; SANS 1822 ZIP; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; UNIQUE IDENTIFIER 240-44175132; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS
0566630	JACKET OVRL:CLEAN CONDITION;82 CM;WHITE	JACKET, OVERALL: TYPE: CLEAN CONDITION; SIZE: 82 CM; MATERIAL: COTTON 100% D59 PRE-SHRUNK; COLOR: WHITE; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE A CLOSED ONE PANEL ONLY MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE JACKET SHALL HAVE NO POCKETS; NO BUTTONS METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE LEFT-HAND TOP CHEST IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE RIGHT SIDE SLEEVE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TOPS TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH SLEEVES CIRCUMFERENCE ON THE INNER UPPER ARM; SANS 1822 ZIP; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; UNIQUE IDENTIFIER 240-44175132; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS
0566631	JACKET OVRL:CLEAN CONDITION;87 CM;WHITE	JACKET, OVERALL: TYPE: CLEAN CONDITION; SIZE: 87 CM; MATERIAL: COTTON 100% D59 PRE-SHRUNK; COLOR: WHITE; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE A CLOSED ONE PANEL ONLY MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE JACKET SHALL HAVE NO POCKETS; NO BUTTONS METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE LEFT-HAND TOP CHEST IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE RIGHT SIDE SLEEVE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TOPS TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH SLEEVES CIRCUMFERENCE ON THE INNER UPPER ARM; SANS 1822 ZIP; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; UNIQUE IDENTIFIER 240-44175132; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS
0566632	JACKET OVRL:CLEAN CONDITION;92 CM;WHITE	JACKET, OVERALL: TYPE: CLEAN CONDITION; SIZE: 92 CM; MATERIAL: COTTON 100% D59 PRE-SHRUNK; COLOR: WHITE; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE A CLOSED ONE PANEL ONLY MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE JACKET SHALL HAVE NO POCKETS; NO BUTTONS METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE LEFT-HAND TOP CHEST IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE RIGHT SIDE SLEEVE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TOPS TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH SLEEVES CIRCUMFERENCE ON THE INNER UPPER ARM; SANS 1822 ZIP; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; UNIQUE IDENTIFIER 240-44175132; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS

0566633	JACKET OVRL:CLEAN CONDITION;97 CM;WHITE	JACKET, OVERALL: TYPE: CLEAN CONDITION; SIZE: 97 CM; MATERIAL: COTTON 100% D59 PRE-SHRUNK; COLOR: WHITE; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE A CLOSED ONE PANEL ONLY MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE JACKET SHALL HAVE NO POCKETS; NO BUTTONS METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE LEFT-HAND TOP CHEST IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE RIGHT SIDE SLEEVE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TOPS TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH SLEEVES CIRCUMFERENCE ON THE INNER UPPER ARM; SANS 1822 ZIP; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; UNIQUE IDENTIFIER 240-44175132; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS
0566634	JACKET OVRL:CLEAN CONDITION;102 CM;WHITE	JACKET, OVERALL: TYPE: CLEAN CONDITION; SIZE: 102 CM; MATERIAL: COTTON 100% D59 PRE-SHRUNK; COLOR: WHITE; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE A CLOSED ONE PANEL ONLY MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE JACKET SHALL HAVE NO POCKETS; NO BUTTONS METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE LEFT-HAND TOP CHEST IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE RIGHT SIDE SLEEVE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TOPS TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH SLEEVES CIRCUMFERENCE ON THE INNER UPPER ARM; SANS 1822 ZIP; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; UNIQUE IDENTIFIER 240-44175132; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS
0566635	JACKET OVRL:CLEAN CONDITION;107 CM;WHITE	JACKET, OVERALL: TYPE: CLEAN CONDITION; SIZE: 107 CM; MATERIAL: COTTON 100% D59 PRE-SHRUNK; COLOR: WHITE; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE A CLOSED ONE PANEL ONLY MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE JACKET SHALL HAVE NO POCKETS; NO BUTTONS METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE LEFT-HAND TOP CHEST IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE RIGHT SIDE SLEEVE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TOPS TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH SLEEVES CIRCUMFERENCE ON THE INNER UPPER ARM; SANS 1822 ZIP; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; UNIQUE IDENTIFIER 240-44175132; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS
0566636	JACKET OVRL:CLEAN CONDITION;112 CM;WHITE	JACKET, OVERALL: TYPE: CLEAN CONDITION; SIZE: 112 CM; MATERIAL: COTTON 100% D59 PRE-SHRUNK; COLOR: WHITE; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE A CLOSED ONE PANEL ONLY MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE JACKET SHALL HAVE NO POCKETS; NO BUTTONS METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE LEFT-HAND TOP CHEST IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE RIGHT SIDE SLEEVE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TOPS TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH SLEEVES CIRCUMFERENCE ON THE INNER UPPER ARM; SANS 1822 ZIP; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; UNIQUE IDENTIFIER 240-44175132; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS



0566637	JACKET OVRL:CLEAN CONDITION;117 CM;WHITE	JACKET, OVERALL: TYPE: CLEAN CONDITION; SIZE: 117 CM; MATERIAL: COTTON 100% D59 PRE-SHRUNK; COLOR: WHITE; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE A CLOSED ONE PANEL ONLY MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE JACKET SHALL HAVE NO POCKETS; NO BUTTONS METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE LEFT-HAND TOP CHEST IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE RIGHT SIDE SLEEVE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TOPS TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH SLEEVES CIRCUMFERENCE ON THE INNER UPPER ARM; SANS 1822 ZIP; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; UNIQUE IDENTIFIER 240-44175132; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS
0566638	JACKET OVRL:CLEAN CONDITION;122 CM;WHITE	JACKET, OVERALL: TYPE: CLEAN CONDITION; SIZE: 122 CM; MATERIAL: COTTON 100% D59 PRE-SHRUNK; COLOR: WHITE; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE A CLOSED ONE PANEL ONLY MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE JACKET SHALL HAVE NO POCKETS; NO BUTTONS METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE LEFT-HAND TOP CHEST IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE RIGHT SIDE SLEEVE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TOPS TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH SLEEVES CIRCUMFERENCE ON THE INNER UPPER ARM; SANS 1822 ZIP; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; UNIQUE IDENTIFIER 240-44175132; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS
0566639	JACKET OVRL:CLEAN CONDITION;127 CM;WHITE	JACKET, OVERALL: TYPE: CLEAN CONDITION; SIZE: 127 CM; MATERIAL: COTTON 100% D59 PRE-SHRUNK; COLOR: WHITE; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE A CLOSED ONE PANEL ONLY MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE JACKET SHALL HAVE NO POCKETS; NO BUTTONS METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE LEFT-HAND TOP CHEST IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE RIGHT SIDE SLEEVE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TOPS TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH SLEEVES CIRCUMFERENCE ON THE INNER UPPER ARM; SANS 1822 ZIP; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; UNIQUE IDENTIFIER 240-44175132; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS
0566640	JACKET OVRL:CLEAN CONDITION;132 CM;WHITE	JACKET, OVERALL: TYPE: CLEAN CONDITION; SIZE: 132 CM; MATERIAL: COTTON 100% D59 PRE-SHRUNK; COLOR: WHITE; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE A CLOSED ONE PANEL ONLY MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE JACKET SHALL HAVE NO POCKETS; NO BUTTONS METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE LEFT-HAND TOP CHEST IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE RIGHT SIDE SLEEVE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TOPS TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH SLEEVES CIRCUMFERENCE ON THE INNER UPPER ARM; SANS 1822 ZIP; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; UNIQUE IDENTIFIER 240-44175132; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS

0566641	JACKET OVRL:CLEAN CONDITION;137 CM;WHITE	JACKET, OVERALL: TYPE: CLEAN CONDITION; SIZE: 137 CM; MATERIAL: COTTON 100% D59 PRE-SHRUNK; COLOR: WHITE; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE A CLOSED ONE PANEL ONLY MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE JACKET SHALL HAVE NO POCKETS; NO BUTTONS METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE LEFT-HAND TOP CHEST IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE RIGHT SIDE SLEEVE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TOPS TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH SLEEVES CIRCUMFERENCE ON THE INNER UPPER ARM; SANS 1822 ZIP; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; UNIQUE IDENTIFIER 240-44175132; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS
0566642	JACKET OVRL:CLEAN CONDITION;142 CM;WHITE	JACKET, OVERALL: TYPE: CLEAN CONDITION; SIZE: 142 CM; MATERIAL: COTTON 100% D59 PRE-SHRUNK; COLOR: WHITE; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE A CLOSED ONE PANEL ONLY MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE JACKET SHALL HAVE NO POCKETS; NO BUTTONS METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE LEFT-HAND TOP CHEST IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE RIGHT SIDE SLEEVE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TOPS TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH SLEEVES CIRCUMFERENCE ON THE INNER UPPER ARM; SANS 1822 ZIP; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; UNIQUE IDENTIFIER 240-44175132; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS
0566643	JACKET OVRL:CLEAN CONDITION;147 CM;WHITE	JACKET, OVERALL: TYPE: CLEAN CONDITION; SIZE: 147 CM; MATERIAL: COTTON 100% D59 PRE-SHRUNK; COLOR: WHITE; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE A CLOSED ONE PANEL ONLY MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE JACKET SHALL HAVE NO POCKETS; NO BUTTONS METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE LEFT-HAND TOP CHEST IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE RIGHT SIDE SLEEVE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TOPS TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH SLEEVES CIRCUMFERENCE ON THE INNER UPPER ARM; SANS 1822 ZIP; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; UNIQUE IDENTIFIER 240-44175132; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS
0566644	JACKET OVRL:CLEAN CONDITION;152 CM;WHITE	JACKET, OVERALL: TYPE: CLEAN CONDITION; SIZE: 152 CM; MATERIAL: COTTON 100% D59 PRE-SHRUNK; COLOR: WHITE; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE A CLOSED ONE PANEL ONLY MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE JACKET SHALL HAVE NO POCKETS; NO BUTTONS METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE LEFT-HAND TOP CHEST IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE RIGHT SIDE SLEEVE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TOPS TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH SLEEVES CIRCUMFERENCE ON THE INNER UPPER ARM; SANS 1822 ZIP; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; UNIQUE IDENTIFIER 240-44175132; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS

0566645	JACKET OVRL:CLEAN CONDITION;157 CM;WHITE	JACKET, OVERALL: TYPE: CLEAN CONDITION; SIZE: 157 CM; MATERIAL: COTTON 100% D59 PRE-SHRUNK; COLOR: WHITE; THE JACKET SHALL HAVE A COLLAR; THE FRONT SHALL BE A CLOSED ONE PANEL ONLY MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE JACKET SHALL HAVE NO POCKETS; NO BUTTONS METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE LEFT-HAND TOP CHEST IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE RIGHT SIDE SLEEVE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TOPS TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH SLEEVES CIRCUMFERENCE ON THE INNER UPPER ARM; SANS 1822 ZIP; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; UNIQUE IDENTIFIER 240-44175132; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS
0566676	TROUSERS:CLEAN CONDITION;77 CM;WHITE	TROUSERS: TYPE: CLEAN CONDITION; SIZE: 77 CM; COLOR: WHITE; MATERIAL: COTTON 100% D59 PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE SPECIFICATION REQUIREMENTS FOR SIZES UNDER SECTION 2.6 (OVERALL-BOILER SUITS OR 2 PIECE WORK WEAR SUITS) SHALL APPLY; MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE TROUSER SHALL HAVE NO POCKETS; NO BUTTONS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH DRAW CORD 10MM COTTON BELT STRING FOR FASTENING AND WITHOUT ZIP ON THE FRONT NO METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE RIGHT BACK IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE LEFT BACK SIDE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH LEGS CIRCUMFERENCE ON THE INNER UPPER LEG; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS ALL RELAVANT ITEMS TO COMPLY AS PER UNIQUE IDENTIFIER 240-44175132
0566677	TROUSERS:CLEAN CONDITION;82 CM;WHITE	TROUSERS: TYPE: CLEAN CONDITION; SIZE: 82 CM; COLOR: WHITE; MATERIAL: COTTON 100% D59 PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE SPECIFICATION REQUIREMENTS FOR SIZES UNDER SECTION 2.6 (OVERALL-BOILER SUITS OR 2 PIECE WORK WEAR SUITS) SHALL APPLY; MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE TROUSER SHALL HAVE NO POCKETS; NO BUTTONS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH DRAW CORD 10MM COTTON BELT STRING FOR FASTENING AND WITHOUT ZIP ON THE FRONT NO METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE RIGHT BACK IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE LEFT BACK SIDE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH LEGS CIRCUMFERENCE ON THE INNER UPPER LEG; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS ALL RELAVANT ITEMS TO COMPLY AS PER UNIQUE IDENTIFIER 240-44175132

0566678	TROUSERS:CLEAN CONDITION;87 CM;WHITE	<p>TROUSERS: TYPE: CLEAN CONDITION; SIZE: 87 CM; COLOR: WHITE; MATERIAL: COTTON 100% D59 PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE SPECIFICATION REQUIREMENTS FOR SIZES UNDER SECTION 2.6 (OVERALL-BOILER SUITS OR 2 PIECE WORK WEAR SUITS) SHALL APPLY; MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE TROUSER SHALL HAVE NO POCKETS; NO BUTTONS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH DRAW CORD 10MM COTTON BELT STRING FOR FASTENING AND WITHOUT ZIP ON THE FRONT NO METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE RIGHT BACK IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE LEFT BACK SIDE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH LEGS CIRCUMFERENCE ON THE INNER UPPER LEG; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS ALL RELAVANT ITEMS TO COMPLY AS PER UNIQUE IDENTIFIER 240-44175132</p>
0566680	TROUSERS:CLEAN CONDITION;92 CM;WHITE	<p>TROUSERS: TYPE: CLEAN CONDITION; SIZE: 92 CM; COLOR: WHITE; MATERIAL: COTTON 100% D59 PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE SPECIFICATION REQUIREMENTS FOR SIZES UNDER SECTION 2.6 (OVERALL-BOILER SUITS OR 2 PIECE WORK WEAR SUITS) SHALL APPLY; MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE TROUSER SHALL HAVE NO POCKETS; NO BUTTONS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH DRAW CORD 10MM COTTON BELT STRING FOR FASTENING AND WITHOUT ZIP ON THE FRONT NO METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE RIGHT BACK IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE LEFT BACK SIDE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH LEGS CIRCUMFERENCE ON THE INNER UPPER LEG; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS ALL RELAVANT ITEMS TO COMPLY AS PER UNIQUE IDENTIFIER 240-44175132</p>
0566681	TROUSERS:CLEAN CONDITION;97 CM;WHITE	<p>TROUSERS: CLEAN CONDITION; SIZE: 97 CM; COLOR: WHITE; MATERIAL: COTTON 100% D59 PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE SPECIFICATION REQUIREMENTS FOR SIZES UNDER SECTION 2.6 (OVERALL-BOILER SUITS OR 2 PIECE WORK WEAR SUITS) SHALL APPLY; MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE TROUSER SHALL HAVE NO POCKETS; NO BUTTONS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH DRAW CORD 10MM COTTON BELT STRING FOR FASTENING AND WITHOUT ZIP ON THE FRONT NO METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE RIGHT BACK IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE LEFT BACK SIDE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH LEGS CIRCUMFERENCE ON THE INNER UPPER LEG; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS ALL RELAVANT ITEMS TO COMPLY AS PER UNIQUE IDENTIFIER 240-44175132</p>

0566682	TROUSERS:CLEAN CONDITION;102 CM;WHITE	TROUSERS: TYPE: CLEAN CONDITION; SIZE: 102 CM; COLOR: WHITE; MATERIAL: COTTON 100% D59 PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE SPECIFICATION REQUIREMENTS FOR SIZES UNDER SECTION 2.6 (OVERALL-BOILER SUITS OR 2 PIECE WORK WEAR SUITS) SHALL APPLY; MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE TROUSER SHALL HAVE NO POCKETS; NO BUTTONS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH DRAW CORD 10MM COTTON BELT STRING FOR FASTENING AND WITHOUT ZIP ON THE FRONT NO METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE RIGHT BACK IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE LEFT BACK SIDE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH LEGS CIRCUMFERENCE ON THE INNER UPPER LEG; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS ALL RELAVANT ITEMS TO COMPLY AS PER UNIQUE IDENTIFIER 240-44175132
0566683	TROUSERS:CLEAN CONDITION;107 CM;WHITE	TROUSERS: TYPE: CLEAN CONDITION; SIZE: 107 CM; COLOR: WHITE; MATERIAL: COTTON 100% D59 PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE SPECIFICATION REQUIREMENTS FOR SIZES UNDER SECTION 2.6 (OVERALL-BOILER SUITS OR 2 PIECE WORK WEAR SUITS) SHALL APPLY; MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE TROUSER SHALL HAVE NO POCKETS; NO BUTTONS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH DRAW CORD 10MM COTTON BELT STRING FOR FASTENING AND WITHOUT ZIP ON THE FRONT NO METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE RIGHT BACK IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE LEFT BACK SIDE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH LEGS CIRCUMFERENCE ON THE INNER UPPER LEG; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS ALL RELAVANT ITEMS TO COMPLY AS PER UNIQUE IDENTIFIER 240-44175132
0566684	TROUSERS:CLEAN CONDITION;112 CM;WHITE	TROUSERS: TYPE: CLEAN CONDITION; SIZE: 112 CM; COLOR: WHITE; MATERIAL: COTTON 100% D59 PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE SPECIFICATION REQUIREMENTS FOR SIZES UNDER SECTION 2.6 (OVERALL-BOILER SUITS OR 2 PIECE WORK WEAR SUITS) SHALL APPLY; MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE TROUSER SHALL HAVE NO POCKETS; NO BUTTONS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH DRAW CORD 10MM COTTON BELT STRING FOR FASTENING AND WITHOUT ZIP ON THE FRONT NO METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE RIGHT BACK IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE LEFT BACK SIDE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH LEGS CIRCUMFERENCE ON THE INNER UPPER LEG; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS ALL RELAVANT ITEMS TO COMPLY AS PER UNIQUE IDENTIFIER 240-44175132

0566685	TROUSERS:CLEAN CONDITION;117 CM;WHITE	TROUSERS: TYPE: CLEAN CONDITION; SIZE: 117 CM; COLOR: WHITE; MATERIAL: COTTON 100% D59 PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE SPECIFICATION REQUIREMENTS FOR SIZES UNDER SECTION 2.6 (OVERALL-BOILER SUITS OR 2 PIECE WORK WEAR SUITS) SHALL APPLY; MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE TROUSER SHALL HAVE NO POCKETS; NO BUTTONS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH DRAW CORD 10MM COTTON BELT STRING FOR FASTENING AND WITHOUT ZIP ON THE FRONT NO METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE RIGHT BACK IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE LEFT BACK SIDE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH LEGS CIRCUMFERENCE ON THE INNER UPPER LEG; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS ALL RELAVANT ITEMS TO COMPLY AS PER UNIQUE IDENTIFIER 240-44175132
0566686	TROUSERS:CLEAN CONDITION;122 CM;WHITE	TROUSERS: TYPE: CLEAN CONDITION; SIZE: 122 CM; COLOR: WHITE; MATERIAL: COTTON 100% D59 PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE SPECIFICATION REQUIREMENTS FOR SIZES UNDER SECTION 2.6 (OVERALL-BOILER SUITS OR 2 PIECE WORK WEAR SUITS) SHALL APPLY; MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE TROUSER SHALL HAVE NO POCKETS; NO BUTTONS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH DRAW CORD 10MM COTTON BELT STRING FOR FASTENING AND WITHOUT ZIP ON THE FRONT NO METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE RIGHT BACK IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE LEFT BACK SIDE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH LEGS CIRCUMFERENCE ON THE INNER UPPER LEG; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS ALL RELAVANT ITEMS TO COMPLY AS PER UNIQUE IDENTIFIER 240-44175132
0566687	TROUSERS:CLEAN CONDITION;127 CM;WHITE	TROUSERS: TYPE: CLEAN CONDITION; SIZE: 127 CM; COLOR: WHITE; MATERIAL: COTTON 100% D59 PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE SPECIFICATION REQUIREMENTS FOR SIZES UNDER SECTION 2.6 (OVERALL-BOILER SUITS OR 2 PIECE WORK WEAR SUITS) SHALL APPLY; MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE TROUSER SHALL HAVE NO POCKETS; NO BUTTONS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH DRAW CORD 10MM COTTON BELT STRING FOR FASTENING AND WITHOUT ZIP ON THE FRONT NO METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE RIGHT BACK IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE LEFT BACK SIDE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH LEGS CIRCUMFERENCE ON THE INNER UPPER LEG; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS ALL RELAVANT ITEMS TO COMPLY AS PER UNIQUE IDENTIFIER 240-44175132

0566688	TROUSERS:CLEAN CONDITION;132 CM;WHITE	TROUSERS: TYPE: CLEAN CONDITION; SIZE: 132 CM; COLOR: WHITE; MATERIAL: COTTON 100% D59 PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE SPECIFICATION REQUIREMENTS FOR SIZES UNDER SECTION 2.6 (OVERALL-BOILER SUITS OR 2 PIECE WORK WEAR SUITS) SHALL APPLY; MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE TROUSER SHALL HAVE NO POCKETS; NO BUTTONS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH DRAW CORD 10MM COTTON BELT STRING FOR FASTENING AND WITHOUT ZIP ON THE FRONT NO METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE RIGHT BACK IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE LEFT BACK SIDE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH LEGS CIRCUMFERENCE ON THE INNER UPPER LEG; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS ALL RELAVANT ITEMS TO COMPLY AS PER UNIQUE IDENTIFIER 240-44175132
0566689	TROUSERS:CLEAN CONDITION;137 CM;WHITE	TROUSERS: TYPE: CLEAN CONDITION; SIZE: 137 CM; COLOR: WHITE; MATERIAL: COTTON 100% D59 PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE SPECIFICATION REQUIREMENTS FOR SIZES UNDER SECTION 2.6 (OVERALL-BOILER SUITS OR 2 PIECE WORK WEAR SUITS) SHALL APPLY; MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE TROUSER SHALL HAVE NO POCKETS; NO BUTTONS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH DRAW CORD 10MM COTTON BELT STRING FOR FASTENING AND WITHOUT ZIP ON THE FRONT NO METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE RIGHT BACK IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE LEFT BACK SIDE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH LEGS CIRCUMFERENCE ON THE INNER UPPER LEG; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS ALL RELAVANT ITEMS TO COMPLY AS PER UNIQUE IDENTIFIER 240-44175132
0566690	TROUSERS:CLEAN CONDITION;142 CM;WHITE	TROUSERS: TYPE: CLEAN CONDITION; SIZE: 142 CM; COLOR: WHITE; MATERIAL: COTTON 100% D59 PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE SPECIFICATION REQUIREMENTS FOR SIZES UNDER SECTION 2.6 (OVERALL-BOILER SUITS OR 2 PIECE WORK WEAR SUITS) SHALL APPLY; MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE TROUSER SHALL HAVE NO POCKETS; NO BUTTONS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH DRAW CORD 10MM COTTON BELT STRING FOR FASTENING AND WITHOUT ZIP ON THE FRONT NO METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE RIGHT BACK IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE LEFT BACK SIDE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH LEGS CIRCUMFERENCE ON THE INNER UPPER LEG; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS ALL RELAVANT ITEMS TO COMPLY AS PER UNIQUE IDENTIFIER 240-44175132

0566691	TROUSERS:CLEAN CONDITION;147 CM;WHITE	TROUSERS: TYPE: CLEAN CONDITION; SIZE: 147 CM; COLOR: WHITE; MATERIAL: COTTON 100% D59 PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE SPECIFICATION REQUIREMENTS FOR SIZES UNDER SECTION 2.6 (OVERALL-BOILER SUITS OR 2 PIECE WORK WEAR SUITS) SHALL APPLY; MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE TROUSER SHALL HAVE NO POCKETS; NO BUTTONS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH DRAW CORD 10MM COTTON BELT STRING FOR FASTENING AND WITHOUT ZIP ON THE FRONT NO METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE RIGHT BACK IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE LEFT BACK SIDE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH LEGS CIRCUMFERENCE ON THE INNER UPPER LEG; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS ALL RELAVANT ITEMS TO COMPLY AS PER UNIQUE IDENTIFIER 240-44175132
0566692	TROUSERS:CLEAN CONDITION;152 CM;WHITE	TROUSERS: TYPE: CLEAN CONDITION; SIZE: 152 CM; COLOR: WHITE; MATERIAL: COTTON 100% D59 PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE SPECIFICATION REQUIREMENTS FOR SIZES UNDER SECTION 2.6 (OVERALL-BOILER SUITS OR 2 PIECE WORK WEAR SUITS) SHALL APPLY; MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE TROUSER SHALL HAVE NO POCKETS; NO BUTTONS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH DRAW CORD 10MM COTTON BELT STRING FOR FASTENING AND WITHOUT ZIP ON THE FRONT NO METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE RIGHT BACK IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE LEFT BACK SIDE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH LEGS CIRCUMFERENCE ON THE INNER UPPER LEG; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS ALL RELAVANT ITEMS TO COMPLY AS PER UNIQUE IDENTIFIER 240-44175132
0566693	TROUSERS:CLEAN CONDITION;157 CM;WHITE	TROUSERS: TYPE: CLEAN CONDITION; SIZE: 157 CM; COLOR: WHITE; MATERIAL: COTTON 100% D59 PRE SHRUNK; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; THE SPECIFICATION REQUIREMENTS FOR SIZES UNDER SECTION 2.6 (OVERALL-BOILER SUITS OR 2 PIECE WORK WEAR SUITS) SHALL APPLY; MATERIAL TYPE D59 PRE-SHRUNK 100% SOFT WOVEN COTTON FABRIC IN ACCORDANCE WITH SANS 1387-4; FLAME RETARDANT; THE TROUSER SHALL HAVE NO POCKETS; NO BUTTONS; THE PANTS SHALL HAVE A WAISTBAND WHICH SHALL BE ELASTICATED RUCHED AT THE BACK WITH DRAW CORD 10MM COTTON BELT STRING FOR FASTENING AND WITHOUT ZIP ON THE FRONT NO METAL ATTACHMENTS; THE ESKOM LOGO SHALL APPEAR ON THE RIGHT BACK IN NAVY BLUE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; THE ZERO HARM IDENTIFICATION SHALL APPEAR ON THE LEFT BACK SIDE AND SHALL BE IN ACCORDANCE WITH ESKOM'S CORPORATE IDENTITY; ALL PERSONAL PROTECTIVE CLOTHING TO BE FITTED WITH REFLECTIVE STRIPS ON BOTH LEGS CIRCUMFERENCE ON THE INNER UPPER LEG; SANS 10101 FOR STITCHING AND SANS 1362 FOR THREADS; TO BE INDIVIDUALLY PACKED IN SEALED PLASTIC BAGS ALL RELAVANT ITEMS TO COMPLY AS PER UNIQUE IDENTIFIER 240-44175132
0566738	MASK RSPTR:HALF DISPOSABLE;ADJUSTABLE	MASK, RESPIRATOR: DESIGN FORM: HALF DISPOSABLE; USAGE DESIGN: DUST/MIST/BIO AGENTS; SIZE: ADJUSTABLE; COLOR: WHITE; MANUF P/N: 5261FFP2 NR D; REFERENCE NO: 1005600; DISPOSABLE PARTICULATE MASK WITH VALVE FOR PROTECTION AGAINST SOLID AND NON-VOLATILE LIQUID PARTICLES ONLY; EN 149:2001+A1 2009 FFP2 NR D CE 0086; PROTECTION FACTOR 10 X WEL MATERIAL THAT HAS LOW BREATHING RESISTANCE WITH EFFECTIVE PROTECTION AGAINST: SUB-MICRON PARTICLES; FINE DUSTS; NON-VOLATILE LIQUID MISTS AND BIOLOGICAL AGENTS; UNIQUE IDENTIFIER 240-44175132



0566568	BOOTS SFTY:3;STRD; STL OR CARBON FIBER	BOOTS, SAFETY: SIZE: 3; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT
0222581	BOOTS SFTY:4;STRD; STL OR CARBON FIBER	BOOTS, SAFETY: SIZE: 4; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT
0222582	BOOTS SFTY:5;STRD; STL OR CARBON FIBER	BOOTS, SAFETY: SIZE: 5; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT
0222583	BOOTS SFTY:6;STRD; STL OR CARBON FIBER	BOOTS, SAFETY: SIZE: 6; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT
0222584	BOOTS SFTY:7;STRD; STL OR CARBON FIBER	BOOTS, SAFETY: SIZE: 7; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT

0222585	BOOTS SFTY:8;STRD; STL OR CARBON FIBER	BOOTS, SAFETY: SIZE: 8; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT
0222586	BOOTS SFTY:9;STRD; STL OR CARBON FIBER	BOOTS, SAFETY: SIZE: 9; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT
0222587	BOOTS SFTY:10;STRD; STL OR CARBON FIBER	BOOTS, SAFETY: SIZE: 10; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT
0566564	BOOTS SFTY:11;STRD; STL OR CARBON FIBER	BOOTS, SAFETY: SIZE: 11; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT
0566565	BOOTS SFTY:12;STRD; STL OR CARBON FIBER	BOOTS, SAFETY: SIZE: 12; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT

0566569	BOOTS SFTY:13;STRD; STL OR CARBON FIBER	BOOTS, SAFETY: SIZE: 13; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT
0566572	SHOES SFTY:3;STRD; STL OR CARBON FIBER	SHOES, SAFETY: SIZE: 3; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; MATERIAL: UPPER LEATHER FULL GRAIN; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD; SHOES TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; THE SHOES TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT SHOE COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT
0235901	SHOES SFTY:4;STRD; STL OR CARBON FIBER	SHOES, SAFETY: SIZE: 4; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; MATERIAL: UPPER LEATHER FULL GRAIN; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD SHOES TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; THE SHOES TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT SHOE COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT
0566573	SHOES SFTY:13;STRD; STL OR CARBON FIBER	SHOES, SAFETY: SIZE: 13; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; MATERIAL: UPPER LEATHER FULL GRAIN; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD; SHOES TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; THE SHOES TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT SHOE COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT
0235903	SHOES SFTY:6;STRD; STL OR CARBON FIBER	SHOES, SAFETY: SIZE: 6; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; MATERIAL: UPPER LEATHER FULL GRAIN; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD SHOES TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; THE SHOES TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT SHOE COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT

0235904	SHOES SFTY:7;STRD; STL OR CARBON FIBER	SHOES, SAFETY: SIZE: 7; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; MATERIAL: UPPER LEATHER FULL GRAIN; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD SHOES TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; THE SHOES TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT SHOE COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT
0235905	SHOES SFTY:8;STRD; STL OR CARBON FIBER	SHOES, SAFETY: SIZE: 8; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; MATERIAL: UPPER LEATHER FULL GRAIN; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD SHOES TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; THE SHOES TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT SHOE COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT
0235906	SHOES SFTY:9;STRD; STL OR CARBON FIBER	SHOES, SAFETY: SIZE: 9; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; MATERIAL: UPPER LEATHER FULL GRAIN; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD SHOES TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; THE SHOES TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT SHOE COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT
0235907	SHOES SFTY:10;STRD; STL OR CARBON FIBER	SHOES, SAFETY: SIZE: 10; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; MATERIAL: UPPER LEATHER FULL GRAIN; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD SHOES TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; THE SHOES TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT SHOE COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT
0566575	SHOES SFTY:11;STRD; STL OR CARBON FIBER	SHOES, SAFETY: SIZE: 11; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; MATERIAL: UPPER LEATHER FULL GRAIN; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD; SHOES TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; THE SHOES TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT SHOE COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT

0566576	SHOES SFTY:12;STRD; STL OR CARBON FIBER	SHOES, SAFETY: SIZE: 12; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; MATERIAL: UPPER LEATHER FULL GRAIN; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD; SHOES TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; THE SHOES TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT SHOE COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT
0235902	SHOES SFTY:5;STRD; STL OR CARBON FIBER	SHOES, SAFETY: SIZE: 5; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; MATERIAL: UPPER LEATHER FULL GRAIN; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD SHOES TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; THE SHOES TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT SHOE COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT

## 2.1 Purchaser's design

Refer to the Technical Specification for PPE document

## 2.2 Procedure for submission and acceptance of Supplier's design

Refer to the Technical Specification for PPE document

## 2.3 Other requirements of the Supplier's design

Refer to the Technical Specification for PPE document

## 2.4 Use of Supplier's design

Refer to the Technical Specification for PPE document.

## 2.5 Manufacture & fabrication

Not Applicable.

## 2.6 Factory acceptance testing (FAT)

Details provided under technical evaluation criteria regarding samples that requires acceptance before bulk delivery.

## 2.7 Other tests and inspections and commissioning in place of use

Once the goods are delivered at Hendrina Power Station (Warehouse), goods receipts will be done (however the goods will still undergo a Quality Control (QC) process no later than seventy two (72) hours after delivery. If the goods pass the QC process they will be stored in the Warehouse. Should the goods fail the QC process, the Purchaser will inform the Supplier of such, the Supplier must make the necessary arrangements to come and collect the goods (at his costs) no later than 48 hours after notice is issued.

## 2.8 Operating manuals and maintenance schedules

Not Applicable.

## 3 Supply Requirements

The Supply Requirements for this contract are in an Annexure (Technical Evaluation Criteria) to the Contract Data provided by the *Purchaser*.

## 4. Specification of the *services* to be provided

Not Applicable.

## 5. Constraints on how the *Supplier* Provides the Goods

### 5.1. Programming constraints

The Contract is “As and when required”, the *Supplier* to stick to the stipulated conditions.

### 5.2. Work to be done by the Delivery Date

A Delivery Date is the date that will be indicated in the purchase order, which is constituted by the Supplier arriving at the Delivery Place with the goods to the Delivery Place, offload the goods, the goods then undergo a Quality Control process to ensure they meets the required standard and conform to requirements.

### 5.3. Marking the *goods*

The goods that will be delivered needs to be clearly marked i.e. their description, sizes, quantities and all relevant information.

### 5.4. Constraints at the delivery place and place of use

Not Applicable, but the Delivery Place is Stores at Hendrina Power Station (which is a National Key Point) and all the rules and regulations will apply.

### 5.5. Cooperating with Others

Not Applicable.

### 5.6. Services & other things to be provided by the *Purchaser* or *Supplier*

Not Applicable, however, the Purchaser will provide access to the Supplier when the Supplier intends or wants to deliver the goods to the Delivery Place.

### 5.9 Health and safety risk management

The *Supplier* shall comply with the following health and safety requirements:

The Supplier /Supplier shall at all times comply with the health and safety requirements prescribed by law applicable to these services, including Eskom health and safety procedures. Minimum:

[1] Project SHE specification provided.

[2] Basic conditions of employment act no 75 of 1997.

[3] Compensation for Occupational Diseases and Illnesses Act 130 of 1993

- [4] Occupational health and safety act no 85 of 1993 and regulations.
- [5] National road traffic Act 93 of 1996.
- [6] 32-37 Eskom substance abuse procedure.
- [7] 32-136 Eskom Supplier health and safety requirements
- [8] 240-62196227 Eskom life- saving rules
- [9] 32-95 Eskom environmental, occupational health and safety incident management procedure
- [10] 32-727 Eskom SHEQ policy
- [11] 240-62946386 Eskom vehicle and driver safety management procedure

The Supplier /Supplier shall comply with the health and safety requirements contained in Project SHE specification provided with the tender documents, Occupational health and safety act and all applicable health & safety laws and regulations and rules, guidelines and procedures.

- The Supplier /Supplier shall develop and implement a project specific health and safety plan based on the provided project applicable SHE requirements and legal requirements. The Supplier /Supplier shall submit the plan to the Client/ Safety risk department before commencement of the project for evaluation and approval.
- These documents are shall be maintained for the duration of the contract.
- The Supplier /Supplier and all his personnel shall attend a health and safety induction course prior to starting with the contract works provided by Eskom Hendrina Power Station after the evaluation approval of the project SHE file by the Eskom Hendrina Client and Safety Risk Department.
- The Supplier /Supplier shall ensure all his personnel attend their company project health and safety induction course prior to starting with the Contract works.
- The Supplier /Supplier submit all the documents as indicated in the Safety, Health & Environmental Specifications relevant to the work to Safety Risk Management before the induction course.
- The Supplier /Supplier shall maintain training and competency records with regard to the skills he or she uses to carry out the *works* or any other works in the *Employers* premises.
- The Supplier /Supplier shall maintain compensation commissioner records and proof of registration.
- Keep records and documentation with regard to any sub-Supplier or labour-only contracts he places or uses to carry out the *works* or any other works in *Employers* premises.
- The Supplier shall maintain records of all incidents or accidents, and vehicle accidents, incurred during execution of this contract *works*.
- The Supplier /Supplier shall maintain records of all man-hours, including sub-Suppliers during this record.
- The Supplier /Supplier shall maintain Environmental plan and awareness training.
- The Supplier shall ensure minimum wage compliance for the different skills and to which Bargaining Council compliance is made to and proof of membership, if any.
- The Supplier /Supplier shall implement and maintain Risk Assessment of this type of works.

#### 5.10 Environmental constraints and management

The *Supplier* shall comply with the environmental criteria and constraints [stated here or contained in Annexure \_\_\_\_\_]

#### 5.11 Quality

##### Quality assurance requirements

##### General

- a. The *Supplier* complies with the *Employer's* quality and technical requirements including those listed in the *Employer's* specification document QM58 (Quality Management Specification 240- 105658000).
- b. The *Supplier* submits a QMS as a returnable schedule and uses it for all phases of the Project. The QMS complies with the requirements of ISO 9001 standard. The *Supplier* provides evidence of a fully implemented QMS as and when requested by the *Employer*. The *Supply Manager* may at his sole discretion carry out an audit on the Supplier, the *Supplier's* suppliers and Sub-Suppliers.

**Quality Management documents requirements**

The *Supplier* submits the following document after contract award to the *Supply Manager* for review and acceptance and prior to the commencement of work

The *Supplier* will supply the *Supply Manager* with a QCP which will detail the *Supplier's* organisation, quality assurance and quality control procedures specific to this project. The QCP must be aligned to, and reference ISO 10005:2005 QMS, guidelines for quality plans and in compliance with the guideline in QM 58 (Quality Management Specification 240- 105658000). The QCP will make reference to the *Supplier's* QMS Procedures to be used in this Contract:

- a. The *Supplier's* QMS compliance with the requirements of ISO 9001
- b. *Supplier's* quality manual
- c. *Supplier's* quality procedures
- d. *Supplier's* quality forms and work instructions
- e. *Supplier's* quality system documents referenced in this Works Information

The *Supplier* supplies the *Supply Manager* with a QCP or ITP for review and acceptance.

The *Supplier* provides CVs of the quality management employees who will be responsible for quality on site.

**Quality Management employee's responsibilities include but are not limited to the following:**

- a. Administration of QA/QC functions.
- b. Verification of approval status of their or Sub-Supplier's QCP and procedures/
- c. On-and -offsite inspections.
- d. Co-ordination, inspection and verification of the Employer's intervention points.
- e. Review of Supplier testing and inspection documents (procedures, test results).

The *Supplier* submits as a minimum the following documents, as required by the *Employer*, which requirement does not constitute a compensation event, during the execution of the Works:-

- a. Updated QCP register
- b. Inspection notifications accompanied by their inspection report
- c. Non-conformance and Defects registers and reports
- d. Updated Site and off-site inspection schedules.
- e. Inspections completed/outstanding.
- f. Inspection and test reports

**Quality Responsibility**

- a. The *Supplier* is accountable for the quality of the output and liable for any failures.
- b. The *Supplier* is responsible for defining the level of intervention of QA/QC or inspections. These are in line with the *Supply Manager* requirements.



- c. The interventions points include all witness, hold, verification and review points required by the *Supply Manager*. The *Supplier's* failure to allow the intervention points will constitute a non-conformance.

### **Inspections**

- a. The *Supplier* is responsible for the inspection of all the Works that is performed and the Supply Manager only verifies that the Works is conducted as per the Contract.
- b. The *Supplier* conducts all inspections in accordance with the accepted QCP / ITP.
- c. The *Supplier* drafts a QCP or ITP which shows each activity and submits to the Supply Manager for acceptance.
- d. The *Supplier* provides suitably qualified personnel to conduct on-and-offsite inspections
- e. The *Supplier* ensures that all Works are inspected and approved before the Supply Manager is invited for verification.

### **Non-Conformances and Defects**

Where NCR's and Defect notifications are issued, the *Supplier* acknowledges receipt as per reply period and proposes corrective and preventive actions to the *Supply Manager* as per the contract response period. The corrective and preventive actions will include the implementation and completion dates. Progress on all NCR's and Defect notifications issued to the *Supplier* must be reported to the *Supply Manager* on weekly basis.

- a. The *Supplier's* keeps a register of all NCR's and Defect notifications issued
- b. Deviations from the Contract are treated as a non-conformance.
- c. Records of NCRs and Defect notifications are kept and form part of the data book records.

During the contract execution phase, the *Supplier* will be monitored by the *Supply Manager* for performance on quality related aspects. The monitoring will be in the form of audits and assessments

### **Quality Reporting**

The *Supplier* submits a monthly quality report, on the last working day of the month. The report includes but not limited to the following:

- a) A register of NCRs and defects
- b) Updated QCP / ITP register
- c) Planned and completed local and foreign inspection dates
- d) Completed and outstanding Inspections

## **5.12 Invoicing and payment**

Within one week of receiving a payment certificate from the *Supply Manager* in terms of core clause 51.1, the *Supplier* provides the *Purchaser* with a tax invoice showing the amount due for payment equal to that stated in the *Supply Manager's* certificate

The *Supplier* shall address the tax invoice to *Purchaser* and include on each invoice the following information:

- Name and address of the *Supplier* and the *Supply Manager*;
- The contract number and title;
- *Supplier's* VAT registration number;
- The *Purchaser's* VAT registration number.
- Description of *goods* and *services* provided for each item invoiced based on the Price Schedule;
- Total amount invoiced excluding VAT, the VAT and the invoiced amount including VAT;
- (add other as required)
- All invoices must be submitted to [invoiceseskomlocal@eskom.co.za](mailto:invoiceseskomlocal@eskom.co.za) after the goods have passed the Quality Control processes which include goods receipts.

#### **5.13 Insurance provided by the *Purchaser***

As per Core Clause 84.1.

#### **5.14 Contract change management**

Not Applicable.

#### **5.15 Provision of bonds and guarantees**

Not Applicable.

#### **5.16 Records of Defined Cost, payments & assessments of compensation events to be kept by the *Supplier***

Supplier to keep all related and relevant documentation to this contract for a period of 5 years.